
kwcoco

Release 0.2.21

Jon Crall

Feb 15, 2022

CONTENTS

1 CocoDataset API	5
1.1 CocoDataset classmethods (via MixinCocoExtras)	5
1.2 CocoDataset classmethods (via CocoDataset)	5
1.3 CocoDataset slots	5
1.4 CocoDataset properties	6
1.5 CocoDataset methods (via MixinCocoAddRemove)	6
1.6 CocoDataset methods (via MixinCocoObjects)	7
1.7 CocoDataset methods (via MixinCocoStats)	7
1.8 CocoDataset methods (via MixinCocoAccessors)	7
1.9 CocoDataset methods (via CocoDataset)	8
1.10 CocoDataset methods (via MixinCocoExtras)	8
1.11 CocoDataset methods (via MixinCocoDraw)	8
2 kwcoco	9
2.1 CocoDataset API	11
2.2 Subpackages	14
2.3 Submodules	198
2.4 Package Contents	312
Python Module Index	341
Index	343

If you are new, please see our getting started document: [getting_started](#)

Please also see information in the repo [README](#), which contains similar but complementary information.

For notes about warping and spaces see [warping_and_spaces](#). The Kitware COCO module defines a variant of the Microsoft COCO format, originally developed for the “collected images in context” object detection challenge. We are backwards compatible with the original module, but we also have improved implementations in several places, including segmentations, keypoints, annotation tracks, multi-spectral images, and videos (which represents a generic sequence of images).

A kwcoco file is a “manifest” that serves as a single reference that points to all images, categories, and annotations in a computer vision dataset. Thus, when applying an algorithm to a dataset, it is sufficient to have the algorithm take one dataset parameter: the path to the kwcoco file. Generally a kwcoco file will live in a “bundle” directory along with the data that it references, and paths in the kwcoco file will be relative to the location of the kwcoco file itself.

The main data structure in this model is largely based on the implementation in <https://github.com/cocodataset/cocoapi>. It uses the same efficient core indexing data structures, but in our implementation the indexing can be optionally turned off, functions are silent by default (with the exception of long running processes, which optionally show progress by default). We support helper functions that add and remove images, categories, and annotations.

The `kwcoco.CocoDataset` class is capable of dynamic addition and removal of categories, images, and annotations. Has better support for keypoints and segmentation formats than the original COCO format. Despite being written in Python, this data structure is reasonably efficient.

```
>>> import kwcoco
>>> import json
>>> # Create demo data
>>> demo = kwcoco.CocoDataset.demo()
>>> # Reroot can switch between absolute / relative-paths
>>> demo.reroot(absolute=True)
>>> # could also use demo.dump / demo.dumps, but this is more explicit
>>> text = json.dumps(demo.dataset)
>>> with open('demo.json', 'w') as file:
>>>     file.write(text)

>>> # Read from disk
>>> self = kwcoco.CocoDataset('demo.json')

>>> # Add data
>>> cid = self.add_category('Cat')
>>> gid = self.add_image('new-img.jpg')
>>> aid = self.add_annotation(image_id=gid, category_id=cid, bbox=[0, 0, 100, 100])

>>> # Remove data
>>> self.remove_annotations([aid])
>>> self.remove_images([gid])
>>> self.remove_categories([cid])

>>> # Look at data
>>> import ubelt as ub
>>> print(ub.repr2(self.basic_stats(), nl=1))
>>> print(ub.repr2(self.extended_stats(), nl=2))
>>> print(ub.repr2(self.boxsize_stats(), nl=3))
>>> print(ub.repr2(self.category_annotation_frequency()))
```

(continues on next page)

(continued from previous page)

```
>>> # Inspect data
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> import kwplot
>>> kwplot.autompl()
>>> self.show_image(gid=1)

>>> # Access single-item data via imgs, cats, anns
>>> cid = 1
>>> self.cats[cid]
{'id': 1, 'name': 'astronaut', 'supercategory': 'human'}

>>> gid = 1
>>> self.imgs[gid]
{'id': 1, 'file_name': 'astro.png', 'url': 'https://i.imgur.com/KXhKM72.png'}

>>> aid = 3
>>> self.anns[aid]
{'id': 3, 'image_id': 1, 'category_id': 3, 'line': [326, 369, 500, 500]}

>>> # Access multi-item data via the annots and images helper objects
>>> aids = self.index.gid_to_aids[2]
>>> annots = self.annots(aids)

>>> print('annots = {}'.format(ub.repr2(annots, nl=1, sv=1)))
annots = <Annos(num=2)>

>>> annots.lookup('category_id')
[6, 4]

>>> annots.lookup('bbox')
[[37, 6, 230, 240], [124, 96, 45, 18]]

>>> # built in conversions to efficient kwimage array DataStructures
>>> print(ub.repr2(annots.detections.data, sv=1))
{
    'boxes': <Boxes(xywh,
                      array([[ 37.,   6., 230., 240.],
                             [124.,  96.,  45.,  18.]], dtype=float32))>,
    'class_idxs': [5, 3],
    'keypoints': <PointsList(n=2)>,
    'segmentations': <PolygonList(n=2)>,
}

>>> gids = list(self.imgs.keys())
>>> images = self.images(gids)
>>> print('images = {}'.format(ub.repr2(images, nl=1, sv=1)))
images = <Images(num=3)>

>>> images.lookup('file_name')
['astro.png', 'carl.png', 'stars.png']

>>> print('images.annots = {}'.format(images.annots))
```

(continues on next page)

(continued from previous page)

```
images.annots = <AnnotGroups(n=3, m=3.7, s=3.9)>  
  
=> print('images.annots.cids = {!r}'.format(images.annots.cids))  
images.annots.cids = [[1, 2, 3, 4, 5, 5, 5, 5], [6, 4], []]
```


COCODATASET API

The following is a logical grouping of the public `kwcoco.CocoDataset` API attributes and methods. See the in-code documentation for further details.

1.1 CocoDataset classmethods (via MixinCocoExtras)

- `kwcoco.CocoDataset.coerce` - Attempt to transform the input into the intended CocoDataset.
- `kwcoco.CocoDataset.demo` - Create a toy coco dataset for testing and demo puposes
- `kwcoco.CocoDataset.random` - Creates a random CocoDataset according to distribution parameters

1.2 CocoDataset classmethods (via CocoDataset)

- `kwcoco.CocoDataset.from_coco_paths` - Constructor from multiple coco file paths.
- `kwcoco.CocoDataset.from_data` - Constructor from a json dictionary
- `kwcoco.CocoDataset.from_image_paths` - Constructor from a list of images paths.

1.3 CocoDataset slots

- `kwcoco.CocoDataset.index` - an efficient lookup index into the coco data structure. The index defines its own attributes like `anns`, `cats`, `imgs`, `gid_to_aids`, `file_name_to_img`, etc. See `CocoIndex` for more details on which attributes are available.
- `kwcoco.CocoDataset.hashid` - If computed, this will be a hash uniquely identifying the dataset. To ensure this is computed see `kwcoco.coco_dataset.MixinCocoExtras._build_hashid()`.
- `kwcoco.CocoDataset.hashid_parts` -
- `kwcoco.CocoDataset.tag` - A tag indicating the name of the dataset.
- `kwcoco.CocoDataset.dataset` - raw json data structure. This is the base dictionary that contains {‘annotations’: List, ‘images’: List, ‘categories’: List}
- `kwcoco.CocoDataset.bundle_dpath` - If known, this is the root path that all image file names are relative to. This can also be manually overwritten by the user.
- `kwcoco.CocoDataset.assets_dpath` -
- `kwcoco.CocoDataset.cache_dpath` -

1.4 CocoDataset properties

- `kwcoco.CocoDataset.anns` -
- `kwcoco.CocoDataset.cats` -
- `kwcoco.CocoDataset.cid_to_aids` -
- `kwcoco.CocoDataset.data_fpath` -
- `kwcoco.CocoDataset.data_root` -
- `kwcoco.CocoDataset.fpath` - if known, this stores the filepath the dataset was loaded from
- `kwcoco.CocoDataset.gid_to_aids` -
- `kwcoco.CocoDataset.img_root` -
- `kwcoco.CocoDataset imgs` -
- `kwcoco.CocoDataset.n_annot`s -
- `kwcoco.CocoDataset.n_cats` -
- `kwcoco.CocoDataset.n_images` -
- `kwcoco.CocoDataset.n_videos` -
- `kwcoco.CocoDataset.name_to_cat` -

1.5 CocoDataset methods (via MixinCocoAddRemove)

- `kwcoco.CocoDataset.add_annotation` - Add an annotation to the dataset (dynamically updates the index)
- `kwcoco.CocoDataset.add_annotations` - Faster less-safe multi-item alternative to add_annotation.
- `kwcoco.CocoDataset.add_category` - Adds a category
- `kwcoco.CocoDataset.add_image` - Add an image to the dataset (dynamically updates the index)
- `kwcoco.CocoDataset.add_images` - Faster less-safe multi-item alternative
- `kwcoco.CocoDataset.add_video` - Add a video to the dataset (dynamically updates the index)
- `kwcoco.CocoDataset.clear_annotations` - Removes all annotations (but not images and categories)
- `kwcoco.CocoDataset.clear_images` - Removes all images and annotations (but not categories)
- `kwcoco.CocoDataset.ensure_category` - Like add_category(), but returns the existing category id if it already exists instead of failing. In this case all metadata is ignored.
- `kwcoco.CocoDataset.ensure_image` - Like add_image(), but returns the existing image id if it already exists instead of failing. In this case all metadata is ignored.
- `kwcoco.CocoDataset.remove_annotation` - Remove a single annotation from the dataset
- `kwcoco.CocoDataset.remove_annotation_keypoints` - Removes all keypoints with a particular category
- `kwcoco.CocoDataset.remove_annotations` - Remove multiple annotations from the dataset.
- `kwcoco.CocoDataset.remove_categories` - Remove categories and all annotations in those categories. Currently does not change any hierarchy information
- `kwcoco.CocoDataset.remove_images` - Remove images and any annotations contained by them

- `kwcoco.CocoDataset.remove_keypoint_categories` - Removes all keypoints of a particular category as well as all annotation keypoints with those ids.
- `kwcoco.CocoDataset.remove_videos` - Remove videos and any images / annotations contained by them
- `kwcoco.CocoDataset.set_annotation_category` - Sets the category of a single annotation

1.6 CocoDataset methods (via MixinCocoObjects)

- `kwcoco.CocoDataset.annots` - Return vectorized annotation objects
- `kwcoco.CocoDataset.categories` - Return vectorized category objects
- `kwcoco.CocoDataset.images` - Return vectorized image objects
- `kwcoco.CocoDataset.videos` - Return vectorized video objects

1.7 CocoDataset methods (via MixinCocoStats)

- `kwcoco.CocoDataset.basic_stats` - Reports number of images, annotations, and categories.
- `kwcoco.CocoDataset.boxsize_stats` - Compute statistics about bounding box sizes.
- `kwcoco.CocoDataset.category_annotation_frequency` - Reports the number of annotations of each category
- `kwcoco.CocoDataset.category_annotation_type_frequency` - Reports the number of annotations of each type for each category
- `kwcoco.CocoDataset.conform` - Make the COCO file conform a stricter spec, infers attributes where possible.
- `kwcoco.CocoDataset.extended_stats` - Reports number of images, annotations, and categories.
- `kwcoco.CocoDataset.find_representative_images` - Find images that have a wide array of categories. Attempt to find the fewest images that cover all categories using images that contain both a large and small number of annotations.
- `kwcoco.CocoDataset.keypoint_annotation_frequency` -
- `kwcoco.CocoDataset.stats` - This function corresponds to `kwcoco.cli.coco_stats`.
- `kwcoco.CocoDataset.validate` - Performs checks on this coco dataset.

1.8 CocoDataset methods (via MixinCocoAccessors)

- `kwcoco.CocoDataset.category_graph` - Construct a networkx category hierarchy
- `kwcoco.CocoDataset.delayed_load` - Experimental method
- `kwcoco.CocoDataset.get_auxiliary_fpath` - Returns the full path to auxiliary data for an image
- `kwcoco.CocoDataset.get_image_fpath` - Returns the full path to the image
- `kwcoco.CocoDataset.keypoint_categories` - Construct a consistent CategoryTree representation of key-point classes
- `kwcoco.CocoDataset.load_annot_sample` - Reads the chip of an annotation. Note this is much less efficient than using a sampler, but it doesn't require disk cache.

- `kwcoco.CocoDataset.load_image` - Reads an image from disk and
- `kwcoco.CocoDataset.object_categories` - Construct a consistent CategoryTree representation of object classes

1.9 CocoDataset methods (via CocoDataset)

- `kwcoco.CocoDataset.copy` - Deep copies this object
- `kwcoco.CocoDataset.dump` - Writes the dataset out to the json format
- `kwcoco.CocoDataset.dumps` - Writes the dataset out to the json format
- `kwcoco.CocoDataset.subset` - Return a subset of the larger coco dataset by specifying which images to port. All annotations in those images will be taken.
- `kwcoco.CocoDataset.union` - Merges multiple CocoDataset items into one. Names and associations are retained, but ids may be different.
- `kwcoco.CocoDataset.view_sql` - Create a cached SQL interface to this dataset suitable for large scale multiproCESSing use cases.

1.10 CocoDataset methods (via MixinCocoExtras)

- `kwcoco.CocoDataset.corrupted_images` - Check for images that don't exist or can't be opened
- `kwcoco.CocoDataset.missing_images` - Check for images that don't exist
- `kwcoco.CocoDataset.rename_categories` - Rename categories with a potentially coarser categorization.
- `kwcoco.CocoDataset.reroot` - Rebase image/data paths onto a new image/data root.

1.11 CocoDataset methods (via MixinCocoDraw)

- `kwcoco.CocoDataset.draw_image` - Use kwimage to draw all annotations on an image and return the pixels as a numpy array.
- `kwcoco.CocoDataset.imread` - Loads a particular image
- `kwcoco.CocoDataset.show_image` - Use matplotlib to show an image with annotations overlaid

KWCOCO

The Kitware COCO module defines a variant of the Microsoft COCO format, originally developed for the “collected images in context” object detection challenge. We are backwards compatible with the original module, but we also have improved implementations in several places, including segmentations, keypoints, annotation tracks, multi-spectral images, and videos (which represents a generic sequence of images).

A kwcoco file is a “manifest” that serves as a single reference that points to all images, categories, and annotations in a computer vision dataset. Thus, when applying an algorithm to a dataset, it is sufficient to have the algorithm take one dataset parameter: the path to the kwcoco file. Generally a kwcoco file will live in a “bundle” directory along with the data that it references, and paths in the kwcoco file will be relative to the location of the kwcoco file itself.

The main data structure in this model is largely based on the implementation in <https://github.com/cocodataset/cocoapi>. It uses the same efficient core indexing data structures, but in our implementation the indexing can be optionally turned off, functions are silent by default (with the exception of long running processes, which optionally show progress by default). We support helper functions that add and remove images, categories, and annotations.

The `kwcoco.CocoDataset` class is capable of dynamic addition and removal of categories, images, and annotations. Has better support for keypoints and segmentation formats than the original COCO format. Despite being written in Python, this data structure is reasonably efficient.

```
>>> import kwcoco
>>> import json
>>> # Create demo data
>>> demo = kwcoco.CocoDataset.demo()
>>> # Reroot can switch between absolute / relative-paths
>>> demo.reroot(absolute=True)
>>> # could also use demo.dump / demo.dumps, but this is more explicit
>>> text = json.dumps(demo.dataset)
>>> with open('demo.json', 'w') as file:
>>>     file.write(text)

>>> # Read from disk
>>> self = kwcoco.CocoDataset('demo.json')

>>> # Add data
>>> cid = self.add_category('Cat')
>>> gid = self.add_image('new-img.jpg')
>>> aid = self.add_annotation(image_id=gid, category_id=cid, bbox=[0, 0, 100, 100])

>>> # Remove data
>>> self.remove_annotations([aid])
>>> self.remove_images([gid])
>>> self.remove_categories([cid])
```

(continues on next page)

(continued from previous page)

```

>>> # Look at data
>>> import ubelt as ub
>>> print(ub.repr2(self.basic_stats(), nl=1))
>>> print(ub.repr2(self.extended_stats(), nl=2))
>>> print(ub.repr2(self.boxsize_stats(), nl=3))
>>> print(ub.repr2(self.category_annotation_frequency()))

>>> # Inspect data
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> import kwplot
>>> kwplot.autompl()
>>> self.show_image(gid=1)

>>> # Access single-item data via imgs, cats, anns
>>> cid = 1
>>> self.cats[cid]
{'id': 1, 'name': 'astronaut', 'supercategory': 'human'}

>>> gid = 1
>>> self.imgs[gid]
{'id': 1, 'file_name': 'astro.png', 'url': 'https://i.imgur.com/KXhKM72.png'}

>>> aid = 3
>>> self.anns[aid]
{'id': 3, 'image_id': 1, 'category_id': 3, 'line': [326, 369, 500, 500]}

>>> # Access multi-item data via the annots and images helper objects
>>> aids = self.index.gid_to_aids[2]
>>> annots = self.annots(aids)

>>> print('annots = {}'.format(ub.repr2(annots, nl=1, sv=1)))
annots = <Annots(num=2)>

>>> annots.lookup('category_id')
[6, 4]

>>> annots.lookup('bbox')
[[37, 6, 230, 240], [124, 96, 45, 18]]

>>> # built in conversions to efficient kwimage array DataStructures
>>> print(ub.repr2(annots.detections.data, sv=1))
{
    'boxes': <Boxes(xywh,
                      array([[ 37.,   6., 230., 240.],
                             [124.,  96.,  45.,  18.]], dtype=float32))>,
    'class_idxs': [5, 3],
    'keypoints': <PointsList(n=2)>,
    'segmentations': <PolygonList(n=2)>,
}

```

(continues on next page)

(continued from previous page)

```
>>> gids = list(self.imgs.keys())
>>> images = self.images(gids)
>>> print('images = {}'.format(ub.repr2(images, nl=1, sv=1)))
images = <Images(num=3)>

>>> images.lookup('file_name')
['astro.png', 'carl.png', 'stars.png']

>>> print('images.annots = {}'.format(images.annots))
images.annots = <AnnotGroups(n=3, m=3.7, s=3.9)>

>>> print('images.annots.cids = {!r}'.format(images.annots.cids))
images.annots.cids = [[1, 2, 3, 4, 5, 5, 5, 5, 5], [6, 4], []]
```

2.1 CocoDataset API

The following is a logical grouping of the public kwcoco.CocoDataset API attributes and methods. See the in-code documentation for further details.

2.1.1 CocoDataset classmethods (via MixinCocoExtras)

- `kwcoco.CocoDataset.coerce` - Attempt to transform the input into the intended CocoDataset.
- `kwcoco.CocoDataset.demo` - Create a toy coco dataset for testing and demo purposes
- `kwcoco.CocoDataset.random` - Creates a random CocoDataset according to distribution parameters

2.1.2 CocoDataset classmethods (via CocoDataset)

- `kwcoco.CocoDataset.from_coco_paths` - Constructor from multiple coco file paths.
- `kwcoco.CocoDataset.from_data` - Constructor from a json dictionary
- `kwcoco.CocoDataset.from_image_paths` - Constructor from a list of images paths.

2.1.3 CocoDataset slots

- `kwcoco.CocoDataset.index` - an efficient lookup index into the coco data structure. The index defines its own attributes like anns, cats, imgs, gid_to_aids, file_name_to_img, etc. See CocoIndex for more details on which attributes are available.
- `kwcoco.CocoDataset.hashid` - If computed, this will be a hash uniquely identifying the dataset. To ensure this is computed see `kwcoco.coco_dataset.MixinCocoExtras._build_hashid()`.
- `kwcoco.CocoDataset.hashid_parts` -
- `kwcoco.CocoDataset.tag` - A tag indicating the name of the dataset.
- `kwcoco.CocoDataset.dataset` - raw json data structure. This is the base dictionary that contains {‘annotations’: List, ‘images’: List, ‘categories’: List}

- `kwcoco.CocoDataset.bundle_dpath` - If known, this is the root path that all image file names are relative to. This can also be manually overwritten by the user.
- `kwcoco.CocoDataset.assets_dpath` -
- `kwcoco.CocoDataset.cache_dpath` -

2.1.4 CocoDataset properties

- `kwcoco.CocoDataset.anns` -
- `kwcoco.CocoDataset.cats` -
- `kwcoco.CocoDataset.cid_to_aids` -
- `kwcoco.CocoDataset.data_fpath` -
- `kwcoco.CocoDataset.data_root` -
- `kwcoco.CocoDataset.fpath` - if known, this stores the filepath the dataset was loaded from
- `kwcoco.CocoDataset.gid_to_aids` -
- `kwcoco.CocoDataset.img_root` -
- `kwcoco.CocoDataset.imgs` -
- `kwcoco.CocoDataset.n_annot` -
- `kwcoco.CocoDataset.n_cats` -
- `kwcoco.CocoDataset.n_images` -
- `kwcoco.CocoDataset.n_videos` -
- `kwcoco.CocoDataset.name_to_cat` -

2.1.5 CocoDataset methods (via MixinCocoAddRemove)

- `kwcoco.CocoDataset.add_annotation` - Add an annotation to the dataset (dynamically updates the index)
- `kwcoco.CocoDataset.add_annotations` - Faster less-safe multi-item alternative to add_annotation.
- `kwcoco.CocoDataset.add_category` - Adds a category
- `kwcoco.CocoDataset.add_image` - Add an image to the dataset (dynamically updates the index)
- `kwcoco.CocoDataset.add_images` - Faster less-safe multi-item alternative
- `kwcoco.CocoDataset.add_video` - Add a video to the dataset (dynamically updates the index)
- `kwcoco.CocoDataset.clear_annotations` - Removes all annotations (but not images and categories)
- `kwcoco.CocoDataset.clear_images` - Removes all images and annotations (but not categories)
- `kwcoco.CocoDataset.ensure_category` - Like add_category(), but returns the existing category id if it already exists instead of failing. In this case all metadata is ignored.
- `kwcoco.CocoDataset.ensure_image` - Like add_image(), but returns the existing image id if it already exists instead of failing. In this case all metadata is ignored.
- `kwcoco.CocoDataset.remove_annotation` - Remove a single annotation from the dataset
- `kwcoco.CocoDataset.remove_annotation_keypoints` - Removes all keypoints with a particular category
- `kwcoco.CocoDataset.remove_annotations` - Remove multiple annotations from the dataset.

- `kwcoco.CocoDataset.remove_categories` - Remove categories and all annotations in those categories. Currently does not change any hierarchy information
- `kwcoco.CocoDataset.remove_images` - Remove images and any annotations contained by them
- `kwcoco.CocoDataset.remove_keypoint_categories` - Removes all keypoints of a particular category as well as all annotation keypoints with those ids.
- `kwcoco.CocoDataset.remove_videos` - Remove videos and any images / annotations contained by them
- `kwcoco.CocoDataset.set_annotation_category` - Sets the category of a single annotation

2.1.6 CocoDataset methods (via MixinCocoObjects)

- `kwcoco.CocoDataset.annots` - Return vectorized annotation objects
- `kwcoco.CocoDataset.categories` - Return vectorized category objects
- `kwcoco.CocoDataset.images` - Return vectorized image objects
- `kwcoco.CocoDataset.videos` - Return vectorized video objects

2.1.7 CocoDataset methods (via MixinCocoStats)

- `kwcoco.CocoDataset.basic_stats` - Reports number of images, annotations, and categories.
- `kwcoco.CocoDataset.boxsize_stats` - Compute statistics about bounding box sizes.
- `kwcoco.CocoDataset.category_annotation_frequency` - Reports the number of annotations of each category
- `kwcoco.CocoDataset.category_annotation_type_frequency` - Reports the number of annotations of each type for each category
- `kwcoco.CocoDataset.conform` - Make the COCO file conform a stricter spec, infers attributes where possible.
- `kwcoco.CocoDataset.extended_stats` - Reports number of images, annotations, and categories.
- `kwcoco.CocoDataset.find_representative_images` - Find images that have a wide array of categories. Attempt to find the fewest images that cover all categories using images that contain both a large and small number of annotations.
- `kwcoco.CocoDataset.keypoint_annotation_frequency` -
- `kwcoco.CocoDataset.stats` - This function corresponds to `kwcoco.cli.coco_stats`.
- `kwcoco.CocoDataset.validate` - Performs checks on this coco dataset.

2.1.8 CocoDataset methods (via MixinCocoAccessors)

- `kwcoco.CocoDataset.category_graph` - Construct a networkx category hierarchy
- `kwcoco.CocoDataset.delayed_load` - Experimental method
- `kwcoco.CocoDataset.get_auxiliary_fpath` - Returns the full path to auxiliary data for an image
- `kwcoco.CocoDataset.get_image_fpath` - Returns the full path to the image
- `kwcoco.CocoDataset.keypoint_categories` - Construct a consistent CategoryTree representation of key-point classes

- `kwcoco.CocoDataset.load_annot_sample` - Reads the chip of an annotation. Note this is much less efficient than using a sampler, but it doesn't require disk cache.
- `kwcoco.CocoDataset.load_image` - Reads an image from disk and
- `kwcoco.CocoDataset.object_categories` - Construct a consistent CategoryTree representation of object classes

2.1.9 CocoDataset methods (via CocoDataset)

- `kwcoco.CocoDataset.copy` - Deep copies this object
- `kwcoco.CocoDataset.dump` - Writes the dataset out to the json format
- `kwcoco.CocoDataset.dumps` - Writes the dataset out to the json format
- `kwcoco.CocoDataset.subset` - Return a subset of the larger coco dataset by specifying which images to port. All annotations in those images will be taken.
- `kwcoco.CocoDataset.union` - Merges multiple `CocoDataset` items into one. Names and associations are retained, but ids may be different.
- `kwcoco.CocoDataset.view_sql` - Create a cached SQL interface to this dataset suitable for large scale multiprocesing use cases.

2.1.10 CocoDataset methods (via MixinCocoExtras)

- `kwcoco.CocoDataset.corrupted_images` - Check for images that don't exist or can't be opened
- `kwcoco.CocoDataset.missing_images` - Check for images that don't exist
- `kwcoco.CocoDataset.rename_categories` - Rename categories with a potentially coarser categorization.
- `kwcoco.CocoDataset.reroot` - Rebase image/data paths onto a new image/data root.

2.1.11 CocoDataset methods (via MixinCocoDraw)

- `kwcoco.CocoDataset.draw_image` - Use kwimage to draw all annotations on an image and return the pixels as a numpy array.
- `kwcoco.CocoDataset.imread` - Loads a particular image
- `kwcoco.CocoDataset.show_image` - Use matplotlib to show an image with annotations overlaid

2.2 Subpackages

2.2.1 kwcoco.cli

Submodules

`kwcoco.cli.__main__`

Module Contents

Functions

<code>main(cmdline=True, **kw)</code>	kw = dict(command='stats')
---	----------------------------

```
kwcoco.cli.__main__.main(cmdline=True, **kw)
    kw = dict(command='stats') cmdline = False
```

`kwcoco.cli.coco_conform`

Module Contents

Classes

<code>CocoConformCLI</code>	
---	--

Attributes

<code>_CLI</code>	
-----------------------------------	--

```
class kwcoco.cli.coco_conform.CocoConformCLI
    class CLIConfig(data=None, default=None, cmdline=False)
        Bases: scriptconfig.Config

        Make the COCO file conform to the spec.

        Populates inferable information such as image size, annotation area, etc.

        epilog = Multiline-String
            1     Example Usage:
            2         kwcoco conform --help
            3         kwcoco conform --src=special:shapes8 --dst conformed.json

        default

        name = conform

    classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> # xdoctest: +SKIP
>>> kw = {'src': 'special:shapes8'}
>>> cmdline = False
>>> cls = CocoConformCLI
>>> cls.main(cmdline, **kw)
```

`kwcoco.cli.coco_conform._CLI`

`kwcoco.cli.coco_eval`

Wraps the logic in `kwcoco/coco_evaluator.py` with a command line script

Module Contents

Classes

<code>CocoEvalCLIConfig</code>	Base class for custom configuration objects
<code>CocoEvalCLI</code>	

Functions

`main(cmdline=True, **kw)`

Todo:

- [X] should live in `kwcoco.cli.coco_eval`
-

Attributes

`_CLI`

`class kwcoco.cli.coco_eval.CocoEvalCLIConfig(data=None, default=None, cmdline=False)`
Bases: `scriptconfig.Config`

Base class for custom configuration objects

A configuration that can be specified by commandline args, a yaml config file, and / or a in-code dictionary. To use, define a class variable named “default” and assing it to a dict of default values. You can also use special *Value* classes to denote types. You can also define a method *normalize*, to postprocess the arguments after this class receives them.

Usage: Create a class that herits from this class.

Assign the “default” class-level variable as a dictionary of options

The keys of this dictionary must be command line friendly strings.

The values of the “defaults dictionary” can be literal values or instances of the `scriptconfig.Value` class, which allows for specification of default values, type information, help strings, and aliases.

You may also implement `normalize` (function with that takes no args and has no return) to postprocess your results after initialization.

When creating an instance of the class the `defaults` variable is used to make a dictionary-like object. You can override defaults by specifying the `data` keyword argument to either a file path or another dictionary. You can also specify `cmdline=True` to allow the contents of `sys.argv` to influence the values of the new object.

An instance of the config class behaves like a dictionary, except that you cannot set keys that do not already exist (as specified in the `defaults` dict).

Key Methods:

- `dump` - dump a json representation to a file
- `dumps` - dump a json representation to a string
- `argparse` - create the argparse object associated with this config
- **`argparse` - create an `argparse.ArgumentParser` object that** is defined by the defaults of this config.
- **`load` - rewrite the values based on a filepath, dictionary, or** command line contents.

Variables

- **`_data`** – this protected variable holds the raw state of the config object and is accessed by the dict-like
- **`_default`** – this protected variable maintains the default values for this config.

Example

```
>>> # Inherit from `Config` and assign `default`
>>> import scriptconfig as scfg
>>> class MyConfig(scfg.Config):
>>>     default = {
>>>         'option1': scfg.Value((1, 2, 3), tuple),
>>>         'option2': 'bar',
>>>         'option3': None,
>>>     }
>>> # You can now make instances of this class
>>> config1 = MyConfig()
>>> config2 = MyConfig(default=dict(option1='baz'))
```

`__doc__`

`default`

```
class kwcoco.cli.coco_eval.CocoEvalCLI
    name = eval
    CLICConfig
    classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> import ubelt as ub
>>> from kwcoco.cli.coco_eval import * # NOQA
>>> from os.path import join
>>> import kwcoco
>>> dpath = ub.ensure_app_cache_dir('kwcoco/tests/eval')
>>> true_dset = kwcoco.CocoDataset.demo('shapes8')
>>> from kwcoco.demo.perterb import perterb_coco
>>> kwargs = {
>>>     'box_noise': 0.5,
>>>     'n_fp': (0, 10),
>>>     'n_fn': (0, 10),
>>> }
>>> pred_dset = perterb_coco(true_dset, **kwargs)
>>> true_dset.fpath = join(dpath, 'true.mscoco.json')
>>> pred_dset.fpath = join(dpath, 'pred.mscoco.json')
>>> true_dset.dump(true_dset.fpath)
>>> pred_dset.dump(pred_dset.fpath)
>>> draw = False # set to false for faster tests
>>> CocoEvalCLI.main(
>>>     true_dataset=true_dset.fpath,
>>>     pred_dataset=pred_dset.fpath,
>>>     draw=draw)
```

kwcoco.cli.coco_eval.main(cmdline=True, **kw)

Todo:

- [X] should live in kwcoco.cli.coco_eval
-

CommandLine

```
# Generate test data
xdoctest -m kwcoco.cli.coco_eval CocoEvalCLI.main

kwcoco eval \
--true_dataset=$HOME/.cache/kwcoco/tests/eval/true.mscoco.json \
--pred_dataset=$HOME/.cache/kwcoco/tests/eval/pred.mscoco.json \
--out_dpath=$HOME/.cache/kwcoco/tests/eval/out \
--force_pycocoutils=False \
--area_range=all,0-4096,4096-inf

nautilus $HOME/.cache/kwcoco/tests/eval/out
```

kwcoco.cli.coco_eval._CLI

kwcoco.cli.coco_grab**Module Contents****Classes**

CocoGrabCLI

Attributes

_CLI

```
class kwcoco.cli.coco_grab.CocoGrabCLI
    class CLIConfig(data=None, default=None, cmdline=False)
        Bases: scriptconfig.Config
        Grab standard datasets.
```

Example

```
kwcoco grab cifar10 camvid
default
name = grab
classmethod main(cls, cmdline=True, **kw)
kwcoco.cli.coco_grab._CLI
```

kwcoco.cli.coco_modify_categories**Module Contents****Classes**

CocoModifyCatsCLI

Remove, rename, or coarsen categories.

Attributes

_CLI

```
class kwcoco.cli.coco_modify_categories.CocoModifyCatsCLI
```

Remove, rename, or coarsen categories.

```
class CLIConfig(data=None, default=None, cmdline=False)
```

Bases: `scriptconfig.Config`

Rename or remove categories

```
epilog = Multiline-String
```

```
1     Example Usage:  
2         kwCOCO modify_categories --help  
3         kwCOCO modify_categories --src=src:shapes8 --dst=  
4         ↵modcats.json  
5             kwCOCO modify_categories --src=src:shapes8 --dst=  
6             ↵modcats.json --rename eff:F,star:sun  
7                 kwCOCO modify_categories --src=src:shapes8 --dst=  
8                 ↵modcats.json --remove eff,star  
9                     kwCOCO modify_categories --src=src:shapes8 --dst=  
10                    ↵modcats.json --keep eff,  
11  
12                        kwCOCO modify_categories --src=src:shapes8 --dst=  
13                        ↵modcats.json --keep=[] --keep_annots=True
```

```
default
```

```
name = modify_categories
```

```
classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> # xdoctest: +SKIP  
>>> kw = {'src': 'src:shapes8'}  
>>> cmdline = False  
>>> cls = CocoModifyCatsCLI  
>>> cls.main(cmdline, **kw)
```

`kwCOCO.cli.coco_modify_categories._CLI`

kwcococo.cli.coco_reroot**Module Contents****Classes**

CocoRerootCLI

Attributes

_CLI

```
class kwcococo.cli.coco_reroot.CocoRerootCLI
    class CLIConfig(data=None, default=None, cmdline=False)
        Bases: scriptconfig.Config

        Reroot image paths onto a new image root.

        Modify the root of a coco dataset such to either make paths relative to a new root or make paths absolute.
```

Todo:

- [] Evaluate that all tests cases work
-

epilog = Multiline-String

```
1     Example Usage:
2         kwcococo reroot --help
3         kwcococo reroot --src=special:shapes8 --dst rerooted.json
4         kwcococo reroot --src=special:shapes8 --new_prefix=foo --
5             ↵check=True --dst rerooted.json
```

default**name = reroot****classmethod main(cls, cmdline=True, **kw)****Example**

```
>>> # xdoctest: +SKIP
>>> kw = {'src': 'special:shapes8'}
>>> cmdline = False
>>> cls = CocoRerootCLI
>>> cls.main(cmdline, **kw)
```

kwcococo.cli.coco_reroot._CLI

`kwcoco.cli.coco_show`

Module Contents

Classes

`CocoShowCLI`

Attributes

`_CLI`

```
class kwcoco.cli.coco_show.CocoShowCLI
    class CLIConfig(data=None, default=None, cmdline=False)
        Bases: scriptconfig.Config

        Visualize a COCO image using matplotlib or opencv, optionally writing it to disk

        epilog = Multiline-String
            1     Example Usage:
            2         kwcoco show --help
            3         kwcoco show --src=special:shapes8 --gid=1
            4         kwcoco show --src=special:shapes8 --gid=1 --dst out.png

        default
        name = show
    classmethod main(cls, cmdline=True, **kw)
```

Todo:

- [] Visualize auxiliary data
-

Example

```
>>> # xdoctest: +SKIP
>>> kw = {'src': 'special:shapes8'}
>>> cmdline = False
>>> cls = CocoShowCLI
>>> cls.main(cmdline, **kw)
```

`kwcoco.cli.coco_show._CLI`

`kwcococo.cli.coco_split`**Module Contents****Classes**

`CocoSplitCLI`

Attributes

`_CLI`

```
class kwcococo.cli.coco_split.CocoSplitCLI
    Bases: object

    class CLICConfig(data=None, default=None, cmdline=False)
        Bases: scriptconfig.Config

        Split a single COCO dataset into two sub-datasets.

        default

        epilog = Multiline-String
            Example Usage:
            1             kwcococo split --src special:shapes8 --dst1=learn.mscoco.
            2             ↪json --dst2=test.mscoco.json --factor=3 --rng=42

    name = split

    classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> kw = {'src': 'special:shapes8',
>>>         'dst1': 'train.json', 'dst2': 'test.json'}
>>> cmdline = False
>>> cls = CocoSplitCLI
>>> cls.main(cmdline, **kw)
```

`kwcococo.cli.coco_split._CLI`

`kwcoco.cli.coco_stats`

Module Contents

Classes

`CocoStatsCLI`

Attributes

`_CLI`

```
class kwcoco.cli.coco_stats.CocoStatsCLI
    class CLIConfig(data=None, default=None, cmdline=False)
        Bases: scriptconfig.Config

        Compute summary statistics about a COCO dataset

        default

        epilog = Multiline-String
            1     Example Usage:
            2         kwcoco stats --src=special:shapes8
            3         kwcoco stats --src=special:shapes8 --boxes=True

        name = stats

        classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> kw = {'src': 'special:shapes8'}
>>> cmdline = False
>>> cls = CocoStatsCLI
>>> cls.main(cmdline, **kw)
```

`kwcoco.cli.coco_stats._CLI`

kwcoco.cli.coco_subset**Module Contents****Classes**

CocoSubsetCLI

Functions

`query_subset(dset, config)`

Example**Attributes**

_CLI

```
class kwcoco.cli.coco_subset.CocoSubsetCLI
    Bases: object

class CLICConfig(data=None, default=None, cmdline=False)
    Bases: scriptconfig.Config

    Take a subset of this dataset and write it to a new file

    default

    epilog = Multiline-String

        1     Example Usage:
        2         kwcoco subset --src special:shapes8 --dst=foo.kwcoco.json
        3
        4             # Take only the even image-ids
        5             kwcoco subset --src special:shapes8 --dst=foo-even.kwcoco.
        ↵json --select_images '.id % 2 == 0'
        6
        7                 # Take only the videos where the name ends with 2
        8                 kwcoco subset --src special:vidshapes8 --dst=vidsub.
        ↵kwcoco.json --select_videos '.name | endswith("2")'

    name = subset

    classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> kw = {'src': 'special:shapes8',
>>>         'dst': 'subset.json', 'include_categories': 'superstar'}
>>> cmdline = False
>>> cls = CocoSubsetCLI
>>> cls.main(cmdline, **kw)
```

kwcoco.cli.coco_subset.query_subset(dset, config)

Example

```
>>> # xdoctest: +REQUIRES(module:jq)
>>> from kwcoco.cli.coco_subset import * # NOQA
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo()
>>> assert dset.n_images == 3
>>> #
>>> config = CocoSubsetCLI.CLICConfig({'select_images': '.id < 3'})
>>> new_dset = query_subset(dset, config)
>>> assert new_dset.n_images == 2
>>> #
>>> config = CocoSubsetCLI.CLICConfig({'select_images': '.file_name | test(".*.png")'
-> ''})
>>> new_dset = query_subset(dset, config)
>>> assert all(n.endswith('.png') for n in new_dset.images().lookup('file_name'))
>>> assert new_dset.n_images == 2
>>> #
>>> config = CocoSubsetCLI.CLICConfig({'select_images': '.file_name | test(".*.png")'
-> '| not'})
>>> new_dset = query_subset(dset, config)
>>> assert not any(n.endswith('.png') for n in new_dset.images().lookup('file_name'
->'))
>>> assert new_dset.n_images == 1
>>> #
>>> config = CocoSubsetCLI.CLICConfig({'select_images': '.id < 3 and (.file_name |'
-> test(".*.png"))'})
>>> new_dset = query_subset(dset, config)
>>> assert new_dset.n_images == 1
>>> #
>>> config = CocoSubsetCLI.CLICConfig({'select_images': '.id < 3 or (.file_name |'
-> test(".*.png"))'})
>>> new_dset = query_subset(dset, config)
>>> assert new_dset.n_images == 3
```

Example

```
>>> # xdoctest: +REQUIRES(module:jq)
>>> from kwcoco.cli.coco_subset import * # NOQA
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes8')
>>> assert dset.n_videos == 8
>>> assert dset.n_images == 16
>>> config = CocoSubsetCLI.CLICConfig({'select_videos': '.name == "toy_video_3"'})
>>> new_dset = query_subset(dset, config)
>>> assert new_dset.n_images == 2
>>> assert new_dset.n_videos == 1
```

`kwcoco.cli.coco_subset._CLI`

`kwcoco.cli.coco_toydata`

Module Contents

Classes

`CocoToyDataCLI`

Attributes

`_CLI`

```
class kwcoco.cli.coco_toydata.CocoToyDataCLI
    Bases: object

    class CLICConfig(data=None, default=None, cmdline=False)
        Bases: scriptconfig.Config

        Create COCO toydata for demo and testing purposes.

        default

        epilog = Multiline-String

            Example Usage:
                kwcoco toydata --key=shapes8 --dst=toydata.kwcoco.json

            kwcoco toydata --key=shapes8 --bundle_dpath=my_test_
            ↳bundle_v1
            kwcoco toydata --key=shapes8 --bundle_dpath=my_test_
            ↳bundle_v1

            kwcoco toydata --key=shapes8
            ↳--dst=../shapes8.kwcoco/dataset.kwcoco.json
```

(continues on next page) ▶

(continued from previous page)

```
8
9     TODO:
10    - [ ] allow specification of images directory
```

```
name = toydata
classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> kw = {'key': 'shapes8', 'dst': 'test.json'}
>>> cmdline = False
>>> cls = CocoToyDataCLI
>>> cls.main(cmdline, **kw)
```

kwcoco.cli.coco_toydata._CLI

kwcoco.cli.coco_union

Module Contents

Classes

CocoUnionCLI

Attributes

_CLI

```
class kwcoco.cli.coco_union.CocoUnionCLI
    Bases: object

    class CLICConfig(data=None, default=None, cmdline=False)
        Bases: scriptconfig.Config

        Combine multiple COCO datasets into a single merged dataset.

        default

        epilog = Multiline-String
```

```
1     Example Usage:
2         kwcoco union --src special:shapes8 special:shapes1 --
3             dst=combo.ms coco.json
```

```
name = union
classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> kw = {'src': ['special:shapes8', 'special:shapes1']}
>>> cmdline = False
>>> cls = CocoUnionCLI
>>> cls.main(cmdline, **kw)
```

`kwcoco.cli.coco_union._CLI`

`kwcoco.cli.coco_validate`

Module Contents

Classes

`CocoValidateCLI`

Attributes

`_CLI`

```
class kwcoco.cli.coco_validate.CocoValidateCLI
    class CLIConfig(data=None, default=None, cmdline=False)
        Bases: scriptconfig.Config

        Validate that a coco file conforms to the json schema, that assets exist, and potentially fix corrupted assets
        by removing them.

        default
        epilog = Multiline-String
            Example Usage:
            1   kwcoco toydata --dst foo.json --key=special:shapes8
            2   kwcoco validate --src=foo.json --corrupted=True
            3

    name = validate
    classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> from kwcoco.cli.coco_validate import * # NOQA
>>> kw = {'src': 'special:shapes8'}
>>> cmdline = False
>>> cls = CocoValidateCLI
>>> cls.main(cmdline, **kw)
```

kwcoco.cli.coco_validate._CLI

2.2.2 kwcoco.data

Submodules

kwcoco.data.grab_camvid

Downloads the CamVid data if necessary, and converts it to COCO.

Module Contents

Functions

`_devcheck_sample_full_image()`

`_devcheck_load_sub_image()`

`grab_camvid_train_test_val_splits(coco_dset,`
mode='segnet')

`grab_camvid_sampler()` Grab a kwcoco.CocoSampler object for the CamVid dataset.

`grab_coco_camvid()`

Example

`grab_raw_camvid()` Grab the raw camvid data.

`rgb_to_cid(r, g, b)`

`cid_to_rgb(cid)`

`convert_camvid_raw_to_coco(camvid_raw_info)` Converts the raw camvid format to an MSCOCO based format, (which lets use

`_define_camvid_class_hierarchy(dset)`

`main()` Dump the paths to the coco file to stdout

kwcoco.data.grab_camvid._devcheck_sample_full_image()

kwcoco.data.grab_camvid._devcheck_load_sub_image()

kwcoco.data.grab_camvid.grab_camvid_train_test_val_splits(coco_dset, mode='segnet')

`kwcoco.data.grab_camvid.grab_camvid_sampler()`
 Grab a kwcoco.CocoSampler object for the CamVid dataset.

Returns sampler

Return type kwcoco.CocoSampler

Example

```
>>> # xdoctest: +REQUIRES(--download)
>>> sampler = grab_camvid_sampler()
>>> print('sampler = {!r}'.format(sampler))
>>> # sampler.load_sample()
>>> for gid in ub.ProgIter(sampler.image_ids, desc='load image'):
>>>     img = sampler.load_image(gid)
```

`kwcoco.data.grab_camvid.grab_coco_camvid()`

Example

```
>>> # xdoctest: +REQUIRES(--download)
>>> dset = grab_coco_camvid()
>>> print('dset = {!r}'.format(dset))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> plt = kwplot.autoplt()
>>> plt.clf()
>>> dset.show_image(gid=1)
```

`kwcoco.data.grab_camvid.grab_raw_camvid()`

Grab the raw camvid data.

`kwcoco.data.grab_camvid.rgb_to_cid(r, g, b)`

`kwcoco.data.grab_camvid.cid_to_rgb(cid)`

`kwcoco.data.grab_camvid.convert_camvid_raw_to_coco(camvid_raw_info)`

Converts the raw camvid format to an MSCOCO based format, (which lets use use kwcoco's COCO backend).

Example

```
>>> # xdoctest: +REQUIRES(--download)
>>> camvid_raw_info = grab_raw_camvid()
>>> # test with a reduced set of data
>>> del camvid_raw_info['img_paths'][2:]
>>> del camvid_raw_info['mask_paths'][2:]
>>> dset = convert_camvid_raw_to_coco(camvid_raw_info)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> plt = kwplot.autoplt()
>>> kwplot.figure(fnum=1, pnum=(1, 2, 1))
>>> dset.show_image(gid=1)
```

(continues on next page)

(continued from previous page)

```
>>> kwplot.figure(fnum=1, pnum=(1, 2, 2))
>>> dset.show_image(gid=2)
```

kwcoco.data.grab_camvid._define_camvid_class_hierarchy(dset)**kwcoco.data.grab_camvid.main()**

Dump the paths to the coco file to stdout

By default these will go to in the path: `~/.cache/kwcoco/camvid/camvid-master`The four files will be: `~/.cache/kwcoco/camvid/camvid-master/camvid-full.mscoco.json``~/.cache/kwcoco/camvid/camvid-master/camvid-train.mscoco.json` `~/.cache/kwcoco/camvid/camvid-master/camvid-vali.mscoco.json` `~/.cache/kwcoco/camvid/camvid-master/camvid-test.mscoco.json`

kwcoco.data.grab_cifar

Downloads and converts CIFAR 10 and CIFAR 100 to kwcoco format

Module Contents

Functions

`_convert_cifar_x(dpath, cifar_dset, cifar_name, classes)`

`convert_cifar10(dpath=None)`

`convert_cifar100(dpath=None)`

`main()`

`kwcoco.data.grab_cifar._convert_cifar_x(dpath, cifar_dset, cifar_name, classes)``kwcoco.data.grab_cifar.convert_cifar10(dpath=None)``kwcoco.data.grab_cifar.convert_cifar100(dpath=None)``kwcoco.data.grab_cifar.main()`

kwcoco.data.grab_datasets

[] HMDB: a large human motion database - <https://serre-lab.clps.brown.edu/resource/hmdb-a-large-human-motion-database/>

[] <https://paperswithcode.com/dataset/imagenet>

[] <https://paperswithcode.com/dataset/coco>

[] <https://paperswithcode.com/dataset/fashion-mnist>

[] <https://paperswithcode.com/dataset/visual-question-answering>

[] <https://paperswithcode.com/dataset/lfw>
[] <https://paperswithcode.com/dataset/lsun>
[] <https://paperswithcode.com/dataset/ava>
[] <https://paperswithcode.com/dataset/activitynet>
[] <https://paperswithcode.com/dataset/clevr>:

kwcoco.data.grab_domainnet

References

<http://ai.bu.edu/M3SDA/#dataset>

Module Contents

Functions

grab_domain_net()

kwcoco.data.grab_domainnet.grab_domain_net()

Todo:

- [] Allow the user to specify the download directory, generalize this pattern across the data grab scripts.
-

kwcoco.data.grab_spacenet

References

<https://medium.com/the-downlinq/the-spacenet-7-multi-temporal-urban-development-challenge-algorithmic-baseline-4515ec9bd9fe>
<https://arxiv.org/pdf/2102.11958.pdf> <https://spacenet.ai/sn7-challenge/>

Module Contents

Functions

grab_spacenet7(data_dpath)

References

continues on next page

Table 31 – continued from previous page

<code>convert_spacenet_to_kwcoco(extract_dpath,</code>	Converts the raw SpaceNet7 dataset to kwcoco
<code>coco_fpath)</code>	
<code>main()</code>	

`kwcoco.data.grab_spacenet.grab_spacenet7(data_dpath)`

References

<https://spacenet.ai/sn7-challenge/>

Requires: awscli

`kwcoco.data.grab_spacenet.convert_spacenet_to_kwcoco(extract_dpath, coco_fpath)`

Converts the raw SpaceNet7 dataset to kwcoco

Note:

- The “train” directory contains 60 “videos” representing a region over time.
- **Each “video” directory contains :**
 - images - unmasked images
 - images_masked - images with masks applied
 - labels - geojson polys in wgs84?
 - labels_match - geojson polys in wgs84 with track ids?
 - labels_match_pix - geojson polys in pixels with track ids?
 - UDM_masks - unusable data masks (binary data corresponding with an image, may not exist)

File names appear like: “global_monthly_2018_01_mosaic_L15-1538E-1163N_6154_3539_13”

`kwcoco.data.grab_spacenet.main()`

`kwcoco.data.grab_voc`

Module Contents

Functions

<code>__torrent_voc()</code>	Requires:
<code>convert_voc_to_coco(dpath=None)</code>	
<code>_convert_voc_split(devkit_dpath, classes, split, split, year = 'train', 2012</code>	
<code>year, root)</code>	
<code>_read_split_paths(devkit_dpath, split, year)</code>	<code>split = 'train'</code>
<code>ensure_voc_data(dpath=None, force=False, years=[2007, 2012])</code>	Download the Pascal VOC data if it does not already exist.

continues on next page

Table 32 – continued from previous page

<code>ensure_voc_coco(dpath=None)</code>	Download the Pascal VOC data and convert it to coco, if it does exit.
<code>main()</code>	

`kwcoco.data.grab_voc.__torrent_voc()`

Requires: pip install deluge pip install python-libtorrent-bin

References

<https://academictorrents.com/details/f6ddac36ac7ae2ef79dc72a26a065b803c9c7230>

Todo:

- [] Is there a pythonic way to download a torrent programatically?
-

`kwcoco.data.grab_voc.convert_voc_to_coco(dpath=None)`

`kwcoco.data.grab_voc._convert_voc_split(devkit_dpath, classes, split, year, root)`
split, year = ‘train’, 2012 split, year = ‘train’, 2007

`kwcoco.data.grab_voc._read_split_paths(devkit_dpath, split, year)`
split = ‘train’ self = VOCdataset(‘test’) year = 2007 year = 2012

`kwcoco.data.grab_voc.ensure_voc_data(dpath=None, force=False, years=[2007, 2012])`
Download the Pascal VOC data if it does not already exist.

Note:

- [] These URLs seem to be dead
-

Example

```
>>> # xdoctest: +REQUIRES(--download)
>>> devkit_dpath = ensure_voc_data()
```

`kwcoco.data.grab_voc.ensure_voc_coco(dpath=None)`

Download the Pascal VOC data and convert it to coco, if it does exit.

Parameters `dpath` (`str`) – download directory. Defaults to “~/data/VOC”.

Returns

mapping from dataset tags to coco file paths. The original datasets have keys prefixed with underscores. The standard splits keys are train, vali, and test.

Return type `Dict[str, str]`

`kwcoco.data.grab_voc.main()`

2.2.3 kwcoco.demo

Submodules

kwcoco.demo.boids

Module Contents

Classes

<i>Boids</i>	Efficient numpy based backend for generating boid positions.
--------------	--

Functions

<code>clamp_mag(vec, mag, axis=None)</code>	<code>vec = np.random.rand(10, 2)</code>
<code>triu_condense_multi_index(multi_index, dims, symmetric=False)</code>	Like <code>np.ravel_multi_index</code> but returns positions in an upper triangular
<code>_spatial_index_scratch()</code>	
<code>closest_point_on_line_segment(pts, e1, e2)</code>	Finds the closet point from p on line segment (e1, e2)
<code>_pygame_render_boids()</code>	Fast and responsive BOID rendering. This is an easter egg.
<code>_yeah_boid()</code>	

```
class kwcoco.demo.boids.Boids(num, dims=2, rng=None, **kwargs)
```

Bases: `ubelt.NiceRepr`

Efficient numpy based backend for generating boid positions.

BOID = bird-oid object

References

<https://www.youtube.com/watch?v=mhjuuHl6qHM> <https://medium.com/better-programming/boids-simulating-birds-flock-behavior-in-python-9fff99375118> <https://en.wikipedia.org/wiki/Boids>

Example

```
>>> from kwcoco.demo.boids import * # NOQA
>>> num_frames = 10
>>> num_objects = 3
>>> rng = None
>>> self = Boids(num=num_objects, rng=rng).initialize()
>>> paths = self.paths(num_frames)
>>> #
>>> # xdoctest: +REQUIRES(--show)
```

(continues on next page)

(continued from previous page)

```
>>> import kwplot
>>> plt = kwplot.autopl()t()
>>> from mpl_toolkits.mplot3d import Axes3D # NOQA
>>> ax = plt.gca(projection='3d')
>>> ax.cla()
>>> #
>>> for path in paths:
>>>     time = np.arange(len(path))
>>>     ax.plot(time, path.T[0] * 1, path.T[1] * 1, ',-')
>>> ax.set_xlim(0, num_frames)
>>> ax.set_ylim(-.01, 1.01)
>>> ax.set_zlim(-.01, 1.01)
>>> ax.set_xlabel('time')
>>> ax.set_ylabel('u-pos')
>>> ax.set_zlabel('v-pos')
>>> kwplot.show_if_requested()
```

```
import xdev _ = xdev.profile_now(self.compute_forces)() _ = xdev.profile_now(self.update_neighbors)()
```

Example

```
>>> # Test determinism
>>> from kwcoco.demo.boids import * # NOQA
>>> num_frames = 2
>>> num_objects = 1
>>> rng = 4532
>>> self = Boids(num=num_objects, rng=rng).initialize()
>>> #print(ub.hash_data(self.pos))
>>> #print(ub.hash_data(self.vel))
>>> #print(ub.hash_data(self.acc))
>>> tocheck = []
>>> for i in range(100):
>>>     self = Boids(num=num_objects, rng=rng).initialize()
>>>     self.step()
>>>     self.step()
>>>     self.step()
>>>     tocheck.append(self.pos.copy())
>>> assert ub.allsame(list(map(ub.hash_data, tocheck)))
```

```
__nice__(self)
initialize(self)
update_neighbors(self)
compute_forces(self)
boundary_conditions(self)
step(self)
Update positions, velocities, and accelerations
paths(self, num_steps)
```

```
kwcococo.demo.boids.clamp_mag(vec, mag, axis=None)
vec = np.random.rand(10, 2) mag = 1.0 axis = 1 new_vec = clamp_mag(vec, mag, axis) np.linalg.norm(new_vec,
axis=axis)
```

```
kwcococo.demo.boids.triu_condense_multi_index(multi_index, dims, symmetric=False)
```

Like np.ravel_multi_index but returns positions in an upper triangular condensed square matrix

Examples

multi_index (Tuple[ArrayLike]): indexes for each dimension into the square matrix

dims (Tuple[int]): shape of each dimension in the square matrix (should all be the same)

symmetric (bool): if True, converts lower triangular indices to their upper triangular location. This may cause a copy to occur.

References

<https://stackoverflow.com/a/36867493/887074> https://numpy.org/doc/stable/reference/generated/numpy.ravel_multi_index.html#numpy.ravel_multi_index

Examples

```
>>> dims = (3, 3)
>>> symmetric = True
>>> multi_index = (np.array([0, 0, 1]), np.array([1, 2, 2]))
>>> condensed_idxs = triu_condense_multi_index(multi_index, dims, symmetric=symmetric)
>>> assert condensed_idxs.tolist() == [0, 1, 2]
```

```
>>> n = 7
>>> symmetric = True
>>> multi_index = np.triu_indices(n=n, k=1)
>>> condensed_idxs = triu_condense_multi_index(multi_index, [n] * 2, ↴
    ↪symmetric=symmetric)
>>> assert condensed_idxs.tolist() == list(range(n * (n - 1) // 2))
>>> from scipy.spatial.distance import pdist, squareform
>>> square_mat = np.zeros((n, n))
>>> condens_mat = squareform(square_mat)
>>> condens_mat[condensed_idxs] = np.arange(len(condensed_idxs)) + 1
>>> square_mat = squareform(condens_mat)
>>> print('square_mat =\n{}'.format(ub.repr2(square_mat, nl=1)))
```

```
>>> n = 7
>>> symmetric = True
>>> multi_index = np.tril_indices(n=n, k=-1)
>>> condensed_idxs = triu_condense_multi_index(multi_index, [n] * 2, ↴
    ↪symmetric=symmetric)
>>> assert sorted(condensed_idxs.tolist()) == list(range(n * (n - 1) // 2))
>>> from scipy.spatial.distance import pdist, squareform
>>> square_mat = np.zeros((n, n))
>>> condens_mat = squareform(square_mat, checks=False)
>>> condens_mat[condensed_idxs] = np.arange(len(condensed_idxs)) + 1
```

(continues on next page)

(continued from previous page)

```
>>> square_mat = squareform(conden_mat)
>>> print('square_mat =\n{}'.format(ub.repr2(square_mat, nl=1)))
```

`kwcococo.demo.boids._spatial_index_scratch()`

`kwcococo.demo.boids.closest_point_on_line_segment(pts, e1, e2)`

Finds the closet point from p on line segment (e1, e2)

Parameters

- `pts (ndarray)` – xy points [Nx2]
- `e1 (ndarray)` – the first xy endpoint of the segment
- `e2 (ndarray)` – the second xy endpoint of the segment

Returns `pt_on_seg` - the closest xy point on (e1, e2) from ptp

Return type ndarray

References

http://en.wikipedia.org/wiki/Distance_from_a_point_to_a_line <http://stackoverflow.com/questions/849211/shortest-distance-between-a-point-and-a-line-segment>

Example

```
>>> # ENABLE_DOCTEST
>>> from kwcococo.demo.boids import * # NOQA
>>> verts = np.array([[ 21.83012702,  13.16987298],
>>>                   [ 16.83012702,  21.83012702],
>>>                   [ 8.16987298,  16.83012702],
>>>                   [ 13.16987298,  8.16987298],
>>>                   [ 21.83012702,  13.16987298]])
```

`kwcococo.demo.boids._pygame_render_boids()`

Fast and responsive BOID rendering. This is an easter egg.

Requirements: pip install pygame

CommandLine

```
python -m kwcococo.demo.boids
pip install pygame kwcococo -U && python -m kwcococo.demo.boids
```

`kwcococo.demo.boids._yeah_boid()`

kwcoco.demo.perterb**Module Contents****Functions**

<code>perterb_coco(coco_dset, **kwargs)</code>	Perterbs a coco dataset
<code>_demo_construct_probs(pred_cxs, pred_scores, classes, rng, hacked=1)</code>	Constructs random probabilities for demo data

kwcoco.demo.perterb.perterb_coco(*coco_dset*, *kwargs*)**

Perterbs a coco dataset

Parameters

- **`rng`** (*int*, *default=0*)
- **`box_noise`** (*int*, *default=0*)
- **`cls_noise`** (*int*, *default=0*)
- **`null_pred`** (*bool*, *default=False*)
- **`with_probs`** (*bool*, *default=False*)
- **`score_noise`** (*float*, *default=0.2*)
- **`hacked`** (*int*, *default=1*)

Example

```
>>> from kwCOCO.demo.perterb import * # NOQA
>>> from kwCOCO.demo.perterb import _demo_construct_probs
>>> import kwCOCO
>>> coco_dset = true_dset = kwCOCO.CocoDataset.demo('shapes8')
>>> kwargs = {
>>>     'box_noise': 0.5,
>>>     'n_fp': 3,
>>>     'with_probs': 1,
>>>     'with_heatmaps': 1,
>>> }
>>> pred_dset = perterb_coco(true_dset, **kwargs)
>>> pred_dset._check_json_serializable()
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()()
>>> gid = 1
>>> canvas = true_dset.delayed_load(gid).finalize()
>>> canvas = true_dset.annots(gid=gid).detections.draw_on(canvas, color='green')
>>> canvas = pred_dset.annots(gid=gid).detections.draw_on(canvas, color='blue')
>>> kwplot.imshow(canvas)
```

kwcoco.demo.perterb._demo_construct_probs(*pred_cxs*, *pred_scores*, *classes*, *rng*, *hacked=1*)

Constructs random probabilities for demo data

Example

```
>>> import kwcoco
>>> import kwarray
>>> rng = kwarray.ensure_rng(0)
>>> classes = kwcoco.CategoryTree.coerce(10)
>>> hacked = 1
>>> pred_cxs = rng.randint(0, 10, 10)
>>> pred_scores = rng.rand(10)
>>> probs = _demo_construct_probs(pred_cxs, pred_scores, classes, rng, hacked)
>>> probs.sum(axis=1)
```

kwcoco.demo.toydata

Generates “toydata” for demo and testing purposes.

Note: The implementation of *demodata_toy_img* and *demodata_toy_dset* should be redone using the tools built for *random_video_dset*, which have more extensible implementations.

Module Contents

Functions

<i>random_single_video_dset</i> (image_size=(600, 600), num_frames=5, num_tracks=3, tid_start=1, gid_start=1, video_id=1, anchors=None, rng=None, render=False, dpath=None, autobuild=True, verbose=3, aux=None, multispectral=False, max_speed=0.01, channels=None, multisensor=False, **kwargs)	Create the video scene layout of object positions.
<i>random_video_dset</i> (num_videos=1, num_frames=2, num_tracks=2, anchors=None, image_size=(600, 600), verbose=3, render=False, aux=None, multispectral=False, multisensor=False, rng=None, dpath=None, max_speed=0.01, channels=None, **kwargs)	Create a toy Coco Video Dataset
<i>demodata_toy_dset</i> (image_size=(600, 600), n_imgs=5, verbose=3, rng=0, newstyle=True, dpath=None, bundle_dpath=None, aux=None, use_cache=True, **kwargs)	Create a toy detection problem
<i>demodata_toy_img</i> (anchors=None, image_size=(104, 104), categories=None, n_annots=(0, 50), fg_scale=0.5, bg_scale=0.8, bg_intensity=0.1, fg_intensity=0.9, gray=True, centerobj=None, exact=False, newstyle=True, rng=None, aux=None, **kwargs)	Generate a single image with non-overlapping toy objects of available

```
kwcoco.demo.toydata.random_single_video_dset(image_size=(600, 600), num_frames=5, num_tracks=3,  
tid_start=1, gid_start=1, video_id=1, anchors=None,  
rng=None, render=False, dpath=None, autobuild=True,  
verbose=3, aux=None, multispectral=False,  
max_speed=0.01, channels=None, multisensor=False,  
**kwargs)
```

Create the video scene layout of object positions.

Note: Does not render the data unless specified.

Parameters

- **image_size** (*Tuple[int, int]*) – size of the images
- **num_frames** (*int*) – number of frames in this video
- **num_tracks** (*int*) – number of tracks in this video
- **tid_start** (*int, default=1*) – track-id start index
- **gid_start** (*int, default=1*) – image-id start index
- **video_id** (*int, default=1*) – video-id of this video
- **anchors** (*ndarray | None*) – base anchor sizes of the object boxes we will generate.
- **rng** (*RandomState*) – random state / seed
- **render** (*bool | dict*) – if truthy, does the rendering according to provided params in the case of dict input.
- **autobuild** (*bool, default=True*) – prebuild coco lookup indexes
- **verbose** (*int*) – verbosity level
- **aux** (*bool | List[str]*) – if specified generates auxiliary channels
- **multispectral** (*bool*) – if specified simulates multispectral imagery This is similar to aux, but has no “main” file.
- **max_speed** (*float*) – max speed of movers
- **channels** (*str | None | ChannelSpec*) – if specified generates multispectral images with dummy channels
- **multisensor** (*bool*) –
if True, generates demodata from “multiple sensors”, in other words, observations may have different “bands”.
- ****kwargs** – used for old backwards compatible argument names gsize - alias for image_size

Todo:

- [] Need maximum allowed object overlap measure
 - [] Need better parameterized path generation
-

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> anchors = np.array([ [0.3, 0.3], [0.1, 0.1]] )
>>> dset = random_single_video_dset(render=True, num_frames=10, num_tracks=10, anchors=anchors, max_speed=0.2)
>>> # xdoctest: +REQUIRES(--show)
>>> # Show the tracks in a single image
>>> import kwplot
>>> kwplot.autopl()
>>> annots = dset.annots()
>>> tids = annots.lookup('track_id')
>>> tid_to_aids = ub.group_items(annots.aids, tids)
>>> paths = []
>>> track_boxes = []
>>> for tid, aids in tid_to_aids.items():
>>>     boxes = dset.annots(aids).boxes.to_cxywh()
>>>     path = boxes.data[:, 0:2]
>>>     paths.append(path)
>>>     track_boxes.append(boxes)
>>> import kwplot
>>> plt = kwplot.autopl()
>>> ax = plt.gca()
>>> ax.cla()
>>> #
>>> import kwimage
>>> colors = kwimage.Color.distinct(len(track_boxes))
>>> for i, boxes in enumerate(track_boxes):
>>>     color = colors[i]
>>>     path = boxes.data[:, 0:2]
>>>     boxes.draw(color=color, centers={'radius': 0.01}, alpha=0.5)
>>>     ax.plot(path.T[0], path.T[1], 'x-', color=color)
```

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> anchors = np.array([ [0.2, 0.2], [0.1, 0.1]] )
>>> gsize = np.array([(600, 600)])
>>> print(anchors * gsize)
>>> dset = random_single_video_dset(render=True, num_frames=10,
>>>                                   anchors=anchors, num_tracks=10,
>>>                                   image_size='random')
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> plt = kwplot.autopl()
>>> plt.clf()
>>> gids = list(dset.imgs.keys())
>>> pnums = kwplot.PlotNums(nSubplots=len(gids))
>>> for gid in gids:
>>>     dset.show_image(gid, pnum=pnums(), fnum=1, title=False)
>>>     pnums = kwplot.PlotNums(nSubplots=len(gids))
```

Example

```
>>> from kwCOCO.demo.toydata_video import * # NOQA
>>> dset = random_single_video_dset(num_frames=10, num_tracks=10, aux=True)
>>> assert 'auxiliary' in dset.imgs[1]
>>> assert dset.imgs[1]['auxiliary'][0]['channels']
>>> assert dset.imgs[1]['auxiliary'][1]['channels']
```

Example

```
>>> from kwCOCO.demo.toydata_video import * # NOQA
>>> multispectral = True
>>> dset = random_single_video_dset(num_frames=1, num_tracks=1, multispectral=True)
>>> dset._check_json_serializable()
>>> dset.dataset['images']
>>> assert dset.imgs[1]['auxiliary'][1]['channels']
>>> # test that we can render
>>> render_toy_dataset(dset, rng=0, dpath=None, renderkw={})
```

Example

```
>>> from kwCOCO.demo.toydata_video import * # NOQA
>>> dset = random_single_video_dset(num_frames=4, num_tracks=1, multispectral=True, ↴
    ↵multisensor=True, image_size='random', rng=2338)
>>> dset._check_json_serializable()
>>> assert dset.imgs[1]['auxiliary'][1]['channels']
>>> # Print before and after render
>>> #print('multisensor-images = {}'.format(ub.repr2(dset.dataset['images'], nl=-2)))
>>> #print('multisensor-images = {}'.format(ub.repr2(dset.dataset, nl=-2)))
>>> print(ub.hash_data(dset.dataset))
>>> # test that we can render
>>> render_toy_dataset(dset, rng=0, dpath=None, renderkw={})
>>> #print('multisensor-images = {}'.format(ub.repr2(dset.dataset['images'], nl=-2)))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> from kwCOCO.demo.toydata_video import _draw_video_sequence # NOQA
>>> gids = [1, 2, 3, 4]
>>> final = _draw_video_sequence(dset, gids)
>>> print('dset.fpath = {!r}'.format(dset.fpath))
>>> kwplot.imshow(final)
```

```
kwCOCO.demo.toydata.random_video_dset(num_videos=1, num_frames=2, num_tracks=2, anchors=None,
                                         image_size=(600, 600), verbose=3, render=False, aux=None,
                                         multispectral=False, multisensor=False, rng=None, dpath=None,
                                         max_speed=0.01, channels=None, **kwargs)
```

Create a toy Coco Video Dataset

Parameters

- **num_videos** (*int*) – number of videos

- **num_frames** (*int*) – number of images per video
- **num_tracks** (*int*) – number of tracks per video
- **image_size** (*Tuple[int, int]*) – The width and height of the generated images
- **render** (*bool | dict*) – if truthy the toy annotations are synthetically rendered. See `render_toy_image()` for details.
- **rng** (*int | None | RandomState*) – random seed / state
- **dpath** (*str*) – only used if render is truthy, place to write rendered images.
- **verbose** (*int, default=3*) – verbosity mode
- **aux** (*bool*) – if True generates dummy auxiliary channels
- **multispectral** (*bool*) – similar to aux, but does not have the concept of a “main” image.
- **max_speed** (*float*) – max speed of movers
- **channels** (*str*) – experimental new way to get MSI with specific band distributions.
- ****kwargs** – used for old backwards compatible argument names gsize - alias for image_size

SeeAlso: `random_single_video_dset`

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> dset = random_video_dset(render=True, num_videos=3, num_frames=2,
>>>                      num_tracks=5, image_size=(128, 128))
>>> # xdoctest: +REQUIRES(--show)
>>> dset.show_image(1, doclf=True)
>>> dset.show_image(2, doclf=True)
```

```
>>> from kwcoco.demo.toydata_video import * # NOQA
dset = random_video_dset(render=False, num_videos=3, num_frames=2,
    num_tracks=10)
dset._tree()
dset.imgs[1]
```

```
dset = random_single_video_dset() dset._tree() dset.imgs[1]
from kwcoco.demo.toydata_video import * # NOQA dset = random_video_dset(render=True, num_videos=3,
num_frames=2,
    num_tracks=10)
print(dset.imgs[1]) print('dset.bundle_dpath = {!r}'.format(dset.bundle_dpath)) dset._tree()
import xdev globals().update(xdev.get_func_kwargs(random_video_dset)) num_videos = 2
kwcoco.demo.toydata.demodata_toy_dset(image_size=(600, 600), n_imgs=5, verbose=3, rng=0,
    newstyle=True, dpath=None, bundle_dpath=None, aux=None,
    use_cache=True, **kwargs)
```

Create a toy detection problem

Parameters

- **image_size** (*Tuple[int, int]*) – The width and height of the generated images

- **n_imgs** (*int*) – number of images to generate
- **rng** (*int | RandomState, default=0*) – random number generator or seed
- **newstyle** (*bool, default=True*) – create newstyle kwcoco data
- **dpath** (*str*) – path to the directory that will contain the bundle, (defaults to a kwcoco cache dir). Ignored if *bundle_dpath* is given.
- **bundle_dpath** (*str*) – path to the directory that will store images. If specified, *dpath* is ignored. If unspecified, a bundle will be written inside *dpath*.
- **aux** (*bool*) – if True generates dummy auxiliary channels
- **verbose** (*int, default=3*) – verbosity mode
- **use_cache** (*bool, default=True*) – if True caches the generated json in the *dpath*.
- ****kwargs** – used for old backwards compatible argument names gsize - alias for image_size

Return type *kwcoco.CocoDataset*

SeeAlso: random_video_dset

CommandLine

```
xdoctest -m kwcoco.demo.toydata_image demodata_toy_dset --show
```

Todo:

- [] Non-homogeneous images sizes
-

Example

```
>>> from kwcoco.demo.toydata_image import *
>>> import kwcoco
>>> dset = demodata_toy_dset(image_size=(300, 300), aux=True, use_cache=False)
>>> # xdoctest: +REQUIRES(--show)
>>> print(ub.repr2(dset.dataset, nl=2))
>>> import kwplot
>>> kwplot.autopl()l()
>>> dset.show_image(gid=1)
>>> ub.startfile(dset.bundle_dpath)
```

dset._tree()

```
>>> from kwcoco.demo.toydata_image import *
>>> import kwcoco
```

```
dset = demodata_toy_dset(image_size=(300, 300), aux=True, use_cache=False) print(dset.imgs[1]) dset._tree()
dset = demodata_toy_dset(image_size=(300, 300), aux=True, use_cache=False, bundle_dpath='test_bundle')
print(dset.imgs[1]) dset._tree()
dset = demodata_toy_dset( image_size=(300, 300), aux=True, use_cache=False, dpath='test_cache_dpath')
```

```
kwcoco.demo.toydata.demodata_toy_img(anchors=None, image_size=(104, 104), categories=None,
                                         n_annot=(0, 50), fg_scale=0.5, bg_scale=0.8, bg_intensity=0.1,
                                         fg_intensity=0.9, gray=True, centerobj=None, exact=False,
                                         newstyle=True, rng=None, aux=None, **kwargs)
```

Generate a single image with non-overlapping toy objects of available categories.

Todo:

DEPRECATE IN FAVOR OF random_single_video_dset + render_toy_image

Parameters

- **anchors** (*ndarray*) – Nx2 base width / height of boxes
- **gsize** (*Tuple[int, int]*) – width / height of the image
- **categories** (*List[str]*) – list of category names
- **n_annot** (*Tuple | int*) – controls how many annotations are in the image. if it is a tuple, then it is interpreted as uniform random bounds
- **fg_scale** (*float*) – standard deviation of foreground intensity
- **bg_scale** (*float*) – standard deviation of background intensity
- **bg_intensity** (*float*) – mean of background intensity
- **fg_intensity** (*float*) – mean of foreground intensity
- **centerobj** (*bool*) – if ‘pos’, then the first annotation will be in the center of the image, if ‘neg’, then no annotations will be in the center.
- **exact** (*bool*) – if True, ensures that exactly the number of specified annots are generated.
- **newstyle** (*bool*) – use new-syle kwCOCO format
- **rng** (*RandomState*) – the random state used to seed the process
- **aux** – if specified builds auxiliary channels
- ****kwargs** – used for old backwards compatible argument names. gsize - alias for image_size

CommandLine

```
xdoctest -m kwCOCO.demo.toydata_image demodata_toy_img:0 --profile
xdoctest -m kwCOCO.demo.toydata_image demodata_toy_img:1 --show
```

Example

```
>>> from kwCOCO.demo.toydata_image import * # NOQA
>>> img, anns = demodata_toy_img(image_size=(32, 32), anchors=[[.3, .3]], rng=0)
>>> img['imdata'] = '<ndarray shape={}>'.format(img['imdata'].shape)
>>> print('img = {}'.format(ub.repr2(img)))
>>> print('anns = {}'.format(ub.repr2(anns, nl=2, cbr=True)))
>>> # xdoctest: +IGNORE_WANT
img = {
    'height': 32,
```

(continues on next page)

(continued from previous page)

```
'imdata': '<ndarray shape=(32, 32, 3)>',
'width': 32,
}
anns = [{`bbox': [15, 10, 9, 8],
'category_name': 'star',
'keypoints': [],
'segmentation': {'counts': '[`06j0000020N1000e8', 'size': [32, 32]},},
{'bbox': [11, 20, 7, 7],
'category_name': 'star',
'keypoints': [],
'segmentation': {'counts': 'g;1m04N0020N102L[=', 'size': [32, 32]},},
{'bbox': [4, 4, 8, 6],
'category_name': 'superstar',
'keypoints': [{"keypoint_category': 'left_eye', 'xy': [7.25, 6.8125]}, {"keypoint_category': 'right_eye', 'xy': [8.75, 6.8125]}],
'segmentation': {'counts': 'U4210j0300001010000MV00ed0', 'size': [32, 32]},},
{'bbox': [3, 20, 6, 7],
'category_name': 'star',
'keypoints': [],
'segmentation': {'counts': 'g31m04N000002L[f0', 'size': [32, 32]},},]
```

Example

```
>>> # xdoctest: +REQUIRES(--show)
>>> img, anns = demodata_toy_img(image_size=(172, 172), rng=None, aux=True)
>>> print('anns = {}'.format(ub.repr2(anns, nl=1)))
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(img['imdata'], pnum=(1, 2, 1), fnum=1)
>>> auxdata = img['auxiliary'][0]['imdata']
>>> kwplot.imshow(auxdata, pnum=(1, 2, 2), fnum=1)
>>> kwplot.show_if_requested()
```

Example

```
>>> # xdoctest: +REQUIRES(--show)
>>> img, anns = demodata_toy_img(image_size=(172, 172), rng=None, aux=True)
>>> print('anns = {}'.format(ub.repr2(anns, nl=1)))
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(img['imdata'], pnum=(1, 2, 1), fnum=1)
>>> auxdata = img['auxiliary'][0]['imdata']
>>> kwplot.imshow(auxdata, pnum=(1, 2, 2), fnum=1)
>>> kwplot.show_if_requested()
```

kwcoco.demo.toydata_image

Generates “toydata” for demo and testing purposes.

Loose image version of the toydata generators.

Note: The implementation of `demodata_toy_img` and `demodata_toy_dset` should be redone using the tools built for `random_video_dset`, which have more extensible implementations.

Module Contents

Functions

<code>demodata_toy_dset(image_size=(600, 600), n_imgs=5, verbose=3, rng=0, newstyle=True, dpath=None, bundle_dpath=None, aux=None, use_cache=True, **kwargs)</code>	Create a toy detection problem
<code>demodata_toy_img(anchors=None, image_size=(104, 104), categories=None, n_annots=(0, 50), fg_scale=0.5, bg_scale=0.8, bg_intensity=0.1, fg_intensity=0.9, gray=True, centerobj=None, exact=False, newstyle=True, rng=None, aux=None, **kwargs)</code>	Generate a single image with non-overlapping toy objects of available

Attributes

`profile`

`TOYDATA_IMAGE_VERSION`

kwcoco.demo.toydata_image.profile

`kwcoco.demo.toydata_image.TODYDATA_IMAGE_VERSION = 20`

`kwcoco.demo.toydata_image.demodata_toy_dset(image_size=(600, 600), n_imgs=5, verbose=3, rng=0, newstyle=True, dpath=None, bundle_dpath=None, aux=None, use_cache=True, **kwargs)`

Create a toy detection problem

Parameters

- `image_size` (`Tuple[int, int]`) – The width and height of the generated images
- `n_imgs` (`int`) – number of images to generate
- `rng` (`int | RandomState, default=0`) – random number generator or seed
- `newstyle` (`bool, default=True`) – create newstyle kwococo data
- `dpath` (`str`) – path to the directory that will contain the bundle, (defaults to a kwococo cache dir). Ignored if `bundle_dpath` is given.

- **bundle_dpath** (*str*) – path to the directory that will store images. If specified, dpath is ignored. If unspecified, a bundle will be written inside *dpath*.
- **aux** (*bool*) – if True generates dummy auxiliary channels
- **verbose** (*int, default=3*) – verbosity mode
- **use_cache** (*bool, default=True*) – if True caches the generated json in the *dpath*.
- ****kwargs** – used for old backwards compatible argument names gsize - alias for image_size

Return type *kwCOCO.CocoDataset*

SeeAlso: random_video_dset

CommandLine

```
xdoctest -m kwCOCO.demo.toydata_image demodata_toy_dset --show
```

Todo:

- [] Non-homogeneous images sizes
-

Example

```
>>> from kwCOCO.demo.toydata_image import *
>>> import kwCOCO
>>> dset = demodata_toy_dset(image_size=(300, 300), aux=True, use_cache=False)
>>> # xdoctest: +REQUIRES(--show)
>>> print(ub.repr2(dset.dataset, nl=2))
>>> import kwplot
>>> kwplot.autompl()
>>> dset.show_image(gid=1)
>>> ub.startfile(dset.bundle_dpath)
```

dset._tree()

```
>>> from kwCOCO.demo.toydata_image import *
>>> import kwCOCO
```

```
dset = demodata_toy_dset(image_size=(300, 300), aux=True, use_cache=False) print(dset.imgs[1]) dset._tree()
dset = demodata_toy_dset(image_size=(300, 300), aux=True, use_cache=False, bundle_dpath='test_bundle')
print(dset.imgs[1]) dset._tree()
dset = demodata_toy_dset(image_size=(300, 300), aux=True, use_cache=False, dpath='test_cache_dpath')
kwCOCO.demo.toydata_image.demodata_toy_img(anchors=None, image_size=(104, 104), categories=None,
                                             n_annot=(0, 50), fg_scale=0.5, bg_scale=0.8,
                                             bg_intensity=0.1, fg_intensity=0.9, gray=True,
                                             centerobj=None, exact=False, newstyle=True, rng=None,
                                             aux=None, **kwargs)
```

Generate a single image with non-overlapping toy objects of available categories.

Todo:**DEPRECATE IN FAVOR OF** random_single_video_dset + render_toy_image

Parameters

- **anchors** (*ndarray*) – Nx2 base width / height of boxes
- **gsize** (*Tuple[int, int]*) – width / height of the image
- **categories** (*List[str]*) – list of category names
- **n_annot** (*Tuple | int*) – controls how many annotations are in the image. if it is a tuple, then it is interpreted as uniform random bounds
- **fg_scale** (*float*) – standard deviation of foreground intensity
- **bg_scale** (*float*) – standard deviation of background intensity
- **bg_intensity** (*float*) – mean of background intensity
- **fg_intensity** (*float*) – mean of foreground intensity
- **centerobj** (*bool*) – if ‘pos’, then the first annotation will be in the center of the image, if ‘neg’, then no annotations will be in the center.
- **exact** (*bool*) – if True, ensures that exactly the number of specified annots are generated.
- **newstyle** (*bool*) – use new-style kwcoco format
- **rng** (*RandomState*) – the random state used to seed the process
- **aux** – if specified builds auxiliary channels
- ****kwargs** – used for old backwards compatible argument names. gsize - alias for image_size

CommandLine

```
xdoctest -m kwcoco.demo.toydata_image demodata_toy_img:0 --profile
xdoctest -m kwcoco.demo.toydata_image demodata_toy_img:1 --show
```

Example

```
>>> from kwcoco.demo.toydata_image import * # NOQA
>>> img, anns = demodata_toy_img(image_size=(32, 32), anchors=[[.3, .3]], rng=0)
>>> img['imdata'] = '<ndarray shape={}>'.format(img['imdata'].shape)
>>> print('img = {}'.format(ub.repr2(img)))
>>> print('anns = {}'.format(ub.repr2(anns, nl=2, cbr=True)))
>>> # xdoctest: +IGNORE_WANT
img = {
    'height': 32,
    'imdata': '<ndarray shape=(32, 32, 3)>',
    'width': 32,
}
anns = [{`bbox`: [15, 10, 9, 8],
`category_name`: 'star'},
```

(continues on next page)

(continued from previous page)

```
'keypoints': [],
'segmentation': {'counts': '[`06j0000020N1000e8', 'size': [32, 32]}, {},
{'bbox': [11, 20, 7, 7],
'category_name': 'star',
'keypoints': [],
'segmentation': {'counts': 'g;1m04N0020N102L[=', 'size': [32, 32]}, {},
{'bbox': [4, 4, 8, 6],
'category_name': 'superstar',
'keypoints': [{"keypoint_category': 'left_eye', 'xy': [7.25, 6.8125]}, {"keypoint_
category': 'right_eye', 'xy': [8.75, 6.8125]}],
'segmentation': {'counts': 'U4210j0300001010000MV00ed0', 'size': [32, 32]}, {},
{'bbox': [3, 20, 6, 7],
'category_name': 'star',
'keypoints': [],
'segmentation': {'counts': 'g31m04N000002L[f0', 'size': [32, 32]}, {}]
```

Example

```
>>> # xdoctest: +REQUIRES(--show)
>>> img, anns = demodata_toy_img(image_size=(172, 172), rng=None, aux=True)
>>> print('anns = {}'.format(ub.repr2(anns, nl=1)))
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(img['imdata'], pnum=(1, 2, 1), fnum=1)
>>> auxdata = img['auxiliary'][0]['imdata']
>>> kwplot.imshow(auxdata, pnum=(1, 2, 2), fnum=1)
>>> kwplot.show_if_requested()
```

Example

```
>>> # xdoctest: +REQUIRES(--show)
>>> img, anns = demodata_toy_img(image_size=(172, 172), rng=None, aux=True)
>>> print('anns = {}'.format(ub.repr2(anns, nl=1)))
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(img['imdata'], pnum=(1, 2, 1), fnum=1)
>>> auxdata = img['auxiliary'][0]['imdata']
>>> kwplot.imshow(auxdata, pnum=(1, 2, 2), fnum=1)
>>> kwplot.show_if_requested()
```

kwcoco.demo.toydata_video

Generates “toydata” for demo and testing purposes.

This is the video version of the toydata generator and should be preferred to the loose image version in toydata_image.

Module Contents

Functions

<code>random_video_dset(num_videos=1, num_frames=2, num_tracks=2, anchors=None, image_size=(600, 600), verbose=3, render=False, aux=None, multispectral=False, multisensor=False, rng=None, dpath=None, max_speed=0.01, channels=None, **kwargs)</code>	Create a toy Coco Video Dataset
<code>random_single_video_dset(image_size=(600, 600), num_frames=5, num_tracks=3, tid_start=1, gid_start=1, video_id=1, anchors=None, rng=None, render=False, dpath=None, autobuild=True, verbose=3, aux=None, multispectral=False, max_speed=0.01, channels=None, multisensor=False, **kwargs)</code>	Create the video scene layout of object positions.
<code>_draw_video_sequence(dset, gids)</code>	Helper to draw a multi-sensor sequence
<code>render_toy_dataset(dset, rng, dpath=None, renderkw=None, verbose=0)</code>	Create toydata_video renderings for a preconstructed coco dataset.
<code>render_toy_image(dset, gid, rng=None, renderkw=None)</code>	Modifies dataset inplace, rendering synthetic annotations.
<code>render_foreground(imdata, chan_to_auxinfo, dset, annots, catpats, with_sseg, with_kpts, dims, newstyle, gray, rng)</code>	Renders demo annotations on top of a demo background
<code>render_background(img, rng, gray, bg_intensity, bg_scale)</code>	
<code>false_color(twochan)</code>	TODO: the function ensure_false_color will eventually be ported to kwimage
<code>random_multi_object_path(num_objects, num_frames, rng=None, max_speed=0.01)</code>	
<code>random_path(num, degree=1, dimension=2, rng=None, mode='boid')</code>	Create a random path using a somem ethod curve.

Attributes

`profile`

`TOYDATA_VIDEO_VERSION`

`kwcoco.demo.toydata_video.profile`

`kwcoco.demo.toydata_video.TOYDATA_VIDEO_VERSION = 21`

```
kwcoco.demo.toydata_video.random_video_dset(num_videos=1, num_frames=2, num_tracks=2,
                                             anchors=None, image_size=(600, 600), verbose=3,
                                             render=False, aux=None, multispectral=False,
                                             multisensor=False, rng=None, dpath=None,
                                             max_speed=0.01, channels=None, **kwargs)
```

Create a toy Coco Video Dataset

Parameters

- **num_videos** (*int*) – number of videos
- **num_frames** (*int*) – number of images per video
- **num_tracks** (*int*) – number of tracks per video
- **image_size** (*Tuple[int, int]*) – The width and height of the generated images
- **render** (*bool | dict*) – if truthy the toy annotations are synthetically rendered. See [render_toy_image\(\)](#) for details.
- **rng** (*int | None | RandomState*) – random seed / state
- **dpath** (*str*) – only used if render is truthy, place to write rendered images.
- **verbose** (*int, default=3*) – verbosity mode
- **aux** (*bool*) – if True generates dummy auxiliary channels
- **multispectral** (*bool*) – similar to aux, but does not have the concept of a “main” image.
- **max_speed** (*float*) – max speed of movers
- **channels** (*str*) – experimental new way to get MSI with specific band distributions.
- ****kwargs** – used for old backwards compatible argument names gsize - alias for image_size

SeeAlso: [random_single_video_dset](#)

Example

```
>>> from kwCOCO.demo.toydata_video import * # NOQA
>>> dset = random_video_dset(render=True, num_videos=3, num_frames=2,
                               num_tracks=5, image_size=(128, 128))
>>> # xdoctest: +REQUIRES(--show)
>>> dset.show_image(1, doclf=True)
>>> dset.show_image(2, doclf=True)
```

```
>>> from kwCOCO.demo.toydata_video import * # NOQA
dset = random_video_dset(render=False, num_videos=3, num_frames=2,
                         num_tracks=10)
dset._tree()
dset.imgs[1]
```

```
dset = random_single_video_dset() dset._tree() dset.imgs[1]
```

```
from kwCOCO.demo.toydata_video import * # NOQA dset = random_video_dset(render=True, num_videos=3,
                           num_frames=2,
                           num_tracks=10)
```

```

print(dset.imgs[1]) print('dset.bundle_dpath = {!r}'.format(dset.bundle_dpath)) dset._tree()
import xdev globals().update(xdev.get_func_kwargs(random_video_dset)) num_videos = 2
kwcoco.demo.toydata_video.random_single_video_dset(image_size=(600, 600), num_frames=5,
                                                    num_tracks=3, tid_start=1, gid_start=1,
                                                    video_id=1, anchors=None, rng=None,
                                                    render=False, dpath=None, autobuild=True,
                                                    verbose=3, aux=None, multispectral=False,
                                                    max_speed=0.01, channels=None,
                                                    multisensor=False, **kwargs)

```

Create the video scene layout of object positions.

Note: Does not render the data unless specified.

Parameters

- **image_size** (*Tuple[int, int]*) – size of the images
- **num_frames** (*int*) – number of frames in this video
- **num_tracks** (*int*) – number of tracks in this video
- **tid_start** (*int, default=1*) – track-id start index
- **gid_start** (*int, default=1*) – image-id start index
- **video_id** (*int, default=1*) – video-id of this video
- **anchors** (*ndarray | None*) – base anchor sizes of the object boxes we will generate.
- **rng** (*RandomState*) – random state / seed
- **render** (*bool | dict*) – if truthy, does the rendering according to provided params in the case of dict input.
- **autobuild** (*bool, default=True*) – prebuild coco lookup indexes
- **verbose** (*int*) – verbosity level
- **aux** (*bool | List[str]*) – if specified generates auxiliary channels
- **multispectral** (*bool*) – if specified simulates multispectral imagery This is similar to aux, but has no “main” file.
- **max_speed** (*float*) – max speed of movers
- **channels** (*str | None | ChannelSpec*) – if specified generates multispectral images with dummy channels
- **multisensor** (*bool*) –

if True, generates demodata from “multiple sensors”, in other words, observations may have different “bands”.
- ****kwargs** – used for old backwards compatible argument names gsize - alias for image_size

Todo:

- [] Need maximum allowed object overlap measure
- [] Need better parameterized path generation

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> anchors = np.array([ [0.3, 0.3], [0.1, 0.1]] )
>>> dset = random_single_video_dset(render=True, num_frames=10, num_tracks=10, ↴
    ↪anchors=anchors, max_speed=0.2)
>>> # xdoctest: +REQUIRES(--show)
>>> # Show the tracks in a single image
>>> import kwplot
>>> kwplot.autompl()
>>> annots = dset.annots()
>>> tids = annots.lookup('track_id')
>>> tid_to_aids = ub.group_items(annots.aids, tids)
>>> paths = []
>>> track_boxes = []
>>> for tid, aids in tid_to_aids.items():
>>>     boxes = dset.annots(aids).boxes.to_cxywh()
>>>     path = boxes.data[:, 0:2]
>>>     paths.append(path)
>>>     track_boxes.append(boxes)
>>> import kwplot
>>> plt = kwplot.autopl()
>>> ax = plt.gca()
>>> ax.cla()
>>> #
>>> import kwimage
>>> colors = kwimage.Color.distinct(len(track_boxes))
>>> for i, boxes in enumerate(track_boxes):
>>>     color = colors[i]
>>>     path = boxes.data[:, 0:2]
>>>     boxes.draw(color=color, centers={'radius': 0.01}, alpha=0.5)
>>>     ax.plot(path.T[0], path.T[1], 'x-', color=color)
```

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> anchors = np.array([ [0.2, 0.2], [0.1, 0.1]] )
>>> gsize = np.array([(600, 600)])
>>> print(anchors * gsize)
>>> dset = random_single_video_dset(render=True, num_frames=10,
>>>                                 anchors=anchors, num_tracks=10,
>>>                                 image_size='random')
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> plt = kwplot.autopl()
>>> plt.clf()
>>> gids = list(dset.imgs.keys())
>>> pnums = kwplot.PlotNums(nSubplots=len(gids))
>>> for gid in gids:
```

(continues on next page)

(continued from previous page)

```
>>>     dset.show_image(gid, pnum=pnums(), fnum=1, title=False)
>>> pnums = kwplot.PlotNums(nSubplots=len(gids))
```

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> dset = random_single_video_dset(num_frames=10, num_tracks=10, aux=True)
>>> assert 'auxiliary' in dset.imgs[1]
>>> assert dset.imgs[1]['auxiliary'][0]['channels']
>>> assert dset.imgs[1]['auxiliary'][1]['channels']
```

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> multispectral = True
>>> dset = random_single_video_dset(num_frames=1, num_tracks=1, multispectral=True)
>>> dset._check_json_serializable()
>>> dset.dataset['images']
>>> assert dset.imgs[1]['auxiliary'][1]['channels']
>>> # test that we can render
>>> render_toy_dataset(dset, rng=0, dpath=None, renderkw={})
```

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> dset = random_single_video_dset(num_frames=4, num_tracks=1, multispectral=True, ↴
    ↪multisensor=True, image_size='random', rng=2338)
>>> dset._check_json_serializable()
>>> assert dset.imgs[1]['auxiliary'][1]['channels']
>>> # Print before and after render
>>> #print('multisensor-images = {}'.format(ub.repr2(dset.dataset['images'], nl=-2)))
>>> #print('multisensor-images = {}'.format(ub.repr2(dset.dataset, nl=-2)))
>>> print(ub.hash_data(dset.dataset))
>>> # test that we can render
>>> render_toy_dataset(dset, rng=0, dpath=None, renderkw={})
>>> #print('multisensor-images = {}'.format(ub.repr2(dset.dataset['images'], nl=-2)))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> from kwcoco.demo.toydata_video import _draw_video_sequence # NOQA
>>> gids = [1, 2, 3, 4]
>>> final = _draw_video_sequence(dset, gids)
>>> print('dset.fpath = {!r}'.format(dset.fpath))
>>> kwplot.imshow(final)
```

`kwcoco.demo.toydata_video._draw_video_sequence(dset, gids)`

Helper to draw a multi-sensor sequence

`kwcoco.demo.toydata_video.render_toy_dataset(dset, rng, dpath=None, renderkw=None, verbose=0)`

Create toydata_video renderings for a preconstructed coco dataset.

Parameters

- **dset** (*CocoDataset*) – A dataset that contains special “renderable” annotations. (e.g. the demo shapes). Each image can contain special fields that influence how an image will be rendered.
Currently this process is simple, it just creates a noisy image with the shapes superimposed over where they should exist as indicated by the annotations. In the future this may become more sophisticated.
Each item in *dset.dataset[‘images’]* will be modified to add the “file_name” field indicating where the rendered data is written.
- **rng** (*int | None | RandomState*) – random state
- **dpath** (*str*) – The location to write the images to. If unspecified, it is written to the rendered folder inside the kwcoco cache directory.
- **renderkw** (*dict*) – See [render_toy_image\(\)](#) for details. Also takes imwrite keywords args only handled in this function. TODO better docs.

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> import kwarray
>>> rng = None
>>> rng = kwarray.ensure_rng(rng)
>>> num_tracks = 3
>>> dset = random_video_dset(rng=rng, num_videos=3, num_frames=5,
>>>                         num_tracks=num_tracks, image_size=(128, 128))
>>> dset = render_toy_dataset(dset, rng)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> plt = kwplot.autoplt()
>>> plt.clf()
>>> gids = list(dset.imgs.keys())
>>> pnums = kwplot.PlotNums(nSubplots=len(gids), nRows=num_tracks)
>>> for gid in gids:
>>>     dset.show_image(gid, pnum=pnums(), fnum=1, title=False)
>>> pnums = kwplot.PlotNums(nSubplots=len(gids))
```

`kwcoco.demo.toydata_video.render_toy_image(dset, gid, rng=None, renderkw=None)`

Modifies dataset inplace, rendering synthetic annotations.

This does not write to disk. Instead this writes to placeholder values in the image dictionary.

Parameters

- **dset** (*CocoDataset*) – coco dataset with renderable annotations / images
- **gid** (*int*) – image to render
- **rng** (*int | None | RandomState*) – random state
- **renderkw** (*dict*) – rendering config gray (bool): gray or color images fg_scale (float): foreground noisiness (gauss std) bg_scale (float): background noisiness (gauss std) fg_intensity

(float): foreground brightness (gauss mean) bg_intensity (float): background brightness (gauss mean) newstyle (bool): use new kwcoco datastructure formats with_kpts (bool): include keypoint info with_sseg (bool): include segmentation info

Returns the inplace-modified image dictionary

Return type Dict

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> image_size=(600, 600)
>>> num_frames=5
>>> verbose=3
>>> rng = None
>>> import karray
>>> rng = karray.ensure_rng(rng)
>>> aux = 'mx'
>>> dset = random_single_video_dset(
>>>     image_size=image_size, num_frames=num_frames, verbose=verbose, aux=aux, ↴
>>>     rng=rng)
>>> print('dset.dataset = {}'.format(ub.repr2(dset.dataset, nl=2)))
>>> gid = 1
>>> renderkw = {}
>>> render_toy_image(dset, gid, rng, renderkw=renderkw)
>>> img = dset.imgs[gid]
>>> canvas = img['imdata']
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(canvas, doclf=True, pnum=(1, 2, 1))
>>> dets = dset.annots(gid=gid).detections
>>> dets.draw()
```

```
>>> auxdata = img['auxiliary'][0]['imdata']
>>> aux_canvas = false_color(auxdata)
>>> kwplot.imshow(aux_canvas, pnum=(1, 2, 2))
>>> _ = dets.draw()
```

```
>>> # xdoctest: +REQUIRES(--show)
>>> img, anns = demodata_toy_img(image_size=(172, 172), rng=None, aux=True)
>>> print('anns = {}'.format(ub.repr2(anns, nl=1)))
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(img['imdata'], pnum=(1, 2, 1), fnum=1)
>>> auxdata = img['auxiliary'][0]['imdata']
>>> kwplot.imshow(auxdata, pnum=(1, 2, 2), fnum=1)
>>> kwplot.show_if_requested()
```

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> multispectral = True
>>> dset = random_single_video_dset(num_frames=1, num_tracks=1, multispectral=True)
>>> gid = 1
>>> dset.imgs[gid]
>>> rng = kwarray.ensure_rng(0)
>>> renderkw = {'with_sseg': True}
>>> img = render_toy_image(dset, gid, rng=rng, renderkw=renderkw)
```

`kwcoco.demo.toydata_video.render_foreground(imdata, chan_to_auxinfo, dset, annots, catpats, with_sseg, with_kpts, dims, newstyle, gray, rng)`

Renders demo annotations on top of a demo background

`kwcoco.demo.toydata_video.render_background(img, rng, gray, bg_intensity, bg_scale)`

`kwcoco.demo.toydata_video.false_color(twochan)`

TODO: the function ensure_false_color will eventually be ported to kwimage use that instead.

`kwcoco.demo.toydata_video.random_multi_object_path(num_objects, num_frames, rng=None, max_speed=0.01)`

`kwcoco.demo.toydata_video.random_path(num, degree=1, dimension=2, rng=None, mode='boid')`

Create a random path using a somem ethod curve.

Parameters

- `num (int)` – number of points in the path
- `degree (int, default=1)` – degree of curvieness of the path
- `dimension (int, default=2)` – number of spatial dimensions
- `mode (str)` – can be boid, walk, or bezier
- `rng (RandomState, default=None)` – seed

References

<https://github.com/dhermes/bezier>

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> num = 10
>>> dimension = 2
>>> degree = 3
>>> rng = None
>>> path = random_path(num, degree, dimension, rng, mode='boid')
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> plt = kwplot.autoplt()
>>> kwplot.multi_plot(xdata=path[:, 0], ydata=path[:, 1], fnum=1, doclf=1, xlim=(0, -1), ylim=(0, 1))
>>> kwplot.show_if_requested()
```

Example

```
>>> # xdoctest: +REQUIRES(--3d)
>>> # xdoctest: +REQUIRES(module:bezier)
>>> import kwarray
>>> import kwplot
>>> plt = kwplot.autoplt()
>>> #
>>> num= num_frames = 100
>>> rng = kwarray.ensure_rng(0)
>>> #
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> paths = []
>>> paths.append(random_path(num, degree=3, dimension=3, mode='bezier'))
>>> paths.append(random_path(num, degree=2, dimension=3, mode='bezier'))
>>> paths.append(random_path(num, degree=4, dimension=3, mode='bezier'))
>>> #
>>> from mpl_toolkits.mplot3d import Axes3D # NOQA
>>> ax = plt.gca(projection='3d')
>>> ax.cla()
>>> #
>>> for path in paths:
>>>     time = np.arange(len(path))
>>>     ax.plot(time, path.T[0] * 1, path.T[1] * 1, 'o-')
>>> ax.set_xlim(0, num_frames)
>>> ax.set_ylim(-.01, 1.01)
>>> ax.set_zlim(-.01, 1.01)
>>> ax.set_xlabel('x')
>>> ax.set_ylabel('y')
>>> ax.set_zlabel('z')
```

kwcoco.demo.toypatterns

Module Contents

Classes

CategoryPatterns

Example

Rasters

Functions

<code>star(a, dtype=np.uint8)</code>	Generates a star shaped structuring element.
--------------------------------------	--

Attributes

<code>profile</code>

```
kwcoco.demo.toypatterns.profile  
class kwcoco.demo.toypatterns.CategoryPatterns(categories=None, fg_scale=0.5, fg_intensity=0.9,  
                                                rng=None)  
Bases: object
```

Example

```
>>> from kwcoco.demo.toypatterns import * # NOQA  
>>> self = CategoryPatterns.coerce()  
>>> chip = np.zeros((100, 100, 3))  
>>> offset = (20, 10)  
>>> dims = (160, 140)  
>>> info = self.random_category(chip, offset, dims)  
>>> print('info = {}'.format(ub.repr2(info, nl=1)))  
>>> # xdoctest: +REQUIRES(--show)  
>>> import kwplot  
>>> kwplot.autopl()  
>>> kwplot.imshow(info['data'], pnum=(1, 2, 1), fnum=1, title='chip-space')  
>>> kpts = kwimage.Points._from_coco(info['keypoints'])  
>>> kpts.translate(-np.array(offset)).draw(radius=3)  
>>> #####  
>>> mask = kwimage.Mask.coerce(info['segmentation'])  
>>> kwplot.imshow(mask.to_c_mask().data, pnum=(1, 2, 2), fnum=1, title='img-space')  
>>> kpts.draw(radius=3)  
>>> kwplot.show_if_requested()
```

```
_default_categories  
_default_keypoint_categories  
_default_catnames = ['star', 'eff', 'superstar']  
classmethod coerce(CategoryPatterns, data=None, **kwargs)
```

Construct category patterns from either defaults or only with specific categories. Can accept either an existig category pattern object, a list of known catnames, or mscoco category dictionaries.

Example

```
>>> data = ['superstar']
>>> self = CategoryPatterns.coerce(data)

__len__(self)
__getitem__(self, index)
__iter__(self)
index(self, name)
get(self, index, default=ub.NoParam)
random_category(self, chip, xy_offset=None, dims=None, newstyle=True, size=None)
```

Example

```
>>> from kwcoco.demo.toypatterns import * # NOQA
>>> self = CategoryPatterns.coerce(['superstar'])
>>> chip = np.random.rand(64, 64)
>>> info = self.random_category(chip)

render_category(self, cname, chip, xy_offset=None, dims=None, newstyle=True, size=None)
```

Example

```
>>> from kwcoco.demo.toypatterns import * # NOQA
>>> self = CategoryPatterns.coerce(['superstar'])
>>> chip = np.random.rand(64, 64)
>>> info = self.render_category('superstar', chip, newstyle=True)
>>> print('info = {}'.format(ub.repr2(info, nl=-1)))
>>> info = self.render_category('superstar', chip, newstyle=False)
>>> print('info = {}'.format(ub.repr2(info, nl=-1)))
```

Example

```
>>> from kwcoco.demo.toypatterns import * # NOQA
>>> self = CategoryPatterns.coerce(['superstar'])
>>> chip = None
>>> dims = (64, 64)
>>> info = self.render_category('superstar', chip, newstyle=True, dims=dims, size=dims)
>>> print('info = {}'.format(ub.repr2(info, nl=-1)))
```

`_todo_refactor_geometric_info(self, cname, xy_offset, dims)`

This function is used to populate kpts and sseg information in the autogenerated coco dataset before rendering. It is redundant with other functionality.

TODO: rectify with `_from_elem`

Example

```
>>> self = CategoryPatterns.coerce(['superstar'])
>>> dims = (64, 64)
>>> cname = 'superstar'
>>> xy_offset = None
>>> self._todo_refactor_geometric_info(cname, xy_offset, dims)
```

```
_package_info(self, cname, data, mask, kpts, xy_offset, dims, newstyle)
```

packages data from _from_elem into coco-like annotation

```
_from_elem(self, cname, chip, size=None)
```

Example

```
>>> # hack to allow chip to be None
>>> chip = None
>>> size = (32, 32)
>>> cname = 'superstar'
>>> self = CategoryPatterns.coerce()
>>> self._from_elem(cname, chip, size)
```

`kwcoco.demo.toypatterns.star(a, dtype=np.uint8)`

Generates a star shaped structuring element.

Much faster than skimage.morphology version

```
class kwcoco.demo.toypatterns.Rasters
    static superstar()
        test data patch

    static eff()
        test data patch
```

2.2.4 kwcoco.examples

Submodules

`kwcoco.examples.bench_large_hyperspectral`

Module Contents

Functions

```
benchmark_large_hyperspectral()
```

`kwcoco.examples.bench_large_hyperspectral.benchmark_large_hyperspectral()`

`kwcoco.examples.draw_gt_and_predicted_boxes`**Module Contents****Functions**

<code>draw_true_and_pred_boxes(true_fpath, pred_fpath, gid, viz_fpath)</code>	How do you generally visualize gt and predicted bound- ing boxes together?
---	---

`kwcoco.examples.draw_gt_and_predicted_boxes.draw_true_and_pred_boxes(true_fpath, pred_fpath,
gid, viz_fpath)`

How do you generally visualize gt and predicted bounding boxes together?

Example

```
>>> import kwcoco
>>> import ubelt as ub
>>> from os.path import join
>>> from kwcoco.demo.perterb import perterb_coco
>>> # Create a working directory
>>> dpath = ub.ensure_app_cache_dir('kwcoco/examples/draw_true_and_pred_boxes')
>>> # Lets setup some dummy true data
>>> true_dset = kwcoco.CocoDataset.demo('shapes2')
>>> true_dset.fpath = join(dpath, 'true_dset.kwcoco.json')
>>> true_dset.dump(true_dset.fpath, newlines=True)
>>> # Lets setup some dummy predicted data
>>> pred_dset = perterb_coco(true_dset, box_noise=100, rng=421)
>>> pred_dset.fpath = join(dpath, 'pred_dset.kwcoco.json')
>>> pred_dset.dump(pred_dset.fpath, newlines=True)
>>> #
>>> # We now have our true and predicted data, lets visualize
>>> true_fpath = true_dset.fpath
>>> pred_fpath = pred_dset.fpath
>>> print('dpath = {!r}'.format(dpath))
>>> print('true_fpath = {!r}'.format(true_fpath))
>>> print('pred_fpath = {!r}'.format(pred_fpath))
>>> # Lets choose an image id to visualize and a path to write to
>>> gid = 1
>>> viz_fpath = join(dpath, 'viz_{}.jpg'.format(gid))
>>> # The answer to the question is in the logic of this function
>>> draw_true_and_pred_boxes(true_fpath, pred_fpath, gid, viz_fpath)
```

kwcoco.examples.faq

These are answers to the questions: How do I?

Module Contents

Functions

`get_images_with_videoid()`

Q: How would you recommend querying a kwcoco file to get all of the images

`kwcoco.examples.faq.get_images_with_videoid()`

Q: How would you recommend querying a kwcoco file to get all of the images associated with a video id?

kwcoco.examples.getting_started_existing_dataset

Module Contents

Functions

`getting_started_existing_dataset()`

If you want to start using the Python API. Just open IPython and try:

`the_core_dataset_backend()`

`demo_vectorize_interface()`

>>> import kwcoco

`kwcoco.examples.getting_started_existing_dataset.getting_started_existing_dataset()`

If you want to start using the Python API. Just open IPython and try:

`kwcoco.examples.getting_started_existing_dataset.the_core_dataset_backend()`

`kwcoco.examples.getting_started_existing_dataset.demo_vectorize_interface()`

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes2')
>>> #
>>> aids = [1, 2, 3, 4]
>>> annots = dset.annots(aids)
...
>>> print('annots = {!r}'.format(annots))
annots = <Annots(num=4) at ...>
```

```
>>> annots.lookup('bbox')
[[346.5, 335.2, 33.2, 99.4],
 [344.5, 327.7, 48.8, 111.1],
 [548.0, 154.4, 57.2, 62.1],
 [548.7, 151.0, 59.4, 80.5]]
```

```
>>> gids = annots.lookup('image_id')
>>> print('gids = {!r}'.format(gids))
gids = [1, 2, 1, 2]
```

```
>>> images = dset.images(gids)
>>> list(zip(images.lookup('width'), images.lookup('height')))
[(600, 600), (600, 600), (600, 600), (600, 600)]
```

kwcoco.examples.loading_multispectral_data

Module Contents

Functions

`demo_load_msi_data()`

kwcoco.examples.loading_multispectral_data.`demo_load_msi_data()`

kwcoco.examples.modification_example

Module Contents

Functions

<code>dataset_modification_example_via_copy()</code>	Say you are given a dataset as input and you need to add your own
<code>dataset_modification_example_via_construction()</code>	Alternatively you can make a new dataset and copy over categories / images

kwcoco.examples.modification_example.`dataset_modification_example_via_copy()`

Say you are given a dataset as input and you need to add your own annotation “predictions” to it. You could copy the existing dataset, remove all the annotations, and then add your new annotations.

kwcoco.examples.modification_example.`dataset_modification_example_via_construction()`

Alternatively you can make a new dataset and copy over categories / images as needed

kwcoco.examples.simple_kwCOCO_torch_dataset

This example demonstrates how to use kwCOCO to write a very simple torch dataset. This assumes the dataset will be single-image RGB inputs. This file is intended to talk the reader through what we are doing and why.

This example aims for clarity over being concise. There are APIs exposed by kwCOCO (and its sister module ndsampler) that can perform the same tasks more efficiently and with fewer lines of code.

If you run the doctest, it will produce a visualization that shows the images with boxes drawn on it, running it multiple times will let you see the augmentations. This can be done with the following command:

```
xdoctest -m kwcoco.examples.simple_kwcoco_torch_dataset KW CocoSimpleTorchDataset --show  
Or just copy the doctest into IPython and run it.
```

Module Contents

Classes

<code>KWCocoSimpleTorchDataset</code>	A simple torch dataloader where each image is considered a single item.
---------------------------------------	---

Attributes

<code>DatasetBase</code>

```
kwcoco.examples.simple_kwcoco_torch_dataset.DatasetBase  
class kwcoco.examples.simple_kwcoco_torch_dataset.KWCocoSimpleTorchDataset(coco_dset,  
                           input_dims=None,  
                           antialias=False,  
                           rng=None)
```

Bases: `DatasetBase`

A simple torch dataloader where each image is considered a single item.

Parameters

- **coco_dset** (`kwcoco.CocoDataset` | `str`) – something coercable to a kwcoco dataset, this could either be a `kwcoco.CocoDataset` object, a path to a kwcoco manifest on disk, or a special toydata code. See `kwcoco.CocoDataset.coerce()` for more details.
- **input_dims** (`Tuple[int, int]`) – These are the (height, width) dimensions that the image will be resized to.
- **antialias** (`bool, default=False`) – If true, we will antialias before downsampling.
- **rng** (`RandomState` | `int` | `None`) – an existing random number generator or a random seed to produce deterministic augmentations.

Example

```
>>> # xdoctest: +REQUIRES(module:torch)
>>> from kwcoco.examples.simple_kwcoco_torch_dataset import * # NOQA
>>> import kwcoco
>>> coco_dset = kwcoco.CocoDataset.demo('shapes8')
>>> input_dims = (384, 384)
>>> self = torch_dset = KWCocoSimpleTorchDataset(coco_dset, input_dims=input_dims)
>>> index = len(self) // 2
>>> item = self[index]
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
```

(continues on next page)

(continued from previous page)

```
>>> kwplot.figure(doclf=True, fnum=1)
>>> kwplot.autompl()
>>> canvas = item['inputs']['rgb'].numpy().transpose(1, 2, 0)
>>> # Construct kwimage objects for batch item visualization
>>> dets = kwimage.Detections(
>>>     boxes=kwimage.Boxes(item['labels']['cxywh'], 'cxywh'),
>>>     class_idxs=item['labels']['class_idxs'],
>>>     classes=self.classes,
>>> ).numpy()
>>> # Overlay annotations on the image
>>> canvas = dets.draw_on(canvas)
>>> kwplot.imshow(canvas)
>>> kwplot.show_if_requested()
```

__len__(self)

Return the number of items in the Dataset

__getitem__(self, index)

Construct a batch item to be used in training

`kwcoco.examples.vectorized_interface`**Module Contents****Functions****`demo_vectorized_interface()`**

This demonstrates how to use the kwcoco vectorized interface for images /

`kwcoco.examples.vectorized_interface.demo_vectorized_interface()`

This demonstrates how to use the kwcoco vectorized interface for images / categories / annotations.

2.2.5 `kwcoco.metrics`

mkinit kwcoco.metrics -w --relative

Submodules**`kwcoco.metrics.assignment`**

when deciding whether to go up or down in the tree.

[] medschool applications true-pred matching (applicant proposing) fast algorithm.

[] Maybe looping over truth rather than pred is faster? but it makes you have to combine pred score / ious, which is weird.

2.2. Subpackages

[x] preallocate ndarray and use hstack to build confusion vectors?

doesn't help

[] relevant classes / classes / classes-of-interest we care about needs

to be a first class member of detection metrics.

[] Add parameter that allows one prediction to “match” to more than one

truth object. (example: we have a duck detector problem and all the ducks in a row are annotated as separate object, and we only care about getting the group):

Module Contents

Functions

<code>_assign_confusion_vectors(true_dets, pred_dets, bg_weight=1.0, iou_thresh=0.5, bg_cidx=-1, bias=0.0, classes=None, compat='all', prioritize='iou', ignore_classes='ignore', max_dets=None)</code>	Create confusion vectors for detections by assigning to ground true boxes
<code>_critical_loop(true_dets, pred_dets, iou_lookup, is_valid_lookup, cx_to_matchable_txs, bg_weight, prioritize, iou_thresh_, pdist_priority, cx_to_ancestors, bg_cidx, ignore_classes, max_dets)</code>	
<code>_fast_pdist_priority(classes, prioritize, _cache={})</code>	Custom priority computation. Needs some vetting.
<code>_filter_ignore_regions(true_dets, pred_dets, ioaa_thresh=0.5, ignore_classes='ignore')</code>	Determine which true and predicted detections should be ignored.

Attributes

`USE_NEG_INF`

`kwcoco.metrics.assignment.USE_NEG_INF = True`

`kwcoco.metrics.assignment._assign_confusion_vectors(true_dets, pred_dets, bg_weight=1.0, iou_thresh=0.5, bg_cidx=-1, bias=0.0, classes=None, compat='all', prioritize='iou', ignore_classes='ignore', max_dets=None)`

Create confusion vectors for detections by assigning to ground true boxes

Given predictions and truth for an image return (`y_pred`, `y_true`, `y_score`), which is suitable for sklearn classification metrics

Parameters

- **true_dets** (*Detections*) – groundtruth with boxes, classes, and weights
- **pred_dets** (*Detections*) – predictions with boxes, classes, and scores
- **iou_thresh** (*float, default=0.5*) – bounding box overlap iou threshold required for assignment

- **bias** (*float, default=0.0*) – for computing bounding box overlap, either 1 or 0
- **gids** (*List[int], default=None*) – which subset of images ids to compute confusion metrics on. If not specified all images are used.
- **compat** (*str, default='all'*) – can be ('ancestors' | 'mutex' | 'all'). determines which pred boxes are allowed to match which true boxes. If 'mutex', then pred boxes can only match true boxes of the same class. If 'ancestors', then pred boxes can match true boxes that match or have a coarser label. If 'all', then any pred can match any true, regardless of its category label.
- **prioritize** (*str, default='iou'*) – can be ('iou' | 'class' | 'correct') determines which box to assign to if mutiple true boxes overlap a predicted box. if prioritize is iou, then the true box with maximum iou (above iou_thresh) will be chosen. If prioritize is class, then it will prefer matching a compatible class above a higher iou. If prioritize is correct, then ancestors of the true class are preferred over descendants of the true class, over unrelated classes.
- **bg_cidx** (*int, default=-1*) – The index of the background class. The index used in the truth column when a predicted bounding box does not match any true bounding box.
- **classes** (*List[str] | kwcoco.CategoryTree*) – mapping from class indices to class names. Can also contain class heirarchy information.
- **ignore_classes** (*str | List[str]*) – class name(s) indicating ignore regions
- **max_dets** (*int*) – maximum number of detections to consider

Todo:

- [] This is a bottleneck function. An implementation in C / C++ / Cython would likely improve the overall system.
- [] **Implement crowd truth. Allow multiple predictions to match any** truth objet marked as "iscrowd".

Returns

with relevant confusion vectors. This keys of this dict can be interpreted as columns of a data frame. The *txs* / *pxs* columns represent the indexes of the true / predicted annotations that were assigned as matching. Additionally each row also contains the true and predicted class index, the predicted score, the true weight and the iou of the true and predicted boxes. A *txs* value of -1 means that the predicted box was not assigned to a true annotation and a *pxs* value of -1 means that the true annotation was not assigne to any predicted annotation.

Return type dict

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> import pandas as pd
>>> import kwimage
>>> # Given a raw numpy representation construct Detection wrappers
>>> true_dets = kwimage.Detections(
>>>     boxes=kwimage.Boxes(np.array([
>>>         [ 0,  0, 10, 10], [10,  0, 20, 10],
>>>         [10,  0, 20, 10], [20,  0, 30, 10]]), 'tlbr'),
>>>     weights=np.array([1, 0, .9, 1]),
```

(continues on next page)

(continued from previous page)

```
>>> class_idxs=np.array([0, 0, 1, 2])
>>> pred_dets = kwimage.Detections(
>>>     boxes=kwimage.Boxes(np.array([
>>>         [6, 2, 20, 10], [3, 2, 9, 7],
>>>         [3, 9, 9, 7], [3, 2, 9, 7],
>>>         [2, 6, 7, 7], [20, 0, 30, 10]]), 'tlbr'),
>>>     scores=np.array([.5, .5, .5, .5, .5]),
>>>     class_idxs=np.array([0, 0, 1, 2, 0, 1]))
>>> bg_weight = 1.0
>>> compat = 'all'
>>> iou_thresh = 0.5
>>> bias = 0.0
>>> import kwcoco
>>> classes = kwcoco.CategoryTree.from_mutex(list(range(3)))
>>> bg_cidx = -1
>>> y = _assign_confusion_vectors(true_dets, pred_dets, bias=bias,
>>>                                bg_weight=bg_weight, iou_thresh=iou_thresh,
>>>                                compat=compat)
>>> y = pd.DataFrame(y)
>>> print(y) # xdoc: +IGNORE_WANT
   pred  true  score  weight      iou    txs    pxs
0     1     2  0.5000  1.0000  1.0000     3     5
1     0    -1  0.5000  1.0000 -1.0000    -1     4
2     2    -1  0.5000  1.0000 -1.0000    -1     3
3     1    -1  0.5000  1.0000 -1.0000    -1     2
4     0    -1  0.5000  1.0000 -1.0000    -1     1
5     0     0  0.5000  0.0000  0.6061     1     0
6    -1     0  0.0000  1.0000 -1.0000     0    -1
7    -1     1  0.0000  0.9000 -1.0000     2    -1
```

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> import pandas as pd
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(nimgs=1, nclasses=8,
>>>                             nboxes=(0, 20), n_fp=20,
>>>                             box_noise=.2, cls_noise=.3)
>>> classes = dmet.classes
>>> gid = 0
>>> true_dets = dmet.true_detections(gid)
>>> pred_dets = dmet.pred_detections(gid)
>>> y = _assign_confusion_vectors(true_dets, pred_dets,
>>>                               classes=dmet.classes,
>>>                               compat='all', prioritize='class')
>>> y = pd.DataFrame(y)
>>> print(y) # xdoc: +IGNORE_WANT
>>> y = _assign_confusion_vectors(true_dets, pred_dets,
>>>                               classes=dmet.classes,
>>>                               compat='ancestors', iou_thresh=.5)
```

(continues on next page)

(continued from previous page)

```
>>> y = pd.DataFrame(y)
>>> print(y) # xdoc: +IGNORE_WANT
```

`kwcoco.metrics.assignment._critical_loop(true_dets, pred_dets, iou_lookup, isvalid_lookup,
cx_to_matchable_txs, bg_weight, prioritize, iou_thresh_,
pdist_priority, cx_to_ancestors, bg_cidx, ignore_classes,
max_dets)`

`kwcoco.metrics.assignment._fast_pdist_priority(classes, prioritize, _cache={})`
Custom priority computation. Needs some vetting.

This is the priority used when deciding which prediction to assign to which truth.

Todo:

- [] Look at absolute difference in sibling entropy when deciding whether to go up or down in the tree.

`kwcoco.metrics.assignment._filter_ignore_regions(true_dets, pred_dets, ioaa_thresh=0.5,
ignore_classes='ignore')`

Determine which true and predicted detections should be ignored.

Parameters

- `true_dets` (*Detections*)
- `pred_dets` (*Detections*)
- `ioaa_thresh` (*float*) – intersection over other area thresh for ignoring a region.

Returns

flags indicating which **true** and **predicted** detections should be ignored.

Return type Tuple[ndarray, ndarray]

Example

```
>>> from kwcoco.metrics.assignment import * # NOQA
>>> from kwcoco.metrics.assignment import _filter_ignore_regions
>>> import kwimage
>>> pred_dets = kwimage.Detections.random(classes=['a', 'b', 'c'])
>>> true_dets = kwimage.Detections.random(
>>>     segmentations=True, classes=['a', 'b', 'c', 'ignore'])
>>> ignore_classes = {'ignore', 'b'}
>>> ioaa_thresh = 0.5
>>> print('true_dets = {!r}'.format(true_dets))
>>> print('pred_dets = {!r}'.format(pred_dets))
>>> flags1, flags2 = _filter_ignore_regions(
>>>     true_dets, pred_dets, ioaa_thresh=ioaa_thresh, ignore_classes=ignore_
>>> classes)
>>> print('flags1 = {!r}'.format(flags1))
>>> print('flags2 = {!r}'.format(flags2))
```

```
>>> flags3, flags4 = _filter_ignore_regions(
>>>     true_dets, pred_dets, ioaa_thresh=ioaa_thresh,
>>>     ignore_classes={c.upper() for c in ignore_classes})
>>> assert np.all(flags1 == flags3)
>>> assert np.all(flags2 == flags4)
```

kwcoco.metrics.clf_report

Module Contents

Functions

<code>classification_report(y_true, y_pred, target_names=None, sample_weight=None, verbose=False, remove_unsupported=False, log=None, ascii_only=False)</code>	Computes a classification report which is a collection of various metrics
<code>ovr_classification_report(mc_y_true, mc_probs, target_names=None, sample_weight=None, metrics=None, verbose=0, remove_unsupported=False, log=None)</code>	One-vs-rest classification report

Attributes

`ASCII_ONLY`

`kwcoco.metrics.clf_report.ASCII_ONLY`

```
kwcoco.metrics.clf_report.classification_report(y_true, y_pred, target_names=None,
                                                sample_weight=None, verbose=False,
                                                remove_unsupported=False, log=None,
                                                ascii_only=False)
```

Computes a classification report which is a collection of various metrics commonly used to evaluate classification quality. This can handle binary and multiclass settings.

Note that this function does not accept probabilities or scores and must instead act on final decisions. See `ovr_classification_report` for a probability based report function using a one-vs-rest strategy.

This emulates the `bm(cm)` Matlab script written by David Powers that is used for computing bookmaker, markedness, and various other scores.

References: <https://csem.flinders.edu.au/research/techreps/SIE07001.pdf> <https://www.mathworks.com/matlabcentral/fileexchange/5648-bm-cm-?requestedDomain=www.mathworks.com> Jurman, Riccadonna, Furlanello, (2012). A Comparison of MCC and CEN

Error Measures in MultiClass Prediction

Args: `y_true` (array): true labels for each item `y_pred` (array): predicted labels for each item `target_names` (List): mapping from label to category name `sample_weight` (ndarray): weight

for each item verbose (False): print if True log (callable): print or logging function remove_unsupported (bool, default=False): removes categories that have no support.

ascii_only (bool, default=False): if True dont use unicode characters. if the environ ASCII_ONLY is present this is forced to True and cannot be undone.

Example:

```
>>> # xdoctest: +IGNORE_WANT
>>> # xdoctest: +REQUIRES(module:sklearn)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> y_true = [1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 3, 3, 3, 3, 3, 3, 3, 3]
>>> y_pred = [1, 2, 1, 3, 1, 2, 2, 3, 2, 2, 3, 3, 2, 3, 3, 3, 1, 3]
>>> target_names = None
>>> sample_weight = None
>>> report = classification_report(y_true, y_pred, verbose=0, ascii_
->only=1)
>>> print(report['confusion'])
pred  1   2   3   r
real
1      3   1   1   5
2      0   4   1   5
3      1   1   6   8
p     4   6   8   18
>>> print(report['metrics'])
metric  precision  recall    fpr  markedness  bookmaker  mcc
->support
class
1          0.7500  0.6000  0.0769      0.6071      0.5231  0.5635
->5
2          0.6667  0.8000  0.1538      0.5833      0.6462  0.6139
->5
3          0.7500  0.7500  0.2000      0.5500      0.5500  0.5500
->8
combined    0.7269  0.7222  0.1530      0.5751      0.5761  0.5758
->18
```

Example:

```
>>> # xdoctest: +IGNORE_WANT
>>> # xdoctest: +REQUIRES(module:sklearn)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics.clf_report import *  # NOQA
>>> y_true = [1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 3, 3, 3, 3, 3, 3, 3, 3]
>>> y_pred = [1, 2, 1, 3, 1, 2, 2, 3, 2, 2, 3, 3, 2, 3, 3, 3, 1, 3]
>>> target_names = None
>>> sample_weight = None
>>> logs = []
>>> report = classification_report(y_true, y_pred, verbose=1, ascii_
->only=True, log=logs.append)
>>> print('
```

```
'join(logs))
```

Ignore:

```
>>> size = 100
>>> rng = np.random.RandomState(0)
>>> p_classes = np.array([.90, .05, .05][0:2])
>>> p_classes = p_classes / p_classes.sum()
>>> p_wrong = np.array([.03, .01, .02][0:2])
>>> y_true = testdata_ytrue(p_classes, p_wrong, size, rng)
>>> rs = []
>>> for x in range(17):
>>>     p_wrong += .05
>>>     y_pred = testdata_ypred(y_true, p_wrong, rng)
>>>     report = classification_report(y_true, y_pred, verbose='hack')
>>>     rs.append(report)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> import pandas as pd
>>> df = pd.DataFrame(rs).drop(['raw'], axis=1)
>>> delta = df.subtract(df['target'], axis=0)
>>> sqrd_error = np.sqrt((delta ** 2).sum(axis=0))
>>> print('Error')
>>> print(sqrd_error.sort_values())
>>> ys = df.to_dict(orient='list')
>>> kwplot.multi_plot(ydata_list=ys)
```

```
kwcococo.metrics.clf_report.ovr_classification_report(mc_y_true, mc_probs, target_names=None,
                                                       sample_weight=None, metrics=None,
                                                       verbose=0, remove_unsupported=False,
                                                       log=None)
```

One-vs-rest classification report

Parameters

- **mc_y_true** (*ndarray[int]*) – multiclass truth labels (integer label format). Shape [N].
- **mc_probs** (*ndarray*) – multiclass probabilities for each class. Shape [N x C].
- **target_names** (*Dict[int, str]*) – mapping from int label to string name
- **sample_weight** (*ndarray*) – weight for each item. Shape [N].
- **metrics** (*List[str]*) – names of metrics to compute

Example

```
>>> # xdoctest: +IGNORE_WANT
>>> # xdoctest: +REQUIRES(module:sklearn)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcococo.metrics.clf_report import * # NOQA
>>> y_true = [1, 1, 1, 1, 1, 2, 2, 2, 2, 0, 0, 0, 0, 0, 0, 0, 0]
>>> y_probs = np.random.rand(len(y_true), max(y_true) + 1)
>>> target_names = None
>>> sample_weight = None
```

(continues on next page)

(continued from previous page)

```
>>> verbose = True
>>> report = ovr_classification_report(y_true, y_probs)
>>> print(report['ave'])
auc      0.6541
ap       0.6824
kappa    0.0963
mcc      0.1002
brier    0.2214
dtype: float64
>>> print(report['ovr'])
     auc   ap  kappa   mcc  brier  support  weight
0 0.6062 0.6161 0.0526 0.0598 0.2608      8  0.4444
1 0.5846 0.6014 0.0000 0.0000 0.2195      5  0.2778
2 0.8000 0.8693 0.2623 0.2652 0.1602      5  0.2778
```

kwcococo.metrics.confusion_measures

Classes that store accumulated confusion measures (usually derived from confusion vectors).

For each chosen threshold value:

- thresholds[i] - the i-th threshold value

The primary data we manipulate are arrays of “confusion” counts, i.e.

- tp_count[i] - true positives at the i-th threshold
- fp_count[i] - false positives at the i-th threshold
- fn_count[i] - false negatives at the i-th threshold
- tn_count[i] - true negatives at the i-th threshold

Module Contents

Classes

<i>Measures</i>	Holds accumulated confusion counts, and derived measures
<i>PerClass_Measures</i>	
<i>MeasureCombiner</i>	Helper to iteratively combine binary measures generated by some process
<i>OneVersusRestMeasureCombiner</i>	Helper to iteratively combine ovr measures generated by some process

Functions

<code>reversible_diff(arr, assume_sorted=1, reverse=False)</code>	re- Does a reversable array difference operation.
<code>populate_info(info)</code>	Given raw accumulated confusion counts, populated secondary measures like

`class kwcococo.metrics.confusion_measures.Measures(info)`
Bases: `ubelt.NiceRepr, kwcococo.metrics.util.DictProxy`

Holds accumulated confusion counts, and derived measures

Example

```
>>> from kwcococo.metrics.confusion_vectors import BinaryConfusionVectors # NOQA
>>> binvecs = BinaryConfusionVectors.demo(n=100, p_error=0.5)
>>> self = binvecs.measures()
>>> print('self = {!r}'.format(self))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> self.draw(doclf=True)
>>> self.draw(key='pr', pnum=(1, 2, 1))
>>> self.draw(key='roc', pnum=(1, 2, 2))
>>> kwplot.show_if_requested()
```

```
property catname(self)
__nice__(self)
reconstruct(self)
classmethod from_json(cls, state)
__json__(self)
```

Example

```
>>> from kwcococo.metrics.confusion_vectors import BinaryConfusionVectors # NOQA
>>> binvecs = BinaryConfusionVectors.demo(n=10, p_error=0.5)
>>> self = binvecs.measures()
>>> info = self.__json__()
>>> print('info = {}'.format(ub.repr2(info, nl=1)))
>>> populate_info(info)
>>> print('info = {}'.format(ub.repr2(info, nl=1)))
>>> recon = Measures.from_json(info)
```

```
summary(self)
maximized_thresholds(self)
    Returns thresholds that maximize metrics.
counts(self)
draw(self, key=None, prefix='', **kw)
```

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics.confusion_vectors import ConfusionVectors # NOQA
>>> cfsn_vecs = ConfusionVectors.demo()
>>> ovr_cfsn = cfsn_vecs.binarize_ovr(keyby='name')
>>> self = ovr_cfsn.measures()['perclass']
>>> self.draw('mcc', doclf=True, fnum=1)
>>> self.draw('pr', doclf=1, fnum=2)
>>> self.draw('roc', doclf=1, fnum=3)
```

`summary_plot(self, fnum=1, title='', subplots='auto')`

Example

```
>>> from kwcoco.metrics.confusion_measures import * # NOQA
>>> from kwcoco.metrics.confusion_vectors import ConfusionVectors # NOQA
>>> cfsn_vecs = ConfusionVectors.demo(n=3, p_error=0.5)
>>> binvecs = cfsn_vecs.binarize_classless()
>>> self = binvecs.measures()
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> self.summary_plot()
>>> kwplot.show_if_requested()
```

`classmethod demo(cls, **kwargs)`

Create a demo Measures object for testing / demos

Parameters `**kwargs` – passed to `BinaryConfusionVectors.demo()`. some valid keys are:
`n`, `rng`, `p_rue`, `p_error`, `p_miss`.

`classmethod combine(cls, tocombine, precision=None, growth=None, thresh_bins=None)`

Combine binary confusion metrics

Parameters

- **tocombine** (`List[Measures]`) – a list of measures to combine into one
- **precision** (`int | None`) – If specified rounds thresholds to this precision which can prevent a RAM explosion when combining a large number of measures. However, this is a lossy operation and will impact the underlying scores. NOTE: use `growth` instead.
- **growth** (`int | None`) – if specified this limits how much the resulting measures are allowed to grow by. If `None`, `growth` is unlimited. Otherwise, if `growth` is ‘max’, the growth is limited to the maximum length of an input. We might make this more numerical in the future.
- **thresh_bins** (`int`) – Force this many threshold bins.

Returns Measures

Example

```
>>> from kwcoco.metrics.confusion_measures import * # NOQA
>>> measures1 = Measures.demo(n=15)
>>> measures2 = measures1
>>> tocombine = [measures1, measures2]
>>> new_measures = Measures.combine(tocombine)
>>> new_measures.reconstruct()
>>> print('new_measures = {!r}'.format(new_measures))
>>> print('measures1 = {!r}'.format(measures1))
>>> print('measures2 = {!r}'.format(measures2))
>>> print(ub.repr2(measures1.__json__(), nl=1, sort=0))
>>> print(ub.repr2(measures2.__json__(), nl=1, sort=0))
>>> print(ub.repr2(new_measures.__json__(), nl=1, sort=0))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.figure(fnum=1)
>>> new_measures.summary_plot()
>>> measures1.summary_plot()
>>> measures1.draw('roc')
>>> measures2.draw('roc')
>>> new_measures.draw('roc')
```

Example

```
>>> # Demonstrate issues that can arise from choosing a precision
>>> # that is too low when combining metrics. Breakpoints
>>> # between different metrics can get muddled, but choosing a
>>> # precision that is too high can overwhelm memory.
>>> from kwcoco.metrics.confusion_measures import * # NOQA
>>> base = ub.map_vals(np.asarray, {
>>>     'tp_count': [ 1, 1, 2, 2, 2, 2, 3],
>>>     'fp_count': [ 0, 1, 1, 2, 3, 4, 5],
>>>     'fn_count': [ 1, 1, 0, 0, 0, 0, 0],
>>>     'tn_count': [ 5, 4, 4, 3, 2, 1, 0],
>>>     'thresholds': [.0, .0, .0, .0, .0, .0, .0],
>>> })
>>> # Make tiny offsets to thresholds
>>> rng = kwarray.ensure_rng(0)
>>> n = len(base['thresholds'])
>>> offsets = [
>>>     sorted(rng.rand(n) * 10 ** -rng.randint(4, 7))[::-1]
>>>     for _ in range(20)
>>> ]
>>> tocombine = []
>>> for offset in offsets:
>>>     base_n = base.copy()
>>>     base_n['thresholds'] += offset
>>>     measures_n = Measures(base_n).reconstruct()
>>>     tocombine.append(measures_n)
```

(continues on next page)

(continued from previous page)

```
>>> for precision in [6, 5, 2]:
>>>     combo = Measures.combine(tocombine, precision=precision).reconstruct()
>>>     print('precision = {!r}'.format(precision))
>>>     print('combo = {}'.format(ub.repr2(combo, nl=1)))
>>>     print('num_thresholds = {}'.format(len(combo['thresholds'])))
>>> for growth in [None, 'max', 'log', 'root', 'half']:
>>>     combo = Measures.combine(tocombine, growth=growth).reconstruct()
>>>     print('growth = {!r}'.format(growth))
>>>     print('combo = {}'.format(ub.repr2(combo, nl=1)))
>>>     print('num_thresholds = {}'.format(len(combo['thresholds'])))
>>> #print(combo.counts().pandas())
```

Example

```
>>> # Test case: combining a single measures should leave it unchanged
>>> from kwCOCO.metrics.confusion_measures import * # NOQA
>>> measures = Measures.demo(n=40, p_true=0.2, p_error=0.4, p_miss=0.6)
>>> df1 = measures.counts().pandas().fillna(0)
>>> print(df1)
>>> tocombine = [measures]
>>> combo = Measures.combine(tocombine)
>>> df2 = combo.counts().pandas().fillna(0)
>>> print(df2)
>>> assert np.allclose(df1, df2)
```

```
>>> combo = Measures.combine(tocombine, thresh_bins=2)
>>> df3 = combo.counts().pandas().fillna(0)
>>> print(df3)
```

```
>>> # I am NOT sure if this is correct or not
>>> combo = Measures.combine(tocombine, thresh_bins=20)
>>> df4 = combo.counts().pandas().fillna(0)
>>> print(df4)
```

```
assert np.allclose(combo['thresholds'], measures['thresholds']) assert np.allclose(combo['fp_count'], measures['fp_count']) assert np.allclose(combo['tp_count'], measures['tp_count']) assert np.allclose(combo['tp_count'], measures['tp_count'])
```

`kwCOCO.metrics.confusion_measures.reversible_diff(arr, assume_sorted=True, reverse=False)`

Does a reversible array difference operation.

This will be used to find positions where accumulation happened in confusion count array.

```
class kwCOCO.metrics.confusion_measures.PerClass_Measures(cx_to_info)
Bases: ubelt.NiceRepr, kwCOCO.metrics.util.DictProxy

__nice__(self)
summary(self)
classmethod from_json(cls, state)
__json__(self)
draw(self, key='mcc', prefix='', **kw)
```

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> from kwCOCO.metrics.confusion_vectors import ConfusionVectors # NOQA
>>> cfsn_vecs = ConfusionVectors.demo()
>>> ovr_cfsn = cfsn_vecs.binarize_ovr(keyby='name')
>>> self = ovr_cfsn.measures()['perclass']
>>> self.draw('mcc', doclf=True, fnum=1)
>>> self.draw('pr', doclf=1, fnum=2)
>>> self.draw('roc', doclf=1, fnum=3)
```

```
draw_roc(self, prefix='', **kw)
draw_pr(self, prefix='', **kw)
summary_plot(self, fnum=1, title='', subplots='auto')
```

CommandLine

```
python ~/code/kwCOCO/kwCOCO/metrics/confusion_measures.py PerClass_Measures.
->summary_plot --show
```

Example

```
>>> from kwCOCO.metrics.confusion_measures import * # NOQA
>>> from kwCOCO.metrics.detect_metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo()
>>>     n_fp=(0, 1), n_fn=(0, 3), nimgs=32, nboxes=(0, 32),
>>>     classes=3, rng=0, newstyle=1, box_noise=0.7, cls_noise=0.2, score_
>>> noise=0.3, with_probs=False)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> ovr_cfsn = cfsn_vecs.binarize_ovr(keyby='name', ignore_classes=['vector',
>>> 'raster'])
>>> self = ovr_cfsn.measures()['perclass']
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> import seaborn as sns
>>> sns.set()
>>> self.summary_plot(title='demo summary_plot ovr', subplots=['pr', 'roc'])
>>> kwplot.show_if_requested()
>>> self.summary_plot(title='demo summary_plot ovr', subplots=['mcc', 'acc'],
>>> fnum=2)
```

```
class kwCOCO.metrics.confusion_measures.MeasureCombiner(precision=None, growth=None,
                                                        thresh_bins=None)
```

Helper to iteratively combine binary measures generated by some process

Example

```
>>> from kwcococo.metrics.confusion_measures import * # NOQA
>>> from kwcococo.metrics.confusion_vectors import BinaryConfusionVectors
>>> rng = kwarray.ensure_rng(0)
>>> bin_combiner = MeasureCombiner(growth='max')
>>> for _ in range(80):
>>>     bin_cfsn_vecs = BinaryConfusionVectors.demo(n=rng.randint(40, 50), rng=rng,
->>>     p_true=0.2, p_error=0.4, p_miss=0.6)
>>>     bin_measures = bin_cfsn_vecs.measures()
>>>     bin_combiner.submit(bin_measures)
>>> combined = bin_combiner.finalize()
>>> print('combined = {!r}'.format(combined))
```

`property queue_size(self)`

`submit(self, other)`

`combine(self)`

`finalize(self)`

`class kwcococo.metrics.confusion_measures.OneVersusRestMeasureCombiner(precision=None,
 growth=None,
 thresh_bins=None)`

Helper to iteratively combine ovr measures generated by some process

Example

```
>>> from kwcococo.metrics.confusion_measures import * # NOQA
>>> from kwcococo.metrics.confusion_vectors import OneVsRestConfusionVectors
>>> rng = kwarray.ensure_rng(0)
>>> ovr_combiner = OneVersusRestMeasureCombiner(growth='max')
>>> for _ in range(80):
>>>     ovr_cfsn_vecs = OneVsRestConfusionVectors.demo()
>>>     ovr_measures = ovr_cfsn_vecs.measures()
>>>     ovr_combiner.submit(ovr_measures)
>>> combined = ovr_combiner.finalize()
>>> print('combined = {!r}'.format(combined))
```

`submit(self, other)`

`_summary(self)`

`combine(self)`

`finalize(self)`

`kwcococo.metrics.confusion_measures.populate_info(info)`

Given raw accumulated confusion counts, populated secondary measures like AP, AUC, F1, MCC, etc..

kwcoco.metrics.confusion_vectors

Classes that store raw confusion vectors, which can be accumulated into confusion measures.

Module Contents**Classes**

<i>ConfusionVectors</i>	Stores information used to construct a confusion matrix. This includes
<i>OneVsRestConfusionVectors</i>	Container for multiple one-vs-rest binary confusion vectors
<i>BinaryConfusionVectors</i>	Stores information about a binary classification problem.

Functions

_stabalize_data(y_true, y_score, sample_weight, npad=7) Adds ideally calibrated dummy values to curves with few positive examples.

class kwcoco.metrics.confusion_vectors.ConfusionVectors(*cfsn_vecs, data, classes, probs=None*)
Bases: `ubelt.NiceRepr`

Stores information used to construct a confusion matrix. This includes corresponding vectors of predicted labels, true labels, sample weights, etc...

Variables

- **data** (`kwarray.DataFrameArray`) – should at least have keys true, pred, weight
- **classes** (`Sequence / CategoryTree`) – list of category names or category graph
- **probs** (`ndarray, optional`) – probabilities for each class

Example

```
>>> # xdoctest: IGNORE_WANT
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     nimgs=10, nboxes=(0, 10), n_fp=(0, 1), classes=3)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> print(cfsn_vecs.data._pandas())
   pred  true    score    weight      iou    txs    pxs    gid
0      2      2  10.0000  1.0000  1.0000      0      4      0
1      2      2   7.5025  1.0000  1.0000      1      3      0
2      1      1   5.0050  1.0000  1.0000      2      2      0
3      3     -1   2.5075  1.0000 -1.0000     -1      1      0
4      2     -1   0.0100  1.0000 -1.0000     -1      0      0
5     -1      2   0.0000  1.0000 -1.0000      3     -1      0
```

(continues on next page)

(continued from previous page)

6	-1	2	0.0000	1.0000	-1.0000	4	-1	0
7	2	2	10.0000	1.0000	1.0000	0	5	1
8	2	2	8.0020	1.0000	1.0000	1	4	1
9	1	1	6.0040	1.0000	1.0000	2	3	1
..
62	-1	2	0.0000	1.0000	-1.0000	7	-1	7
63	-1	3	0.0000	1.0000	-1.0000	8	-1	7
64	-1	1	0.0000	1.0000	-1.0000	9	-1	7
65	1	-1	10.0000	1.0000	-1.0000	-1	0	8
66	1	1	0.0100	1.0000	1.0000	0	1	8
67	3	-1	10.0000	1.0000	-1.0000	-1	3	9
68	2	2	6.6700	1.0000	1.0000	0	2	9
69	2	2	3.3400	1.0000	1.0000	1	1	9
70	3	-1	0.0100	1.0000	-1.0000	-1	0	9
71	-1	2	0.0000	1.0000	-1.0000	2	-1	9

```
>>> # xdoctest: +REQUIRES(--show)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> import kwplot
>>> kwplot.autopl()
>>> from kwcoco.metrics.confusion_vectors import ConfusionVectors
>>> cfsn_vecs = ConfusionVectors.demo(
>>>     nimgs=128, nboxes=(0, 10), n_fp=(0, 3), n_fn=(0, 3), classes=3)
>>> cx_to_binvecs = cfsn_vecs.binarize_ovr()
>>> measures = cx_to_binvecs.measures()['perclass']
>>> print('measures = {!r}'.format(measures))
measures = <PerClass_Measures{
    'cat_1': <Measures({'ap': 0.227, 'auc': 0.507, 'catname': cat_1, 'max_f1': f1=0.
    ↵45@0.47, 'nsupport': 788.000}>,
    'cat_2': <Measures({'ap': 0.288, 'auc': 0.572, 'catname': cat_2, 'max_f1': f1=0.
    ↵51@0.43, 'nsupport': 788.000}>,
    'cat_3': <Measures({'ap': 0.225, 'auc': 0.484, 'catname': cat_3, 'max_f1': f1=0.
    ↵46@0.40, 'nsupport': 788.000}>,
}) at 0x7facf77bdfd0>
>>> kwplot.figure(fnum=1, doclf=True)
>>> measures.draw(key='pr', fnum=1, pnum=(1, 3, 1))
>>> measures.draw(key='roc', fnum=1, pnum=(1, 3, 2))
>>> measures.draw(key='mcc', fnum=1, pnum=(1, 3, 3))
...

```

__nice__(cfsn_vecs)
__json__(self)
 Serialize to json

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics import ConfusionVectors
>>> self = ConfusionVectors.demo(n_imgs=1, classes=2, n_fp=0, nboxes=1)
>>> state = self.__json__()
>>> print('state = {}'.format(ub.repr2(state, nl=2, precision=2, align=1)))
>>> recon = ConfusionVectors.from_json(state)
```

classmethod `from_json`(*cls*, *state*)
classmethod `demo`(*cfsn_vecs*, ***kw*)

Parameters `**kwargs` – See `kwcoco.metrics.DetectionMetrics.demo()`

Returns `ConfusionVectors`

Example

```
>>> cfsn_vecs = ConfusionVectors.demo()
>>> print('cfsn_vecs = {!r}'.format(cfsn_vecs))
>>> cx_to_binvecs = cfsn_vecs.binarize_ovr()
>>> print('cx_to_binvecs = {!r}'.format(cx_to_binvecs))
```

classmethod `from_arrays`(*ConfusionVectors*, *true*, *pred=None*, *score=None*, *weight=None*, *probs=None*, *classes=None*)

Construct confusion vector data structure from component arrays

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> import kwarray
>>> classes = ['person', 'vehicle', 'object']
>>> rng = kwarray.ensure_rng(0)
>>> true = (rng.rand(10) * len(classes)).astype(int)
>>> probs = rng.rand(len(true), len(classes))
>>> cfsn_vecs = ConfusionVectors.from_arrays(true=true, probs=probs, ↴
>>> classes=classes)
>>> cfsn_vecs.confusion_matrix()
pred      person  vehicle  object
real
person        0        0        0
vehicle        2        4        1
object        2        1        0
```

`confusion_matrix`(*cfsn_vecs*, *compress=False*)

Builds a confusion matrix from the confusion vectors.

Parameters `compress` (*bool*, *default=False*) – if True removes rows / columns with no entries

Returns

`cm` [the labeled confusion matrix]

(Note: we should write a efficient replacement for this use case. #remove_pandas)

Return type pd.DataFrame

CommandLine

```
xdoctest -m kwcoco.metrics.confusion_vectors ConfusionVectors.confusion_matrix
```

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo()
>>> nimgs=10, nboxes=(0, 10), n_fp=(0, 1), n_fn=(0, 1), classes=3, cls_noise=.2
>>> cfsn_vecs = dmet.confusion_vectors()
>>> cm = cfsn_vecs.confusion_matrix()
...
>>> print(cm.to_string(float_format=lambda x: '%.2f' % x))
pred      background  cat_1  cat_2  cat_3
real
background      0.00   1.00   2.00   3.00
cat_1           3.00  12.00   0.00   0.00
cat_2           3.00   0.00  14.00   0.00
cat_3           2.00   0.00   0.00  17.00
```

coarsen(*cfsn_vecs*, *cxs*)

Creates a coarsened set of vectors

Returns ConfusionVectors

binarize_classless(*cfsn_vecs*, *negative_classes=None*)

Creates a binary representation useful for measuring the performance of detectors. It is assumed that scores of “positive” classes should be high and “negative” classes should be low.

Parameters *negative_classes* (*List[str | int]*) – list of negative class names or idxs, by default chooses any class with a true class index of -1. These classes should ideally have low scores.

Returns BinaryConfusionVectors

Note: The “classlessness” of this depends on the *compat=”all”* argument being used when constructing confusion vectors, otherwise it becomes something like a macro-average because the class information was used in deciding which true and predicted boxes were allowed to match.

Example

```
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo()
>>> nimgs=10, nboxes=(0, 10), n_fp=(0, 1), n_fn=(0, 1), classes=3
>>> cfsn_vecs = dmet.confusion_vectors()
>>> class_idxs = list(dmet.classes.node_to_idx.values())
>>> binvecs = cfsn_vecs.binarize_classless()
```

binarize_ovr(*cfsn_vecs*, *mode*=1, *keyby*='name', *ignore_classes*={'ignore'}, *approx*=0)
Transforms *cfsn_vecs* into one-vs-rest BinaryConfusionVectors for each category.

Parameters

- **mode** (*int, default=1*) – 0 for heirarchy aware or 1 for voc like. MODE 0 IS PROBABLY BROKEN
- **keyby** (*int | str*) – can be cx or name
- **ignore_classes** (*Set[str]*) – category names to ignore
- **approx** (*bool, default=0*) – if True try and approximate missing scores otherwise assume they are irrecoverable and use -inf

Returns

which behaves like Dict[int, BinaryConfusionVectors]: *cx_to_binvecs*

Return type *OneVsRestConfusionVectors*

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> cfsn_vecs = ConfusionVectors.demo()
>>> print('cfsn_vecs = {!r}'.format(cfsn_vecs))
>>> catname_to_binvecs = cfsn_vecs.binarize_ovr(keyby='name')
>>> print('catname_to_binvecs = {!r}'.format(catname_to_binvecs))
```

cfsn_vecs.data.pandas() *catname_to_binvecs*.cx_to_binvecs['class_1'].data.pandas()

Note:

classification_report(*cfsn_vecs*, *verbose*=0)
Build a classification report with various metrics.

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> cfsn_vecs = ConfusionVectors.demo()
>>> report = cfsn_vecs.classification_report(verbose=1)
```

class kwcoco.metrics.confusion_vectors.**OneVsRestConfusionVectors**(*cx_to_binvecs*, *classes*)
Bases: ubelt.NiceRepr

Container for multiple one-vs-rest binary confusion vectors

Variables

- `cx_to_binvecs` –
- `classes` –

Example

```
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     nimgs=10, nboxes=(0, 10), n_fp=(0, 1), classes=3)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> self = cfsn_vecs.binarize_ovr(keyby='name')
>>> print('self = {!r}'.format(self))
```

`__nice__(self)`

`classmethod demo(cls)`

Parameters `**kwargs` – See `kwcoco.metrics.DetectionMetrics.demo()`

Returns ConfusionVectors

`keys(self)`

`__getitem__(self, cx)`

`measures(self, stabilize_thresh=7, fp_cutoff=None, monotonic_ppv=True, ap_method='pycocotools')`

Creates binary confusion measures for every one-versus-rest category.

Parameters

- `stabilize_thresh` (`int, default=7`) – if fewer than this many data points inserts dummy stabilization data so curves can still be drawn.
- `fp_cutoff` (`int, default=None`) – maximum number of false positives in the truncated roc curves. None is equivalent to `float('inf')`
- `monotonic_ppv` (`bool, default=True`) – if True ensures that precision is always increasing as recall decreases. This is done in pycocotools scoring, but I'm not sure its a good idea.

SeeAlso: `BinaryConfusionVectors.measures()`

Example

```
>>> self = OneVsRestConfusionVectors.demo()
>>> thresh_result = self.measures()['perclass']
```

`abstract ovr_classification_report(self)`

`class kwcoco.metrics.confusion_vectors.BinaryConfusionVectors(data, cx=None, classes=None)`
Bases: `ubelt.NiceRepr`

Stores information about a binary classification problem. This is always with respect to a specific class, which is given by `cx` and `classes`.

The **data DataFrameArray** must contain *is_true* - if the row is an instance of class *classes[cx]* *pred_score* - the predicted probability of class *classes[cx]*, and *weight* - sample weight of the example

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> self = BinaryConfusionVectors.demo(n=10)
>>> print('self = {!r}'.format(self))
>>> print('measures = {}'.format(ub.repr2(self.measures())))
```

```
>>> self = BinaryConfusionVectors.demo(n=0)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
```

```
>>> self = BinaryConfusionVectors.demo(n=1)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
```

```
>>> self = BinaryConfusionVectors.demo(n=2)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
```

classmethod demo(cls, n=10, p_true=0.5, p_error=0.2, p_miss=0.0, rng=None)
Create random data for tests

Parameters

- **n** (*int*) – number of rows
- **p_true** (*int*) – fraction of real positive cases
- **p_error** (*int*) – probability of making a recoverable mistake
- **p_miss** (*int*) – probability of making a unrecoverable mistake
- **rng** (*int* | *RandomState*) – random seed / state

Returns BinaryConfusionVectors

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> cfsn = BinaryConfusionVectors.demo(n=1000, p_error=0.1, p_miss=0.1)
>>> measures = cfsn.measures()
>>> print('measures = {}'.format(ub.repr2(measures, nl=1)))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.figure(fnum=1, pnum=(1, 2, 1))
>>> measures.draw('pr')
>>> kwplot.figure(fnum=1, pnum=(1, 2, 2))
>>> measures.draw('roc')
```

property catname(self)

__nice__(self)

__len__(self)

measures(*self*, *stabalize_thresh*=7, *fp_cutoff*=None, *monotonic_ppv*=True, *ap_method*='pycocotools')
Get statistics (F1, G1, MCC) versus thresholds

Parameters

- **stabalize_thresh** (*int*, *default*=7) – if fewer than this many data points inserts dummy stabalization data so curves can still be drawn.
- **fp_cutoff** (*int*, *default*=None) – maximum number of false positives in the truncated roc curves. None is equivalent to `float('inf')`
- **monotonic_ppv** (*bool*, *default*=True) – if True ensures that precision is always increasing as recall decreases. This is done in pycocotools scoring, but I'm not sure its a good idea.

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> self = BinaryConfusionVectors.demo(n=0)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
>>> self = BinaryConfusionVectors.demo(n=1, p_true=0.5, p_error=0.5)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
>>> self = BinaryConfusionVectors.demo(n=3, p_true=0.5, p_error=0.5)
>>> print('measures = {}'.format(ub.repr2(self.measures())))

>>> self = BinaryConfusionVectors.demo(n=100, p_true=0.5, p_error=0.5, p_miss=0.
...     ↵3)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
>>> print('measures = {}'.format(ub.odict(self.measures()))))
```

References

https://en.wikipedia.org/wiki/Confusion_matrix https://en.wikipedia.org/wiki/Precision_and_recall https://en.wikipedia.org/wiki/Matthews_correlation_coefficient

_binary_clf_curves(*self*, *stabalize_thresh*=7, *fp_cutoff*=None)

Compute TP, FP, TN, and FN counts for this binary confusion vector.

Code common to ROC, PR, and threshold measures, computes the elements of the binary confusion matrix at all relevant operating point thresholds.

Parameters

- **stabalize_thresh** (*int*) – if fewer than this many data points insert stabalization data.
- **fp_cutoff** (*int*) – maximum number of false positives

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> self = BinaryConfusionVectors.demo(n=1, p_true=0.5, p_error=0.5)
>>> self._binary_clf_curves()
```

```
>>> self = BinaryConfusionVectors.demo(n=0, p_true=0.5, p_error=0.5)
>>> self._binary_clf_curves()
```

```
>>> self = BinaryConfusionVectors.demo(n=100, p_true=0.5, p_error=0.5)
>>> self._binary_clf_curves()
```

```
draw_distribution(self)
```

```
_3dplot(self)
```

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> from kwcoco.metrics.detect_metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     n_fp=(0, 1), n_fn=(0, 2), nimgs=256, nboxes=(0, 10),
>>>     bbox_noise=10,
>>>     classes=1)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> self = bin_cfsn = cfsn_vecs.binarize_classless()
>>> #dmet.summarize(plot=True)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.figure(fnum=3)
>>> self._3dplot()
```

`kwcoco.metrics.confusion_vectors._stabalize_data(y_true, y_score, sample_weight, npad=7)`

Adds ideally calibrated dummy values to curves with few positive examples. This acts somewhat like a Bayesian prior and smooths out the curve.

Example

```
y_score = np.array([0.5, 0.6]) y_true = np.array([1, 1]) sample_weight = np.array([1, 1]) npad = 7 _stabalize_data(y_true, y_score, sample_weight, npad=npad)
```

`kwcoco.metrics.detect_metrics`

Module Contents

Classes

<code>DetectionMetrics</code>	Object that computes associations between detections and can convert them
-------------------------------	---

Functions

<code>_demo_construct_probs(pred_cxs, classes, rng, hacked=1)</code>	Constructs random probabilities for demo data
<code>pycocotools_confusion_vectors(dmet, iou_thresh=0.5, verbose=0)</code>	

Example

<code>eval_detections_cli(**kw)</code>	DEPRECATED USE <code>kwcoco eval</code> instead
<code>_summarize(self, ap=1, areaRngLbl='all', maxDets=100)</code>	
<code>pct_summarize2(self)</code>	

`class kwcoco.metrics.detect_metrics.DetectionMetrics(dmet, classes=None)`
Bases: `ubelt.NiceRepr`

Object that computes associations between detections and can convert them into sklearn-compatible representations for scoring.

Variables

- `gid_to_true_dets` (`Dict`) – maps image ids to truth
- `gid_to_pred_dets` (`Dict`) – maps image ids to predictions
- `classes` (`CategoryTree`) – category coder

Example

```
>>> dmet = DetectionMetrics.demo(  
>>>     nimgs=100, nboxes=(0, 3), n_fp=(0, 1), classes=8, score_noise=0.9,  
>>>     hacked=False)  
>>> print(dmet.score_kwCOCO(bias=0, compat='mutex', prioritize='iou')['mAP'])  
...  
>>> # NOTE: IN GENERAL NETHARN AND VOC ARE NOT THE SAME  
>>> print(dmet.score_voc(bias=0)['mAP'])  
0.8582...  
>>> #print(dmet.score_coco()['mAP'])
```

`score_coco`

`clear(dmet)`

`__nice__(dmet)`

`classmethod from_coco(DetectionMetrics, true_coco, pred_coco, gids=None, verbose=0)`

Create detection metrics from two coco files representing the truth and predictions.

Parameters

- `true_coco` (`kwCOCO.CocoDataset`)
- `pred_coco` (`kwCOCO.CocoDataset`)

Example

```
>>> import kwCOCO  
>>> from kwCOCO.demo.perterb import perterb_coco  
>>> true_coco = kwCOCO.CocoDataset.demo('shapes')  
>>> perterbkw = dict(box_noise=0.5, cls_noise=0.5, score_noise=0.5)  
>>> pred_coco = perterb_coco(true_coco, **perterbkw)  
>>> self = DetectionMetrics.from_coco(true_coco, pred_coco)  
>>> self.score_voc()
```

`_register_imagename(dmet, imgname, gid=None)`

`add_predictions(dmet, pred_dets, imgname=None, gid=None)`

Register/Add predicted detections for an image

Parameters

- `pred_dets` (`Detections`) – predicted detections
- `imgname` (`str`) – a unique string to identify the image
- `gid` (`int, optional`) – the integer image id if known

`add_truth(dmet, true_dets, imgname=None, gid=None)`

Register/Add groundtruth detections for an image

Parameters

- `true_dets` (`Detections`) – groundtruth
- `imgname` (`str`) – a unique string to identify the image
- `gid` (`int, optional`) – the integer image id if known

true_detections(*dmet, gid*)

gets Detections representation for groundtruth in an image

pred_detections(*dmet, gid*)

gets Detections representation for predictions in an image

confusion_vectors(*dmet, iou_thresh=0.5, bias=0, gids=None, compat='mutex', prioritize='iou', ignore_classes='ignore', background_class=ub.NoParam, verbose='auto', workers=0, track_probs='try', max_dets=None*)

Assigns predicted boxes to the true boxes so we can transform the detection problem into a classification problem for scoring.

Parameters

- **iou_thresh** (*float | List[float], default=0.5*) – bounding box overlap iou threshold required for assignment if a list, then return type is a dict
- **bias** (*float, default=0.0*) – for computing bounding box overlap, either 1 or 0
- **gids** (*List[int], default=None*) – which subset of images ids to compute confusion metrics on. If not specified all images are used.
- **compat** (*str, default='all'*) – can be ('ancestors' | 'mutex' | 'all'). determines which pred boxes are allowed to match which true boxes. If 'mutex', then pred boxes can only match true boxes of the same class. If 'ancestors', then pred boxes can match true boxes that match or have a coarser label. If 'all', then any pred can match any true, regardless of its category label.
- **prioritize** (*str, default='iou'*) – can be ('iou' | 'class' | 'correct') determines which box to assign to if multiple true boxes overlap a predicted box. if prioritize is iou, then the true box with maximum iou (above iou_thresh) will be chosen. If prioritize is class, then it will prefer matching a compatible class above a higher iou. If prioritize is correct, then ancestors of the true class are preferred over descendants of the true class, over unrelated classes.
- **ignore_classes** (*set, default={'ignore'}*) – class names indicating ignore regions
- **background_class** (*str, default=ub.NoParam*) – Name of the background class. If unspecified we try to determine it with heuristics. A value of None means there is no background class.
- **verbose** (*int, default='auto'*) – verbosity flag. In auto mode, verbose=1 if len(gids) > 1000.
- **workers** (*int, default=0*) – number of parallel assignment processes
- **track_probs** (*str, default='try'*) – can be 'try', 'force', or False. if truthy, we assume probabilities for multiple classes are available.

Returns ConfusionVectors | Dict[float, ConfusionVectors]

Example

```
>>> dmet = DetectionMetrics.demo(nimgs=30, classes=3,
>>>                               nboxes=10, n_fp=3, box_noise=10,
>>>                               with_probs=False)
>>> iou_to_cfsn = dmet.confusion_vectors(iou_thresh=[0.3, 0.5, 0.9])
>>> for t, cfsn in iou_to_cfsn.items():
>>>     print('t = {!r}'.format(t))
```

(continues on next page)

(continued from previous page)

```
...     print(cfsn.binarize_ovr().measures())
...     print(cfsn.binarize_classless().measures())
```

score_kwant(*dmet*, *iou_thresh*=0.5)

Scores the detections using kwant

score_kwccoco(*dmet*, *iou_thresh*=0.5, *bias*=0, *gids*=None, *compat*='all', *prioritize*='iou')

our scoring method

score_voc(*dmet*, *iou_thresh*=0.5, *bias*=1, *method*='voc2012', *gids*=None, *ignore_classes*='ignore')

score using voc method

Example

```
>>> dmet = DetectionMetrics.demo()
>>> nimgs=100, nboxes=(0, 3), n_fp=(0, 1), classes=8,
>>> score_noise=.5
>>> print(dmet.score_voc()['mAP'])
0.9399...
```

_to_coco(*dmet*)

Convert to a coco representation of truth and predictions

with inverse aid mappings

score_pycocotools(*dmet*, *with_evaler*=False, *with_confusion*=False, *verbose*=0, *iou_thresholds*=None)

score using ms-coco method

Returns dictionary with pct info**Return type** Dict**Example**

```
>>> # xdoctest: +REQUIRES(module:pycocotools)
>>> from kwccoco.metrics.detect_metrics import *
>>> dmet = DetectionMetrics.demo()
>>> nimgs=10, nboxes=(0, 3), n_fn=(0, 1), n_fp=(0, 1), classes=8, with_
>>> _probs=False
>>> pct_info = dmet.score_pycocotools(verbose=1,
>>>                               with_evaler=True,
>>>                               with_confusion=True,
>>>                               iou_thresholds=[0.5, 0.9])
>>> evaler = pct_info['evaler']
>>> iou_to_cfsn_vecs = pct_info['iou_to_cfsn_vecs']
>>> for iou_thresh in iou_to_cfsn_vecs.keys():
>>>     print('iou_thresh = {!r}'.format(iou_thresh))
>>>     cfsn_vecs = iou_to_cfsn_vecs[iou_thresh]
>>>     ovr_measures = cfsn_vecs.binarize_ovr().measures()
>>>     print('ovr_measures = {}'.format(ub.repr2(ovr_measures, nl=1,
>>>                                         precision=4)))
```

Note: by default pycocotools computes average precision as the literal average of computed precisions at 101 uniformly spaced recall thresholds.

pycocoutils seems to only allow predictions with the same category as the truth to match those truth objects. This should be the same as calling dmet.confusion_vectors with compat = mutex

pycocoutils does not take into account the fact that each box often has a score for each category.

pycocoutils will be incorrect if any annotation has an id of 0

a major difference in the way kwcoco scores versus pycocoutils is the calculation of AP. The assignment between truth and predicted detections produces similar enough results. Given our confusion vectors we use the scikit-learn definition of AP, whereas pycocoutils seems to compute precision and recall — more or less correctly — but then it resamples the precision at various specified recall thresholds (in the *accumulate* function, specifically how *pr* is resampled into the *q* array). This can lead to a large difference in reported scores.

pycocoutils also smooths out the precision such that it is monotonic decreasing, which might not be the best idea.

pycocotools area ranges are inclusive on both ends, that means the “small” and “medium” truth selections do overlap somewhat.

classmethod demo(*cls*, *kwargs*)**

Creates random true boxes and predicted boxes that have some noisy offset from the truth.

Kwargs:

classes (int, default=1): class list or the number of foreground classes.

nimgs (int, default=1): number of images in the coco datasets. **nboxes (int, default=1):** boxes per image.

n_fp (int, default=0): number of false positives. **n_fn (int, default=0):** number of false negatives.

box_noise (float, default=0): std of a normal distribution used to

perterb both box location and box size.

cls_noise (float, default=0): probability that a class label will change. Must be within 0 and 1.

anchors (ndarray, default=None): used to create random boxes **null_pred (bool, default=0):**

if True, predicted classes are returned as null, which means only localization scoring is suitable.

with_probs (bool, default=1): if True, includes per-class probabilities with predictions

CommandLine

```
xdoctest -m kwcoco.metrics.detect_metrics DetectionMetrics.demo:2 --show
```

Example

```
>>> kwargs = {}
>>> # Seed the RNG
>>> kwargs['rng'] = 0
>>> # Size parameters determine how big the data is
>>> kwargs['nimgs'] = 5
>>> kwargs['nboxes'] = 7
>>> kwargs['classes'] = 11
>>> # Noise parameters perterb predictions further from the truth
>>> kwargs['n_fp'] = 3
>>> kwargs['box_noise'] = 0.1
>>> kwargs['cls_noise'] = 0.5
>>> dmet = DetectionMetrics.demo(**kwargs)
>>> print('dmet.classes = {}'.format(dmet.classes))
dmet.classes = <CategoryTree(nNodes=12, maxDepth=3, maxBreadth=4...)>
>>> # Can grab kwimage.Detection object for any image
>>> print(dmet.true_detections(gid=0))
<Detections(4)>
>>> print(dmet.pred_detections(gid=0))
<Detections(7)>
```

Example

```
>>> # Test case with null predicted categories
>>> dmet = DetectionMetrics.demo(nimgs=30, null_pred=1, classes=3,
>>>                               nboxes=10, n_fp=3, box_noise=0.1,
>>>                               with_probs=False)
>>> dmet.gid_to_pred_dets[0].data
>>> dmet.gid_to_true_dets[0].data
>>> cfsn_vecs = dmet.confusion_vectors()
>>> binvecs_ovr = cfsn_vecs.binarize_ovr()
>>> binvecs_per = cfsn_vecs.binarize_classless()
>>> measures_per = binvecs_per.measures()
>>> measures_ovr = binvecs_ovr.measures()
>>> print('measures_per = {!r}'.format(measures_per))
>>> print('measures_ovr = {!r}'.format(measures_ovr))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> measures_ovr['perclass'].draw(key='pr', fnum=2)
```

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> from kwcoco.metrics.detect_metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     n_fp=(0, 1), n_fn=(0, 1), nimgs=32, nboxes=(0, 16),
>>>     classes=3, rng=0, newstyle=1, box_noise=0.5, cls_noise=0.0, score_
>>> _noise=0.3, with_probs=False)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> summary = dmet.summarize(plot=True, title='DetectionMetrics summary demo', u
>>> _with_ovr=True, with_bin=False)
>>> summary['bin_measures']
>>> kwplot.show_if_requested()
```

`summarize(dmet, out_dpath=None, plot=False, title='', with_bin='auto', with_ovr='auto')`

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> from kwcoco.metrics.detect_metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     n_fp=(0, 128), n_fn=(0, 4), nimgs=512, nboxes=(0, 32),
>>>     classes=3, rng=0)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> dmet.summarize(plot=True, title='DetectionMetrics summary demo')
>>> kwplot.show_if_requested()
```

`kwcoco.metrics.detect_metrics._demo_construct_probs(pred_cxs, pred_scores, classes, rng, hacked=1)`
Constructs random probabilities for demo data

`kwcoco.metrics.detect_metrics.pycocotools_confusion_vectors(dmet, evaler, iou_thresh=0.5,`
`verbose=0)`

Example

```
>>> # xdoctest: +REQUIRES(module:pycocotools)
>>> from kwcoco.metrics.detect_metrics import *
>>> dmet = DetectionMetrics.demo(
>>>     nimgs=10, nboxes=(0, 3), n_fn=(0, 1), n_fp=(0, 1), classes=8, with_
>>> _probs=False)
>>> coco_scores = dmet.score_pycocotools(with_evaler=True)
>>> evaler = coco_scores['evaler']
>>> cfsn_vecs = pycocotools_confusion_vectors(dmet, evaler, verbose=1)
```

`kwcoco.metrics.detect_metrics.eval_detections_cli(**kw)`
DEPRECATED USE `kwcoco eval` instead

CommandLine

```
xdoctest -m ~/code/kwCOCO/kwCOCO/metrics/detect_metrics.py eval_detections_cli
```

```
kwCOCO.metrics.detect_metrics._summarize(self, ap=1, iouThr=None, areaRngLbl='all', maxDets=100)
kwCOCO.metrics.detect_metrics.pct_summarize2(self)
```

kwCOCO.metrics.drawing

Module Contents

Functions

```
draw_perclass_roc(cx_to_info, classes=None, pre-
fix='', fnum=1, fp_axis='count', **kw)
```

Parameters

- **cx_to_info** (*PerClass_Measures | Dict*)

```
demo_format_options()
```

```
concise_si_display(val, eps=1e-08, precision=2, Display numbers in scientific notation if above a thresh-
si_thresh=4) old
```

```
_realpos_label_suffix(info) Creates a label suffix that indicates the number of real
positive cases
```

```
draw_perclass_prcurve(cx_to_info, classes=None, pre-
fix='', fnum=1, **kw)
```

Parameters cx_to_info (Per- Class_Measures | Dict)

```
draw_perclass_thresholds(cx_to_info, key='mcc', classes=None, prefix='', fnum=1, **kw)
```

Parameters cx_to_info (Per- Class_Measures | Dict)

```
draw_roc(info, prefix='', fnum=1, **kw)
```

Parameters info (Measures | Dict)

```
draw_prcurve(info, prefix='', fnum=1, **kw) Draws a single pr curve.
```

```
draw_threshold_curves(info, keys=None, prefix='', fnum=1, **kw)
```

Parameters info (Measures | Dict)

```
kwCOCO.metrics.drawing.draw_perclass_roc(cx_to_info, classes=None, prefix='', fnum=1, fp_axis='count',
**kw)
```

Parameters

- **cx_to_info** (*PerClass_Measures | Dict*)
- **fp_axis** (*str*) – can be count or rate

```
kwCOCO.metrics.drawing.demo_format_options()
```

`kwcoco.metrics.drawing.concise_si_display(val, eps=1e-08, precision=2, si_thresh=4)`

Display numbers in scientific notation if above a threshold

Parameters

- `eps (float)` – threshold to be formated as an integer if other integer conditions hold.
- `precision (int)` – maximum significant digits (might print less)
- `si_thresh (int)` – If the number is less than $10^{\{si_thresh\}}$, then it will be printed as an integer if it is within `eps` of an integer.

References

<https://docs.python.org/2/library/stdtypes.html#string-formatting-operations>

Example

```
>>> grid = {
>>>     'sign': [1, -1],
>>>     'exp': [1, -1],
>>>     'big_part': [0, 32132e3, 4000000032],
>>>     'med_part': [0, 0.5, 0.9432, 0.000043, 0.01, 1, 2],
>>>     'small_part': [0, 1321e-3, 43242e-11],
>>> }
>>> for kw in ub.named_product(grid):
>>>     sign = kw.pop('sign')
>>>     exp = kw.pop('exp')
>>>     raw = (sum(map(float, kw.values())))
>>>     val = sign * raw ** exp if raw != 0 else sign * raw
>>>     print('{:>20} - {}'.format(concise_si_display(val), val))
>>> from kwcoco.metrics.drawing import * # NOQA
>>> print(concise_si_display(40000000432432))
>>> print(concise_si_display(473243280432890))
>>> print(concise_si_display(473243284289))
>>> print(concise_si_display(473243289))
>>> print(concise_si_display(4739))
>>> print(concise_si_display(473))
>>> print(concise_si_display(0.432432))
>>> print(concise_si_display(0.132432))
>>> print(concise_si_display(1.0000043))
>>> print(concise_si_display(01.0000000000000000000000000000043))
```

`kwcoco.metrics.drawing._realpos_label_suffix(info)`

Creates a label suffix that indicates the number of real positive cases versus the total amount of cases considered for an evaluation curve.

Parameters `info (Dict)` – with keys, nsupport, realpos_total

Example

```
>>> from kwCOCO.metrics.drawing import * # NOQA
>>> info = {'nsupport': 10, 'realpos_total': 10}
>>> _realpos_label_suffix(info)
10/10
>>> info = {'nsupport': 10.0, 'realpos_total': 10.0}
>>> _realpos_label_suffix(info)
10/10
>>> info = {'nsupport': 10.3333, 'realpos_total': 10.22222}
>>> _realpos_label_suffix(info)
10.22/10.33
>>> info = {'nsupport': 10.00000001, 'realpos_total': None}
>>> _realpos_label_suffix(info)
10
>>> info = {'nsupport': 10.009}
>>> _realpos_label_suffix(info)
10.01
>>> info = {'nsupport': 3331033334342.432, 'realpos_total': 1033334342.432}
>>> _realpos_label_suffix(info)
1e9/3.3e12
>>> info = {'nsupport': 0.007, 'realpos_total': 0.0000893}
>>> _realpos_label_suffix(info)
8.9e-5/0.007
```

`kwCOCO.metrics.drawing.draw_perclass_prcurve(cx_to_info, classes=None, prefix="", fnum=1, **kw)`

Parameters `cx_to_info` (*PerClass_Measures | Dict*)

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> from kwCOCO.metrics.drawing import * # NOQA
>>> from kwCOCO.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo()
>>> nimgs=3, nboxes=(0, 10), n_fp=(0, 3), n_fn=(0, 2), classes=3, score_noise=0.
-> 1, box_noise=0.1, with_probs=False)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> print(cfsn_vecs.data.pandas())
>>> classes = cfsn_vecs.classes
>>> cx_to_info = cfsn_vecs.binarize_ovr().measures()['perclass']
>>> print('cx_to_info = {}'.format(ub.repr2(cx_to_info, nl=1)))
>>> import kwplot
>>> kwplot.autopl()
>>> draw_perclass_prcurve(cx_to_info, classes)
>>> # xdoctest: +REQUIRES(--show)
>>> kwplot.show_if_requested()
```

`kwCOCO.metrics.drawing.draw_perclass_thresholds(cx_to_info, key='mcc', classes=None, prefix="",
fnum=1, **kw)`

Parameters `cx_to_info` (*PerClass_Measures | Dict*)

Note: Each category is inspected independently of one another, there is no notion of confusion.

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> from kwcoco.metrics.drawing import * # NOQA
>>> from kwcoco.metrics import ConfusionVectors
>>> cfsn_vecs = ConfusionVectors.demo()
>>> classes = cfsn_vecs.classes
>>> ovr_cfsn = cfsn_vecs.binarize_ovr(keyby='name')
>>> cx_to_info = ovr_cfsn.measures()['perclass']
>>> import kwplot
>>> kwplot.autopl()
>>> key = 'mcc'
>>> draw_perclass_thresholds(cx_to_info, key, classes)
>>> # xdoctest: +REQUIRES(--show)
>>> kwplot.show_if_requested()
```

`kwcoco.metrics.drawing.draw_roc(info, prefix='', fnum=1, **kw)`

Parameters `info` (*Measures | Dict*)

Note: There needs to be enough negative examples for using ROC to make any sense!

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot, module:seaborn)
>>> from kwcoco.metrics.drawing import * # NOQA
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(nimgs=30, null_pred=1, classes=3,
>>>                           nboxes=10, n_fp=10, box_noise=0.3,
>>>                           with_probs=False)
>>> dmet.true_detections().data
>>> cfsn_vecs = dmet.confusion_vectors(compat='mutex', prioritize='iou', bias=0)
>>> print(cfsn_vecs.data._pandas().sort_values('score'))
>>> classes = cfsn_vecs.classes
>>> info = ub.peek(cfsn_vecs.binarize_ovr().measures()['perclass'].values())
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> draw_roc(info)
>>> kwplot.show_if_requested()
```

`kwcoco.metrics.drawing.draw_prcurve(info, prefix='', fnum=1, **kw)`

Draws a single pr curve.

Parameters `info` (*Measures | Dict*)

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     nimgs=10, nboxes=(0, 10), n_fp=(0, 1), classes=3)
>>> cfsn_vecs = dmet.confusion_vectors()
```

```
>>> classes = cfsn_vecs.classes
>>> info = cfsn_vecs.binarize_classless().measures()
>>> import kwplot
>>> kwplot.autopl()
>>> draw_prcurve(info)
>>> # xdoctest: +REQUIRES(--show)
>>> kwplot.show_if_requested()
```

`kwcoco.metrics.drawing.draw_threshold_curves(info, keys=None, prefix='', fnum=1, **kw)`

Parameters `info` (*Measures | Dict*)

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> import sys, ubelt
>>> sys.path.append(ubelt.expandpath('~/code/kwcoco'))
>>> from kwcoco.metrics.drawing import * # NOQA
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     nimgs=10, nboxes=(0, 10), n_fp=(0, 1), classes=3)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> info = cfsn_vecs.binarize_classless().measures()
>>> keys = None
>>> import kwplot
>>> kwplot.autopl()
>>> draw_threshold_curves(info, keys)
>>> # xdoctest: +REQUIRES(--show)
>>> kwplot.show_if_requested()
```

`kwcoco.metrics.functional`

Module Contents

Functions

<code>fast_confusion_matrix(y_true, y_pred, n_labels, sample_weight=None)</code>	faster version of sklearn confusion matrix that avoids the sample_weight=None
<code>_truncated_roc(y_df, bg_idx=-1, fp_cutoff=None)</code>	Computes truncated ROC info
<code>-pr_curves(y)</code>	Compute a PR curve from a method

continues on next page

Table 64 – continued from previous page

<code>_average_precision(tpr, ppv)</code>	Compute average precision of a binary PR curve. This is simply the area
---	---

`kwcoco.metrics.functional.fast_confusion_matrix(y_true, y_pred, n_labels, sample_weight=None)`
faster version of sklearn confusion matrix that avoids the expensive checks and label rectification

Parameters

- **y_true** (`ndarray[int]`) – ground truth class label for each sample
- **y_pred** (`ndarray[int]`) – predicted class label for each sample
- **n_labels** (`int`) – number of labels
- **sample_weight** (`ndarray[int|float]`) – weight of each sample

Returns matrix where rows represent real and cols represent pred and the value at each cell is the total amount of weight

Return type `ndarray[int64|float64, dim=2]`

Example

```
>>> y_true = np.array([0, 0, 0, 0, 1, 1, 1, 0, 1])
>>> y_pred = np.array([0, 0, 0, 0, 0, 0, 0, 1, 1])
>>> fast_confusion_matrix(y_true, y_pred, 2)
array([[4, 2],
       [3, 1]])
>>> fast_confusion_matrix(y_true, y_pred, 2).ravel()
array([4, 2, 3, 1])
```

`kwcoco.metrics.functional._truncated_roc(y_df, bg_idx=-1, fp_cutoff=None)`
Computes truncated ROC info

`kwcoco.metrics.functional._pr_curves(y)`
Compute a PR curve from a method

Parameters `y (pd.DataFrame | DataFrameArray)` – output of detection_confusions
Returns `Tuple[float, ndarray, ndarray]`

Example

```
>>> # xdoctest: +REQUIRES(module:sklearn)
>>> import pandas as pd
>>> y1 = pd.DataFrame.from_records([
>>>     {'pred': 0, 'score': 10.00, 'true': -1, 'weight': 1.00},
>>>     {'pred': 0, 'score': 1.65, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 8.64, 'true': -1, 'weight': 1.00},
>>>     {'pred': 0, 'score': 3.97, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 1.68, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 5.06, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 0.25, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 1.75, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 8.52, 'true': 0, 'weight': 1.00},
```

(continues on next page)

(continued from previous page)

```
>>>     {'pred': 0, 'score': 5.20, 'true': 0, 'weight': 1.00},  
>>> ])  
>>> import kwcoco as nh  
>>> import kwarray  
>>> y2 = kwarray.DataFrameArray(y1)  
>>> _pr_curves(y2)  
>>> _pr_curves(y1)
```

kwcoco.metrics.functional._average_precision(*tpr, ppv*)

Compute average precision of a binary PR curve. This is simply the area under the curve.

Parameters

- **tpr** (*ndarray*) – true positive rate - aka recall
- **ppv** (*ndarray*) – positive predictive value - aka precision

kwcoco.metrics.sklearn_alts

Faster pure-python versions of sklearn functions that avoid expensive checks and label rectifications. It is assumed that all labels are consecutive non-negative integers.

Module Contents

Functions

confusion_matrix(*y_true, y_pred, n_labels=None, labels=None, sample_weight=None*) faster version of sklearn confusion matrix that avoids the

global_accuracy_from_confusion(*cfsn*)

class_accuracy_from_confusion(*cfsn*)

_binary_clf_curve2(*y_true, y_score, pos_label=None, sample_weight=None*) MODIFIED VERSION OF SCIKIT-LEARN API

kwcoco.metrics.sklearn_alts.confusion_matrix(*y_true, y_pred, n_labels=None, labels=None, sample_weight=None*)

faster version of sklearn confusion matrix that avoids the expensive checks and label rectification

Runs in about 0.7ms

Returns matrix where rows represent real and cols represent pred

Return type ndarray

Example

```
>>> y_true = np.array([0, 0, 0, 0, 1, 1, 1, 0, 1])
>>> y_pred = np.array([0, 0, 0, 0, 0, 0, 1, 1, 1])
>>> confusion_matrix(y_true, y_pred, 2)
array([[4, 2],
       [3, 1]])
>>> confusion_matrix(y_true, y_pred, 2).ravel()
array([4, 2, 3, 1])
```

Benchmarks: import ubelt as ub
`y_true = np.random.randint(0, 2, 10000)`
`y_pred = np.random.randint(0, 2, 10000)`

`n = 1000` for timer in ub.Timerit(n, bestof=10, label='py-time'):

```
    sample_weight = [1] * len(y_true)  confusion_matrix(y_true, y_pred, 2, sample_weight=sample_weight)
```

```
for timer in ub.Timerit(n, bestof=10, label='np-time'):
    sample_weight = np.ones(len(y_true), dtype=int)  confusion_matrix(y_true, y_pred, 2, sample_weight=sample_weight)
```

`kwcococo.metrics.sklearn_alts.global_accuracy_from_confusion(cfsn)`

`kwcococo.metrics.sklearn_alts.class_accuracy_from_confusion(cfsn)`

`kwcococo.metrics.sklearn_alts._binary_clf_curve2(y_true, y_score, pos_label=None, sample_weight=None)`

MODIFIED VERSION OF SCIKIT-LEARN API

Calculate true and false positives per binary classification threshold.

Parameters

- **y_true** (*array, shape = [n_samples]*) – True targets of binary classification
- **y_score** (*array, shape = [n_samples]*) – Estimated probabilities or decision function
- **pos_label** (*int or str, default=None*) – The label of the positive class
- **sample_weight** (*array-like of shape (n_samples,), default=None*) – Sample weights.

Returns

- **fps** (*array, shape = [n_thresholds]*) – A count of false positives, at index i being the number of negative samples assigned a score $\geq \text{thresholds}[i]$. The total number of negative samples is equal to `fps[-1]` (thus true negatives are given by `fps[-1] - fps`).
- **tps** (*array, shape = [n_thresholds <= len(np.unique(y_score))]*) – An increasing count of true positives, at index i being the number of positive samples assigned a score $\geq \text{thresholds}[i]$. The total number of positive samples is equal to `tps[-1]` (thus false negatives are given by `tps[-1] - tps`).
- **thresholds** (*array, shape = [n_thresholds]*) – Decreasing score values.

Example

```
>>> y_true = [    1,    1,    1,    1,    1,    0]
>>> y_score = [ np.nan, 0.2, 0.3, 0.4, 0.5, 0.6, 0.3]
>>> sample_weight = None
>>> pos_label = None
>>> fps, tps, thresholds = _binary_clf_curve2(y_true, y_score)
```

kwcoco.metrics.util

Module Contents

Classes

<i>DictProxy</i>	Allows an object to proxy the behavior of a dict attribute
----------------------------------	--

```
class kwcoco.metrics.util.DictProxy
Bases: scriptconfig.dict_like.DictLike

Allows an object to proxy the behavior of a dict attribute

__getitem__(self, key)
__setitem__(self, key, value)
keys(self)
__json__(self)
```

kwcoco.metrics.voc_metrics

Module Contents

Classes

<i>VOC_Metrics</i>	API to compute object detection scores using Pascal VOC evaluation method.
------------------------------------	--

Functions

<i>_pr_curves</i>(y, method='voc2012')	Compute a PR curve from a method
<i>_voc_eval</i>(lines, recs, classname, iou_thresh=0.5, method='voc2012', bias=1.0)	VOC AP evaluation for a single category.
<i>_voc_ave_precision</i>(rec, prec, method='voc2012')	Compute AP from precision and recall

```
class kwcoco.metrics.voc_metrics.VOC_Metrics(classes=None)
Bases: ubelt.NiceRepr
```

API to compute object detection scores using Pascal VOC evaluation method.

To use, add true and predicted detections for each image and then run the `VOC_Metrics.score()` function.

Variables

- `recs` (`Dict[int, List[dict]]`) – true boxes for each image. maps image ids to a list of records within that image. Each record is a tlbr bbox, a difficult flag, and a class name.
- `cx_to_lines` (`Dict[int, List]`) – VOC formatted prediction predictions. mapping from class index to all predictions for that category. Each “line” is a list of [

[<imgid>, <score>, <tl_x>, <tl_y>, <br_x>, <br_y>]].

```
__nice__(self)
add_truth(self, true_dets, gid)
add_predictions(self, pred_dets, gid)
score(self, iou_thresh=0.5, bias=1, method='voc2012')
Compute VOC scores for every category
```

Example

```
>>> from kwcoco.metrics.detect_metrics import DetectionMetrics
>>> from kwcoco.metrics.voc_metrics import * # NOQA
>>> dmet = DetectionMetrics.demo()
>>> nimgs=1, nboxes=(0, 100), n_fp=(0, 30), n_fn=(0, 30), classes=2, score_
>>> _noise=0.9
>>> self = VOC_Metrics(classes=dmet.classes)
>>> self.add_truth(dmet.true_detections(0), 0)
>>> self.add_predictions(dmet.pred_detections(0), 0)
>>> voc_scores = self.score()
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()l()
>>> kwplot.figure(fnum=1, doclf=True)
>>> voc_scores['perclass'].draw()
```

```
kwplot.figure(fnum=2)      dmet.true_detections(0).draw(color='green',           labels=None)
dmet.pred_detections(0).draw(color='blue',   labels=None)  kwplot.autopl().gca().set_xlim(0, 100)
kwplot.autopl().gca().set_ylim(0, 100)
```

`kwcoco.metrics.voc_metrics._pr_curves(y, method='voc2012')`

Compute a PR curve from a method

Parameters `y` (`pd.DataFrame | DataFrameArray`) – output of `detection_confusions`

Returns `Tuple[float, ndarray, ndarray]`

Example

```
>>> import pandas as pd
>>> y1 = pd.DataFrame.from_records([
>>>     {'pred': 0, 'score': 10.00, 'true': -1, 'weight': 1.00},
>>>     {'pred': 0, 'score': 1.65, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 8.64, 'true': -1, 'weight': 1.00},
>>>     {'pred': 0, 'score': 3.97, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 1.68, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 5.06, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 0.25, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 1.75, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 8.52, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 5.20, 'true': 0, 'weight': 1.00},
>>> ])
>>> import kwarray
>>> y2 = kwarray.DataFrameArray(y1)
>>> _pr_curves(y2)
>>> _pr_curves(y1)
```

```
kwcoco.metrics.voc_metrics._voc_eval(lines, recs, classname, iou_thresh=0.5, method='voc2012',
                                         bias=1.0)
```

VOC AP evaluation for a single category.

Parameters

- **lines** (*List[list]*) – VOC formatted predictions. Each “line” is a list of [[<imgid>, <score>, <tl_x>, <tl_y>, <br_x>, <br_y>]].
- **recs** (*Dict[int, List[dict]]*) – true boxes for each image. maps image ids to a list of records within that image. Each record is a tlbr bbox, a difficult flag, and a class name.
- **classname** (*str*) – the category to evaluate.
- **method** (*str*) – code for how the AP is computed.
- **bias** (*float*) – either 1.0 or 0.0.

Returns info about the evaluation containing AP. Contains fp, tp, prec, rec,

Return type Dict

Note: Raw replication of matlab implementation of creating assignments and the resulting PR-curves and AP. Based on MATLAB code [1].

References

[1] http://host.robots.ox.ac.uk/pascal/VOC/voc2012/VOCdevkit_18-May-2011.tar

```
kwcoco.metrics.voc_metrics._voc_ave_precision(rec, prec, method='voc2012')
```

Compute AP from precision and recall Based on MATLAB code in¹, ², and³.

Parameters

¹ http://host.robots.ox.ac.uk/pascal/VOC/voc2012/VOCdevkit_18-May-2011.tar

² https://github.com/rbgirshick/voc-dpm/blob/master/test/pascal_eval.m

³ https://github.com/rbgirshick/voc-dpm/blob/c0b88564bd668bcc6216bbffe96cb061613be768/utils/bootstrap/VOCevaldet_bootstrap.m

- **rec** (*ndarray*) – recall
- **prec** (*ndarray*) – precision
- **method** (*str*) – either voc2012 or voc2007

Returns ap: average precision

Return type float

References

Package Contents

Classes

<i>DetectionMetrics</i>	Object that computes associations between detections and can convert them
<i>BinaryConfusionVectors</i>	Stores information about a binary classification problem.
<i>ConfusionVectors</i>	Stores information used to construct a confusion matrix. This includes
<i>Measures</i>	Holds accumulated confusion counts, and derived measures
<i>OneVsRestConfusionVectors</i>	Container for multiple one-vs-rest binary confusion vectors
<i>PerClass_Measures</i>	

Functions

<code>eval_detections_cli(**kw)</code>	DEPRECATED USE <code>kwcoco eval</code> instead
--	---

`class kwcoco.metrics.DetectionMetrics(dmet, classes=None)`

Bases: `ubelt.NiceRepr`

Object that computes associations between detections and can convert them into sklearn-compatible representations for scoring.

Variables

- **gid_to_true_dets** (*Dict*) – maps image ids to truth
- **gid_to_pred_dets** (*Dict*) – maps image ids to predictions
- **classes** (*CategoryTree*) – category coder

Example

```
>>> dmet = DetectionMetrics.demo(  
>>>     nimgs=100, nboxes=(0, 3), n_fp=(0, 1), classes=8, score_noise=0.9,  
>>>     hacked=False)  
>>> print(dmet.score_kwCOCO(bias=0, compat='mutex', prioritize='iou')['mAP'])  
...  
>>> # NOTE: IN GENERAL NETHARN AND VOC ARE NOT THE SAME  
>>> print(dmet.score_voc(bias=0)['mAP'])  
0.8582...  
>>> #print(dmet.score_coco()['mAP'])
```

`score_coco`

`clear(dmet)`

`__nice__(dmet)`

`classmethod from_coco(DetectionMetrics, true_coco, pred_coco, gids=None, verbose=0)`

Create detection metrics from two coco files representing the truth and predictions.

Parameters

- `true_coco` (`kwCOCO.CocoDataset`)
- `pred_coco` (`kwCOCO.CocoDataset`)

Example

```
>>> import kwCOCO  
>>> from kwCOCO.demo.perterb import perterb_coco  
>>> true_coco = kwCOCO.CocoDataset.demo('shapes')  
>>> perterbkw = dict(box_noise=0.5, cls_noise=0.5, score_noise=0.5)  
>>> pred_coco = perterb_coco(true_coco, **perterbkw)  
>>> self = DetectionMetrics.from_coco(true_coco, pred_coco)  
>>> self.score_voc()
```

`_register_imagename(dmet, imgname, gid=None)`

`add_predictions(dmet, pred_dets, imgname=None, gid=None)`

Register/Add predicted detections for an image

Parameters

- `pred_dets` (`Detections`) – predicted detections
- `imgname` (`str`) – a unique string to identify the image
- `gid` (`int, optional`) – the integer image id if known

`add_truth(dmet, true_dets, imgname=None, gid=None)`

Register/Add groundtruth detections for an image

Parameters

- `true_dets` (`Detections`) – groundtruth
- `imgname` (`str`) – a unique string to identify the image
- `gid` (`int, optional`) – the integer image id if known

true_detections(*dmet, gid*)

gets Detections representation for groundtruth in an image

pred_detections(*dmet, gid*)

gets Detections representation for predictions in an image

confusion_vectors(*dmet, iou_thresh=0.5, bias=0, gids=None, compat='mutex', prioritize='iou', ignore_classes='ignore', background_class=ub.NoParam, verbose='auto', workers=0, track_probs='try', max_dets=None*)

Assigns predicted boxes to the true boxes so we can transform the detection problem into a classification problem for scoring.

Parameters

- **iou_thresh** (*float | List[float], default=0.5*) – bounding box overlap iou threshold required for assignment if a list, then return type is a dict
- **bias** (*float, default=0.0*) – for computing bounding box overlap, either 1 or 0
- **gids** (*List[int], default=None*) – which subset of images ids to compute confusion metrics on. If not specified all images are used.
- **compat** (*str, default='all'*) – can be ('ancestors' | 'mutex' | 'all'). determines which pred boxes are allowed to match which true boxes. If 'mutex', then pred boxes can only match true boxes of the same class. If 'ancestors', then pred boxes can match true boxes that match or have a coarser label. If 'all', then any pred can match any true, regardless of its category label.
- **prioritize** (*str, default='iou'*) – can be ('iou' | 'class' | 'correct') determines which box to assign to if multiple true boxes overlap a predicted box. if prioritize is iou, then the true box with maximum iou (above iou_thresh) will be chosen. If prioritize is class, then it will prefer matching a compatible class above a higher iou. If prioritize is correct, then ancestors of the true class are preferred over descendants of the true class, over unrelated classes.
- **ignore_classes** (*set, default={'ignore'}*) – class names indicating ignore regions
- **background_class** (*str, default=ub.NoParam*) – Name of the background class. If unspecified we try to determine it with heuristics. A value of None means there is no background class.
- **verbose** (*int, default='auto'*) – verbosity flag. In auto mode, verbose=1 if len(gids) > 1000.
- **workers** (*int, default=0*) – number of parallel assignment processes
- **track_probs** (*str, default='try'*) – can be 'try', 'force', or False. if truthy, we assume probabilities for multiple classes are available.

Returns ConfusionVectors | Dict[float, ConfusionVectors]

Example

```
>>> dmet = DetectionMetrics.demo(nimgs=30, classes=3,
>>>                               nboxes=10, n_fp=3, box_noise=10,
>>>                               with_probs=False)
>>> iou_to_cfsn = dmet.confusion_vectors(iou_thresh=[0.3, 0.5, 0.9])
>>> for t, cfsn in iou_to_cfsn.items():
>>>     print('t = {!r}'.format(t))
```

(continues on next page)

(continued from previous page)

```
...     print(cfsn.binarize_ovr().measures())
...     print(cfsn.binarize_classless().measures())
```

score_kwant(*dmet*, *iou_thresh*=0.5)

Scores the detections using kwant

score_kwccoco(*dmet*, *iou_thresh*=0.5, *bias*=0, *gids*=None, *compat*='all', *prioritize*='iou')

our scoring method

score_voc(*dmet*, *iou_thresh*=0.5, *bias*=1, *method*='voc2012', *gids*=None, *ignore_classes*='ignore')

score using voc method

Example

```
>>> dmet = DetectionMetrics.demo()
>>> nimgs=100, nboxes=(0, 3), n_fp=(0, 1), classes=8,
>>> score_noise=.5
>>> print(dmet.score_voc()['mAP'])
0.9399...
```

_to_coco(*dmet*)

Convert to a coco representation of truth and predictions

with inverse aid mappings

score_pycocotools(*dmet*, *with_evaler*=False, *with_confusion*=False, *verbose*=0, *iou_thresholds*=None)

score using ms-coco method

Returns dictionary with pct info**Return type** Dict**Example**

```
>>> # xdoctest: +REQUIRES(module:pycocotools)
>>> from kwccoco.metrics.detect_metrics import *
>>> dmet = DetectionMetrics.demo()
>>> nimgs=10, nboxes=(0, 3), n_fn=(0, 1), n_fp=(0, 1), classes=8, with_
>>> _probs=False
>>> pct_info = dmet.score_pycocotools(verbose=1,
>>>                               with_evaler=True,
>>>                               with_confusion=True,
>>>                               iou_thresholds=[0.5, 0.9])
>>> evaler = pct_info['evaler']
>>> iou_to_cfsn_vecs = pct_info['iou_to_cfsn_vecs']
>>> for iou_thresh in iou_to_cfsn_vecs.keys():
>>>     print('iou_thresh = {!r}'.format(iou_thresh))
>>>     cfsn_vecs = iou_to_cfsn_vecs[iou_thresh]
>>>     ovr_measures = cfsn_vecs.binarize_ovr().measures()
>>>     print('ovr_measures = {}'.format(ub.repr2(ovr_measures, nl=1,
>>>                                         precision=4)))
```

Note: by default pycocotools computes average precision as the literal average of computed precisions at 101 uniformly spaced recall thresholds.

pycocoutils seems to only allow predictions with the same category as the truth to match those truth objects. This should be the same as calling dmet.confusion_vectors with compat = mutex

pycocoutils does not take into account the fact that each box often has a score for each category.

pycocoutils will be incorrect if any annotation has an id of 0

a major difference in the way kwcoco scores versus pycocoutils is the calculation of AP. The assignment between truth and predicted detections produces similar enough results. Given our confusion vectors we use the scikit-learn definition of AP, whereas pycocoutils seems to compute precision and recall — more or less correctly — but then it resamples the precision at various specified recall thresholds (in the *accumulate* function, specifically how *pr* is resampled into the *q* array). This can lead to a large difference in reported scores.

pycocoutils also smooths out the precision such that it is monotonic decreasing, which might not be the best idea.

pycocotools area ranges are inclusive on both ends, that means the “small” and “medium” truth selections do overlap somewhat.

classmethod demo(*cls*, *kwargs*)**

Creates random true boxes and predicted boxes that have some noisy offset from the truth.

Kwargs:

classes (int, default=1): class list or the number of foreground classes.

nimgs (int, default=1): number of images in the coco datasets. nboxes (int, default=1): boxes per image. n_fp (int, default=0): number of false positives. n_fn (int, default=0): number of false negatives. box_noise (float, default=0): std of a normal distribution used to

perterb both box location and box size.

cls_noise (float, default=0): probability that a class label will change. Must be within 0 and 1.

anchors (ndarray, default=None): used to create random boxes null_pred (bool, default=False):

if True, predicted classes are returned as null, which means only localization scoring is suitable.

with_probs (bool, default=True): if True, includes per-class probabilities with predictions

CommandLine

```
xdoctest -m kwcoco.metrics.detect_metrics DetectionMetrics.demo:2 --show
```

Example

```
>>> kwargs = {}
>>> # Seed the RNG
>>> kwargs['rng'] = 0
>>> # Size parameters determine how big the data is
>>> kwargs['nimgs'] = 5
>>> kwargs['nboxes'] = 7
>>> kwargs['classes'] = 11
>>> # Noise parameters perterb predictions further from the truth
>>> kwargs['n_fp'] = 3
>>> kwargs['box_noise'] = 0.1
>>> kwargs['cls_noise'] = 0.5
>>> dmet = DetectionMetrics.demo(**kwargs)
>>> print('dmet.classes = {}'.format(dmet.classes))
dmet.classes = <CategoryTree(nNodes=12, maxDepth=3, maxBreadth=4...)>
>>> # Can grab kwimage.Detection object for any image
>>> print(dmet.true_detections(gid=0))
<Detections(4)>
>>> print(dmet.pred_detections(gid=0))
<Detections(7)>
```

Example

```
>>> # Test case with null predicted categories
>>> dmet = DetectionMetrics.demo(nimgs=30, null_pred=1, classes=3,
>>>                               nboxes=10, n_fp=3, box_noise=0.1,
>>>                               with_probs=False)
>>> dmet.gid_to_pred_dets[0].data
>>> dmet.gid_to_true_dets[0].data
>>> cfsn_vecs = dmet.confusion_vectors()
>>> binvecs_ovr = cfsn_vecs.binarize_ovr()
>>> binvecs_per = cfsn_vecs.binarize_classless()
>>> measures_per = binvecs_per.measures()
>>> measures_ovr = binvecs_ovr.measures()
>>> print('measures_per = {!r}'.format(measures_per))
>>> print('measures_ovr = {!r}'.format(measures_ovr))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> measures_ovr['perclass'].draw(key='pr', fnum=2)
```

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> from kwcoco.metrics.detect_metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     n_fp=(0, 1), n_fn=(0, 1), nimgs=32, nboxes=(0, 16),
>>>     classes=3, rng=0, newstyle=1, box_noise=0.5, cls_noise=0.0, score_
>>> _noise=0.3, with_probs=False)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> summary = dmet.summarize(plot=True, title='DetectionMetrics summary demo', u
>>> _with_ovr=True, with_bin=False)
>>> summary['bin_measures']
>>> kwplot.show_if_requested()
```

`summarize(dmet, out_dpath=None, plot=False, title='', with_bin='auto', with_ovr='auto')`

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> from kwcoco.metrics.detect_metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     n_fp=(0, 128), n_fn=(0, 4), nimgs=512, nboxes=(0, 32),
>>>     classes=3, rng=0)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> dmet.summarize(plot=True, title='DetectionMetrics summary demo')
>>> kwplot.show_if_requested()
```

`kwcoco.metrics.eval_detections_cli(**kw)`

DEPRECATED USE `kwcoco eval` instead

CommandLine

```
xdoctest -m ~/code/kwcoco/kwcoco/metrics/detect_metrics.py eval_detections_cli
```

`class kwcoco.metrics.BinaryConfusionVectors(data, cx=None, classes=None)`

Bases: `ubelt.NiceRepr`

Stores information about a binary classification problem. This is always with respect to a specific class, which is given by `cx` and `classes`.

The `data DataFrameArray` must contain `is_true` - if the row is an instance of class `classes[cx]` `pred_score` - the predicted probability of class `classes[cx]`, and `weight` - sample weight of the example

Example

```
>>> from kwcococo.metrics.confusion_vectors import * # NOQA
>>> self = BinaryConfusionVectors.demo(n=10)
>>> print('self = {!r}'.format(self))
>>> print('measures = {}'.format(ub.repr2(self.measures())))
```

```
>>> self = BinaryConfusionVectors.demo(n=0)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
```

```
>>> self = BinaryConfusionVectors.demo(n=1)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
```

```
>>> self = BinaryConfusionVectors.demo(n=2)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
```

classmethod demo(cls, n=10, p_true=0.5, p_error=0.2, p_miss=0.0, rng=None)

Create random data for tests

Parameters

- **n** (*int*) – number of rows
- **p_true** (*int*) – fraction of real positive cases
- **p_error** (*int*) – probability of making a recoverable mistake
- **p_miss** (*int*) – probability of making a unrecoverable mistake
- **rng** (*int | RandomState*) – random seed / state

Returns BinaryConfusionVectors

Example

```
>>> from kwcococo.metrics.confusion_vectors import * # NOQA
>>> cfsn = BinaryConfusionVectors.demo(n=1000, p_error=0.1, p_miss=0.1)
>>> measures = cfsn.measures()
>>> print('measures = {}'.format(ub.repr2(measures, nl=1)))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.figure(fnum=1, pnum=(1, 2, 1))
>>> measures.draw('pr')
>>> kwplot.figure(fnum=1, pnum=(1, 2, 2))
>>> measures.draw('roc')
```

property catname(self)

__nice__(self)

__len__(self)

measures(self, stabalize_thresh=7, fp_cutoff=None, monotonic_ppv=True, ap_method='pycocotools')

Get statistics (F1, G1, MCC) versus thresholds

Parameters

- **stabalize_thresh** (*int, default=7*) – if fewer than this many data points inserts dummy stabilization data so curves can still be drawn.
- **fp_cutoff** (*int, default=None*) – maximum number of false positives in the truncated roc curves. None is equivalent to `float('inf')`
- **monotonic_ppv** (*bool, default=True*) – if True ensures that precision is always increasing as recall decreases. This is done in pycocotools scoring, but I'm not sure its a good idea.

Example

```
>>> from kwcococo.metrics.confusion_vectors import * # NOQA
>>> self = BinaryConfusionVectors.demo(n=0)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
>>> self = BinaryConfusionVectors.demo(n=1, p_true=0.5, p_error=0.5)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
>>> self = BinaryConfusionVectors.demo(n=3, p_true=0.5, p_error=0.5)
>>> print('measures = {}'.format(ub.repr2(self.measures())))

>>> self = BinaryConfusionVectors.demo(n=100, p_true=0.5, p_error=0.5, p_miss=0.
   ↪3)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
>>> print('measures = {}'.format(ub.repr2(ub.odict(self.measures()))))
```

References

https://en.wikipedia.org/wiki/Confusion_matrix https://en.wikipedia.org/wiki/Precision_and_recall https://en.wikipedia.org/wiki/Matthews_correlation_coefficient

`_binary_clf_curves(self, stabalize_thresh=7, fp_cutoff=None)`

Compute TP, FP, TN, and FN counts for this binary confusion vector.

Code common to ROC, PR, and threshold measures, computes the elements of the binary confusion matrix at all relevant operating point thresholds.

Parameters

- **stabalize_thresh** (*int*) – if fewer than this many data points insert stabilization data.
- **fp_cutoff** (*int*) – maximum number of false positives

Example

```
>>> from kwcococo.metrics.confusion_vectors import * # NOQA
>>> self = BinaryConfusionVectors.demo(n=1, p_true=0.5, p_error=0.5)
>>> self._binary_clf_curves()

>>> self = BinaryConfusionVectors.demo(n=0, p_true=0.5, p_error=0.5)
>>> self._binary_clf_curves()

>>> self = BinaryConfusionVectors.demo(n=100, p_true=0.5, p_error=0.5)
>>> self._binary_clf_curves()
```

```
draw_distribution(self)
_3dplot(self)
```

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> from kwcoco.metrics.detect_metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     n_fp=(0, 1), n_fn=(0, 2), nimgs=256, nboxes=(0, 10),
>>>     bbox_noise=10,
>>>     classes=1)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> self = bin_cfsn = cfsn_vecs.binarize_classless()
>>> #dmet.summarize(plot=True)
>>> import kwplot
>>> kwplot.autopl()l()
>>> kwplot.figure(fnum=3)
>>> self._3dplot()
```

class kwcoco.metrics.ConfusionVectors(*cfsn_vecs*, *data*, *classes*, *probs=None*)
Bases: `ubelt.NiceRepr`

Stores information used to construct a confusion matrix. This includes corresponding vectors of predicted labels, true labels, sample weights, etc...

Variables

- ***data*** (`kwarray.DataFrameArray`) – should at least have keys true, pred, weight
- ***classes*** (`Sequence` / `CategoryTree`) – list of category names or category graph
- ***probs*** (`ndarray`, *optional*) – probabilities for each class

Example

```
>>> # xdoctest: IGNORE_WANT
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     nimgs=10, nboxes=(0, 10), n_fp=(0, 1), classes=3)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> print(cfsn_vecs.data._pandas())
   pred  true    score  weight      iou    txs    pxs    gid
0      2      2  10.0000  1.0000  1.0000      0      4      0
1      2      2   7.5025  1.0000  1.0000      1      3      0
2      1      1   5.0050  1.0000  1.0000      2      2      0
3      3     -1   2.5075  1.0000 -1.0000     -1      1      0
4      2     -1   0.0100  1.0000 -1.0000     -1      0      0
5     -1      2   0.0000  1.0000 -1.0000      3     -1      0
6     -1      2   0.0000  1.0000 -1.0000      4     -1      0
7      2      2  10.0000  1.0000  1.0000      0      5      1
```

(continues on next page)

(continued from previous page)

8	2	2	8.0020	1.0000	1.0000	1	4	1
9	1	1	6.0040	1.0000	1.0000	2	3	1
..
62	-1	2	0.0000	1.0000	-1.0000	7	-1	7
63	-1	3	0.0000	1.0000	-1.0000	8	-1	7
64	-1	1	0.0000	1.0000	-1.0000	9	-1	7
65	1	-1	10.0000	1.0000	-1.0000	-1	0	8
66	1	1	0.0100	1.0000	1.0000	0	1	8
67	3	-1	10.0000	1.0000	-1.0000	-1	3	9
68	2	2	6.6700	1.0000	1.0000	0	2	9
69	2	2	3.3400	1.0000	1.0000	1	1	9
70	3	-1	0.0100	1.0000	-1.0000	-1	0	9
71	-1	2	0.0000	1.0000	-1.0000	2	-1	9

```
>>> # xdoctest: +REQUIRES(--show)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> import kwplot
>>> kwplot.autopl()
>>> from kwcoco.metrics.confusion_vectors import ConfusionVectors
>>> cfsn_vecs = ConfusionVectors.demo(
    nimgs=128, nboxes=(0, 10), n_fp=(0, 3), n_fn=(0, 3), classes=3)
>>> cx_to_binvecs = cfsn_vecs.binarize_ovr()
>>> measures = cx_to_binvecs.measures()['perclass']
>>> print('measures = {!r}'.format(measures))
measures = <PerClass_Measures({
    'cat_1': <Measures({'ap': 0.227, 'auc': 0.507, 'catname': cat_1, 'max_f1': f1=0.
    ↵45@0.47, 'nsupport': 788.000})>,
    'cat_2': <Measures({'ap': 0.288, 'auc': 0.572, 'catname': cat_2, 'max_f1': f1=0.
    ↵51@0.43, 'nsupport': 788.000})>,
    'cat_3': <Measures({'ap': 0.225, 'auc': 0.484, 'catname': cat_3, 'max_f1': f1=0.
    ↵46@0.40, 'nsupport': 788.000})>,
}) at 0x7facf77bdf0>
>>> kwplot.figure(fnum=1, doclf=True)
>>> measures.draw(key='pr', fnum=1, pnum=(1, 3, 1))
>>> measures.draw(key='roc', fnum=1, pnum=(1, 3, 2))
>>> measures.draw(key='mcc', fnum=1, pnum=(1, 3, 3))
...

```

nice(cfsn_vecs)_json_(self)

Serialize to json

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics import ConfusionVectors
>>> self = ConfusionVectors.demo(n_imgs=1, classes=2, n_fp=0, nboxes=1)
>>> state = self._json_()
>>> print('state = {}'.format(ub.repr2(state, nl=2, precision=2, align=1)))
>>> recon = ConfusionVectors.from_json(state)
```

classmethod `from_json`(`cls, state`)
classmethod `demo`(`cfsn_vecs, **kw`)

Parameters `**kwargs` – See `kwcoco.metrics.DetectionMetrics.demo()`

Returns `ConfusionVectors`

Example

```
>>> cfsn_vecs = ConfusionVectors.demo()
>>> print('cfsn_vecs = {!r}'.format(cfsn_vecs))
>>> cx_to_binvecs = cfsn_vecs.binarize_ovr()
>>> print('cx_to_binvecs = {!r}'.format(cx_to_binvecs))
```

classmethod `from_arrays`(`ConfusionVectors, true, pred=None, score=None, weight=None, probs=None, classes=None`)

Construct confusion vector data structure from component arrays

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> import kwarray
>>> classes = ['person', 'vehicle', 'object']
>>> rng = kwarray.ensure_rng(0)
>>> true = (rng.rand(10) * len(classes)).astype(int)
>>> probs = rng.rand(len(true), len(classes))
>>> cfsn_vecs = ConfusionVectors.from_arrays(true=true, probs=probs, u
  _classes=classes)
>>> cfsn_vecs.confusion_matrix()
pred      person    vehicle    object
real
person        0        0        0
vehicle        2        4        1
object        2        1        0
```

confusion_matrix(`cfsn_vecs, compress=False`)

Builds a confusion matrix from the confusion vectors.

Parameters `compress` (`bool, default=False`) – if True removes rows / columns with no entries

Returns

`cm` [the labeled confusion matrix]

(Note: we should write a efficient replacement for this use case. #remove_pandas)

Return type pd.DataFrame

CommandLine

```
xdoctest -m kwcoco.metrics.confusion_vectors ConfusionVectors.confusion_matrix
```

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo()
>>> nimgs=10, nboxes=(0, 10), n_fp=(0, 1), n_fn=(0, 1), classes=3, cls_noise=.2
>>> cfsn_vecs = dmet.confusion_vectors()
>>> cm = cfsn_vecs.confusion_matrix()
...
>>> print(cm.to_string(float_format=lambda x: '%.2f' % x))
pred      background  cat_1  cat_2  cat_3
real
background      0.00   1.00   2.00   3.00
cat_1           3.00  12.00   0.00   0.00
cat_2           3.00   0.00  14.00   0.00
cat_3           2.00   0.00   0.00  17.00
```

coarsen(*cfsn_vecs*, *cxs*)

Creates a coarsened set of vectors

Returns ConfusionVectors

binarize_classless(*cfsn_vecs*, *negative_classes=None*)

Creates a binary representation useful for measuring the performance of detectors. It is assumed that scores of “positive” classes should be high and “negative” classes should be low.

Parameters *negative_classes* (*List[str | int]*) – list of negative class names or idxs, by default chooses any class with a true class index of -1. These classes should ideally have low scores.

Returns BinaryConfusionVectors

Note: The “classlessness” of this depends on the *compat=”all”* argument being used when constructing confusion vectors, otherwise it becomes something like a macro-average because the class information was used in deciding which true and predicted boxes were allowed to match.

Example

```
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo()
>>> nimgs=10, nboxes=(0, 10), n_fp=(0, 1), n_fn=(0, 1), classes=3
>>> cfsn_vecs = dmet.confusion_vectors()
>>> class_idxs = list(dmet.classes.node_to_idx.values())
>>> binvecs = cfsn_vecs.binarize_classless()
```

binarize_ovr(*cfsn_vecs*, *mode*=1, *keyby*='name', *ignore_classes*={'ignore'}, *approx*=0)
Transforms *cfsn_vecs* into one-vs-rest BinaryConfusionVectors for each category.

Parameters

- **mode** (*int, default=1*) – 0 for heirarchy aware or 1 for voc like. MODE 0 IS PROBABLY BROKEN
- **keyby** (*int | str*) – can be cx or name
- **ignore_classes** (*Set[str]*) – category names to ignore
- **approx** (*bool, default=0*) – if True try and approximate missing scores otherwise assume they are irrecoverable and use -inf

Returns

which behaves like Dict[int, BinaryConfusionVectors]: cx_to_binvecs

Return type *OneVsRestConfusionVectors*

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> cfsn_vecs = ConfusionVectors.demo()
>>> print('cfsn_vecs = {!r}'.format(cfsn_vecs))
>>> catname_to_binvecs = cfsn_vecs.binarize_ovr(keyby='name')
>>> print('catname_to_binvecs = {!r}'.format(catname_to_binvecs))
```

cfsn_vecs.data.pandas() *catname_to_binvecs*.cx_to_binvecs['class_1'].data.pandas()

Note:

classification_report(*cfsn_vecs*, *verbose*=0)
Build a classification report with various metrics.

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> cfsn_vecs = ConfusionVectors.demo()
>>> report = cfsn_vecs.classification_report(verbose=1)
```

class kwcoco.metrics.Measures(*info*)
Bases: *ubelt.NiceRepr*, *kwcoco.metrics.util.DictProxy*

Holds accumulated confusion counts, and derived measures

Example

```
>>> from kwcoco.metrics.confusion_vectors import BinaryConfusionVectors # NOQA
>>> binvecs = BinaryConfusionVectors.demo(n=100, p_error=0.5)
>>> self = binvecs.measures()
>>> print('self = {!r}'.format(self))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> self.draw(doclf=True)
>>> self.draw(key='pr', pnum=(1, 2, 1))
>>> self.draw(key='roc', pnum=(1, 2, 2))
>>> kwplot.show_if_requested()
```

```
property catname(self)
__nice__(self)
reconstruct(self)
classmethod from_json(cls, state)
__json__(self)
```

Example

```
>>> from kwcoco.metrics.confusion_vectors import BinaryConfusionVectors # NOQA
>>> binvecs = BinaryConfusionVectors.demo(n=10, p_error=0.5)
>>> self = binvecs.measures()
>>> info = self.__json__()
>>> print('info = {}'.format(ub.repr2(info, nl=1)))
>>> populate_info(info)
>>> print('info = {}'.format(ub.repr2(info, nl=1)))
>>> recon = Measures.from_json(info)
```

```
summary(self)
maximized_thresholds(self)
    Returns thresholds that maximize metrics.
counts(self)
draw(self, key=None, prefix='', **kw)
```

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcococo.metrics.confusion_vectors import ConfusionVectors # NOQA
>>> cfsn_vecs = ConfusionVectors.demo()
>>> ovr_cfsn = cfsn_vecs.binarize_ovr(keyby='name')
>>> self = ovr_cfsn.measures()['perclass']
>>> self.draw('mcc', doclf=True, fnum=1)
>>> self.draw('pr', doclf=1, fnum=2)
>>> self.draw('roc', doclf=1, fnum=3)
```

```
summary_plot(self,fnum=1, title='', subplots='auto')
```

Example

```
>>> from kwcococo.metrics.confusion_measures import * # NOQA
>>> from kwcococo.metrics.confusion_vectors import ConfusionVectors # NOQA
>>> cfsn_vecs = ConfusionVectors.demo(n=3, p_error=0.5)
>>> binvecs = cfsn_vecs.binarize_classless()
>>> self = binvecs.measures()
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> self.summary_plot()
>>> kwplot.show_if_requested()
```

```
classmethod demo(cls, **kwargs)
```

Create a demo Measures object for testing / demos

Parameters ****kwargs** – passed to `BinaryConfusionVectors.demo()`. some valid keys are:
n, rng, p_rue, p_error, p_miss.

```
classmethod combine(cls, tocombine, precision=None, growth=None, thresh_bins=None)
```

Combine binary confusion metrics

Parameters

- **tocombine** (`List[Measures]`) – a list of measures to combine into one
- **precision** (`int | None`) – If specified rounds thresholds to this precision which can prevent a RAM explosion when combining a large number of measures. However, this is a lossy operation and will impact the underlying scores. NOTE: use `growth` instead.
- **growth** (`int | None`) – if specified this limits how much the resulting measures are allowed to grow by. If `None`, `growth` is unlimited. Otherwise, if `growth` is ‘`max`’, the `growth` is limited to the maximum length of an input. We might make this more numerical in the future.
- **thresh_bins** (`int`) – Force this many threshold bins.

Returns Measures

Example

```
>>> from kwcoco.metrics.confusion_measures import * # NOQA
>>> measures1 = Measures.demo(n=15)
>>> measures2 = measures1
>>> tocombine = [measures1, measures2]
>>> new_measures = Measures.combine(tocombine)
>>> new_measures.reconstruct()
>>> print('new_measures = {!r}'.format(new_measures))
>>> print('measures1 = {!r}'.format(measures1))
>>> print('measures2 = {!r}'.format(measures2))
>>> print(ub.repr2(measures1.__json__(), nl=1, sort=0))
>>> print(ub.repr2(measures2.__json__(), nl=1, sort=0))
>>> print(ub.repr2(new_measures.__json__(), nl=1, sort=0))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.figure(fnum=1)
>>> new_measures.summary_plot()
>>> measures1.summary_plot()
>>> measures1.draw('roc')
>>> measures2.draw('roc')
>>> new_measures.draw('roc')
```

Example

```
>>> # Demonstrate issues that can arise from choosing a precision
>>> # that is too low when combining metrics. Breakpoints
>>> # between different metrics can get muddled, but choosing a
>>> # precision that is too high can overwhelm memory.
>>> from kwcoco.metrics.confusion_measures import * # NOQA
>>> base = ub.map_vals(np.asarray, {
>>>     'tp_count': [ 1, 1, 2, 2, 2, 2, 3],
>>>     'fp_count': [ 0, 1, 1, 2, 3, 4, 5],
>>>     'fn_count': [ 1, 1, 0, 0, 0, 0, 0],
>>>     'tn_count': [ 5, 4, 4, 3, 2, 1, 0],
>>>     'thresholds': [.0, .0, .0, .0, .0, .0, .0],
>>> })
>>> # Make tiny offsets to thresholds
>>> rng = kwarray.ensure_rng(0)
>>> n = len(base['thresholds'])
>>> offsets = [
>>>     sorted(rng.rand(n) * 10 ** -rng.randint(4, 7))[::-1]
>>>     for _ in range(20)
>>> ]
>>> tocombine = []
>>> for offset in offsets:
>>>     base_n = base.copy()
>>>     base_n['thresholds'] += offset
>>>     measures_n = Measures(base_n).reconstruct()
>>>     tocombine.append(measures_n)
```

(continues on next page)

(continued from previous page)

```
>>> for precision in [6, 5, 2]:
>>>     combo = Measures.combine(tocombine, precision=precision).reconstruct()
>>>     print('precision = {!r}'.format(precision))
>>>     print('combo = {}'.format(ub.repr2(combo, nl=1)))
>>>     print('num_thresholds = {}'.format(len(combo['thresholds'])))
>>> for growth in [None, 'max', 'log', 'root', 'half']:
>>>     combo = Measures.combine(tocombine, growth=growth).reconstruct()
>>>     print('growth = {!r}'.format(growth))
>>>     print('combo = {}'.format(ub.repr2(combo, nl=1)))
>>>     print('num_thresholds = {}'.format(len(combo['thresholds'])))
>>> #print(combo.counts().pandas())
```

Example

```
>>> # Test case: combining a single measures should leave it unchanged
>>> from kwcoco.metrics.confusion_measures import * # NOQA
>>> measures = Measures.demo(n=40, p_true=0.2, p_error=0.4, p_miss=0.6)
>>> df1 = measures.counts().pandas().fillna(0)
>>> print(df1)
>>> tocombine = [measures]
>>> combo = Measures.combine(tocombine)
>>> df2 = combo.counts().pandas().fillna(0)
>>> print(df2)
>>> assert np.allclose(df1, df2)
```

```
>>> combo = Measures.combine(tocombine, thresh_bins=2)
>>> df3 = combo.counts().pandas().fillna(0)
>>> print(df3)
```

```
>>> # I am NOT sure if this is correct or not
>>> combo = Measures.combine(tocombine, thresh_bins=20)
>>> df4 = combo.counts().pandas().fillna(0)
>>> print(df4)
```

assert np.allclose(combo['thresholds'], measures['thresholds']) assert np.allclose(combo['fp_count'], measures['fp_count']) assert np.allclose(combo['tp_count'], measures['tp_count']) assert np.allclose(combo['tp_count'], measures['tp_count'])

class kwcoco.metrics.OneVsRestConfusionVectors(cx_to_binvecs, classes)

Bases: `ubelt.NiceRepr`

Container for multiple one-vs-rest binary confusion vectors

Variables

- `cx_to_binvecs` –
- `classes` –

Example

```
>>> from kwCOCO.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     nImgs=10, nBoxes=(0, 10), n_fp=(0, 1), classes=3)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> self = cfsn_vecs.binarize_ovr(keyby='name')
>>> print('self = {!r}'.format(self))
```

`__nice__(self)`

`classmethod demo(cls)`

Parameters **kwargs – See `kwCOCO.metrics.DetectionMetrics.demo()`

Returns ConfusionVectors

`keys(self)`

`__getitem__(self, cx)`

`measures(self, stabilize_thresh=7, fp_cutoff=None, monotonic_ppv=True, ap_method='pycocotools')`

Creates binary confusion measures for every one-versus-rest category.

Parameters

- `stabilize_thresh` (int, default=7) – if fewer than this many data points inserts dummy stabilization data so curves can still be drawn.
- `fp_cutoff` (int, default=None) – maximum number of false positives in the truncated roc curves. None is equivalent to `float('inf')`
- `monotonic_ppv` (bool, default=True) – if True ensures that precision is always increasing as recall decreases. This is done in pycocotools scoring, but I'm not sure its a good idea.

SeeAlso: `BinaryConfusionVectors.measures()`

Example

```
>>> self = OneVsRestConfusionVectors.demo()
>>> thresh_result = self.measures()['perclass']
```

`abstract ovr_classification_report(self)`

`class kwCOCO.metrics.PerClass_Measures(cx_to_info)`
Bases: `ubelt.NiceRepr, kwCOCO.metrics.util.DictProxy`

`__nice__(self)`

`summary(self)`

`classmethod from_json(cls, state)`

`__json__(self)`

`draw(self, key='mcc', prefix='', **kw)`

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> from kwCOCO.metrics.confusion_vectors import ConfusionVectors # NOQA
>>> cfsn_vecs = ConfusionVectors.demo()
>>> ovr_cfsn = cfsn_vecs.binarize_ovr(keyby='name')
>>> self = ovr_cfsn.measures()['perclass']
>>> self.draw('mcc', doclf=True, fnum=1)
>>> self.draw('pr', doclf=1, fnum=2)
>>> self.draw('roc', doclf=1, fnum=3)
```

```
draw_roc(self, prefix='', **kw)
draw_pr(self, prefix='', **kw)
summary_plot(self, fnum=1, title='', subplots='auto')
```

CommandLine

```
python ~/code/kwCOCO/kwCOCO/metrics/confusion_measures.py PerClass_Measures.
->summary_plot --show
```

Example

```
>>> from kwCOCO.metrics.confusion_measures import * # NOQA
>>> from kwCOCO.metrics.detect_metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo()
>>>     n_fp=(0, 1), n_fn=(0, 3), nimgs=32, nboxes=(0, 32),
>>>     classes=3, rng=0, newstyle=1, box_noise=0.7, cls_noise=0.2, score_
>>> noise=0.3, with_probs=False)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> ovr_cfsn = cfsn_vecs.binarize_ovr(keyby='name', ignore_classes=['vector',
>>> 'raster'])
>>> self = ovr_cfsn.measures()['perclass']
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> import seaborn as sns
>>> sns.set()
>>> self.summary_plot(title='demo summary_plot ovr', subplots=['pr', 'roc'])
>>> kwplot.show_if_requested()
>>> self.summary_plot(title='demo summary_plot ovr', subplots=['mcc', 'acc'],
>>> fnum=2)
```

2.2.6 kwcococo.util

`mkinit ~/code/kwcoco/kwcoco/util/_init__.py -w`

Submodules

`kwcococo.util.dict_like`

Module Contents

Classes

<code>DictLike</code>	An inherited class must specify the <code>getitem</code> , <code>setitem</code> , and
-----------------------	---

`class kwcococo.util.dict_like.DictLike`

Bases: `ubelt.NiceRepr`

An inherited class must specify the `getitem`, `setitem`, and keys methods.

A class is dictionary like if it has:

`__iter__`, `__len__`, `__contains__`, `__getitem__`, `items`, `keys`, `values`, `get`, and if it should be writable it should have: `__delitem__`, `__setitem__`, `update`,

And perhaps: `copy`,

`__iter__`, `__len__`, `__contains__`, `__getitem__`, `items`, `keys`, `values`, `get`, and if it should be writable it should have: `__delitem__`, `__setitem__`, `update`,

And perhaps: `copy`,

`asdict`

`abstract getitem(self, key)`

`abstract setitem(self, key, value)`

`abstract delitem(self, key)`

`abstract keys(self)`

`__len__(self)`

`__iter__(self)`

`__contains__(self, key)`

`__delitem__(self, key)`

`__getitem__(self, key)`

`__setitem__(self, key, value)`

`items(self)`

`values(self)`

`copy(self)`

`to_dict(self)`

```
update(self, other)
get(self, key, default=None)
```

kwcococo.util.jsonschema_elements

Functional interface into defining jsonschema structures.

See mixin classes for details.

Example

```
>>> from kwcococo.util.jsonschema_elements import * # NOQA
>>> elem = SchemaElements()
>>> for base in SchemaElements.__bases__:
>>>     print('\n\n====\nbase = {!r}'.format(base))
>>>     attrs = [key for key in dir(base) if not key.startswith('_')]
>>>     for key in attrs:
>>>         value = getattr(elem, key)
>>>         print('  {} = {}'.format(key, value))
```

Module Contents

Classes

<i>Element</i>	A dictionary used to define an element of a JSON Schema.
<i>ScalarElements</i>	Single-valued elements
<i>QuantifierElements</i>	Quantifier types
<i>ContainerElements</i>	Types that contain other types
<i>SchemaElements</i>	Functional interface into defining jsonschema structures.

Attributes

elem

ALLOF

ANY

ANYOF

ARRAY

BOOLEAN

continues on next page

Table 73 – continued from previous page

<i>INTEGER</i>
<i>NOT</i>
<i>NULL</i>
<i>NUMBER</i>
<i>OBJECT</i>
<i>ONEOF</i>
<i>STRING</i>

```
class kwcococo.util.jsonschema_elements.Element(base, options={}, _magic=None)
Bases: dict
```

A dictionary used to define an element of a JSON Schema.

The exact keys/values for the element will depend on the type of element being described. The *SchemaElements* defines exactly what these are for the core elements. (e.g. OBJECT, INTEGER, NULL, ARRAY, ANYOF)

Example

```
>>> from kwcococo.coco_schema import * # NOQA
>>> self = Element(base={'type': 'demo'}, options={'opt1', 'opt2'})
>>> new = self(opt1=3)
>>> print('self = {}'.format(ub.repr2(self, nl=1, sort=1)))
>>> print('new = {}'.format(ub.repr2(new, nl=1, sort=1)))
>>> print('new2 = {}'.format(ub.repr2(new(), nl=1, sort=1)))
>>> print('new3 = {}'.format(ub.repr2(new(title='myvar'), nl=1, sort=1)))
>>> print('new4 = {}'.format(ub.repr2(new(title='myvar')(examples=['']), nl=1, sort=1)))
>>> print('new5 = {}'.format(ub.repr2(new(badattr=True), nl=1, sort=1)))
self = {
    'type': 'demo',
}
new = {
    'opt1': 3,
    'type': 'demo',
}
new2 = {
    'opt1': 3,
    'type': 'demo',
}
new3 = {
    'opt1': 3,
    'title': 'myvar',
    'type': 'demo',
}
new4 = {
```

(continues on next page)

(continued from previous page)

```
'examples': [''],
'opt1': 3,
'title': 'myvar',
'type': 'demo',
}
new5 = {
    'opt1': 3,
    'type': 'demo',
}
```

__generics__**__call__**(*self*, **args*, ***kw*)**validate**(*self*, *instance*=*ub.NoParam*)

If *instance* is given, validates that that dictionary conforms to this schema. Otherwise validates that this is a valid schema element.

Parameters ***instance*** (*dict*) – a dictionary to validate

__or__(*self*, *other*)

Syntax for making an anyOf relationship

Example

```
>>> from kwcococo.util.jsonschema_elements import * # NOQA
>>> obj1 = OBJECT(dict(opt1=NUMBER()))
>>> obj2 = OBJECT(dict(opt2=STRING()))
>>> obj3 = OBJECT(dict(opt3=ANY()))
>>> any_v1 = obj1 | obj2
>>> any_v2 = ANYOF(obj1, obj2)
>>> assert any_v1 == any_v2
>>> any_v3 = any_v1 | obj3
>>> any_v4 = ANYOF(obj1, obj2, obj3)
>>> assert any_v3 == any_v4
```

class kwcococo.util.jsonschema_elements.**ScalarElements**

Bases: *object*

Single-valued elements

property **NULL**(*self*)

<https://json-schema.org/understanding-json-schema/reference/null.html>

property **BOOLEAN**(*self*)

<https://json-schema.org/understanding-json-schema/reference/null.html>

property **STRING**(*self*)

<https://json-schema.org/understanding-json-schema/reference/string.html>

property **NUMBER**(*self*)

<https://json-schema.org/understanding-json-schema/reference/numeric.html#number>

property **INTEGER**(*self*)

<https://json-schema.org/understanding-json-schema/reference/numeric.html#integer>

class kwcococo.util.jsonschema_elements.QquantifierElements

Bases: object

Quantifier types

<https://json-schema.org/understanding-json-schema/reference/combing.html#allof>

Example

```
>>> from kwcococo.util.jsonschema_elements import * # NOQA
>>> elem.ANYOF(elem.STRING, elem.NUMBER).validate()
>>> elem.ONEOF(elem.STRING, elem.NUMBER).validate()
>>> elem.NOT(elem.NULL).validate()
>>> elem.NOT(elem.ANY).validate()
>>> elem.ANY.validate()
```

property ANY(self)

ALLOF(self, *TYPES)

ANYOF(self, *TYPES)

ONEOF(self, *TYPES)

NOT(self, TYPE)

class kwcococo.util.jsonschema_elements.ContainerElements

Types that contain other types

Example

```
>>> from kwcococo.util.jsonschema_elements import * # NOQA
>>> print(elem.ARRAY().validate())
>>> print(elem.OBJECT().validate())
>>> print(elem.OBJECT().validate())
{'type': 'array', 'items': []}
{'type': 'object', 'properties': {}}
{'type': 'object', 'properties': {}}
```

ARRAY(self, TYPE={}, **kw)

<https://json-schema.org/understanding-json-schema/reference/array.html>

Example

```
>>> from kwcococo.util.jsonschema_elements import * # NOQA
>>> ARRAY(numItems=3)
>>> schema = ARRAY(minItems=3)
>>> schema.validate()
{'type': 'array', 'items': [], 'minItems': 3}
```

OBJECT(self, PROPERTIES={}, **kw)

<https://json-schema.org/understanding-json-schema/reference/object.html>

Example

```
>>> import jsonschema
>>> schema = elem.OBJECT()
>>> jsonschema.validate({}, schema)
>>> #
>>> import jsonschema
>>> schema = elem.OBJECT({
>>>     'key1': elem.ANY(),
>>>     'key2': elem.ANY(),
>>> }, required=['key1'])
>>> jsonschema.validate({'key1': None}, schema)
>>> #
>>> import jsonschema
>>> schema = elem.OBJECT({
>>>     'key1': elem.OBJECT({'arr': elem.ARRAY()}),
>>>     'key2': elem.ANY(),
>>> }, required=['key1'], title='a title')
>>> schema.validate()
>>> print('schema = {}'.format(ub.repr2(schema, sort=1, nl=-1)))
>>> jsonschema.validate({'key1': {'arr': []}}, schema)
schema = {
    'properties': {
        'key1': {
            'properties': {
                'arr': {'items': {}, 'type': 'array'}
            },
            'type': 'object'
        },
        'key2': {}
    },
    'required': ['key1'],
    'title': 'a title',
    'type': 'object'
}
```

class kwcococo.util.jsonschema_elements.SchemaElements
Bases: *ScalarElements, QuantifierElements, ContainerElements*

Functional interface into defining jsonschema structures.

See mixin classes for details.

References

<https://json-schema.org/understanding-json-schema/>

Todo:

- [] Generics: title, description, default, examples
-

CommandLine

```
xdoctest -m /home/joncrall/code/kwcoco/kwcoco/util/jsonschema_elements.py
↳ SchemaElements
```

Example

```
>>> from kwcoco.util.jsonschema_elements import * # NOQA
>>> elem = SchemaElements()
>>> elem.ARRAY(elem.ANY())
>>> schema = OBJECT({
>>>     'prop1': ARRAY(INTEGER, minItems=3),
>>>     'prop2': ARRAY(STRING, numItems=2),
>>>     'prop3': ARRAY(OBJECT({
>>>         'subprob1': NUMBER,
>>>         'subprob2': NUMBER,
>>>     })))
>>> })
>>> print('schema = {}'.format(ub.repr2(schema, nl=2, sort=1)))
schema = {
    'properties': {
        'prop1': {'items': {'type': 'integer'}, 'minItems': 3, 'type': 'array'},
        'prop2': {'items': {'type': 'string'}, 'maxItems': 2, 'minItems': 2, 'type':
↳ ': 'array'},
        'prop3': {'items': {'properties': {'subprob1': {'type': 'number'}, 'subprob2':
↳ ': {'type': 'number'}}}, 'type': 'object'}, 'type': 'array'},
    },
    'type': 'object',
}
```

```
>>> TYPE = elem.OBJECT({
>>>     'p1': ANY,
>>>     'p2': ANY,
>>> }, required=['p1'])
>>> import jsonschema
>>> inst = {'p1': None}
>>> jsonschema.validate(inst, schema=TYPE)
>>> #jsonschema.validate({'p2': None}, schema=TYPE)
```

kwcococo.util.jsonschema_elements.elem
kwcococo.util.jsonschema_elements.ALLOF
kwcococo.util.jsonschema_elements.ANY
kwcococo.util.jsonschema_elements.ANYOF
kwcococo.util.jsonschema_elements.ARRAY
kwcococo.util.jsonschema_elements.BOOLEAN
kwcococo.util.jsonschema_elements.INTEGER
kwcococo.util.jsonschema_elements.NOT
kwcococo.util.jsonschema_elements.NULL

`kwcoco.util.jsonschema_elements.NUMBER`
`kwcoco.util.jsonschema_elements.OBJECT`
`kwcoco.util.jsonschema_elements.ONEOF`
`kwcoco.util.jsonschema_elements.STRING`

`kwcoco.util.lazy_frame_backends`

Ducktyped interfaces for loading subregions of images with standard slice syntax

Module Contents

Classes

<code>LazySpectralFrameFile</code>	Potentially faster than GDAL for HDR formats.
<code>LazyRasterIOFrameFile</code>	fpath = '/home/joncrall/.cache/kwcoco/demo/large_hyperspectral/big_img_1.hdr'
<code>LazyGDalFrameFile</code>	

Functions

<code>_have_gdal()</code>	
<code>_have_rasterio()</code>	
<code>_have_spectral()</code>	
<code>_rectify_slice_dim(part, D)</code>	
<code>_validate_nonzero_data(file)</code>	Test to see if the image is all black.
<code>_read_envi_header(file)</code>	USAGE: <code>hdr = _read_envi_header(file)</code>

Attributes

<code>profile</code>	
<code>_GDAL_DTYPE_LUT</code>	
<hr/>	
<code>kwcoco.util.lazy_frame_backends.profile</code>	
<code>kwcoco.util.lazy_frame_backends._have_gdal()</code>	
<code>kwcoco.util.lazy_frame_backends._have_rasterio()</code>	
<code>kwcoco.util.lazy_frame_backends._have_spectral()</code>	
<code>kwcoco.util.lazy_frame_backends._GDAL_DTYPE_LUT</code>	

```

class kwcoco.util.lazy_frame_backends.LazySpectralFrameFile(filepath)
Bases: ubelt.NiceRepr

    Potentially faster than GDAL for HDR formats.

    _ds(self)

    classmethod available(self)
        Returns True if this backend is available

    property ndim(self)
    property shape(self)
    property dtype(self)
    __nice__(self)
    __getitem__(self, index)

class kwcoco.util.lazy_frame_backends.LazyRasterIOFrameFile(filepath)
Bases: ubelt.NiceRepr

    filepath = '/home/joncrall/.cache/kwcoco/demo/large_hyperspectral/big_img_128.bsq' lazy_rio = LazyRasterI-
    OFrameFile(filepath) ds = lazy_rio._ds

    classmethod available(self)
        Returns True if this backend is available

    _ds(self)

    property ndim(self)
    property shape(self)
    property dtype(self)
    __nice__(self)
    __getitem__(self, index)

class kwcoco.util.lazy_frame_backends.LazyGDalFrameFile(filepath)
Bases: ubelt.NiceRepr

```

Todo:

- [] Move to its own backend module
 - [] When used with COCO, allow the image metadata to populate the height, width, and channels if possible.
-

Example

```

>>> # xdoctest: +REQUIRES(module:osgeo)
>>> self = LazyGDalFrameFile.demo()
>>> print('self = {!r}'.format(self))
>>> self[0:3, 0:3]
>>> self[:, :, 0]
>>> self[0]
>>> self[0, 3]

```

```
>>> # import kwplot
>>> # kwplot.imshow(self[:])
```

Example

```
>>> # See if we can reproduce the INTERLEAVE bug
```

```
data = np.random.rand(128, 128, 64) import kwimage import ubelt as ub from os.path import join dpath
= ub.ensure_app_cache_dir('kwcoco/tests/reader') fpath = join(dpath, 'foo.tiff') kwimage.imwrite(fpath, data,
backend='skimage') recon1 = kwimage.imread(fpath) recon1.shape

self = LazyGDalFrameFile(fpath) self.shape self[:]

classmethod available(self)
    Returns True if this backend is available

_ds(self)

classmethod demo(cls, key='astro', dsize=None)

property ndim(self)

property shape(self)

property dtype(self)

__nice__(self)

__getitem__(self, index)
```

References

<https://gis.stackexchange.com/questions/162095/gdal-driver-create-typeerror>

```
__array__(self)
    Allow this object to be passed to np.asarray
```

References

<https://numpy.org/doc/stable/user/basics.dispatch.html>

```
kwcoco.util.lazy_frame_backends._rectify_slice_dim(part, D)
kwcoco.util.lazy_frame_backends._validate_nonzero_data(file)
    Test to see if the image is all black.

    May fail on all-black images
```

Example

```
>>> # xdoctest: +REQUIRES(module:osgeo)
>>> import kwimage
>>> gpath = kwimage.grab_test_image_fpath()
>>> file = LazyGDalFrameFile(gpath)
>>> _validate_nonzero_data(file)
```

`kwcoco.util.lazy_frame_backends._read_envi_header(file)`

USAGE: `hdr = _read_envi_header(file)`

Reads an ENVI “.hdr” file header and returns the parameters in a dictionary as strings. Header field names are treated as case insensitive and all keys in the dictionary are lowercase.

Modified from `spectral/io/envi.py`

References

<https://github.com/spectralpython/spectral>

`kwcoco.util.util_archive`

Module Contents

Classes

`Archive`

Abstraction over zipfile and tarfile

Functions

`unarchive_file(archive_fpath, output_dpath='.', verbose=1, overwrite=True)`

`class kwcoco.util.util_archive.Archive(fpath=None, mode='r', backend=None, file=None)`
Bases: `object`

Abstraction over zipfile and tarfile

Todo: see if we can use one of these other tools instead

SeeAlso: <https://github.com/RKrahl/archive-tools> <https://pypi.org/project/arlib/>

Example

```
>>> from os.path import join
>>> dpath = ub.ensure_app_cache_dir('ubelt', 'tests', 'archive')
>>> ub.delete(dpath)
>>> dpath = ub.ensure_app_cache_dir(dpath)
>>> import pathlib
>>> dpath = pathlib.Path(dpath)
>>> #
>>> #
>>> mode = 'w'
>>> self1 = Archive(str(dpath / 'demo.zip'), mode=mode)
>>> self2 = Archive(str(dpath / 'demo.tar.gz'), mode=mode)
>>> #
>>> open(dpath / 'data_1only.txt', 'w').write('bazbzzz')
>>> open(dpath / 'data_2only.txt', 'w').write('buzzz')
>>> open(dpath / 'data_both.txt', 'w').write('foobar')
>>> #
>>> self1.add(dpath / 'data_both.txt')
>>> self1.add(dpath / 'data_1only.txt')
>>> #
>>> self2.add(dpath / 'data_both.txt')
>>> self2.add(dpath / 'data_2only.txt')
>>> #
>>> self1.close()
>>> self2.close()
>>> #
>>> self1 = Archive(str(dpath / 'demo.zip'), mode='r')
>>> self2 = Archive(str(dpath / 'demo.tar.gz'), mode='r')
>>> #
>>> extract_dpath = ub.ensuredir(str(dpath / 'extracted'))
>>> extracted1 = self1.extractall(extract_dpath)
>>> extracted2 = self2.extractall(extract_dpath)
>>> for fpath in extracted2:
>>>     print(open(fpath, 'r').read())
>>> for fpath in extracted1:
>>>     print(open(fpath, 'r').read())
```

classmethod _open(cls, fpath, mode)

__iter__(self)

classmethod coerce(cls, data)

Either open an archive file path or coerce an existing ZipFile or tarfile structure into this wrapper class

add(self, fpath, arcname=None)

close(self)

__enter__(self)

__exit__(self, *args)

extractall(self, output_dpath='.', verbose=1, overwrite=True)

`kwcococo.util.util_archive.unarchive_file(archive_fpath, output_dpath='.', verbose=1, overwrite=True)`

kwcoco.util.util_delayed_poc

This module is ported from ndsampler, and will likely eventually move to kwimage and be refactored using symbolic. The classes in this file represent a tree of delayed operations.

Proof of concept for delayed chainable transforms in Python.

There are several optimizations that could be applied.

This is similar to GDAL's virtual raster table, but it works in memory and I think it is easier to chain operations.

SeeAlso: ../../dev/symbolic_delayed.py

Warning: As the name implies this is a proof of concept, and the actual implementation was hacked together too quickly. Serious refactoring will be necessary.

Concepts:

Each class should be a layer that adds a new transformation on top of underlying nested layers. Adding new layers should be quick, and there should always be the option to “finalize” a stack of layers, chaining the transforms / operations and then applying one final efficient transform at the end.

Todo:

- [] Need to handle masks / nodata values when warping. Might need to rely more on gdal / rasterio for this.
-

Conventions:

- dszie = (always in width / height), no channels are present
- shape for images is always (height, width, channels)
- channels are always the last dimension of each image, if no channel dim is specified, finalize will add it.
- **Videos must be the last process in the stack, and add a leading** time dimension to the shape. dszie is still width, height, but shape is now: (time, height, width, chan)

Example

```
>>> # Example demonstrating the motivating use case
>>> # We have multiple aligned frames for a video, but each of
>>> # those frames is in a different resolution. Furthermore,
>>> # each of the frames consists of channels in different resolutions.
>>> # Create raw channels in some "native" resolution for frame 1
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> f1_chan1 = DelayedIdentity.demo('astro', chan=0, dszie=(300, 300))
>>> f1_chan2 = DelayedIdentity.demo('astro', chan=1, dszie=(200, 200))
>>> f1_chan3 = DelayedIdentity.demo('astro', chan=2, dszie=(10, 10))
>>> # Create raw channels in some "native" resolution for frame 2
>>> f2_chan1 = DelayedIdentity.demo('carl', dszie=(64, 64), chan=0)
>>> f2_chan2 = DelayedIdentity.demo('carl', dszie=(260, 260), chan=1)
>>> f2_chan3 = DelayedIdentity.demo('carl', dszie=(10, 10), chan=2)
>>> #
>>> # Delayed warp each channel into its "image" space
```

(continues on next page)

(continued from previous page)

```
>>> # Note: the images never actually enter this space we transform through it
>>> f1_dsize = np.array((3, 3))
>>> f2_dsize = np.array((2, 2))
>>> f1_img = DelayedChannelConcat([
>>>     f1_chan1.delayed_warp(Affine.scale(f1_dsize / f1_chan1.dsize), dsize=f1_dsize),
>>>     f1_chan2.delayed_warp(Affine.scale(f1_dsize / f1_chan2.dsize), dsize=f1_dsize),
>>>     f1_chan3.delayed_warp(Affine.scale(f1_dsize / f1_chan3.dsize), dsize=f1_dsize),
>>> ])
>>> f2_img = DelayedChannelConcat([
>>>     f2_chan1.delayed_warp(Affine.scale(f2_dsize / f2_chan1.dsize), dsize=f2_dsize),
>>>     f2_chan2.delayed_warp(Affine.scale(f2_dsize / f2_chan2.dsize), dsize=f2_dsize),
>>>     f2_chan3.delayed_warp(Affine.scale(f2_dsize / f2_chan3.dsize), dsize=f2_dsize),
>>> ])
>>> # Combine frames into a video
>>> vid_dsize = np.array((280, 280))
>>> vid = DelayedFrameConcat([
>>>     f1_img.delayed_warp(Affine.scale(vid_dsize / f1_img.dsize), dsize=vid_dsize),
>>>     f2_img.delayed_warp(Affine.scale(vid_dsize / f2_img.dsize), dsize=vid_dsize),
>>> ])
>>> vid.nesting
>>> print('vid.nesting = {}' .format(ub.repr2(vid.__json__(), nl=-2)))
>>> final = vid.finalize(interpolation='nearest')
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(final[0], pnum=(1, 2, 1), fnum=1)
>>> kwplot.imshow(final[1], pnum=(1, 2, 2), fnum=1)
```

Example

```
>>> import kwCOCO
>>> dset = kwCOCO.CocoDataset.demo('vidshapes8-multispectral')
>>> delayed = dset.delayed_load(1)
>>> from kwCOCO.util.util_delayed_poc import * # NOQA
>>> astro = DelayedLoad.demo('astro')
>>> print('MSI = ' + ub.repr2(delayed.__json__(), nl=-3, sort=0))
>>> print('ASTRO = ' + ub.repr2(astro.__json__(), nl=2, sort=0))
```

```
>>> subchan = delayed.take_channels('B1|B8')
>>> subcrop = subchan.delayed_crop((slice(10, 80), slice(30, 50)))
>>> #
>>> subcrop.nesting()
>>> subchan.nesting()
>>> subchan.finalize()
>>> subcrop.finalize()
>>> #
>>> msi_crop = delayed.delayed_crop((slice(10, 80), slice(30, 50)))
>>> msi_warp = msi_crop.delayed_warp(kwimage.Affine.scale(3), dsize='auto')
>>> subdata = msi_warp.take_channels('B11|B1')
>>> final = subdata.finalize()
```

(continues on next page)

(continued from previous page)

```
>>> assert final.shape == (210, 60, 2)
```

Example

```
>>> # test case where an auxiliary image does not map entirely on the image.
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> import kwimage
>>> from os.path import join
>>> dpath = ub.ensure_app_cache_dir('kwcoco/tests/delayed_poc')
>>> chan1_fpath = join(dpath, 'chan1.tif')
>>> chan2_fpath = join(dpath, 'chan2.tif')
>>> chan3_fpath = join(dpath, 'chan2.tif')
>>> chan1_raw = np.random.rand(128, 128, 1)
>>> chan2_raw = np.random.rand(64, 64, 1)
>>> chan3_raw = np.random.rand(256, 256, 1)
>>> kwimage.imwrite(chan1_fpath, chan1_raw)
>>> kwimage.imwrite(chan2_fpath, chan2_raw)
>>> kwimage.imwrite(chan3_fpath, chan3_raw)
>>> #
>>> c1 = channel_spec.FusedChannelSpec.coerce('c1')
>>> c2 = channel_spec.FusedChannelSpec.coerce('c2')
>>> c3 = channel_spec.FusedChannelSpec.coerce('c2')
>>> aux1 = DelayedLoad(chan1_fpath, dsize=chan1_raw.shape[0:2][::-1], channels=c1, num_
-> bands=1)
>>> aux2 = DelayedLoad(chan2_fpath, dsize=chan2_raw.shape[0:2][::-1], channels=c2, num_
-> bands=1)
>>> aux3 = DelayedLoad(chan3_fpath, dsize=chan3_raw.shape[0:2][::-1], channels=c3, num_
-> bands=1)
>>> #
>>> img_dsize = (128, 128)
>>> transform1 = kwimage.Affine.coerce(scale=0.5)
>>> transform2 = kwimage.Affine.coerce(theta=0.5, shear=0.01, offset=(-20, -40))
>>> transform3 = kwimage.Affine.coerce(offset=(64, 0)) @ kwimage.Affine.random(rng=10)
>>> part1 = aux1.delayed_warp(np.eye(3), dsize=img_dsize)
>>> part2 = aux2.delayed_warp(transform2, dsize=img_dsize)
>>> part3 = aux3.delayed_warp(transform3, dsize=img_dsize)
>>> delayed = DelayedChannelConcat([part1, part2, part3])
>>> #
>>> delayed_crop = delayed.crop((slice(0, 10), slice(0, 10)))
>>> delayed_final = delayed_crop.finalize()
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> final = delayed.finalize()
>>> kwplot.imshow(final, fnum=1, pnum=(1, 2, 1))
>>> kwplot.imshow(delayed_final, fnum=1, pnum=(1, 2, 2))
```

```
comp = delayed_crop.components[2]
comp.sub_data.finalize()
data = np.array([[0]]).astype(np.float32) kwimage.warp_affine(data, np.eye(3), dsize=(32, 32)) kwim-
```

```
age.warp_affine(data, np.eye(3))
kwimage.warp_affine(data[0:0], np.eye(3))
transform = kwimage.Affine.coerce(scale=0.1) data = np.array([[0]]).astype(np.float32)
data = np.array([[]]).astype(np.float32) kwimage.warp_affine(data, transform, dsize=(0, 2), antialias=True)
data = np.array([[]]).astype(np.float32) kwimage.warp_affine(data, transform, dsize=(10, 10))
data = np.array([[0]]).astype(np.float32) kwimage.warp_affine(data, transform, dsize=(0, 2), antialias=True)
data = np.array([[0]]).astype(np.float32) kwimage.warp_affine(data, transform, dsize=(10, 10))

cv2.warpAffine( kwimage.grab_test_image(dsize=(1, 1)), kwimage.Affine.coerce(scale=0.1).matrix[0:2], dsize=(0,
    1),
)
```

Module Contents

Classes

<i>DelayedVisionOperation</i>	Base class for nodes in a tree of delayed computer-vision operations
<i>DelayedVideoOperation</i>	Base class for nodes in a tree of delayed computer-vision operations
<i>DelayedImageOperation</i>	Operations that pertain only to images
<i>DelayedIdentity</i>	Noop leaf that does nothing. Can be used to hold raw data.
<i>DelayedNans</i>	Constructs nan channels as needed
<i>DelayedLoad</i>	A load operation for a specific sub-region and sub-bands in a specified
<i>DelayedFrameConcat</i>	Represents multiple frames in a video
<i>DelayedChannelConcat</i>	Represents multiple channels in an image that could be concatenated
<i>DelayedWarp</i>	POC for chainable transforms
<i>DelayedCrop</i>	Represent a delayed crop operation

Functions

<i>_compute_leaf_subcrop(root_region_bounds,</i> <i>tf_leaf_to_root)</i>	Given a region in a "root" image and a trasnform between that "root" and
<i>_largest_shape(shapes)</i>	Finds maximum over all shapes
<i>_devcheck_corner()</i>	
<i>_auto_dsize(transform, sub_dsize)</i>	

Attributes

`profile`

```
kwcoco.util.util_delayed_poc.profile
class kwcoco.util.util_delayed_poc.DelayedVisionOperation
Bases: ubelt.NiceRepr
Base class for nodes in a tree of delayed computer-vision operations
__nice__(self)
abstract finalize(self)
abstract children(self)
Abstract method, which should generate all of the direct children of a node in the operation tree.
_optimize_paths(self, **kwargs)
Iterate through the leaf nodes, which are virtually transformed into the root space.
This returns some sort of hueristically optimized leaf repr wrt warps.
__json__(self)
nesting(self)
warp(self, *args, **kwargs)
alias for delayed_warp, might change to this API in the future
crop(self, *args, **kwargs)
alias for delayed_crop, might change to this API in the future
class kwcoco.util.util_delayed_poc.DelayedVideoOperation
Bases: DelayedVisionOperation
Base class for nodes in a tree of delayed computer-vision operations
class kwcoco.util.util_delayed_poc.DelayedImageOperation
Bases: DelayedVisionOperation
Operations that pertain only to images
delayed_crop(self, region_slices)
Create a new delayed image that performs a crop in the transformed “self” space.
Parameters region_slices (Tuple[slice, slice]) – y-slice and x-slice.
```

Note: Returns a heuristically “simplified” tree. In the current implementation there are only 3 operations, cat, warp, and crop. All cats go at the top, all crops go at the bottom, all warps are in the middle.

Returns lazy executed delayed transform

Return type `DelayedWarp`

Example

```
>>> dsize = (100, 100)
>>> tf2 = Affine.affine(scale=3).matrix
>>> self = DelayedWarp(np.random.rand(33, 33), tf2, dsize)
>>> region_slices = (slice(5, 10), slice(1, 12))
>>> delayed_crop = self.delayed_crop(region_slices)
>>> print(ub.repr2(delayed_crop.nesting(), nl=-1, sort=0))
>>> delayed_crop.finalize()
```

Example

```
>>> chan1 = DelayedLoad.demo('astro')
>>> chan2 = DelayedLoad.demo('carl')
>>> warped1a = chan1.delayed_warp(Affine.scale(1.2).matrix)
>>> warped2a = chan2.delayed_warp(Affine.scale(1.5))
>>> warped1b = warped1a.delayed_warp(Affine.scale(1.2).matrix)
>>> warped2b = warped2a.delayed_warp(Affine.scale(1.5))
>>> #
>>> region_slices = (slice(97, 677), slice(5, 691))
>>> self = warped2b
>>> #
>>> crop1 = warped1b.delayed_crop(region_slices)
>>> crop2 = warped2b.delayed_crop(region_slices)
>>> print(ub.repr2(warped1b.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(warped2b.nesting(), nl=-1, sort=0))
>>> # Notice how the crop merges the two nesting layers
>>> # (via the heuristic optimize step)
>>> print(ub.repr2(crop1.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(crop2.nesting(), nl=-1, sort=0))
>>> frame1 = crop1.finalize(dsize=(500, 500))
>>> frame2 = crop2.finalize(dsize=(500, 500))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(frame1, pnum=(1, 2, 1), fnum=1)
>>> kwplot.imshow(frame2, pnum=(1, 2, 2), fnum=1)
```

delayed_warp(self, transform, dsize=None)

Delayed transform the underlying data.

Note: this deviates from kwimage warp functions because instead of “output_dims” (specified in c-style shape) we specify dsize (w, h).

Returns new delayed transform a chained transform

Return type *DelayedWarp*

abstract **take_channels(self, channels)**

class **kwcoco.util.util_delayed_poc.DelayedIdentity**(*sub_data*, *dsize=None*, *channels=None*)
Bases: *DelayedImageOperation*

Noop leaf that does nothing. Can be used to hold raw data.

Typically used to just hold raw data.

```
DelayedIdentity.demo('astro', chan=0, dsize=(32, 32))
```

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> sub_data = np.random.rand(31, 37, 3)
>>> self = DelayedIdentity(sub_data)
>>> self = DelayedIdentity(sub_data, channels='L|a|b')
```

`__hack_dont_optimize__ = True`

`classmethod demo(cls, key='astro', chan=None, dsize=None)`

`children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`_optimize_paths(self, **kwargs)`

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of hueristically optimized leaf repr wrt warps.

`finalize(self)`

`take_channels(self, channels)`

`class kwcoco.util.util_delayed_poc.DelayedNans(dsize=None, channels=None)`

Bases: `DelayedImageOperation`

Constructs nan channels as needed

Example

```
self = DelayedNans((10, 10), channel_spec.FusedChannelSpec.coerce('rgb')) region_slices = (slice(5, 10),
slice(1, 12)) delayed = self.delayed_crop(region_slices)
```

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> dsize = (307, 311)
>>> c1 = DelayedNans(dsize=dsize, channels=channel_spec.FusedChannelSpec.coerce('foo
˓→'))
>>> c2 = DelayedLoad.demo('astro', dsize=dsize).load_shape(True)
>>> cat = DelayedChannelConcat([c1, c2])
>>> warped_cat = cat.delayed_warp(kwimage.Affine.scale(1.07), dsize=(328, 332))
>>> warped_cat.finalize()
```

#>>> cropped = warped_cat.delayed_crop((slice(0, 300), slice(0, 100))) #>>> cropped.finalize().shape

`property shape(self)`

`property num_bands(self)`

`property dsize(self)`

property channels(self)**children(self)**

Abstract method, which should generate all of the direct children of a node in the operation tree.

_optimize_paths(self, **kwargs)

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of heuristically optimized leaf repr wrt warps.

finalize(self, **kwargs)**delayed_crop(self, region_slices)**

Create a new delayed image that performs a crop in the transformed “self” space.

Parameters `region_slices` (`Tuple[slice, slice]`) – y-slice and x-slice.

Note: Returns a heuristically “simplified” tree. In the current implementation there are only 3 operations, cat, warp, and crop. All cats go at the top, all crops go at the bottom, all warps are in the middle.

Returns lazy executed delayed transform

Return type `DelayedWarp`

Example

```
>>> dsize = (100, 100)
>>> tf2 = Affine.affine(scale=3).matrix
>>> self = DelayedWarp(np.random.rand(33, 33), tf2, dsize)
>>> region_slices = (slice(5, 10), slice(1, 12))
>>> delayed_crop = self.delayed_crop(region_slices)
>>> print(ub.repr2(delayed_crop.nesting(), nl=-1, sort=0))
>>> delayed_crop.finalize()
```

Example

```
>>> chan1 = DelayedLoad.demo('astro')
>>> chan2 = DelayedLoad.demo('carl')
>>> warped1a = chan1.delayed_warp(Affine.scale(1.2).matrix)
>>> warped2a = chan2.delayed_warp(Affine.scale(1.5))
>>> warped1b = warped1a.delayed_warp(Affine.scale(1.2).matrix)
>>> warped2b = warped2a.delayed_warp(Affine.scale(1.5))
>>> #
>>> region_slices = (slice(97, 677), slice(5, 691))
>>> self = warped2b
>>> #
>>> crop1 = warped1b.delayed_crop(region_slices)
>>> crop2 = warped2b.delayed_crop(region_slices)
>>> print(ub.repr2(warped1b.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(warped2b.nesting(), nl=-1, sort=0))
>>> # Notice how the crop merges the two nesting layers
>>> # (via the heuristic optimize step)
>>> print(ub.repr2(crop1.nesting(), nl=-1, sort=0))
```

(continues on next page)

(continued from previous page)

```
>>> print(ub.repr2(crop2.nesting(), nl=-1, sort=0))
>>> frame1 = crop1.finalize(dsize=(500, 500))
>>> frame2 = crop2.finalize(dsize=(500, 500))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> kwplot.imshow(frame1, pnum=(1, 2, 1), fnum=1)
>>> kwplot.imshow(frame2, pnum=(1, 2, 2), fnum=1)
```

delayed_warp(*self, transform, dsize=None*)

Delayed transform the underlying data.

Note: this deviates from kwimage warp functions because instead of “output_dims” (specified in c-style shape) we specify dsize (w, h).

Returns new delayed transform a chained transform

Return type *DelayedWarp*

```
class kwcoco.util.util_delayed_poc.DelayedLoad(fp, channels=None, dsize=None, num_bands=None,
                                              immediate_crop=None, immediate_chan_idxs=None,
                                              immediate_dsize=None)
```

Bases: *DelayedImageOperation*

A load operation for a specific sub-region and sub-bands in a specified image.

Note: This class contains support for fusing certain lazy operations into this layer, namely cropping, scaling, and channel selection.

For now these are named **immediates**

Example

```
>>> fpath = kwimage.grab_test_image_fpath()
>>> self = DelayedLoad(fpath)
>>> print('self = {!r}'.format(self))
>>> self.load_shape()
>>> print('self = {!r}'.format(self))
>>> self.finalize()
```

```
>>> f1_img = DelayedLoad.demo('astro', dsize=(300, 300))
>>> f2_img = DelayedLoad.demo('carl', dsize=(256, 320))
>>> print('f1_img = {!r}'.format(f1_img))
>>> print('f2_img = {!r}'.format(f2_img))
>>> print(f2_img.finalize().shape)
>>> print(f1_img.finalize().shape)
```

```
>>> fpath = kwimage.grab_test_image_fpath()
>>> channels = channel_spec.FusedChannelSpec.coerce('rgb')
>>> self = DelayedLoad(fpath, channels=channels)
```

`_hack_dont_optimize_` = True

`classmethod demo(DelayedLoad, key='astro', dsize=None)`

`abstract classmethod coerce(cls, data)`

`children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`nesting(self)`

`_optimize_paths(self, **kwargs)`

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of heuristically optimized leaf repr wrt warps.

`load_shape(self, use_channel_heuristic=False)`

`_ensure_dsize(self)`

`property shape(self)`

`property num_bands(self)`

`property dsize(self)`

`property channels(self)`

`property fpath(self)`

`finalize(self, **kwargs)`

Parameters `**kwargs` –

`nodata` [if specified this data item is treated as nodata, the] data is then converted to floats and the nodata value is replaced with nan.

`delayed_crop(self, region_slices)`

Parameters `region_slices` (`Tuple[slice, slice]`) – y-slice and x-slice.

Returns a new delayed load object with a fused crop operation

Return type `DelayedLoad`

Example

```
>>> # Test chained crop operations
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> self = orig = DelayedLoad.demo('astro').load_shape()
>>> region_slices = slices1 = (slice(0, 90), slice(30, 60))
>>> self = crop1 = orig.delayed_crop(slices1)
>>> region_slices = slices2 = (slice(10, 21), slice(10, 22))
>>> self = crop2 = crop1.delayed_crop(slices2)
>>> region_slices = slices3 = (slice(3, 20), slice(5, 20))
>>> crop3 = crop2.delayed_crop(slices3)
```

(continues on next page)

(continued from previous page)

```
>>> # Spot check internals
>>> print('orig = {}'.format(ub.repr2(orig.__json__(), nl=2)))
>>> print('crop1 = {}'.format(ub.repr2(crop1.__json__(), nl=2)))
>>> print('crop2 = {}'.format(ub.repr2(crop2.__json__(), nl=2)))
>>> print('crop3 = {}'.format(ub.repr2(crop3.__json__(), nl=2)))
>>> # Test internals
>>> assert crop3._immediates['crop'][0].start == 13
>>> assert crop3._immediates['crop'][0].stop == 21
>>> # Test shapes work out correctly
>>> assert crop3.finalize().shape == (8, 7, 3)
>>> assert crop2.finalize().shape == (11, 12, 3)
>>> assert crop1.take_channels([1, 2]).finalize().shape == (90, 30, 2)
>>> assert orig.finalize().shape == (512, 512, 3)
```

Note:

This chart gives an intuition on how new absolute `slice` coords are computed **from existing** absolute coords and relative coords.

5	7	<- new
3	5	<- rel
<hr/>		
01234567		<- relative coordinates
<hr/>		
2	9	<- curr
<hr/>		
0123456789		<- absolute coordinates
<hr/>		

take_channels(self, channels)

This method returns a subset of the vision data with only the specified bands / channels.

Parameters `channels` (`List[int] | slice | channel_spec.FusedChannelSpec`) – List of integers indexes, a slice, or a channel spec, which is typically a pipe (|) delimited list of channel codes. See `kwcoco.ChannelSpec` for more details.

Returns a new delayed load with a fused take channel operation

Return type `DelayedLoad`

Note: The channel subset must exist here or it will raise an error. A better implementation (via symbolic) might be able to do better

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> import kwcoco
>>> self = DelayedLoad.demo('astro').load_shape()
>>> channels = [2, 0]
>>> new = self.take_channels(channels)
>>> new3 = new.take_channels([1, 0])
```

```
>>> final1 = self.finalize()
>>> final2 = new.finalize()
>>> final3 = new3.finalize()
>>> assert np.all(final1[..., 2] == final2[..., 0])
>>> assert np.all(final1[..., 0] == final2[..., 1])
>>> assert final2.shape[2] == 2
```

```
>>> assert np.all(final1[..., 2] == final3[..., 1])
>>> assert np.all(final1[..., 0] == final3[..., 0])
>>> assert final3.shape[2] == 2
```

class kwcoco.util.util_delayed_poc.DelayedFrameConcat(frames, dsize=None)
Bases: *DelayedVideoOperation*

Represents multiple frames in a video

Note:

```
Video[0]:
  Frame[0]:
    Chan[0]: (32) +-----+
    Chan[1]: (16) +-----+
    Chan[2]: ( 8) +----+
  Frame[1]:
    Chan[0]: (30) +-----+
    Chan[1]: (14) +-----+
    Chan[2]: ( 6) +----+
```

Todo:

- [] Support computing the transforms when none of the data is loaded
-

Example

```
>>> # Simpler case with fewer nesting levels
>>> rng = kwarray.ensure_rng(None)
>>> # Delayed warp each channel into its "image" space
>>> # Note: the images never enter the space we transform through
>>> f1_img = DelayedLoad.demo('astro', (300, 300))
>>> f2_img = DelayedLoad.demo('carl', (256, 256))
>>> # Combine frames into a video
>>> vid_dsize = np.array((100, 100))
>>> self = vid = DelayedFrameConcat([
>>>     f1_img.delayed_warp(Affine.scale(vid_dsize / f1_img.dsize)),
>>>     f2_img.delayed_warp(Affine.scale(vid_dsize / f2_img.dsize)),
>>> ], dsize=vid_dsize)
>>> print(ub.repr2(vid.nesting(), nl=-1, sort=0))
>>> final = vid.finalize(interpolation='nearest', dsize=(32, 32))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(final[0], pnum=(1, 2, 1), fnum=1)
>>> kwplot.imshow(final[1], pnum=(1, 2, 2), fnum=1)
>>> region_slices = (slice(0, 90), slice(30, 60))
```

`children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`property channels(self)`

`property shape(self)`

`finalize(self, **kwargs)`

Execute the final transform

`delayed_crop(self, region_slices)`

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> # Create raw channels in some "native" resolution for frame 1
>>> f1_chan1 = DelayedIdentity.demo('astro', chan=1, 0, dsize=(300, 300))
>>> f1_chan2 = DelayedIdentity.demo('astro', chan=2, dsize=(10, 10))
>>> # Create raw channels in some "native" resolution for frame 2
>>> f2_chan1 = DelayedIdentity.demo('carl', dsize=(64, 64), chan=(1, 0))
>>> f2_chan2 = DelayedIdentity.demo('carl', dsize=(10, 10), chan=2)
>>> #
>>> f1_dsize = np.array(f1_chan1.dsize)
>>> f2_dsize = np.array(f2_chan1.dsize)
>>> f1_img = DelayedChannelConcat([
>>>     f1_chan1.delayed_warp(Affine.scale(f1_dsize / f1_chan1.dsize), dsize=f1_
>>> -dsize),
>>>     f1_chan2.delayed_warp(Affine.scale(f1_dsize / f1_chan2.dsize), dsize=f1_
>>> -dsize),
>>> ])
>>> f2_img = DelayedChannelConcat([
```

(continues on next page)

(continued from previous page)

```

>>>     f2_chan1.delayed_warp(Affine.scale(f2_dsize / f2_chan1.dsize), dsize=f2_
->>>     _dsize),
>>>     f2_chan2.delayed_warp(Affine.scale(f2_dsize / f2_chan2.dsize), dsize=f2_
->>>     _dsize),
>>>   ])
>>> vid_dsize = np.array((280, 280))
>>> full_vid = DelayedFrameConcat([
>>>     f1_img.delayed_warp(Affine.scale(vid_dsize / f1_img.dsize), dsize=vid_
->>>     _dsize),
>>>     f2_img.delayed_warp(Affine.scale(vid_dsize / f2_img.dsize), dsize=vid_
->>>     _dsize),
>>>   ])
>>> region_slices = (slice(80, 200), slice(80, 200))
>>> print(ub.repr2(full_vid.nesting(), nl=-1, sort=0))
>>> crop_vid = full_vid.delayed_crop(region_slices)
>>> final_full = full_vid.finalize(interpolation='nearest')
>>> final_crop = crop_vid.finalize(interpolation='nearest')
>>> import pytest
>>> with pytest.raises(ValueError):
>>>     # should not be able to crop a crop yet
>>>     crop_vid.delayed_crop(region_slices)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> kwplot.imshow(final_full[0], pnum=(2, 2, 1), fnum=1)
>>> kwplot.imshow(final_full[1], pnum=(2, 2, 2), fnum=1)
>>> kwplot.imshow(final_crop[0], pnum=(2, 2, 3), fnum=1)
>>> kwplot.imshow(final_crop[1], pnum=(2, 2, 4), fnum=1)

```

delayed_warp(self, transform, dsize=None)

Delayed transform the underlyng data.

Note: this deviates from kwimage warp functions because instead of “output_dims” (specified in c-style shape) we specify dsize (w, h).

Returns new delayed transform a chained transform

Return type *DelayedWarp*

class kwcoco.util.util_delayed_poc.DelayedChannelConcat(*components*, *dsize=None*)
Bases: *DelayedImageOperation*

Represents multiple channels in an image that could be concatenated

Variables **components** (*List[DelayedWarp]*) – a list of stackable channels. Each component may be comprised of multiple channels.

Todo:

- [] can this be generalized into a delayed concat?
- [] can all concats be delayed until the very end?

Example

```
>>> comp1 = DelayedWarp(np.random.rand(11, 7))
>>> comp2 = DelayedWarp(np.random.rand(11, 7, 3))
>>> comp3 = DelayedWarp(
    np.random.rand(3, 5, 2),
    transform=Affine.affine(scale=(7/5, 11/3)).matrix,
    dsize=(7, 11)
)
>>> components = [comp1, comp2, comp3]
>>> chans = DelayedChannelConcat(components)
>>> final = chans.finalize()
>>> assert final.shape == chans.shape
>>> assert final.shape == (11, 7, 6)
```

```
>>> # We should be able to nest DelayedChannelConcat inside virtual images
>>> frame1 = DelayedWarp(
    chans, transform=Affine.affine(scale=2.2).matrix,
    dsize=(20, 26))
>>> frame2 = DelayedWarp(
    np.random.rand(3, 3, 6), dsize=(20, 26))
>>> frame3 = DelayedWarp(
    np.random.rand(3, 3, 6), dsize=(20, 26))
```

```
>>> print(ub.repr2(frame1.nesting(), nl=-1, sort=False))
>>> frame1.finalize()
>>> vid = DelayedFrameConcat([frame1, frame2, frame3])
>>> print(ub.repr2(vid.nesting(), nl=-1, sort=False))
```

`children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`classmethod random(cls, num_parts=3, rng=None)`

Example

```
>>> self = DelayedChannelConcat.random()
>>> print('self = {!r}'.format(self))
>>> print(ub.repr2(self.nesting(), nl=-1, sort=0))
```

`property channels(self)`

`property shape(self)`

`finalize(self, **kwargs)`

Execute the final transform

`delayed_warp(self, transform, dsize=None)`

Delayed transform the underlying data.

Note: this deviates from kwimage warp functions because instead of “output_dims” (specified in c-style shape) we specify dsize (w, h).

Returns new delayed transform a chained transform

Return type *DelayedWarp*

take_channels(*self, channels*)

This method returns a subset of the vision data with only the specified bands / channels.

Parameters *channels* (*List[int] | slice | channel_spec.FusedChannelSpec*) – List of integers indexes, a slice, or a channel spec, which is typically a pipe (|) delimited list of channel codes. See `kwcoco.ChannelSpec` for more details.

Returns a delayed vision operation that only operates on the following channels.

Return type *DelayedVisionOperation*

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral')
>>> self = delayed = dset.delayed_load(1)
>>> channels = 'B11|B8|B1|B10'
>>> new = self.take_channels(channels)
```

Example

```
>>> # Complex case
>>> import kwcoco
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral')
>>> delayed = dset.delayed_load(1)
>>> astro = DelayedLoad.demo('astro').load_shape(use_channel_heuristic=True)
>>> aligned = astro.warp(kwimage.Affine.scale(600 / 512), dszie='auto')
>>> self = combo = DelayedChannelConcat(delayed.components + [aligned])
>>> channels = 'B1|r|B8|g'
>>> new = self.take_channels(channels)
>>> new_cropped = new.crop((slice(10, 200), slice(12, 350)))
>>> datas = new_cropped.finalize()
>>> vizable = kwimage.normalize_intensity(datas, axis=2)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> stacked = kwimage.stack_images(vizable.transpose(2, 0, 1))
>>> kwplot.imshow(stacked)
```

CommandLine

```
xdoc test -m /home/joncrall/code/kwcoco/kwcoco/util/util_delayed_poc.py
  ↳DelayedChannelConcat.take_channels:2 --profile
```

Example

```
>>> # Test case where requested channel does not exist
>>> import kwcoco
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral', use_cache=1,
  ↳verbose=100)
>>> self = dset.delayed_load(1)
>>> channels = 'B1|foobar|bazbiz|B8'
>>> new = self.take_channels(channels)
>>> new_cropped = new.crop((slice(10, 200), slice(12, 350)))
>>> fused = new_cropped.finalize()
>>> assert fused.shape == (190, 338, 4)
>>> assert np.all(np.isnan(fused[..., 1:3]))
>>> assert not np.any(np.isnan(fused[..., 0]))
>>> assert not np.any(np.isnan(fused[..., 3]))
```

class kwcoco.util.util_delayed_poc.DelayedWarp(*sub_data*, *transform*=None, *dsize*=None)

Bases: *DelayedImageOperation*

POC for chainable transforms

Note: “sub” is used to refer to the underlying data in its native coordinates and resolution.

“self” is used to refer to the data in the transformed coordinates that are exposed by this class.

Variables

- **sub_data** (*DelayedWarp* / *ArrayLike*) – array-like image data at a native resolution
- **transform** (*Transform*) – transforms data from native “sub”-image-space to “self”-image-space.

Example

```
>>> dsize = (12, 12)
>>> tf1 = np.array([[2, 0, 0], [0, 2, 0], [0, 0, 1]])
>>> tf2 = np.array([[3, 0, 0], [0, 3, 0], [0, 0, 1]])
>>> tf3 = np.array([[4, 0, 0], [0, 4, 0], [0, 0, 1]])
>>> band1 = DelayedWarp(np.random.rand(6, 6), tf1, dsize)
>>> band2 = DelayedWarp(np.random.rand(4, 4), tf2, dsize)
>>> band3 = DelayedWarp(np.random.rand(3, 3), tf3, dsize)
>>> #
>>> # Execute a crop in a one-level transformed space
>>> region_slices = (slice(5, 10), slice(0, 12))
>>> delayed_crop = band2.delayed_crop(region_slices)
```

(continues on next page)

(continued from previous page)

```
>>> final_crop = delayed_crop.finalize()
>>> #
>>> # Execute a crop in a nested transformed space
>>> tf4 = np.array([[1.5, 0, 0], [0, 1.5, 0], [0, 0, 1]])
>>> chained = DelayedWarp(band2, tf4, (18, 18))
>>> delayed_crop = chained.delayed_crop(region_slices)
>>> final_crop = delayed_crop.finalize()
>>> #
>>> tf4 = np.array([[.5, 0, 0], [0, .5, 0], [0, 0, 1]])
>>> chained = DelayedWarp(band2, tf4, (6, 6))
>>> delayed_crop = chained.delayed_crop(region_slices)
>>> final_crop = delayed_crop.finalize()
>>> #
>>> region_slices = (slice(1, 5), slice(2, 4))
>>> delayed_crop = chained.delayed_crop(region_slices)
>>> final_crop = delayed_crop.finalize()
```

Example

```
>>> dsizes = (17, 12)
>>> tf = np.array([[5.2, 0, 1.1], [0, 3.1, 2.2], [0, 0, 1]])
>>> self = DelayedWarp(np.random.rand(3, 5, 13), tf, dsizes=dsizes)
>>> self.finalize().shape
```

`classmethod random(cls, nesting=(2, 5), rng=None)`

Example

```
>>> self = DelayedWarp.random(nesting=(4, 7))
>>> print('self = {!r}'.format(self))
>>> print(ub.repr2(self.nesting(), nl=-1, sort=0))
```

`property channels(self)`

`children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`property dsizes(self)`

`property num_bands(self)`

`property shape(self)`

`_optimize_paths(self, **kwargs)`

Example

```
>>> self = DelayedWarp.random()
>>> leafs = list(self._optimize_paths())
>>> print('leafs = {!r}'.format(leafs))
```

finalize(*self*, *transform*=*None*, *dsize*=*None*, *interpolation*='linear', ***kwargs*)

Execute the final transform

Can pass a parent transform to augment this underlying transform.

Parameters

- **transform** (*Transform*) – an additional transform to perform
- **dsize** (*Tuple[int, int]*) – overrides destination canvas size

Example

```
>>> tf = np.array([[0.9, 0, 3.9], [0, 1.1, -.5], [0, 0, 1]])
>>> raw = kwimage.grab_test_image(dsize=(54, 65))
>>> raw = kwimage.ensure_float01(raw)
>>> # Test nested finalize
>>> layer1 = raw
>>> num = 10
>>> for _ in range(num):
...     layer1 = DelayedWarp(layer1, tf, dsize='auto')
>>> final1 = layer1.finalize()
>>> # Test non-nested finalize
>>> layer2 = list(layer1._optimize_paths())[0]
>>> final2 = layer2.finalize()
>>> #
>>> print(ub.repr2(layer1.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(layer2.nesting(), nl=-1, sort=0))
>>> print('final1 = {!r}'.format(final1))
>>> print('final2 = {!r}'.format(final2))
>>> print('final1.shape = {!r}'.format(final1.shape))
>>> print('final2.shape = {!r}'.format(final2.shape))
>>> assert np.allclose(final1, final2)
>>> #
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> kwplot.imshow(raw, pnum=(1, 3, 1), fnum=1)
>>> kwplot.imshow(final1, pnum=(1, 3, 2), fnum=1)
>>> kwplot.imshow(final2, pnum=(1, 3, 3), fnum=1)
>>> kwplot.show_if_requested()
```

Example

```
>>> # Test aliasing
>>> s = DelayedIdentity.demo()
>>> s = DelayedIdentity.demo('checkerboard')
>>> a = s.delayed_warp(Affine.scale(0.05), dsize='auto')
>>> b = s.delayed_warp(Affine.scale(3), dsize='auto')
```

```
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> # It looks like downsampling linear and area is the same
>>> # Does warpAffine have no alias handling?
>>> pnum_ = kwplot.PlotNums(nRows=2, nCols=4)
>>> kwplot.imshow(a.finalize(interpolation='area'), pnum=pnum_, title=
...>>> 'warpAffine area')
>>> kwplot.imshow(a.finalize(interpolation='linear'), pnum=pnum_, title=
...>>> 'warpAffine linear')
>>> kwplot.imshow(a.finalize(interpolation='nearest'), pnum=pnum_, title=
...>>> 'warpAffine nearest')
>>> kwplot.imshow(a.finalize(interpolation='nearest', antialias=False),
...>>> pnum=pnum_, title='warpAffine nearest AA=0')
>>> kwplot.imshow(kwimage.imresize(s.finalize(), dsize=a.dsize, interpolation=
...>>> 'area'), pnum=pnum_, title='resize area')
>>> kwplot.imshow(kwimage.imresize(s.finalize(), dsize=a.dsize, interpolation=
...>>> 'linear'), pnum=pnum_, title='resize linear')
>>> kwplot.imshow(kwimage.imresize(s.finalize(), dsize=a.dsize, interpolation=
...>>> 'nearest'), pnum=pnum_, title='resize nearest')
>>> kwplot.imshow(kwimage.imresize(s.finalize(), dsize=a.dsize, interpolation=
...>>> 'cubic'), pnum=pnum_, title='resize cubic')
```

`take_channels(self, channels)`

`class kwcoco.util.util_delayed_poc.DelayedCrop(sub_data, sub_slices)`

Bases: `DelayedImageOperation`

Represent a delayed crop operation

Example

```
>>> sub_data = DelayedLoad.demo()
>>> sub_slices = (slice(5, 10), slice(1, 12))
>>> self = DelayedCrop(sub_data, sub_slices)
>>> print(ub.repr2(self.nesting(), nl=-1, sort=0))
>>> final = self.finalize()
>>> print('final.shape = {!r}'.format(final.shape))
```

Example

```
>>> sub_data = DelayedLoad.demo()
>>> sub_slices = (slice(5, 10), slice(1, 12))
>>> crop1 = DelayedCrop(sub_data, sub_slices)
>>> import pytest
>>> # Should only error while heuristics are in use.
>>> with pytest.raises(ValueError):
>>>     crop2 = DelayedCrop(crop1, sub_slices)
```

`__hack_dont_optimize__ = True`

`property channels(self)`

`children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`finalize(self, **kwargs)`

`abstract _optimize_paths(self, **kwargs)`

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of heuristically optimized leaf repr wrt warps.

`kwcoco.util.util_delayed_poc._compute_leaf_subcrop(root_region_bounds, tf_leaf_to_root)`

Given a region in a “root” image and a transform between that “root” and some “leaf” image, compute the appropriate quantized region in the “leaf” image and the adjusted transformation between that root and leaf.

Example

```
>>> region_slices = (slice(33, 100), slice(22, 62))
>>> region_shape = (100, 100, 1)
>>> root_region_box = kwimage.Boxes.from_slice(region_slices, shape=region_shape)
>>> root_region_bounds = root_region_box.to_polygons()[0]
>>> tf_leaf_to_root = Affine.affine(scale=7).matrix
>>> slices, tf_new = _compute_leaf_subcrop(root_region_bounds, tf_leaf_to_root)
>>> print('tf_new =\n{}'.format(tf_new))
>>> print('slices = {}'.format(slices))
```

`kwcoco.util.util_delayed_poc._largest_shape(shapes)`

Finds maximum over all shapes

Example

```
>>> shapes = [
>>>     (10, 20), None, (None, 30), (40, 50, 60, None), (100, )
>>> ]
>>> largest = _largest_shape(shapes)
>>> print('largest = {}'.format(largest))
>>> assert largest == (100, 50, 60, None)
```

`kwcoco.util.util_delayed_poc._devcheck_corner()`

`kwcoco.util.util_delayed_poc._auto_dsize(transform, sub_dsize)`

kwcoco.util.util_futures

Deprecated and functionality moved to ubelt

kwcoco.util.util_json

Module Contents

Functions

<code>ensure_json_serializable(dict_, normalize_containers=False, verbose=0)</code>	normal-	Attempt to convert common types (e.g. numpy) into something json compliant
<code>find_json_unserializable(data, quickcheck=False)</code>		Recurse through json datastructure and find any component that
<code>indexable_allclose(dct1, dct2, return_info=False)</code>		Walks through two nested data structures and ensures that everything is

Attributes

IndexableWalker

kwcoco.util.util_json.IndexableWalker

`kwcoco.util.util_json.ensure_json_serializable(dict_, normalize_containers=False, verbose=0)`

Attempt to convert common types (e.g. numpy) into something json compliant

Convert numpy and tuples into lists

Parameters `normalize_containers (bool, default=False)` – if True, normalizes dict containers to be standard python structures.

Example

```
>>> data = ub.ddict(lambda: int)
>>> data['foo'] = ub.ddict(lambda: int)
>>> data['bar'] = np.array([1, 2, 3])
>>> data['foo']['a'] = 1
>>> data['foo']['b'] = (1, np.array([1, 2, 3]), {3: np.int32(3), 4: np.float16(1.0)})
>>>
>>> dict_ = data
>>> print(ub.repr2(data, nl=-1))
>>> assert list(find_json_unserializable(data))
>>> result = ensure_json_serializable(data, normalize_containers=True)
>>> print(ub.repr2(result, nl=-1))
>>> assert not list(find_json_unserializable(result))
>>> assert type(result) is dict
```

kwcoco.util.util_json.find_json_unserializable(data, quickcheck=False)

Recurse through json datastructure and find any component that causes a serialization error. Record the location of these errors in the datastructure as we recurse through the call tree.

Parameters

- **data** (*object*) – data that should be json serializable
- **quickcheck** (*bool*) – if True, check the entire datastructure assuming its ok before doing the python-based recursive logic.

Returns

list of “bad part” dictionaries containing items ‘value’ - the value that caused the serialization error ‘loc’ - which contains a list of key/indexes that can be used

to lookup the location of the unserializable value. If the “loc” is a list, then it indicates a rare case where a key in a dictionary is causing the serialization error.

Return type List[Dict]

Example

```
>>> from kwcoco.util.util_json import * # NOQA
>>> part = ub.ddict(lambda: int)
>>> part['foo'] = ub.ddict(lambda: int)
>>> part['bar'] = np.array([1, 2, 3])
>>> part['foo']['a'] = 1
>>> # Create a dictionary with two unserializable parts
>>> data = [1, 2, {'nest1': [2, part]}, {frozenset({'badkey'}): 3, 2: 4}]
>>> parts = list(find_json_unserializable(data))
>>> print('parts = {}'.format(ub.repr2(parts, nl=1)))
>>> # Check expected structure of bad parts
>>> assert len(parts) == 2
>>> part = parts[1]
>>> assert list(part['loc']) == [2, 'nest1', 1, 'bar']
>>> # We can use the "loc" to find the bad value
>>> for part in parts:
>>>     # "loc" is a list of directions containing which keys/indexes
>>>     # to traverse at each descent into the data structure.
>>>     directions = part['loc']
>>>     curr = data
>>>     special_flag = False
>>>     for key in directions:
>>>         if isinstance(key, list):
>>>             # special case for bad keys
>>>             special_flag = True
>>>             break
>>>         else:
>>>             # normal case for bad values
>>>             curr = curr[key]
>>>     if special_flag:
>>>         assert part['data'] in curr.keys()
>>>         assert part['data'] is key[1]
>>>     else:
>>>         assert part['data'] is curr
```

kwcoco.util.util_json.indexable_allclose(*dct1, dct2, return_info=False*)

Walks through two nested data structures and ensures that everything is roughly the same.

Parameters

- **dct1** – a nested indexable item
- **dct2** – a nested indexable item

Example

```
>>> from kwcoco.util.util_json import indexable_allclose
>>> dct1 = {
>>>     'foo': [1.222222, 1.333],
>>>     'bar': 1,
>>>     'baz': [],
>>> }
>>> dct2 = {
>>>     'foo': [1.22222, 1.333],
>>>     'bar': 1,
>>>     'baz': [],
>>> }
>>> assert indexable_allclose(dct1, dct2)
```

kwcoco.util.util_monkey**Module Contents****Classes*****SupressPrint***

Temporarily replace the print function in a module with a noop

class kwcoco.util.util_monkey.*SupressPrint*(mods*, ***kw*)**

Bases: *object*

Temporarily replace the print function in a module with a noop

Parameters

- ***mods** – the modules to disable print in
- ****kw** – only accepts “enabled” enabled (bool, default=True): enables or disables this context

__enter__(*self*)**__exit__(*self, a, b, c*)**

kwcoco.util.util_sklearn

Extensions to sklearn constructs

Module Contents

Classes

<i>StratifiedGroupKFold</i>	Stratified K-Folds cross-validator with Grouping
<p>class kwcoco.util.util_sklearn.StratifiedGroupKFold(<i>n_splits</i>=3, <i>shuffle</i>=False, <i>random_state</i>=None)</p> <p>Bases: sklearn.model_selection._split._BaseKFold</p> <p>Stratified K-Folds cross-validator with Grouping</p> <p>Provides train/test indices to split data in train/test sets.</p> <p>This cross-validation object is a variation of GroupKFold that returns stratified folds. The folds are made by preserving the percentage of samples for each class.</p> <p>Read more in the User Guide.</p> <p>Parameters <i>n_splits</i> (int, default=3) – Number of folds. Must be at least 2.</p> <p>_make_test_folds(self, X, y=None, groups=None)</p> <p>Parameters</p> <ul style="list-style-type: none"> • X (ndarray) – data • y (ndarray) – labels • groups (ndarray) – groupids for items. Items with the same groupid must be placed in the same group. <p>Returns test_folds</p> <p>Return type list</p> <p>Example</p> <pre>>>> import kwarray >>> rng = kwarray.ensure_rng(0) >>> groups = [1, 1, 3, 4, 2, 2, 7, 8, 8] >>> y = [1, 1, 1, 1, 2, 2, 2, 3, 3] >>> X = np.empty((len(y), 0)) >>> self = StratifiedGroupKFold(random_state=rng, shuffle=True) >>> skf_list = list(self.split(X=X, y=y, groups=groups)) ... >>> import ubelt as ub >>> print(ub.repr2(skf_list, nl=1, with_dtype=False)) [</pre>	

(continues on next page)

(continued from previous page)

```
[np.array([0, 1, 3, 4, 5, 6, 7, 8]), np.array([2])),  
]
```

_iter_test_masks(self, X, y=None, groups=None)

Generates boolean masks corresponding to test sets.

By default, delegates to _iter_test_indices(X, y, groups)

split(self, X, y, groups=None)

Generate indices to split data into training and test set.

kwCOCO.util.util_truncate

Truncate utility based on python-slugify.

<https://pypi.org/project/python-slugify/1.2.2/>

Module Contents

Functions

```
_trunc_op(string, max_length, trunc_loc)
```

Example

```
smart_truncate(string, max_length=0, separator=' ', Truncate a string.  
trunc_loc=0.5)
```

kwCOCO.util.util_truncate._trunc_op(string, max_length, trunc_loc)

Example

```
>>> from kwCOCO.util.util_truncate import _trunc_op  
>>> string =  
< 'DarnOvercastSculptureTipperBlazerConcaveUnsuitedDerangedHexagonRockband'  
>>> max_length = 16  
>>> trunc_loc = 0.5  
>>> _trunc_op(string, max_length, trunc_loc)
```

```
>>> from kwCOCO.util.util_truncate import _trunc_op  
>>> max_length = 16  
>>> string = 'a' * 16  
>>> _trunc_op(string, max_length, trunc_loc)
```

```
>>> string = 'a' * 17  
>>> _trunc_op(string, max_length, trunc_loc)
```

kwCOCO.util.util_truncate.smart_truncate(string, max_length=0, separator=' ', trunc_loc=0.5)
Truncate a string. :param string (str): string for modification :param max_length (int): output string length

:param word_boundary (bool): :param save_order (bool): if True then word order of output string is like input string :param separator (str): separator between words :param trunc_loc (float): fraction of location where to remove the text :return:

Package Contents

Classes

<i>DictLike</i>	An inherited class must specify the <code>getitem</code> , <code>setitem</code> , and
<i>ContainerElements</i>	Types that contain other types
<i>Element</i>	A dictionary used to define an element of a JSON Schema.
<i>QuantifierElements</i>	Quantifier types
<i>ScalarElements</i>	Single-valued elements
<i>SchemaElements</i>	Functional interface into defining jsonschema structures.
<i>LazyGDalFrameFile</i>	
<i>LazyRasterIOFrameFile</i>	fpath = '/home/joncrall/.cache/kwcoco/demo/large_hyperspectral/big_img_1.tif'
<i>LazySpectralFrameFile</i>	Potentially faster than GDAL for HDR formats.
<i>Archive</i>	Abstraction over zipfile and tarfile
<i>DelayedChannelConcat</i>	Represents multiple channels in an image that could be concatenated
<i>DelayedCrop</i>	Represent a delayed crop operation
<i>DelayedFrameConcat</i>	Represents multiple frames in a video
<i>DelayedIdentity</i>	Noop leaf that does nothing. Can be used to hold raw data.
<i>DelayedImageOperation</i>	Operations that pertain only to images
<i>DelayedLoad</i>	A load operation for a specific sub-region and sub-bands in a specified
<i>DelayedNans</i>	Constructs nan channels as needed
<i>DelayedVideoOperation</i>	Base class for nodes in a tree of delayed computer-vision operations
<i>DelayedVisionOperation</i>	Base class for nodes in a tree of delayed computer-vision operations
<i>DelayedWarp</i>	POC for chainable transforms
<i>SupressPrint</i>	Temporarily replace the print function in a module with a noop
<i>StratifiedGroupKFold</i>	Stratified K-Folds cross-validator with Grouping

Functions

<code>unarchive_file(archive_fpath, output_dpath='.', verbose=1, overwrite=True)</code>		
<code>ensure_json_serializable(dict_, normalize_containers=False, verbose=0)</code>	normal-	Attempt to convert common types (e.g. numpy) into something json compliant
<code>find_json_unserializable(data, quickcheck=False)</code>		Recurse through json datastructure and find any component that

continues on next page

Table 88 – continued from previous page

<code>indexable_allclose(dct1, dct2, return_info=False)</code>	Walks through two nested data structures and ensures that everything is
<code>smart_truncate(string, max_length=0, separator=' ', trunc_loc=0.5)</code>	Truncate a string.

Attributes

`ALLOF`

`ANY`

`ANYOF`

`ARRAY`

`BOOLEAN`

`INTEGER`

`NOT`

`NULL`

`NUMBER`

`OBJECT`

`ONEOF`

`STRING`

`elem`

`IndexableWalker`

`class kwcoc.util.DictLike`

Bases: `ubelt.NiceRepr`

An inherited class must specify the `getitem`, `setitem`, and `keys` methods.

A class is dictionary like if it has:

`__iter__`, `__len__`, `__contains__`, `__getitem__`, `items`, `keys`, `values`, `get`,

and if it should be writable it should have: `__delitem__`, `__setitem__`, `update`,

And perhaps: `copy`,

`__iter__`, `__len__`, `__contains__`, `__getitem__`, `items`, `keys`, `values`, `get`,

and if it should be writable it should have: `__delitem__`, `__setitem__`, `update`,

And perhaps: `copy`,

```

asdict
abstract getitem(self, key)
abstract setitem(self, key, value)
abstract delitem(self, key)
abstract keys(self)
__len__(self)
__iter__(self)
__contains__(self, key)
__delitem__(self, key)
__getitem__(self, key)
__setitem__(self, key, value)
items(self)
values(self)
copy(self)
to_dict(self)
update(self, other)
get(self, key, default=None)

kwcoco.util.ALLOF
kwcoco.util.ANY
kwcoco.util.ANYOF
kwcoco.util.ARRAY
kwcoco.util.BOOLEAN

class kwcoco.util.ContainerElements
    Types that contain other types

```

Example

```

>>> from kwcoco.util.jsonschema_elements import * # NOQA
>>> print(elem.ARRAY().validate())
>>> print(elem.OBJECT().validate())
>>> print(elem.OBJECT().validate())
{'type': 'array', 'items': []}
{'type': 'object', 'properties': {}}
{'type': 'object', 'properties': {}}

```

ARRAY(*self*, *TYPE={}*, ***kw*)
<https://json-schema.org/understanding-json-schema/reference/array.html>

Example

```
>>> from kwcococo.util.jsonschema_elements import * # NOQA
>>> ARRAY(numItems=3)
>>> schema = ARRAY(minItems=3)
>>> schema.validate()
{'type': 'array', 'items': {}, 'minItems': 3}
```

OBJECT(*self*, PROPERTIES={}, ***kw*)
<https://json-schema.org/understanding-json-schema/reference/object.html>

Example

```
>>> import jsonschema
>>> schema = elem.OBJECT()
>>> jsonschema.validate({}, schema)
>>> #
>>> import jsonschema
>>> schema = elem.OBJECT({
>>>     'key1': elem.ANY(),
>>>     'key2': elem.ANY(),
>>> }, required=['key1'])
>>> jsonschema.validate({'key1': None}, schema)
>>> #
>>> import jsonschema
>>> schema = elem.OBJECT({
>>>     'key1': elem.OBJECT({'arr': elem.ARRAY()}),
>>>     'key2': elem.ANY(),
>>> }, required=['key1'], title='a title')
>>> schema.validate()
>>> print('schema = {}'.format(ub.repr2(schema, sort=1, nl=-1)))
>>> jsonschema.validate({'key1': {'arr': []}}, schema)
schema = {
    'properties': {
        'key1': {
            'properties': {
                'arr': {'items': {}, 'type': 'array'}
            },
            'type': 'object'
        },
        'key2': {}
    },
    'required': ['key1'],
    'title': 'a title',
    'type': 'object'
}
```

class kwcococo.util.Element(*base*, options={}, _magic=None)
Bases: dict

A dictionary used to define an element of a JSON Schema.

The exact keys/values for the element will depend on the type of element being described. The *SchemaElements* defines exactly what these are for the core elements. (e.g. OBJECT, INTEGER, NULL, ARRAY, ANYOF)

Example

```
>>> from kwcococo.coco_schema import * # NOQA
>>> self = Element(base={'type': 'demo'}, options={'opt1', 'opt2'})
>>> new = self(opt1=3)
>>> print('self = {}'.format(ub.repr2(self, nl=1, sort=1)))
>>> print('new = {}'.format(ub.repr2(new, nl=1, sort=1)))
>>> print('new2 = {}'.format(ub.repr2(new(), nl=1, sort=1)))
>>> print('new3 = {}'.format(ub.repr2(new(title='myvar'), nl=1, sort=1)))
>>> print('new4 = {}'.format(ub.repr2(new(title='myvar')(examples=['']), nl=1, sort=1)))
>>> print('new5 = {}'.format(ub.repr2(new(badattr=True), nl=1, sort=1)))
self = {
    'type': 'demo',
}
new = {
    'opt1': 3,
    'type': 'demo',
}
new2 = {
    'opt1': 3,
    'type': 'demo',
}
new3 = {
    'opt1': 3,
    'title': 'myvar',
    'type': 'demo',
}
new4 = {
    'examples': [],
    'opt1': 3,
    'title': 'myvar',
    'type': 'demo',
}
new5 = {
    'opt1': 3,
    'type': 'demo',
}
```

__generics__

__call__(*self*, **args*, ***kw*)

validate(*self*, *instance*=*ub.NoParam*)

If *instance* is given, validates that that dictionary conforms to this schema. Otherwise validates that this is a valid schema element.

Parameters **instance** (*dict*) – a dictionary to validate

__or__(*self*, *other*)

Syntax for making an anyOf relationship

Example

```
>>> from kwCoco.util.jsonschema_elements import * # NOQA
>>> obj1 = OBJECT(dict(opt1=NUMBER()))
>>> obj2 = OBJECT(dict(opt2=STRING()))
>>> obj3 = OBJECT(dict(opt3=ANY()))
>>> any_v1 = obj1 | obj2
>>> any_v2 = ANYOF(obj1, obj2)
>>> assert any_v1 == any_v2
>>> any_v3 = any_v1 | obj3
>>> any_v4 = ANYOF(obj1, obj2, obj3)
>>> assert any_v3 == any_v4
```

kwCoco.util.INTEGER

kwCoco.util.NOT

kwCoco.util.NULL

kwCoco.util.NUMBER

kwCoco.util.OBJECT

kwCoco.util.ONEOF

class kwCoco.util.QuantifierElements

Bases: object

Quantifier types

<https://json-schema.org/understanding-json-schema/reference/combining.html#allof>

Example

```
>>> from kwCoco.util.jsonschema_elements import * # NOQA
>>> elem.ANYOF(elem.STRING, elem.NUMBER).validate()
>>> elem.ONEOF(elem.STRING, elem.NUMBER).validate()
>>> elem.NOT(elem.NULL).validate()
>>> elem.NOT(elem.ANY).validate()
>>> elem.ANY.validate()
```

property ANY(self)

ALLOF(self, *TYPES)

ANYOF(self, *TYPES)

ONEOF(self, *TYPES)

NOT(self, TYPE)

kwCoco.util.STRING

class kwCoco.util.ScalarElements

Bases: object

Single-valued elements

property NULL(self)

<https://json-schema.org/understanding-json-schema/reference/null.html>

```

property BOOLEAN(self)
    https://json-schema.org/understanding-json-schema/reference/null.html

property STRING(self)
    https://json-schema.org/understanding-json-schema/reference/string.html

property NUMBER(self)
    https://json-schema.org/understanding-json-schema/reference/numeric.html#number

property INTEGER(self)
    https://json-schema.org/understanding-json-schema/reference/numeric.html#integer

```

class kwcococo.util.SchemaElements

Bases: *ScalarElements, QuantifierElements, ContainerElements*

Functional interface into defining jsonschema structures.

See mixin classes for details.

References

<https://json-schema.org/understanding-json-schema/>

Todo:

- [] Generics: title, description, default, examples
-

CommandLine

```
xdoctest -m /home/joncrall/code/kwcoco/kwcoco/util/jsonschema_elements.py
↳ SchemaElements
```

Example

```

>>> from kwcococo.util.jsonschema_elements import * # NOQA
>>> elem = SchemaElements()
>>> elem.ARRAY(elem.ANY())
>>> schema = OBJECT({
>>>     'prop1': ARRAY(INTEGER, minItems=3),
>>>     'prop2': ARRAY(STRING, numItems=2),
>>>     'prop3': ARRAY(OBJECT({
>>>         'subprob1': NUMBER,
>>>         'subprob2': NUMBER,
>>>     })),
>>> })
>>> print('schema = {}'.format(ub.repr2(schema, nl=2, sort=1)))
schema = {
    'properties': {
        'prop1': {'items': {'type': 'integer'}, 'minItems': 3, 'type': 'array'},
        'prop2': {'items': {'type': 'string'}, 'maxItems': 2, 'minItems': 2, 'type':
↳ 'array'},
        'prop3': {'items': {'properties': {'subprob1': {'type': 'number'}, 'subprob2':
↳ {'type': 'number'}}}, 'type': 'object'}, 'type': 'array'}
}

```

(continues on next page)

(continued from previous page)

```
    },
    'type': 'object',
}
```

```
>>> TYPE = elem.OBJECT({
>>>     'p1': ANY,
>>>     'p2': ANY,
>>> }, required=['p1'])
>>> import jsonschema
>>> inst = {'p1': None}
>>> jsonschema.validate(inst, schema=TYPE)
>>> #jsonschema.validate({'p2': None}, schema=TYPE)
```

kwcoco.util.elem

```
class kwcoco.util.LazyGDalFrameFile(fpath)
Bases: ubelt.NiceRepr
```

Todo:

- [] Move to its own backend module
 - [] When used with COCO, allow the image metadata to populate the height, width, and channels if possible.
-

Example

```
>>> # xdoctest: +REQUIRES(module:osgeo)
>>> self = LazyGDalFrameFile.demo()
>>> print('self = {!r}'.format(self))
>>> self[0:3, 0:3]
>>> self[:, :, 0]
>>> self[0]
>>> self[0, 3]
```

```
>>> # import kwplot
>>> # kwplot.imshow(self[:])
```

Example

```
>>> # See if we can reproduce the INTERLEAVE bug
```

```
data = np.random.rand(128, 128, 64) import kwimage import ubelt as ub from os.path import join dpath = ub.ensure_app_cache_dir('kwcoco/tests/reader') fpath = join(dpath, 'foo.tiff') kwimage.imwrite(fpath, data, backend='skimage') recon1 = kwimage.imread(fpath) recon1.shape
```

```
self = LazyGDalFrameFile(fpath) self.shape self[:]
```

```
classmethod available(self)
```

Returns True if this backend is available

```

_dds(self)
classmethod demo(cls, key='astro', dsize=None)
property ndim(self)
property shape(self)
property dtype(self)
__nice__(self)
__getitem__(self, index)

```

References

<https://gis.stackexchange.com/questions/162095/gdal-driver-create-typeerror>

```

__array__(self)
Allow this object to be passed to np.asarray

```

References

<https://numpy.org/doc/stable/user/basics.dispatch.html>

```

class kwcoco.util.LazyRasterIOFrameFile(fp)
Bases: ubelt.NiceRepr
fp = '/home/joncrall/.cache/kwcoco/demo/large_hyperspectral/big_img_128.bsq' lazy_rio = LazyRasterIOframeFile(fp) ds = lazy_rio._ds

classmethod available(self)
Returns True if this backend is available

_dds(self)
property ndim(self)
property shape(self)
property dtype(self)
__nice__(self)
__getitem__(self, index)

class kwcoco.util.LazySpectralFrameFile(fp)
Bases: ubelt.NiceRepr
Potentially faster than GDAL for HDR formats.

_dds(self)
classmethod available(self)
Returns True if this backend is available

property ndim(self)
property shape(self)
property dtype(self)
__nice__(self)
__getitem__(self, index)

```

```
class kwcococo.util.Archive(fp=path=None, mode='r', backend=None, file=None)
Bases: object

Abstraction over zipfile and tarfile
```

Todo: see if we can use one of these other tools instead

SeeAlso: <https://github.com/RKrahl/archive-tools> <https://pypi.org/project/arlib/>

Example

```
>>> from os.path import join
>>> dpath = ub.ensure_app_cache_dir('ubelt', 'tests', 'archive')
>>> ub.delete(dpath)
>>> dpath = ub.ensure_app_cache_dir(dpath)
>>> import pathlib
>>> dpath = pathlib.Path(dpath)
>>> #
>>> #
>>> mode = 'w'
>>> self1 = Archive(str(dpath / 'demo.zip'), mode=mode)
>>> self2 = Archive(str(dpath / 'demo.tar.gz'), mode=mode)
>>> #
>>> open(dpath / 'data_1only.txt', 'w').write('bazbzzz')
>>> open(dpath / 'data_2only.txt', 'w').write('buzzz')
>>> open(dpath / 'data_both.txt', 'w').write('foobar')
>>> #
>>> self1.add(dpath / 'data_both.txt')
>>> self1.add(dpath / 'data_1only.txt')
>>> #
>>> self2.add(dpath / 'data_both.txt')
>>> self2.add(dpath / 'data_2only.txt')
>>> #
>>> self1.close()
>>> self2.close()
>>> #
>>> self1 = Archive(str(dpath / 'demo.zip'), mode='r')
>>> self2 = Archive(str(dpath / 'demo.tar.gz'), mode='r')
>>> #
>>> extract_dpath = ub.ensuredir(str(dpath / 'extracted'))
>>> extracted1 = self1.extractall(extract_dpath)
>>> extracted2 = self2.extractall(extract_dpath)
>>> for fpath in extracted2:
>>>     print(open(fpath, 'r').read())
>>> for fpath in extracted1:
>>>     print(open(fpath, 'r').read())
```

classmethod _open(cls, fpath, mode)

__iter__(self)

classmethod coerce(cls, data)

Either open an archive file path or coerce an existing ZipFile or tarfile structure into this wrapper class

```

add(self, fpather, arcname=None)
close(self)
__enter__(self)
__exit__(self, *args)
extractall(self, output_dpath='.', verbose=1, overwrite=True)
kwcoco.util.unarchive_file(archive_fpath, output_dpath='.', verbose=1, overwrite=True)
class kwcoco.util.DelayedChannelConcat(components, dsize=None)
Bases: DelayedImageOperation

Represents multiple channels in an image that could be concatenated

```

Variables **components** (*List[DelayedWarp]*) – a list of stackable channels. Each component may be comprised of multiple channels.

Todo:

- [] can this be generalized into a delayed concat?
- [] can all concats be delayed until the very end?

Example

```

>>> comp1 = DelayedWarp(np.random.rand(11, 7))
>>> comp2 = DelayedWarp(np.random.rand(11, 7, 3))
>>> comp3 = DelayedWarp(
>>>     np.random.rand(3, 5, 2),
>>>     transform=Affine.affine(scale=(7/5, 11/3)).matrix,
>>>     dsize=(7, 11)
>>> )
>>> components = [comp1, comp2, comp3]
>>> chans = DelayedChannelConcat(components)
>>> final = chans.finalize()
>>> assert final.shape == chans.shape
>>> assert final.shape == (11, 7, 6)

```

```

>>> # We should be able to nest DelayedChannelConcat inside virtual images
>>> frame1 = DelayedWarp(
>>>     chans, transform=Affine.affine(scale=2.2).matrix,
>>>     dsize=(20, 26))
>>> frame2 = DelayedWarp(
>>>     np.random.rand(3, 3, 6), dsize=(20, 26))
>>> frame3 = DelayedWarp(
>>>     np.random.rand(3, 3, 6), dsize=(20, 26))

```

```

>>> print(ub.repr2(frame1.nesting(), nl=-1, sort=False))
>>> frame1.finalize()
>>> vid = DelayedFrameConcat([frame1, frame2, frame3])
>>> print(ub.repr2(vid.nesting(), nl=-1, sort=False))

```

children(*self*)

Abstract method, which should generate all of the direct children of a node in the operation tree.

classmethod random(*cls*, *num_parts*=3, *rng*=None)**Example**

```
>>> self = DelayedChannelConcat.random()
>>> print('self = {!r}'.format(self))
>>> print(ub.repr2(self.nesting(), nl=-1, sort=0))
```

property channels(*self*)**property shape**(*self*)**finalize**(*self*, ***kwargs*)

Execute the final transform

delayed_warp(*self*, *transform*, *dsizes*=None)

Delayed transform the underlying data.

Note: this deviates from kwimage warp functions because instead of “output_dims” (specified in c-style shape) we specify dsizes (w, h).

Returns new delayed transform a chained transform

Return type *DelayedWarp*

take_channels(*self*, *channels*)

This method returns a subset of the vision data with only the specified bands / channels.

Parameters *channels* (*List[int]* | *slice* | *channel_spec.FusedChannelSpec*) – List of integers indexes, a slice, or a channel spec, which is typically a pipe (|) delimited list of channel codes. See kwcoco.ChannelSpec for more details.

Returns a delayed vision operation that only operates on the following channels.

Return type *DelayedVisionOperation*

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral')
>>> self = delayed = dset.delayed_load(1)
>>> channels = 'B11|B8|B1|B10'
>>> new = self.take_channels(channels)
```

Example

```
>>> # Complex case
>>> import kwcoco
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral')
>>> delayed = dset.delayed_load(1)
>>> astro = DelayedLoad.demo('astro').load_shape(use_channel_heuristic=True)
>>> aligned = astro.warp(kwimage.Affine.scale(600 / 512), dsize='auto')
>>> self = combo = DelayedChannelConcat(delayed.components + [aligned])
>>> channels = 'B1|r|B8|g'
>>> new = self.take_channels(channels)
>>> new_cropped = new.crop((slice(10, 200), slice(12, 350)))
>>> datas = new_cropped.finalize()
>>> vizable = kwimage.normalize_intensity(datas, axis=2)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> stacked = kwimage.stack_images(vizable.transpose(2, 0, 1))
>>> kwplot.imshow(stacked)
```

CommandLine

```
xdoctest -m /home/joncrall/code/kwcoco/kwcoco/util/util_delayed_poc.py
  DelayedChannelConcat.take_channels:2 --profile
```

Example

```
>>> # Test case where requested channel does not exist
>>> import kwcoco
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral', use_cache=1, verbose=100)
>>> self = dset.delayed_load(1)
>>> channels = 'B1|foobar|bazbiz|B8'
>>> new = self.take_channels(channels)
>>> new_cropped = new.crop((slice(10, 200), slice(12, 350)))
>>> fused = new_cropped.finalize()
>>> assert fused.shape == (190, 338, 4)
>>> assert np.all(np.isnan(fused[..., 1:3]))
>>> assert not np.any(np.isnan(fused[..., 0]))
>>> assert not np.any(np.isnan(fused[..., 3]))
```

`class kwcoco.util.DelayedCrop(sub_data, sub_slices)`

Bases: `DelayedImageOperation`

Represent a delayed crop operation

Example

```
>>> sub_data = DelayedLoad.demo()
>>> sub_slices = (slice(5, 10), slice(1, 12))
>>> self = DelayedCrop(sub_data, sub_slices)
>>> print(ub.repr2(self.nesting(), nl=-1, sort=0))
>>> final = self.finalize()
>>> print('final.shape = {!r}'.format(final.shape))
```

Example

```
>>> sub_data = DelayedLoad.demo()
>>> sub_slices = (slice(5, 10), slice(1, 12))
>>> crop1 = DelayedCrop(sub_data, sub_slices)
>>> import pytest
>>> # Should only error while heuristics are in use.
>>> with pytest.raises(ValueError):
>>>     crop2 = DelayedCrop(crop1, sub_slices)
```

`__hack_dont_optimize__ = True`

`property channels(self)`

`children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`finalize(self, **kwargs)`

`abstract _optimize_paths(self, **kwargs)`

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of heuristically optimized leaf repr wrt warps.

`class kwcoco.util.DelayedFrameConcat(frames, dsize=None)`

Bases: `DelayedVideoOperation`

Represents multiple frames in a video

Note:

```
Video[0]:
  Frame[0]:
    Chan[0]: (32) +-----+
    Chan[1]: (16) +-----+
    Chan[2]: ( 8) +----+
  Frame[1]:
    Chan[0]: (30) +-----+
    Chan[1]: (14) +-----+
    Chan[2]: ( 6) +----+
```

Todo:

- [] Support computing the transforms when none of the data is loaded
-

Example

```
>>> # Simpler case with fewer nesting levels
>>> rng = kwarray.ensure_rng(None)
>>> # Delayed warp each channel into its "image" space
>>> # Note: the images never enter the space we transform through
>>> f1_img = DelayedLoad.demo('astro', (300, 300))
>>> f2_img = DelayedLoad.demo('carl', (256, 256))
>>> # Combine frames into a video
>>> vid_dsize = np.array((100, 100))
>>> self = vid = DelayedFrameConcat([
>>>     f1_img.delayed_warp(Affine.scale(vid_dsize / f1_img.dsize)),
>>>     f2_img.delayed_warp(Affine.scale(vid_dsize / f2_img.dsize)),
>>> ], dsize=vid_dsize)
>>> print(ub.repr2(vid.nesting(), nl=-1, sort=0))
>>> final = vid.finalize(interpolation='nearest', dsize=(32, 32))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(final[0], pnum=(1, 2, 1), fnum=1)
>>> kwplot.imshow(final[1], pnum=(1, 2, 2), fnum=1)
>>> region_slices = (slice(0, 90), slice(30, 60))
```

`children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`property channels(self)`

`property shape(self)`

`finalize(self, **kwargs)`

Execute the final transform

`delayed_crop(self, region_slices)`

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> # Create raw channels in some "native" resolution for frame 1
>>> f1_chan1 = DelayedIdentity.demo('astro', chan=1, 0, dsize=(300, 300))
>>> f1_chan2 = DelayedIdentity.demo('astro', chan=2, dsize=(10, 10))
>>> # Create raw channels in some "native" resolution for frame 2
>>> f2_chan1 = DelayedIdentity.demo('carl', dsize=(64, 64), chan=(1, 0))
>>> f2_chan2 = DelayedIdentity.demo('carl', dsize=(10, 10), chan=2)
>>> #
>>> f1_dsize = np.array(f1_chan1.dsize)
>>> f2_dsize = np.array(f2_chan1.dsize)
>>> f1_img = DelayedChannelConcat([
>>>     f1_chan1.delayed_warp(Affine.scale(f1_dsize / f1_chan1.dsize), dsize=f1_
>>> -dsize),
>>>     f1_chan2.delayed_warp(Affine.scale(f1_dsize / f1_chan2.dsize), dsize=f1_
>>> -dsize),
>>> ])
>>> f2_img = DelayedChannelConcat([
```

(continues on next page)

(continued from previous page)

```

>>>     f2_chan1.delayed_warp(Affine.scale(f2_dsize / f2_chan1.dsize), dsize=f2_
->>>     _dsize),
>>>     f2_chan2.delayed_warp(Affine.scale(f2_dsize / f2_chan2.dsize), dsize=f2_
->>>     _dsize),
>>>   ])
>>> vid_dsize = np.array((280, 280))
>>> full_vid = DelayedFrameConcat([
>>>     f1_img.delayed_warp(Affine.scale(vid_dsize / f1_img.dsize), dsize=vid_
->>>     _dsize),
>>>     f2_img.delayed_warp(Affine.scale(vid_dsize / f2_img.dsize), dsize=vid_
->>>     _dsize),
>>>   ])
>>> region_slices = (slice(80, 200), slice(80, 200))
>>> print(ub.repr2(full_vid.nesting(), nl=-1, sort=0))
>>> crop_vid = full_vid.delayed_crop(region_slices)
>>> final_full = full_vid.finalize(interpolation='nearest')
>>> final_crop = crop_vid.finalize(interpolation='nearest')
>>> import pytest
>>> with pytest.raises(ValueError):
>>>     # should not be able to crop a crop yet
>>>     crop_vid.delayed_crop(region_slices)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> kwplot.imshow(final_full[0], pnum=(2, 2, 1), fnum=1)
>>> kwplot.imshow(final_full[1], pnum=(2, 2, 2), fnum=1)
>>> kwplot.imshow(final_crop[0], pnum=(2, 2, 3), fnum=1)
>>> kwplot.imshow(final_crop[1], pnum=(2, 2, 4), fnum=1)

```

delayed_warp(*self, transform, dsize=None*)

Delayed transform the underlyng data.

Note: this deviates from kwimage warp functions because instead of “output_dims” (specified in c-style shape) we specify dsize (w, h).

Returns new delayed transform a chained transform

Return type *DelayedWarp*

```
class kwcoco.util.DelayedImageIdentity(sub_data, dsize=None, channels=None)
Bases: DelayedImageOperation
```

Noop leaf that does nothing. Can be used to hold raw data.

Typically used to just hold raw data.

```
DelayedIdentity.demo('astro', chan=0, dsize=(32, 32))
```

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> sub_data = np.random.rand(31, 37, 3)
>>> self = DelayedIdentity(sub_data)
>>> self = DelayedIdentity(sub_data, channels='L|a|b')
```

`__hack_dont_optimize__ = True`

`classmethod demo(cls, key='astro', chan=None, dsize=None)`

`children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`_optimize_paths(self, **kwargs)`

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of heuristically optimized leaf repr wrt warps.

`finalize(self)`

`take_channels(self, channels)`

`class kwcoco.util.DelayedImageOperation`

Bases: `DelayedVisionOperation`

Operations that pertain only to images

`delayed_crop(self, region_slices)`

Create a new delayed image that performs a crop in the transformed “self” space.

Parameters `region_slices (Tuple[slice, slice])` – y-slice and x-slice.

Note: Returns a heuristically “simplified” tree. In the current implementation there are only 3 operations, cat, warp, and crop. All cats go at the top, all crops go at the bottom, all warps are in the middle.

Returns lazy executed delayed transform

Return type `DelayedWarp`

Example

```
>>> dsize = (100, 100)
>>> tf2 = Affine.affine(scale=3).matrix
>>> self = DelayedWarp(np.random.rand(33, 33), tf2, dsize)
>>> region_slices = (slice(5, 10), slice(1, 12))
>>> delayed_crop = self.delayed_crop(region_slices)
>>> print(ub.repr2(delayed_crop.nesting(), nl=-1, sort=0))
>>> delayed_crop.finalize()
```

Example

```
>>> chan1 = DelayedLoad.demo('astro')
>>> chan2 = DelayedLoad.demo('carl')
>>> warped1a = chan1.delayed_warp(Affine.scale(1.2).matrix)
>>> warped2a = chan2.delayed_warp(Affine.scale(1.5))
>>> warped1b = warped1a.delayed_warp(Affine.scale(1.2).matrix)
>>> warped2b = warped2a.delayed_warp(Affine.scale(1.5))
>>> #
>>> region_slices = (slice(97, 677), slice(5, 691))
>>> self = warped2b
>>> #
>>> crop1 = warped1b.delayed_crop(region_slices)
>>> crop2 = warped2b.delayed_crop(region_slices)
>>> print(ub.repr2(warped1b.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(warped2b.nesting(), nl=-1, sort=0))
>>> # Notice how the crop merges the two nesting layers
>>> # (via the heuristic optimize step)
>>> print(ub.repr2(crop1.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(crop2.nesting(), nl=-1, sort=0))
>>> frame1 = crop1.finalize(dszie=(500, 500))
>>> frame2 = crop2.finalize(dszie=(500, 500))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(frame1, pnum=(1, 2, 1), fnum=1)
>>> kwplot.imshow(frame2, pnum=(1, 2, 2), fnum=1)
```

delayed_warp(*self*, *transform*, *dszie=None*)

Delayed transform the underlying data.

Note: this deviates from kwimage warp functions because instead of “output_dims” (specified in c-style shape) we specify dszie (w, h).

Returns new delayed transform a chained transform

Return type *DelayedWarp*

abstract **take_channels**(*self*, *channels*)

class **kwcoco.util.DelayedLoad**(*fpath*, *channels=None*, *dszie=None*, *num_bands=None*,
 immediate_crop=None, *immediate_chan_idxs=None*,
 immediate_dszie=None)

Bases: *DelayedImageOperation*

A load operation for a specific sub-region and sub-bands in a specified image.

Note: This class contains support for fusing certain lazy operations into this layer, namely cropping, scaling, and channel selection.

For now these are named **immediates**

Example

```
>>> fpath = kwimage.grab_test_image_fpath()
>>> self = DelayedLoad(fpath)
>>> print('self = {!r}'.format(self))
>>> self.load_shape()
>>> print('self = {!r}'.format(self))
>>> self.finalize()
```

```
>>> f1_img = DelayedLoad.demo('astro', dsizes=(300, 300))
>>> f2_img = DelayedLoad.demo('carl', dsizes=(256, 320))
>>> print('f1_img = {!r}'.format(f1_img))
>>> print('f2_img = {!r}'.format(f2_img))
>>> print(f2_img.finalize().shape)
>>> print(f1_img.finalize().shape)
```

```
>>> fpath = kwimage.grab_test_image_fpath()
>>> channels = channel_spec.FusedChannelSpec.coerce('rgb')
>>> self = DelayedLoad(fpath, channels=channels)
```

`__hack_dont_optimize__ = True`

`classmethod demo(DelayedLoad, key='astro', dsizes=None)`

`abstract classmethod coerce(cls, data)`

`children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`nesting(self)`

`_optimize_paths(self, **kwargs)`

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of heuristically optimized leaf repr wrt warps.

`load_shape(self, use_channel_heuristic=False)`

`_ensure_dsize(self)`

`property shape(self)`

`property num_bands(self)`

`property dsize(self)`

`property channels(self)`

`property fpath(self)`

`finalize(self, **kwargs)`

Parameters `**kwargs` –

`nodata` [if specified this data item is treated as nodata, the] data is then converted to floats and the nodata value is replaced with nan.

`delayed_crop(self, region_slices)`

Parameters `region_slices` (`Tuple[slice, slice]`) – y-slice and x-slice.

Returns a new delayed load object with a fused crop operation

Return type *DelayedLoad*

Example

```
>>> # Test chained crop operations
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> self = orig = DelayedLoad.demo('astro').load_shape()
>>> region_slices = slices1 = (slice(0, 90), slice(30, 60))
>>> self = crop1 = orig.delayed_crop(slices1)
>>> region_slices = slices2 = (slice(10, 21), slice(10, 22))
>>> self = crop2 = crop1.delayed_crop(slices2)
>>> region_slices = slices3 = (slice(3, 20), slice(5, 20))
>>> crop3 = crop2.delayed_crop(slices3)
>>> # Spot check internals
>>> print('orig = {}'.format(ub.repr2(orig.__json__(), nl=2)))
>>> print('crop1 = {}'.format(ub.repr2(crop1.__json__(), nl=2)))
>>> print('crop2 = {}'.format(ub.repr2(crop2.__json__(), nl=2)))
>>> print('crop3 = {}'.format(ub.repr2(crop3.__json__(), nl=2)))
>>> # Test internals
>>> assert crop3._immediates['crop'][0].start == 13
>>> assert crop3._immediates['crop'][0].stop == 21
>>> # Test shapes work out correctly
>>> assert crop3.finalize().shape == (8, 7, 3)
>>> assert crop2.finalize().shape == (11, 12, 3)
>>> assert crop1.take_channels([1, 2]).finalize().shape == (90, 30, 2)
>>> assert orig.finalize().shape == (512, 512, 3)
```

Note:

This chart gives an intuition on how new absolute `slice` coords are computed **from existing** absolute coords and relative coords.

```
5 7    <- new
3 5    <- rel
-----
01234567 <- relative coordinates
-----
2     9  <- curr
-----
0123456789 <- absolute coordinates
-----
```

`take_channels(self, channels)`

This method returns a subset of the vision data with only the specified bands / channels.

Parameters `channels` (`List[int] | slice | channel_spec.FusedChannelSpec`) – List of integers indexes, a slice, or a channel spec, which is typically a pipe (|) delimited list of channel codes. See `kwcoco.ChannelSpec` for more details.

Returns a new delayed load with a fused take channel operation

Return type *DelayedLoad*

Note: The channel subset must exist here or it will raise an error. A better implementation (via pymymbolic) might be able to do better

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> import kwcoco
>>> self = DelayedLoad.demo('astro').load_shape()
>>> channels = [2, 0]
>>> new = self.take_channels(channels)
>>> new3 = new.take_channels([1, 0])
```

```
>>> final1 = self.finalize()
>>> final2 = new.finalize()
>>> final3 = new3.finalize()
>>> assert np.all(final1[..., 2] == final2[..., 0])
>>> assert np.all(final1[..., 0] == final2[..., 1])
>>> assert final2.shape[2] == 2
```

```
>>> assert np.all(final1[..., 2] == final3[..., 1])
>>> assert np.all(final1[..., 0] == final3[..., 0])
>>> assert final3.shape[2] == 2
```

class kwcoco.util.DelayedNans(*dsize=None*, *channels=None*)
Bases: *DelayedImageOperation*

Constructs nan channels as needed

Example

```
self = DelayedNans((10, 10), channel_spec.FusedChannelSpec.coerce('rgb')) region_slices = (slice(5, 10), slice(1, 12)) delayed = self.delayed_crop(region_slices)
```

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> dsize = (307, 311)
>>> c1 = DelayedNans(dsize=dsize, channels=channel_spec.FusedChannelSpec.coerce('foo
  ↴'))
>>> c2 = DelayedLoad.demo('astro', dsize=dsize).load_shape(True)
>>> cat = DelayedChannelConcat([c1, c2])
>>> warped_cat = cat.delayed_warp(kwimage.Affine.scale(1.07), dsize=(328, 332))
>>> warped_cat.finalize()
```

```
#>>> cropped = warped_cat.delayed_crop((slice(0, 300), slice(0, 100))) #>>> cropped.finalize().shape
```

```
property shape(self)
```

```
property num_bands(self)
```

```
property dsizes(self)
property channels(self)
```

children(self)

Abstract method, which should generate all of the direct children of a node in the operation tree.

_optimize_paths(self, **kwargs)

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of heuristically optimized leaf repr wrt warps.

finalize(self, **kwargs)

delayed_crop(self, region_slices)

Create a new delayed image that performs a crop in the transformed “self” space.

Parameters `region_slices` (`Tuple[slice, slice]`) – y-slice and x-slice.

Note: Returns a heuristically “simplified” tree. In the current implementation there are only 3 operations, cat, warp, and crop. All cats go at the top, all crops go at the bottom, all warps are in the middle.

Returns lazy executed delayed transform

Return type `DelayedWarp`

Example

```
>>> dsizes = (100, 100)
>>> tf2 = Affine.affine(scale=3).matrix
>>> self = DelayedWarp(np.random.rand(33, 33), tf2, dsizes)
>>> region_slices = (slice(5, 10), slice(1, 12))
>>> delayed_crop = self.delayed_crop(region_slices)
>>> print(ub.repr2(delayed_crop.nesting(), nl=-1, sort=0))
>>> delayed_crop.finalize()
```

Example

```
>>> chan1 = DelayedLoad.demo('astro')
>>> chan2 = DelayedLoad.demo('carl')
>>> warped1a = chan1.delayed_warp(Affine.scale(1.2).matrix)
>>> warped2a = chan2.delayed_warp(Affine.scale(1.5))
>>> warped1b = warped1a.delayed_warp(Affine.scale(1.2).matrix)
>>> warped2b = warped2a.delayed_warp(Affine.scale(1.5))
>>> #
>>> region_slices = (slice(97, 677), slice(5, 691))
>>> self = warped2b
>>> #
>>> crop1 = warped1b.delayed_crop(region_slices)
>>> crop2 = warped2b.delayed_crop(region_slices)
>>> print(ub.repr2(warped1b.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(warped2b.nesting(), nl=-1, sort=0))
>>> # Notice how the crop merges the two nesting layers
```

(continues on next page)

(continued from previous page)

```
>>> # (via the hueristic optimize step)
>>> print(ub.repr2(crop1.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(crop2.nesting(), nl=-1, sort=0))
>>> frame1 = crop1.finalize(dszie=(500, 500))
>>> frame2 = crop2.finalize(dszie=(500, 500))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(frame1, pnum=(1, 2, 1), fnum=1)
>>> kwplot.imshow(frame2, pnum=(1, 2, 2), fnum=1)
```

delayed_warp(*self*, *transform*, *dszie=None*)

Delayed transform the underlying data.

Note: this deviates from kwimage warp functions because instead of “output_dims” (specified in c-style shape) we specify dszie (w, h).

Returns new delayed transform a chained transform

Return type *DelayedWarp*

class kwcoco.util.DelayedVideoOperationBases: *DelayedVisionOperation*

Base class for nodes in a tree of delayed computer-vision operations

class kwcoco.util.DelayedVisionOperationBases: *ubelt.NiceRepr*

Base class for nodes in a tree of delayed computer-vision operations

__nice__(*self*)**abstract finalize**(*self*)**abstract children**(*self*)

Abstract method, which should generate all of the direct children of a node in the operation tree.

_optimize_paths(*self*, ***kwargs*)

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of hueristically optimized leaf repr wrt warps.

__json__(*self*)**nesting**(*self*)**warp**(*self*, **args*, ***kwargs*)

alias for delayed_warp, might change to this API in the future

crop(*self*, **args*, ***kwargs*)

alias for delayed_crop, might change to this API in the future

class kwcoco.util.DelayedWarp(*sub_data*, *transform=None*, *dszie=None*)Bases: *DelayedImageOperation*

POC for chainable transforms

Note: “sub” is used to refer to the underlying data in its native coordinates and resolution.

“self” is used to refer to the data in the transformed coordinates that are exposed by this class.

Variables

- **sub_data** (`DelayedWarp` / `ArrayLike`) – array-like image data at a native resolution
- **transform** (`Transform`) – transforms data from native “sub”-image-space to “self”-image-space.

Example

```
>>> dsizes = (12, 12)
>>> tf1 = np.array([[2, 0, 0], [0, 2, 0], [0, 0, 1]])
>>> tf2 = np.array([[3, 0, 0], [0, 3, 0], [0, 0, 1]])
>>> tf3 = np.array([[4, 0, 0], [0, 4, 0], [0, 0, 1]])
>>> band1 = DelayedWarp(np.random.rand(6, 6), tf1, dsizes)
>>> band2 = DelayedWarp(np.random.rand(4, 4), tf2, dsizes)
>>> band3 = DelayedWarp(np.random.rand(3, 3), tf3, dsizes)
>>> #
>>> # Execute a crop in a one-level transformed space
>>> region_slices = (slice(5, 10), slice(0, 12))
>>> delayed_crop = band2.delayed_crop(region_slices)
>>> final_crop = delayed_crop.finalize()
>>> #
>>> # Execute a crop in a nested transformed space
>>> tf4 = np.array([[1.5, 0, 0], [0, 1.5, 0], [0, 0, 1]])
>>> chained = DelayedWarp(band2, tf4, (18, 18))
>>> delayed_crop = chained.delayed_crop(region_slices)
>>> final_crop = delayed_crop.finalize()
>>> #
>>> tf4 = np.array([[.5, 0, 0], [0, .5, 0], [0, 0, 1]])
>>> chained = DelayedWarp(band2, tf4, (6, 6))
>>> delayed_crop = chained.delayed_crop(region_slices)
>>> final_crop = delayed_crop.finalize()
>>> #
>>> region_slices = (slice(1, 5), slice(2, 4))
>>> delayed_crop = chained.delayed_crop(region_slices)
>>> final_crop = delayed_crop.finalize()
```

Example

```
>>> dsizes = (17, 12)
>>> tf = np.array([[5.2, 0, 1.1], [0, 3.1, 2.2], [0, 0, 1]])
>>> self = DelayedWarp(np.random.rand(3, 5, 13), tf, dsizes=dsizes)
>>> self.finalize().shape
```

```
classmethod random(cls, nesting=(2, 5), rng=None)
```

Example

```
>>> self = DelayedWarp.random(nesting=(4, 7))
>>> print('self = {!r}'.format(self))
>>> print(ub.repr2(self.nesting(), nl=-1, sort=0))
```

property channels(self)

children(self)

Abstract method, which should generate all of the direct children of a node in the operation tree.

property dsize(self)

property num_bands(self)

property shape(self)

_optimize_paths(self, **kwargs)

Example

```
>>> self = DelayedWarp.random()
>>> leafs = list(self._optimize_paths())
>>> print('leafs = {!r}'.format(leafs))
```

finalize(self, transform=None, dsize=None, interpolation='linear', **kwargs)

Execute the final transform

Can pass a parent transform to augment this underlying transform.

Parameters

- **transform (Transform)** – an additional transform to perform
- **dsize (Tuple[int, int])** – overrides destination canvas size

Example

```
>>> tf = np.array([[0.9, 0, 3.9], [0, 1.1, -.5], [0, 0, 1]])
>>> raw = kwimage.grab_test_image(dsize=(54, 65))
>>> raw = kwimage.ensure_float01(raw)
>>> # Test nested finalize
>>> layer1 = raw
>>> num = 10
>>> for _ in range(num):
...     layer1 = DelayedWarp(layer1, tf, dsize='auto')
>>> final1 = layer1.finalize()
>>> # Test non-nested finalize
>>> layer2 = list(layer1._optimize_paths())[0]
>>> final2 = layer2.finalize()
>>> #
>>> print(ub.repr2(layer1.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(layer2.nesting(), nl=-1, sort=0))
>>> print('final1 = {!r}'.format(final1))
>>> print('final2 = {!r}'.format(final2))
```

(continues on next page)

(continued from previous page)

```
>>> print('final1.shape = {!r}'.format(final1.shape))
>>> print('final2.shape = {!r}'.format(final2.shape))
>>> assert np.allclose(final1, final2)
>>> #
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> kwplot.imshow(raw, pnum=(1, 3, 1), fnum=1)
>>> kwplot.imshow(final1, pnum=(1, 3, 2), fnum=1)
>>> kwplot.imshow(final2, pnum=(1, 3, 3), fnum=1)
>>> kwplot.show_if_requested()
```

Example

```
>>> # Test aliasing
>>> s = DelayedIdentity.demo()
>>> s = DelayedIdentity.demo('checkerboard')
>>> a = s.delayed_warp(Affine.scale(0.05), dsiz='auto')
>>> b = s.delayed_warp(Affine.scale(3), dsiz='auto')

>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> # It looks like downsampling linear and area is the same
>>> # Does warpAffine have no alias handling?
>>> pnum_ = kwplot.PlotNums(nRows=2, nCols=4)
>>> kwplot.imshow(a.finalize(interpolation='area'), pnum=pnum_(), title=
-> 'warpAffine area')
>>> kwplot.imshow(a.finalize(interpolation='linear'), pnum=pnum_(), title=
-> 'warpAffine linear')
>>> kwplot.imshow(a.finalize(interpolation='nearest'), pnum=pnum_(), title=
-> 'warpAffine nearest')
>>> kwplot.imshow(a.finalize(interpolation='nearest', antialias=False),_
-> pnum=pnum_(), title='warpAffine nearest AA=0')
>>> kwplot.imshow(kwimage.imresize(s.finalize(), dsiz=a.dsiz, interpolation=
-> 'area'), pnum=pnum_(), title='resize area')
>>> kwplot.imshow(kwimage.imresize(s.finalize(), dsiz=a.dsiz, interpolation=
-> 'linear'), pnum=pnum_(), title='resize linear')
>>> kwplot.imshow(kwimage.imresize(s.finalize(), dsiz=a.dsiz, interpolation=
-> 'nearest'), pnum=pnum_(), title='resize nearest')
>>> kwplot.imshow(kwimage.imresize(s.finalize(), dsiz=a.dsiz, interpolation=
-> 'cubic'), pnum=pnum_(), title='resize cubic')
```

`take_channels(self, channels)`

`kwcoco.util.IndexableWalker`

`kwcoco.util.ensure_json_serializable(dict_, normalize_containers=False, verbose=0)`

Attempt to convert common types (e.g. numpy) into something json compliant

Convert numpy and tuples into lists

Parameters `normalize_containers` (*bool, default=False*) – if True, normalizes dict containers to be standard python structures.

Example

```
>>> data = ub.ddict(lambda: int)
>>> data['foo'] = ub.ddict(lambda: int)
>>> data['bar'] = np.array([1, 2, 3])
>>> data['foo']['a'] = 1
>>> data['foo']['b'] = (1, np.array([1, 2, 3]), {3: np.int32(3), 4: np.float16(1.0)})
>>>
>>> dict_ = data
>>> print(ub.repr2(data, nl=-1))
>>> assert list(find_json_unserializable(data))
>>> result = ensure_json_serializable(data, normalize_containers=True)
>>> print(ub.repr2(result, nl=-1))
>>> assert not list(find_json_unserializable(result))
>>> assert type(result) is dict
```

`kwcococo.util.find_json_unserializable`(*data, quickcheck=False*)

Recurse through json datastructure and find any component that causes a serialization error. Record the location of these errors in the datastructure as we recurse through the call tree.

Parameters

- `data` (*object*) – data that should be json serializable
- `quickcheck` (*bool*) – if True, check the entire datastructure assuming its ok before doing the python-based recursive logic.

Returns

list of “bad part” dictionaries containing items ‘value’ - the value that caused the serialization error ‘loc’ - which contains a list of key/indexes that can be used

to lookup the location of the unserializable value. If the “loc” is a list, then it indicates a rare case where a key in a dictionary is causing the serialization error.

Return type List[Dict]

Example

```
>>> from kwcococo.util.util_json import * # NOQA
>>> part = ub.ddict(lambda: int)
>>> part['foo'] = ub.ddict(lambda: int)
>>> part['bar'] = np.array([1, 2, 3])
>>> part['foo']['a'] = 1
>>> # Create a dictionary with two unserializable parts
>>> data = [1, 2, {'nest1': [2, part]}, {frozenset({'badkey'})): 3, 2: 4}]
>>> parts = list(find_json_unserializable(data))
>>> print('parts = {}'.format(ub.repr2(parts, nl=1)))
>>> # Check expected structure of bad parts
>>> assert len(parts) == 2
>>> part = parts[1]
>>> assert list(part['loc']) == [2, 'nest1', 1, 'bar']
```

(continues on next page)

(continued from previous page)

```
>>> # We can use the "loc" to find the bad value
>>> for part in parts:
>>>     # "loc" is a list of directions containing which keys/indexes
>>>     # to traverse at each descent into the data structure.
>>>     directions = part['loc']
>>>     curr = data
>>>     special_flag = False
>>>     for key in directions:
>>>         if isinstance(key, list):
>>>             # special case for bad keys
>>>             special_flag = True
>>>             break
>>>         else:
>>>             # normal case for bad values
>>>             curr = curr[key]
>>>     if special_flag:
>>>         assert part['data'] in curr.keys()
>>>         assert part['data'] is key[1]
>>>     else:
>>>         assert part['data'] is curr
```

kwcococo.util.indexable_allclose(dct1, dct2, return_info=False)

Walks through two nested data structures and ensures that everything is roughly the same.

Parameters

- **dct1** – a nested indexable item
- **dct2** – a nested indexable item

Example

```
>>> from kwcococo.util.util_json import indexable_allclose
>>> dct1 = {
>>>     'foo': [1.222222, 1.333],
>>>     'bar': 1,
>>>     'baz': [],
>>> }
>>> dct2 = {
>>>     'foo': [1.22222, 1.333],
>>>     'bar': 1,
>>>     'baz': [],
>>> }
>>> assert indexable_allclose(dct1, dct2)
```

class kwcococo.util.SuppressPrint(*mods, **kw)Bases: `object`

Temporarily replace the print function in a module with a noop

Parameters

- ***mods** – the modules to disable print in
- ****kw** – only accepts “enabled” enabled (bool, default=True): enables or disables this context

```
__enter__(self)
__exit__(self, a, b, c)

class kwcoco.util.StratifiedGroupKFold(n_splits=3, shuffle=False, random_state=None)
    Bases: sklearn.model_selection._split._BaseKFold
    Stratified K-Folds cross-validator with Grouping
    Provides train/test indices to split data in train/test sets.
```

This cross-validation object is a variation of GroupKFold that returns stratified folds. The folds are made by preserving the percentage of samples for each class.

Read more in the User Guide.

Parameters `n_splits` (`int, default=3`) – Number of folds. Must be at least 2.

`_make_test_folds(self, X, y=None, groups=None)`

Parameters

- `X` (`ndarray`) – data
- `y` (`ndarray`) – labels
- `groups` (`ndarray`) – groupids for items. Items with the same groupid must be placed in the same group.

Returns `test_folds`

Return type `list`

Example

```
>>> import kwarray
>>> rng = kwarray.ensure_rng(0)
>>> groups = [1, 1, 3, 4, 2, 2, 7, 8, 8]
>>> y      = [1, 1, 1, 1, 2, 2, 2, 3, 3]
>>> X = np.empty((len(y), 0))
>>> self = StratifiedGroupKFold(random_state=rng, shuffle=True)
>>> skf_list = list(self.split(X=X, y=y, groups=groups))
...
>>> import ubelt as ub
>>> print(ub.repr2(skf_list, nl=1, with_dtype=False))
[
    (np.array([2, 3, 4, 5, 6]), np.array([0, 1, 7, 8])),
    (np.array([0, 1, 2, 7, 8]), np.array([3, 4, 5, 6])),
    (np.array([0, 1, 3, 4, 5, 6, 7, 8]), np.array([2]))
]
```

`_iter_test_masks(self, X, y=None, groups=None)`

Generates boolean masks corresponding to test sets.

By default, delegates to `_iter_test_indices(X, y, groups)`

`split(self, X, y, groups=None)`

Generate indices to split data into training and test set.

```
kwcoco.util.smart_truncate(string, max_length=0, separator=' ', trunc_loc=0.5)
```

Truncate a string. :param string (str): string for modification :param max_length (int): output string length :param word_boundary (bool): :param save_order (bool): if True then word order of output string is like input string :param separator (str): separator between words :param trunc_loc (float): fraction of location where to remove the text :return:

2.3 Submodules

2.3.1 kwcoco.__main__

2.3.2 kwcoco._helpers

These items were split out of coco_dataset.py which is becoming too big

These are helper data structures used to do things like auto-increment ids, recycle ids, do renaming, extend sortedcontainers etc...

Module Contents

Classes

<code>_NextId</code>	Helper class to tracks unused ids for new items
<code>_ID_Remapper</code>	Helper to recycle ids for unions.
<code>UniqueNameRemapper</code>	helper to ensure names will be unique by appending suffixes
<code>SortedSetQuiet</code>	Sorted set is a sorted mutable set.

Functions

```
_lut_frame_index(imgs, gid)
```

```
_delitems(items, remove_idxs, thresh=750)
```

Parameters

- **items** (*List*) -- list which will be modified
-

```
class kwcoco._helpers._NextId(parent)
```

Bases: `object`

Helper class to tracks unused ids for new items

```
_update_unused(self, key)
```

Scans for what the next safe id can be for key

```
get(self, key)
```

Get the next safe item id for key

```
class kwcoco._helpers._ID_Remapper(reuse=False)
```

Bases: `object`

Helper to recycle ids for unions.

For each dataset we create a mapping between each old id and a new id. If possible and reuse=True we allow the new id to match the old id. After each dataset is finished we mark all those ids as used and subsequent new-ids cannot be chosen from that pool.

Parameters `reuse (bool)` – if True we are allowed to reuse ids as long as they haven't been used before.

Example

```
>>> video_trackids = [[1, 1, 3, 3, 200, 4], [204, 1, 2, 3, 3, 4, 5, 9]]
>>> self = _ID_Remapper(reuse=True)
>>> for tids in video_trackids:
>>>     new_tids = [self.remap(old_tid) for old_tid in tids]
>>>     self.block_seen()
>>>     print('new_tids = {!r}'.format(new_tids))
new_tids = [1, 1, 3, 3, 200, 4]
new_tids = [204, 205, 2, 206, 206, 207, 5, 9]
>>> #
>>> self = _ID_Remapper(reuse=False)
>>> for tids in video_trackids:
>>>     new_tids = [self.remap(old_tid) for old_tid in tids]
>>>     self.block_seen()
>>>     print('new_tids = {!r}'.format(new_tids))
new_tids = [0, 0, 1, 1, 2, 3]
new_tids = [4, 5, 6, 7, 7, 8, 9, 10]
```

`remap(self, old_id)`

Convert a old-id into a new-id. If self.reuse is True then we will return the same id if it hasn't been blocked yet.

`block_seen(self)`

Mark all seen ids as unable to be used. Any ids sent to remap will now generate new ids.

`next_id(self)`

Generate a new id that hasnt been used yet

class kwcoco._helpers.UniqueNameRemapper

Bases: `object`

helper to ensure names will be unique by appending suffixes

Example

```
>>> from kwcoco.coco_dataset import * # NOQA
>>> self = UniqueNameRemapper()
>>> assert self.remap('foo') == 'foo'
>>> assert self.remap('foo') == 'foo_v001'
>>> assert self.remap('foo') == 'foo_v002'
>>> assert self.remap('foo_v001') == 'foo_v003'
```

`remap(self, name)`

`kwcoco._helpers._lut_frame_index(imgs, gid)`

```
class kwcoco._helpers.SortedSetQuiet(iterable=None, key=None)
```

Bases: sortedcontainers.SortedSet

Sorted set is a sorted mutable set.

Sorted set values are maintained in sorted order. The design of sorted set is simple: sorted set uses a set for set-operations and maintains a sorted list of values.

Sorted set values must be hashable and comparable. The hash and total ordering of values must not change while they are stored in the sorted set.

Mutable set methods:

- `SortedSet.__contains__()`
- `SortedSet.__iter__()`
- `SortedSet.__len__()`
- `SortedSet.add()`
- `SortedSet.discard()`

Sequence methods:

- `SortedSet.__getitem__()`
- `SortedSet.__delitem__()`
- `SortedSet.__reversed__()`

Methods for removing values:

- `SortedSet.clear()`
- `SortedSet.pop()`
- `SortedSet.remove()`

Set-operation methods:

- `SortedSet.difference()`
- `SortedSet.difference_update()`
- `SortedSet.intersection()`
- `SortedSet.intersection_update()`
- `SortedSet.symmetric_difference()`
- `SortedSet.symmetric_difference_update()`
- `SortedSet.union()`
- `SortedSet.update()`

Methods for miscellany:

- `SortedSet.copy()`
- `SortedSet.count()`
- `SortedSet.__repr__()`
- `SortedSet._check()`

Sorted list methods available:

- `SortedList.bisect_left()`

- `SortedList.bisect_right()`
- `SortedList.index()`
- `SortedList.irange()`
- `SortedList.islice()`
- `SortedList._reset()`

Additional sorted list methods available, if key-function used:

- `SortedKeyList.bisect_key_left()`
- `SortedKeyList.bisect_key_right()`
- `SortedKeyList.irange_key()`

Sorted set comparisons use subset and superset relations. Two sorted sets are equal if and only if every element of each sorted set is contained in the other (each is a subset of the other). A sorted set is less than another sorted set if and only if the first sorted set is a proper subset of the second sorted set (is a subset, but is not equal). A sorted set is greater than another sorted set if and only if the first sorted set is a proper superset of the second sorted set (is a superset, but is not equal).

`__repr__(self)`

Return string representation of sorted set.

`ss.__repr__() <==> repr(ss)`

Returns string representation

`kwcoco._helpers._delitems(items, remove_idxs, thresh=750)`

Parameters

- `items (List)` – list which will be modified
- `remove_idxs (List[int])` – integers to remove (MUST BE UNIQUE)

2.3.3 kwcoco.abstract_coco_dataset

Module Contents

Classes

<code>AbstractCocoDataset</code>	This is a common base for all variants of the Coco Dataset
----------------------------------	--

`class kwcoco.abstract_coco_dataset.AbstractCocoDataset`

Bases: `abc.ABC`

This is a common base for all variants of the Coco Dataset

At the time of writing there is `kwcoco.CocoDataset` (which is the dictionary-based backend), and the `kwcoco.coco_sql_dataset.CocoSqlDataset`, which is experimental.

2.3.4 kwcoco.category_tree

The `category_tree` module defines the `CategoryTree` class, which is used for maintaining flat or hierarchical category information. The kwcoco version of this class only contains the datastructure and does not contain any torch operations. See the ndsampler version for the extension with torch operations.

Module Contents

Classes

<code>CategoryTree</code>	Wrapper that maintains flat or hierarchical category information.
---------------------------	---

`class kwcoco.category_tree.CategoryTree(graph=None, checks=True)`
Bases: `ubelt.NiceRepr`

Wrapper that maintains flat or hierarchical category information.

Helps compute softmaxes and probabilities for tree-based categories where a directed edge (A, B) represents that A is a superclass of B.

Note: There are three basic properties that this object maintains:

`node:`

Alphanumeric string names that should be generally descriptive. Using spaces `and` special characters `in` these names `is` discouraged, but can be done. This `is` the COCO category "name" attribute. For categories this may be denoted `as` (name, node, cname, catname).

`id:`

The integer `id` of a category should ideally remain consistent. These are often given by a dataset (e.g. a COCO dataset). This `is` the COCO category "id" attribute. For categories this `is` often denoted `as` (id, cid).

`index:`

Contiguous zero-based indices that indexes the `list` of categories. These should be used `for` the fastest access `in` backend computation tasks. Typically corresponds to the ordering of the channels `in` the final linear layer `in` an associated model. For categories this `is` often denoted `as` (index, cidx, idx, `or` cx).

Variables

- `idx_to_node` (`List[str]`) – a list of class names. Implicitly maps from index to category name.
- `id_to_node` (`Dict[int, str]`) – maps integer ids to category names
- `node_to_id` (`Dict[str, int]`) – maps category names to ids

- **node_to_idx** (*Dict[str, int]*) – maps category names to indexes
- **graph** (*networkx.Graph*) – a Graph that stores any hierarchy information. For standard mutually exclusive classes, this graph is edgeless. Nodes in this graph can maintain category attributes / properties.
- **idx_groups** (*List[List[int]]*) – groups of category indices that share the same parent category.

Example

```
>>> from kwcoco.category_tree import *
>>> graph = nx.from_dict_of_lists({
>>>     'background': [],
>>>     'foreground': ['animal'],
>>>     'animal': ['mammal', 'fish', 'insect', 'reptile'],
>>>     'mammal': ['dog', 'cat', 'human', 'zebra'],
>>>     'zebra': ['grevys', 'plains'],
>>>     'grevys': ['fred'],
>>>     'dog': ['boxer', 'beagle', 'golden'],
>>>     'cat': ['maine coon', 'persian', 'sphynx'],
>>>     'reptile': ['bearded dragon', 't-rex'],
>>> }, nx.DiGraph)
>>> self = CategoryTree(graph)
>>> print(self)
<CategoryTree(nNodes=22, maxDepth=6, maxBreadth=4...)>
```

Example

```
>>> # The coerce classmethod is the easiest way to create an instance
>>> import kwcoco
>>> kwcoco.CategoryTree.coerce(['a', 'b', 'c'])
<CategoryTree...nNodes=3, nodes='a', 'b', 'c'...
>>> kwcoco.CategoryTree.coerce(4)
<CategoryTree...nNodes=4, nodes='class_1', 'class_2', 'class_3', ...
>>> kwcoco.CategoryTree.coerce(4)
```

```
copy(self)
classmethod from_mutex(cls, nodes, bg_hack=True)
```

Parameters **nodes** (*List[str]*) – or a list of class names (in which case they will all be assumed to be mutually exclusive)

Example

```
>>> print(CategoryTree.from_mutex(['a', 'b', 'c']))
<CategoryTree(nNodes=3, ...)>
```

classmethod from_json(*cls, state*)

Parameters state (*Dict*) – see `__getstate__` / `__json__` for details

classmethod from_coco(*cls, categories*)

Create a CategoryTree object from coco categories

Parameters List[*Dict*] – list of coco-style categories

classmethod coerce(*cls, data, **kw*)

Attempt to coerce data as a CategoryTree object.

This is primarily useful for when the software stack depends on categories being represented

This will work if the input data is a specially formatted json dict, a list of mutually exclusive classes, or if it is already a CategoryTree. Otherwise an error will be thrown.

Parameters

- **data (*object*)** – a known representation of a category tree.
- ****kwargs** – input type specific arguments

Returns self

Return type *CategoryTree*

Raises

- **TypeError** – if the input format is unknown –
- **ValueError** – if kwargs are not compatible with the input format –

Example

```
>>> import kwcoco
>>> classes1 = kwcoco.CategoryTree.coerce(3) # integer
>>> classes2 = kwcoco.CategoryTree.coerce(classes1.__json__()) # graph dict
>>> classes3 = kwcoco.CategoryTree.coerce(['class_1', 'class_2', 'class_3']) # _mutex list
>>> classes4 = kwcoco.CategoryTree.coerce(classes1.graph) # nx Graph
>>> classes5 = kwcoco.CategoryTree.coerce(classes1) # cls
>>> # xdoctest: +REQUIRES(module:nd sampler)
>>> import nd sampler
>>> classes6 = nd sampler.CategoryTree.coerce(3)
>>> classes7 = nd sampler.CategoryTree.coerce(classes1)
>>> classes8 = kwcoco.CategoryTree.coerce(classes6)
```

classmethod demo(*cls, key='coco', **kwargs*)

Parameters key (*str*) – specify which demo dataset to use. Can be ‘coco’ (which uses the default coco demo data). Can be ‘btree’ which creates a binary tree and accepts kwargs ‘r’ and ‘h’ for branching-factor and height. Can be ‘btree2’, which is the same as btree but returns strings

CommandLine

```
xdoc test -m ~/code/kwcoco/kwcoco/category_tree.py CategoryTree.demo
```

Example

```
>>> from kwcoco.category_tree import *
>>> self = CategoryTree.demo()
>>> print('self = {}'.format(self))
self = <CategoryTree(nNodes=10, maxDepth=2, maxBreadth=4...)>
```

to_coco(self)

Converts to a coco-style data structure

Yields *Dict* – coco category dictionaries

id_to_idx(self)

Example

```
>>> import kwcoco
>>> self = kwcoco.CategoryTree.demo()
>>> self.id_to_idx[1]
```

idx_to_id(self)

Example

```
>>> import kwcoco
>>> self = kwcoco.CategoryTree.demo()
>>> self.idx_to_id[0]
```

idx_to_ancestor_idxs(self, include_self=True)

Mapping from a class index to its ancestors

Parameters **include_self** (*bool*, *default=True*) – if True includes each node as its own ancestor.

idx_to_descendants_idxs(self, include_self=False)

Mapping from a class index to its descendants (including itself)

Parameters **include_self** (*bool*, *default=False*) – if True includes each node as its own descendant.

idx_pairwise_distance(self)

Get a matrix encoding the distance from one class to another.

Distances

- from parents to children are positive (descendants),
- from children to parents are negative (ancestors),
- between unreachable nodes (wrt to forward and reverse graph) are nan.

__len__(self)

```
__iter__(self)
__getitem__(self, index)
__contains__(self, node)
__json__(self)
```

Example

```
>>> import pickle
>>> self = CategoryTree.demo()
>>> print('self = {!r}'.format(self.__json__()))
```

```
__getstate__(self)
Serializes information in this class
```

Example

```
>>> from kwcoco.category_tree import *
>>> import pickle
>>> self = CategoryTree.demo()
>>> state = self.__getstate__()
>>> serialization = pickle.dumps(self)
>>> recon = pickle.loads(serialization)
>>> assert recon.__json__() == self.__json__()
```

```
__setstate__(self, state)
__nice__(self)
is_mutex(self)
Returns True if all categories are mutually exclusive (i.e. flat)

If true, then the classes may be represented as a simple list of class names without any loss of information,
otherwise the underlying category graph is necessary to preserve all knowledge.
```

Todo:

- [] what happens when we have a dummy root?
-

```
property num_classes(self)
property class_names(self)
property category_names(self)
property cats(self)
Returns a mapping from category names to category attributes.

If this category tree was constructed from a coco-dataset, then this will contain the coco category attributes.

>Returns Dict[str, Dict[str, object]]
```

Example

```
>>> from kwcoco.category_tree import *
>>> self = CategoryTree.demo()
>>> print('self.cats = {!r}'.format(self.cats))
```

index(self, node)

Return the index that corresponds to the category name

_build_index(self)

construct lookup tables

show(self)

forest_str(self)

normalize(self)

Applies a normalization scheme to the categories.

Note: this may break other tasks that depend on exact category names.

Returns CategoryTree

Example

```
>>> from kwcoco.category_tree import * # NOQA
>>> import kwcoco
>>> orig = kwcoco.CategoryTree.demo('animals_v1')
>>> self = kwcoco.CategoryTree(nx.relabel_nodes(orig.graph, str.upper))
>>> norm = self.normalize()
```

2.3.5 kwcoco.channel_spec

The ChannelSpec has these simple rules:

- * each 1D channel **is** a alphanumeric string.
- * The pipe ('|') separates aligned early fused streams (non-commutative)
- * The comma (',') separates late-fused streams, (happens after pipe operations, **and is** commutative)
- * Certain common sets of early fused channels have codenames, **for** example:


```
rgb = r|g|b
rgba = r|g|b|a
dxdy = dy|dy
```
- * Multiple channels can be specified via a "slice" notation. For example:


```
mychan.0:4
represents 4 channels:
mychan.0, mychan.1, mychan.2, and mychan.3
```

(continues on next page)

(continued from previous page)

```
slices after the "..." work like python slices
```

For single arrays, the spec is always an early fused spec.

Todo:

- [X] : normalize representations? e.g: `rgb = r|g|b?` - OPTIONAL
 - [X] : rename to BandsSpec or SensorSpec? - REJECTED
 - [] : allow bands to be coerced, i.e. `rgb -> gray`, or `gray->rgb`
-

Todo:

- [x]: Use FusedChannelSpec as a member of ChannelSpec
 - [x]: Handle special slice suffix for length calculations
-

Note:

- do not specify the same channel in FusedChannelSpec twice
-

Example

```
>>> import kwcoco
>>> spec = kwcoco.ChannelSpec('b1|b2|b3,m.0:4|x1|x2,x.3|x.4|x.5')
>>> print(spec)
<ChannelSpec(b1|b2|b3,m.0:4|x1|x2,x.3|x.4|x.5)>
>>> for stream in spec.streams():
>>>     print(stream)
<FusedChannelSpec(b1|b2|b3)>
<FusedChannelSpec(m.0:4|x1|x2)>
<FusedChannelSpec(x.3|x.4|x.5)>
>>> # Normalization
>>> normalized = spec.normalize()
>>> print(normalized)
<ChannelSpec(b1|b2|b3,m.0|m.1|m.2|m.3|x1|x2,x.3|x.4|x.5)>
>>> print(normalized.fuse().spec)
b1|b2|b3|m.0|m.1|m.2|m.3|x1|x2|x.3|x.4|x.5
>>> print(normalized.fuse().concise().spec)
b1|b2|b3|m:4|x1|x2|x.3:6
```

Module Contents

Classes

<code>BaseChannelSpec</code>	Common code API between <code>FusedChannelSpec</code> and <code>ChannelSpec</code>
<code>FusedChannelSpec</code>	A specific type of channel spec with only one early fused stream.
<code>ChannelSpec</code>	Parse and extract information about network input channel specs for

Functions

<code>_cached_single_fused_mapping(item_keys,</code> <code>parsed_items, axis=0)</code>	
<code>_cached_single_stream_idxs(key, axis=0)</code>	
<code>subsequence_index(ose1, oset2)</code>	Returns a slice into the first items indicating the position of
<code>_parse_concise_slice_syntax(v)</code>	Helper for our slice syntax, which is may be a bit strange
<code>ose1_insert(self, index, obj)</code>	
<code>ose1_delitem(self, index)</code>	for ubelt oset, todo contribute back to luminosoinsight

`class kwcococo.channel_spec.BaseChannelSpec`

Bases: `ubelt.NiceRepr`

Common code API between `FusedChannelSpec` and `ChannelSpec`

Todo:

- [] Keep working on this base spec and ensure the inheriting classes conform to it.
-

`property spec(self)`

The string encodeing of this spec

Returns str

`abstract classmethod coerce(cls, data)`

Try and interpret the input data as some sort of spec

Parameters data (str | int | list | dict | `BaseChannelSpec`) – any input data that is known to represent a spec

Returns BaseChannelSpec

`abstract streams(self)`

Breakup this spec into individual early-fused components

Returns List[`FusedChannelSpec`]

`abstract normalize(self)`

Expand all channel codes into their normalized long-form

Returns BaseChannelSpec

```
abstract intersection(self)
abstract difference(self)
__sub__(self, other)
__nice__(self)
__json__(self)
__and__(self, other)

class kwcoco.channel_spec.FusedChannelSpec(parsed, _is_normalized=False)
Bases: BaseChannelSpec
```

A specific type of channel spec with only one early fused stream.

The channels in this stream are non-commutative

Behaves like a list of atomic-channel codes (which may represent more than 1 channel), normalized codes always represent exactly 1 channel.

Note: This class name and API is in flux and subject to change.

Todo: A special code indicating a name and some number of bands that that names contains, this would primarily be used for large numbers of channels produced by a network. Like:

resnet_d35d060_L5:512

or

resnet_d35d060_L5[:512]

might refer to a very specific (hashed) set of resnet parameters with 512 bands

maybe we can do something slicly like:

resnet_d35d060_L5[A:B] resnet_d35d060_L5:A:B

Do we want to “just store the code” and allow for parsing later?

Or do we want to ensure the serialization is parsed before we construct the data structure?

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> import pickle
>>> self = FusedChannelSpec.coerce(3)
>>> recon = pickle.loads(pickle.dumps(self))
>>> self = ChannelSpec.coerce('a|b,c|d')
>>> recon = pickle.loads(pickle.dumps(self))
```

_alias_lut

_memo

_size_lut

__len__(self)
__getitem__(self, index)
classmethod concat(cls, items)
spec(self)
The string encodeing of this spec
Returns str
unique(self)
classmethod parse(cls, spec)
classmethod coerce(cls, data)

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> FusedChannelSpec.coerce(['a', 'b', 'c'])
>>> FusedChannelSpec.coerce('a|b|c')
>>> FusedChannelSpec.coerce(3)
>>> FusedChannelSpec.coerce(FusedChannelSpec(['a']))
>>> assert FusedChannelSpec.coerce('') .numel() == 0
```

concise(self)
Shorted the channel spec by de-normaliz slice syntax
Returns concise spec
Return type *FusedChannelSpec*

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> self = FusedChannelSpec.coerce(
    ...     'b|a|a.0|a.1|a.2|a.5|c|a.8|a.9|b.0:3|c.0')
>>> short = self.concise()
>>> long = short.normalize()
>>> numels = [c.numel() for c in [self, short, long]]
>>> print('self.spec = {!r}'.format(self.spec))
>>> print('short.spec = {!r}'.format(short.spec))
>>> print('long.spec = {!r}'.format(long.spec))
>>> print('numels = {!r}'.format(numels))
self.spec = 'b|a|a.0|a.1|a.2|a.5|c|a.8|a.9|b.0:3|c.0'
short.spec = 'b|a|a:3|a.5|c|a.8:10|b:3|c.0'
long.spec = 'b|a|a.0|a.1|a.2|a.5|c|a.8|a.9|b.0|b.1|b.2|c.0'
numels = [13, 13, 13]
>>> assert long.concise().spec == short.spec
```

normalize(self)
Replace aliases with explicit single-band-per-code specs
Returns normalize spec
Return type *FusedChannelSpec*

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> self = FusedChannelSpec.coerce('b1|b2|b3|rgb')
>>> normed = self.normalize()
>>> print('self = {}'.format(self))
>>> print('normed = {}'.format(normed))
self = <FusedChannelSpec(b1|b2|b3|rgb)>
normed = <FusedChannelSpec(b1|b2|b3|r|g|b)>
>>> self = FusedChannelSpec.coerce('B:1:11')
>>> normed = self.normalize()
>>> print('self = {}'.format(self))
>>> print('normed = {}'.format(normed))
self = <FusedChannelSpec(B:1:11)>
normed = <FusedChannelSpec(B.1|B.2|B.3|B.4|B.5|B.6|B.7|B.8|B.9|B.10)>
>>> self = FusedChannelSpec.coerce('B.1:11')
>>> normed = self.normalize()
>>> print('self = {}'.format(self))
>>> print('normed = {}'.format(normed))
self = <FusedChannelSpec(B.1:11)>
normed = <FusedChannelSpec(B.1|B.2|B.3|B.4|B.5|B.6|B.7|B.8|B.9|B.10)>
```

`numel(self)`

Total number of channels in this spec

`sizes(self)`

Returns a list indicating the size of each atomic code

Returns List[int]

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> self = FusedChannelSpec.coerce('b1|Z:3|b2|b3|rgb')
>>> self.sizes()
[1, 3, 1, 1, 3]
>>> assert(FusedChannelSpec.parse('a.0').numel() == 1
>>> assert(FusedChannelSpec.parse('a:0').numel() == 0
>>> assert(FusedChannelSpec.parse('a:1').numel() == 1
```

`__contains__(self, key)`

Example

```
>>> FCS = FusedChannelSpec.coerce
>>> 'disparity' in FCS('rgb|disparity|flowx|flowy')
True
>>> 'gray' in FCS('rgb|disparity|flowx|flowy')
False
```

`code_list(self)`

Return the expanded code list

as_list(self)**as_oset(self)****as_set(self)****as_path(self)**

Returns a string suitable for use in a path.

Note, this may no longer be a valid channel spec

__set__(self)**difference(self, other)**

Set difference

Example

```
>>> FCS = FusedChannelSpec.coerce
>>> self = FCS('rgb|disparity|flowx|flowy')
>>> other = FCS('r|b')
>>> self.difference(other)
>>> other = FCS('flowx')
>>> self.difference(other)
>>> FCS = FusedChannelSpec.coerce
>>> assert len((FCS('a') - {'a'}).parsed) == 0
>>> assert len((FCS('a.0:3') - {'a.0'}).parsed) == 2
```

intersection(self, other)

Example

```
>>> FCS = FusedChannelSpec.coerce
>>> self = FCS('rgb|disparity|flowx|flowy')
>>> other = FCS('r|b|XX')
>>> self.intersection(other)
```

component_indices(self, axis=2)

Look up component indices within this stream

Example

```
>>> FCS = FusedChannelSpec.coerce
>>> self = FCS('disparity|rgb|flowx|flowy')
>>> component_indices = self.component_indices()
>>> print('component_indices = {}'.format(ub.repr2(component_indices, nl=1)))
component_indices =
{'disparity': (slice(...), slice(...), slice(0, 1, None)),
 'flowx': (slice(...), slice(...), slice(4, 5, None)),
 'flowy': (slice(...), slice(...), slice(5, 6, None)),
 'rgb': (slice(...), slice(...), slice(1, 4, None)),}
```

streams(*self*)
Idempotence with *ChannelSpec.streams()*

fuse(*self*)
Idempotence with *ChannelSpec.streams()*

class `kwcococo.channel_spec.ChannelSpec(spec, parsed=None)`
Bases: *BaseChannelSpec*

Parse and extract information about network input channel specs for early or late fusion networks.

Behaves like a dictionary of *FusedChannelSpec* objects

Todo:

- [] Rename to something that indicates this is a collection of *FusedChannelSpec*? *MultiChannelSpec*?
-

Note: This class name and API is in flux and subject to change.

Note: The pipe ('|') character represents an early-fused input stream, and order matters (it is non-commutative). The comma (',') character separates different inputs streams/branches for a multi-stream/branch network which will be later fused. Order does not matter

Example

```
>>> from kwcococo.channel_spec import * # NOQA
>>> # Integer spec
>>> ChannelSpec.coerce(3)
<ChannelSpec(u0|u1|u2) ...>
```

```
>>> # single mode spec
>>> ChannelSpec.coerce('rgb')
<ChannelSpec(rgb) ...>
```

```
>>> # early fused input spec
>>> ChannelSpec.coerce('rgb|disparity')
<ChannelSpec(rgb|disparity) ...>
```

```
>>> # late fused input spec
>>> ChannelSpec.coerce('rgb,disparity')
<ChannelSpec(rgb,disparity) ...>
```

```
>>> # early and late fused input spec
>>> ChannelSpec.coerce('rgb|ir,disparity')
<ChannelSpec(rgb|ir,disparity) ...>
```

Example

```
>>> self = ChannelSpec('gray')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>> self = ChannelSpec('rgb')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>> self = ChannelSpec('rgb|disparity')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>> self = ChannelSpec('rgb|disparity,disparity')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>> self = ChannelSpec('rgb,disparity,flowx|flowy')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
```

Example

```
>>> specs = [
>>>     'rgb',                      # and rgb input
>>>     'rgb|disparity',            # rgb early fused with disparity
>>>     'rgb,disparity',           # rgb early late with disparity
>>>     'rgb|ir,disparity',         # rgb early fused with ir and late fused with disparity
>>>     3,                          # 3 unknown channels
>>> ]
>>> for spec in specs:
>>>     print('=====')
>>>     print('spec = {!r}'.format(spec))
>>>     #
>>>     self = ChannelSpec.coerce(spec)
>>>     print('self = {!r}'.format(self))
>>>     sizes = self.sizes()
>>>     print('sizes = {!r}'.format(sizes))
>>>     print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>>     #
>>>     item = self._demo_item((1, 1), rng=0)
>>>     inputs = self.encode(item)
>>>     components = self.decode(inputs)
>>>     input_shapes = ub.map_vals(lambda x: x.shape, inputs)
>>>     component_shapes = ub.map_vals(lambda x: x.shape, components)
>>>     print('item = {}'.format(ub.repr2(item, precision=1)))
>>>     print('inputs = {}'.format(ub.repr2(inputs, precision=1)))
>>>     print('input_shapes = {}'.format(ub.repr2(input_shapes)))
>>>     print('components = {}'.format(ub.repr2(components, precision=1)))
>>>     print('component_shapes = {}'.format(ub.repr2(component_shapes, nl=1)))
```

property spec(self)

The string encodeing of this spec

Returns str

__contains__(self, key)

Example

```
>>> 'disparity' in ChannelSpec('rgb,disparity,flowx|flowy')
True
>>> 'gray' in ChannelSpec('rgb,disparity,flowx|flowy')
False
```

property info(self)
classmethod coerce(cls, data)
Attempt to interpret the data as a channel specification
Returns ChannelSpec

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> data = FusedChannelSpec.coerce(3)
>>> assert ChannelSpec.coerce(data).spec == 'u0|u1|u2'
>>> data = ChannelSpec.coerce(3)
>>> assert data.spec == 'u0|u1|u2'
>>> assert ChannelSpec.coerce(data).spec == 'u0|u1|u2'
>>> data = ChannelSpec.coerce('u:3')
>>> assert data.normalize().spec == 'u.0|u.1|u.2'
```

parse(self)
Build internal representation

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> self = ChannelSpec('b1|b2|b3|rgb,B:3')
>>> print(self.parse())
>>> print(self.normalize().parse())
>>> ChannelSpec('').parse()
```

Example

```
>>> base = ChannelSpec('rgb|disparity,flowx|r|flowy')
>>> other = ChannelSpec('rgb')
>>> self = base.intersection(other)
>>> assert self.numel() == 4
```

concise(self)

Example

```
>>> self = ChannelSpec('b1|b2,b3|rgb|B.0,B.1|B.2')
>>> print(self.concise().spec)
b1|b2,b3|r|g|b|B.0,B.1:3
```

normalize(self)

Replace aliases with explicit single-band-per-code specs

Returns normalized spec**Return type** *ChannelSpec***Example**

```
>>> self = ChannelSpec('b1|b2,b3|rgb,B:3')
>>> normed = self.normalize()
>>> print('self  = {}'.format(self))
>>> print('normed = {}'.format(normed))
self  = <ChannelSpec(b1|b2,b3|rgb,B:3)>
normed = <ChannelSpec(b1|b2,b3|r|g|b,B.0|B.1|B.2)>
```

keys(self)**values(self)****items(self)****fuse(self)**

Fuse all parts into an early fused channel spec

Returns FusedChannelSpec**Example**

```
>>> from kwcoco.channel_spec import * # NOQA
>>> self = ChannelSpec.coerce('b1|b2,b3|rgb,B:3')
>>> fused = self.fuse()
>>> print('self  = {}'.format(self))
>>> print('fused = {}'.format(fused))
self  = <ChannelSpec(b1|b2,b3|rgb,B:3)>
fused = <FusedChannelSpec(b1|b2|b3|rgb|B:3)>
```

streams(self)

Breaks this spec up into one spec for each early-fused input stream

Example

```
self = ChannelSpec.coerce('r|g,B1|B2,fx|fy') list(map(len, self.streams()))  
code_list(self)  
as_path(self)
```

Returns a string suitable for use in a path.

Note, this may no longer be a valid channel spec

```
difference(self, other)
```

Set difference. Remove all instances of other channels from this set of channels.

Example

```
>>> from kwCOCO.channel_spec import *  
>>> self = ChannelSpec('rgb|disparity,flowx|r|flowy')  
>>> other = ChannelSpec('rgb')  
>>> print(self.difference(other))  
>>> other = ChannelSpec('flowx')  
>>> print(self.difference(other))  
<ChannelSpec(disparity,flowx|flowy)>  
<ChannelSpec(r|g|b|disparity,r|flowy)>
```

Example

```
>>> from kwCOCO.channel_spec import *  
>>> self = ChannelSpec('a|b,c|d')  
>>> new = self - {'a', 'b'}  
>>> len(new.sizes()) == 1  
>>> empty = new - 'c|d'  
>>> assert empty.numel() == 0
```

```
intersection(self, other)
```

Set difference. Remove all instances of other channels from this set of channels.

Example

```
>>> from kwCOCO.channel_spec import *  
>>> self = ChannelSpec('rgb|disparity,flowx|r|flowy')  
>>> other = ChannelSpec('rgb')  
>>> new = self.intersection(other)  
>>> print(new)  
>>> print(new.numel())  
>>> other = ChannelSpec('flowx')  
>>> new = self.intersection(other)  
>>> print(new)  
>>> print(new.numel())  
<ChannelSpec(r|g|b,r)>  
4
```

(continues on next page)

(continued from previous page)

```
<ChannelSpec(flowx)>
1
```

numel(self)

Total number of channels in this spec

sizes(self)

Number of dimensions for each fused stream channel

IE: The EARLY-FUSED channel sizes

Example

```
>>> self = ChannelSpec('rgb|disparity,flowx|flowy,B:10')
>>> self.normalize().concise()
>>> self.sizes()
```

unique(self, normalize=False)

Returns the unique channels that will need to be given or loaded

_item_shapes(self, dims)

Expected shape for an input item

Parameters **dims** (*Tuple[int, int]*) – the spatial dimension

Returns *Dict[int, tuple]*

_demo_item(self, dims=(4, 4), rng=None)

Create an input that satisfies this spec

Returns

an item like it might appear when its returned from the `__getitem__` method of a `torch...Dataset`.

Return type `dict`

Example

```
>>> dims = (1, 1)
>>> ChannelSpec.coerce(3)._demo_item(dims, rng=0)
>>> ChannelSpec.coerce('r|g|b|disparity')._demo_item(dims, rng=0)
>>> ChannelSpec.coerce('rgb|disparity')._demo_item(dims, rng=0)
>>> ChannelSpec.coerce('rgb,disparity')._demo_item(dims, rng=0)
>>> ChannelSpec.coerce('rgb')._demo_item(dims, rng=0)
>>> ChannelSpec.coerce('gray')._demo_item(dims, rng=0)
```

encode(self, item, axis=0, mode=1)

Given a dictionary containing preloaded components of the network inputs, build a concatenated (fused) network representations of each input stream.

Parameters

- **item** (*Dict[str, Tensor]*) – a batch item containing unfused parts. each key should be a single-stream (optionally early fused) channel key.
- **axis** (*int, default=0*) – concatenation dimension

Returns mapping between input stream and its early fused tensor input.

Return type Dict[str, Tensor]

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> import numpy as np
>>> dims = (4, 4)
>>> item = {
>>>     'rgb': np.random.rand(3, *dims),
>>>     'disparity': np.random.rand(1, *dims),
>>>     'flowx': np.random.rand(1, *dims),
>>>     'flowy': np.random.rand(1, *dims),
>>> }
>>> # Complex Case
>>> self = ChannelSpec('rgb,disparity,rgb|disparity|flowx|flowy,flowx|flowy')
>>> fused = self.encode(item)
>>> input_shapes = ub.map_vals(lambda x: x.shape, fused)
>>> print('input_shapes = {}'.format(ub.repr2(input_shapes, nl=1)))
>>> # Simpler case
>>> self = ChannelSpec('rgb|disparity')
>>> fused = self.encode(item)
>>> input_shapes = ub.map_vals(lambda x: x.shape, fused)
>>> print('input_shapes = {}'.format(ub.repr2(input_shapes, nl=1)))
```

Example

```
>>> # Case where we have to break up early fused data
>>> import numpy as np
>>> dims = (40, 40)
>>> item = {
>>>     'rgb|disparity': np.random.rand(4, *dims),
>>>     'flowx': np.random.rand(1, *dims),
>>>     'flowy': np.random.rand(1, *dims),
>>> }
>>> # Complex Case
>>> self = ChannelSpec('rgb,disparity,rgb|disparity,rgb|disparity|flowx|flowy,
>>> ~flowx|flowy,flowx,disparity')
>>> inputs = self.encode(item)
>>> input_shapes = ub.map_vals(lambda x: x.shape, inputs)
>>> print('input_shapes = {}'.format(ub.repr2(input_shapes, nl=1)))
```

```
>>> # xdoctest: +REQUIRES(--bench)
>>> #self = ChannelSpec('rgb/disparity,flowx/flowy')
>>> import timerit
>>> ti = timerit.Timerit(100, bestof=10, verbose=2)
>>> for timer in ti.reset('mode=simple'):
>>>     with timer:
>>>         inputs = self.encode(item, mode=0)
>>> for timer in ti.reset('mode=minimize-concat'):
```

(continues on next page)

(continued from previous page)

```
>>>     with timer:
>>>         inputs = self.encode(item, mode=1)
```

decode(self, inputs, axis=1)
break an early fused item into its components

Parameters

- **inputs** (*Dict[str, Tensor]*) – dictionary of components
- **axis** (*int, default=1*) – channel dimension

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> import numpy as np
>>> dims = (4, 4)
>>> item_components = {
>>>     'rgb': np.random.rand(3, *dims),
>>>     'ir': np.random.rand(1, *dims),
>>> }
>>> self = ChannelSpec('rgb|ir')
>>> item_encoded = self.encode(item_components)
>>> batch = {k: np.concatenate([v[None, :], v[None, :]], axis=0)
...         for k, v in item_encoded.items()}
>>> components = self.decode(batch)
```

Example

```
>>> # xdoctest: +REQUIRES(module:netharn, module:torch)
>>> import torch
>>> import numpy as np
>>> dims = (4, 4)
>>> components = {
>>>     'rgb': np.random.rand(3, *dims),
>>>     'ir': np.random.rand(1, *dims),
>>> }
>>> components = ub.map_vals(torch.from_numpy, components)
>>> self = ChannelSpec('rgb|ir')
>>> encoded = self.encode(components)
>>> from netharn.data import data_containers
>>> item = {k: data_containers.ItemContainer(v, stack=True)
...         for k, v in encoded.items()}
>>> batch = data_containers.container_collate([item, item])
>>> components = self.decode(batch)
```

component_indices(self, axis=2)
Look up component indices within fused streams

Example

```
>>> dims = (4, 4)
>>> inputs = ['flowx', 'flowy', 'disparity']
>>> self = ChannelSpec('disparity,flowx|flowy')
>>> component_indices = self.component_indices()
>>> print('component_indices = {}'.format(ub.repr2(component_indices, nl=1)))
component_indices =
    'disparity': ('disparity', (slice(None, None, None), slice(None, None, None), slice(0, 1, None))),
    'flowx': ('flowx|flowy', (slice(None, None, None), slice(None, None, None), slice(0, 1, None))),
    'flowy': ('flowx|flowy', (slice(None, None, None), slice(None, None, None), slice(1, 2, None))),
```

kwcoco.channel_spec._cached_single_fused_mapping(item_keys, parsed_items, axis=0)

kwcoco.channel_spec._cached_single_stream_idxs(key, axis=0)

kwcoco.channel_spec.subsequence_index(oset1, oset2)

Returns a slice into the first items indicating the position of the second items if they exist.

This is a variant of the substring problem.

Returns None | slice

Example

```
>>> oset1 = ub.oset([1, 2, 3, 4, 5, 6])
>>> oset2 = ub.oset([2, 3, 4])
>>> index = subsequence_index(oset1, oset2)
>>> assert index
```

```
>>> oset1 = ub.oset([1, 2, 3, 4, 5, 6])
>>> oset2 = ub.oset([2, 4, 3])
>>> index = subsequence_index(oset1, oset2)
>>> assert not index
```

kwcoco.channel_spec._parse_concise_slice_syntax(v)

Helper for our slice syntax, which is may be a bit strange

Example

```
>>> print(_parse_concise_slice_syntax('B:10'))
>>> print(_parse_concise_slice_syntax('B.0:10:3'))
>>> print(_parse_concise_slice_syntax('B.:10:3'))
>>> print(_parse_concise_slice_syntax('B::10:3'))
>>> # Careful, this next one is quite different
>>> print(_parse_concise_slice_syntax('B:10:3'))
>>> print(_parse_concise_slice_syntax('B:3:10:3'))
>>> print(_parse_concise_slice_syntax('B.:10'))
```

(continues on next page)

(continued from previous page)

```

>>> print(_parse_concise_slice_syntax('B.:3:'))
>>> print(_parse_concise_slice_syntax('B.:3:2'))
>>> print(_parse_concise_slice_syntax('B::2:3'))
>>> print(_parse_concise_slice_syntax('B.0:10:3'))
>>> print(_parse_concise_slice_syntax('B.:10:3'))
('B', 0, 10, 1)
('B', 0, 10, 3)
('B', 0, 10, 3)
('B', 0, 10, 3)
('B', 10, 3, 1)
('B', 3, 10, 3)
('B', 0, 10, 1)
('B', 0, 3, 1)
('B', 0, 3, 2)
('B', 0, 2, 3)
('B', 0, 10, 3)
('B', 0, 10, 3)
>>> import pytest
>>> with pytest.raises(ValueError):
>>>     _parse_concise_slice_syntax('B.0')
>>> with pytest.raises(ValueError):
>>>     _parse_concise_slice_syntax('B0')
>>> with pytest.raises(ValueError):
>>>     _parse_concise_slice_syntax('B:')
>>> with pytest.raises(ValueError):
>>>     _parse_concise_slice_syntax('B:0.10')
>>> with pytest.raises(ValueError):
>>>     _parse_concise_slice_syntax('B::')

```

`kwcoco.channel_spec.oset_insert(self, index, obj)`

`kwcoco.channel_spec.oset_delitem(self, index)`

for ubelt oset, todo contribute back to luminosoinight

```

>>> self = ub.oset([1, 2, 3, 4, 5, 6, 7, 8, 9])
>>> index = slice(3, 5)
>>> oset_delitem(self, index)

```

2.3.6 kwcoco.coco_dataset

An implementation and extension of the original MS-COCO API¹.

Extends the format to also include line annotations.

The following describes psuedo-code for the high level spec (some of which may not be have full support in the Python API). A formal json-schema is defined in `kwcoco.coco_schema`.

An informal spec is as follows:

```

# All object categories are defined here.
category = {

```

(continues on next page)

¹ <http://cocodataset.org/#format-data>

(continued from previous page)

```

'id': int,
'name': str, # unique name of the category
'supercategory': str, # parent category name
}

# Videos are used to manage collections or sequences of images.
# Frames do not necessarily have to be aligned or uniform time steps
video = {
    'id': int,
    'name': str, # a unique name for this video.

    'width': int # the base width of this video (all associated images must have this)
    'height': int # the base height of this video (all associated images must have this)
    }

    # In the future this may be extended to allow pointing to video files
}

# Specifies how to find sensor data of a particular scene at a particular
# time. This is usually paths to rgb images, but auxiliary information
# can be used to specify multiple bands / etc...
image = {
    'id': int,

    'name': str, # an encouraged but optional unique name
    'file_name': str, # relative path to the "base" image data

    'width': int, # pixel width of "base" image
    'height': int, # pixel height of "base" image

    'channels': <ChannelSpec>, # a string encoding of the channels in the main image

    'auxiliary': [ # information about any auxiliary channels / bands
        {
            'file_name': str, # relative path to associated file
            'channels': <ChannelSpec>, # a string encoding
            'width': <int> # pixel width of auxiliary image
            'height': <int> # pixel height of auxiliary image
            'warp_aux_to_img': <TransformSpec>, # transform from "base" image space to
            # auxiliary image space. (identity if unspecified)
        },
        ...
    ]

    'video_id': str # if this image is a frame in a video sequence, this id is shared
    # by all frames in that sequence.
    'timestamp': str | int # a iso-string timestamp or an integer in flicks.
    'frame_index': int # ordinal frame index which can be used if timestamp is unknown.
    'warp_img_to_vid': <TransformSpec> # a transform image space to video space
    # (identity if unspecified), can be used for sensor alignment or video stabilization
}

```

(continues on next page)

(continued from previous page)

TransformSpec:

The spec can be anything coercable to a `kwimage.Affine` object.

This can be an explicit affine transform matrix like:

```
{'type': 'affine': 'matrix': <a-3x3 matrix>},
```

But it can also be a concise dict containing one or more of these keys

```
{
    'scale': <float|Tuple[float, float]>,
    'offset': <float|Tuple[float, float]>,
    'skew': <float>,
    'theta': <float>, # radians counter-clock-wise
}
```

ChannelSpec:

This is a string that describes the channel composition of an image.

For the purposes of kwcoco, separate different channel names with a pipe ('|'). If the spec is not specified, methods may fall back on grayscale or rgb processing. There are special string. For instance 'rgb' will expand into 'r|g|b'. In other applications you can "late fuse" inputs by separating them with a "," and "early fuse" by separating with a "|". Early fusion returns a solid array/tensor, late fusion returns separated arrays/tensors.

```
# Ground truth is specified as annotations, each belongs to a spatial
# region in an image. This must reference a subregion of the image in pixel
# coordinates. Additional non-schema properties can be specified to track
# location in other coordinate systems. Annotations can be linked over time
# by specifying track-ids.

annotation = {
    'id': int,
    'image_id': int,
    'category_id': int,

    'track_id': <int | str | uuid> # indicates association between annotations across
    ↵images

    'bbox': [tl_x, tl_y, w, h], # xywh format
    'score' : float,
    'prob' : List[float],
    'weight' : float,

    'caption': str, # a text caption for this annotation
    'keypoints' : <Keypoints | List[int] > # an accepted keypoint format
    'segmentation': <RunLengthEncoding | Polygon | MaskPath | WKT >, # an accepted
    ↵segmentation format
}

# A dataset bundles a manifest of all aforementioned data into one structure.
dataset = [
    'categories': [category, ...],
    'videos': [video, ...]
    'images': [image, ...]
```

(continues on next page)

(continued from previous page)

```
'annotations': [annotation, ...]
'licenses': [],
'info': [],
}
```

Polygon:

A flattened list of xy coordinates.
 $[x_1, y_1, x_2, y_2, \dots, x_n, y_n]$

or a list of flattened list of xy coordinates if the CCs are disjoint
 $[[x_1, y_1, x_2, y_2, \dots, x_n, y_n], [x_1, y_1, \dots, x_m, y_m], \dots]$

Note: the original coco spec does not allow for holes in polygons.

We also allow a non-standard dictionary encoding of polygons

```
{'exterior': [(x1, y1)...],
 'interiors': [[[x1, y1], ...], ...]}
```

TODO: Support WTK

RunLengthEncoding:

The RLE can be in a special bytes encoding or in a binary array encoding. We reuse the original C functions are in [2]_ in ``kwimage.structs.Mask`` to provide a convenient way to abstract this rather esoteric bytes encoding.

For pure python implementations see kwimage:

Converting from an image to RLE can be done via kwimage.run_length_encoding
 Converting from RLE back to an image can be done via:
`kwimage.decode_run_length`

For compatibility with the COCO specs ensure the binary flags for these functions are set to true.

Keypoints:

Annotation keypoints may also be specified in this non-standard (but ultimately more general) way:

```
'annotations': [
  {
    'keypoints': [
      {
        'xy': <x1, y1>,
        'visible': <0 or 1 or 2>,
        'keypoint_category_id': <kp_cid>,
        'keypoint_category': <kp_name, optional>, # this can be specified
        ↵ instead of an id
        },
      ...
    ],
  ...
],
'keypoint_categories': [{
```

(continues on next page)

(continued from previous page)

```

'name': <str>,
'id': <int>, # an id for this keypoint category
'supercategory': <kp_name> # name of coarser parent keypoint class (for


```

In this scheme the "keypoints" property of each annotation (which used to be a list of floats) is now specified as a list of dictionaries that specify each keypoints location, id, and visibility explicitly. This allows for things like non-unique keypoints, partial keypoint annotations. This also removes the ordering requirement, which makes it simpler to keep track of each keypoints class type.

We also have a new top-level dictionary to specify all the possible keypoint categories.

TODO: Support WTK

Auxiliary Channels:

For multimodal or multispectral images it is possible to specify auxiliary channels in an image dictionary as follows:

```

{
    'id': int,
    'file_name': str, # path to the "base" image (may be None)
    'name': str, # a unique name for the image (must be given if file_name
is None)
    'channels': <spec>, # a spec code that indicates the layout of the "base" image
channels.
    'auxiliary': [ # information about auxiliary channels
        {
            'file_name': str,
            'channels': <spec>
        }, ... # can have many auxiliary channels with unique specs
    ]
}

```

Video Sequences:

For video sequences, we add the following video level index:

```

'videos': [
    { 'id': <int>, 'name': <video_name:str> },
]

```

Note that the videos might be given as encoded mp4/avi/etc.. files (in which case the name should correspond to a path) or as a series of frames in which case the images should be used to index the extracted frames and information in them.

(continues on next page)

(continued from previous page)

Then image dictionaries are augmented as follows:

```
{
    'video_id': str # optional, if this image is a frame in a video sequence, this id is shared by all frames in that sequence.
    'timestamp': int # optional, timestamp (ideally in flicks), used to identify the timestamp of the frame. Only applicable video inputs.
    'frame_index': int # optional, ordinal frame index which can be used if timestamp is unknown.
}
```

And annotations are augmented as follows:

```
{
    'track_id': <int | str | uuid> # optional, indicates association between annotations across frames
}
```

Note: The main object in this file is `CocoDataset`, which is composed of several mixin classes. See the class and method documentation for more details.

Todo:

- [] Use ijson to lazily load pieces of the dataset in the background or on demand. This will give us faster access to categories / images, whereas we will always have to wait for annotations etc...
 - [X] Should img_root be changed to bundle_dpath?
 - [] Read video data, return numpy arrays (requires API for images)
 - [] Spec for video URI, and convert to frames @ framerate function.
 - [] Document channel spec
 - [X] remove videos
-

References

Module Contents

Classes

<code>MixinCocoDeprecate</code>	These functions are marked for deprecation and may be removed at any time
<code>MixinCocoAccessors</code>	TODO: better name
<code>MixinCocoExtras</code>	Misc functions for coco
<code>MixinCocoObjects</code>	Expose methods to construct object lists / groups.
<code>MixinCocoStats</code>	Methods for getting stats about the dataset
<code>MixinCocoDraw</code>	Matplotlib / display functionality

continues on next page

Table 96 – continued from previous page

<code>MixinCocoAddRemove</code>	Mixin functions to dynamically add / remove annotations images and
<code>CocoIndex</code>	Fast lookup index for the COCO dataset with dynamic modification
<code>MixinCocoIndex</code>	Give the dataset top level access to index attributes
<code>CocoDataset</code>	The main coco dataset class with a json dataset backend.

Functions

<code>demo_coco_data()</code>	Simple data for testing.
-------------------------------	--------------------------

Attributes

`_dict``SPEC_KEYS``kwcoco.coco_dataset._dict``kwcoco.coco_dataset.SPEC_KEYS = ['info', 'licenses', 'categories', 'keypoint_categories', 'videos', 'images', 'annotations']``class kwcoco.coco_dataset.MixinCocoDeprecate`Bases: `object`

These functions are marked for deprecation and may be removed at any time

`class kwcoco.coco_dataset.MixinCocoAccessors`Bases: `object`

TODO: better name

`delayed_load(self, gid, channels=None, space='image')`

Experimental method

Parameters

- `gid (int)` – image id to load
- `channels (FusedChannelSpec)` – specific channels to load. if unspecified, all channels are loaded.
- `space (str)` – can either be “image” for loading in image space, or “video” for loading in video space.

Todo:

- [X] **Currently can only take all or none of the channels from each base-image / auxiliary dict.**
For instance if the main image is r|g|b you can't just select g|b at the moment.
- [X] **The order of the channels in the delayed load should** match the requested channel order.
- [X] TODO: add nans to bands that don't exist or throw an error

Example

```
>>> import kwCOCO
>>> gid = 1
>>> #
>>> self = kwCOCO.CocoDataset.demo('vidshapes8-multispectral')
>>> delayed = self.delayed_load(gid)
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize()))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
>>> #
>>> self = kwCOCO.CocoDataset.demo('shapes8')
>>> delayed = self.delayed_load(gid)
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize()))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
```

```
>>> crop = delayed.delayed_crop((slice(0, 3), slice(0, 3)))
>>> crop.finalize()
>>> crop.finalize(as_xarray=True)
```

```
>>> # TODO: should only select the "red" channel
>>> self = kwCOCO.CocoDataset.demo('shapes8')
>>> delayed = self.delayed_load(gid, channels='r')
```

```
>>> import kwCOCO
>>> gid = 1
>>> #
>>> self = kwCOCO.CocoDataset.demo('vidshapes8-multispectral')
>>> delayed = self.delayed_load(gid, channels='B1|B2', space='image')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
>>> delayed = self.delayed_load(gid, channels='B1|B2|B11', space='image')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
>>> delayed = self.delayed_load(gid, channels='B8|B1', space='video')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
```

```
>>> delayed = self.delayed_load(gid, channels='B8|foo|bar|B1', space='video')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
```

load_image(*self*, *gid_or_img*, *channels=None*)

Reads an image from disk and

Parameters

- **gid_or_img** (*int or dict*) – image id or image dict
- **channels** (*str | None*) – if specified, load data from auxiliary channels instead

Returns the image

Return type np.ndarray

Todo:

- [] allow specification of multiple channels - use `delayed image` for this.
-

get_image_fpath(*self*, *gid_or_img*, *channels=None*)

Returns the full path to the image

Parameters

- **gid_or_img** (*int or dict*) – image id or image dict
- **channels** (*str, default=None*) – if specified, return a path to data containing auxiliary channels instead

Returns full path to the image

Return type PathLike

_get_img_auxiliary(*self*, *gid_or_img*, *channels*)

returns the auxiliary dictionary for a specific channel

get_auxiliary_fpath(*self*, *gid_or_img*, *channels*)

Returns the full path to auxiliary data for an image

Parameters

- **gid_or_img** (*int | dict*) – an image or its id
- **channels** (*str*) – the auxiliary channel to load (e.g. disparity)

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo('shapes8', aux=True)
>>> self.get_auxiliary_fpath(1, 'disparity')
```

load_annot_sample(*self*, *aid_or_ann*, *image=None*, *pad=None*)

Reads the chip of an annotation. Note this is much less efficient than using a sampler, but it doesn't require disk cache.

Maybe deprecate?

Parameters

- **aid_or_int** (*int or dict*) – annot id or dict
- **image** (*ArrayLike, default=None*) – preloaded image (note: this process is inefficient unless image is specified)

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> sample = self.load_annot_sample(2, pad=100)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(sample['im'])
>>> kwplot.show_if_requested()
```

_resolve_to_id(self, id_or_dict)

Ensures output is an id

_resolve_to_cid(self, id_or_name_or_dict)

Ensures output is an category id

Note: this does not resolve aliases (yet), for that see _alias_to_cat

Todo: we could maintain an alias index to make this fast

_resolve_to_gid(self, id_or_name_or_dict)

Ensures output is an category id

_resolve_to_vidid(self, id_or_name_or_dict)

Ensures output is an video id

_resolve_to_ann(self, aid_or_ann)

Ensures output is an annotation dictionary

_resolve_to_img(self, gid_or_img)

Ensures output is an image dictionary

_resolve_to_kpcat(self, kp_identifier)

Lookup a keypoint-category dict via its name or id

Parameters **kp_identifier** (*int | str | dict*) – either the keypoint category name, alias, or its key-point_category_id.

Returns keypoint category dictionary

Return type Dict

Example

```
>>> self = CocoDataset.demo('shapes')
>>> kpcat1 = self._resolve_to_kpcat(1)
>>> kpcat2 = self._resolve_to_kpcat('left_eye')
>>> assert kpcat1 is kpcat2
>>> import pytest
>>> with pytest.raises(KeyError):
>>>     self._resolve_to_cat('human')
```

_resolve_to_cat(self, cat_identifier)

Lookup a coco-category dict via its name, alias, or id.

Parameters `cat_identifier` (`int | str | dict`) – either the category name, alias, or its category_id.

Raises `KeyError` – if the category doesn't exist.

Note: If the index is not built, the method will work but may be slow.

Example

```
>>> self = CocoDataset.demo()
>>> cat = self._resolve_to_cat('human')
>>> import pytest
>>> assert self._resolve_to_cat(cat['id']) is cat
>>> assert self._resolve_to_cat(cat) is cat
>>> with pytest.raises(KeyError):
>>>     self._resolve_to_cat(32)
>>> self.index.clear()
>>> assert self._resolve_to_cat(cat['id']) is cat
>>> with pytest.raises(KeyError):
>>>     self._resolve_to_cat(32)
```

_alias_to_cat(self, alias_catname)

Lookup a coco-category via its name or an “alias” name. In production code, use `_resolve_to_cat()` instead.

Parameters `alias_catname` (`str`) – category name or alias

Returns coco category dictionary

Return type `dict`

Example

```
>>> self = CocoDataset.demo()
>>> cat = self._alias_to_cat('human')
>>> import pytest
>>> with pytest.raises(KeyError):
>>>     self._alias_to_cat('person')
>>> cat['alias'] = ['person']
>>> self._alias_to_cat('person')
>>> cat['alias'] = 'person'
>>> self._alias_to_cat('person')
>>> assert self._alias_to_cat(None) is None
```

category_graph(self)

Construct a networkx category hierarchy

Returns graph: a directed graph where category names are the nodes, supercategories define edges, and items in each category dict (e.g. category id) are added as node properties.

Return type `networkx.DiGraph`

Example

```
>>> self = CocoDataset.demo()
>>> graph = self.category_graph()
>>> assert 'astronaut' in graph.nodes()
>>> assert 'keypoints' in graph.nodes['human']
```

object_categories(self)

Construct a consistent CategoryTree representation of object classes

Returns category data structure

Return type *kwcoco.CategoryTree*

Example

```
>>> self = CocoDataset.demo()
>>> classes = self.object_categories()
>>> print('classes = {}'.format(classes))
```

keypoint_categories(self)

Construct a consistent CategoryTree representation of keypoint classes

Returns category data structure

Return type *kwcoco.CategoryTree*

Example

```
>>> self = CocoDataset.demo()
>>> classes = self.keypoint_categories()
>>> print('classes = {}'.format(classes))
```

_keypoint_category_names(self)

Construct keypoint categories names.

Uses new-style if possible, otherwise this falls back on old-style.

Returns names: list of keypoint category names

Return type List[str]

Example

```
>>> self = CocoDataset.demo()
>>> names = self._keypoint_category_names()
>>> print(names)
```

_lookup_kpnames(self, cid)

Get the keypoint categories for a certain class

_coco_image(self, gid)**coco_image(self, gid)**

Parameters `gid` (*int*) – image id
Returns `kwcoco.coco_image.CocoImage`

`class kwcoco.coco_dataset.MixinCocoExtras`
Bases: `object`

Misc functions for coco

`classmethod coerce(cls, key, **kw)`

Attempt to transform the input into the intended CocoDataset.

Parameters

- `key` – this can either be an instance of a CocoDataset, a string URI pointing to an on-disk dataset, or a special key for creating demodata.
- `**kw` – passed to whatever constructor is chosen (if any)

Example

```
>>> # test coerce for various input methods
>>> import kwcoco
>>> from kwcoco.coco_sql_dataset import assert_dsets_allclose
>>> dct_dset = kwcoco.CocoDataset.coerce('special:shapes8')
>>> copy1 = kwcoco.CocoDataset.coerce(dct_dset)
>>> copy2 = kwcoco.CocoDataset.coerce(dct_dset.fpath)
>>> assert assert_dsets_allclose(dct_dset, copy1)
>>> assert assert_dsets_allclose(dct_dset, copy2)
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> sql_dset = dct_dset.view_sql()
>>> copy3 = kwcoco.CocoDataset.coerce(sql_dset)
>>> copy4 = kwcoco.CocoDataset.coerce(sql_dset.fpath)
>>> assert assert_dsets_allclose(dct_dset, sql_dset)
>>> assert assert_dsets_allclose(dct_dset, copy3)
>>> assert assert_dsets_allclose(dct_dset, copy4)
```

`classmethod demo(cls, key='photos', **kwargs)`

Create a toy coco dataset for testing and demo purposes

Parameters

- `key` (*str, default=photos*) – Either ‘photos’, ‘shapes’, or ‘vidshapes’. There are also special suffixes that can control behavior.

Basic options that define which flavor of demodata to generate are: *photos*, *shapes*, and *vidshapes*. A numeric suffix e.g. *vidshapes8* can be specified to indicate the size of the generated demo dataset. There are other special suffixes that are available. See the code in this function for explicit details on what is allowed.

TODO: better documentation for these demo datasets.

As a quick summary: the *vidshapes* key is the most robust and mature demodata set, and here are several useful variants of the *vidshapes* key.

- (1) *vidshapes8* - the 8 suffix is the number of videos in this case.
- (2) *vidshapes8-multispectral* - generate 8 multispectral videos.
- (3) *vidshapes8-msi* - msi is an alias for multispectral.

(4) vidshapes8-frames5 - generate 8 videos with 5 frames each. (4) vidshapes2-speed0.1-frames7 - generate 2 videos with 7

frames where the objects move with with a speed of 0.1.

- ****kwargs** – if key is shapes, these arguments are passed to toydata generation. The Kwargs section of this docstring documents a subset of the available options. For full details, see `demodata_toy_dset()` and `random_video_dset()`.

Kwargs: `image_size (Tuple[int, int]):` width / height size of the images

dpath (str): path to the output image directory, defaults to using kwcoco cache dir.

`aux (bool):` if True generates dummy auxiliary channels

rng (int | RandomState, default=0): random number generator or seed

`verbose (int, default=3):` verbosity mode

Example

```
>>> # Basic demodata keys
>>> print(CocoDataset.demo('photos', verbose=1))
>>> print(CocoDataset.demo('shapes', verbose=1))
>>> print(CocoDataset.demo('vidshapes', verbose=1))
>>> # Variants of demodata keys
>>> print(CocoDataset.demo('shapes8', verbose=0))
>>> print(CocoDataset.demo('shapes8-msi', verbose=0))
>>> print(CocoDataset.demo('shapes8-frames1-speed0.2-msi', verbose=0))
```

Example

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes5', num_frames=5,
>>>                               verbose=0, rng=None)
>>> dset = kwcoco.CocoDataset.demo('vidshapes5', num_frames=5,
>>>                               num_tracks=4, verbose=0, rng=44)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> pnums = kwplot.PlotNums(nSubplots=len(dset.index.imgs))
>>> fnum = 1
>>> for gx, gid in enumerate(dset.index.imgs.keys()):
>>>     canvas = dset.draw_image(gid=gid)
>>>     kwplot.imshow(canvas, pnum=pnums[gx], fnum=fnum)
>>>     #dset.show_image(gid=gid, pnum=pnums[gx])
>>> kwplot.show_if_requested()
```

Example

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes5-aux', num_frames=1,
>>>                                         verbose=0, rng=None)
```

Example

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes1-multispectral', num_frames=5,
>>>                                         verbose=0, rng=None)
>>> # This is the first use-case of image names
>>> assert len(dset.index.file_name_to_img) == 0, (
>>>     'the multispectral demo case has no "base" image')
>>> assert len(dset.index.name_to_img) == len(dset.index.imgs) == 5
>>> dset.remove_images([1])
>>> assert len(dset.index.name_to_img) == len(dset.index.imgs) == 4
>>> dset.remove_videos([1])
>>> assert len(dset.index.name_to_img) == len(dset.index.imgs) == 0
```

_tree(self)

developer helper

classmethod random(cls, rng=None)

Creates a random CocoDataset according to distribution parameters

Todo:

- [] parametrize

_build_hashid(self, hash_pixels=False, verbose=0)

Construct a hash that uniquely identifies the state of this dataset.

Parameters

- **hash_pixels** (*bool*, *default=False*) – If False the image data is not included in the hash, which can speed up computation, but is not 100% robust.
- **verbose** (*int*) – verbosity level

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> self._build_hashid(hash_pixels=True, verbose=3)
...
>>> # Shorten hashes for readability
>>> walker = ub.IndexableWalker(self.hashid_parts)
>>> for path, val in walker:
>>>     if isinstance(val, str):
>>>         walker[path] = val[0:8]
>>> # Note: this may change in different versions of kwcoco
```

(continues on next page)

(continued from previous page)

```
>>> print('self.hashid_parts = ' + ub.repr2(self.hashid_parts))
>>> print('self.hashid = {!r}'.format(self.hashid[0:8]))
self.hashid_parts = {
    'annotations': {
        'json': 'e573f49d',
        'num': 11,
    },
    'images': {
        'pixels': '67d741fe',
        'json': '2221c714',
        'num': 3,
    },
    'categories': {
        'json': '82d22e00',
        'num': 8,
    },
}
self.hashid = '77d445f0'
```

Doctest:

```
>>> self = CocoDataset.demo()
>>> self._build_hashid(hash_pixels=True, verbose=3)
>>> self.hashid_parts
>>> # Test that when we modify the dataset only the relevant
>>> # hashid parts are recomputed.
>>> orig = self.hashid_parts['categories']['json']
>>> self.add_category('foobar')
>>> assert 'categories' not in self.hashid_parts
>>> self.hashid_parts
>>> self.hashid_parts['images']['json'] = 'should not change'
>>> self._build_hashid(hash_pixels=True, verbose=3)
>>> assert self.hashid_parts['categories']['json']
>>> assert self.hashid_parts['categories']['json'] != orig
>>> assert self.hashid_parts['images']['json'] == 'should not change'
```

_invalidate_hashid(self, parts=None)

Called whenever the coco dataset is modified. It is possible to specify which parts were modified so unmodified parts can be reused next time the hash is constructed.

Todo:

- [] Rename to _notify_modification — or something like that
-

_cached_hashid(self)

Under Construction.

_dataset_id(self)**_ensure_imgsize(self, workers=0, verbose=1, fail=False)**

Populate the imgsize field if it does not exist.

Parameters

- **workers** (*int, default=0*) – number of workers for parallel processing.
- **verbose** (*int, default=1*) – verbosity level
- **fail** (*bool, default=False*) – if True, raises an exception if anything size fails to load.

Returns

a list of “bad” image dictionaries where the size could not be determined. Typically these are corrupted images and should be removed.

Return type List[dict]

Example

```
>>> # Normal case
>>> self = CocoDataset.demo()
>>> bad_imgs = self._ensure_imgsize()
>>> assert len(bad_imgs) == 0
>>> assert self.imgs[1]['width'] == 512
>>> assert self.imgs[2]['width'] == 300
>>> assert self.imgs[3]['width'] == 256
```

```
>>> # Fail cases
>>> self = CocoDataset()
>>> self.add_image('does-not-exist.jpg')
>>> bad_imgs = self._ensure_imgsize()
>>> assert len(bad_imgs) == 1
>>> import pytest
>>> with pytest.raises(Exception):
>>>     self._ensure_imgsize(fail=True)
```

_ensure_image_data(self, gids=None, verbose=1)

Download data from “url” fields if specified.

Parameters **gids** (*List*) – subset of images to download

missing_images(self, check_aux=False, verbose=0)

Check for images that don’t exist

Parameters

- **check_aux** (*bool, default=False*) – if specified also checks auxiliary images
- **verbose** (*int*) – verbosity level

Returns bad indexes and paths and ids

Return type List[Tuple[int, str, int]]

corrupted_images(self, check_aux=False, verbose=0)

Check for images that don’t exist or can’t be opened

Parameters

- **check_aux** (*bool, default=False*) – if specified also checks auxiliary images
- **verbose** (*int*) – verbosity level

Returns bad indexes and paths and ids

Return type List[Tuple[int, str, int]]

rename_categories(*self, mapper, rebuild=True, merge_policy='ignore'*)

Rename categories with a potentially coarser categorization.

Parameters

- **mapper** (*dict or Function*) – maps old names to new names. If multiple names are mapped to the same category, those categories will be merged.
- **merge_policy** (*str*) – How to handle multiple categories that map to the same name. Can be update or ignore.

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> self.rename_categories({'astronomer': 'person',
>>>                         'astronaut': 'person',
>>>                         'mouth': 'person',
>>>                         'helmet': 'hat'})
>>> assert 'hat' in self.name_to_cat
>>> assert 'helmet' not in self.name_to_cat
>>> # Test merge case
>>> self = kwcoco.CocoDataset.demo()
>>> mapper = {
>>>     'helmet': 'rocket',
>>>     'astronomer': 'rocket',
>>>     'human': 'rocket',
>>>     'mouth': 'helmet',
>>>     'star': 'gas'
>>> }
>>> self.rename_categories(mapper)
```

_ensure_json_serializable(*self*)

_aspycoco(*self*)

Converts to the official pycocotools.coco.COCO object

Todo:

- [] Maybe expose as a public API?

reroot(*self, new_root=None, old_prefix=None, new_prefix=None, absolute=False, check=True, safe=True*)

Modify the prefix of the image/data paths onto a new image/data root.

Parameters

- **new_root** (*str, default=None*) – New image root. If unspecified the current *self.bundle_dpath* is used. If *old_prefix* and *new_prefix* are unspecified, they will attempt to be determined based on the current root (which assumes the file paths exist at that root) and this new root.
- **old_prefix** (*str, default=None*) – If specified, removes this prefix from file names. This also prevents any inferences that might be made via “*new_root*”.
- **new_prefix** (*str, default=None*) – If specified, adds this prefix to the file names. This also prevents any inferences that might be made via “*new_root*”.

- **absolute** (*bool, default=False*) – if True, file names are stored as absolute paths, otherwise they are relative to the new image root.
- **check** (*bool, default=True*) – if True, checks that the images all exist.
- **safe** (*bool, default=True*) – if True, does not overwrite values until all checks pass

CommandLine

```
xdotest -m kwcoco.coco_dataset MixinCocoExtras.reroot
```

Todo:

- [] Incorporate maximum ordered subtree embedding?
-

Example

```
>>> import kwcoco
>>> def report(dset, name):
>>>     gid = 1
>>>     abs_fpath = dset.get_image_fpath(gid)
>>>     rel_fpath = dset.index.imgs[gid]['file_name']
>>>     color = 'green' if exists(abs_fpath) else 'red'
>>>     print('strategy_name = {!r}'.format(name))
>>>     print(ub.color_text('abs_fpath = {!r}'.format(abs_fpath), color))
>>>     print('rel_fpath = {!r}'.format(rel_fpath))
>>> dset = self = kwcoco.CocoDataset.demo()
>>> # Change base relative directory
>>> bundle_dpath = ub.expandpath('~')
>>> print('ORIG self.imgs = {!r}'.format(self.imgs))
>>> print('ORIG dset.bundle_dpath = {!r}'.format(dset.bundle_dpath))
>>> print('NEW bundle_dpath      = {!r}'.format(bundle_dpath))
>>> self.reroot(bundle_dpath)
>>> report(self, 'self')
>>> print('NEW self.imgs = {!r}'.format(self.imgs))
>>> assert self.imgs[1]['file_name'].startswith('.cache')
```

```
>>> # Use absolute paths
>>> self.reroot(absolute=True)
>>> assert self.imgs[1]['file_name'].startswith(bundle_dpath)
```

```
>>> # Switch back to relative paths
>>> self.reroot()
>>> assert self.imgs[1]['file_name'].startswith('.cache')
```

Example

```
>>> # demo with auxiliary data
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo('shapes8', aux=True)
>>> bundle_dpath = ub.expandpath('~')
>>> print(self.imgs[1]['file_name'])
>>> print(self.imgs[1]['auxiliary'][0]['file_name'])
>>> self.reroot(new_root=bundle_dpath)
>>> print(self.imgs[1]['file_name'])
>>> print(self.imgs[1]['auxiliary'][0]['file_name'])
>>> assert self.imgs[1]['file_name'].startswith('.cache')
>>> assert self.imgs[1]['auxiliary'][0]['file_name'].startswith('.cache')
```

property data_root(self)

In the future we will deprecate data_root for bundle_dpath

property img_root(self)

In the future we will deprecate img_root for bundle_dpath

property data_fpath(self)

data_fpath is an alias of fpath

class kwcoco.coco_dataset.MixinCocoObjects

Bases: `object`

Expose methods to construct object lists / groups.

This is an alternative vectorized ORM-like interface to the coco dataset

annots(self, aids=None, gid=None, trackid=None)

Return vectorized annotation objects

Parameters

- **aids** (`List[int]`) – annotation ids to reference, if unspecified all annotations are returned.
- **gid** (`int`) – return all annotations that belong to this image id. mutually exclusive with other arguments.
- **trackid** (`int`) – return all annotations that belong to this track. mutually exclusive with other arguments.

Returns vectorized annotation object

Return type `Annots`

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> annots = self.annots()
>>> print(annots)
<Annots(num=11)>
>>> sub_annotss = annots.take([1, 2, 3])
>>> print(sub_annotss)
<Annots(num=3)>
>>> print(ub.repr2(sub_annotss.get('bbox', None)))
```

(continues on next page)

(continued from previous page)

```
[  
    [350, 5, 130, 290],  
    None,  
    None,  
]
```

images(*self*, *gids=None*, *vidid=None*, *names=None*)

Return vectorized image objects

Parameters

- **gids** (*List[int]*) – image ids to reference, if unspecified all images are returned.
- **vidid** (*int*) – returns all images that belong to this video id. mutually exclusive with *gids* arg.
- **names** (*List[str]*) – lookup images by their names.

Returns vectorized image object**Return type** *Images***Example**

```
>>> import kwcoco  
>>> self = kwcoco.CocoDataset.demo()  
>>> images = self.images()  
>>> print(images)  
<Images(num=3)>
```

```
>>> self = kwcoco.CocoDataset.demo('vidshapes2')  
>>> vidid = 1  
>>> images = self.images(vidid=vidid)  
>>> assert all(v == vidid for v in images.lookup('video_id'))  
>>> print(images)  
<Images(num=2)>
```

categories(*self*, *cids=None*)

Return vectorized category objects

Parameters **cids** (*List[int]*) – category ids to reference, if unspecified all categories are returned.**Returns** vectorized category object**Return type** *Categories*

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> categories = self.categories()
>>> print(categories)
<Categories(num=8)>
```

videos(self, vidids=None, names=None)
Return vectorized video objects

Parameters

- **vidids** (*List[int]*) – video ids to reference, if unspecified all videos are returned.
- **names** (*List[str]*) – lookup videos by their name.

Returns vectorized video object

Return type *Videos*

Todo:

- [] This conflicts with what should be the property that should redirect to `index.videos`, we should resolve this somehow. E.g. all other main members of the index (anns, imgs, cats) have a toplevel dataset property, we don't have one for videos because the name we would pick conflicts with this.
-

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo('vidshapes2')
>>> videos = self.videos()
>>> print(videos)
>>> videos.lookup('name')
>>> videos.lookup('id')
>>> print('videos objs = {}'.format(ub.repr2(videos.objs[0:2], nl=1)))
```

class kwcoco.coco_dataset.MixinCocoStats

Bases: *object*

Methods for getting stats about the dataset

property n_annotss(self)

The number of annotations in the dataset

property n_images(self)

The number of images in the dataset

property n_cats(self)

The number of categories in the dataset

property n_videos(self)

The number of videos in the dataset

keypoint_annotation_frequency(self)

DEPRECATED

Example

```
>>> from kwCOCO.coco_dataset import *
>>> self = CocoDataset.demo('shapes', rng=0)
>>> hist = self.keypoint_annotation_frequency()
>>> hist = ub.odict(sorted(hist.items()))
>>> # FIXME: for whatever reason demodata generation is not deterministic when
>>> ~seeded
>>> print(ub.repr2(hist)) # xdoc: +IGNORE_WANT
{
    'bot_tip': 6,
    'left_eye': 14,
    'mid_tip': 6,
    'right_eye': 14,
    'top_tip': 6,
}
```

category_annotation_frequency(self)

Reports the number of annotations of each category

Example

```
>>> from kwCOCO.coco_dataset import *
>>> self = CocoDataset.demo()
>>> hist = self.category_annotation_frequency()
>>> print(ub.repr2(hist))
{
    'astroturf': 0,
    'human': 0,
    'astronaut': 1,
    'astronomer': 1,
    'helmet': 1,
    'rocket': 1,
    'mouth': 2,
    'star': 5,
}
```

category_annotation_type_frequency(self)

DEPRECATED

Reports the number of annotations of each type for each category

Example

```
>>> self = CocoDataset.demo()
>>> hist = self.category_annotation_frequency()
>>> print(ub.repr2(hist))
```

conform(self, **config)

Make the COCO file conform a stricter spec, infers attributes where possible.

Corresponds to the kwCOCO conform CLI tool.

KWArgs:

****config** : pycocotools_info (default=True): returns info required by pycocotools ensure_imgszie (default=True): ensure image size is populated legacy (default=False): if true tries to convert data structures to items compatible with the original pycocotools spec workers (int): number of parallel jobs for IO tasks

Example

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('shapes8')
>>> dset.index.imgs[1].pop('width')
>>> dset.conform(legacy=True)
>>> assert 'width' in dset.index.imgs[1]
>>> assert 'area' in dset.index.anns[1]
```

validate(self, **config)

Performs checks on this coco dataset.

Corresponds to the `kwcoco validate` CLI tool.

KWArgs:

****config** : schema (default=True): validates the json-schema unique (default=True): validates unique secondary keys missing (default=True): validates registered files exist corrupted (default=False): validates data in registered files verbose (default=1): verbosity flag fastfail (default=False): if True raise errors immediately

Returns

result containing keys: status (bool): False if any errors occurred errors (List[str]): list of all error messages missing (List): List of any missing images corrupted (List): List of any corrupted images

Return type dict

SeeAlso: `_check_integrity()` - performs internal checks

Example

```
>>> from kwcoco.coco_dataset import *
>>> self = CocoDataset.demo()
>>> import pytest
>>> with pytest.warns(UserWarning):
>>>     result = self.validate()
>>> assert not result['errors']
>>> assert result['warnings']
```

stats(self, **kwargs)

Compute summary statistics to describe the dataset at a high level

This function corresponds to `kwcoco.cli.coco_stats`.

KWargs: basic(bool, default=True): return basic stats' extended(bool, default=True): return extended stats' catfreq(bool, default=True): return category frequency stats' boxes(bool, default=False): return bounding box stats'

annot_attrs(bool, default=True): return annotation attribute information' image_attrs(bool, default=True): return image attribute information'

Returns info

Return type dict

basic_stats(self)

Reports number of images, annotations, and categories.

SeeAlso: [kwcoco.coco_dataset.MixinCocoStats.basic_stats\(\)](#) [kwcoco.coco_dataset.MixinCocoStats.extended_stats\(\)](#)

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> print(ub.repr2(self.basic_stats()))
{
    'n_annts': 11,
    'n_imgs': 3,
    'n_videos': 0,
    'n_cats': 8,
}
```

```
>>> from kwcoco.demo.toydata_video import random_video_dset
>>> dset = random_video_dset(render=True, num_frames=2, num_tracks=10, rng=0)
>>> print(ub.repr2(dset.basic_stats()))
{
    'n_annts': 20,
    'n_imgs': 2,
    'n_videos': 1,
    'n_cats': 3,
}
```

extended_stats(self)

Reports number of images, annotations, and categories.

SeeAlso: [kwcoco.coco_dataset.MixinCocoStats.basic_stats\(\)](#) [kwcoco.coco_dataset.MixinCocoStats.extended_stats\(\)](#)

Example

```
>>> self = CocoDataset.demo()  
>>> print(ub.repr2(self.extended_stats()))
```

boxsize_stats(*self*, *anchors=None*, *perclass=True*, *gids=None*, *aids=None*, *verbose=0*, *clusterkw={}*,
 statskw={})

Compute statistics about bounding box sizes.

Also computes anchor boxes using kmeans if *anchors* is specified.

Parameters

- **anchors** (*int*) – if specified also computes box anchors via KMeans clustering
- **perclass** (*bool*) – if True also computes stats for each category
- **gids** (*List[int]*, *default=None*) – if specified only compute stats for these image ids.
- **aids** (*List[int]*, *default=None*) – if specified only compute stats for these annotation ids.
- **verbose** (*int*) – verbosity level
- **clusterkw** (*dict*) – kwargs for `sklearn.cluster.KMeans` used if computing anchors.
- **statskw** (*dict*) – kwargs for `kwarray.stats_dict()`

Returns Stats are returned in width-height format.

Return type Dict[str, Dict[str, Dict | ndarray]]

Example

```
>>> import kwcoco  
>>> self = kwcoco.CocoDataset.demo('shapes32')  
>>> infos = self.boxsize_stats(anchors=4, perclass=False)  
>>> print(ub.repr2(infos, nl=-1, precision=2))
```

```
>>> infos = self.boxsize_stats(gids=[1], statskw=dict(median=True))  
>>> print(ub.repr2(infos, nl=-1, precision=2))
```

findRepresentativeImages(*self*, *gids=None*)

Find images that have a wide array of categories.

Attempt to find the fewest images that cover all categories using images that contain both a large and small number of annotations.

Parameters **gids** (*None* | *List*) – Subset of image ids to consider when finding representative images. Uses all images if unspecified.

Returns list of image ids determined to be representative

Return type List

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> gids = self.find_representative_images()
>>> print('gids = {!r}'.format(gids))
>>> gids = self.find_representative_images([3])
>>> print('gids = {!r}'.format(gids))
```

```
>>> self = kwcoco.CocoDataset.demo('shapes8')
>>> gids = self.find_representative_images()
>>> print('gids = {!r}'.format(gids))
>>> valid = {7, 1}
>>> gids = self.find_representative_images(valid)
>>> assert valid.issuperset(gids)
>>> print('gids = {!r}'.format(gids))
```

class kwcoco.coco_dataset.MixinCocoDraw

Bases: `object`

Matplotlib / display functionality

imread(self, gid)

DEPRECATE: use `load_image` or `delayed_image`

Loads a particular image

draw_image(self, gid, channels=None)

Use `kwimage` to draw all annotations on an image and return the pixels as a numpy array.

Parameters

- **gid** (`int`) – image id to draw
- **channels** (`ChannelSpec`) – the channel to draw on

Returns canvas

Return type ndarray

SeeAlso `kwcoco.coco_dataset.MixinCocoDraw.draw_image()`

`kwcoco.coco_dataset.`

`MixinCocoDraw.show_image()`

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo('shapes8')
>>> self.draw_image(1)
>>> # Now you can dump the annotated image to disk / whatever
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(canvas)
```

show_image(self, gid=None, aids=None, aid=None, channels=None, **kwargs)

Use matplotlib to show an image with annotations overlaid

Parameters

- **gid** (*int*) – image to show
- **aids** (*list*) – aids to highlight within the image
- **aid** (*int*) – a specific aid to focus on. If gid is not give, look up gid based on this aid.
- ****kwargs** – show_annots, show_aid, show_catname, show_kpname, show_segmentation, title, show_gid, show_filename, show_boxes,

SeeAlso `kwcoco.coco_dataset.MixinCocoDraw.draw_image()` `kwcoco.coco_dataset.MixinCocoDraw.show_image()`

Example

```
>>> # xdoctest: +REQUIRES(--show)
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-msi')
>>> dset.show_image(gid=1, channels='B8')
```

class `kwcoco.coco_datasetMixinCocoAddRemove`
Bases: `object`

Mixin functions to dynamically add / remove annotations images and categories while maintaining lookup indexes.

add_video(*self, name, id=None, **kw*)

Register a new video with the dataset

Parameters

- **name** (*str*) – Unique name for this video.
- **id** (*None or int*) – ADVANCED. Force using this image id.
- ****kw** – stores arbitrary key/value pairs in this new video

Returns the video id assigned to the new video

Return type `int`

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset()
>>> print('self.index.videos = {}'.format(ub.repr2(self.index.videos, nl=1)))
>>> print('self.index.imgs = {}'.format(ub.repr2(self.index.imgs, nl=1)))
>>> print('self.index.vidid_to_gids = {!r}'.format(self.index.vidid_to_gids))
```

```
>>> vidid1 = self.add_video('foo', id=3)
>>> vidid2 = self.add_video('bar')
>>> vidid3 = self.add_video('baz')
>>> print('self.index.videos = {}'.format(ub.repr2(self.index.videos, nl=1)))
>>> print('self.index.imgs = {}'.format(ub.repr2(self.index.imgs, nl=1)))
>>> print('self.index.vidid_to_gids = {!r}'.format(self.index.vidid_to_gids))
```

```
>>> gid1 = self.add_image('foo1.jpg', video_id=vidid1, frame_index=0)
>>> gid2 = self.add_image('foo2.jpg', video_id=vidid1, frame_index=1)
>>> gid3 = self.add_image('foo3.jpg', video_id=vidid1, frame_index=2)
>>> gid4 = self.add_image('bar1.jpg', video_id=vidid2, frame_index=0)
>>> print('self.index.videos = {}'.format(ub.repr2(self.index.videos, nl=1)))
>>> print('self.index.imgs = {}'.format(ub.repr2(self.index.imgs, nl=1)))
>>> print('self.index.vidid_to_gids = {!r}'.format(self.index.vidid_to_gids))
```

```
>>> self.remove_images([gid2])
>>> print('self.index.vidid_to_gids = {!r}'.format(self.index.vidid_to_gids))
```

add_image(*self*, *file_name=None*, *id=None*, ***kw*)

Register a new image with the dataset

Parameters

- **file_name** (*str*) – relative or absolute path to image
- **id** (*None* or *int*) – ADVANCED. Force using this image id.
- **name** (*str*) – a unique key to identify this image
- **width** (*int*) – base width of the image
- **height** (*int*) – base height of the image
- **channels** (*ChannelSpec*) – specification of base channels
- **auxiliary** (*List[Dict]*) – specification of auxiliary information
- **video_id** (*int*) – parent video, if applicable
- **frame_index** (*int*) – frame index in parent video
- **timestamp** (*number* | *str*) – timestamp of frame index
- ****kw** – stores arbitrary key/value pairs in this new image

Returns the image id assigned to the new image

Return type *int*

SeeAlso: [add_image\(\)](#) [add_images\(\)](#) [ensure_image\(\)](#)

Example

```
>>> self = CocoDataset.demo()
>>> import kwimage
>>> gname = kwimage.grab_test_image_fpath('paraview')
>>> gid = self.add_image(gname)
>>> assert self.imgs[gid]['file_name'] == gname
```

add_annotation(*self*, *image_id*, *category_id=None*, *bbox=ub.NoParam*, *segmentation=ub.NoParam*, *keypoints=ub.NoParam*, *id=None*, ***kw*)

Register a new annotation with the dataset

Parameters

- **image_id** (*int*) – image_id the annotation is added to.
- **category_id** (*int* | *None*) – category_id for the new annotation

- **bbox** (*list | kwimage.Boxes*) – bounding box in xywh format
- **segmentation** (*MaskLike | MultiPolygonLike*) – keypoints in some accepted format, see `kwimage.Mask.to_coco()` and `kwimage.MultiPolygon.to_coco()`.
- **keypoints** (*KeypointsLike*) – keypoints in some accepted format, see `kwimage.Keypoints.to_coco()`.
- **id** (*None | int*) – Force using this annotation id. Typically you should NOT specify this. A new unused id will be chosen and returned.
- ****kw** – stores arbitrary key/value pairs in this new image. Common respected key/values include but are not limited to the following:
 - track_id** (*int | str*): some value used to associate annotations that belong to the same “track”.
 - score** : float
 - prob** : List[float]
 - weight (float)**: a weight, usually used to indicate if a ground truth annotation is difficult / important. This generalizes standard “is_hard” or “ignore” attributes in other formats.
 - caption (str)**: a text caption for this annotation

Returns the annotation id assigned to the new annotation

Return type `int`

SeeAlso: `kwcoco.coco_dataset.MixinCocoAddRemove.add_annotation()` `kwcoco.coco_dataset.MixinCocoAddRemove.add_annotations()`

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> image_id = 1
>>> cid = 1
>>> bbox = [10, 10, 20, 20]
>>> aid = self.add_annotation(image_id, cid, bbox)
>>> assert self.anns[aid]['bbox'] == bbox
```

Example

```
>>> import kwimage
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> new_det = kwimage.Detections.random(1, segmentations=True, keypoints=True)
>>> # kwimage datastructures have methods to convert to coco recognized formats
>>> new_ann_data = list(new_det.to_coco(style='new'))[0]
>>> image_id = 1
>>> aid = self.add_annotation(image_id, **new_ann_data)
>>> # Lookup the annotation we just added
>>> ann = self.index.anns[aid]
>>> print('ann = {}'.format(ub.repr2(ann, nl=-2)))
```

Example

```
>>> # Attempt to add annot without a category or bbox
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> image_id = 1
>>> aid = self.add_annotation(image_id)
>>> assert None in self.index.cid_to_aids
```

Example

```
>>> # Attempt to add annot using various styles of kwimage structures
>>> import kwcoco
>>> import kwimage
>>> self = kwcoco.CocoDataset.demo()
>>> image_id = 1
>>> #--
>>> kw = {}
>>> kw['segmentation'] = kwimage.Polygon.random()
>>> kw['keypoints'] = kwimage.Points.random()
>>> aid = self.add_annotation(image_id, **kw)
>>> ann = self.index.anns[aid]
>>> print('ann = {}'.format(ub.repr2(ann, nl=2)))
>>> #--
>>> kw = {}
>>> kw['segmentation'] = kwimage.Mask.random()
>>> aid = self.add_annotation(image_id, **kw)
>>> ann = self.index.anns[aid]
>>> assert ann.get('segmentation', None) is not None
>>> print('ann = {}'.format(ub.repr2(ann, nl=2)))
>>> #--
>>> kw = {}
>>> kw['segmentation'] = kwimage.Mask.random().to_array_rle()
>>> aid = self.add_annotation(image_id, **kw)
>>> ann = self.index.anns[aid]
>>> assert ann.get('segmentation', None) is not None
>>> print('ann = {}'.format(ub.repr2(ann, nl=2)))
>>> #--
>>> kw = {}
>>> kw['segmentation'] = kwimage.Polygon.random().to_coco()
>>> kw['keypoints'] = kwimage.Points.random().to_coco()
>>> aid = self.add_annotation(image_id, **kw)
>>> ann = self.index.anns[aid]
>>> assert ann.get('segmentation', None) is not None
>>> assert ann.get('keypoints', None) is not None
>>> print('ann = {}'.format(ub.repr2(ann, nl=2)))
```

add_category(*self*, *name*, *supercategory=None*, *id=None*, ***kw*)

Register a new category with the dataset

Parameters

- **name** (*str*) – name of the new category

- **supercategory** (*str, optional*) – parent of this category
- **id** (*int, optional*) – use this category id, if it was not taken
- ****kw** – stores arbitrary key/value pairs in this new image

Returns the category id assigned to the new category

Return type `int`

SeeAlso: `kwcoco.coco_dataset.MixinCocoAddRemove.add_category()` `kwcoco.coco_dataset.MixinCocoAddRemove.ensure_category()`

`kwcoco.`

Example

```
>>> self = CocoDataset.demo()
>>> prev_n_cats = self.n_cats
>>> cid = self.add_category('dog', supercategory='object')
>>> assert self.cats[cid]['name'] == 'dog'
>>> assert self.n_cats == prev_n_cats + 1
>>> import pytest
>>> with pytest.raises(ValueError):
>>>     self.add_category('dog', supercategory='object')
```

ensure_image(*self, file_name, id=None, **kw*)

Register an image if it is new or returns an existing id.

Like `kwcoco.coco_dataset.MixinCocoAddRemove.add_image()`, but returns the existing image id if it already exists instead of failing. In this case all metadata is ignored.

Parameters

- **file_name** (*str*) – relative or absolute path to image
- **id** (*None or int*) – ADVANCED. Force using this image id.
- ****kw** – stores arbitrary key/value pairs in this new image

Returns the existing or new image id

Return type `int`

SeeAlso: `kwcoco.coco_dataset.MixinCocoAddRemove.add_image()` `kwcoco.coco_dataset.MixinCocoAddRemove.add_images()` `kwcoco.coco_dataset.MixinCocoAddRemove.ensure_image()`

ensure_category(*self, name, supercategory=None, id=None, **kw*)

Register a category if it is new or returns an existing id.

Like `kwcoco.coco_dataset.MixinCocoAddRemove.add_category()`, but returns the existing category id if it already exists instead of failing. In this case all metadata is ignored.

Returns the existing or new category id

Return type `int`

SeeAlso: `kwcoco.coco_dataset.MixinCocoAddRemove.add_category()` `kwcoco.coco_dataset.MixinCocoAddRemove.ensure_category()`

`kwcoco.`

add_annotations(self, anns)

Faster less-safe multi-item alternative to add_annotation.

We assume the annotations are well formatted in kwcoco compliant dictionaries, including the “id” field. No validation checks are made when calling this function.

Parameters `anns` (`List[Dict]`) – list of annotation dictionaries

SeeAlso: `add_annotation()` `add_annotations()`

Example

```
>>> self = CocoDataset.demo()
>>> anns = [self.anns[aid] for aid in [2, 3, 5, 7]]
>>> self.remove_annotations(anns)
>>> assert self.n_annot == 7 and self._check_index()
>>> self.add_annotations(anns)
>>> assert self.n_annot == 11 and self._check_index()
```

add_images(self, imgs)

Faster less-safe multi-item alternative

We assume the images are well formatted in kwcoco compliant dictionaries, including the “id” field. No validation checks are made when calling this function.

Note: THIS FUNCTION WAS DESIGNED FOR SPEED, AS SUCH IT DOES NOT CHECK IF THE IMAGE-IDS OR FILE NAMES ARE DUPLICATED AND WILL BLINDLY ADD DATA EVEN IF IT IS BAD. THE SINGLE IMAGE VERSION IS SLOWER BUT SAFER.

Parameters `imgs` (`List[Dict]`) – list of image dictionaries

SeeAlso: `kwcoco.coco_dataset.MixinCocoAddRemove.add_image()` `kwcoco.coco_dataset.MixinCocoAddRemove.add_images()` `kwcoco.coco_dataset.MixinCocoAddRemove.ensure_image()`

Example

```
>>> imgs = CocoDataset.demo().dataset['images']
>>> self = CocoDataset()
>>> self.add_images(imgs)
>>> assert self.n_images == 3 and self._check_index()
```

clear_images(self)

Removes all images and annotations (but not categories)

Example

```
>>> self = CocoDataset.demo()
>>> self.clear_images()
>>> print(ub.repr2(self.basic_stats(), nobr=1, nl=0, si=1))
n_anns: 0, n_imgs: 0, n_videos: 0, n_cats: 8
```

`clear_annotations(self)`

Removes all annotations (but not images and categories)

Example

```
>>> self = CocoDataset.demo()
>>> self.clear_annotations()
>>> print(ub.repr2(self.basic_stats(), nobr=1, nl=0, si=1))
n_anns: 0, n_imgs: 3, n_videos: 0, n_cats: 8
```

`remove_annotation(self, aid_or_ann)`

Remove a single annotation from the dataset

If you have multiple annotations to remove its more efficient to remove them in batch with `kwCOCO.coco_dataset.MixinCocoAddRemove.remove_annotations()`

Example

```
>>> import kwCOCO
>>> self = kwCOCO.CocoDataset.demo()
>>> aids_or_anns = [self.anns[2], 3, 4, self.anns[1]]
>>> self.remove_annotations(aids_or_anns)
>>> assert len(self.dataset['annotations']) == 7
>>> self._check_index()
```

`remove_annotations(self, aids_or_anns, verbose=0, safe=True)`

Remove multiple annotations from the dataset.

Parameters

- `aids_or_anns (List)` – list of annotation dicts or ids
- `safe (bool, default=True)` – if True, we perform checks to remove duplicates and non-existing identifiers.

`Returns` `num_removed`: information on the number of items removed

`Return type` Dict

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> prev_n_annots = self.n_annots
>>> aids_or_annots = [self.anns[2], 3, 4, self.anns[1]]
>>> self.remove_annotations(aids_or_annots) # xdoc: +IGNORE_WANT
{'annotations': 4}
>>> assert len(self.dataset['annotations']) == prev_n_annots - 4
>>> self._check_index()
```

remove_categories(*self*, *cat_identifiers*, *keep_annots=False*, *verbose=0*, *safe=True*)

Remove categories and all annotations in those categories.

Currently does not change any hierarchy information

Parameters

- **cat_identifiers** (*List*) – list of category dicts, names, or ids
- **keep_annots** (*bool, default=False*) – if True, keeps annotations, but removes category labels.
- **safe** (*bool, default=True*) – if True, we perform checks to remove duplicates and non-existing identifiers.

Returns num_removed: information on the number of items removed

Return type Dict

Example

```
>>> self = CocoDataset.demo()
>>> cat_identifiers = [self.cats[1], 'rocket', 3]
>>> self.remove_categories(cat_identifiers)
>>> assert len(self.dataset['categories']) == 5
>>> self._check_index()
```

remove_images(*self*, *gids_or_imgs*, *verbose=0*, *safe=True*)

Remove images and any annotations contained by them

Parameters

- **gids_or_imgs** (*List*) – list of image dicts, names, or ids
- **safe** (*bool, default=True*) – if True, we perform checks to remove duplicates and non-existing identifiers.

Returns num_removed: information on the number of items removed

Return type Dict

Example

```
>>> from kwCOCO.coco_dataset import *
>>> self = CocoDataset.demo()
>>> assert len(self.dataset['images']) == 3
>>> gids_or_imgs = [self.imgs[2], 'astro.png']
>>> self.remove_images(gids_or_imgs) # xdoc: +IGNORE_WANT
{'annotations': 11, 'images': 2}
>>> assert len(self.dataset['images']) == 1
>>> self._check_index()
>>> gids_or_imgs = [3]
>>> self.remove_images(gids_or_imgs)
>>> assert len(self.dataset['images']) == 0
>>> self._check_index()
```

remove_videos(*self*, *vidids_or_videos*, *verbose*=0, *safe*=True)

Remove videos and any images / annotations contained by them

Parameters

- **vidids_or_videos** (*List*) – list of video dicts, names, or ids
- **safe** (*bool*, *default=True*) – if True, we perform checks to remove duplicates and non-existing identifiers.

Returns num_removed: information on the number of items removed

Return type Dict

Example

```
>>> from kwCOCO.coco_dataset import *
>>> self = CocoDataset.demo('vidshapes8')
>>> assert len(self.dataset['videos']) == 8
>>> vidids_or_videos = [self.dataset['videos'][0]['id']]
>>> self.remove_videos(vidids_or_videos) # xdoc: +IGNORE_WANT
{'annotations': 4, 'images': 2, 'videos': 1}
>>> assert len(self.dataset['videos']) == 7
>>> self._check_index()
```

remove_annotation_keypoints(*self*, *kp_identifiers*)

Removes all keypoints with a particular category

Parameters **kp_identifiers** (*List*) – list of keypoint category dicts, names, or ids

Returns num_removed: information on the number of items removed

Return type Dict

remove_keypoint_categories(*self*, *kp_identifiers*)

Removes all keypoints of a particular category as well as all annotation keypoints with those ids.

Parameters **kp_identifiers** (*List*) – list of keypoint category dicts, names, or ids

Returns num_removed: information on the number of items removed

Return type Dict

Example

```
>>> self = CocoDataset.demo('shapes', rng=0)
>>> kp_identifiers = ['left_eye', 'mid_tip']
>>> remove_info = self.remove_keypoint_categories(kp_identifiers)
>>> print('remove_info = {!r}'.format(remove_info))
>>> # FIXME: for whatever reason demodata generation is not deterministic when
>>> # seeded
>>> # assert remove_info == {'keypoint_categories': 2, 'annotation_keypoints': 16,
>>> # 'reflection_ids': 1}
>>> assert self._resolve_to_kpcat('right_eye')['reflection_id'] is None
```

set_annotation_category(*self, aid_or_ann, cid_or_cat*)

Sets the category of a single annotation

Parameters

- **aid_or_ann** (*dict | int*) – annotation dict or id
- **cid_or_cat** (*dict | int*) – category dict or id

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> old_freq = self.category_annotation_frequency()
>>> aid_or_ann = aid = 2
>>> cid_or_cat = new_cid = self.ensure_category('kitten')
>>> self.set_annotation_category(aid, new_cid)
>>> new_freq = self.category_annotation_frequency()
>>> print('new_freq = {}'.format(ub.repr2(new_freq, nl=1)))
>>> print('old_freq = {}'.format(ub.repr2(old_freq, nl=1)))
>>> assert sum(new_freq.values()) == sum(old_freq.values())
>>> assert new_freq['kitten'] == 1
```

class kwcoco.coco_dataset.CocoIndex(*index*)

Bases: *object*

Fast lookup index for the COCO dataset with dynamic modification

Variables

- **imgs** (*Dict[int, dict]*) – mapping between image ids and the image dictionaries
- **anns** (*Dict[int, dict]*) – mapping between annotation ids and the annotation dictionaries
- **cats** (*Dict[int, dict]*) – mapping between category ids and the category dictionaries
- **kpcats** (*Dict[int, dict]*) – mapping between keypoint category ids and keypoint category dictionaries
- **gid_to_aids** (*Dict[int, List[int]]*) – mapping between an image-id and annotation-ids that belong to it
- **cid_to_aids** (*Dict[int, List[int]]*) – mapping between an category-id and annotation-ids that belong to it

- **cid_to_gids** (*Dict[int, List[int]]*) – mapping between an category-id and image-ids that contain at least one annotation with this category id.
- **trackid_to_aids** (*Dict[int, List[int]]*) – mapping between a track-id and annotation-ids that belong to it
- **vidid_to_gids** (*Dict[int, List[int]]*) – mapping between an video-id and images-ids that belong to it
- **name_to_video** (*Dict[str, dict]*) – mapping between a video name and the video dictionary.
- **name_to_cat** (*Dict[str, dict]*) – mapping between a category name and the category dictionary.
- **name_to_img** (*Dict[str, dict]*) – mapping between a image name and the image dictionary.
- **file_name_to_img** (*Dict[str, dict]*) – mapping between a image file_name and the image dictionary.

_set

__nonzero__

_set_sorted_by_frame_index(*index, gids=None*)

Helper for ensuring that vidid_to_gids returns image ids ordered by frame index.

__bool__(*index*)

property cid_to_gids(*index*)

Example

```
>>> import kwcoco
>>> self = dset = kwcoco.CocoDataset()
>>> self.index.cid_to_gids
```

_add_video(*index, vidid, video*)

_add_image(*index, gid, img*)

Example

```
>>> # Test adding image to video that doesn't exist
>>> import kwcoco
>>> self = dset = kwcoco.CocoDataset()
>>> dset.add_image(file_name='frame1', video_id=1, frame_index=0)
>>> dset.add_image(file_name='frame2', video_id=1, frame_index=0)
>>> dset._check_pointers()
>>> dset._check_index()
>>> print('dset.index.vidid_to_gids = {!r}'.format(dset.index.vidid_to_gids))
>>> assert len(dset.index.vidid_to_gids) == 1
>>> dset.add_video(name='foo-vid', id=1)
>>> assert len(dset.index.vidid_to_gids) == 1
>>> dset._check_pointers()
>>> dset._check_index()
```

_add_images(index, imgs)

See ./dev/bench/bench_add_image_check.py

Note: THIS FUNCTION WAS DESIGNED FOR SPEED, AS SUCH IT DOES NOT CHECK IF THE IMAGE-IDS or FILE_NAMES ARE DUPLICATED AND WILL BLINDLY ADD DATA EVEN IF IT IS BAD. THE SINGLE IMAGE VERSION IS SLOWER BUT SAFER.

_add_annotation(index, aid, gid, cid, tid, ann)
_add_annotations(index, anns)
_add_category(index, cid, name, cat)
_remove_all_annotations(index)
_remove_all_images(index)
_remove_annotations(index, remove_aids, verbose=0)
_remove_categories(index, remove_cids, verbose=0)
_remove_images(index, remove_gids, verbose=0)
_remove_videos(index, remove_vidids, verbose=0)
clear(index)

build(index, parent)

Build all id-to-obj reverse indexes from scratch.

Parameters *parent* (*CocoDataset*) – the dataset to index

Notation: aid - Annotation ID gid - imaGe ID cid - Category ID vidid - Video ID

Example

```
>>> import kwcoco
>>> parent = kwcoco.CocoDataset.demo('vidshapes1', num_frames=4, rng=1)
>>> index = parent.index
>>> index.build(parent)
```

```
class kwcoco.coco_dataset.MixinCocoIndex
```

Bases: *object*

Give the dataset top level access to index attributes

```
property anns(self)
property imgs(self)
property cats(self)
property gid_to_aids(self)
property cid_to_aids(self)
property name_to_cat(self)
```

```
class kwcoco.coco_dataset.CocoDataset(data=None, tag=None, bundle_dpath=None, img_root=None,
                                       fname=None, autobuild=True)
Bases:      kwcoco.abstract_coco_dataset.AbstractCocoDataset,      MixinCocoAddRemove,
            MixinCocoStats, MixinCocoObjects, MixinCocoDraw, MixinCocoAccessors, MixinCocoExtras,
            MixinCocoIndex, MixinCocoDepriate, ubelt.NiceRepr
```

The main coco dataset class with a json dataset backend.

Variables

- **dataset** (*Dict*) – raw json data structure. This is the base dictionary that contains {‘annotations’: List, ‘images’: List, ‘categories’: List}
- **index** (*CocoIndex*) – an efficient lookup index into the coco data structure. The index defines its own attributes like `anns`, `cats`, `imgs`, `gid_to_aids`, `file_name_to_img`, etc. See `CocoIndex` for more details on which attributes are available.
- **fpath** (*PathLike* / *None*) – if known, this stores the filepath the dataset was loaded from
- **tag** (*str*) – A tag indicating the name of the dataset.
- **bundle_dpath** (*PathLike* / *None*) – If known, this is the root path that all image file names are relative to. This can also be manually overwritten by the user.
- **hashid** (*str* / *None*) – If computed, this will be a hash uniquely identifying the dataset. To ensure this is computed see `kwcoco.coco_dataset.MixinCocoExtras._build_hashid()`.

References

<http://cocodataset.org/#format> <http://cocodataset.org/#download>

CommandLine

```
python -m kwcoco.coco_dataset CocoDataset --show
```

Example

```
>>> from kwcoco.coco_dataset import demo_coco_data
>>> import kwcoco
>>> import ubelt as ub
>>> # Returns a coco json structure
>>> dataset = demo_coco_data()
>>> # Pass the coco json structure to the API
>>> self = kwcoco.CocoDataset(dataset, tag='demo')
>>> # Now you can access the data using the index and helper methods
>>> #
>>> # Start by looking up an image by it's COCO id.
>>> image_id = 1
>>> img = self.index.imgs[image_id]
>>> print(ub.repr2(img, nl=1, sort=1))
{
```

```
    'file_name': 'astro.png',
    'id': 1,
```

(continues on next page)

(continued from previous page)

```

        'url': 'https://i.imgur.com/KXhKM72.png',
    }

>>> #
>>> # Use the (gid_to_aids) index to lookup annotations in the iamge
>>> annotation_id = sorted(self.index.gid_to_aids[image_id])[0]
>>> ann = self.index.anns[annotation_id]
>>> print(ub.repr2(ub.dict_diff(ann, {'segmentation'}), nl=1))
{
    'bbox': [10, 10, 360, 490],
    'category_id': 1,
    'id': 1,
    'image_id': 1,
    'keypoints': [247, 101, 2, 202, 100, 2],
}
>>> #
>>> # Use annotation category id to look up that information
>>> category_id = ann['category_id']
>>> cat = self.index.cats[category_id]
>>> print('cat = {}'.format(ub.repr2(cat, nl=1, sort=1)))
cat = {
    'id': 1,
    'name': 'astronaut',
    'supercategory': 'human',
}
>>> #
>>> # Now play with some helper functions, like extended statistics
>>> extended_stats = self.extended_stats()
>>> print('extended_stats = {}'.format(ub.repr2(extended_stats, nl=1, precision=2,
    sort=1)))
extended_stats = {
    'annots_per_img': {'mean': 3.67, 'std': 3.86, 'min': 0.00, 'max': 9.00, 'nMin': 1,
    'nMax': 1, 'shape': (3,)},
    'imgs_per_cat': {'mean': 0.88, 'std': 0.60, 'min': 0.00, 'max': 2.00, 'nMin': 2,
    'nMax': 1, 'shape': (8,)},
    'cats_per_img': {'mean': 2.33, 'std': 2.05, 'min': 0.00, 'max': 5.00, 'nMin': 1,
    'nMax': 1, 'shape': (3,)},
    'annots_per_cat': {'mean': 1.38, 'std': 1.49, 'min': 0.00, 'max': 5.00, 'nMin': 2,
    'nMax': 1, 'shape': (8,)},
    'imgs_per_video': {'empty_list': True},
}
>>> # You can "draw" a raster of the annotated image with cv2
>>> canvas = self.draw_image(2)
>>> # Or if you have matplotlib you can "show" the image with mpl objects
>>> # xdoctest: +REQUIRES(--show)
>>> from matplotlib import pyplot as plt
>>> fig = plt.figure()
>>> ax1 = fig.add_subplot(1, 2, 1)
>>> self.show_image(gid=2)
>>> ax2 = fig.add_subplot(1, 2, 2)
>>> ax2.imshow(canvas)
>>> ax1.set_title('show with matplotlib')
>>> ax2.set_title('draw with cv2')

```

(continues on next page)

(continued from previous page)

```
>>> plt.show()
```

property fpath(self)

In the future we will deprecate img_root for bundle_dpath

_infer_dirs(self)**classmethod from_data(CocoDataset, data, bundle_dpath=None, img_root=None)**

Constructor from a json dictionary

classmethod from_image_paths(CocoDataset, gpaths, bundle_dpath=None, img_root=None)

Constructor from a list of images paths.

This is a convinience method.

Parameters **gpaths** (*List[str]*) – list of image paths

Example

```
>>> coco_dset = CocoDataset.from_image_paths(['a.png', 'b.png'])
>>> assert coco_dset.n_images == 2
```

classmethod from_coco_paths(CocoDataset, fpaths, max_workers=0, verbose=1, mode='thread', union='try')

Constructor from multiple coco file paths.

Loads multiple coco datasets and unions the result

Note: if the union operation fails, the list of individually loaded files is returned instead.

Parameters

- **fpaths** (*List[str]*) – list of paths to multiple coco files to be loaded and unioned.
- **max_workers** (*int*, *default=0*) – number of worker threads / processes
- **verbose** (*int*) – verbosity level
- **mode** (*str*) – thread, process, or serial
- **union** (*str | bool*, *default='try'*) – If True, unions the result datasets after loading. If False, just returns the result list. If ‘try’, then try to preform the union, but return the result list if it fails.

copy(self)

Deep copies this object

Example

```
>>> from kwcoco.coco_dataset import *
>>> self = CocoDataset.demo()
>>> new = self.copy()
>>> assert new.imgs[1] is new.dataset['images'][0]
>>> assert new.imgs[1] == self.dataset['images'][0]
>>> assert new.imgs[1] is not self.dataset['images'][0]
```

`__nice__(self)`

`dumps(self, indent=None, newlines=False)`

Writes the dataset out to the json format

Parameters `newlines (bool)` – if True, each annotation, image, category gets its own line

Note:

Using `newlines=True` is similar to: `print(ub.repr2(dset.dataset, nl=2, trailsep=False))` However, the above may not output valid json if it contains ndarrays.

Example

```
>>> from kwcoco.coco_dataset import *
>>> import json
>>> self = CocoDataset.demo()
>>> text = self.dumps(newlines=True)
>>> print(text)
>>> self2 = CocoDataset(json.loads(text), tag='demo2')
>>> assert self2.dataset == self.dataset
>>> assert self2.dataset is not self.dataset
```

```
>>> text = self.dumps(newlines=True)
>>> print(text)
>>> self2 = CocoDataset(json.loads(text), tag='demo2')
>>> assert self2.dataset == self.dataset
>>> assert self2.dataset is not self.dataset
```

`dump(self, file, indent=None, newlines=False)`

Writes the dataset out to the json format

Parameters

- `file (PathLike | FileLike)` – Where to write the data. Can either be a path to a file or an open file pointer / stream.
- `newlines (bool)` – if True, each annotation, image, category gets its own line.

Example

```
>>> import tempfile
>>> from kwcoco.coco_dataset import *
>>> self = CocoDataset.demo()
>>> file = tempfile.NamedTemporaryFile('w')
>>> self.dump(file)
>>> file.seek(0)
>>> text = open(file.name, 'r').read()
>>> print(text)
>>> file.seek(0)
>>> dataset = json.load(open(file.name, 'r'))
>>> self2 = CocoDataset(dataset, tag='demo2')
>>> assert self2.dataset == self.dataset
>>> assert self2.dataset is not self.dataset
```

```
>>> file = tempfile.NamedTemporaryFile('w')
>>> self.dump(file, newlines=True)
>>> file.seek(0)
>>> text = open(file.name, 'r').read()
>>> print(text)
>>> file.seek(0)
>>> dataset = json.load(open(file.name, 'r'))
>>> self2 = CocoDataset(dataset, tag='demo2')
>>> assert self2.dataset == self.dataset
>>> assert self2.dataset is not self.dataset
```

_check_json_serializable(self, verbose=1)
Debug which part of a coco dataset might not be json serializable

_check_integrity(self)
perform all checks

_check_index(self)

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> self._check_index()
>>> # Force a failure
>>> self.index.anns.pop(1)
>>> self.index.anns.pop(2)
>>> import pytest
>>> with pytest.raises(AssertionError):
>>>     self._check_index()
```

_check_pointers(self, verbose=1)
Check that all category and image ids referenced by annotations exist

_build_index(self)

```
union(*others, disjoint_tracks=True, **kwargs)
```

Merges multiple `CocoDataset` items into one. Names and associations are retained, but ids may be different.

Parameters

- ***others** – a series of CocoDatasets that we will merge. Note, if called as an instance method, the “self” instance will be the first item in the “others” list. But if called like a classmethod, “others” will be empty by default.
- **disjoint_tracks (bool, default=True)** – if True, we will assume track-ids are disjoint and if two datasets share the same track-id, we will disambiguate them. Otherwise they will be copied over as-is.
- ****kwargs** – constructor options for the new merged CocoDataset

Returns a new merged coco dataset

Return type `CocoDataset`

CommandLine

```
xdoctest -m kwcoco.coco_dataset CocoDataset.union
```

Example

```
>>> # Test union works with different keypoint categories
>>> dset1 = CocoDataset.demo('shapes1')
>>> dset2 = CocoDataset.demo('shapes2')
>>> dset1.remove_keypoint_categories(['bot_tip', 'mid_tip', 'right_eye'])
>>> dset2.remove_keypoint_categories(['top_tip', 'left_eye'])
>>> dset_12a = CocoDataset.union(dset1, dset2)
>>> dset_12b = dset1.union(dset2)
>>> dset_21 = dset2.union(dset1)
>>> def add_hist(h1, h2):
>>>     return {k: h1.get(k, 0) + h2.get(k, 0) for k in set(h1) | set(h2)}
>>> kpfreq1 = dset1.keypoint_annotation_frequency()
>>> kpfreq2 = dset2.keypoint_annotation_frequency()
>>> kpfreq_want = add_hist(kpfreq1, kpfreq2)
>>> kpfreq_got1 = dset_12a.keypoint_annotation_frequency()
>>> kpfreq_got2 = dset_12b.keypoint_annotation_frequency()
>>> assert kpfreq_want == kpfreq_got1
>>> assert kpfreq_want == kpfreq_got2
```

```
>>> # Test disjoint gid datasets
>>> import kwcoco
>>> dset1 = kwcoco.CocoDataset.demo('shapes3')
>>> for new_gid, img in enumerate(dset1.dataset['images'], start=10):
>>>     for aid in dset1.gid_to_aids[img['id']]:
>>>         dset1.anns[aid]['image_id'] = new_gid
>>>     img['id'] = new_gid
>>> dset1.index.clear()
>>> dset1._build_index()
```

(continues on next page)

(continued from previous page)

```
>>> # -----
>>> dset2 = kwCOCO.CocoDataset.demo('shapes2')
>>> for new_gid, img in enumerate(dset2.dataset['images'], start=100):
>>>     for aid in dset2.gid_to_aids[img['id']]:
>>>         dset2.anns[aid]['image_id'] = new_gid
>>>     img['id'] = new_gid
>>> dset1.index.clear()
>>> dset2._build_index()
>>> others = [dset1, dset2]
>>> merged = kwCOCO.CocoDataset.union(*others)
>>> print('merged = {!r}'.format(merged))
>>> print('merged imgs = {}'.format(ub.repr2(merged.imgs, nl=1)))
>>> assert set(merged.imgs) & set([10, 11, 12, 100, 101]) == set(merged.imgs)
```

```
>>> # Test data is not preserved
>>> dset2 = kwCOCO.CocoDataset.demo('shapes2')
>>> dset1 = kwCOCO.CocoDataset.demo('shapes3')
>>> others = (dset1, dset2)
>>> cls = self = kwCOCO.CocoDataset
>>> merged = cls.union(*others)
>>> print('merged = {!r}'.format(merged))
>>> print('merged imgs = {}'.format(ub.repr2(merged.imgs, nl=1)))
>>> assert set(merged.imgs) & set([1, 2, 3, 4, 5]) == set(merged.imgs)
```

```
>>> # Test track-ids are mapped correctly
>>> dset1 = kwCOCO.CocoDataset.demo('vidshapes1')
>>> dset2 = kwCOCO.CocoDataset.demo('vidshapes2')
>>> dset3 = kwCOCO.CocoDataset.demo('vidshapes3')
>>> others = (dset1, dset2, dset3)
>>> for dset in others:
>>>     [a.pop('segmentation', None) for a in dset.index.anns.values()]
>>>     [a.pop('keypoints', None) for a in dset.index.anns.values()]
>>> cls = self = kwCOCO.CocoDataset
>>> merged = cls.union(*others, disjoint_tracks=1)
>>> print('dset1.anns = {}'.format(ub.repr2(dset1.anns, nl=1)))
>>> print('dset2.anns = {}'.format(ub.repr2(dset2.anns, nl=1)))
>>> print('dset3.anns = {}'.format(ub.repr2(dset3.anns, nl=1)))
>>> print('merged.anns = {}'.format(ub.repr2(merged.anns, nl=1)))
```

Example

```
>>> import kwCOCO
>>> # Test empty union
>>> empty_union = kwCOCO.CocoDataset.union()
>>> assert len(empty_union.index.imgs) == 0
```

Todo:

- [] are supercategories broken?
- [] reuse image ids where possible

- [] reuse annotation / category ids where possible
- [X] handle case where no inputs are given
- [x] disambiguate track-ids
- [x] disambiguate video-ids

subset(self, gids, copy=False, autobuild=True)

Return a subset of the larger coco dataset by specifying which images to port. All annotations in those images will be taken.

Parameters

- **gids** (*List[int]*) – image-ids to copy into a new dataset
- **copy** (*bool, default=False*) – if True, makes a deep copy of all nested attributes, otherwise makes a shallow copy.
- **autobuild** (*bool, default=True*) – if True will automatically build the fast lookup index.

Example

```
>>> self = CocoDataset.demo()
>>> gids = [1, 3]
>>> sub_dset = self.subset(gids)
>>> assert len(self.index.gid_to_aids) == 3
>>> assert len(sub_dset.gid_to_aids) == 2
```

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo('vidshapes2')
>>> gids = [1, 2]
>>> sub_dset = self.subset(gids, copy=True)
>>> assert len(sub_dset.index.videos) == 1
>>> assert len(self.index.videos) == 2
```

Example

```
>>> self = CocoDataset.demo()
>>> sub1 = self.subset([1])
>>> sub2 = self.subset([2])
>>> sub3 = self.subset([3])
>>> others = [sub1, sub2, sub3]
>>> rejoined = CocoDataset.union(*others)
>>> assert len(sub1.anns) == 9
>>> assert len(sub2.anns) == 2
>>> assert len(sub3.anns) == 0
>>> assert rejoined.basic_stats() == self.basic_stats()
```

view_sql(self, force_rewrite=False, memory=False)

Create a cached SQL interface to this dataset suitable for large scale multiprocessing use cases.

Parameters

- **force_rewrite** (*bool, default=False*) – if True, forces an update to any existing cache file on disk
- **memory** (*bool, default=False*) – if True, the database is constructed in memory.

Note: This view cache is experimental and currently depends on the timestamp of the file pointed to by `self.fpath`. In other words dont use this on in-memory datasets.

`kwcoco.coco_dataset.demo_coco_data()`

Simple data for testing.

This contains several non-standard fields, which help ensure robustness of functions tested with this data. For more compliant demodata see the `kwcoco.demodata` submodule

Example

```
>>> # xdoctest: +REQUIRES(--show)
>>> from kwcoco.coco_dataset import demo_coco_data, CocoDataset
>>> dataset = demo_coco_data()
>>> self = CocoDataset(dataset, tag='demo')
>>> import kwplot
>>> kwplot.autopl()l()
>>> self.show_image(gid=1)
>>> kwplot.show_if_requested()
```

2.3.7 `kwcoco.coco_evaluator`

Evaluates a predicted coco dataset against a truth coco dataset.

The components in this module work programmaticaly or as a command line script.

Todo:

- [] **does evaluate return one result or multiple results** based on different configurations?
 - [] max_dets - TODO: in original pycocoutils but not here
 - [] Flag that allows for polygon instead of bounding box overlap
 - [] **How do we note what iou_thresh and area-range were in** the result plots?
-

CommandLine

```
xdoc test -m kwcoco.coco_evaluator __doc__:0 --vd --slow
```

Example

```
>>> from kwcoco.coco_evaluator import * # NOQA
>>> from kwcoco.coco_evaluator import CocoEvaluator
>>> import kwcoco
>>> # note: increase the number of images for better looking metrics
>>> true_dset = kwcoco.CocoDataset.demo('shapes8')
>>> from kwcoco.demo.perterb import perterb_coco
>>> kwargs = {
>>>     'box_noise': 0.5,
>>>     'n_fp': (0, 10),
>>>     'n_fn': (0, 10),
>>>     'with_probs': True,
>>> }
>>> pred_dset = perterb_coco(true_dset, **kwargs)
>>> print('true_dset = {!r}'.format(true_dset))
>>> print('pred_dset = {!r}'.format(pred_dset))
>>> config = {
>>>     'true_dataset': true_dset,
>>>     'pred_dataset': pred_dset,
>>>     'area_range': ['all', 'small'],
>>>     'iou_thresh': [0.3, 0.95],
>>> }
>>> coco_eval = CocoEvaluator(config)
>>> results = coco_eval.evaluate()
>>> # Now we can draw / serialize the results as we please
>>> dpath = ub.ensure_app_cache_dir('kwcoco/tests/test_out_dpath')
>>> results_fpath = join(dpath, 'metrics.json')
>>> print('results_fpath = {!r}'.format(results_fpath))
>>> results.dump(results_fpath, indent='    ')
>>> measures = results['area_range=all,iou_thresh=0.3'].ncls_measures
>>> import pandas as pd
>>> print(pd.DataFrame(ub.dict_isect(
>>>     measures, ['f1', 'g1', 'mcc', 'thresholds',
>>>                 'ppv', 'tpr', 'tnr', 'npv', 'fpr',
>>>                 'tp_count', 'fp_count',
>>>                 'tn_count', 'fn_count'])).iloc[:100])
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> # xdoctest: +REQUIRES(--slow)
>>> results.dump_figures(dpath)
>>> print('dpath = {!r}'.format(dpath))
>>> # xdoctest: +REQUIRES(--vd)
>>> if ub.argflag('--vd') or 1:
>>>     import xdev
>>>     xdev.view_directory(dpath)
```

Module Contents

Classes

<i>CocoEvalConfig</i>	Evaluate and score predicted versus truth detections / classifications in a COCO dataset
<i>CocoEvaluator</i>	Abstracts the evaluation process to execute on two coco datasets.
<i>CocoResults</i>	

CommandLine

<i>CocoSingleResult</i>	Container class to store, draw, summarize, and serialize results from
-------------------------	---

Functions

<i>_dmet_area_weights(dmet, orig_weights, cfsn_vecs, area_ranges, coco_eval, use_area_attr=False)</i>	Hacky function to compute confusion vector ignore weights for different
<i>_writefig(fig, metrics_dpath, fname, figsize, verbose, tight)</i>	
<i>_load_dets(pred_fpaths, workers=0)</i>	

Example

<i>_load_dets_worker(single_pred_fpath, with_coco=True)</i>

Attributes

<i>profile</i>
<i>COCO_SAMPLER_CLS</i>

```
kwcoco.coco_evaluator.profile
kwcoco.coco_evaluator.COCO_SAMPLER_CLS
class kwcoco.coco_evaluator.CocoEvalConfig(data=None, default=None, cmdline=False)
    Bases: scriptconfig.Config
    Evaluate and score predicted versus truth detections / classifications in a COCO dataset
    default
    normalize(self)
        overloadable function called after each load
class kwcoco.coco_evaluator.CocoEvaluator(coco_eval, config)
    Bases: object
```

Abstracts the evaluation process to execute on two coco datasets.

This can be run as a standalone script where the user specifies the paths to the true and predicted dataset explicitly, or this can be used by a higher level script that produces the predictions and then sends them to this evaluator.

Example

```
>>> from kwcoco.coco_evaluator import CocoEvaluator
>>> from kwcoco.demo.perterb import perterb_coco
>>> import kwcoco
>>> true_dset = kwcoco.CocoDataset.demo('shapes8')
>>> kwargs = {
>>>     'box_noise': 0.5,
>>>     'n_fp': (0, 10),
>>>     'n_fn': (0, 10),
>>>     'with_probs': True,
>>> }
>>> pred_dset = perterb_coco(true_dset, **kwargs)
>>> config = {
>>>     'true_dataset': true_dset,
>>>     'pred_dataset': pred_dset,
>>>     'classes_of_interest': [],
>>> }
>>> coco_eval = CocoEvaluator(config)
>>> results = coco_eval.evaluate()
```

Config

`log(coco_eval, msg, level='INFO')`

`_init(coco_eval)`

Performs initial coercion from given inputs into dictionaries of kwimage.Detection objects and attempts to ensure comparable category and image ids.

`_ensure_init(coco_eval)`

`classmethod _rectify_classes(coco_eval, true_classes, pred_classes)`

`classmethod _coerce_dets(CocoEvaluator, dataset, verbose=0, workers=0)`

Coerce the input to a mapping from image-id to kwimage.Detection

Also capture a CocoDataset if possible.

Returns `gid_to_det`: mapping from gid to dets extra: any extra information we gathered via coercion

Return type `Tuple[Dict[int, Detections], Dict]`

Example

```
>>> from kwCOCO.coco_evaluator import * # NOQA
>>> import kwCOCO
>>> coco_dset = kwCOCO.CocoDataset.demo('shapes8')
>>> gid_to_det, extras = CocoEvaluator._coerce_dets(coco_dset)
```

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwCOCO.coco_evaluator import * # NOQA
>>> import kwCOCO
>>> coco_dset = kwCOCO.CocoDataset.demo('shapes8').view_sql()
>>> gid_to_det, extras = CocoEvaluator._coerce_dets(coco_dset)
```

`_build_dmet(coco_eval)`

Builds the detection metrics object

Returns

DetectionMetrics - object that can perform assignment and build confusion vectors.

`evaluate(coco_eval)`

Executes the main evaluation logic. Performs assignments between detections to make DetectionMetrics object, then creates per-item and ovr confusion vectors, and performs various threshold-vs-confusion analyses.

Returns

container storing (and capable of drawing / serializing) results

Return type *CocoResults*

`kwCOCO.coco_evaluator.dmet_area_weights(dmet, orig_weights, cfsn_vecs, area_ranges, coco_eval, use_area_attr=False)`

Hacky function to compute confusion vector ignore weights for different area thresholds. Needs to be slightly refactored.

`class kwCOCO.coco_evaluator.CocoResults(results, resdata=None)`

Bases: `ubelt.NiceRepr, kwCOCO.metrics.util.DictProxy`

CommandLine

```
xdoctest -m /home/joncrall/code/kwCOCO/kwCOCO/coco_evaluator.py CocoResults --
    -profile
```

Example

```
>>> from kwcoco.coco_evaluator import * # NOQA
>>> from kwcoco.coco_evaluator import CocoEvaluator
>>> import kwcoco
>>> true_dset = kwcoco.CocoDataset.demo('shapes2')
>>> from kwcoco.demo.perterb import perterb_coco
>>> kwargs = {
>>>     'box_noise': 0.5,
>>>     'n_fp': (0, 10),
>>>     'n_fn': (0, 10),
>>> }
>>> pred_dset = perterb_coco(true_dset, **kwargs)
>>> print('true_dset = {!r}'.format(true_dset))
>>> print('pred_dset = {!r}'.format(pred_dset))
>>> config = {
>>>     'true_dataset': true_dset,
>>>     'pred_dataset': pred_dset,
>>>     'area_range': ['small'],
>>>     'iou_thresh': [0.3],
>>> }
>>> coco_eval = CocoEvaluator(config)
>>> results = coco_eval.evaluate()
>>> # Now we can draw / serialize the results as we please
>>> dpath = ub.ensure_app_cache_dir('kwcoco/tests/test_out_dpath')
>>> #
>>> # test deserialization works
>>> state = results.__json__()
>>> self2 = CocoResults.from_json(state)
>>> #
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> results.dump_figures(dpath, figsize=(3, 2), tight=False) # make this go faster
>>> results.dump(join(dpath, 'metrics.json'), indent=' ')
```

`dump_figures(results, out_dpath, expt_title=None, figsize='auto', tight=True)`

`__json__(results)`

`classmethod from_json(cls, state)`

`dump(result, file, indent='')`

Serialize to json file

`class kwcoco.coco_evaluator.CocoSingleResult(result, nocls_measures, ovr_measures, cfsn_vecs, meta=None)`

Bases: `ubelt.NiceRepr`

Container class to store, draw, summarize, and serialize results from CocoEvaluator.

Example

```
>>> # xdoctest: +REQUIRES(--slow)
>>> from kwcoco.coco_evaluator import * # NOQA
>>> from kwcoco.coco_evaluator import CocoEvaluator
>>> import kwcoco
>>> true_dset = kwcoco.CocoDataset.demo('shapes8')
>>> from kwcoco.demo.perterb import perterb_coco
>>> kwargs = {
>>>     'box_noise': 0.2,
>>>     'n_fp': (0, 3),
>>>     'n_fn': (0, 3),
>>>     'with_probs': False,
>>> }
>>> pred_dset = perterb_coco(true_dset, **kwargs)
>>> print('true_dset = {!r}'.format(true_dset))
>>> print('pred_dset = {!r}'.format(pred_dset))
>>> config = {
>>>     'true_dataset': true_dset,
>>>     'pred_dataset': pred_dset,
>>>     'area_range': [(0, 32 ** 2), (32 ** 2, 96 ** 2)],
>>>     'iou_thresh': [0.3, 0.5, 0.95],
>>> }
>>> coco_eval = CocoEvaluator(config)
>>> results = coco_eval.evaluate()
>>> result = ub.peek(results.values())
>>> state = result.__json__()
>>> print('state = {}'.format(ub.repr2(state, nl=-1)))
>>> recon = CocoSingleResult.from_json(state)
>>> state = recon.__json__()
>>> print('state = {}'.format(ub.repr2(state, nl=-1)))
```

`__nice__(result)`

`classmethod from_json(cls, state)`

`__json__(result)`

`dump(result, file, indent=' ')`

Serialize to json file

`dump_figures(result, out_dpath, expt_title=None, figsize='auto', tight=True, verbose=1)`

`kwcoco.coco_evaluator._writefig(fig, metrics_dpath, fname, figsize, verbose, tight)`

`kwcoco.coco_evaluator._load_dets(pred_fpaths, workers=0)`

Example

```
>>> from kwcoco.coco_evaluator import _load_dets, _load_dets_worker
>>> import ubelt as ub
>>> import kwcoco
>>> from os.path import join
>>> dpath = ub.ensure_app_cache_dir('kwcoco/tests/load_dets')
>>> N = 4
>>> pred_fpaths = []
>>> for i in range(1, N + 1):
>>>     dset = kwcoco.CocoDataset.demo('shapes{}'.format(i))
>>>     dset.fpath = join(dpath, 'shapes_{}.mscoco.json'.format(i))
>>>     dset.dump(dset.fpath)
>>>     pred_fpaths.append(dset.fpath)
>>> dets, coco_dset = _load_dets(pred_fpaths)
>>> print('dets = {!r}'.format(dets))
>>> print('coco_dset = {!r}'.format(coco_dset))
```

`kwcoco.coco_evaluator._load_dets_worker(single_pred_fpath, with_coco=True)`

2.3.8 kwcoco.coco_image

Module Contents

Classes

<code>CocoImage</code>	An object-oriented representation of a coco image.
------------------------	--

Functions

`_delay_load_imglike(bundle_dpath, obj)`

`class kwcoco.coco_image.CocoImage(img, dset=None)`
Bases: `ubelt.NiceRepr`

An object-oriented representation of a coco image.

It provides helper methods that are specific to a single image.

This operates directly on a single coco image dictionary, but it can optionally be connected to a parent dataset, which allows it to use CocoDataset methods to query about relationships and resolve pointers.

This is different than the Images class in coco_object1d, which is just a vectorized interface to multiple objects.

Example

```
>>> import kwcoco
>>> dset1 = kwcoco.CocoDataset.demo('shapes8')
>>> dset2 = kwcoco.CocoDataset.demo('vidshapes8-multispectral')

>>> self = CocoImage(dset1 imgs[1], dset1)
>>> print('self = {!r}'.format(self))
>>> print('self.channels = {}'.format(ub.repr2(self.channels, nl=1)))

>>> self = CocoImage(dset2 imgs[1], dset2)
>>> print('self.channels = {}'.format(ub.repr2(self.channels, nl=1)))
>>> self.primary_asset()

classmethod from_gid(cls, dset, gid)

property bundle_dpath(self)

property video(self)
    Helper to grab the video for this image if it exists

detach(self)
    Removes references to the underlying coco dataset, but keeps special information such that it wont be
    needed.

__nice__(self)
```

Example

```
>>> from kwcoco.coco_image import * # NOQA
>>> import kwcoco
>>> with ub.CaptureStdout() as cap:
...     dset = kwcoco.CocoDataset.demo('shapes8')
>>> self = CocoImage(dset.dataset['images'][0], dset)
>>> print('self = {!r}'.format(self))

>>> dset = kwcoco.CocoDataset.demo()
>>> self = CocoImage(dset.dataset['images'][0], dset)
>>> print('self = {!r}'.format(self))

stats(self)

__getitem__(self, key)

keys(self)

get(self, key, default=ub.NoParam)
    Duck type some of the dict interface

property channels(self)

property num_channels(self)

property dsize(self)

primary_image_filepath(self, requires=None)
```

primary_asset(self, requires=None)

Compute a “main” image asset.

Parameters **requires** (*List[str]*) – list of attribute that must be non-None to consider an object as the primary one.

Todo:

- [] Add in primary heuristics

iter_image_filepaths(self)**iter_asset_objs(self)**

Iterate through base + auxiliary dicts that have file paths

Yields *dict* – an image or auxiliary dictionary

add_auxiliary_item(self, file_name=None, channels=None, imdata=None, warp_aux_to_img=None, width=None, height=None, imwrite=False)

Adds an auxiliary item to the image dictionary.

This operation can be done purely in-memory (the default), or the image data can be written to a file on disk (via the imwrite=True flag).

Parameters

- **file_name** (*str | None*) – The name of the file relative to the bundle directory. If unspecified, imdata must be given.
- **channels** (*str | kwcoco.FusedChannelSpec*) – The channel code indicating what each of the bands represents. These channels should be disjoint wrt to the existing data in this image (this is not checked).
- **imdata** (*ndarray | None*) – The underlying image data this auxiliary item represents. If unspecified, it is assumed file_name points to a path on disk that will eventually exist. If imdata, file_name, and the special imwrite=True flag are specified, this function will write the data to disk.
- **warp_aux_to_img** (*kwimage.Affine*) – The transformation from this auxiliary space to image space. If unspecified, assumes this item is related to image space by only a scale factor.
- **width** (*int*) – Width of the data in auxiliary space (inferred if unspecified)
- **height** (*int*) – Height of the data in auxiliary space (inferred if unspecified)
- **imwrite** (*bool*) – If specified, both imdata and file_name must be specified, and this will write the data to disk. Note: it is recommended that you simply call imwrite yourself before or after calling this function. This lets you better control imwrite parameters.

Todo:

- [] Allow imwrite to specify an executor that is used to return a Future so the imwrite call does not block.

Example

```
>>> from kwCOCO.coco_image import * # NOQA
>>> import kwCOCO
>>> dset = kwCOCO.CocoDataset.demo('vidshapes8-multispectral')
>>> coco_img = dset.coco_image(1)
>>> imdata = np.random.rand(32, 32, 5)
>>> channels = kwCOCO.FusedChannelSpec.coerce('Aux:5')
>>> coco_img.add_auxiliary_item(imdata=imdata, channels=channels)
```

delay(self, channels=None, space='image', bundle_dpath=None)

Perform a delayed load on the data in this image.

The delayed load can load a subset of channels, and perform lazy warping operations. If the underlying data is in a tiled format this can reduce the amount of disk IO needed to read the data if only a small crop or lower resolution view of the data is needed.

Note: This method is experimental and relies on the delayed load proof-of-concept.

Parameters

- **gid** (*int*) – image id to load
- **channels** (*FusedChannelSpec*) – specific channels to load. if unspecified, all channels are loaded.
- **space** (*str*) – can either be “image” for loading in image space, or “video” for loading in video space.

Todo:

- [X] **Currently can only take all or none of the channels from each base-image / auxiliary dict.**
For instance if the main image is r|g|b you can't just select g|b at the moment.
 - [X] **The order of the channels in the delayed load should** match the requested channel order.
 - [X] TODO: add nans to bands that don't exist or throw an error
 - [] **This function could stand to have a better name. Maybe imread with a delayed=True flag? Or maybe just delayed_load?**
-

Example

```
>>> from kwCOCO.coco_image import * # NOQA
>>> import kwCOCO
>>> gid = 1
>>> #
>>> dset = kwCOCO.CocoDataset.demo('vidshapes8-multispectral')
>>> self = CocoImage(dset.imgs[gid], dset)
>>> delayed = self.delay()
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize()))
```

(continues on next page)

(continued from previous page)

```
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
>>> #
>>> dset = kwCOCO.CocoDataset.demo('shapes8')
>>> delayed = dset.delayed_load(gid)
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize()))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
```

```
>>> crop = delayed.delayed_crop((slice(0, 3), slice(0, 3)))
>>> crop.finalize()
>>> crop.finalize(as_xarray=True)
```

```
>>> # TODO: should only select the "red" channel
>>> dset = kwCOCO.CocoDataset.demo('shapes8')
>>> delayed = CocoImage(dset.imgs[gid], dset).delay(channels='r')
```

```
>>> import kwCOCO
>>> gid = 1
>>> #
>>> dset = kwCOCO.CocoDataset.demo('vidshapes8-multispectral')
>>> delayed = dset.delayed_load(gid, channels='B1|B2', space='image')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
>>> delayed = dset.delayed_load(gid, channels='B1|B2|B11', space='image')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
>>> delayed = dset.delayed_load(gid, channels='B8|B1', space='video')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
```

```
>>> delayed = dset.delayed_load(gid, channels='B8|foo|bar|B1', space='video')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
```

Example

```
>>> import kwCOCO
>>> dset = kwCOCO.CocoDataset.demo()
>>> coco_img = dset.coco_image(1)
>>> # Test case where nothing is registered in the dataset
>>> delayed = coco_img.delay()
>>> final = delayed.finalize()
>>> assert final.shape == (512, 512, 3)
```

Example

```
>>> # Test that delay works when imdata is stored in the image
>>> # dictionary itself.
>>> from kwcoco.coco_image import * # NOQA
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral')
>>> coco_img = dset.coco_image(1)
>>> imdata = np.random.rand(6, 6, 5)
>>> imdata[:] = np.arange(5)[None, None, :]
>>> channels = kwcoco.FusedChannelSpec.coerce('Aux:5')
>>> coco_img.add_auxiliary_item(imdata=imdata, channels=channels)
>>> delayed = coco_img.delay(channels='B1|Aux:2:4')
>>> final = delayed.finalize()
```

```
kwcoco.coco_image._delay_load_imglike(bundle_dpath, obj)
```

2.3.9 kwcoco.coco_objects1d

Vectorized ORM-like objects used in conjunction with coco_dataset

Module Contents

Classes

<i>ObjectList1D</i>	Vectorized access to lists of dictionary objects
<i>ObjectGroups</i>	An object for holding a groups of <i>ObjectList1D</i> objects
<i>Categories</i>	Vectorized access to category attributes
<i>Videos</i>	Vectorized access to video attributes
<i>Images</i>	Vectorized access to image attributes
<i>Annots</i>	Vectorized access to annotation attributes
<i>AnnotGroups</i>	An object for holding a groups of <i>ObjectList1D</i> objects
<i>ImageGroups</i>	An object for holding a groups of <i>ObjectList1D</i> objects

```
class kwcoco.coco_objects1d.ObjectList1D(ids, dset, key)
```

Bases: `ubelt.NiceRepr`

Vectorized access to lists of dictionary objects

Lightweight reference to a set of object (e.g. annotations, images) that allows for convenient property access.

Parameters

- **ids** (`List[int]`) – list of ids
- **dset** (`CocoDataset`) – parent dataset
- **key** (`str`) – main object name (e.g. ‘images’, ‘annotations’)

Types: ObjT = Ann | Img | Cat # can be one of these types ObjectList1D gives us access to a List[ObjT]

Example

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo()
>>> # Both annots and images are object lists
>>> self = dset.annots()
>>> self = dset.images()
>>> # can call with a list of ids or not, for everything
>>> self = dset.annots([1, 2, 11])
>>> self = dset.images([1, 2, 3])
>>> self.lookup('id')
>>> self.lookup(['id'])
```

`__nice__(self)`
`__iter__(self)`
`__len__(self)`
`property _id_to_obj(self)`
`__getitem__(self, index)`
`property objs(self)`

Returns all object dictionaries

Return type List[ObjT]

`take(self, idxs)`
 Take a subset by index

Returns ObjectList1D

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo().annots()
>>> assert len(self.take([0, 2, 3])) == 3
```

`compress(self, flags)`
 Take a subset by flags

Returns ObjectList1D

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo().images()
>>> assert len(self.compress([True, False, True])) == 2
```

`peek(self)`
 Return the first object dictionary

Returns object dictionary

Return type ObjT

Example

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo()
>>> self = dset.images()
>>> assert self.peek()['id'] == 1
>>> # Check that subsets return correct items
>>> sub0 = self.compress([i % 2 == 0 for i in range(len(self))])
>>> sub1 = self.compress([i % 2 == 1 for i in range(len(self))])
>>> assert sub0.peek()['id'] == 1
>>> assert sub1.peek()['id'] == 2
```

lookup(*self*, *key*, *default*=*ub.NoParam*, *keepid*=*False*)

Lookup a list of object attributes

Parameters

- **key** (*str* | *Iterable*) – name of the property you want to lookup can also be a list of names, in which case we return a dict
- **default** – if specified, uses this value if it doesn't exist in an ObjT.
- **keepid** – if True, return a mapping from ids to the property

Returns a list of whatever type the object is Dict[str, ObjT]

Return type List[ObjT]

Example

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo()
>>> self = dset.annots()
>>> self.lookup('id')
>>> key = ['id']
>>> default = None
>>> self.lookup(key=['id', 'image_id'])
>>> self.lookup(key=['id', 'image_id'])
>>> self.lookup(key='foo', default=None, keepid=True)
>>> self.lookup(key=['foo'], default=None, keepid=True)
>>> self.lookup(key=['id', 'image_id'], keepid=True)
```

get(*self*, *key*, *default*=*ub.NoParam*, *keepid*=*False*)

Lookup a list of object attributes

Parameters

- **key** (*str*) – name of the property you want to lookup
- **default** – if specified, uses this value if it doesn't exist in an ObjT.
- **keepid** – if True, return a mapping from ids to the property

Returns a list of whatever type the object is Dict[str, ObjT]

Return type List[ObjT]

Example

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo()
>>> self = dset.annots()
>>> self.get('id')
>>> self.get(key='foo', default=None, keepid=True)
```

`set(self, key, values)`

Assign a value to each annotation

Parameters

- `key (str)` – the annotation property to modify
- `values (Iterable | scalar)` – an iterable of values to set for each annot in the dataset. If the item is not iterable, it is assigned to all objects.

Example

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo()
>>> self = dset.annots()
>>> self.set('my-key1', 'my-scalar-value')
>>> self.set('my-key2', np.random.rand(len(self)))
>>> print('dset.imgs = {}'.format(ub.repr2(dset.imgs, nl=1)))
>>> self.get('my-key2')
```

`_set(self, key, values)`

faster less safe version of set

`_lookup(self, key, default=ub.NoParam)`

Example

```
>>> # xdoctest: +REQUIRES(--benchmark)
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('shapes256')
>>> self = annots = dset.annots()
>>> #
>>> import timerit
>>> ti = timerit.Timerit(100, bestof=10, verbose=2)
>>> #
>>> for timer in ti.reset('lookup'):
>>>     with timer:
>>>         self.lookup('image_id')
>>> #
>>> for timer in ti.reset('_lookup'):
>>>     with timer:
>>>         self._lookup('image_id')
>>> #
>>> for timer in ti.reset('image_id'):
>>>     with timer:
```

(continues on next page)

(continued from previous page)

```
>>>         self.image_id
>>> #
>>> for timer in ti.reset('raw1'):
>>>     with timer:
>>>         key = 'image_id'
>>>         [self._dset.anns[_id][key] for _id in self._ids]
>>> #
>>> for timer in ti.reset('raw2'):
>>>     with timer:
>>>         anns = self._dset.anns
>>>         key = 'image_id'
>>>         [anns[_id][key] for _id in self._ids]
>>> #
>>> for timer in ti.reset('lut-gen'):
>>>     with timer:
>>>         _lut = self._obj_lut
>>>         objs = (_lut[_id] for _id in self._ids)
>>>         [obj[key] for obj in objs]
>>> #
>>> for timer in ti.reset('lut-gen-single'):
>>>     with timer:
>>>         _lut = self._obj_lut
>>>         [_lut[_id][key] for _id in self._ids]
```

attribute_frequency(*self*)

Compute the number of times each key is used in a dictionary

Returns Dict[str, int]**Example**

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo()
>>> self = dset.annots()
>>> attrs = self.attribute_frequency()
>>> print('attrs = {}'.format(ub.repr2(attrs, nl=1)))
```

class kwcoco.coco_objects1d.ObjectGroups(*groups, dset*)Bases: *ubelt.NiceRepr*An object for holding a groups of *ObjectList1D* objects**_lookup(*self, key*)****__getitem__(*self, index*)****lookup(*self, key, default=ub.NoParam*)****__nice__(*self*)****class kwcoco.coco_objects1d.Categories(*ids, dset*)**Bases: *ObjectList1D*

Vectorized access to category attributes

SeeAlso: *kwcoco.coco_dataset.MixinCocoObjects.categories()*

Example

```
>>> from kwcoco.coco_objects1d import Categories # NOQA
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo()
>>> ids = list(dset.cats.keys())
>>> self = Categories(ids, dset)
>>> print('self.name = {!r}'.format(self.name))
>>> print('self.supercategory = {!r}'.format(self.supercategory))
```

property cids(self)**property name(self)****property supercategory(self)****class kwcoco.coco_objects1d.Videos(ids, dset)**Bases: *ObjectList1D*

Vectorized access to video attributes

SeeAlso: [kwcoco.coco_dataset.MixinCocoObjects.videos\(\)](#)**Example**

```
>>> from kwcoco.coco_objects1d import Videos # NOQA
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes5')
>>> ids = list(dset.index.videos.keys())
>>> self = Videos(ids, dset)
>>> print('self = {!r}'.format(self))
```

property images(self)**Example**

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo('vidshapes8').videos()
>>> print(self.images)
<ImageGroups(n=8, m=2.0, s=0.0)>
```

class kwcoco.coco_objects1d.Images(ids, dset)Bases: *ObjectList1D*

Vectorized access to image attributes

SeeAlso: [kwcoco.coco_dataset.MixinCocoObjects.images\(\)](#)**property coco_images(self)****property gids(self)****property gname(self)****property gpath(self)****property width(self)**

```
property height(self)
property size(self)
```

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo().images()
>>> self._dset._ensure_imgsized()
>>> print(self.size)
[(512, 512), (300, 250), (256, 256)]
```

```
property area(self)
```

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo().images()
>>> self._dset._ensure_imgsized()
>>> print(self.area)
[262144, 75000, 65536]
```

```
property n_annots(self)
```

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo().images()
>>> print(ub.repr2(self.n_annots, nl=0))
[9, 2, 0]
```

```
property aids(self)
```

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo().images()
>>> print(ub.repr2(list(map(list, self.aids)), nl=0))
[[1, 2, 3, 4, 5, 6, 7, 8, 9], [10, 11], []]
```

```
property annots(self)
```

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo().images()
>>> print(self.annots)
<AnnotGroups(n=3, m=3.7, s=3.9)>
```

class kwcoco.coco_objects1d.Annots(*ids, dset*)

Bases: *ObjectList1D*

Vectorized access to annotation attributes

SeeAlso: *kwcoco.coco_dataset.MixinCocoObjects.annots()*

property aids(*self*)

The annotation ids of this column of annotations

property images(*self*)

Get the column of images

Returns Images

property image_id(*self*)

property category_id(*self*)

property gids(*self*)

Get the column of image-ids

Returns list of image ids

Return type List[int]

property cids(*self*)

Get the column of category-ids

Returns List[int]

property cnames(*self*)

Get the column of category names

Returns List[int]

property detections(*self*)

Get the kwimage-style detection objects

Returns kwimage.Detections

Example

```
>>> # xdoctest: +REQUIRES(module:kwimage)
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo('shapes32').annots([1, 2, 11])
>>> dets = self.detections
>>> print('dets.data = {!r}'.format(dets.data))
>>> print('dets.meta = {!r}'.format(dets.meta))
```

property boxes(*self*)

Get the column of kwimage-style bounding boxes

Example

```
>>> import kwCOCO
>>> self = kwCOCO.CocoDataset.demo().annots([1, 2, 11])
>>> print(self.boxes)
<Boxes(xywh,
       array([[ 10,  10, 360, 490],
              [350,   5, 130, 290],
              [124,  96,  45, 18]]))>
```

property xywh(self)

Returns raw boxes

Example

```
>>> import kwCOCO
>>> self = kwCOCO.CocoDataset.demo().annots([1, 2, 11])
>>> print(self.xywh)
```

class kwCOCO.coco_objects1d.AnnotGroups(groups, dset)Bases: *ObjectGroups*An object for holding a groups of *ObjectList1D* objects**property cids(self)****property cnames(self)****class kwCOCO.coco_objects1d.ImageGroups(groups, dset)**Bases: *ObjectGroups*An object for holding a groups of *ObjectList1D* objects

2.3.10 kwCOCO.coco_schema

CommandLine

```
python -m kwCOCO.coco_schema
xdoc test -m kwCOCO.coco_schema __doc__
```

Example

```
>>> import kwCOCO
>>> from kwCOCO.coco_schema import COCO_SCHEMA
>>> import jsonschema
>>> dset = kwCOCO.CocoDataset.demo('shapes1')
>>> # print('dset.dataset = {}'.format(ub.repr2(dset.dataset, nl=2)))
>>> COCO_SCHEMA.validate(dset.dataset)
```

```
>>> try:
>>>     jsonschema.validate(dset.dataset, schema=COCO_SCHEMA)
>>> except jsonschema.exceptions.ValidationError as ex:
>>>     vali_ex = ex
>>>     print('ex = {!r}'.format(ex))
>>>     raise
>>> except jsonschema.exceptions.SchemaError as ex:
>>>     print('ex = {!r}'.format(ex))
>>>     schema_ex = ex
>>>     print('schema_ex.instance = {}'.format(ub.repr2(schema_ex.instance, nl=-1)))
>>>     raise
```

```
>>> # Test the multispectral image defintino
>>> import copy
>>> dataset = dset.copy().dataset
>>> img = dataset['images'][0]
>>> img.pop('file_name')
>>> import pytest
>>> with pytest.raises(jsonschema.ValidationError):
>>>     COCO_SCHEMA.validate(dataset)
>>> import pytest
>>> img['auxiliary'] = [{'file_name': 'foobar'}]
>>> with pytest.raises(jsonschema.ValidationError):
>>>     COCO_SCHEMA.validate(dataset)
>>> img['name'] = 'aux-only images must have a name'
>>> COCO_SCHEMA.validate(dataset)
```

Module Contents

Functions

`deprecated(*args)`

`TUPLE(*args, **kw)`

Attributes

`elem`

`ALLOF`

`ANY`

`ANYOF`

continues on next page

Table 106 – continued from previous page

ARRAY
BOOLEAN
INTEGER
NOT
NULL
NUMBER
OBJECT
ONEOF
STRING
UUID
PATH
KWCOCO_KEYPOINT
KWCOCO_POLYGON
ORIG_COCO_KEYPOINTS
KWCOCO_KEYPOINTS
KEYPOINTS
ORIG_COCO_POLYGON
POLYGON
RUN_LENGTH_ENCODING
BBOX
SEGMENTATION
CATEGORY
KEYPOINT_CATEGORY
VIDEO
CHANNELS

continues on next page

Table 106 – continued from previous page

<i>IMAGE</i>	
<i>ANNOTATION</i>	
<i>COCO_SCHEMA</i>	
kwcoco.coco_schema. deprecated (*args)	
kwcoco.coco_schema. TUPLE (*args, **kw)	
kwcoco.coco_schema. elem	
kwcoco.coco_schema. ALLOF	
kwcoco.coco_schema. ANY	
kwcoco.coco_schema. ANYOF	
kwcoco.coco_schema. ARRAY	
kwcoco.coco_schema. BOOLEAN	
kwcoco.coco_schema. INTEGER	
kwcoco.coco_schema. NOT	
kwcoco.coco_schema. NULL	
kwcoco.coco_schema. NUMBER	
kwcoco.coco_schema. OBJECT	
kwcoco.coco_schema. ONEOF	
kwcoco.coco_schema. STRING	
kwcoco.coco_schema. UUID	
kwcoco.coco_schema. PATH	
kwcoco.coco_schema. KWCOCO_KEYPOINT	
kwcoco.coco_schema. KWCOCO_POLYGON	
kwcoco.coco_schema. ORIG_COCO_KEYPOINTS	
kwcoco.coco_schema. KWCOCO_KEYPOINTS	
kwcoco.coco_schema. KEYPOINTS	
kwcoco.coco_schema. ORIG_COCO_POLYGON	
kwcoco.coco_schema. POLYGON	
kwcoco.coco_schema. RUN_LENGTH_ENCODING	
kwcoco.coco_schema. BBOX	
kwcoco.coco_schema. SEGMENTATION	
kwcoco.coco_schema. CATEGORY	
kwcoco.coco_schema. KEYPOINT_CATEGORY	
kwcoco.coco_schema. VIDEO	
kwcoco.coco_schema. CHANNELS	

`kwcoco.coco_schema.IMAGE`

`kwcoco.coco_schema.ANNOTATION`

`kwcoco.coco_schema.COCO_SCHEMA`

2.3.11 `kwcoco.coco_sql_dataset`

speed difference so we can take advantage of alchemy's expressiveness?:

Finally got a baseline implementation of an SQLite backend for COCO datasets. This mostly plugs into my existing tools (as long as only read operations are used; haven't implemented writing yet) by duck-typing the dict API.

This solves the issue of forking and then accessing nested dictionaries in the JSON-style COCO objects. (When you access the dictionary Python will increment a reference count which triggers copy-on-write for whatever memory page that data happened to live in. Non-contiguous access had the effect of excessive memory copies).

For "medium sized" datasets it's quite a bit slower. Running through a torch DataLoader with 4 workers for 10,000 images executes at a rate of 100Hz but takes 850MB of RAM. Using the duck-typed SQL backend only uses 500MB (which includes the cost of caching), but runs at 45Hz (which includes the benefit of caching).

However, once I scale up to 100,000 images I start seeing benefits. The in-memory dictionary interface chugs at 1.05HZ, and is taking more than 4GB of memory at the time I killed the process (eta was over an hour). The SQL backend ran at 45Hz and took about 3 minutes and used about 2.45GB of memory.

Without a cache, SQL runs at 30HZ and takes 400MB for 10,000 images, and for 100,000 images it gets 30Hz with 1.1GB. There is also a much larger startup time. I'm not exactly sure what it is yet, but it's probably some preprocessing I'm doing.

Using a LRU cache we get 45Hz and 1.05GB of memory, so that's a clear win. We do need to be sure to disable the cache if we ever implement write mode.

I'd like to be a bit faster on the medium sized datasets (I'd really like to avoid caching rows, which is why the speed is currently semi-reasonable), but I don't think I can do any better than this because single-row lookup time is $O(\log(N))$ for sqlite, whereas it's $O(1)$ for dictionaries. (I wish sqlite had an option to create a hash-table index for a table, but I don't think it does). I optimized as many of the dictionary operations as possible (for instance, iterating through keys, values, and items should be $O(N)$ instead of $O(N \log(N))$), but the majority of the runtime cost is in the single-row lookup time.

There are a few questions I still have if anyone has insight:

- Say I want to select a subset of K rows from a table with N entries, and I have a list of all of the rowids that I want. Is there any way to do this better than $O(K \log(N))$? I tried using a `SELECT col FROM table WHERE id IN (?, ?, ?, ?, ...)` filling in enough ? as there are rows in my subset. I'm not sure what the complexity of using a query like this is. I'm not sure what the `IN` implementation looks like. Can this be done more efficiently by with a temporary table and a `JOIN`?
- There really is no way to do $O(1)$ row lookup in sqlite right? Is there a way in PostgreSQL or some other backend sqlalchemy supports?

I found that PostgreSQL does support hash indexes: <https://www.postgresql.org/docs/13/indexes-types.html> I'm really not interested in setting up a global service though. I also found a 10-year old thread with a hash-index feature request for SQLite, which I unabashedly resurrected <http://sqlite.1065341.n5.nabble.com/Feature-request-hash-index-td23367.html>

Module Contents

Classes

<i>Category</i>	
<i>KeypointCategory</i>	
<i>Video</i>	
<i>Image</i>	
<i>Annotation</i>	
<i>SqlListProxy</i>	A view of an SQL table that behaves like a Python list
<i>SqlDictProxy</i>	Duck-types an SQL table as a dictionary of dictionaries.
<i>SqlIdGroupDictProxy</i>	Similar to <i>SqlDictProxy</i> , but maps ids to groups of other ids.
<i>CocoSqlIndex</i>	Simulates the dictionary provided by <i>kwcoco.coco_dataset.CocoIndex</i>
<i>CocoSqlDatabase</i>	Provides an API nearly identical to <i>kwcoco.CocoDatabase</i> , but uses

Functions

<i>orm_to_dict</i> (obj)	
<i>_orm_yielder</i> (query, size=300)	TODO: figure out the best way to yield, in batches or otherwise
<i>_raw_yielder</i> (result, size=300)	TODO: figure out the best way to yield, in batches or otherwise
<i>_new_proxy_cache()</i>	By returning None, we wont use item caching
<i>_handle_sql_uri</i> (uri)	Temporary function to deal with URI. Modern tools seem to use RFC 3968
<i>cached_sql_coco_view</i> (dct_db_fpath=None, sql_db_fpath=None, dset=None, force_rewrite=False)	Attempts to load a cached SQL-View dataset, only loading and converting the
<i>ensure_sql_coco_view</i> (dset, db_fpath=None, force_rewrite=False)	Create a cached on-disk SQL view of an on-disk COCO dataset.
<i>demo</i> (num=10)	
<i>assert_dsets_allclose</i> (dset1, dset2, tag1='dset1', tag2='dset2')	
<i>_benchmark_dset_readtime</i> (dset, tag='?')	Helper for understanding the time differences between backends
<i>_benchmark_dict_proxy_ops</i> (proxy)	Get insight on the efficiency of operations
<i>devcheck</i> ()	Scratch work for things that should eventually become unit or doc tests

Attributes

CocoBase

ALCHEMY_MODE_DEFAULT

TBLNAME_TO_CLASS

tblname

```
kwcoco.coco_sql_dataset.CocoBase
class kwcoco.coco_sql_dataset.Category
    Bases: CocoBase
        __tablename__ = categories
        id
        name
        alias
        supercategory
        extra

class kwcoco.coco_sql_dataset.KeypointCategory
    Bases: CocoBase
        __tablename__ = keypoint_categories
        id
        name
        alias
        supercategory
        reflection_id
        extra

class kwcoco.coco_sql_dataset.Video
    Bases: CocoBase
        __tablename__ = videos
        id
        name
        caption
        width
        height
        extra

class kwcoco.coco_sql_dataset.Image
    Bases: CocoBase
```

```
__tablename__ = images
id
name
file_name
width
height
video_id
timestamp
frame_index
channels
auxiliary
extra

class kwcoco.coco_sql_dataset.Annotation
    Bases: CocoBase

    __tablename__ = annotations
    id
    image_id
    category_id
    track_id
    segmentation
    keypoints
    bbox
    _bbox_x
    _bbox_y
    _bbox_w
    _bbox_h
    score
    weight
    prob
    iscrowd
    caption
    extra

kwcoco.coco_sql_dataset.ALCHEMY_MODE_DEFAULT = 0
kwcoco.coco_sql_dataset.TBLNAME_TO_CLASS
kwcoco.coco_sql_dataset.tblname
kwcoco.coco_sql_dataset.orm_to_dict(obj)
```

```
kwcoco.coco_sql_dataset._orm_yielder(query, size=300)
    TODO: figure out the best way to yield, in batches or otherwise
```

```
kwcoco.coco_sql_dataset._raw_yielder(result, size=300)
    TODO: figure out the best way to yield, in batches or otherwise
```

```
kwcoco.coco_sql_dataset._new_proxy_cache()
    By returning None, we wont use item caching
```

```
class kwcoco.coco_sql_dataset.SqlListProxy(proxy, session, cls)
    Bases: ubelt.NiceRepr
```

A view of an SQL table that behaves like a Python list

```
__len__(proxy)
__nice__(proxy)
__iter__(proxy)
__getitem__(proxy, index)
__contains__(proxy, item)
__setitem__(proxy, index, value)
__delitem__(proxy, index)
```

```
class kwcoco.coco_sql_dataset.SqlDictProxy(proxy, session, cls, keyattr=None, ignore_null=False)
    Bases: kwcoco.util.dict_like.DictLike
```

Duck-types an SQL table as a dictionary of dictionaries.

The key is specified by an indexed column (by default it is the *id* column). The values are dictionaries containing all data for that row.

Note: With SQLite indexes are B-Trees so lookup is O(log(N)) and not O(1) as will regular dictionaries. Iteration should still be O(N), but databases have much more overhead than Python dictionaries.

Parameters

- **session** (*Session*) – the sqlalchemy session
- **cls** (*Type*) – the declarative sqlalchemy table class
- **keyattr** – the indexed column to use as the keys
- **ignore_null** (*bool*) – if True, ignores any keys set to NULL, otherwise NULL keys are allowed.

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcoco.coco_sql_dataset import *  # NOQA
>>> import pytest
>>> sql_dset, dct_dset = demo(num=10)
>>> proxy = sql_dset.index.anns
```

```
>>> keys = list(proxy.keys())
>>> values = list(proxy.values())
>>> items = list(proxy.items())
>>> item_keys = [t[0] for t in items]
>>> item_vals = [t[1] for t in items]
>>> lut_vals = [proxy[key] for key in keys]
>>> assert item_vals == lut_vals == values
>>> assert item_keys == keys
>>> assert len(proxy) == len(keys)
```

```
>>> goodkey1 = keys[1]
>>> badkey1 = -1000000000000
>>> badkey2 = 'foobarbazbiz'
>>> badkey3 = object()
>>> assert goodkey1 in proxy
>>> assert badkey1 not in proxy
>>> assert badkey2 not in proxy
>>> assert badkey3 not in proxy
>>> with pytest.raises(KeyError):
>>>     proxy[badkey1]
>>> with pytest.raises(KeyError):
>>>     proxy[badkey2]
>>> with pytest.raises(KeyError):
>>>     proxy[badkey3]
```

```
>>> # xdoctest: +SKIP
>>> from kwcoco.coco_sql_dataset import _benchmark_dict_proxy_ops
>>> ti = _benchmark_dict_proxy_ops(proxy)
>>> print('ti.measures = {}'.format(ub.repr2(ti.measures, nl=2, align=':', precision=6)))
```

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcoco.coco_sql_dataset import * # NOQA
>>> import kwcoco
>>> # Test the variant of the SqlDictProxy where we ignore None keys
>>> # This is the case for name_to_img and file_name_to_img
>>> dct_dset = kwcoco.CocoDataset.demo('shapes1')
>>> dct_dset.add_image(name='no_file_image1')
>>> dct_dset.add_image(name='no_file_image2')
>>> dct_dset.add_image(name='no_file_image3')
>>> sql_dset = dct_dset.view_sql(memory=True)
>>> assert len(dct_dset.index.imgs) == 4
>>> assert len(dct_dset.index.file_name_to_img) == 1
>>> assert len(dct_dset.index.name_to_img) == 3
>>> assert len(sql_dset.index.imgs) == 4
>>> assert len(sql_dset.index.file_name_to_img) == 1
>>> assert len(sql_dset.index.name_to_img) == 3
```

```
>>> proxy = sql_dset.index.file_name_to_img
>>> assert len(list(proxy.keys())) == 1
>>> assert len(list(proxy.values())) == 1
```

```
>>> proxy = sql_dset.index.name_to_img
>>> assert len(list(proxy.keys())) == 3
>>> assert len(list(proxy.values())) == 3
```

```
>>> proxy = sql_dset.index.imgs
>>> assert len(list(proxy.keys())) == 4
>>> assert len(list(proxy.values())) == 4
```

`__len__(proxy)`

`__nice__(proxy)`

`__contains__(proxy, key)`

`__getitem__(proxy, key)`

`keys(proxy)`

`values(proxy)`

`items(proxy)`

`class kwcococo.coco_sql_dataset.SqlIdGroupDictProxy(proxy, session, valattr, keyattr, parent_keyattr, group_order_attr=None)`

Bases: `kwcococo.util.dict_like.DictLike`

Similar to `SqlDictProxy`, but maps ids to groups of other ids.

Simulates a dictionary that maps ids of a parent table to all ids of another table corresponding to rows where a specific column has that parent id.

The items in the group can be sorted by the `group_order_attr` if specified.

For example, imagine two tables: images with one column (`id`) and annotations with two columns (`id`, `image_id`). This class can help provide a mapping from each `image.id` to a `Set[annotation.id]` where those annotation rows have `annotation.image_id = image.id`.

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcococo.coco_sql_dataset import * # NOQA
>>> sql_dset, dct_dset = demo(num=10)
>>> proxy = sql_dset.index.gid_to_aids
```

```
>>> keys = list(proxy.keys())
>>> values = list(proxy.values())
>>> items = list(proxy.items())
>>> item_keys = [t[0] for t in items]
>>> item_vals = [t[1] for t in items]
>>> lut_vals = [proxy[key] for key in keys]
>>> assert item_vals == lut_vals == values
>>> assert item_keys == keys
>>> assert len(proxy) == len(keys)
```

```
>>> # xdoctest: +SKIP
>>> from kwcoco.coco_sql_dataset import _benchmark_dict_proxy_ops
>>> ti = _benchmark_dict_proxy_ops(proxy)
>>> print('ti.measures = {}'.format(ub.repr2(ti.measures, nl=2, align=':', precision=6)))
```

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcoco.coco_sql_dataset import * # NOQA
>>> import kwcoco
>>> # Test the group sorted variant of this by using vidid_to_gids
>>> # where the "gids" must be sorted by the image frame indexes
>>> dct_dset = kwcoco.CocoDataset.demo('vidshapes1')
>>> dct_dset.add_image(name='frame-index-order-demo1', frame_index=-30, video_id=1)
>>> dct_dset.add_image(name='frame-index-order-demo2', frame_index=10, video_id=1)
>>> dct_dset.add_image(name='frame-index-order-demo3', frame_index=3, video_id=1)
>>> dct_dset.add_video(name='empty-video1')
>>> dct_dset.add_video(name='empty-video2')
>>> dct_dset.add_video(name='empty-video3')
>>> sql_dset = dct_dset.view_sql(memory=True)
>>> orig = dct_dset.index.vidid_to_gids
>>> proxy = sql_dset.index.vidid_to_gids
>>> from kwcoco.util.util_json import indexable_allclose
>>> assert indexable_allclose(orig, dict(proxy))
>>> items = list(proxy.items())
>>> vals = list(proxy.values())
>>> keys = list(proxy.keys())
>>> assert len(keys) == len(vals)
>>> assert dict(zip(keys, vals)) == dict(items)
```

`__nice__(self)`
`__len__(proxy)`
`__getitem__(proxy, key)`
`__contains__(proxy, key)`
`keys(proxy)`
`items(proxy)`
`values(proxy)`

`class kwcoco.coco_sql_dataset.CocoSqlIndex(index)`

Bases: `object`

Simulates the dictionary provided by `kwcoco.coco_dataset.CocoIndex`

`build(index, parent)`

`kwcoco.coco_sql_dataset._handle_sql_uri(uri)`

Temporary function to deal with URI. Modern tools seem to use RFC 3968 URIs, but sqlalchemy uses RFC 1738. Attempt to gracefully handle special cases. With a better understanding of the above specs, this function may be able to be written more eloquently.

```
class kwcoco.coco_sql_dataset.CocoSqlDatabase(uri=None, tag=None, img_root=None)
Bases:      kwcoco.abstract_coco_dataset.AbstractCocoDataset,      kwcoco.coco_dataset.
MixinCocoAccessors,      kwcoco.coco_dataset.MixinCocoObjects,      kwcoco.coco_dataset.
MixinCocoStats, kwcoco.coco_dataset.MixinCocoDraw, ubelt.NiceRepr
```

Provides an API nearly identical to `kwcoco.CocoDatabase`, but uses an SQL backend data store. This makes it robust to copy-on-write memory issues that arise when forking, as discussed in¹.

Note: By default constructing an instance of the `CocoSqlDatabase` does not create a connection to the database. Use the `connect()` method to open a connection.

References

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcoco.coco_sql_dataset import *  # NOQA
>>> sql_dset, dct_dset = demo()
>>> dset1, dset2 = sql_dset, dct_dset
>>> tag1, tag2 = 'dset1', 'dset2'
>>> assert_dsets_allclose(sql_dset, dct_dset)
```

```
MEMORY_URI = sqlite:///memory:
__nice__(self)
__getstate__(self)
```

Return only the minimal info when pickling this object.

Note: This object IS pickled when the multiprocessing context is “spawn”.

This object is NOT pickled when the multiprocessing context is “fork”. In this case the user needs to be careful to create new connections in the forked subprocesses.

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcoco.coco_sql_dataset import *  # NOQA
>>> sql_dset, dct_dset = demo()
>>> # Test pickling works correctly
>>> import pickle
>>> serialized = pickle.dumps(sql_dset)
>>> assert len(serialized) < 3e4, 'should be very small'
>>> copy = pickle.loads(serialized)
>>> dset1, dset2, tag1, tag2 = sql_dset, copy, 'orig', 'copy'
>>> assert_dsets_allclose(dset1, dset2, tag1, tag2)
>>> # --- other methods of copying ---
>>> rw_copy = CocoSqlDatabase(
>>>     sql_dset.uri, img_root=sql_dset.img_root, tag=sql_dset.tag)
```

(continues on next page)

¹ <https://github.com/pytorch/pytorch/issues/13246>

(continued from previous page)

```
>>> rw_copy.connect()
>>> ro_copy = CocoSqlDatabase(
...     sql_dset.uri, img_root=sql_dset.img_root, tag=sql_dset.tag)
>>> ro_copy.connect(readonly=True)
>>> assert_dsets_allclose(dset1, ro_copy, tag1, 'ro-copy')
>>> assert_dsets_allclose(dset1, rw_copy, tag1, 'rw-copy')
```

`__setstate__(self, state)`

Reopen new readonly connections when unpickling the object.

`disconnect(self)`

Drop references to any SQL or cache objects

`connect(self, readonly=False)`

Connects this instance to the underlying database.

References

details on read only mode, some of these didnt seem to work <https://github.com/sqlalchemy/sqlalchemy/blob/master/lib/sqlalchemy/dialects/sqlite/pysqlite.py#L71> <https://github.com/pudo/dataset/issues/136>
<https://writeonly.wordpress.com/2009/07/16/simple-read-only-sqlalchemy-sessions/>

`property fpath(self)`**`delete(self)`****`populate_from(self, dset, verbose=1)`**

Copy the information in a CocoDataset into this SQL database.

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcoco.coco_sql_dataset import _benchmark_dset_readtime # NOQA
>>> import kwcoco
>>> from kwcoco.coco_sql_dataset import *
>>> dset2 = dset = kwcoco.CocoDataset.demo()
>>> dset1 = self = CocoSqlDatabase('sqlite:///memory:')
>>> self.connect()
>>> self.populate_from(dset)
>>> assert_dsets_allclose(dset1, dset2, tag1='sql', tag2='dct')
>>> ti_sql = _benchmark_dset_readtime(dset1, 'sql')
>>> ti_dct = _benchmark_dset_readtime(dset2, 'dct')
>>> print('ti_sql.rankings = {}'.format(ub.repr2(ti_sql.rankings, nl=2,
... -precision=6, align=':')))
>>> print('ti_dct.rankings = {}'.format(ub.repr2(ti_dct.rankings, nl=2,
... -precision=6, align=':')))
```

`property dataset(self)`**`property anns(self)`****`property cats(self)`****`property imgs(self)`**

```
property name_to_cat(self)

raw_table(self, table_name)
    Loads an entire SQL table as a pandas DataFrame

    Parameters table_name (str) – name of the table

    Returns DataFrame
```

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcococo.coco_sql_dataset import * # NOQA
>>> self, dset = demo()
>>> table_df = self.raw_table('annotations')
>>> print(table_df)
```

_column_lookup(self, tablename, key, rowids, default=ub.NoParam, keepid=False)
Convinience method to lookup only a single column of information

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcococo.coco_sql_dataset import * # NOQA
>>> self, dset = demo(10)
>>> tablename = 'annotations'
>>> key = 'category_id'
>>> rowids = list(self.anns.keys())[::-3]
>>> cids1 = self._column_lookup(tablename, key, rowids)
>>> cids2 = self.annots(rowids).get(key)
>>> cids3 = dset.annots(rowids).get(key)
>>> assert cids3 == cids2 == cids1
```

_all_rows_column_lookup(self, tablename, keys)
Convinience method to look up all rows from a table and only a few columns.

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcococo.coco_sql_dataset import * # NOQA
>>> self, dset = demo(10)
>>> tablename = 'annotations'
>>> keys = ['id', 'category_id']
>>> rows = self._all_rows_column_lookup(tablename, keys)
```

tabular_targets(self)
Convinience method to create an in-memory summary of basic annotation properties with minimal SQL overhead.

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcoco.coco_sql_dataset import * # NOQA
>>> self, dset = demo()
>>> targets = self.tabular_targets()
>>> print(targets.pandas())
```

property bundle_dpath(self)
property data_fpath(self)
 data_fpath is an alias of fpath
classmethod coerce(self, data)
 Create an SQL CocoDataset from the input pointer.

Example

```
import kwcoco dset = kwcoco.CocoDataset.demo('shapes8') data = dset.fpath self = CocoSqlDatabase.coerce(data)

from kwcoco.coco_sql_dataset import CocoSqlDatabase import kwcoco dset = kwcoco.CocoDataset.coerce('spacenet7.kwcoco.json')

self = CocoSqlDatabase.coerce(dset)

from kwcoco.coco_sql_dataset import CocoSqlDatabase sql_dset = CocoSqlDatabase.coerce('spacenet7.kwcoco.json')

# from kwcoco.coco_sql_dataset import CocoSqlDatabase import kwcoco sql_dset = kwcoco.CocoDataset.coerce('_spacenet7.kwcoco.view.v006.sqlite')

kwcoco.coco_sql_dataset.cached_sql_coco_view(dct_db_fpath=None, sql_db_fpath=None, dset=None, force_rewrite=False)

Attempts to load a cached SQL-View dataset, only loading and converting the json dataset if necessary.

kwcoco.coco_sql_dataset.ensure_sql_coco_view(dset, db_fpath=None, force_rewrite=False)

Create a cached on-disk SQL view of an on-disk COCO dataset.
```

Note: This function is fragile. It depends on looking at file modified timestamps to determine if it needs to write the dataset.

```
kwcoco.coco_sql_dataset.demo(num=10)

kwcoco.coco_sql_dataset.assert_dsets_allclose(dset1, dset2, tag1='dset1', tag2='dset2')

kwcoco.coco_sql_dataset._benchmark_dset_readtime(dset, tag='?')
  Helper for understanding the time differences between backends

kwcoco.coco_sql_dataset._benchmark_dict_proxy_ops(proxy)
  Get insight on the efficiency of operations

kwcoco.coco_sql_dataset.devcheck()
  Scratch work for things that should eventually become unit or doc tests

from kwcoco.coco_sql_dataset import * # NOQA self, dset = demo()
```

2.3.12 `kwcoco.compat_dataset`

A wrapper around the basic kwCOCO dataset with a pycocotools API.

We do not recommend using this API because it has some idiosyncrasies, where names can be misleading and APIs are not always clear / efficient: e.g.

- (1) `catToImgs` returns integer image ids but `imgToAnns` returns annotation dictionaries.
- (2) `showAnns` takes a dictionary list as an argument instead of an integer list

The cool thing is that this extends the kwCOCO API so you can drop this for compatibility with the old API, but you still get access to all of the kwCOCO API including dynamic addition / removal of categories / annotations / images.

Module Contents

Classes

`COCO`

A wrapper around the basic kwCOCO dataset with a pycocotools API.

class `kwcoco.compat_dataset.COCO(annotation_file=None, **kw)`
Bases: `kwcoco.coco_dataset.CocoDataset`

A wrapper around the basic kwCOCO dataset with a pycocotools API.

Example

```
>>> from kwcoco.compat_dataset import * # NOQA
>>> import kwcoco
>>> basic = kwcoco.CocoDataset.demo('shapes8')
>>> self = COCO(basic.dataset)
>>> self.info()
>>> print('self.imgToAnns = {!r}'.format(self.imgToAnns[1]))
>>> print('self.catToImgs = {!r}'.format(self.catToImgs))
```

`createIndex(self)`

`info(self)`

Print information about the annotation file. :return:

`property imgToAnns(self)`

`property catToImgs(self)`

unlike the name implies, this actually goes from category to image ids Name retained for backward compatibility

`getAnnIds(self, imgIds=[], catIds=[], areaRng=[], iscrowd=None)`

Get ann ids that satisfy given filter conditions. default skips that filter :param imgIds (int array) : get anns for given imgs

catIds (int array) : get anns for given cats areaRng (float array) : get anns for given area range
(e.g. [0 inf]) iscrowd (boolean) : get anns for given crowd label (False or True)

Returns ids (int array) : integer array of ann ids

Example

```
>>> from kwcoco.compat_dataset import * # NOQA
>>> import kwcoco
>>> self = COCO(kwcoco.CocoDataset.demo('shapes8').dataset)
>>> self.getAnnIds()
>>> self.getAnnIds(imgIds=1)
>>> self.getAnnIds(imgIds=[1])
>>> self.getAnnIds(catIds=[3])
```

getCatIds(*self*, *catNms*=[], *supNms*=[], *catIds*=[])

filtering parameters. default skips that filter. :param catNms (str array) : get cats for given cat names :param supNms (str array) : get cats for given supercategory names :param catIds (int array) : get cats for given cat ids :return: ids (int array) : integer array of cat ids

Example

```
>>> from kwcoco.compat_dataset import * # NOQA
>>> import kwcoco
>>> self = COCO(kwcoco.CocoDataset.demo('shapes8').dataset)
>>> self.getCatIds()
>>> self.getCatIds(catNms=['superstar'])
>>> self.getCatIds(supNms=['raster'])
>>> self.getCatIds(catIds=[3])
```

getImgIds(*self*, *imgIds*=[], *catIds*=[])

Get img ids that satisfy given filter conditions. :param imgIds (int array) : get imgs for given ids :param catIds (int array) : get imgs with all given cats :return: ids (int array) : integer array of img ids

Example

```
>>> from kwcoco.compat_dataset import * # NOQA
>>> import kwcoco
>>> self = COCO(kwcoco.CocoDataset.demo('shapes8').dataset)
>>> self.getImgIds(imgIds=[1, 2])
>>> self.getImgIds(catIds=[3, 6, 7])
>>> self.getImgIds(catIds=[3, 6, 7], imgIds=[1, 2])
```

loadAnns(*self*, *ids*=[])

Load anns with the specified ids. :param ids (int array) : integer ids specifying anns :return: anns (object array) : loaded ann objects

loadCats(*self*, *ids*=[])

Load cats with the specified ids. :param ids (int array) : integer ids specifying cats :return: cats (object array) : loaded cat objects

loadImgs(*self*, *ids*=[])

Load anns with the specified ids. :param ids (int array) : integer ids specifying img :return: imgs (object array) : loaded img objects

showAnns(*self*, *anns*, *draw_bbox=False*)

Display the specified annotations. :param anns (array of object): annotations to display :return: None

loadRes(*self, resFile*)

Load result file and return a result api object. :param resFile (str) : file name of result file :return: res (obj) : result api object

download(*self, tarDir=None, imgIds=[]*)

Download COCO images from mscoco.org server. :param tarDir (str): COCO results directory name
imgIds (list): images to be downloaded

Returns**loadNumpyAnnotations**(*self, data*)

Convert result data from a numpy array [Nx7] where each row contains {imageID,x1,y1,w,h,score,class} :param data (numpy.ndarray) :return: annotations (python nested list)

annToRLE(*self, ann*)

Convert annotation which can be polygons, uncompressed RLE to RLE. :return: binary mask (numpy 2D array)

Note:

- This requires the C-extensions for kwimage to be installed due to the need to interface with the bytes RLE format.
-

Example

```
>>> from kwcoco.compat_dataset import * # NOQA
>>> import kwcoco
>>> self = COCO(kwcoco.CocoDataset.demo('shapes8').dataset)
>>> try:
>>>     rle = self.annToRLE(self.anns[1])
>>> except NotImplementedError:
>>>     import pytest
>>>     pytest.skip('missing kwimage c-extensions')
>>> else:
>>>     assert len(rle['counts']) > 2
>>> # xdoctest: +REQUIRES(module:pycocotools)
>>> self.conform(legacy=True)
>>> orig = self._aspycoco().annToRLE(self.anns[1])
```

annToMask(*self, ann*)

Convert annotation which can be polygons, uncompressed RLE, or RLE to binary mask.

Returns binary mask (numpy 2D array)

Note: The mask is returned as a fortran (F-style) array with the same dimensions as the parent image.

2.3.13 kwcoco.kpf

WIP:

Conversions to and from KPF format.

Module Contents

Functions

<code>coco_to_kpf(coco_dset)</code>	import kwcoco
<code>demo()</code>	

```
kwcoco.kpf.coco_to_kpf(coco_dset)
    import kwcoco coco_dset = kwcoco.CocoDataset.demo('shapes8')
kwcoco.kpf.demo()
```

2.3.14 kwcoco.kw18

A helper for converting COCO to / from KW18 format.

KW18 File Format <https://docs.google.com/spreadsheets/d/1DFCwoTKnDv8qfy3raM7QXtir2Fjfj9j8-z8px5Bu0q8/edit#gid=10>

The kw18.trk files are text files, space delimited; each row is one frame of one track and all rows have the same number of columns. The fields are:

01) track_ID	: identifies the track
02) num_frames:	number of frames in the track
03) frame_id	: frame number for this track sample
04) loc_x	: X-coordinate of the track (image/ground coords)
05) loc_y	: Y-coordinate of the track (image/ground coords)
06) vel_x	: X-velocity of the object (image/ground coords)
07) vel_y	: Y-velocity of the object (image/ground coords)
08) obj_loc_x	: X-coordinate of the object (image coords)
09) obj_loc_y	: Y-coordinate of the object (image coords)
10) bbox_min_x	: minimum X-coordinate of bounding box (image coords)
11) bbox_min_y	: minimum Y-coordinate of bounding box (image coords)
12) bbox_max_x	: maximum X-coordinate of bounding box (image coords)
13) bbox_max_y	: maximum Y-coordinate of bounding box (image coords)
14) area	: area of object (pixels)
15) world_loc_x	: X-coordinate of object in world
16) world_loc_y	: Y-coordinate of object in world
17) world_loc_z	: Z-coordiante of object in world
18) timestamp	: timestamp of frame (frames)

For the location **and** velocity of **object** centroids, use fields 4-7.

Bounding box **is** specified using coordinates of the top-left **and** bottom right corners. Fields 15-17 may be ignored.

The kw19.trk **and** kw20.trk files, when present, add the following field(s):

(continues on next page)

(continued from previous page)

- 19) object class: estimated **class of** the **object**, either 1 (person), 2 (vehicle), **or** 3 (other).
- 20) Activity ID -- refer to activities.txt **for** index **and** list of activities.

Module Contents

Classes

KW18	A DataFrame like object that stores KW18 column data
------	--

Functions

_ensure_kw18_column_order(df)	Ensure expected kw18 columns exist and are in the correct order.
-------------------------------	--

class kwcoco.kw18.KW18(*data*)
Bases: kwarray.DataFrameArray
A DataFrame like object that stores KW18 column data

Example

```
>>> import kwcoco
>>> from kwcoco.kw18 import KW18
>>> coco_dset = kwcoco.CocoDataset.demo('shapes')
>>> kw18_dset = KW18.from_coco(coco_dset)
>>> print(kw18_dset.pandas())
```

```
DEFAULT_COLUMNS = ['track_id', 'track_length', 'frame_number',
'tracking_plane_loc_x', 'tracking_plane_loc_y',...
@classmethod def demo(KW18)
@classmethod def from_coco(KW18, coco_dset)
to_coco(self, image_paths=None, video_name=None)
Translates a kw18 files to a CocoDataset.
```

Note: kw18 does not contain complete information, and as such the returned coco dataset may need to be augmented.

Parameters

- **image_paths** (*Dict[int, str]*, *default=None*) – if specified, maps frame numbers to image file paths.
- **video_name** (*str*, *default=None*) – if specified records the name of the video this kw18 belongs to

Todo:

- [X] allow kwargs to specify path to frames / videos
-

Example

```
>>> from kwcoco.kw18 import KW18
>>> from os.path import join
>>> import ubelt as ub
>>> import kwimage
>>> # Prep test data - autogen a demo kw18 and write it to disk
>>> dpath = ub.ensure_app_cache_dir('kwcoco/kw18')
>>> kw18_fpath = join(dpath, 'test.kw18')
>>> KW18.demo().dump(kw18_fpath)
>>> #
>>> # Load the kw18 file
>>> self = KW18.load(kw18_fpath)
>>> # Pretend that these image correspond to kw18 frame numbers
>>> frame_names = [kwimage.grab_test_image_fpath(k) for k in kwimage.grab_test_
...image.keys()]
>>> frame_ids = sorted(set(self['frame_number']))
>>> image_paths = dict(zip(frame_ids, frame_names))
>>> #
>>> # Convert the kw18 to kw coco and specify paths to images
>>> coco_dset = self.to_coco(image_paths=image_paths, video_name='dummy.mp4')
>>> #
>>> # Now we can draw images
>>> canvas = coco_dset.draw_image(1)
>>> # xdoctest: +REQUIRES(--draw)
>>> kwimage.imwrite('foo.jpg', canvas)
>>> # Draw all images
>>> for gid in coco_dset.imgs.keys():
>>>     canvas = coco_dset.draw_image(gid)
>>>     fpath = join(dpath, 'gid_{}.jpg'.format(gid))
>>>     print('write fpath = {!r}'.format(fpath))
>>>     kwimage.imwrite(fpath, canvas)
```

classmethod `load(KW18, file)`

Example

```
>>> import kwcoco
>>> from kwcoco.kw18 import KW18
>>> coco_dset = kwcoco.CocoDataset.demo('shapes')
>>> kw18_dset = KW18.from_coco(coco_dset)
>>> print(kw18_dset.pandas())
```

classmethod `loads(KW18, text)`

Example

```
>>> self = KW18.demo()  
>>> text = self.dumps()  
>>> self2 = KW18.loads(text)  
>>> empty = KW18.loads('')
```

dump(self, file)

dumps(self)

Example

```
>>> self = KW18.demo()  
>>> text = self.dumps()  
>>> print(text)
```

`kwcoco.kw18._ensure_kw18_column_order(df)`

Ensure expected kw18 columns exist and are in the correct order.

Example

```
>>> import pandas as pd  
>>> df = pd.DataFrame(columns=KW18.DEFAULT_COLUMNS[0:18])  
>>> _ensure_kw18_column_order(df)  
>>> df = pd.DataFrame(columns=KW18.DEFAULT_COLUMNS[0:19])  
>>> _ensure_kw18_column_order(df)  
>>> df = pd.DataFrame(columns=KW18.DEFAULT_COLUMNS[0:18] + KW18.DEFAULT_  
+ COLUMNS[20:21])  
>>> assert np.all(_ensure_kw18_column_order(df).columns == df.columns)
```

2.4 Package Contents

2.4.1 Classes

<code>AbstractCocoDataset</code>	This is a common base for all variants of the Coco Dataset
<code>CategoryTree</code>	Wrapper that maintains flat or hierarchical category information.
<code>CocoDataset</code>	The main coco dataset class with a json dataset backend.
<code>ChannelSpec</code>	Parse and extract information about network input channel specs for
<code>FusedChannelSpec</code>	A specific type of channel spec with only one early fused stream.

`class kwcoco.AbstractCocoDataset`

Bases: `abc.ABC`

This is a common base for all variants of the Coco Dataset

At the time of writing there is kwcoco.CocoDataset (which is the dictionary-based backend), and the kwcoco.coco_sql_dataset.CocoSqlDataset, which is experimental.

```
class kwcoco.CategoryTree(graph=None, checks=True)
```

Bases: `ubelt.NiceRepr`

Wrapper that maintains flat or hierarchical category information.

Helps compute softmaxes and probabilities for tree-based categories where a directed edge (A, B) represents that A is a superclass of B.

Note: There are three basic properties that this object maintains:

`node`:

Alphanumeric string names that should be generally descriptive. Using spaces `and` special characters `in` these names `is` discouraged, but can be done. This `is` the COCO category `"name"` attribute. For categories this may be denoted `as` (`name`, `node`, `cname`, `catname`).

`id`:

The integer `id` of a category should ideally remain consistent. These are often given by a dataset (e.g. a COCO dataset). This `is` the COCO category `"id"` attribute. For categories this `is` often denoted `as` (`id`, `cid`).

`index`:

Contiguous zero-based indices that indexes the `list` of categories. These should be used `for` the fastest access `in` backend computation tasks. Typically corresponds to the ordering of the channels `in` the final linear layer `in` an associated model. For categories this `is` often denoted `as` (`index`, `cidx`, `idx`, `or` `cx`).

Variables

- `idx_to_node` (`List[str]`) – a list of class names. Implicitly maps from index to category name.
- `id_to_node` (`Dict[int, str]`) – maps integer ids to category names
- `node_to_id` (`Dict[str, int]`) – maps category names to ids
- `node_to_idx` (`Dict[str, int]`) – maps category names to indexes
- `graph` (`networkx.Graph`) – a Graph that stores any hierarchy information. For standard mutually exclusive classes, this graph is edgeless. Nodes in this graph can maintain category attributes / properties.
- `idx_groups` (`List[List[int]]`) – groups of category indices that share the same parent category.

Example

```
>>> from kwCOCO.category_tree import *
>>> graph = nx.from_dict_of_lists({
...     'background': [],
...     'foreground': ['animal'],
...     'animal': ['mammal', 'fish', 'insect', 'reptile'],
...     'mammal': ['dog', 'cat', 'human', 'zebra'],
...     'zebra': ['grevys', 'plains'],
...     'grevys': ['fred'],
...     'dog': ['boxer', 'beagle', 'golden'],
...     'cat': ['maine coon', 'persian', 'sphynx'],
...     'reptile': ['bearded dragon', 't-rex'],
... }, nx.DiGraph)
>>> self = CategoryTree(graph)
>>> print(self)
<CategoryTree(nNodes=22, maxDepth=6, maxBreadth=4...)>
```

Example

```
>>> # The coerce classmethod is the easiest way to create an instance
>>> import kwCOCO
>>> kwCOCO.CategoryTree.coerce(['a', 'b', 'c'])
<CategoryTree...nNodes=3, nodes='a', 'b', 'c'...
>>> kwCOCO.CategoryTree.coerce(4)
<CategoryTree...nNodes=4, nodes='class_1', 'class_2', 'class_3', ...
>>> kwCOCO.CategoryTree.coerce(4)
```

`copy(self)`
`classmethod from_mutex(cls, nodes, bg_hack=True)`

Parameters `nodes` (`List[str]`) – or a list of class names (in which case they will all be assumed to be mutually exclusive)

Example

```
>>> print(CategoryTree.from_mutex(['a', 'b', 'c']))
<CategoryTree(nNodes=3, ...)>
```

`classmethod from_json(cls, state)`

Parameters `state` (`Dict`) – see `__getstate__` / `__json__` for details

`classmethod from_coco(cls, categories)`

Create a CategoryTree object from coco categories

Parameters `List[Dict]` – list of coco-style categories

`classmethod coerce(cls, data, **kw)`

Attempt to coerce data as a CategoryTree object.

This is primarily useful for when the software stack depends on categories being represent

This will work if the input data is a specially formatted json dict, a list of mutually exclusive classes, or if it is already a CategoryTree. Otherwise an error will be thrown.

Parameters

- **data** (*object*) – a known representation of a category tree.
- ****kwargs** – input type specific arguments

Returns self

Return type *CategoryTree*

Raises

- **TypeError** – if the input format is unknown –
- **ValueError** – if kwargs are not compatible with the input format –

Example

```
>>> import kwcoco
>>> classes1 = kwcoco.CategoryTree.coerce(3) # integer
>>> classes2 = kwcoco.CategoryTree.coerce(classes1.__json__()) # graph dict
>>> classes3 = kwcoco.CategoryTree.coerce(['class_1', 'class_2', 'class_3']) # list
>>> classes4 = kwcoco.CategoryTree.coerce(classes1.graph) # nx Graph
>>> classes5 = kwcoco.CategoryTree.coerce(classes1) # cls
>>> # xdoctest: +REQUIRES(module:nd sampler)
>>> import nd sampler
>>> classes6 = nd sampler.CategoryTree.coerce(3)
>>> classes7 = nd sampler.CategoryTree.coerce(classes1)
>>> classes8 = kwcoco.CategoryTree.coerce(classes6)
```

classmethod demo(*cls*, *key='coco'*, ***kwargs*)

Parameters key (*str*) – specify which demo dataset to use. Can be ‘coco’ (which uses the default coco demo data). Can be ‘btree’ which creates a binary tree and accepts kwargs ‘r’ and ‘h’ for branching-factor and height. Can be ‘btree2’, which is the same as btree but returns strings

CommandLine

```
xdoctest -m ~/code/kwcoco/kwcoco/category_tree.py CategoryTree.demo
```

Example

```
>>> from kwcoco.category_tree import *
>>> self = CategoryTree.demo()
>>> print('self = {}'.format(self))
self = <CategoryTree(nNodes=10, maxDepth=2, maxBreadth=4...)>
```

to_coco(*self*)

Converts to a coco-style data structure

Yields *Dict* – coco category dictionaries

`id_to_idx(self)`

Example

```
>>> import kwcoco
>>> self = kwcoco.CategoryTree.demo()
>>> self.id_to_idx[1]
```

`idx_to_id(self)`

Example

```
>>> import kwcoco
>>> self = kwcoco.CategoryTree.demo()
>>> self.idx_to_id[0]
```

`idx_to_ancestor_idxs(self, include_self=True)`

Mapping from a class index to its ancestors

Parameters `include_self (bool, default=True)` – if True includes each node as its own ancestor.

`idx_to_descendants_idxs(self, include_self=False)`

Mapping from a class index to its descendants (including itself)

Parameters `include_self (bool, default=False)` – if True includes each node as its own descendant.

`idx_pairwise_distance(self)`

Get a matrix encoding the distance from one class to another.

Distances

- from parents to children are positive (descendants),
- from children to parents are negative (ancestors),
- between unreachable nodes (wrt to forward and reverse graph) are nan.

`__len__(self)`

`__iter__(self)`

`__getitem__(self, index)`

`__contains__(self, node)`

`__json__(self)`

Example

```
>>> import pickle
>>> self = CategoryTree.demo()
>>> print('self = {!r}'.format(self.__json__()))
```

__getstate__(self)
Serializes information in this class

Example

```
>>> from kwcoco.category_tree import *
>>> import pickle
>>> self = CategoryTree.demo()
>>> state = self.__getstate__()
>>> serialization = pickle.dumps(self)
>>> recon = pickle.loads(serialization)
>>> assert recon.__json__() == self.__json__()
```

__setstate__(self, state)
_nice__(self)
is_mutex(self)
Returns True if all categories are mutually exclusive (i.e. flat)
If true, then the classes may be represented as a simple list of class names without any loss of information, otherwise the underlying category graph is necessary to preserve all knowledge.

Todo:

- [] what happens when we have a dummy root?

property num_classes(self)
property class_names(self)
property category_names(self)
property cats(self)
Returns a mapping from category names to category attributes.
If this category tree was constructed from a coco-dataset, then this will contain the coco category attributes.
Returns Dict[str, Dict[str, object]]

Example

```
>>> from kwcoco.category_tree import *
>>> self = CategoryTree.demo()
>>> print('self.cats = {!r}'.format(self.cats))
```

index(self, node)

Return the index that corresponds to the category name

_build_index(self)

construct lookup tables

show(self)

forest_str(self)

normalize(self)

Applies a normalization scheme to the categories.

Note: this may break other tasks that depend on exact category names.

Returns CategoryTree

Example

```
>>> from kwcoco.category_tree import * # NOQA
>>> import kwcoco
>>> orig = kwcoco.CategoryTree.demo('animals_v1')
>>> self = kwcoco.CategoryTree(nx.relabel_nodes(orig.graph, str.upper))
>>> norm = self.normalize()
```

class kwcoco.CocoDataset(data=None, tag=None, bundle_dpath=None, img_root=None, fname=None, autobuild=True)
Bases: *kwcoco.abstract_coco_dataset.AbstractCocoDataset, MixinCocoAddRemove, MixinCocoStats, MixinCocoObjects, MixinCocoDraw, MixinCocoAccessors, MixinCocoExtras, MixinCocoIndex, MixinCocoDepricate, ubelt.NiceRepr*

The main coco dataset class with a json dataset backend.

Variables

- **dataset** (*Dict*) – raw json data structure. This is the base dictionary that contains {‘annotations’: List, ‘images’: List, ‘categories’: List}
- **index** (*CocoIndex*) – an efficient lookup index into the coco data structure. The index defines its own attributes like `anns`, `cats`, `imgs`, `gid_to_aids`, `file_name_to_img`, etc. See `CocoIndex` for more details on which attributes are available.
- **fpath** (*PathLike* / *None*) – if known, this stores the filepath the dataset was loaded from
- **tag** (*str*) – A tag indicating the name of the dataset.
- **bundle_dpath** (*PathLike* / *None*) – If known, this is the root path that all image file names are relative to. This can also be manually overwritten by the user.
- **hashid** (*str* / *None*) – If computed, this will be a hash uniquely identifying the dataset. To ensure this is computed see `kwcoco.coco_dataset.MixinCocoExtras._build_hashid()`.

References

<http://cocodataset.org/#format> <http://cocodataset.org/#download>

CommandLine

```
python -m kwcoco.coco_dataset CocoDataset --show
```

Example

```
>>> from kwcoco.coco_dataset import demo_coco_data
>>> import kwcoco
>>> import ubelt as ub
>>> # Returns a coco json structure
>>> dataset = demo_coco_data()
>>> # Pass the coco json structure to the API
>>> self = kwcoco.CocoDataset(dataset, tag='demo')
>>> # Now you can access the data using the index and helper methods
>>> #
>>> # Start by looking up an image by it's COCO id.
>>> image_id = 1
>>> img = self.index.imgs[image_id]
>>> print(ub.repr2(img, nl=1, sort=1))
{
    'file_name': 'astro.png',
    'id': 1,
    'url': 'https://i.imgur.com/KXhKM72.png',
}
>>> #
>>> # Use the (gid_to_aids) index to lookup annotations in the iamge
>>> annotation_id = sorted(self.index.gid_to_aids[image_id])[0]
>>> ann = self.index.anns[annotation_id]
>>> print(ub.repr2(ub.dict_diff(ann, {'segmentation'}), nl=1))
{
    'bbox': [10, 10, 360, 490],
    'category_id': 1,
    'id': 1,
    'image_id': 1,
    'keypoints': [247, 101, 2, 202, 100, 2],
}
>>> #
>>> # Use annotation category id to look up that information
>>> category_id = ann['category_id']
>>> cat = self.index.cats[category_id]
>>> print('cat = {}'.format(ub.repr2(cat, nl=1, sort=1)))
cat = {
    'id': 1,
    'name': 'astronaut',
    'supercategory': 'human',
}
>>> #
```

(continues on next page)

(continued from previous page)

```
>>> # Now play with some helper functions, like extended statistics
>>> extended_stats = self.extended_stats()
>>> print('extended_stats = {}'.format(ub.repr2(extended_stats, nl=1, precision=2, ↵
    ↵sort=1)))
extended_stats = {
    'annots_per_img': {'mean': 3.67, 'std': 3.86, 'min': 0.00, 'max': 9.00, 'nMin': ↵
        ↵1, 'nMax': 1, 'shape': (3,)},
    'imgs_per_cat': {'mean': 0.88, 'std': 0.60, 'min': 0.00, 'max': 2.00, 'nMin': 2, ↵
        ↵'nMax': 1, 'shape': (8,)},
    'cats_per_img': {'mean': 2.33, 'std': 2.05, 'min': 0.00, 'max': 5.00, 'nMin': 1, ↵
        ↵'nMax': 1, 'shape': (3,)},
    'annots_per_cat': {'mean': 1.38, 'std': 1.49, 'min': 0.00, 'max': 5.00, 'nMin': ↵
        ↵2, 'nMax': 1, 'shape': (8,)},
    'imgs_per_video': {'empty_list': True},
}
>>> # You can "draw" a raster of the annotated image with cv2
>>> canvas = self.draw_image(2)
>>> # Or if you have matplotlib you can "show" the image with mpl objects
>>> # xdoctest: +REQUIRES(--show)
>>> from matplotlib import pyplot as plt
>>> fig = plt.figure()
>>> ax1 = fig.add_subplot(1, 2, 1)
>>> self.show_image(gid=2)
>>> ax2 = fig.add_subplot(1, 2, 2)
>>> ax2.imshow(canvas)
>>> ax1.set_title('show with matplotlib')
>>> ax2.set_title('draw with cv2')
>>> plt.show()
```

property fpath(self)

In the future we will deprecate img_root for bundle_dpath

_infer_dirs(self)**classmethod from_data(CocoDataset, data, bundle_dpath=None, img_root=None)**

Constructor from a json dictionary

classmethod from_image_paths(CocoDataset, gpaths, bundle_dpath=None, img_root=None)

Constructor from a list of images paths.

This is a convinience method.

Parameters **gpaths** (*List[str]*) – list of image paths**Example**

```
>>> coco_dset = CocoDataset.from_image_paths(['a.png', 'b.png'])
>>> assert coco_dset.n_images == 2
```

classmethod from_coco_paths(CocoDataset, fpaths, max_workers=0, verbose=1, mode='thread', union='try')

Constructor from multiple coco file paths.

Loads multiple coco datasets and unions the result

Note: if the union operation fails, the list of individually loaded files is returned instead.

Parameters

- **fpPaths** (*List[str]*) – list of paths to multiple coco files to be loaded and unioned.
- **max_workers** (*int, default=0*) – number of worker threads / processes
- **verbose** (*int*) – verbosity level
- **mode** (*str*) – thread, process, or serial
- **union** (*str | bool, default='try'*) – If True, unions the result datasets after loading. If False, just returns the result list. If ‘try’, then try to preform the union, but return the result list if it fails.

copy(*self*)

Deep copies this object

Example

```
>>> from kwcoco.coco_dataset import *
>>> self = CocoDataset.demo()
>>> new = self.copy()
>>> assert new.imgs[1] is new.dataset['images'][0]
>>> assert new.imgs[1] == self.dataset['images'][0]
>>> assert new.imgs[1] is not self.dataset['images'][0]
```

__nice__(*self*)

dumps(*self, indent=None, newlines=False*)

Writes the dataset out to the json format

Parameters **newlines** (*bool*) – if True, each annotation, image, category gets its own line

Note:

Using newlines=True is similar to: print(ub.repr2(dset.dataset, nl=2, trailsep=False)) However, the above may not output valid json if it contains ndarrays.

Example

```
>>> from kwcoco.coco_dataset import *
>>> import json
>>> self = CocoDataset.demo()
>>> text = self.dumps(newlines=True)
>>> print(text)
>>> self2 = CocoDataset(json.loads(text), tag='demo2')
>>> assert self2.dataset == self.dataset
>>> assert self2.dataset is not self.dataset
```

```
>>> text = self.dumps(newlines=True)
>>> print(text)
>>> self2 = CocoDataset(json.loads(text), tag='demo2')
>>> assert self2.dataset == self.dataset
>>> assert self2.dataset is not self.dataset
```

dump(self, file, indent=None, newlines=False)

Writes the dataset out to the json format

Parameters

- **file (PathLike | FileLike)** – Where to write the data. Can either be a path to a file or an open file pointer / stream.
- **newlines (bool)** – if True, each annotation, image, category gets its own line.

Example

```
>>> import tempfile
>>> from kwcoco.coco_dataset import *
>>> self = CocoDataset.demo()
>>> file = tempfile.NamedTemporaryFile('w')
>>> self.dump(file)
>>> file.seek(0)
>>> text = open(file.name, 'r').read()
>>> print(text)
>>> file.seek(0)
>>> dataset = json.load(open(file.name, 'r'))
>>> self2 = CocoDataset(dataset, tag='demo2')
>>> assert self2.dataset == self.dataset
>>> assert self2.dataset is not self.dataset
```

```
>>> file = tempfile.NamedTemporaryFile('w')
>>> self.dump(file, newlines=True)
>>> file.seek(0)
>>> text = open(file.name, 'r').read()
>>> print(text)
>>> file.seek(0)
>>> dataset = json.load(open(file.name, 'r'))
>>> self2 = CocoDataset(dataset, tag='demo2')
>>> assert self2.dataset == self.dataset
>>> assert self2.dataset is not self.dataset
```

_check_json_serializable(self, verbose=1)

Debug which part of a coco dataset might not be json serializable

_check_integrity(self)

perform all checks

_check_index(self)

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> self._check_index()
>>> # Force a failure
>>> self.index.anns.pop(1)
>>> self.index.anns.pop(2)
>>> import pytest
>>> with pytest.raises(AssertionError):
>>>     self._check_index()
```

`_check_pointers(self, verbose=1)`

Check that all category and image ids referenced by annotations exist

`_build_index(self)`

`union(*others, disjoint_tracks=True, **kwargs)`

Merges multiple `CocoDataset` items into one. Names and associations are retained, but ids may be different.

Parameters

- `*others` – a series of CocoDatasets that we will merge. Note, if called as an instance method, the “self” instance will be the first item in the “others” list. But if called like a classmethod, “others” will be empty by default.
- `disjoint_tracks (bool, default=True)` – if True, we will assume track-ids are disjoint and if two datasets share the same track-id, we will disambiguate them. Otherwise they will be copied over as-is.
- `**kwargs` – constructor options for the new merged CocoDataset

`Returns` a new merged coco dataset

`Return type` `CocoDataset`

CommandLine

```
xdoctest -m kwcoco.coco_dataset CocoDataset.union
```

Example

```
>>> # Test union works with different keypoint categories
>>> dset1 = CocoDataset.demo('shapes1')
>>> dset2 = CocoDataset.demo('shapes2')
>>> dset1.remove_keypoint_categories(['bot_tip', 'mid_tip', 'right_eye'])
>>> dset2.remove_keypoint_categories(['top_tip', 'left_eye'])
>>> dset_12a = CocoDataset.union(dset1, dset2)
>>> dset_12b = dset1.union(dset2)
>>> dset_21 = dset2.union(dset1)
>>> def add_hist(h1, h2):
>>>     return {k: h1.get(k, 0) + h2.get(k, 0) for k in set(h1) | set(h2)}
>>> kpfreq1 = dset1.keypoint_annotation_frequency()
```

(continues on next page)

(continued from previous page)

```
>>> kpfreq2 = dset2.keypoint_annotation_frequency()
>>> kpfreq_want = add_hist(kpfreq1, kpfreq2)
>>> kpfreq_got1 = dset_12a.keypoint_annotation_frequency()
>>> kpfreq_got2 = dset_12b.keypoint_annotation_frequency()
>>> assert kpfreq_want == kpfreq_got1
>>> assert kpfreq_want == kpfreq_got2
```

```
>>> # Test disjoint gid datasets
>>> import kwCOCO
>>> dset1 = kwCOCO.CocoDataset.demo('shapes3')
>>> for new_gid, img in enumerate(dset1.dataset['images'], start=10):
>>>     for aid in dset1.gid_to_aids[img['id']]:
>>>         dset1.anns[aid]['image_id'] = new_gid
>>>     img['id'] = new_gid
>>> dset1.index.clear()
>>> dset1._build_index()
>>> # -----
>>> dset2 = kwCOCO.CocoDataset.demo('shapes2')
>>> for new_gid, img in enumerate(dset2.dataset['images'], start=100):
>>>     for aid in dset2.gid_to_aids[img['id']]:
>>>         dset2.anns[aid]['image_id'] = new_gid
>>>     img['id'] = new_gid
>>> dset1.index.clear()
>>> dset2._build_index()
>>> others = [dset1, dset2]
>>> merged = kwCOCO.CocoDataset.union(*others)
>>> print('merged = {!r}'.format(merged))
>>> print('merged imgs = {}'.format(ub.repr2(merged.imgs, nl=1)))
>>> assert set(merged.imgs) & set([10, 11, 12, 100, 101]) == set(merged.imgs)
```

```
>>> # Test data is not preserved
>>> dset2 = kwCOCO.CocoDataset.demo('shapes2')
>>> dset1 = kwCOCO.CocoDataset.demo('shapes3')
>>> others = (dset1, dset2)
>>> cls = self = kwCOCO.CocoDataset
>>> merged = cls.union(*others)
>>> print('merged = {!r}'.format(merged))
>>> print('merged imgs = {}'.format(ub.repr2(merged.imgs, nl=1)))
>>> assert set(merged.imgs) & set([1, 2, 3, 4, 5]) == set(merged.imgs)
```

```
>>> # Test track-ids are mapped correctly
>>> dset1 = kwCOCO.CocoDataset.demo('vidshapes1')
>>> dset2 = kwCOCO.CocoDataset.demo('vidshapes2')
>>> dset3 = kwCOCO.CocoDataset.demo('vidshapes3')
>>> others = (dset1, dset2, dset3)
>>> for dset in others:
>>>     [a.pop('segmentation', None) for a in dset.index.anns.values()]
>>>     [a.pop('keypoints', None) for a in dset.index.anns.values()]
>>> cls = self = kwCOCO.CocoDataset
>>> merged = cls.union(*others, disjoint_tracks=1)
>>> print('dset1.anns = {}'.format(ub.repr2(dset1.anns, nl=1)))
```

(continues on next page)

(continued from previous page)

```
>>> print('dset2.anns = {}'.format(ub.repr2(dset2.anns, nl=1)))
>>> print('dset3.anns = {}'.format(ub.repr2(dset3.anns, nl=1)))
>>> print('merged.anns = {}'.format(ub.repr2(merged.anns, nl=1)))
```

Example

```
>>> import kwcoco
>>> # Test empty union
>>> empty_union = kwcoco.CocoDataset.union()
>>> assert len(empty_union.index.imgs) == 0
```

Todo:

- [] are supercategories broken?
- [] reuse image ids where possible
- [] reuse annotation / category ids where possible
- [X] handle case where no inputs are given
- [x] disambiguate track-ids
- [x] disambiguate video-ids

`subset(self, gids, copy=False, autobuild=True)`

Return a subset of the larger coco dataset by specifying which images to port. All annotations in those images will be taken.

Parameters

- **gids** (*List[int]*) – image-ids to copy into a new dataset
- **copy** (*bool, default=False*) – if True, makes a deep copy of all nested attributes, otherwise makes a shallow copy.
- **autobuild** (*bool, default=True*) – if True will automatically build the fast lookup index.

Example

```
>>> self = CocoDataset.demo()
>>> gids = [1, 3]
>>> sub_dset = self.subset(gids)
>>> assert len(self.index.gid_to_aids) == 3
>>> assert len(sub_dset.gid_to_aids) == 2
```

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo('vidshapes2')
>>> gids = [1, 2]
>>> sub_dset = self.subset(gids, copy=True)
>>> assert len(sub_dset.index.videos) == 1
>>> assert len(self.index.videos) == 2
```

Example

```
>>> self = CocoDataset.demo()
>>> sub1 = self.subset([1])
>>> sub2 = self.subset([2])
>>> sub3 = self.subset([3])
>>> others = [sub1, sub2, sub3]
>>> rejoined = CocoDataset.union(*others)
>>> assert len(sub1.anns) == 9
>>> assert len(sub2.anns) == 2
>>> assert len(sub3.anns) == 0
>>> assert rejoined.basic_stats() == self.basic_stats()
```

view_sql(*self*, *force_rewrite=False*, *memory=False*)

Create a cached SQL interface to this dataset suitable for large scale multiprocessing use cases.

Parameters

- **force_rewrite** (*bool*, *default=False*) – if True, forces an update to any existing cache file on disk
- **memory** (*bool*, *default=False*) – if True, the database is constructed in memory.

Note: This view cache is experimental and currently depends on the timestamp of the file pointed to by *self.fpath*. In other words dont use this on in-memory datasets.

class kwcoco.ChannelSpec(*spec*, *parsed=None*)

Bases: BaseChannelSpec

Parse and extract information about network input channel specs for early or late fusion networks.

Behaves like a dictionary of FusedChannelSpec objects

Todo:

- [] Rename to something that indicates this is a collection of FusedChannelSpec? MultiChannelSpec?
-

Note: This class name and API is in flux and subject to change.

Note: The pipe ('|') character represents an early-fused input stream, and order matters (it is non-commutative).

The comma (',') character separates different inputs streams/branches for a multi-stream/branch network which will be later fused. Order does not matter

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> # Integer spec
>>> ChannelSpec.coerce(3)
<ChannelSpec(u0|u1|u2) ...>
```

```
>>> # single mode spec
>>> ChannelSpec.coerce('rgb')
<ChannelSpec(rgb) ...>
```

```
>>> # early fused input spec
>>> ChannelSpec.coerce('rgb|disparity')
<ChannelSpec(rgb|disparity) ...>
```

```
>>> # late fused input spec
>>> ChannelSpec.coerce('rgb,disparity')
<ChannelSpec(rgb,disparity) ...>
```

```
>>> # early and late fused input spec
>>> ChannelSpec.coerce('rgb|ir,disparity')
<ChannelSpec(rgb|ir,disparity) ...>
```

Example

```
>>> self = ChannelSpec('gray')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>> self = ChannelSpec('rgb')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>> self = ChannelSpec('rgb|disparity')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>> self = ChannelSpec('rgb|disparity,disparity')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>> self = ChannelSpec('rgb,disparity,flowx|flowy')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
```

Example

```
>>> specs = [
>>>     'rgb',           # and rgb input
>>>     'rgb|disparity', # rgb early fused with disparity
>>>     'rgb,disparity', # rgb early late with disparity
>>>     'rgb|ir,disparity', # rgb early fused with ir and late fused with disparity
>>>     3,               # 3 unknown channels
>>> ]
>>> for spec in specs:
>>>     print('=====')
>>>     print('spec = {!r}'.format(spec))
>>>     #
>>>     self = ChannelSpec.coerce(spec)
>>>     print('self = {!r}'.format(self))
>>>     sizes = self.sizes()
>>>     print('sizes = {!r}'.format(sizes))
>>>     print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>>     #
>>>     item = self._demo_item((1, 1), rng=0)
>>>     inputs = self.encode(item)
>>>     components = self.decode(inputs)
>>>     input_shapes = ub.map_vals(lambda x: x.shape, inputs)
>>>     component_shapes = ub.map_vals(lambda x: x.shape, components)
>>>     print('item = {}'.format(ub.repr2(item, precision=1)))
>>>     print('inputs = {}'.format(ub.repr2(inputs, precision=1)))
>>>     print('input_shapes = {}'.format(ub.repr2(input_shapes)))
>>>     print('components = {}'.format(ub.repr2(components, precision=1)))
>>>     print('component_shapes = {}'.format(ub.repr2(component_shapes, nl=1)))
```

property spec(self)

The string encodeing of this spec

Returns str

__contains__(self, key)**Example**

```
>>> 'disparity' in ChannelSpec('rgb,disparity,flowx|flowy')
True
>>> 'gray' in ChannelSpec('rgb,disparity,flowx|flowy')
False
```

property info(self)**classmethod coerce(cls, data)**

Attempt to interpret the data as a channel specification

Returns ChannelSpec

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> data = FusedChannelSpec.coerce(3)
>>> assert ChannelSpec.coerce(data).spec == 'u0|u1|u2'
>>> data = ChannelSpec.coerce(3)
>>> assert data.spec == 'u0|u1|u2'
>>> assert ChannelSpec.coerce(data).spec == 'u0|u1|u2'
>>> data = ChannelSpec.coerce('u:3')
>>> assert data.normalize().spec == 'u.0|u.1|u.2'
```

parse(self)
Build internal representation

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> self = ChannelSpec('b1|b2|b3|rgb,B:3')
>>> print(self.parse())
>>> print(self.normalize().parse())
>>> ChannelSpec('').parse()
```

Example

```
>>> base = ChannelSpec('rgb|disparity,flowx|r|flowy')
>>> other = ChannelSpec('rgb')
>>> self = base.intersection(other)
>>> assert self.numel() == 4
```

concise(self)

Example

```
>>> self = ChannelSpec('b1|b2,b3|rgb|B.0,B.1|B.2')
>>> print(self.concise().spec)
b1|b2,b3|r|g|b|B.0,B.1:3
```

normalize(self)
Replace aliases with explicit single-band-per-code specs

Returns normalized spec

Return type *ChannelSpec*

Example

```
>>> self = ChannelSpec('b1|b2,b3|rgb,B:3')
>>> normed = self.normalize()
>>> print('self = {}'.format(self))
>>> print('normed = {}'.format(normed))
self = <ChannelSpec(b1|b2,b3|rgb,B:3)>
normed = <ChannelSpec(b1|b2,b3|r|g|b,B.0|B.1|B.2)>
```

keys(*self*)

values(*self*)

items(*self*)

fuse(*self*)

Fuse all parts into an early fused channel spec

Returns FusedChannelSpec

Example

```
>>> from kwcocoo.channel_spec import * # NOQA
>>> self = ChannelSpec.coerce('b1|b2,b3|rgb,B:3')
>>> fused = self.fuse()
>>> print('self = {}'.format(self))
>>> print('fused = {}'.format(fused))
self = <ChannelSpec(b1|b2,b3|rgb,B:3)>
fused = <FusedChannelSpec(b1|b2|b3|rgb|B:3)>
```

streams(*self*)

Breaks this spec up into one spec for each early-fused input stream

Example

```
self = ChannelSpec.coerce('r|g,B1|B2,fx|fy') list(map(len, self.streams()))
```

code_list(*self*)

as_path(*self*)

Returns a string suitable for use in a path.

Note, this may no longer be a valid channel spec

difference(*self, other*)

Set difference. Remove all instances of other channels from this set of channels.

Example

```
>>> from kwcoco.channel_spec import *
>>> self = ChannelSpec('rgb|disparity,flowx|r|flowy')
>>> other = ChannelSpec('rgb')
>>> print(self.difference(other))
>>> other = ChannelSpec('flowx')
>>> print(self.difference(other))
<ChannelSpec(disparity,flowx|flowy)>
<ChannelSpec(r|g|b|disparity,r|flowy)>
```

Example

```
>>> from kwcoco.channel_spec import *
>>> self = ChannelSpec('a|b,c|d')
>>> new = self - {'a', 'b'}
>>> len(new.sizes()) == 1
>>> empty = new - 'c|d'
>>> assert empty.numel() == 0
```

intersection(self, other)

Set difference. Remove all instances of other channels from this set of channels.

Example

```
>>> from kwcoco.channel_spec import *
>>> self = ChannelSpec('rgb|disparity,flowx|r|flowy')
>>> other = ChannelSpec('rgb')
>>> new = self.intersection(other)
>>> print(new)
>>> print(new.numel())
>>> other = ChannelSpec('flowx')
>>> new = self.intersection(other)
>>> print(new)
>>> print(new.numel())
<ChannelSpec(r|g|b,r)>
4
<ChannelSpec(flowx)>
1
```

numel(self)

Total number of channels in this spec

sizes(self)

Number of dimensions for each fused stream channel

IE: The EARLY-FUSED channel sizes

Example

```
>>> self = ChannelSpec('rgb|disparity,flowx|flowy,B:10')
>>> self.normalize().concise()
>>> self.sizes()
```

`unique(self, normalize=False)`

Returns the unique channels that will need to be given or loaded

`_item_shapes(self, dims)`

Expected shape for an input item

Parameters `dims` (`Tuple[int, int]`) – the spatial dimension

Returns `Dict[int, tuple]`

`_demo_item(self, dims=(4, 4), rng=None)`

Create an input that satisfies this spec

Returns

an item like it might appear when its returned from the `__getitem__` method of a `torch...Dataset`.

Return type `dict`

Example

```
>>> dims = (1, 1)
>>> ChannelSpec.coerce(3)._demo_item(dims, rng=0)
>>> ChannelSpec.coerce('r|g|b|disparity')._demo_item(dims, rng=0)
>>> ChannelSpec.coerce('rgb|disparity')._demo_item(dims, rng=0)
>>> ChannelSpec.coerce('rgb,disparity')._demo_item(dims, rng=0)
>>> ChannelSpec.coerce('rgb')._demo_item(dims, rng=0)
>>> ChannelSpec.coerce('gray')._demo_item(dims, rng=0)
```

`encode(self, item, axis=0, mode=1)`

Given a dictionary containing preloaded components of the network inputs, build a concatenated (fused) network representations of each input stream.

Parameters

- `item` (`Dict[str, Tensor]`) – a batch item containing unfused parts. each key should be a single-stream (optionally early fused) channel key.
- `axis` (`int, default=0`) – concatenation dimension

Returns mapping between input stream and its early fused tensor input.

Return type `Dict[str, Tensor]`

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> import numpy as np
>>> dims = (4, 4)
>>> item = {
    '>>>     'rgb': np.random.rand(3, *dims),
    '>>>     'disparity': np.random.rand(1, *dims),
    '>>>     'flowx': np.random.rand(1, *dims),
    '>>>     'flowy': np.random.rand(1, *dims),
}
>>> # Complex Case
>>> self = ChannelSpec('rgb|disparity', 'flowx|flowy')
>>> fused = self.encode(item)
>>> input_shapes = ub.map_vals(lambda x: x.shape, fused)
>>> print('input_shapes = {}'.format(ub.repr2(input_shapes, nl=1)))
>>> # Simpler case
>>> self = ChannelSpec('rgb|disparity')
>>> fused = self.encode(item)
>>> input_shapes = ub.map_vals(lambda x: x.shape, fused)
>>> print('input_shapes = {}'.format(ub.repr2(input_shapes, nl=1)))
```

Example

```
>>> # Case where we have to break up early fused data
>>> import numpy as np
>>> dims = (40, 40)
>>> item = {
    '>>>     'rgb|disparity': np.random.rand(4, *dims),
    '>>>     'flowx': np.random.rand(1, *dims),
    '>>>     'flowy': np.random.rand(1, *dims),
}
>>> # Complex Case
>>> self = ChannelSpec('rgb|disparity', 'flowx|flowy|disparity')
>>> inputs = self.encode(item)
>>> input_shapes = ub.map_vals(lambda x: x.shape, inputs)
>>> print('input_shapes = {}'.format(ub.repr2(input_shapes, nl=1)))
```

```
>>> # xdoctest: +REQUIRES(--bench)
>>> #self = ChannelSpec('rgb|disparity', 'flowx|flowy')
>>> import timerit
>>> ti = timerit.Timerit(100, bestof=10, verbose=2)
>>> for timer in ti.reset('mode=simple'):
    with timer:
        inputs = self.encode(item, mode=0)
>>> for timer in ti.reset('mode=minimize-concat'):
    with timer:
        inputs = self.encode(item, mode=1)
```

`decode(self, inputs, axis=1)`
break an early fused item into its components

Parameters

- **inputs** (*Dict[str, Tensor]*) – dictionary of components
- **axis** (*int, default=1*) – channel dimension

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> import numpy as np
>>> dims = (4, 4)
>>> item_components = {
>>>     'rgb': np.random.rand(3, *dims),
>>>     'ir': np.random.rand(1, *dims),
>>> }
>>> self = ChannelSpec('rgb|ir')
>>> item_encoded = self.encode(item_components)
>>> batch = {k: np.concatenate([v[None, :], v[None, :]]), axis=0}
>>>         for k, v in item_encoded.items()}
>>> components = self.decode(batch)
```

Example

```
>>> # xdoctest: +REQUIRES(module:netharn, module:torch)
>>> import torch
>>> import numpy as np
>>> dims = (4, 4)
>>> components = {
>>>     'rgb': np.random.rand(3, *dims),
>>>     'ir': np.random.rand(1, *dims),
>>> }
>>> components = ub.map_vals(torch.from_numpy, components)
>>> self = ChannelSpec('rgb|ir')
>>> encoded = self.encode(components)
>>> from netharn.data import data_containers
>>> item = {k: data_containers.ItemContainer(v, stack=True)
>>>         for k, v in encoded.items()}
>>> batch = data_containers.container_collate([item, item])
>>> components = self.decode(batch)
```

component_indices(*self, axis=2*)

Look up component indices within fused streams

Example

```
>>> dims = (4, 4)
>>> inputs = ['flowx', 'flowy', 'disparity']
>>> self = ChannelSpec('disparity,flowx|flowy')
>>> component_indices = self.component_indices()
>>> print('component_indices = {}'.format(ub.repr2(component_indices, nl=1)))
component_indices =
    'disparity': ('disparity', (slice(None, None, None), slice(None, None, None),
        slice(0, 1, None))),
    'flowx': ('flowx|flowy', (slice(None, None, None), slice(None, None, None),
        slice(0, 1, None))),
    'flowy': ('flowx|flowy', (slice(None, None, None), slice(None, None, None),
        slice(1, 2, None))),
}
```

`class kwcococo.FusedChannelSpec(parsed, _is_normalized=False)`

Bases: BaseChannelSpec

A specific type of channel spec with only one early fused stream.

The channels in this stream are non-commutative

Behaves like a list of atomic-channel codes (which may represent more than 1 channel), normalized codes always represent exactly 1 channel.

Note: This class name and API is in flux and subject to change.

Todo: A special code indicating a name and some number of bands that that names contains, this would primarily be used for large numbers of channels produced by a network. Like:

resnet_d35d060_L5:512

or

resnet_d35d060_L5[:512]

might refer to a very specific (hashed) set of resnet parameters with 512 bands

maybe we can do something slicily like:

resnet_d35d060_L5[A:B] resnet_d35d060_L5:A:B

Do we want to “just store the code” and allow for parsing later?

Or do we want to ensure the serialization is parsed before we construct the data structure?

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> import pickle
>>> self = FusedChannelSpec.coerce(3)
>>> recon = pickle.loads(pickle.dumps(self))
>>> self = ChannelSpec.coerce('a|b,c|d')
>>> recon = pickle.loads(pickle.dumps(self))
```

`_alias_lut`

`_memo`

`_size_lut`

`__len__(self)`

`__getitem__(self, index)`

`classmethod concat(cls, items)`

`spec(self)`

The string encodeing of this spec

Returns str

`unique(self)`

`classmethod parse(cls, spec)`

`classmethod coerce(cls, data)`

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> FusedChannelSpec.coerce(['a', 'b', 'c'])
>>> FusedChannelSpec.coerce('a|b|c')
>>> FusedChannelSpec.coerce(3)
>>> FusedChannelSpec.coerce(FusedChannelSpec(['a']))
>>> assert FusedChannelSpec.coerce('') .numel() == 0
```

`concise(self)`

Shorted the channel spec by de-normaliz slice syntax

Returns concise spec

Return type *FusedChannelSpec*

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> self = FusedChannelSpec.coerce(
>>>     'b|a|a.0|a.1|a.2|a.5|c|a.8|a.9|b.0:3|c.0')
>>> short = self.concise()
>>> long = short.normalize()
>>> numels = [c.numel() for c in [self, short, long]]
>>> print('self.spec = {!r}'.format(self.spec))
```

(continues on next page)

(continued from previous page)

```
>>> print('short.spec = {!r}'.format(short.spec))
>>> print('long.spec = {!r}'.format(long.spec))
>>> print('numels = {!r}'.format(numels))
self.spec = 'b|a|a.0|a.1|a.2|a.5|c|a.8|a.9|b.0:3|c.0'
short.spec = 'b|a|a:3|a.5|c|a.8:10|b:3|c.0'
long.spec = 'b|a|a.0|a.1|a.2|a.5|c|a.8|a.9|b.0|b.1|b.2|c.0'
numels = [13, 13, 13]
>>> assert long.concise().spec == short.spec
```

normalize(self)

Replace aliases with explicit single-band-per-code specs

Returns normalize spec**Return type** *FusedChannelSpec***Example**

```
>>> from kwcoco.channel_spec import * # NOQA
>>> self = FusedChannelSpec.coerce('b1|b2|b3|rgb')
>>> normed = self.normalize()
>>> print('self = {}'.format(self))
>>> print('normed = {}'.format(normed))
self = <FusedChannelSpec(b1|b2|b3|rgb)>
normed = <FusedChannelSpec(b1|b2|b3|r|g|b)>
>>> self = FusedChannelSpec.coerce('B:1:11')
>>> normed = self.normalize()
>>> print('self = {}'.format(self))
>>> print('normed = {}'.format(normed))
self = <FusedChannelSpec(B:1:11)>
normed = <FusedChannelSpec(B.1|B.2|B.3|B.4|B.5|B.6|B.7|B.8|B.9|B.10)>
>>> self = FusedChannelSpec.coerce('B.1:11')
>>> normed = self.normalize()
>>> print('self = {}'.format(self))
>>> print('normed = {}'.format(normed))
self = <FusedChannelSpec(B.1:11)>
normed = <FusedChannelSpec(B.1|B.2|B.3|B.4|B.5|B.6|B.7|B.8|B.9|B.10)>
```

numel(self)

Total number of channels in this spec

sizes(self)

Returns a list indicating the size of each atomic code

Returns List[int]

Example

```
>>> from kwcoc.channel_spec import * # NOQA
>>> self = FusedChannelSpec.coerce('b1|Z:3|b2|b3|rgb')
>>> self.sizes()
[1, 3, 1, 1, 3]
>>> assert(FusedChannelSpec.parse('a.0')).numel() == 1
>>> assert(FusedChannelSpec.parse('a:0')).numel() == 0
>>> assert(FusedChannelSpec.parse('a:1')).numel() == 1
```

`__contains__(self, key)`

Example

```
>>> FCS = FusedChannelSpec.coerce
>>> 'disparity' in FCS('rgb|disparity|flowx|flowy')
True
>>> 'gray' in FCS('rgb|disparity|flowx|flowy')
False
```

`code_list(self)`

Return the expanded code list

`as_list(self)`

`as_oset(self)`

`as_set(self)`

`as_path(self)`

Returns a string suitable for use in a path.

Note, this may no longer be a valid channel spec

`__set__(self)`

`difference(self, other)`

Set difference

Example

```
>>> FCS = FusedChannelSpec.coerce
>>> self = FCS('rgb|disparity|flowx|flowy')
>>> other = FCS('r|b')
>>> self.difference(other)
>>> other = FCS('flowx')
>>> self.difference(other)
>>> FCS = FusedChannelSpec.coerce
>>> assert len((FCS('a') - {'a'}).parsed) == 0
>>> assert len((FCS('a.0:3') - {'a.0'}).parsed) == 2
```

`intersection(self, other)`

Example

```
>>> FCS = FusedChannelSpec.coerce
>>> self = FCS('rgb|disparity|flowx|flowy')
>>> other = FCS('r|b|XX')
>>> self.intersection(other)
```

component_indices(self, axis=2)

Look up component indices within this stream

Example

```
>>> FCS = FusedChannelSpec.coerce
>>> self = FCS('disparity|rgb|flowx|flowy')
>>> component_indices = self.component_indices()
>>> print('component_indices = {}'.format(ub.repr2(component_indices, nl=1)))
component_indices = {
    'disparity': (slice(...), slice(...), slice(0, 1, None)),
    'flowx': (slice(...), slice(...), slice(4, 5, None)),
    'flowy': (slice(...), slice(...), slice(5, 6, None)),
    'rgb': (slice(...), slice(...), slice(1, 4, None)),
}
```

streams(self)Idempotence with `ChannelSpec.streams()`**fuse(self)**Idempotence with `ChannelSpec.streams()`

PYTHON MODULE INDEX

k

kwcoco, 9
kwcoco.__init__, 1
kwcoco.__main__, 198
kwcoco._helpers, 198
kwcoco.abstract_coco_dataset, 201
kwcoco.category_tree, 202
kwcoco.channel_spec, 207
kwcoco.cli, 14
kwcoco.cli.__main__, 14
kwcoco.cli.coco_conform, 15
kwcoco.cli.coco_eval, 16
kwcoco.cli.coco_grab, 19
kwcoco.cli.coco_modify_categories, 19
kwcoco.cli.coco_reroot, 21
kwcoco.cli.coco_show, 22
kwcoco.cli.coco_split, 23
kwcoco.cli.coco_stats, 24
kwcoco.cli.coco_subset, 25
kwcoco.cli.coco_toydata, 27
kwcoco.cli.coco_union, 28
kwcoco.cli.coco_validate, 29
kwcoco.coco_dataset, 223
kwcoco.coco_evaluator, 270
kwcoco.coco_image, 277
kwcoco.coco_objects1d, 282
kwcoco.coco_schema, 290
kwcoco.coco_sql_dataset, 294
kwcoco.compat_dataset, 306
kwcoco.data, 30
kwcoco.data.grab_camvid, 30
kwcoco.data.grab_cifar, 32
kwcoco.data.grab_datasets, 32
kwcoco.data.grab_domainnet, 33
kwcoco.data.grab_spacenet, 33
kwcoco.data.grab_voc, 34
kwcoco.demo, 36
kwcoco.demo.boids, 36
kwcoco.demo.perterb, 40
kwcoco.demo.toydata, 41
kwcoco.demo.toydata_image, 49
kwcoco.demo.toydata_video, 53
kwcoco.demo.toypatterns, 61
kwcoco.examples, 64
kwcoco.examples.bench_large_hyperspectral, 64
kwcoco.examples.draw_gt_and_predicted_boxes, 65
kwcoco.examples.faq, 66
kwcoco.examples.getting_started_existing_dataset, 66
kwcoco.examples.loading_multispectral_data, 67
kwcoco.examples.modification_example, 67
kwcoco.examples.simple_kwcoco_torch_dataset, 67
kwcoco.examples.vectorized_interface, 69
kwcoco.kpf, 309
kwcoco.kw18, 309
kwcoco.metrics, 69
kwcoco.metrics.assignment, 69
kwcoco.metrics.clf_report, 74
kwcoco.metrics.confusion_measures, 77
kwcoco.metrics.confusion_vectors, 84
kwcoco.metrics.detect_metrics, 93
kwcoco.metrics.drawing, 100
kwcoco.metrics.functional, 104
kwcoco.metrics.sklearn_alts, 106
kwcoco.metrics.util, 108
kwcoco.metrics.voc_metrics, 108
kwcoco.util, 131
kwcoco.util.dict_like, 131
kwcoco.util.jsonschema_elements, 132
kwcoco.util.lazy_frame_backends, 138
kwcoco.util.util_archive, 141
kwcoco.util.util_delayed_poc, 143
kwcoco.util.util_futures, 164
kwcoco.util.util_json, 164
kwcoco.util.util_monkey, 166
kwcoco.util.util_sklearn, 167
kwcoco.util.util_truncate, 168

INDEX

Symbols

_3dplot() (kwcoco.metrics.BinaryConfusionVectors method), 120
_3dplot() (kwcoco.metrics.confusion_vectors.BinaryConfusionVectors method), 92
_CLI (in module kwcoco.cli.coco_conform), 16
_CLI (in module kwcoco.cli.coco_eval), 18
_CLI (in module kwcoco.cli.coco_grab), 19
_CLI (in module kwcoco.cli.coco_modify_categories), 20
_CLI (in module kwcoco.cli.coco_reroot), 21
_CLI (in module kwcoco.cli.coco_show), 22
_CLI (in module kwcoco.cli.coco_split), 23
_CLI (in module kwcoco.cli.coco_stats), 24
_CLI (in module kwcoco.cli.coco_subset), 27
_CLI (in module kwcoco.cli.coco_toydata), 28
_CLI (in module kwcoco.cli.coco_union), 29
_CLI (in module kwcoco.cli.coco_validate), 30
_GDAL_DTYPE_LUT (in module coco.util.lazy_frame_backends), 138
_ID_Remapper (class in kwcoco._helpers), 198
_NextId (class in kwcoco._helpers), 198
__and__() (kwcoco.channel_spec.BaseChannelSpec method), 210
__array__() (kwcoco.util.LazyGDalFrameFile method), 177
__array__() (kwcoco.util.lazy_frame_backends.LazyGDalFrameFile method), 140
__bool__() (kwcoco.coco_dataset.CocoIndex method), 260
__call__() (kwcoco.util.Element method), 173
__call__() (kwcoco.util.jsonschema_elements.Element method), 134
__contains__() (kwcoco.CategoryTree method), 316
__contains__() (kwcoco.ChannelSpec method), 328
__contains__() (kwcoco.FusedChannelSpec method), 338
__contains__() (kwcoco.category_tree.CategoryTree method), 206
__contains__() (kwcoco.channel_spec.ChannelSpec method), 215
__contains__() (kwcoco.channel_spec.FusedChannelSpec method), 212
__contains__() (kwcoco.coco_sql_dataset.SqlDictProxy method), 300
__contains__() (kwcoco.coco_sql_dataset.SqlIdGroupDictProxy method), 301
__contains__() (kwcoco.coco_sql_dataset.SqlListProxy method), 298
__contains__() (kwcoco.util.DictLike method), 171
__contains__() (kwcoco.util.dict_like.DictLike method), 131
__delitem__() (kwcoco.coco_sql_dataset.SqlListProxy method), 298
__delitem__() (kwcoco.util.DictLike method), 171
__delitem__() (kwcoco.util.dict_like.DictLike method), 131
__doc__ (kwcoco.cli.coco_eval.CocoEvalCLICConfig attribute), 17
__enter__() (kwcoco.util.Archive method), 179
__enter__() (kwcoco.util.SuppressPrint method), 196
__enter__() (kwcoco.util.util_archive.Archive method), 142
__enter__() (kwcoco.util.util_monkey.SuppressPrint method), 166
__exit__() (kwcoco.util.Archive method), 179
__exit__() (kwcoco.util.SuppressPrint method), 197
__exit__() (kwcoco.util.util_archive.Archive method), 142
__exit__() (kwcoco.util.util_monkey.SuppressPrint method), 166
__generics__ (kwcoco.util.Element attribute), 173
__generics__ (kwcoco.util.jsonschema_elements.Element attribute), 134
__getitem__() (kwcoco.CategoryTree method), 316
__getitem__() (kwcoco.FusedChannelSpec method), 336
__getitem__() (kwcoco.category_tree.CategoryTree method), 206
__getitem__() (kwcoco.channel_spec.FusedChannelSpec method), 211
__getitem__() (kwcoco.coco_image.CocoImage method), 278
__getitem__() (kwcoco.coco_objects1d.ObjectGroups method), 286

__getitem__(kwcoco.coco_objects1d.ObjectList1D method), 283
__getitem__(kwcoco.coco_sql_dataset.SqlDictProxy method), 300
__getitem__(kwcoco.coco_sql_dataset.SqlIdGroupDictProxy method), 301
__getitem__(kwcoco.coco_sql_dataset.SqlListProxy method), 298
__getitem__(kwcoco.demo.toypatterns.CategoryPatterns method), 298
__getitem__(kwcoco.demo.toypatterns.CategoryPatterns iter)(kwcoco.util.Archive method), 178
method), 63
__getitem__(kwcoco.examples.simple_kwccoco_torch_datatreeKWCCoSimpleTorchDatatree.DictLike method),
method), 69
131
__getitem__(kwcoco.metrics.OneVsRestConfusionVectors iter)(kwcoco.util.util_archive.Archive method),
method), 129
142
__getitem__(kwcoco.metrics.confusion_vectors.OneVsRestConfusionVectors CategoryTree method), 316
method), 89
__getitem__(kwcoco.metrics.util.DictProxy method), 108
__getitem__(kwcoco.util.DictLike method), 171
__getitem__(kwcoco.util.LazyGDalFrameFile method), 177
__getitem__(kwcoco.util.LazyRasterIOFrameFile method), 177
__getitem__(kwcoco.util.LazySpectralFrameFile method), 177
__getitem__(kwcoco.util.dict_like.DictLike method), 131
__getitem__(kwcoco.util.lazy_frame_backends.LazyGDalFrameFile method), 129
method), 140
__getitem__(kwcoco.util.lazy_frame_backends.LazyRasterIOFrameFile), 78
method), 139
__getitem__(kwcoco.util.lazy_frame_backends.LazySpectralFrameFile), 81
method), 139
__getstate__(kwcoco.CategoryTree method), 317
__getstate__(kwcoco.category_tree.CategoryTree method), 206
__getstate__(kwcoco.coco_sql_dataset.CocoSqlDatabase json)(kwcoco.util.DelayedVisionOperation
method), 302
__hack_dont_optimize__(kwcoco.util.DelayedCrop attribute), 182
__hack_dont_optimize__(kwcoco.util.DelayedIdentity attribute), 185
__hack_dont_optimize__(kwcoco.util.DelayedLoad attribute), 187
__hack_dont_optimize__(kwcoco.util.util_delayed_poc.DelayedCrop attribute), 163
__hack_dont_optimize__(kwcoco.util.util_delayed_poc.DelayedIdentity attribute), 149
__hack_dont_optimize__(kwcoco.util.util_delayed_poc.DelayedLoad attribute), 152
__iter__(kwcoco.CategoryTree method), 316
__iter__(kwcoco.category_tree.CategoryTree
method), 205
__iter__(kwcoco.coco_objects1d.ObjectList1D
method), 283
__iter__(kwcoco.coco_sql_dataset.SqlListProxy
method), 298
__iter__(kwcoco.demo.toypatterns.CategoryPatterns
method), 63
__iter__(kwcoco.util.DictLike method), 171
__iter__(kwcoco.util.util_archive.Archive
method), 142
__json__(kwcoco.category_tree.CategoryTree
method), 206
__json__(kwcoco.channel_spec.BaseChannelSpec
method), 210
__json__(kwcoco.coco_evaluator.CocoResults
method), 275
__json__(kwcoco.coco_evaluator.CocoSingleResult
method), 276
__json__(kwcoco.metrics.ConfusionVectors
method), 121
__json__(kwcoco.metrics.Measures method), 125
__json__(kwcoco.metrics.PerClass_Measures
method), 125
__json__(kwcoco.metrics.confusion_measures.Measures
method), 129
__json__(kwcoco.metrics.confusion_measures.PerClass_Measures
method), 139
__json__(kwcoco.metrics.confusion_vectors.ConfusionVectors
method), 85
__json__(kwcoco.metrics.util.DictProxy
method), 108
__len__(kwcoco.CategoryTree method), 316
__len__(kwcoco.FusedChannelSpec method), 336
__len__(kwcoco.category_tree.CategoryTree
method), 205
__len__(kwcoco.channel_spec.FusedChannelSpec
method), 210
__len__(kwcoco.coco_objects1d.ObjectList1D
method), 283
__len__(kwcoco.coco_sql_dataset.SqlDictProxy
method), 300
__len__(kwcoco.coco_sql_dataset.SqlIdGroupProxy
method), 301
__len__(kwcoco.coco_sql_dataset.SqlListProxy
method), 298

```

__len__(kwcoco.demo.toypatterns.CategoryPatterns __nice__(kwcoco.metrics.confusion_vectors.OneVsRestConfusionVector
    method), 63                                     method), 89
__len__(kwcoco.examples.simple_kwco_coco_torch_dataset.KwCocoSimpleTorchDataset.detect_metrics.DetectionMetrics
    method), 69                                     method), 94
__len__(kwcoco.metrics.BinaryConfusionVectors __nice__(kwcoco.metrics.voc_metrics.VOC_Metrics
    method), 118                                     method), 109
__len__(kwcoco.metrics.confusion_vectors.BinaryConfusionVector __nice__(kwcoco.util.DelayedVisionOperation
    method), 90                                     method), 191
__len__(kwcoco.util.DictLike method), 171 __nice__(kwcoco.util.LazyGdalFrameFile method),
__len__(kwcoco.util.dict_like.DictLike method), 131                                         177
__nice__(kwcoco.CategoryTree method), 317 __nice__(kwcoco.util.LazyRasterIOFrameFile
__nice__(kwcoco.CocoDataset method), 321 __nice__(kwcoco.util.LazySpectralFrameFile
                                         method), 177
__nice__(kwcoco.category_tree.CategoryTree __nice__(kwcoco.util.lazy_frame_backends.LazyGdalFrameFile
    method), 206                                     method), 140
__nice__(kwcoco.channel_spec.BaseChannelSpec __nice__(kwcoco.util.lazy_frame_backends.LazyRasterIOFrameFile
    method), 210                                     method), 139
__nice__(kwcoco.coco_dataset.CocoDataset __nice__(kwcoco.util.lazy_frame_backends.LazySpectralFrameFile
    method), 265                                     method), 139
__nice__(kwcoco.coco_evaluator.CocoSingleResult __nice__(kwcoco.util.util_delayed_poc.DelayedVisionOperation
    method), 276                                     method), 147
__nice__(kwcoco.coco_image.CocoImage method), 278 __nonzero__(kwcoco.coco_dataset.CocoIndex
__nice__(kwcoco.coco_objects1d.ObjectGroups attribute), 260
    method), 286 __or__(kwcoco.util.Element method), 173
__nice__(kwcoco.coco_objects1d.ObjectList1D __or__(kwcoco.util.jsonschema_elements.Element
    method), 283                                     method), 134
__nice__(kwcoco.coco_sql_dataset.CocoSqlDatabase __repr__(kwcoco._helpers.SortedSetQuiet method),
    method), 302                                     201
__nice__(kwcoco.coco_sql_dataset.SqlDictProxy __set__(kwcoco.FusedChannelSpec method), 338
    method), 300 __set__(kwcoco.channel_spec.FusedChannelSpec
__nice__(kwcoco.coco_sql_dataset.SqlIdGroupDictProxy method), 301                                     method), 213
__nice__(kwcoco.coco_sql_dataset.SqlListProxy __setitem__(kwcoco.coco_sql_dataset.SqlListProxy
    method), 298                                     method), 298
__nice__(kwcoco.demo.boids.Boids method), 37 __setitem__(kwcoco.metrics.util.DictProxy
__nice__(kwcoco.metrics.BinaryConfusionVectors method), 118                                     method), 108
__nice__(kwcoco.metrics.ConfusionVectors method), 121 __setitem__(kwcoco.util.DictLike method), 171
__nice__(kwcoco.metrics.DetectionMetrics method), 112 __setitem__(kwcoco.util.dict_like.DictLike
__nice__(kwcoco.metrics.Measures method), 125                                     method), 131
__nice__(kwcoco.metrics.OneVsRestConfusionVectors __setstate__(kwcoco.CategoryTree method), 317
    method), 129 __setstate__(kwcoco.category_tree.CategoryTree
__nice__(kwcoco.metrics.PerClass_Measures __sub__(kwcoco.channel_spec.BaseChannelSpec
    method), 129                                     method), 210
__nice__(kwcoco.metrics.confusion_measures.Measures_tablelename_ (kwcoco.coco_sql_dataset.Annotation
    method), 78                                     attribute), 297
__nice__(kwcoco.metrics.confusion_measures.PerClass_Measures_tablelename_ (kwcoco.coco_sql_dataset.Category
    method), 81                                     attribute), 296
__nice__(kwcoco.metrics.confusion_vectors.BinaryConfusionVector __table_name__(kwcoco.coco_sql_dataset.Image
    method), 90                                     attribute), 296
__nice__(kwcoco.metrics.confusion_vectors.ConfusionVector __table_name__(kwcoco.coco_sql_dataset.KeypointCategory
    method), 85                                     attribute), 296

```

`_tablename_` (*kwcoco.coco_sql_dataset.Video attribute*), 296
`_torrent_voc()` (*in module kwcoco.data.grab_voc*), 35
`_add_annotation()` (*kwcoco.coco_dataset.CocoIndex method*), 261
`_add_annotations()` (*kwcoco.coco_dataset.CocoIndex method*), 261
`_add_category()` (*kwcoco.coco_dataset.CocoIndex method*), 261
`_add_image()` (*kwcoco.coco_dataset.CocoIndex method*), 260
`_add_images()` (*kwcoco.coco_dataset.CocoIndex method*), 260
`_add_video()` (*kwcoco.coco_dataset.CocoIndex method*), 260
`_alias_lut` (*kwcoco.FusedChannelSpec attribute*), 336
`_alias_lut` (*kwcoco.channel_spec.FusedChannelSpec attribute*), 210
`_alias_to_cat()` (*kwcoco.coco_dataset.MixinCocoAccessors method*), 233
`_all_rows_column_lookup()` (*kwcoco.coco_sql_dataset.CocoSqlDatabase method*), 304
`_aspycoco()` (*kwcoco.coco_dataset.MixinCocoExtras method*), 240
`_assign_confusion_vectors()` (*in module kwcoco.metrics.assignment*), 70
`_auto_dsize()` (*in module kwcoco.util.util_delayed_poc*), 163
`_average_precision()` (*in module kwcoco.metrics.functional*), 106
`_bbox_h` (*kwcoco.coco_sql_dataset.Annotation attribute*), 297
`_bbox_w` (*kwcoco.coco_sql_dataset.Annotation attribute*), 297
`_bbox_x` (*kwcoco.coco_sql_dataset.Annotation attribute*), 297
`_bbox_y` (*kwcoco.coco_sql_dataset.Annotation attribute*), 297
`_benchmark_dict_proxy_ops()` (*in module kwcoco.coco_sql_dataset*), 305
`_benchmark_dset_readtime()` (*in module kwcoco.coco_sql_dataset*), 305
`_binary_clf_curve2()` (*in module kwcoco.metrics.sklearn_alts*), 107
`_binary_clf_curves()` (*kwcoco.metrics.BinaryConfusionVectors method*), 119
`_binary_clf_curves()` (*kwcoco.metrics.confusion_vectors.BinaryConfusionVectors method*), 91
`_build_dmet()` (*kwcoco.coco_evaluator.CocoEvaluator*)
`_build_hashid()` (*kwcoco.coco_dataset.MixinCocoExtras method*), 237
`_build_index()` (*kwcoco.CategoryTree method*), 318
`_build_index()` (*kwcoco.CocoDataset method*), 323
`_build_index()` (*kwcoco.category_tree.CategoryTree method*), 207
`_build_index()` (*kwcoco.coco_dataset.CocoDataset method*), 266
`_cached_hashid()` (*kwcoco.coco_dataset.MixinCocoExtras method*), 238
`_cached_single_fused_mapping()` (*in module kwcoco.channel_spec*), 222
`_cached_single_stream_idxs()` (*in module kwcoco.channel_spec*), 222
`_check_index()` (*kwcoco.CocoDataset method*), 322
`_check_index()` (*kwcoco.coco_dataset.CocoDataset method*), 266
`_check_integrity()` (*kwcoco.CocoDataset method*), 322
`_check_integrity()` (*kwcoco.coco_dataset.CocoDataset method*), 266
`_check_json_serializable()` (*kwcoco.CocoDataset method*), 322
`_check_json_serializable()` (*kwcoco.coco_dataset.CocoDataset method*), 266
`_check_pointers()` (*kwcoco.CocoDataset method*), 323
`_check_pointers()` (*kwcoco.coco_dataset.CocoDataset method*), 266
`_coco_image()` (*kwcoco.coco_dataset.MixinCocoAccessors method*), 234
`_coerce_dets()` (*kwcoco.coco_evaluator.CocoEvaluator class method*), 273
`_column_lookup()` (*kwcoco.coco_sql_dataset.CocoSqlDatabase method*), 304
`_compute_leaf_subcrop()` (*in module kwcoco.util.util_delayed_poc*), 163
`_convert_cifar_x()` (*in module kwcoco.data.grab_cifar*), 32
`_convert_voc_split()` (*in module kwcoco.data.grab_voc*), 35
`_critical_loop()` (*in module kwcoco.metrics.assignment*), 73
`_dataset_id()` (*kwcoco.coco_dataset.MixinCocoExtras method*), 238
`_default_categories` (*kwcoco.demo.toypatterns.CategoryPatterns*)

attribute), 62

`_default_catnames` (kw-
 *coco.demo.toypatterns.CategoryPatterns
 attribute), 62*

`_default_keypoint_categories` (kw-
 *coco.demo.toypatterns.CategoryPatterns
 attribute), 62*

`_define_camvid_class_hierarchy()` (in module kw-
 coco.data.grab_camvid), 32

`_delay_load_imglike()` (in module kw-
 coco.coco_image), 282

`_delitems()` (in module *kwcoco._helpers*), 201

`_demo_construct_probs()` (in module kw-
 coco.demo.perverb), 40

`_demo_construct_probs()` (in module kw-
 coco.metrics.detect_metrics), 99

`_demo_item()` (*kwcoco.ChannelSpec method*), 332

`_demo_item()` (*kwcoco.channel_spec.ChannelSpec
 method*), 219

`_devcheck_corner()` (in module kw-
 coco.util.util_delayed_poc), 163

`_devcheck_load_sub_image()` (in module kw-
 coco.data.grab_camvid), 30

`_devcheck_sample_full_image()` (in module kw-
 coco.data.grab_camvid), 30

`_dict` (in module *kwcoco.coco_dataset*), 229

`_draw_video_sequence()` (in module kw-
 coco.demo.toydata_video), 57

`_ds()` (*kwcoco.util.LazyGdalFrameFile method*), 176

`_ds()` (*kwcoco.util.LazyRasterIOFrameFile method*),
 177

`_ds()` (*kwcoco.util.LazySpectralFrameFile method*), 177

`_ds()` (*kwcoco.util.lazy_frame_backends.LazyGdalFrameFile
 method*), 140

`_ds()` (*kwcoco.util.lazy_frame_backends.LazyRasterIOFrameFile
 method*), 139

`_ds()` (*kwcoco.util.lazy_frame_backends.LazySpectralFrameFile
 method*), 139

`_ensure_dsize()` (*kwcoco.util.DelayedLoad method*),
 187

`_ensure_dsize()` (kw-
 *coco.util.util_delayed_poc.DelayedLoad
 method*), 152

`_ensure_image_data()` (kw-
 coco.coco_dataset.MixinCocoExtras method),
 239

`_ensure_imgszie()` (kw-
 coco.coco_dataset.MixinCocoExtras method),
 238

`_ensure_init()` (*kwcoco.coco_evaluator.CocoEvaluator
 method*), 273

`_ensure_json_serializable()` (kw-
 coco.coco_dataset.MixinCocoExtras method),
 240

`_ensure_kw18_column_order()` (in module kw-
 coco_kw18), 312

`_fast_pdist_priority()` (in module kw-
 coco.metrics.assignment), 73

`_filter_ignore_regions()` (in module kw-
 coco.metrics.assignment), 73

`_from_elem()` (*kwcoco.demo.toypatterns.CategoryPatterns
 method*), 64

`_get_img_auxiliary()` (kw-
 *coco.coco_dataset.MixinCocoAccessors
 method*), 231

`_handle_sql_uri()` (in module kw-
 coco.coco_sql_dataset), 301

`_have_gdal()` (in module kw-
 coco.util.lazy_frame_backends), 138

`_have_rasterio()` (in module kw-
 coco.util.lazy_frame_backends), 138

`_have_spectral()` (in module kw-
 coco.util.lazy_frame_backends), 138

`_id_to_obj` (*kwcoco.coco_objects1d.ObjectList1D
 property*), 283

`_infer_dirs()` (*kwcoco.CocoDataset method*), 320

`_infer_dirs()` (*kwcoco.coco_dataset.CocoDataset
 method*), 264

`_init()` (*kwcoco.coco_evaluator.CocoEvaluator
 method*), 273

`_invalidate_hashid()` (kw-
 coco.coco_dataset.MixinCocoExtras method),
 238

`_item_shapes()` (*kwcoco.ChannelSpec method*), 332

`_item_shapes()` (*kwcoco.channel_spec.ChannelSpec
 method*), 219

`_item_shapes()` (*kwcoco.ChannelSpec method*), 332

`_item_shapes()` (*kwcoco.channel_spec.ChannelSpec
 method*), 219

`_lazy_group_kfold()` (kw-
 *coco.util.StratifiedGroupKFold
 method*), 197

`_iter_test_masks()` (kw-
 *coco.util.util_sklearn.StratifiedGroupKFold
 method*), 168

`_keypoint_category_names()` (kw-
 *coco.coco_dataset.MixinCocoAccessors
 method*), 234

`_largest_shape()` (in module kw-
 coco.util.util_delayed_poc), 163

`_load_dets()` (in module *kwcoco.coco_evaluator*), 276

`_load_dets_worker()` (in module kw-
 coco.coco_evaluator), 277

`_lookup()` (*kwcoco.coco_objects1d.ObjectGroups
 method*), 286

`_lookup()` (*kwcoco.coco_objects1d.ObjectList1D
 method*), 285

`_lookup_kpnames()` (kw-
 *coco.coco_dataset.MixinCocoAccessors
 method*), 234

`_lut_frame_index()` (in module *kwcoco._helpers*), 199

_make_test_folds() (kw-
 coco.util.StratifiedGroupKFold
 method), 197

_make_test_folds() (kw-
 coco.util.util_sklearn.StratifiedGroupKFold
 method), 167

_memo (kwcoco.FusedChannelSpec attribute), 336

_memo (kwcoco.channel_spec.FusedChannelSpec attribute), 210

_new_proxy_cache() (in module kw-
 coco.coco_sql_dataset), 298

_open() (kwcoco.util.Archive class method), 178

_open() (kwcoco.util.util_archive.Archive class method), 142

_optimize_paths() (kwcoco.util.DelayedCrop
 method), 182

_optimize_paths() (kwcoco.util.DelayedIdentity
 method), 185

_optimize_paths() (kwcoco.util.DelayedLoad
 method), 187

_optimize_paths() (kwcoco.util.DelayedNans
 method), 190

_optimize_paths() (kw-
 coco.util.DelayedVisionOperation
 method), 191

_optimize_paths() (kwcoco.util.DelayedWarp
 method), 193

_optimize_paths() (kw-
 coco.util.util_delayed_poc.DelayedCrop
 method), 163

_optimize_paths() (kw-
 coco.util.util_delayed_poc.DelayedIdentity
 method), 149

_optimize_paths() (kw-
 coco.util.util_delayed_poc.DelayedLoad
 method), 152

_optimize_paths() (kw-
 coco.util.util_delayed_poc.DelayedNans
 method), 150

_optimize_paths() (kw-
 coco.util.util_delayed_poc.DelayedVisionOperation
 method), 147

_optimize_paths() (kw-
 coco.util.util_delayed_poc.DelayedWarp
 method), 160

_orm_yielder() (in module kwcoco.coco_sql_dataset), 297

_package_info() (kw-
 coco.demo.toypatterns.CategoryPatterns
 method), 64

_parse_concise_slice_syntax() (in module kw-
 coco.channel_spec), 222

_pr_curves() (in module kwcoco.metrics.functional), 105

_pr_curves() (in module kwcoco.metrics.voc_metrics), 109

_pygame_render_boids() (in module kw-
 coco.demo.boids), 39

_raw_yielder() (in module kwcoco.coco_sql_dataset), 298

_read_envi_header() (in module kw-
 coco.util.lazy_frame_backends), 141

_read_split_paths() (in module kw-
 coco.data.grab_voc), 35

_realpos_label_suffix() (in module kw-
 coco.metrics.drawing), 101

_rectify_classes() (kw-
 coco.coco_evaluator.CocoEvaluator
 method), 273

_rectify_slice_dim() (in module kw-
 coco.util.lazy_frame_backends), 140

_register_imagename() (kw-
 coco.metrics.DetectionMetrics
 method), 112

_register_imagename() (kw-
 coco.metrics.detect_metrics.DetectionMetrics
 method), 94

_remove_all_annotations() (kw-
 coco.coco_dataset.CocoIndex method), 261

_remove_all_images() (kw-
 coco.coco_dataset.CocoIndex method), 261

_remove_annotations() (kw-
 coco.coco_dataset.CocoIndex method), 261

_remove_categories() (kw-
 coco.coco_dataset.CocoIndex method), 261

_remove_images() (kwcoco.coco_dataset.CocoIndex
 method), 261

_remove_videos() (kwcoco.coco_dataset.CocoIndex
 method), 261

_resolve_to_ann() (kw-
 coco.coco_dataset.MixinCocoAccessors
 method), 232

_resolve_to_cat() (kw-
 coco.coco_dataset.MixinCocoAccessors
 method), 232

_resolve_to_cid() (kw-
 coco.coco_dataset.MixinCocoAccessors
 method), 232

_resolve_to_gid() (kw-
 coco.coco_dataset.MixinCocoAccessors
 method), 232

_resolve_to_id() (kw-
 coco.coco_dataset.MixinCocoAccessors
 method), 232

_resolve_to_img() (kw-
 coco.coco_dataset.MixinCocoAccessors
 method), 232

_resolve_to_kpcat() (kw-

`coco.coco_dataset.MixinCocoAccessors
method), 232`
`_resolve_to_vidid() (kw-
coco.coco_dataset.MixinCocoAccessors
method), 232`
`_set (kwcoco.coco_dataset.CocoIndex attribute), 260`
`_set() (kwcoco.coco_objects1d.ObjectListID method),
285`
`_set_sorted_by_frame_index() (kw-
coco.coco_dataset.CocoIndex method), 260`
`_size_lut (kwcoco.FusedChannelSpec attribute), 336`
`_size_lut (kwcoco.channel_spec.FusedChannelSpec
attribute), 210`
`_spatial_index_scratch() (in module kw-
coco.demo.boids), 39`
`_stabalize_data() (in module kw-
coco.metrics.confusion_vectors), 92`
`_summarize() (in module kw-
coco.metrics.detect_metrics), 100`
`_summary() (kwcoco.metrics.confusion_measures.OneVsAll
method), 83`
`_to_coco() (kwcoco.metrics.DetectionMetrics method),
114`
`_to_coco() (kwcoco.metrics.detect_metrics.DetectionMetric
method), 96`
`_todo_refactor_geometric_info() (kw-
coco.demo.toypatterns.CategoryPatterns
method), 63`
`_tree() (kwcoco.coco_dataset.MixinCocoExtras
method), 237`
`_trunc_op() (in module kwcoco.util.util_truncate), 168`
`_truncated_roc() (in module kw-
coco.metrics.functional), 105`
`_update_unused() (kwcoco._helpers._NextId method),
198`
`_validate_nonzero_data() (in module kw-
coco.util.lazy_frame_backends), 140`
`_voc_ave_precision() (in module kw-
coco.metrics.voc_metrics), 110`
`_voc_eval() (in module kwcoco.metrics.voc_metrics),
110`
`_writefig() (in module kwcoco.coco_evaluator), 276`
`_yeah_boid() (in module kwcoco.demo.boids), 39`

A

`AbstractCocoDataset (class in kwcoco), 312`
`AbstractCocoDataset (class in kw-
coco.abstract_coco_dataset), 201`
`add() (kwcoco.util.Archive method), 178`
`add() (kwcoco.util.util_archive.Archive method), 142`
`add_annotation() (kw-
coco.coco_dataset.MixinCocoAddRemove
method), 251`
`add_annotations() (kw-
coco.coco_dataset.MixinCocoAddRemove
method), 254`
`add_auxiliary_item() (kw-
coco.coco_image.CocoImage method), 279`
`add_category() (kwcoco.coco_dataset.MixinCocoAddRemove
method), 253`
`add_image() (kwcoco.coco_dataset.MixinCocoAddRemove
method), 251`
`add_images() (kwcoco.coco_dataset.MixinCocoAddRemove
method), 255`
`add_predictions() (kw-
coco.metrics.detect_metrics.DetectionMetrics
method), 94`
`add_predictions() (kwcoco.metrics.DetectionMetrics
method), 112`
`add_predictions() (kw-
coco.metrics.voc_metrics.VOC_Metrics
method), 109`
~~`add_predictions() (kw-
coco.metrics.voc_metrics.VOC_Metrics
method), 94`~~
`add_truth() (kwcoco.metrics.DetectionMetrics
method), 112`
~~`add_truth() (kwcoco.metrics.voc_metrics.VOC_Metrics
method), 109`~~
`add_video() (kwcoco.coco_dataset.MixinCocoAddRemove
method), 250`
`aids (kwcoco.coco_objects1d.Annots property), 289`
`aids (kwcoco.coco_objects1d.Images property), 288`
`ALCHEMY_MODE_DEFAULT (in module kw-
coco.coco_sql_dataset), 297`
`alias (kwcoco.coco_sql_dataset.Category attribute),
296`
`alias (kwcoco.coco_sql_dataset.KeypointCategory at-
tribute), 296`
`ALLOF (in module kwcoco.coco_schema), 293`
`ALLOF (in module kwcoco.util), 171`
`ALLOF (in module kwcoco.util.jsonschema_elements), 137`
`ALLOF() (kwcoco.util.jsonschema_elements.QuantifierElements
method), 135`
`ALLOF() (kwcoco.util.QuantifierElements method), 174`
`Annotation (class in kwcoco.coco_sql_dataset), 297`
`ANNOTATION (in module kwcoco.coco_schema), 294`
`AnnotGroups (class in kwcoco.coco_objects1d), 290`
`Annots (class in kwcoco.coco_objects1d), 289`
`annots (kwcoco.coco_objects1d.Images property), 288`
`annots() (kwcoco.coco_dataset.MixinCocoObjects
method), 242`
`anns (kwcoco.coco_dataset.MixinCocoIndex property),
261`
`anns (kwcoco.coco_sql_dataset.CocoSqlDatabase prop-
erty), 303`
`annToMask() (kwcoco.compat_dataset.COCO method),
308`

annToRLE() (*kwcoco.compat_dataset.COCO* method), 308
ANY (*in module kwcoco.coco_schema*), 293
ANY (*in module kwcoco.util*), 171
ANY (*in module kwcoco.util.jsonschema_elements*), 137
ANY (*kwcoco.util.jsonschema_elements.QuantifierElements* property), 135
ANY (*kwcoco.util.QuantifierElements* property), 174
ANYOF (*in module kwcoco.coco_schema*), 293
ANYOF (*in module kwcoco.util*), 171
ANYOF (*in module kwcoco.util.jsonschema_elements*), 137
ANYOF () (*kwcoco.util.jsonschema_elements.QuantifierElements* method), 135
ANYOF () (*kwcoco.util.QuantifierElements* method), 174
Archive (*class in kwcoco.util*), 177
Archive (*class in kwcoco.util.util_archive*), 141
area (*kwcoco.coco_objects1d.Images* property), 288
ARRAY (*in module kwcoco.coco_schema*), 293
ARRAY (*in module kwcoco.util*), 171
ARRAY (*in module kwcoco.util.jsonschema_elements*), 137
ARRAY () (*kwcoco.util.ContainerElements* method), 171
ARRAY () (*kwcoco.util.jsonschema_elements.ContainerElements* method), 135
as_list() (*kwcoco.channel_spec.FusedChannelSpec* method), 212
as_list() (*kwcoco.FusedChannelSpec* method), 338
as_oerset() (*kwcoco.channel_spec.FusedChannelSpec* method), 213
as_oerset() (*kwcoco.FusedChannelSpec* method), 338
as_path() (*kwcoco.channel_spec.ChannelSpec* method), 218
as_path() (*kwcoco.channel_spec.FusedChannelSpec* method), 213
as_path() (*kwcoco.ChannelSpec* method), 330
as_path() (*kwcoco.FusedChannelSpec* method), 338
as_set() (*kwcoco.channel_spec.FusedChannelSpec* method), 213
as_set() (*kwcoco.FusedChannelSpec* method), 338
ASCII_ONLY (*in module kwcoco.metrics.clf_report*), 74
asdict (*kwcoco.util.dict_like.DictLike* attribute), 131
asdict (*kwcoco.util.DictLike* attribute), 170
assert_dsets_allclose() (*in module kwcoco.coco_sql_dataset*), 305
attribute_frequency() (*kwcoco.coco_objects1d.ObjectListID* method), 286
auxiliary (*kwcoco.coco_sql_dataset.Image* attribute), 297
available() (*kwcoco.util.lazy_frame_backends.LazyGdalFrameFile* class method), 140
available() (*kwcoco.util.lazy_frame_backends.LazyRasterIOFrameFile* class method), 139
available() (*kwcoco.util.lazy_frame_backends.LazySpectralFrameFile* class method), 139
available() (*kwcoco.util.LazyGdalFrameFile* class method), 176
available() (*kwcoco.util.LazyRasterIOFrameFile* class method), 177
available() (*kwcoco.util.LazySpectralFrameFile* class method), 177

B

BaseChannelSpec (*class in kwcoco.channel_spec*), 209
basic_stats() (*kwcoco.coco_dataset.MixinCocoStats* method), 247
bbox (*in module kwcoco.coco_schema*), 293
bbox (*kwcoco.coco_sql_dataset.Annotation* attribute), 297
benchmark_large_hyperspectral() (*in module kwcoco.examples.bench_large_hyperspectral*), 64
binarize_classless() (*kwcoco.metrics.confusion_vectors.ConfusionVectors* method), 87
binarize_classless() (*kwcoco.metrics.ConfusionVectors* method), 123
binarize_ovr() (*kwcoco.metrics.confusion_vectors.ConfusionVectors* method), 88
binarize_ovr() (*kwcoco.metrics.ConfusionVectors* method), 124
BinaryConfusionVectors (*class in kwcoco.metrics*), 117
BinaryConfusionVectors (*class in kwcoco.metrics.confusion_vectors*), 89
block_seen() (*kwcoco._helpers._ID_Remapper* method), 199
Boids (*class in kwcoco.demo.boids*), 36
BOOLEAN (*in module kwcoco.coco_schema*), 293
BOOLEAN (*in module kwcoco.util*), 171
BOOLEAN (*in module kwcoco.util.jsonschema_elements*), 137
BOOLEAN (*kwcoco.util.jsonschema_elements.ScalarElements* property), 134
BOOLEAN (*kwcoco.util.ScalarElements* property), 174
boundary_conditions() (*kwcoco.demo.boids.Boids* method), 37
boxes (*kwcoco.coco_objects1d.Annots* property), 289
boxsize_stats() (*kwcoco.coco_dataset.MixinCocoStats* method), 248
build() (*kwcoco.coco_dataset.CocoIndex* method), 261
build() (*kwcoco.coco_sql_dataset.CocoSqlIndex* method), 301
bundle_dpath (*kwcoco.coco_image.CocoImage* property), 278
bundle_dpath (*kwcoco.coco_sql_dataset.CocoSqlDatabase* property), 305

C

cached_sql_coco_view() (in module `kwcoco.coco_sql_dataset`), 305
 caption (`kwcoco.coco_sql_dataset.Annotation` attribute), 297
`caption` (`kwcoco.coco_sql_dataset.Video` attribute), 296
`Categories` (class in `kwcoco.coco_objectsId`), 286
`categories()` (`kwcoco.coco_dataset.MixinCocoObjects` method), 243
`Category` (class in `kwcoco.coco_sql_dataset`), 296
`CATEGORY` (in module `kwcoco.coco_schema`), 293
`category_annotation_frequency()` (`kwcoco.coco_dataset.MixinCocoStats` method), 245
`category_annotation_type_frequency()` (`kwcoco.coco_dataset.MixinCocoStats` method), 245
`category_graph()` (`kwcoco.coco_dataset.MixinCocoAccessors` method), 233
`category_id` (`kwcoco.coco_objectsId.Annots` property), 289
`category_id` (`kwcoco.coco_sql_dataset.Annotation` attribute), 297
`category_names` (`kwcoco.category_tree.CategoryTree` property), 206
`category_names` (`kwcoco.CategoryTree` property), 317
`CategoryPatterns` (class in `kwcoco.demo.toypatterns`), 62
`CategoryTree` (class in `kwcoco`), 313
`CategoryTree` (class in `kwcoco.category_tree`), 202
`catname` (`kwcoco.metrics.BinaryConfusionVectors` property), 118
`catname` (`kwcoco.metrics.confusion_measures.Measures` property), 78
`catname` (`kwcoco.metrics.confusion_vectors.BinaryConfusionVectors` property), 90
`catname` (`kwcoco.metrics.Measures` property), 125
`cats` (`kwcoco.category_tree.CategoryTree` property), 206
`cats` (`kwcoco.CategoryTree` property), 317
`cats` (`kwcoco.coco_dataset.MixinCocoIndex` property), 261
`cats` (`kwcoco.coco_sql_dataset.CocoSqlDatabase` property), 303
`catToImgs` (`kwcoco.compat_dataset.COCO` property), 306
`CHANNELS` (in module `kwcoco.coco_schema`), 293
`channels` (`kwcoco.coco_image.CocoImage` property), 278
`channels` (`kwcoco.coco_sql_dataset.Image` attribute), 297
`channels` (`kwcoco.util.DelayedChannelConcat` property), 180
`channels` (`kwcoco.util.DelayedCrop` property), 182
`channels` (`kwcoco.util.DelayedFrameConcat` property), 183
`channels` (`kwcoco.util.DelayedLoad` property), 187
`channels` (`kwcoco.util.DelayedNans` property), 190
`channels` (`kwcoco.util.DelayedWarp` property), 193
`channels` (`kwcoco.util.util_delayed_poc.DelayedChannelConcat` property), 157
`channels` (`kwcoco.util.util_delayed_poc.DelayedCrop` property), 163
`channels` (`kwcoco.util.util_delayed_poc.DelayedFrameConcat` property), 155
`channels` (`kwcoco.util.util_delayed_poc.DelayedLoad` property), 152
`channels` (`kwcoco.util.util_delayed_poc.DelayedNans` property), 149
`channels` (`kwcoco.util.util_delayed_poc.DelayedWarp` property), 160
`ChannelSpec` (class in `kwcoco`), 326
`ChannelSpec` (class in `kwcoco.channel_spec`), 214
`children()` (`kwcoco.util.DelayedChannelConcat` method), 179
`children()` (`kwcoco.util.DelayedCrop` method), 182
`children()` (`kwcoco.util.DelayedFrameConcat` method), 183
`children()` (`kwcoco.util.DelayedIdentity` method), 185
`children()` (`kwcoco.util.DelayedLoad` method), 187
`children()` (`kwcoco.util.DelayedNans` method), 190
`children()` (`kwcoco.util.DelayedVisionOperation` method), 191
`children()` (`kwcoco.util.DelayedWarp` method), 193
`children()` (`kwcoco.util.util_delayed_poc.DelayedChannelConcat` method), 157
`children()` (`kwcoco.util.util_delayed_poc.DelayedCrop` method), 163
`children()` (`kwcoco.util.util_delayed_poc.DelayedFrameConcat` method), 155
`children()` (`kwcoco.util.util_delayed_poc.DelayedIdentity` method), 149
`children()` (`kwcoco.util.util_delayed_poc.DelayedLoad` method), 152
`children()` (`kwcoco.util.util_delayed_poc.DelayedNans` method), 150
`children()` (`kwcoco.util.util_delayed_poc.DelayedVisionOperation` method), 147
`children()` (`kwcoco.util.util_delayed_poc.DelayedWarp` method), 160
`cid_to_aids` (`kwcoco.coco_dataset.MixinCocoIndex` property), 261
`cid_to_gids` (`kwcoco.coco_dataset.CocoIndex` property), 260
`cid_to_rgb()` (in module `kwcoco.data.grab_camvid`), 31
`cids` (`kwcoco.coco_objectsId.AnnotGroups` property), 290

cids (*kwcoco.coco_objects1d.Annots* property), 289
cids (*kwcoco.coco_objects1d.Categories* property), 287
clamp_mag() (*in module kwcoco.demo.boids*), 37
class_accuracy_from_confusion() (*in module kw-
coco.metrics.sklearn_alts*), 107
class_names (*kwcoco.category_tree.CategoryTree
property*), 206
class_names (*kwcoco.CategoryTree* property), 317
classification_report() (*in module kw-
coco.metrics.clf_report*), 74
classification_report() (*kw-
coco.metrics.confusion_vectors.ConfusionVectors
method*), 88
classification_report() (*kw-
coco.metrics.ConfusionVectors
method*), 124
clear() (*kwcoco.coco_dataset.CocoIndex* method), 261
clear() (*kwcoco.metrics.detect_metrics.DetectionMetrics
method*), 94
clear() (*kwcoco.metrics.DetectionMetrics* method), 112
clear_annotations() (*kw-
coco.coco_dataset.MixinCocoAddRemove
method*), 256
clear_images() (*kwcoco.coco_dataset.MixinCocoAddRemove
method*), 255
CLIConfig (*kwcoco.cli.coco_eval.CocoEvalCLI
attribute*), 17
close() (*kwcoco.util.Archive* method), 179
close() (*kwcoco.util.util_archive.Archive* method), 142
closest_point_on_line_segment() (*in module kw-
coco.demo.boids*), 39
cnames (*kwcoco.coco_objects1d.AnnotGroups* property),
290
cnames (*kwcoco.coco_objects1d.Annots* property), 289
coarsen() (*kwcoco.metrics.confusion_vectors.Confusion
method*), 87
coarsen() (*kwcoco.metrics.ConfusionVectors* method),
123
COCO (*class in kwcoco.compat_dataset*), 306
coco_image() (*kwcoco.coco_dataset.MixinCocoAccessors
method*), 234
coco_images (*kwcoco.coco_objects1d.Images
property*), 287
COCO_SAMPLER_CLS (*in module kw-
coco.coco_evaluator*), 272
COCO_SCHEMA (*in module kwcoco.coco_schema*), 294
coco_to_kpf() (*in module kwcoco.kpf*), 309
CocoBase (*in module kwcoco.coco_sql_dataset*), 296
CocoConformCLI (*class in kwcoco.cli.coco_conform*), 15
CocoConformCLI.CLICConfig (*class in kw-
coco.cli.coco_conform*), 15
CocoDataset (*class in kwcoco*), 318
CocoDataset (*class in kwcoco.coco_dataset*), 261
CocoEvalCLI (*class in kwcoco.cli.coco_eval*), 17
CocoEvalCLIConfig (*class in kwcoco.cli.coco_eval*), 16
CocoEvalConfig (*class in kwcoco.coco_evaluator*), 272
CocoEvaluator (*class in kwcoco.coco_evaluator*), 272
CocoGrabCLI (*class in kwcoco.cli.coco_grab*), 19
CocoGrabCLI.CLICConfig (*class in kw-
coco.cli.coco_grab*), 19
CocoImage (*class in kwcoco.coco_image*), 277
CocoIndex (*class in kwcoco.coco_dataset*), 259
CocoModifyCatsCLI (*class in kw-
coco.cli.coco_modify_categories*), 20
CocoModifyCatsCLI.CLICConfig (*class in kw-
coco.cli.coco_modify_categories*), 20
CocoRerootCLI (*class in kwcoco.cli.coco_reroot*), 21
CocoRerootCLI.CLICConfig (*class in kw-
coco.cli.coco_reroot*), 21
CocoResults (*class in kwcoco.coco_evaluator*), 274
CocoShowCLI (*class in kwcoco.cli.coco_show*), 22
CocoShowCLI.CLICConfig (*class in kw-
coco.cli.coco_show*), 22
CocoSingleResult (*class in kwcoco.coco_evaluator*),
275
CocoSplitCLI (*class in kwcoco.cli.coco_split*), 23
CocoSplitCLI.CLICConfig (*class in kw-
coco.cli.coco_split*), 23
CocoSqlDatabase (*class in kwcoco.coco_sql_dataset*),
301
CocoSqlIndex (*class in kwcoco.coco_sql_dataset*), 301
CocoStatsCLI (*class in kwcoco.cli.coco_stats*), 24
CocoStatsCLI.CLICConfig (*class in kw-
coco.cli.coco_stats*), 24
CocoSubsetCLI (*class in kwcoco.cli.coco_subset*), 25
CocoSubsetCLI.CLICConfig (*class in kw-
coco.cli.coco_subset*), 25
CocoToyDataCLI (*class in kwcoco.cli.coco_toydata*), 27
CocoToyDataCLI.CLICConfig (*class in kw-
coco.cli.coco_toydata*), 27
CocoUnionCLI (*class in kwcoco.cli.coco_union*), 28
CocoUnionCLI.CLICConfig (*class in kw-
coco.cli.coco_union*), 28
CocoValidateCLI (*class in kwcoco.cli.coco_validate*),
29
CocoValidateCLI.CLICConfig (*class in kw-
coco.cli.coco_validate*), 29
code_list() (*kwcoco.channel_spec.ChannelSpec
method*), 218
code_list() (*kwcoco.channel_spec.FusedChannelSpec
method*), 212
code_list() (*kwcoco.ChannelSpec* method), 330
code_list() (*kwcoco.FusedChannelSpec* method), 338
coerce() (*kwcoco.category_tree.CategoryTree* class
method), 204
coerce() (*kwcoco.CategoryTree* class method), 314
coerce() (*kwcoco.channel_spec.BaseChannelSpec* class
method), 209

coerce() (*kwcoco.channel_spec.ChannelSpec class method*), 216
coerce() (*kwcoco.channel_spec.FusedChannelSpec class method*), 211
coerce() (*kwcoco.ChannelSpec class method*), 328
coerce() (*kwcoco.coco_dataset.MixinCocoExtras class method*), 235
coerce() (*kwcoco.coco_sql_dataset.CocoSqlDatabase class method*), 305
coerce() (*kwcoco.demo.toypatterns.CategoryPatterns class method*), 62
coerce() (*kwcoco.FusedChannelSpec class method*), 336
coerce() (*kwcoco.util.Archive class method*), 178
coerce() (*kwcoco.util.DelayedLoad class method*), 187
coerce() (*kwcoco.util.util_archive.Archive class method*), 142
coerce() (*kwcoco.util.util_delayed_poc.DelayedLoad class method*), 152
combine() (*kwcoco.metrics.confusion_measures.Measure class method*), 83
combine() (*kwcoco.metrics.confusion_measures.Measures class method*), 79
combine() (*kwcoco.metrics.confusion_measures.OneVsRestCombiner class method*), 83
combine() (*kwcoco.metrics.Measures class method*), 126
component_indices() (*kwcoco.channel_spec.ChannelSpec method*), 221
component_indices() (*kwcoco.channel_spec.FusedChannelSpec method*), 213
component_indices() (*kwcoco.ChannelSpec method*), 334
component_indices() (*kwcoco.FusedChannelSpec method*), 339
compress() (*kwcoco.coco_objects1d.ObjectList1D method*), 283
compute_forces() (*kwcoco.demo.boids.Boids method*), 37
concat() (*kwcoco.channel_spec.FusedChannelSpec class method*), 211
concat() (*kwcoco.FusedChannelSpec class method*), 336
concise_si_display() (*in module kwcoco.metrics.drawing*), 100
concise() (*kwcoco.channel_spec.ChannelSpec method*), 216
concise() (*kwcoco.channel_spec.FusedChannelSpec method*), 211
concise() (*kwcoco.ChannelSpec method*), 329
concise() (*kwcoco.FusedChannelSpec method*), 336
Config (*kwcoco.coco_evaluator.CocoEvaluator at- tribute*), 273
conform() (*kwcoco.coco_dataset.MixinCocoStats method*), 245
confusion_matrix() (*in module kwcoco.metrics.sklearn_alts*), 106
confusion_matrix() (*kwcoco.metrics.confusion_vectors.ConfusionVectors method*), 86
confusion_matrix() (*kwcoco.metrics.ConfusionVectors method*), 122
confusion_vectors() (*kwcoco.metrics.detect_metrics.DetectionMetrics method*), 95
confusion_vectors() (*kwcoco.metrics.DetectionMetrics method*), 113
ConfusionVectors (*class in kwcoco.metrics*), 120
ConfusionVectors (*class in kwcoco.metrics.confusion_vectors*), 84
connect() (*kwcoco.coco_sql_dataset.CocoSqlDatabase method*), 303
ContainerElements (*class in kwcoco.util*), 171
ContainerElements (*class in kwcoco.util.jsonschema_elements*), 135
convert_camvid_raw_to_coco() (*in module kwcoco.data.grab_camvid*), 31
convert_cifar10() (*in module kwcoco.data.grab_cifar*), 32
convert_cifar100() (*in module kwcoco.data.grab_cifar*), 32
convert_spacenet_to_kwccoco() (*in module kwcoco.data.grab_spacenet*), 34
convert_voc_to_coco() (*in module kwcoco.data.grab_voc*), 35
copy() (*kwcoco.category_tree.CategoryTree method*), 203
copy() (*kwcoco.CategoryTree method*), 314
copy() (*kwcoco.coco_dataset.CocoDataset method*), 264
copy() (*kwcoco.CocoDataset method*), 321
copy() (*kwcoco.util.dict_like.DictLike method*), 131
copy() (*kwcoco.util.DictLike method*), 171
corrupted_images() (*kwcoco.coco_dataset.MixinCocoExtras method*), 239
counts() (*kwcoco.metrics.confusion_measures.Measures method*), 78
counts() (*kwcoco.metrics.Measures method*), 125
createIndex() (*kwcoco.compat_dataset.COCO method*), 306
crop() (*kwcoco.util.DelayedVisionOperation method*), 191
crop() (*kwcoco.util.util_delayed_poc.DelayedVisionOperation*)

method), 147

D

`data_fpath` (`kwcoco.coco_dataset.MixinCocoExtras`
 property), 242
`data_fpath` (`kwcoco.coco_sql_dataset.CocoSqlDatabase`
 property), 305
`data_root` (`kwcoco.coco_dataset.MixinCocoExtras`
 property), 242
`dataset` (`kwcoco.coco_sql_dataset.CocoSqlDatabase`
 property), 303
`dataset_modification_example_via_construction()`
 (*in* *module* *kw-*
 coco.examples.modification_example), 67
`dataset_modification_example_via_copy()`
 (*in* *module* *kw-*
 coco.examples.modification_example), 67
`DatasetBase` (*in* *module* *kw-*
 coco.examples.simple_kwccoco_torch_dataset),
 68
`decode()` (`kwcoco.channel_spec.ChannelSpec` *method*),
 221
`decode()` (`kwcoco.ChannelSpec` *method*), 333
`default` (`kwcoco.cli.coco_conform.CocoConformCLI`.
 CLICConfig *attribute*), 15
`default` (`kwcoco.cli.coco_eval.CocoEvalCLIConfig` *at-*
 tribute), 17
`default` (`kwcoco.cli.coco_grab.CocoGrabCLI`.
 CLICConfig *attribute*), 19
`default` (`kwcoco.cli.coco_modify_categories.CocoModify`
 CatsCLI.
 CLICConfig *attribute*), 20
`default` (`kwcoco.cli.coco_reroot.CocoRerootCLI`.
 CLICConfig *attribute*), 21
`default` (`kwcoco.cli.coco_show.CocoShowCLI`.
 CLICConfig *attribute*), 22
`default` (`kwcoco.cli.coco_split.CocoSplitCLI`.
 CLICConfig *attribute*), 23
`default` (`kwcoco.cli.coco_stats.CocoStatsCLI`.
 CLICConfig *attribute*), 24
`default` (`kwcoco.cli.coco_subset.CocoSubsetCLI`.
 CLICConfig *attribute*), 25
`default` (`kwcoco.cli.coco_toydata.CocoToyDataCLI`.
 CLICConfig *attribute*), 27
`default` (`kwcoco.cli.coco_union.CocoUnionCLI`.
 CLICConfig *attribute*), 28
`default` (`kwcoco.cli.coco_validate.CocoValidateCLI`.
 CLICConfig *attribute*), 29
`default` (`kwcoco.coco_evaluator.CocoEvalConfig`
 attribute), 272
`DEFAULT_COLUMNS` (`kwcoco.kw18.KW18` *attribute*), 310
`delay()` (`kwcoco.coco_image.CocoImage` *method*), 280
`delayed_crop()` (`kwcoco.util.DelayedFrameConcat`
 method), 183
`DelayedCrop()` (`kwcoco.util.DelayedImageOperation`
 method), 185
`DelayedCrop()` (`kwcoco.util.DelayedLoad` *method*),
 187
`DelayedCrop()` (`kwcoco.util.DelayedNans` *method*),
 190
`DelayedCrop()` (`kwcoco.util.util_delayed_poc.DelayedFrameConcat`
 method), 155
`DelayedCrop()` (`kwcoco.util.util_delayed_poc.DelayedImageOperation`
 method), 147
`DelayedCrop()` (`kwcoco.util.util_delayed_poc.DelayedLoad`
 method), 152
`DelayedCrop()` (`kwcoco.util.util_delayed_poc.DelayedNans`
 method), 150
`DelayedLoad()` (`kwcoco.coco_dataset.MixinCocoAccessors`
 method), 229
`DelayedWarp()` (`kwcoco.util.DelayedChannelConcat`
 method), 180
`DelayedWarp()` (`kwcoco.util.DelayedFrameConcat`
 method), 184
`DelayedWarp()` (`kwcoco.util.DelayedImageOperation`
 method), 186
`DelayedWarp()` (`kwcoco.util.DelayedNans` *method*),
 191
`DelayedWarp()` (`kwcoco.util.util_delayed_poc.DelayedChannelConcat`
 method), 157
`DelayedWarp()` (`kwcoco.util.util_delayed_poc.DelayedFrameConcat`
 method), 156
`DelayedWarp()` (`kwcoco.util.util_delayed_poc.DelayedImageOperation`
 method), 148
`DelayedWarp()` (`kwcoco.util.util_delayed_poc.DelayedNans`
 method), 151
`DelayedChannelConcat` (*class* *in* `kwcoco.util`), 179
`DelayedChannelConcat` (*class* *in* *kw-*
 coco.util.util_delayed_poc), 156
`DelayedCrop` (*class* *in* `kwcoco.util`), 181
`DelayedCrop` (*class* *in* `kwcoco.util.util_delayed_poc`),
 162
`DelayedFrameConcat` (*class* *in* `kwcoco.util`), 182
`DelayedFrameConcat` (*class* *in* *kw-*
 coco.util.util_delayed_poc), 154
`DelayedIdentity` (*class* *in* `kwcoco.util`), 184
`DelayedIdentity` (*class* *in* *kw-*
 coco.util.util_delayed_poc), 148
`DelayedImageOperation` (*class* *in* `kwcoco.util`), 185
`DelayedImageOperation` (*class* *in* *kw-*
 coco.util.util_delayed_poc), 147
`DelayedLoad` (*class* *in* `kwcoco.util`), 186
`DelayedLoad` (*class* *in* `kwcoco.util.util_delayed_poc`),
 151
`DelayedNans` (*class* *in* `kwcoco.util`), 189
`DelayedNans` (*class* *in* `kwcoco.util.util_delayed_poc`),
 149
`DelayedVideoOperation` (*class* *in* `kwcoco.util`), 191

DelayedVideoOperation (class in `coco.util.util_delayed_poc`), 147
DelayedVisionOperation (class in `kwcoco.util`), 191
DelayedVisionOperation (class in `kwcoco.util.util_delayed_poc`), 147
DelayedWarp (class in `kwcoco.util`), 191
DelayedWarp (class in `kwcoco.util.util_delayed_poc`), 159
delete() (`kwcoco.coco_sql_dataset.CocoSqlDatabase` method), 303
delitem() (`kwcoco.util.dict_like.DictLike` method), 131
delitem() (`kwcoco.util.DictLike` method), 171
demo() (in module `kwcoco.coco_sql_dataset`), 305
demo() (in module `kwcoco.kpf`), 309
demo() (`kwcoco.category_tree.CategoryTree` class method), 204
demo() (`kwcoco.CategoryTree` class method), 315
demo() (`kwcoco.coco_dataset.MixinCocoExtras` class method), 235
demo() (`kwcoco.kw18.KW18` class method), 310
demo() (`kwcoco.metrics.BinaryConfusionVectors` class method), 118
demo() (`kwcoco.metrics.confusion_measures.Measures` class method), 79
demo() (`kwcoco.metrics.confusion_vectors.BinaryConfusionVector` class method), 90
demo() (`kwcoco.metrics.confusion_vectors.ConfusionVector` class method), 86
demo() (`kwcoco.metrics.confusion_vectors.OneVsRestConfusionVector` class method), 89
demo() (`kwcoco.metrics.ConfusionVectors` class method), 122
demo() (`kwcoco.metrics.detect_metrics.DetectionMetrics` class method), 97
demo() (`kwcoco.metrics.DetectionMetrics` class method), 115
demo() (`kwcoco.metrics.Measures` class method), 126
demo() (`kwcoco.metrics.OneVsRestConfusionVectors` class method), 129
demo() (`kwcoco.util.DelayedIdentity` class method), 185
demo() (`kwcoco.util.DelayedLoad` class method), 187
demo() (`kwcoco.util.lazy_frame_backends.LazyGDalFrame` class method), 140
demo() (`kwcoco.util.LazyGDalFrameFile` class method), 177
demo() (`kwcoco.util.util_delayed_poc.DelayedIdentity` class method), 149
demo() (`kwcoco.util.util_delayed_poc.DelayedLoad` class method), 152
demo_coco_data() (in module `kwcoco.coco_dataset`), 270
demo_format_options() (in module `coco.metrics.drawing`), 100
demo_load_msi_data() (in module `kwcoco`), 270
coco.examples.loading_multispectral_data, 67
demo_vectorize_interface() (in module `kwcoco.examples.getting_started_existing_dataset`), 66
demo_vectorized_interface() (in module `kwcoco.examples.vectorized_interface`), 69
demodata_toy_dset() (in module `kwcoco.demo.toydata`), 45
demodata_toy_dset() (in module `kwcoco.demo.toydata_image`), 49
demodata_toy_img() (in module `kwcoco.demo.toydata`), 47
demodata_toy_img() (in module `kwcoco.demo.toydata_image`), 50
deprecated() (in module `kwcoco.coco_schema`), 293
detach() (`kwcoco.coco_image.CocoImage` method), 278
DetectionMetrics (class in `kwcoco.metrics`), 111
DetectionMetrics (class in `kwcoco.metrics.detect_metrics`), 93
detections (`kwcoco.coco_objects1d.Annots` property), 289
devcheck() (in module `kwcoco.coco_sql_dataset`), 305
DictLike (class in `kwcoco.util`), 170
DictLike (class in `kwcoco.util.dict_like`), 131
DictProxy (class in `kwcoco.metrics.util`), 108
difference() (`kwcoco.channel_spec.BaseChannelSpec` method), 210
difference() (`kwcoco.channel_spec.ChannelSpec` method), 218
difference() (`kwcoco.channel_spec.FusedChannelSpec` method), 213
difference() (`kwcoco.ChannelSpec` method), 330
difference() (`kwcoco.FusedChannelSpec` method), 338
disconnect() (`kwcoco.coco_sql_dataset.CocoSqlDatabase` method), 303
dmet_area_weights() (in module `kwcoco.coco_evaluator`), 274
download() (`kwcoco.compat_dataset.COCO` method), 308
draw() (`kwcoco.metrics.confusion_measures.Measures` method), 78
draw() (`kwcoco.metrics.confusion_measures.PerClass_Measures` method), 81
draw() (`kwcoco.metrics.Measures` method), 125
draw() (`kwcoco.metrics.PerClass_Measures` method), 129
draw_distribution() (`kwcoco.metrics.BinaryConfusionVectors` method), 119
draw_distribution() (`kwcoco.metrics.confusion_vectors.BinaryConfusionVectors` method), 92

draw_image() (kwCOCO.coco_dataset.MixinCocoDraw method), 249
draw_perclass_prcurve() (in module kwCOCO.coco.metrics.drawing), 102
draw_perclass_roc() (in module kwCOCO.coco.metrics.drawing), 100
draw_perclass_thresholds() (in module kwCOCO.coco.metrics.drawing), 102
draw_pr() (kwCOCO.metrics.confusion_measures.PerClass method), 82
draw_pr() (kwCOCO.metrics.PerClass_Measures method), 130
draw_prcurve() (in module kwCOCO.metrics.drawing), 103
draw_roc() (in module kwCOCO.metrics.drawing), 103
draw_roc() (kwCOCO.metrics.confusion_measures.PerClass method), 82
draw_roc() (kwCOCO.metrics.PerClass_Measures method), 130
draw_threshold_curves() (in module kwCOCO.coco.metrics.drawing), 104
draw_true_and_pred_boxes() (in module kwCOCO.examples.draw_gt_and_predicted_boxes), 65
dszie (kwCOCO.coco_image.CocoImage property), 278
dszie (kwCOCO.util.DelayedLoad property), 187
dszie (kwCOCO.util.DelayedNans property), 190
dszie (kwCOCO.util.DelayedWarp property), 193
dszie (kwCOCO.util.util_delayed_poc.DelayedLoad property), 152
dszie (kwCOCO.util.util_delayed_poc.DelayedNans property), 149
dszie (kwCOCO.util.util_delayed_poc.DelayedWarp property), 160
dtype (kwCOCO.util.lazy_frame_backends.LazyGDalFrameFile property), 140
dtype (kwCOCO.util.lazy_frame_backends.LazyRasterIOFrameFile property), 139
dtype (kwCOCO.util.lazy_frame_backends.LazySpectralFrameFile property), 139
dtype (kwCOCO.util.LazyGDalFrameFile property), 177
dtype (kwCOCO.util.LazyRasterIOFrameFile property), 177
dtype (kwCOCO.util.LazySpectralFrameFile property), 177
dump() (kwCOCO.coco_dataset.CocoDataset method), 265
dump() (kwCOCO.coco_evaluator.CocoResults method), 275
dump() (kwCOCO.coco_evaluator.CocoSingleResult method), 276
dump() (kwCOCO.CocoDataset method), 322
dump() (kwCOCO.kw18.KW18 method), 312
dump_figures() (kwCOCO.coco_evaluator.CocoResults method), 275
dump_figures() (kwCOCO.coco_evaluator.CocoSingleResult method), 276
dumps() (kwCOCO.coco_dataset.CocoDataset method), 265
dumps() (kwCOCO.CocoDataset method), 321
dumps() (kwCOCO.kw18.KW18 method), 312

Measures

eff() (kwCOCO.demo.toypatterns.Rasters static method), 64
elem (in module kwCOCO.coco_schema), 293
elem (in module kwCOCO.util), 176
elem (in module kwCOCO.util.jsonschema_elements), 137
Element (class in kwCOCO.util), 172
Element (class in kwCOCO.util.jsonschema_elements), 133
encode() (kwCOCO.channel_spec.ChannelSpec method), 219
encode() (kwCOCO.ChannelSpec method), 332
ensure_category() (kwCOCO.coco_dataset.MixinCocoAddRemove method), 254
ensure_image() (kwCOCO.coco_dataset.MixinCocoAddRemove method), 254
ensure_json_serializable() (in module kwCOCO.coco.util), 194
ensure_json_serializable() (in module kwCOCO.util.json), 164
ensure_sql_coco_view() (in module kwCOCO.coco_sql_dataset), 305
ensure_voc_coco() (in module kwCOCO.data.grab_voc), 35
ensure_voc_data() (in module kwCOCO.coco.data.grab_voc), 35
epilog (kwCOCO.cli.coco_conform.CocoConformCLI.CLICConfig attribute), 15
epilog (kwCOCO.cli.coco_modify_categories.CocoModifyCatsCLI.CLICConfig attribute), 20
epilog (kwCOCO.cli.coco_reroot.CocoRerootCLI.CLICConfig attribute), 21
epilog (kwCOCO.cli.coco_show.CocoShowCLI.CLICConfig attribute), 22
epilog (kwCOCO.cli.coco_split.CocoSplitCLI.CLICConfig attribute), 23
epilog (kwCOCO.cli.coco_stats.CocoStatsCLI.CLICConfig attribute), 24
epilog (kwCOCO.cli.coco_subset.CocoSubsetCLI.CLICConfig attribute), 25
epilog (kwCOCO.cli.coco_toydata.CocoToyDataCLI.CLICConfig attribute), 27
epilog (kwCOCO.cli.coco_union.CocoUnionCLI.CLICConfig attribute), 28

`epilog(kwcoco.cli.coco_validate.CocoValidateCLI.CLIConfig_finalize() (kwcoco.util.util_delayed_poc.DelayedLoad attribute), 29`

`eval_detections_cli() (in module kwcoco.metrics), 117`

`eval_detections_cli() (in module kwcoco.metrics.detect_metrics), 99`

`evaluate() (kwcoco.coco_evaluator.CocoEvaluator method), 274`

`extended_stats() (kwcoco.coco_dataset.MixinCocoStats method), 247`

`extra (kwcoco.coco_sql_dataset.Annotation attribute), 297`

`extra (kwcoco.coco_sql_dataset.Category attribute), 296`

`extra (kwcoco.coco_sql_dataset.Image attribute), 297`

`extra (kwcoco.coco_sql_dataset.KeypointCategory attribute), 296`

`extra (kwcoco.coco_sql_dataset.Video attribute), 296`

`extractall() (kwcoco.util.Archive method), 179`

`extractall() (kwcoco.util.util_archive.Archive method), 142`

F

`false_color() (in module kwcoco.demo.toydata_video), 60`

`fast_confusion_matrix() (in module kwcoco.metrics.functional), 105`

`file_name (kwcoco.coco_sql_dataset.Image attribute), 297`

`finalize() (kwcoco.metrics.confusion_measures.Measure method), 83`

`finalize() (kwcoco.metrics.confusion_measures.OneVersusRestMeasure), 83`

`finalize() (kwcoco.util.DelayedChannelConcat method), 180`

`finalize() (kwcoco.util.DelayedCrop method), 182`

`finalize() (kwcoco.util.DelayedFrameConcat method), 183`

`finalize() (kwcoco.util.DelayedIdentity method), 185`

`finalize() (kwcoco.util.DelayedLoad method), 187`

`finalize() (kwcoco.util.DelayedNans method), 190`

`finalize() (kwcoco.util.DelayedVisionOperation method), 191`

`finalize() (kwcoco.util.DelayedWarp method), 193`

`finalize() (kwcoco.util.util_delayed_poc.DelayedChannelConcat method), 157`

`finalize() (kwcoco.util.util_delayed_poc.DelayedCrop method), 163`

`finalize() (kwcoco.util.util_delayed_poc.DelayedFrameConcat method), 155`

`finalize() (kwcoco.util.util_delayed_poc.DelayedIdentity method), 149`

`finalize() (kwcoco.util.util_delayed_poc.DelayedLoad method), 152`

`finalize() (kwcoco.util.util_delayed_poc.DelayedNans method), 150`

`finalize() (kwcoco.util.util_delayed_poc.DelayedVisionOperation method), 147`

`finalize() (kwcoco.util.util_delayed_poc.DelayedWarp method), 161`

`find_json_unserializable() (in module kwcoco.util), 195`

`find_json_unserializable() (in module kwcoco.util.util_json), 164`

`findRepresentativeImages() (kwcoco.coco_dataset.MixinCocoStats method), 248`

`forest_str() (kwcoco.category_tree.CategoryTree method), 207`

`forest_str() (kwcoco.CategoryTree method), 318`

`fpPath(kwcoco.coco_dataset.CocoDataset property), 264`

`fpPath (kwcoco.coco_sql_dataset.CocoSqlDatabase property), 303`

`fpPath (kwcoco.CocoDataset property), 320`

`fpPath (kwcoco.util.DelayedLoad property), 187`

`fpPath (kwcoco.util.util_delayed_poc.DelayedLoad property), 152`

`frame_index (kwcoco.coco_sql_dataset.Image attribute), 297`

`from_arrays() (kwcoco.metrics.confusion_vectors.ConfusionVectors class method), 86`

`from_arrays() (kwcoco.metrics.ConfusionVectors class method), 122`

`from_coco() (kwcoco.category_tree.CategoryTree class method), 204`

`from_coco() (kwcoco.CategoryTree class method), 314`

`from_coco() (kwcoco.kw18.KW18 class method), 310`

`from_coco() (kwcoco.metrics.detect_metrics.DetectionMetrics class method), 94`

`from_coco() (kwcoco.metrics.DetectionMetrics class method), 112`

`from_coco_paths() (kwcoco.coco_dataset.CocoDataset class method), 264`

`from_coco_paths() (kwcoco.CocoDataset class method), 320`

`from_data() (kwcoco.coco_dataset.CocoDataset class method), 264`

`from_data() (kwcoco.CocoDataset class method), 320`

`from_gid() (kwcoco.coco_image.CocoImage class method), 278`

`fromImagePaths() (kwcoco.coco_dataset.CocoDataset class method), 264`

`fromImagePaths() (kwcoco.CocoDataset class method), 320`

from_json() (kwcoco.category_tree.CategoryTree class method), 204
from_json() (kwcoco.CategoryTree class method), 314
from_json() (kwcoco.coco_evaluator.CocoResults class method), 275
from_json() (kwcoco.coco_evaluator.CocoSingleResult class method), 276
from_json() (kwcoco.metrics.confusion_measures.Measures class method), 78
from_json() (kwcoco.metrics.confusion_measures.PerClass_Measures class method), 81
from_json() (kwcoco.metrics.confusion_vectors.ConfusionVector class method), 86
from_json() (kwcoco.metrics.ConfusionVectors class method), 122
from_json() (kwcoco.metrics.Measures class method), 125
from_json() (kwcoco.metrics.PerClass_Measures class method), 129
from_mutex() (kwcoco.category_tree.CategoryTree class method), 203
from_mutex() (kwcoco.CategoryTree class method), 314
fuse() (kwcoco.channel_spec.ChannelSpec method), 217
fuse() (kwcoco.channel_spec.FusedChannelSpec method), 214
fuse() (kwcoco.ChannelSpec method), 330
fuse() (kwcoco.FusedChannelSpec method), 339
FusedChannelSpec (class in kwcoco), 335
FusedChannelSpec (class in kwcoco.channel_spec), 210

G

get() (kwcoco._helpers._NextId method), 198
get() (kwcoco.coco_image.CocoImage method), 278
get() (kwcoco.coco_objects1d.ObjectList1D method), 284
get() (kwcoco.demo.toypatterns.CategoryPatterns method), 63
get() (kwcoco.util.dict_like.DictLike method), 132
get() (kwcoco.util.DictLike method), 171
get_auxiliary_fpath() (kwcoco.coco_dataset.MixinCocoAccessors method), 231
get_image_fpath() (kwcoco.coco_dataset.MixinCocoAccessors method), 231
get_images_with_videoid() (in module kwcoco.examples.faq), 66
getAnnIds() (kwcoco.compat_dataset.COCO method), 306
getCatIds() (kwcoco.compat_dataset.COCO method), 307

getImgIds() (kwcoco.compat_dataset.COCO method), 307
getitem() (kwcoco.util.dict_like.DictLike method), 131
getitem() (kwcoco.util.DictLike method), 171
getting_started_existing_dataset() (in module kwcoco.examples.getting_started_existing_dataset), 66
gid_to_aids (kwcoco.coco_dataset.MixinCocoIndex property), 261
gids (kwcoco.coco_objects1d.Annots property), 289
gids (kwcoco.coco_objects1d.Images property), 287
global_accuracy_from_confusion() (in module kwcoco.metrics.sklearn_alts), 107
gname (kwcoco.coco_objects1d.Images property), 287
gpath (kwcoco.coco_objects1d.Images property), 287
grab_camvid_sampler() (in module kwcoco.data.grab_camvid), 30
grab_camvid_train_test_val_splits() (in module kwcoco.data.grab_camvid), 30
grab_coco_camvid() (in module kwcoco.data.grab_camvid), 31
grab_domain_net() (in module kwcoco.data.grab_domainnet), 33
grab_raw_camvid() (in module kwcoco.data.grab_camvid), 31
grab_spacenet7() (in module kwcoco.data.grab_spacenet), 34

H

height (kwcoco.coco_objects1d.Images property), 287
height (kwcoco.coco_sql_dataset.Image attribute), 297
height (kwcoco.coco_sql_dataset.Video attribute), 296

I

id (kwcoco.coco_sql_dataset.Annotation attribute), 297
id (kwcoco.coco_sql_dataset.Category attribute), 296
id (kwcoco.coco_sql_dataset.Image attribute), 297
id (kwcoco.coco_sql_dataset.KeypointCategory attribute), 296
id (kwcoco.coco_sql_dataset.Video attribute), 296
id_to_idx() (kwcoco.category_tree.CategoryTree method), 205
id_to_idx() (kwcoco.CategoryTree method), 315
idx_pairwise_distance() (kwcoco.category_tree.CategoryTree method), 205
idx_pairwise_distance() (kwcoco.CategoryTree method), 316
idx_to_ancestor_idxs() (kwcoco.category_tree.CategoryTree method), 205
idx_to_ancestor_idxs() (kwcoco.CategoryTree method), 316

`idx_to_descendants_idxs()` (*kw-
coco.category_tree.CategoryTree method*), 205
`idx_to_descendants_idxs()` (*kwcoco.CategoryTree method*), 316
`idx_to_id()` (*kwcoco.category_tree.CategoryTree method*), 205
`idx_to_id()` (*kwcoco.CategoryTree method*), 316
`Image` (*class in kwcoco.coco_sql_dataset*), 296
`IMAGE` (*in module kwcoco.coco_schema*), 294
`image_id` (*kwcoco.coco_objects1d.Annots property*), 289
`image_id` (*kwcoco.coco_sql_dataset.Annotation attribute*), 297
`ImageGroups` (*class in kwcoco.coco_objects1d*), 290
`Images` (*class in kwcoco.coco_objects1d*), 287
`images` (*kwcoco.coco_objects1d.Annots property*), 289
`images` (*kwcoco.coco_objects1d.Videos property*), 287
`images()` (*kwcoco.coco_dataset.MixinCocoObjects method*), 243
`img_root` (*kwcoco.coco_dataset.MixinCocoExtras property*), 242
`imgs` (*kwcoco.coco_dataset.MixinCocoIndex property*), 261
`imgs` (*kwcoco.coco_sql_dataset.CocoSqlDatabase property*), 303
`imgToAnns` (*kwcoco.compat_dataset.COCO property*), 306
`imread()` (*kwcoco.coco_dataset.MixinCocoDraw method*), 249
`index()` (*kwcoco.category_tree.CategoryTree method*), 207
`index()` (*kwcoco.CategoryTree method*), 318
`index()` (*kwcoco.demo.toypatterns.CategoryPatterns method*), 63
`indexable_allclose()` (*in module kwcoco.util*), 196
`indexable_allclose()` (*in module kw-
coco.util.util_json*), 165
`IndexableWalker` (*in module kwcoco.util*), 194
`IndexableWalker` (*in module kwcoco.util.util_json*), 164
`info` (*kwcoco.channel_spec.ChannelSpec property*), 216
`info` (*kwcoco.ChannelSpec property*), 328
`info()` (*kwcoco.compat_dataset.COCO method*), 306
`initialize()` (*kwcoco.demo.boids.Boids method*), 37
`INTEGER` (*in module kwcoco.coco_schema*), 293
`INTEGER` (*in module kwcoco.util*), 174
`INTEGER` (*in module kwcoco.util.jsonschema_elements*), 137
`INTEGER` (*kwcoco.util.jsonschema_elements.ScalarElements property*), 134
`INTEGER` (*kwcoco.util.ScalarElements property*), 175
`intersection()` (*kwcoco.channel_spec.BaseChannelSpec method*), 210
`intersection()` (*kwcoco.channel_spec.ChannelSpec method*), 218
`intersection()` (*kwcoco.channel_spec.FusedChannelSpec method*), 213
`intersection()` (*kwcoco.ChannelSpec method*), 331
`intersection()` (*kwcoco.FusedChannelSpec method*), 338
`is_mutex()` (*kwcoco.category_tree.CategoryTree method*), 206
`is_mutex()` (*kwcoco.CategoryTree method*), 317
`iscrowd` (*kwcoco.coco_sql_dataset.Annotation attribute*), 297
`items()` (*kwcoco.channel_spec.ChannelSpec method*), 217
`items()` (*kwcoco.ChannelSpec method*), 330
`items()` (*kwcoco.coco_sql_dataset.SqlDictProxy method*), 300
`items()` (*kwcoco.coco_sql_dataset.SqlIdGroupDictProxy method*), 301
`items()` (*kwcoco.util.dict_like.DictLike method*), 131
`items()` (*kwcoco.util.DictLike method*), 171
`iter_asset_objs()` (*kwcoco.coco_image.CocoImage method*), 279
`iter_image_filepaths()` (*kw-
coco.coco_image.CocoImage method*), 279

K

`keypoint_annotation_frequency()` (*kw-
coco.coco_dataset.MixinCocoStats method*), 244
`keypoint_categories()` (*kw-
coco.coco_dataset.MixinCocoAccessors method*), 234
`KEYPOINT_CATEGORY` (*in module kwcoco.coco_schema*), 293
`KeypointCategory` (*class in kwcoco.coco_sql_dataset*), 296
`KEYPOINTS` (*in module kwcoco.coco_schema*), 293
`keypoints` (*kwcoco.coco_sql_dataset.Annotation attribute*), 297
`keys()` (*kwcoco.channel_spec.ChannelSpec method*), 217
`keys()` (*kwcoco.ChannelSpec method*), 330
`keys()` (*kwcoco.coco_image.CocoImage method*), 278
`keys()` (*kwcoco.coco_sql_dataset.SqlDictProxy method*), 300
`keys()` (*kwcoco.coco_sql_dataset.SqlIdGroupDictProxy method*), 301
`keys()` (*kwcoco.metrics.confusion_vectors.OneVsRestConfusionVectors method*), 89
`keys()` (*kwcoco.metrics.OneVsRestConfusionVectors method*), 129
`keys()` (*kwcoco.metrics.util.DictProxy method*), 108
`keys()` (*kwcoco.util.dict_like.DictLike method*), 131

keys() (*kwcoco.util.DictLike method*), 171
KW18 (*class in kwcoco.kw18*), 310
kwcoco
 module, 9
kwcoco.__init__
 module, 1
kwcoco.__main__
 module, 198
kwcoco._helpers
 module, 198
kwcoco.abstract_coco_dataset
 module, 201
kwcoco.category_tree
 module, 202
kwcoco.channel_spec
 module, 207
kwcoco.cli
 module, 14
kwcoco.cli.__main__
 module, 14
kwcoco.cli.coco_conform
 module, 15
kwcoco.cli.coco_eval
 module, 16
kwcoco.cli.coco_grab
 module, 19
kwcoco.cli.coco_modify_categories
 module, 19
kwcoco.cli.coco_reroot
 module, 21
kwcoco.cli.coco_show
 module, 22
kwcoco.cli.coco_split
 module, 23
kwcoco.cli.coco_stats
 module, 24
kwcoco.cli.coco_subset
 module, 25
kwcoco.cli.coco_toydata
 module, 27
kwcoco.cli.coco_union
 module, 28
kwcoco.cli.coco_validate
 module, 29
kwcoco.coco_dataset
 module, 223
kwcoco.coco_evaluator
 module, 270
kwcoco.coco_image
 module, 277
kwcoco.coco_objects1d
 module, 282
kwcoco.coco_schema
 module, 290
kwcoco.coco_sql_dataset
 module, 294
kwcoco.compat_dataset
 module, 306
kwcoco.data
 module, 30
kwcoco.data.grab_camvid
 module, 30
kwcoco.data.grab_cifar
 module, 32
kwcoco.data.grab_datasets
 module, 32
kwcoco.data.grab_domainnet
 module, 33
kwcoco.data.grab_spacenet
 module, 33
kwcoco.data.grab_voc
 module, 34
kwcoco.demo
 module, 36
kwcoco.demo.boids
 module, 36
kwcoco.demo.perterb
 module, 40
kwcoco.demo.toydata
 module, 41
kwcoco.demo.toydata_image
 module, 49
kwcoco.demo.toydata_video
 module, 53
kwcoco.demo.toypatterns
 module, 61
kwcoco.examples
 module, 64
kwcoco.examples.bench_large_hyperspectral
 module, 64
kwcoco.examples.draw_gt_and_predicted_boxes
 module, 65
kwcoco.examples.faq
 module, 66
kwcoco.examples.getting_started_existing_dataset
 module, 66
kwcoco.examples.loading_multispectral_data
 module, 67
kwcoco.examples.modification_example
 module, 67
kwcoco.examples.simple_kwcoco_torch_dataset
 module, 67
kwcoco.examples.vectorized_interface
 module, 69
kwcoco.kpf
 module, 309
kwcoco.kw18
 module, 309

kwcoco.metrics
 module, 69
kwcoco.metrics.assignment
 module, 69
kwcoco.metrics.clf_report
 module, 74
kwcoco.metrics.confusion_measures
 module, 77
kwcoco.metrics.confusion_vectors
 module, 84
kwcoco.metrics.detect_metrics
 module, 93
kwcoco.metrics.drawing
 module, 100
kwcoco.metrics.functional
 module, 104
kwcoco.metrics.sklearn_alts
 module, 106
kwcoco.metrics.util
 module, 108
kwcoco.metrics.voc_metrics
 module, 108
kwcoco.util
 module, 131
kwcoco.util.dict_like
 module, 131
kwcoco.util.jsonschema_elements
 module, 132
kwcoco.util.lazy_frame_backends
 module, 138
kwcoco.util.util_archive
 module, 141
kwcoco.util.util_delayed_poc
 module, 143
kwcoco.util.util_futures
 module, 164
kwcoco.util.util_json
 module, 164
kwcoco.util.util_monkey
 module, 166
kwcoco.util.util_sklearn
 module, 167
kwcoco.util.util_truncate
 module, 168
KWCOCO_KEYPOINT (in module `kwcoco.coco_schema`), 293
KWCOCO_KEYPOINTS (in module `kwcoco.coco_schema`), 293
KWCOCO_POLYGON (in module `kwcoco.coco_schema`), 293
KWCocoSimpleTorchDataset (class in `kwcoco.examples.simple_kwcoco_torch_dataset`), 68

L

LazyGDalFrameFile (class in `kwcoco.util`), 176
LazyGDalFrameFile (class in `kwcoco.util.lazy_frame_backends`), 139
LazyRasterIOFrameFile (class in `kwcoco.util`), 177
LazyRasterIOFrameFile (class in `kwcoco.util.lazy_frame_backends`), 139
LazySpectralFrameFile (class in `kwcoco.util`), 177
LazySpectralFrameFile (class in `kwcoco.util.lazy_frame_backends`), 139
load() (`kwcoco.kw18.KW18` class method), 311
load_annot_sample() (kw-
`coco.coco_dataset.MixinCocoAccessors`
 method), 231
load_image() (`kwcoco.coco_dataset.MixinCocoAccessors`
 method), 230
load_shape() (`kwcoco.util.DelayedLoad` method), 187
load_shape() (`kwcoco.util.util_delayed_poc.DelayedLoad`
 method), 152
loadAnns() (`kwcoco.compat_dataset.COCO` method),
 307
loadCats() (`kwcoco.compat_dataset.COCO` method),
 307
loadImgs() (`kwcoco.compat_dataset.COCO` method),
 307
loadNumpyAnnotations() (kw-
`coco.compat_dataset.COCO` method), 308
loadRes() (`kwcoco.compat_dataset.COCO` method),
 307
loads() (`kwcoco.kw18.KW18` class method), 311
log() (`kwcoco.coco_evaluator.CocoEvaluator` method),
 273
lookup() (`kwcoco.coco_objects1d.ObjectGroups`
 method), 286
lookup() (`kwcoco.coco_objects1d.ObjectList1D`
 method), 284

M

main() (in module `kwcoco.cli.__main__`), 15
main() (in module `kwcoco.cli.coco_eval`), 18
main() (in module `kwcoco.data.grab_camvid`), 32
main() (in module `kwcoco.data.grab_cifar`), 32
main() (in module `kwcoco.data.grab_spacenet`), 34
main() (in module `kwcoco.data.grab_voc`), 35
main() (`kwcoco.cli.coco_conform.CocoConformCLI`
 class method), 15
main() (`kwcoco.cli.coco_eval.CocoEvalCLI` class
 method), 17
main() (`kwcoco.cli.coco_grab.CocoGrabCLI` class
 method), 19
main() (`kwcoco.cli.coco_modify_categories.CocoModifyCatsCLI`
 class method), 20
main() (`kwcoco.cli.coco_reroot.CocoRerootCLI` class
 method), 21

main() (`kwcoco.cli.coco_show.CocoShowCLI` class method), 22
main() (`kwcoco.cli.coco_split.CocoSplitCLI` class method), 23
main() (`kwcoco.cli.coco_stats.CocoStatsCLI` class method), 24
main() (`kwcoco.cli.coco_subset.CocoSubsetCLI` class method), 25
main() (`kwcoco.cli.coco_toydata.CocoToyDataCLI` class method), 28
main() (`kwcoco.cli.coco_union.CocoUnionCLI` class method), 28
main() (`kwcoco.cli.coco_validate.CocoValidateCLI` class method), 29
maximized_thresholds() (`kwcoco.metrics.confusion_measures.Measures` method), 78
maximized_thresholds() (`kwcoco.metrics.Measures` method), 125
MeasureCombiner (class in `kwcoco.metrics.confusion_measures`), 82
Measures (class in `kwcoco.metrics`), 124
Measures (class in `kwcoco.metrics.confusion_measures`), 78
measures() (`kwcoco.metrics.BinaryConfusionVectors` method), 118
measures() (`kwcoco.metrics.confusion_vectors.BinaryConfusionVectors` method), 90
measures() (`kwcoco.metrics.confusion_vectors.OneVsRestConfusionVectors` method), 89
measures() (`kwcoco.metrics.OneVsRestConfusionVectors` method), 129
MEMORY_URI (`kwcoco.coco_sql_dataset.CocoSqlDatabase` attribute), 302
missing_images() (`kwkoco.coco_dataset.MixinCocoExtras` method), 239
MixinCocoAccessors (class in `kwkoco.coco_dataset`), 229
MixinCocoAddRemove (class in `kwkoco.coco_dataset`), 250
MixinCocoDeprecate (class in `kwkoco.coco_dataset`), 229
MixinCocoDraw (class in `kwkoco.coco_dataset`), 249
MixinCocoExtras (class in `kwkoco.coco_dataset`), 235
MixinCocoIndex (class in `kwkoco.coco_dataset`), 261
MixinCocoObjects (class in `kwkoco.coco_dataset`), 242
MixinCocoStats (class in `kwkoco.coco_dataset`), 244
module
 kwCOCO, 9
 kwCOCO.__init__, 1
 kwCOCO.__main__, 198
 kwCOCO._helpers, 198
 kwCOCO.abstract_coco_dataset, 201
kwCOCO.category_tree, 202
kwCOCO.channel_spec, 207
kwCOCO.cli, 14
kwCOCO.cli.__main__, 14
kwCOCO.cli.coco_conform, 15
kwCOCO.cli.coco_eval, 16
kwCOCO.cli.coco_grab, 19
kwCOCO.cli.coco_modify_categories, 19
kwCOCO.cli.coco_reroot, 21
kwCOCO.cli.coco_show, 22
kwCOCO.cli.coco_split, 23
kwCOCO.cli.coco_stats, 24
kwCOCO.cli.coco_subset, 25
kwCOCO.cli.coco_toydata, 27
kwCOCO.cli.coco_union, 28
kwCOCO.cli.coco_validate, 29
kwCOCO.coco_dataset, 223
kwCOCO.coco_evaluator, 270
kwCOCO.coco_image, 277
kwCOCO.coco_objects1d, 282
kwCOCO.coco_schema, 290
kwCOCO.coco_sql_dataset, 294
kwCOCO.compat_dataset, 306
kwCOCO.data, 30
kwCOCO.data.grab_camvid, 30
kwCOCO.data.grab_cifar, 32
kwCOCO.data.grab_datasets, 32
kwCOCO.data.grab_domainnet, 33
kwCOCO.data.grab_spacenet, 33
kwCOCO.data.grab_voc, 34
kwCOCO.demo, 36
kwCOCO.demo.boids, 36
kwCOCO.demo.perterb, 40
kwCOCO.demo.toydata, 41
kwCOCO.demo.toydata_image, 49
kwCOCO.demo.toydata_video, 53
kwCOCO.demo.toypatterns, 61
kwCOCO.examples, 64
kwCOCO.examples.bench_large_hyperspectral, 64
kwCOCO.examples.draw_gt_and_predicted_boxes, 65
kwCOCO.examples.faq, 66
kwCOCO.examples.getting_started_existing_dataset, 66
kwCOCO.examples.loading_multispectral_data, 67
kwCOCO.examples.modification_example, 67
kwCOCO.examples.simple_kwCOCO_torch_dataset, 67
kwCOCO.examples.vectorized_interface, 69
kwCOCO.kpf, 309
kwCOCO.kw18, 309
kwCOCO.metrics, 69

kwcoco.metrics.assignment, 69
 kwcoco.metrics.clf_report, 74
 kwcoco.metrics.confusion_measures, 77
 kwcoco.metrics.confusion_vectors, 84
 kwcoco.metrics.detect_metrics, 93
 kwcoco.metrics.drawing, 100
 kwcoco.metrics.functional, 104
 kwcoco.metrics.sklearn_alts, 106
 kwcoco.metrics.util, 108
 kwcoco.metrics.voc_metrics, 108
 kwcoco.util, 131
 kwcoco.util.dict_like, 131
 kwcoco.util.jsonschema_elements, 132
 kwcoco.util.lazy_frame_backends, 138
 kwcoco.util.util_archive, 141
 kwcoco.util.util_delayed_poc, 143
 kwcoco.util.util_futures, 164
 kwcoco.util.util_json, 164
 kwcoco.util.util_monkey, 166
 kwcoco.util.util_sklearn, 167
 kwcoco.util.util_truncate, 168

N

n_annot (kwcoco.coco_dataset.MixinCocoStats property), 244
 n_annot (kwcoco.coco_objects1d.Images property), 288
 n_cats (kwcoco.coco_dataset.MixinCocoStats property), 244
 n_images (kwcoco.coco_dataset.MixinCocoStats property), 244
 n_videos (kwcoco.coco_dataset.MixinCocoStats property), 244
 name (kwcoco.cli.coco_conform.CocoConformCLI attribute), 15
 name (kwcoco.cli.coco_eval.CocoEvalCLI attribute), 17
 name (kwcoco.cli.coco_grab.CocoGrabCLI attribute), 19
 name (kwcoco.cli.coco_modify_categories.CocoModifyCatsCLI attribute), 20
 name (kwcoco.cli.coco_reroot.CocoRerootCLI attribute), 21
 name (kwcoco.cli.coco_show.CocoShowCLI attribute), 22
 name (kwcoco.cli.coco_split.CocoSplitCLI attribute), 23
 name (kwcoco.cli.coco_stats.CocoStatsCLI attribute), 24
 name (kwcoco.cli.coco_subset.CocoSubsetCLI attribute), 25
 name (kwcoco.cli.coco_toydata.CocoToyDataCLI attribute), 28
 name (kwcoco.cli.coco_union.CocoUnionCLI attribute), 28
 name (kwcoco.cli.coco_validate.CocoValidateCLI attribute), 29
 name (kwcoco.coco_objects1d.Categories property), 287
 name (kwcoco.coco_sql_dataset.Category attribute), 296

name (kwcoco.coco_sql_dataset.Image attribute), 297
 name (kwcoco.coco_sql_dataset.KeypointCategory attribute), 296
 name (kwcoco.coco_sql_dataset.Video attribute), 296
 name_to_cat (kwcoco.coco_dataset.MixinCocoIndex property), 261
 name_to_cat (kwcoco.coco_sql_dataset.CocoSqlDatabase property), 303
 ndim (kwcoco.util.lazy_frame_backends.LazyGDalFrameFile property), 140
 ndim (kwcoco.util.lazy_frame_backends.LazyRasterIOFrameFile property), 139
 ndim (kwcoco.util.lazy_frame_backends.LazySpectralFrameFile property), 139
 ndim (kwcoco.util.LazyGDalFrameFile property), 177
 ndim (kwcoco.util.LazyRasterIOFrameFile property), 177
 ndim (kwcoco.util.LazySpectralFrameFile property), 177
 nesting() (kwcoco.util.DelayedLoad method), 187
 nesting() (kwcoco.util.DelayedVisionOperation method), 191
 nesting() (kwcoco.util.util_delayed_poc.DelayedLoad method), 152
 nesting() (kwcoco.util.util_delayed_poc.DelayedVisionOperation method), 147
 next_id() (kwcoco._helpers._ID_Remapper method), 199
 normalize() (kwcoco.category_tree.CategoryTree method), 207
 normalize() (kwcoco.CategoryTree method), 318
 normalize() (kwcoco.channel_spec.BaseChannelSpec method), 209
 normalize() (kwcoco.channel_spec.ChannelSpec method), 217
 normalize() (kwcoco.channel_spec.FusedChannelSpec method), 211
 normalize() (kwcoco.ChannelSpec method), 329
 normalize() (kwcoco.coco_evaluator.CocoEvalConfig method), 272
 normalize() (kwcoco.FusedChannelSpec method), 337
 NOT (in module kwcoco.coco_schema), 293
 NOT (in module kwcoco.util), 174
 NOT (in module kwcoco.util.jsonschema_elements), 137
 NOT() (kwcoco.util.jsonschema_elements.QuantifierElements method), 135
 NOT() (kwcoco.util.QuantifierElements method), 174
 NULL (in module kwcoco.coco_schema), 293
 NULL (in module kwcoco.util), 174
 NULL (in module kwcoco.util.jsonschema_elements), 137
 NULL (kwcoco.util.jsonschema_elements.ScalarElements property), 134
 NULL (kwcoco.util.ScalarElements property), 174
 num_bands (kwcoco.util.DelayedLoad property), 187
 num_bands (kwcoco.util.DelayedNans property), 189
 num_bands (kwcoco.util.DelayedWarp property), 193

num_bands (*kwcoco.util.util_delayed_poc.DelayedLoad property*), 152
num_bands (*kwcoco.util.util_delayed_poc.DelayedNans property*), 149
num_bands (*kwcoco.util.util_delayed_poc.DelayedWarp property*), 160
num_channels (*kwcoco.coco_image.CocoImage property*), 278
num_classes (*kwcoco.category_tree.CategoryTree property*), 206
num_classes (*kwcoco.CategoryTree property*), 317
NUMBER (*in module kwcoco.coco_schema*), 293
NUMBER (*in module kwcoco.util*), 174
NUMBER (*in module kwcoco.util.jsonschema_elements*), 138
NUMBER (*kwcoco.util.jsonschema_elements.ScalarElements property*), 134
NUMBER (*kwcoco.util.ScalarElements property*), 175
numel() (*kwcoco.channel_spec.ChannelSpec method*), 219
numel() (*kwcoco.channel_spec.FusedChannelSpec method*), 212
numel() (*kwcoco.ChannelSpec method*), 331
numel() (*kwcoco.FusedChannelSpec method*), 337

O

OBJECT (*in module kwcoco.coco_schema*), 293
OBJECT (*in module kwcoco.util*), 174
OBJECT (*in module kwcoco.util.jsonschema_elements*), 138
OBJECT() (*kwcoco.util.ContainerElements method*), 172
OBJECT() (*kwcoco.util.jsonschema_elements.ContainerElements method*), 135
object_categories() (*kw-coco.coco_dataset.MixinCocoAccessors method*), 234
ObjectGroups (*class in kwcoco.coco_objects1d*), 286
ObjectList1D (*class in kwcoco.coco_objects1d*), 282
objs (*kwcoco.coco_objects1d.ObjectList1D property*), 283
ONEOF (*in module kwcoco.coco_schema*), 293
ONEOF (*in module kwcoco.util*), 174
ONEOF (*in module kwcoco.util.jsonschema_elements*), 138
ONEOF() (*kwcoco.util.jsonschema_elements.QuantifierElements method*), 135
ONEOF() (*kwcoco.util.QuantifierElements method*), 174
OneVersusRestMeasureCombiner (*class in kw-coco.metrics.confusion_measures*), 83
OneVsRestConfusionVectors (*class in kw-coco.metrics*), 128
OneVsRestConfusionVectors (*class in kw-coco.metrics.confusion_vectors*), 88
ORIG_COCO_KEYPOINTS (*in module kwcoco.coco_schema*), 293
ORIG_COCO_POLYGON (*in module kwcoco.coco_schema*), 293
orm_to_dict() (*in module kwcoco.coco_sql_dataset*), 297
oset_delitem() (*in module kwcoco.channel_spec*), 223
oset_insert() (*in module kwcoco.channel_spec*), 223
ovr_classification_report() (*in module kw-coco.metrics.clf_report*), 76
ovr_classification_report() (*kw-coco.metrics.confusion_vectors.OneVsRestConfusionVectors method*), 89
ovr_classification_report() (*kw-coco.metrics.OneVsRestConfusionVectors method*), 129

P

parse() (*kwcoco.channel_spec.ChannelSpec method*), 216
parse() (*kwcoco.channel_spec.FusedChannelSpec class method*), 211
parse() (*kwcoco.ChannelSpec method*), 329
parse() (*kwcoco.FusedChannelSpec class method*), 336
PATH (*in module kwcoco.coco_schema*), 293
paths() (*kwcoco.demo.boids.Boids method*), 37
pct_summarize2() (*in module kw-coco.metrics.detect_metrics*), 100
peek() (*kwcoco.coco_objects1d.ObjectList1D method*), 283
PerClass_Measures (*class in kwcoco.metrics*), 129
PerClass_Measures (*class in kw-coco.metrics.confusion_measures*), 81
perterb_coco() (*in module kwcoco.demo.perterb*), 40
POLYGON (*in module kwcoco.coco_schema*), 293
populate_from() (*kw-coco.coco_sql_dataset.CocoSqlDatabase method*), 303
populate_info() (*in module kw-coco.metrics.confusion_measures*), 83
pred_detections() (*kw-coco.metrics.detect_metrics.DetectionMetrics method*), 95
pred_detections() (*kw-coco.metrics.DetectionMetrics method*), 113
primary_asset() (*kwcoco.coco_image.CocoImage method*), 278
primary_image_filepath() (*kw-coco.coco_image.CocoImage method*), 278
prob (*kwcoco.coco_sql_dataset.Annotation attribute*), 297
profile (*in module kwcoco.coco_evaluator*), 272
profile (*in module kwcoco.demo.toydata_image*), 49
profile (*in module kwcoco.demo.toydata_video*), 53
profile (*in module kwcoco.demo.toypatterns*), 62

profile (in module `kwcoco.util.lazy_frame_backends`), 138
profile (in module `kwcoco.util.util_delayed_poc`), 147
pycocotools_confusion_vectors() (in module `kwcoco.metrics.detect_metrics`), 99

Q

QuantifierElements (class in `kwcoco.util`), 174
QuantifierElements (class in `kwcoco.util.jsonschema_elements`), 134
query_subset() (in module `kwcoco.cli.coco_subset`), 26
queue_size (`kwcoco.metrics.confusion_measures.MeasureCombiner` method), 257
property), 83

R

random() (`kwcoco.coco_dataset.MixinCocoExtras` class method), 237
random() (`kwcoco.util.DelayedChannelConcat` class method), 180
random() (`kwcoco.util.DelayedWarp` class method), 192
random() (`kwcoco.util.util_delayed_poc.DelayedChannelConcat` class method), 157
random() (`kwcoco.util.util_delayed_poc.DelayedWarp` class method), 160
random_category() (`coco.demo.toypatterns.CategoryPatterns` method), 63
random_multi_object_path() (in module `coco.demo.toydata_video`), 60
random_path() (in module `coco.demo.toydata_video`), 60
random_single_video_dset() (in module `coco.demo.toydata`), 41
random_single_video_dset() (in module `coco.demo.toydata_video`), 55
random_video_dset() (in module `coco.demo.toydata`), 44
random_video_dset() (in module `coco.demo.toydata_video`), 53
Rasters (class in `kwcoco.demo.toypatterns`), 64
raw_table() (`kwcoco.coco_sql_dataset.CocoSqlDatabase` method), 304
reconstruct() (`kwcoco.metrics.confusion_measures.Measures` method), 78
reconstruct() (`kwcoco.metrics.Measures` method), 125
reflection_id (`kwcoco.coco_sql_dataset.KeypointCategory` attribute), 296
remap() (`kwcoco._helpers._ID_Remapper` method), 199
remap() (`kwcoco._helpers.UniqueNameRemapper` method), 199
remove_annotation() (kw-
coco.coco_dataset.MixinCocoAddRemove method), 256
remove_annotation_keypoints() (kw-
coco.coco_dataset.MixinCocoAddRemove method), 258
remove_annotations() (kw-
coco.coco_dataset.MixinCocoAddRemove method), 256
remove_categories() (kw-
coco.coco_dataset.MixinCocoAddRemove method), 257
remove_images() (kw-
coco.coco_dataset.MixinCocoAddRemove method), 257
remove_keypoint_categories() (kw-
coco.coco_dataset.MixinCocoAddRemove method), 258
remove_videos() (kw-
coco.coco_dataset.MixinCocoAddRemove method), 258
rename_categories() (kw-
coco.coco_dataset.MixinCocoExtras method), 240
render_background() (in module `coco.demo.toydata_video`), 60
render_category() (kw-
coco.demo.toypatterns.CategoryPatterns method), 63
render_foreground() (in module `coco.demo.toydata_video`), 60
render_toy_dataset() (in module `coco.demo.toydata_video`), 57
render_toy_image() (in module `coco.demo.toydata_video`), 58
rerooot() (`kwcoco.coco_dataset.MixinCocoExtras` method), 240
reversible_diff() (in module `coco.metrics.confusion_measures`), 81
rgb_to_cid() (in module `kwcoco.data.grab_camvid`), 31
RUN_LENGTH_ENCODING (in module `coco.coco_schema`), 293

S

ScalarElements (class in `kwcoco.util`), 174
ScalarElements (class in `coco.util.jsonschema_elements`), 134
SchemaElements (class in `kwcoco.util`), 175
SchemaElements (class in `coco.util.jsonschema_elements`), 136
score (`kwcoco.coco_sql_dataset.Annotation` attribute), 297
score() (`kwcoco.metrics.voc_metrics.VOC_Metrics` method), 109

score_coco (*kwcoco.metrics.detect_metrics.DetectionMetrics attribute*), 94
score_coco (*kwcoco.metrics.DetectionMetrics attribute*), 112
score_kwant() (*kwcoco.metrics.detect_metrics.DetectionMetrics method*), 96
score_kwant() (*kwcoco.metrics.DetectionMetrics method*), 114
score_kwccoco() (*kwcoco.metrics.detect_metrics.DetectionMetrics method*), 96
score_kwccoco() (*kwcoco.metrics.DetectionMetrics method*), 114
score_pycocotools() (*kwcoco.metrics.detect_metrics.DetectionMetrics method*), 96
score_pycocotools() (*kwcoco.metrics.DetectionMetrics method*), 114
score_voc() (*kwcoco.metrics.detect_metrics.DetectionMetrics method*), 96
score_voc() (*kwcoco.metrics.DetectionMetrics method*), 114
SEGMENTATION (*in module kwcoco.coco_schema*), 293
segmentation (*kwcoco.coco_sql_dataset.Annotation attribute*), 297
set() (*kwcoco.coco_objects1d.ObjectList1D method*), 285
set_annotation_category() (*kwcoco.coco_dataset.MixinCocoAddRemove method*), 259
setitem() (*kwcoco.util.dict_like.DictLike method*), 131
setitem() (*kwcoco.util.DictLike method*), 171
shape (*kwcoco.util.DelayedChannelConcat property*), 180
shape (*kwcoco.util.DelayedFrameConcat property*), 183
shape (*kwcoco.util.DelayedLoad property*), 187
shape (*kwcoco.util.DelayedNans property*), 189
shape (*kwcoco.util.DelayedWarp property*), 193
shape (*kwcoco.util.lazy_frame_backends.LazyGDalFrameFile property*), 140
shape (*kwcoco.util.lazy_frame_backends.LazyRasterIOFrameFile property*), 139
shape (*kwcoco.util.lazy_frame_backends.LazySpectralFrameFile property*), 139
shape (*kwcoco.util.LazyGDalFrameFile property*), 177
shape (*kwcoco.util.LazyRasterIOFrameFile property*), 177
shape (*kwcoco.util.LazySpectralFrameFile property*), 177
shape (*kwcoco.util.util_delayed_poc.DelayedChannelConcat property*), 157
shape (*kwcoco.util.util_delayed_poc.DelayedFrameConcat property*), 155
shape (*kwcoco.util.util_delayed_poc.DelayedLoad prop- erty*), 152
shape (*kwcoco.util.util_delayed_poc.DelayedNans property*), 149
shape (*kwcoco.util.util_delayed_poc.DelayedWarp property*), 160
show() (*kwcoco.category_tree.CategoryTree method*), 207
show() (*kwcoco.CategoryTree method*), 318
showImage() (*kwcoco.coco_dataset.MixinCocoDraw method*), 249
showAnns() (*kwcoco.compat_dataset.COCO method*), 307
size (*kwcoco.coco_objects1d.Images property*), 288
sizes() (*kwcoco.channel_spec.ChannelSpec method*), 219
sizes() (*kwcoco.channel_spec.FusedChannelSpec method*), 212
sizes() (*kwcoco.ChannelSpec method*), 331
sizes() (*kwcoco.FusedChannelSpec method*), 337
smart_truncate() (*in module kwcoco.util*), 197
smart_truncate() (*in module kwcoco.util.util_truncate*), 168
SortedSetQuiet (*class in kwcoco._helpers*), 199
spec (*kwcoco.channel_spec.BaseChannelSpec property*), 209
spec (*kwcoco.channel_spec.ChannelSpec property*), 215
spec (*kwcoco.ChannelSpec property*), 328
spec() (*kwcoco.channel_spec.FusedChannelSpec method*), 211
spec() (*kwcoco.FusedChannelSpec method*), 336
SPEC_KEYS (*in module kwcoco.coco_dataset*), 229
split() (*kwcoco.util.StratifiedGroupKFold method*), 197
split() (*kwcoco.util.util_sklearn.StratifiedGroupKFold method*), 168
SqlDictProxy (*class in kwcoco.coco_sql_dataset*), 298
SqlIdGroupDictProxy (*class in kwcoco.coco_sql_dataset*), 300
SqlListProxy (*class in kwcoco.coco_sql_dataset*), 298
star() (*in module kwcoco.demo.toypatterns*), 64
stats() (*kwcoco.coco_dataset.MixinCocoStats method*), 246
stats() (*kwcoco.coco_image.CocoImage method*), 278
step() (*kwcoco.demo.boids.Boids method*), 37
StratifiedGroupKFold (*class in kwcoco.util*), 197
StratifiedGroupKFold (*class in kwcoco.util.util_sklearn*), 167
streams() (*kwcoco.channel_spec.BaseChannelSpec method*), 209
streams() (*kwcoco.channel_spec.ChannelSpec method*), 217
streams() (*kwcoco.channel_spec.FusedChannelSpec method*), 213
streams() (*kwcoco.ChannelSpec method*), 330

s
streams() (*kwcoco.FusedChannelSpec method*), 339
STRING (*in module kwcoco.coco_schema*), 293
STRING (*in module kwcoco.util*), 174
STRING (*in module kwcoco.util.jsonschema_elements*), 138
STRING (*kwcoco.util.jsonschema_elements.ScalarElements property*), 134
STRING (*kwcoco.util.ScalarElements property*), 175
submit() (*kwcoco.metrics.confusion_measures.MeasureCombiner method*), 83
submit() (*kwcoco.metrics.confusion_measures.OneVersusRestMeasurerCombiner method*), 83
subsequence_index() (*in module kwcoco.channel_spec*), 222
subset() (*kwcoco.coco_dataset.CocoDataset method*), 269
subset() (*kwcoco.CocoDataset method*), 325
summarize() (*kwcoco.metrics.detect_metrics.DetectionMetrics method*), 99
summarize() (*kwcoco.metrics.DetectionMetrics method*), 117
summary() (*kwcoco.metrics.confusion_measures.Measures method*), 78
summary() (*kwcoco.metrics.confusion_measures.PerClass_Measures method*), 81
summary() (*kwcoco.metrics.Measures method*), 125
summary() (*kwcoco.metrics.PerClass_Measures method*), 129
summary_plot() (*kwcoco.metrics.confusion_measures.Measures method*), 79
summary_plot() (*kwcoco.metrics.confusion_measures.PerClass_Measures method*), 82
summary_plot() (*kwcoco.metrics.Measures method*), 126
summary_plot() (*kwcoco.metrics.PerClass_Measures method*), 130
supercategory (*kwcoco.coco_objects1d.Categories property*), 287
supercategory (*kwcoco.coco_sql_dataset.Category attribute*), 296
supercategory (*kwcoco.coco_sql_dataset.KeypointCategory attribute*), 296
superstar() (*kwcoco.demo.toypatterns.Rasters static method*), 64
SupressPrint (*class in kwcoco.util*), 196
SupressPrint (*class in kwcoco.util.util_monkey*), 166

T

tabular_targets() (*kwcoco.coco_sql_dataset.CocoSqlDatabase method*), 304
take() (*kwcoco.coco_objects1d.ObjectListID method*), 283

t
take_channels() (*kwcoco.util.DelayedChannelConcat method*), 180
take_channels() (*kwcoco.util.DelayedIdentity method*), 185
take_channels() (*kwcoco.util.DelayedImageOperation method*), 186
take_channels() (*kwcoco.util.DelayedLoad method*), 188
take_channels() (*kwcoco.util.DelayedWarp method*), 189
take_channels() (*kwcoco.util.util_delayed_poc.DelayedChannelConcat method*), 158
take_channels() (*kwcoco.util.util_delayed_poc.DelayedIdentity method*), 149
take_channels() (*kwcoco.util.util_delayed_poc.DelayedImageOperation method*), 148
take_channels() (*kwcoco.util.util_delayed_poc.DelayedLoad method*), 153
take_channels() (*kwcoco.util.util_delayed_poc.DelayedWarp method*), 162
tblname (*in module kwcoco.coco_sql_dataset*), 297
TBLNAME_TO_CLASS (*in module kwcoco.coco_sql_dataset*), 297
the_core_dataset_backend() (*in module kwcoco.coco_sql_dataset*), 66
timestamp (*kwcoco.coco_sql_dataset.Image attribute*), 297
to_coco() (*kwcoco.category_tree.CategoryTree method*), 205
to_coco() (*kwcoco.CategoryTree method*), 315
to_coco() (*kwcoco.kw18.KW18 method*), 310
to_dict() (*kwcoco.util.dict_like.DictLike method*), 131
to_dict() (*kwcoco.util.DictLike method*), 171
TOYDATA_IMAGE_VERSION (*in module kwcoco.demo.toydata_image*), 49
TOYDATA_VIDEO_VERSION (*in module kwcoco.demo.toydata_video*), 53
track_id (*kwcoco.coco_sql_dataset.Annotation attribute*), 297
triu_condense_multi_index() (*in module kwcoco.demo.boids*), 38
true_detections() (*kwcoco.metrics.detect_metrics.DetectionMetrics method*), 94
true_detections() (*kwcoco.metrics.DetectionMetrics method*), 112
TUPLE() (*in module kwcoco.coco_schema*), 293

U

unarchive_file() (in module kwcoco.util), 179
unarchive_file() (in module kwcoco.util_archive), 142
union() (kwcoco.coco_dataset.CocoDataset method), 266
union() (kwcoco.CocoDataset method), 323
unique() (kwcoco.channel_spec.ChannelSpec method), 219
unique() (kwcoco.channel_spec.FusedChannelSpec method), 211
unique() (kwcoco.ChannelSpec method), 332
unique() (kwcoco.FusedChannelSpec method), 336
UniqueNameRemapper (class in kwcoco._helpers), 199
update() (kwcoco.util.dict_like.DictLike method), 132
update() (kwcoco.util.DictLike method), 171
update_neighbors() (kwcoco.demo.boids.Boids method), 37
USE_NEG_INF (in module kwcoco.metrics.assignment), 70
UUID (in module kwcoco.coco_schema), 293

V

validate() (kwcoco.coco_dataset.MixinCocoStats method), 246
validate() (kwcoco.util.Element method), 173
validate() (kwcoco.util.jsonschema_elements.Element method), 134
values() (kwcoco.channel_spec.ChannelSpec method), 217
values() (kwcoco.ChannelSpec method), 330
values() (kwcoco.coco_sql_dataset.SqlDictProxy method), 300
values() (kwcoco.coco_sql_dataset.SqlIdGroupDictProxy method), 301
values() (kwcoco.util.dict_like.DictLike method), 131
values() (kwcoco.util.DictLike method), 171
Video (class in kwcoco.coco_sql_dataset), 296
VIDEO (in module kwcoco.coco_schema), 293
video (kwcoco.coco_image.CocoImage property), 278
video_id (kwcoco.coco_sql_dataset.Image attribute), 297
Videos (class in kwcoco.coco_objects1d), 287
videos() (kwcoco.coco_dataset.MixinCocoObjects method), 244
view_sql() (kwcoco.coco_dataset.CocoDataset method), 269
view_sql() (kwcoco.CocoDataset method), 326
VOC_Metrics (class in kwcoco.metrics.voc_metrics), 108

W

warp() (kwcoco.util.DelayedVisionOperation method), 191

warp() (kwcoco.util.util_delayed_poc.DelayedVisionOperation method), 147
weight (kwcoco.coco_sql_dataset.Annotation attribute), 297
width (kwcoco.coco_objects1d.Images property), 287
width (kwcoco.coco_sql_dataset.Image attribute), 297
width (kwcoco.coco_sql_dataset.Video attribute), 296

X

xywh (kwcoco.coco_objects1d.Annots property), 290