
kwcoco

Release 0.2.25

Jon Crall

Mar 16, 2022

CONTENTS

1 CocoDataset API	5
1.1 CocoDataset classmethods (via MixinCocoExtras)	5
1.2 CocoDataset classmethods (via CocoDataset)	5
1.3 CocoDataset slots	5
1.4 CocoDataset properties	6
1.5 CocoDataset methods (via MixinCocoAddRemove)	6
1.6 CocoDataset methods (via MixinCocoObjects)	7
1.7 CocoDataset methods (via MixinCocoStats)	7
1.8 CocoDataset methods (via MixinCocoAccessors)	7
1.9 CocoDataset methods (via CocoDataset)	8
1.10 CocoDataset methods (via MixinCocoExtras)	8
1.11 CocoDataset methods (via MixinCocoDraw)	8
2 kwcoco	9
2.1 CocoDataset API	11
2.2 Subpackages	14
2.3 Submodules	202
2.4 Package Contents	321
Python Module Index	355
Index	357

If you are new, please see our getting started document: [getting_started](#)

Please also see information in the repo [README](#), which contains similar but complementary information.

For notes about warping and spaces see [warping_and_spaces](#). The Kitware COCO module defines a variant of the Microsoft COCO format, originally developed for the “collected images in context” object detection challenge. We are backwards compatible with the original module, but we also have improved implementations in several places, including segmentations, keypoints, annotation tracks, multi-spectral images, and videos (which represents a generic sequence of images).

A kwcoco file is a “manifest” that serves as a single reference that points to all images, categories, and annotations in a computer vision dataset. Thus, when applying an algorithm to a dataset, it is sufficient to have the algorithm take one dataset parameter: the path to the kwcoco file. Generally a kwcoco file will live in a “bundle” directory along with the data that it references, and paths in the kwcoco file will be relative to the location of the kwcoco file itself.

The main data structure in this model is largely based on the implementation in <https://github.com/cocodataset/cocoapi>. It uses the same efficient core indexing data structures, but in our implementation the indexing can be optionally turned off, functions are silent by default (with the exception of long running processes, which optionally show progress by default). We support helper functions that add and remove images, categories, and annotations.

The `kwcoco.CocoDataset` class is capable of dynamic addition and removal of categories, images, and annotations. Has better support for keypoints and segmentation formats than the original COCO format. Despite being written in Python, this data structure is reasonably efficient.

```
>>> import kwcoco
>>> import json
>>> # Create demo data
>>> demo = kwcoco.CocoDataset.demo()
>>> # Reroot can switch between absolute / relative-paths
>>> demo.reroot(absolute=True)
>>> # could also use demo.dump / demo.dumps, but this is more explicit
>>> text = json.dumps(demo.dataset)
>>> with open('demo.json', 'w') as file:
>>>     file.write(text)

>>> # Read from disk
>>> self = kwcoco.CocoDataset('demo.json')

>>> # Add data
>>> cid = self.add_category('Cat')
>>> gid = self.add_image('new-img.jpg')
>>> aid = self.add_annotation(image_id=gid, category_id=cid, bbox=[0, 0, 100, 100])

>>> # Remove data
>>> self.remove_annotations([aid])
>>> self.remove_images([gid])
>>> self.remove_categories([cid])

>>> # Look at data
>>> import ubelt as ub
>>> print(ub.repr2(self.basic_stats(), nl=1))
>>> print(ub.repr2(self.extended_stats(), nl=2))
>>> print(ub.repr2(self.boxsize_stats(), nl=3))
>>> print(ub.repr2(self.category_annotation_frequency()))
```

(continues on next page)

(continued from previous page)

```
>>> # Inspect data
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> import kwplot
>>> kwplot.autompl()
>>> self.show_image(gid=1)

>>> # Access single-item data via imgs, cats, anns
>>> cid = 1
>>> self.cats[cid]
{'id': 1, 'name': 'astronaut', 'supercategory': 'human'}

>>> gid = 1
>>> self.imgs[gid]
{'id': 1, 'file_name': 'astro.png', 'url': 'https://i.imgur.com/KXhKM72.png'}

>>> aid = 3
>>> self.anns[aid]
{'id': 3, 'image_id': 1, 'category_id': 3, 'line': [326, 369, 500, 500]}

>>> # Access multi-item data via the annots and images helper objects
>>> aids = self.index.gid_to_aids[2]
>>> annots = self.annots(aids)

>>> print('annots = {}'.format(ub.repr2(annots, nl=1, sv=1)))
annots = <Annos(num=2)>

>>> annots.lookup('category_id')
[6, 4]

>>> annots.lookup('bbox')
[[37, 6, 230, 240], [124, 96, 45, 18]]

>>> # built in conversions to efficient kwimage array DataStructures
>>> print(ub.repr2(annots.detections.data, sv=1))
{
    'boxes': <Boxes(xywh,
                      array([[ 37.,   6., 230., 240.],
                             [124.,  96.,  45.,  18.]], dtype=float32))>,
    'class_idxs': [5, 3],
    'keypoints': <PointsList(n=2)>,
    'segmentations': <PolygonList(n=2)>,
}

>>> gids = list(self.imgs.keys())
>>> images = self.images(gids)
>>> print('images = {}'.format(ub.repr2(images, nl=1, sv=1)))
images = <Images(num=3)>

>>> images.lookup('file_name')
['astro.png', 'carl.png', 'stars.png']

>>> print('images.annots = {}'.format(images.annots))
```

(continues on next page)

(continued from previous page)

```
images.annots = <AnnotGroups(n=3, m=3.7, s=3.9)>  
  
=> print('images.annots.cids = {!r}'.format(images.annots.cids))  
images.annots.cids = [[1, 2, 3, 4, 5, 5, 5, 5], [6, 4], []]
```


COCODATASET API

The following is a logical grouping of the public `kwcoco.CocoDataset` API attributes and methods. See the in-code documentation for further details.

1.1 CocoDataset classmethods (via MixinCocoExtras)

- `kwcoco.CocoDataset.coerce` - Attempt to transform the input into the intended CocoDataset.
- `kwcoco.CocoDataset.demo` - Create a toy coco dataset for testing and demo puposes
- `kwcoco.CocoDataset.random` - Creates a random CocoDataset according to distribution parameters

1.2 CocoDataset classmethods (via CocoDataset)

- `kwcoco.CocoDataset.from_coco_paths` - Constructor from multiple coco file paths.
- `kwcoco.CocoDataset.from_data` - Constructor from a json dictionary
- `kwcoco.CocoDataset.from_image_paths` - Constructor from a list of images paths.

1.3 CocoDataset slots

- `kwcoco.CocoDataset.index` - an efficient lookup index into the coco data structure. The index defines its own attributes like `anns`, `cats`, `imgs`, `gid_to_aids`, `file_name_to_img`, etc. See `CocoIndex` for more details on which attributes are available.
- `kwcoco.CocoDataset.hashid` - If computed, this will be a hash uniquely identifying the dataset. To ensure this is computed see `kwcoco.coco_dataset.MixinCocoExtras._build_hashid()`.
- `kwcoco.CocoDataset.hashid_parts` -
- `kwcoco.CocoDataset.tag` - A tag indicating the name of the dataset.
- `kwcoco.CocoDataset.dataset` - raw json data structure. This is the base dictionary that contains {‘annotations’: List, ‘images’: List, ‘categories’: List}
- `kwcoco.CocoDataset.bundle_dpath` - If known, this is the root path that all image file names are relative to. This can also be manually overwritten by the user.
- `kwcoco.CocoDataset.assets_dpath` -
- `kwcoco.CocoDataset.cache_dpath` -

1.4 CocoDataset properties

- `kwcoco.CocoDataset.anns` -
- `kwcoco.CocoDataset.cats` -
- `kwcoco.CocoDataset.cid_to_aids` -
- `kwcoco.CocoDataset.data_fpath` -
- `kwcoco.CocoDataset.data_root` -
- `kwcoco.CocoDataset.fpath` - if known, this stores the filepath the dataset was loaded from
- `kwcoco.CocoDataset.gid_to_aids` -
- `kwcoco.CocoDataset.img_root` -
- `kwcoco.CocoDataset imgs` -
- `kwcoco.CocoDataset.n_annot`s -
- `kwcoco.CocoDataset.n_cat`s -
- `kwcoco.CocoDataset.n_imag`e -
- `kwcoco.CocoDataset.n_vide`o -
- `kwcoco.CocoDataset.name_to_cat` -

1.5 CocoDataset methods (via MixinCocoAddRemove)

- `kwcoco.CocoDataset.add_annotation` - Add an annotation to the dataset (dynamically updates the index)
- `kwcoco.CocoDataset.add_annotations` - Faster less-safe multi-item alternative to add_annotation.
- `kwcoco.CocoDataset.add_category` - Adds a category
- `kwcoco.CocoDataset.add_image` - Add an image to the dataset (dynamically updates the index)
- `kwcoco.CocoDataset.add_images` - Faster less-safe multi-item alternative
- `kwcoco.CocoDataset.add_video` - Add a video to the dataset (dynamically updates the index)
- `kwcoco.CocoDataset.clear_annotation`s - Removes all annotations (but not images and categories)
- `kwcoco.CocoDataset.clear_images` - Removes all images and annotations (but not categories)
- `kwcoco.CocoDataset.ensure_category` - Like add_category(), but returns the existing category id if it already exists instead of failing. In this case all metadata is ignored.
- `kwcoco.CocoDataset.ensure_image` - Like add_image(), but returns the existing image id if it already exists instead of failing. In this case all metadata is ignored.
- `kwcoco.CocoDataset.remove_annotation` - Remove a single annotation from the dataset
- `kwcoco.CocoDataset.remove_annotation_keypoints` - Removes all keypoints with a particular category
- `kwcoco.CocoDataset.remove_annotation`s - Remove multiple annotations from the dataset.
- `kwcoco.CocoDataset.remove_categories` - Remove categories and all annotations in those categories. Currently does not change any hierarchy information
- `kwcoco.CocoDataset.remove_images` - Remove images and any annotations contained by them

- `kwcoco.CocoDataset.remove_keypoint_categories` - Removes all keypoints of a particular category as well as all annotation keypoints with those ids.
- `kwcoco.CocoDataset.remove_videos` - Remove videos and any images / annotations contained by them
- `kwcoco.CocoDataset.set_annotation_category` - Sets the category of a single annotation

1.6 CocoDataset methods (via MixinCocoObjects)

- `kwcoco.CocoDataset.annots` - Return vectorized annotation objects
- `kwcoco.CocoDataset.categories` - Return vectorized category objects
- `kwcoco.CocoDataset.images` - Return vectorized image objects
- `kwcoco.CocoDataset.videos` - Return vectorized video objects

1.7 CocoDataset methods (via MixinCocoStats)

- `kwcoco.CocoDataset.basic_stats` - Reports number of images, annotations, and categories.
- `kwcoco.CocoDataset.boxsize_stats` - Compute statistics about bounding box sizes.
- `kwcoco.CocoDataset.category_annotation_frequency` - Reports the number of annotations of each category
- `kwcoco.CocoDataset.category_annotation_type_frequency` - Reports the number of annotations of each type for each category
- `kwcoco.CocoDataset.conform` - Make the COCO file conform a stricter spec, infers attributes where possible.
- `kwcoco.CocoDataset.extended_stats` - Reports number of images, annotations, and categories.
- `kwcoco.CocoDataset.find_representative_images` - Find images that have a wide array of categories. Attempt to find the fewest images that cover all categories using images that contain both a large and small number of annotations.
- `kwcoco.CocoDataset.keypoint_annotation_frequency` -
- `kwcoco.CocoDataset.stats` - This function corresponds to `kwcoco.cli.coco_stats`.
- `kwcoco.CocoDataset.validate` - Performs checks on this coco dataset.

1.8 CocoDataset methods (via MixinCocoAccessors)

- `kwcoco.CocoDataset.category_graph` - Construct a networkx category hierarchy
- `kwcoco.CocoDataset.delayed_load` - Experimental method
- `kwcoco.CocoDataset.get_auxiliary_fpath` - Returns the full path to auxiliary data for an image
- `kwcoco.CocoDataset.get_image_fpath` - Returns the full path to the image
- `kwcoco.CocoDataset.keypoint_categories` - Construct a consistent CategoryTree representation of key-point classes
- `kwcoco.CocoDataset.load_annot_sample` - Reads the chip of an annotation. Note this is much less efficient than using a sampler, but it doesn't require disk cache.

- `kwcoco.CocoDataset.load_image` - Reads an image from disk and
- `kwcoco.CocoDataset.object_categories` - Construct a consistent CategoryTree representation of object classes

1.9 CocoDataset methods (via CocoDataset)

- `kwcoco.CocoDataset.copy` - Deep copies this object
- `kwcoco.CocoDataset.dump` - Writes the dataset out to the json format
- `kwcoco.CocoDataset.dumps` - Writes the dataset out to the json format
- `kwcoco.CocoDataset.subset` - Return a subset of the larger coco dataset by specifying which images to port. All annotations in those images will be taken.
- `kwcoco.CocoDataset.union` - Merges multiple CocoDataset items into one. Names and associations are retained, but ids may be different.
- `kwcoco.CocoDataset.view_sql` - Create a cached SQL interface to this dataset suitable for large scale multiproCESSing use cases.

1.10 CocoDataset methods (via MixinCocoExtras)

- `kwcoco.CocoDataset.corrupted_images` - Check for images that don't exist or can't be opened
- `kwcoco.CocoDataset.missing_images` - Check for images that don't exist
- `kwcoco.CocoDataset.rename_categories` - Rename categories with a potentially coarser categorization.
- `kwcoco.CocoDataset.reroot` - Rebase image/data paths onto a new image/data root.

1.11 CocoDataset methods (via MixinCocoDraw)

- `kwcoco.CocoDataset.draw_image` - Use kwimage to draw all annotations on an image and return the pixels as a numpy array.
- `kwcoco.CocoDataset.imread` - Loads a particular image
- `kwcoco.CocoDataset.show_image` - Use matplotlib to show an image with annotations overlaid

KWCOCO

The Kitware COCO module defines a variant of the Microsoft COCO format, originally developed for the “collected images in context” object detection challenge. We are backwards compatible with the original module, but we also have improved implementations in several places, including segmentations, keypoints, annotation tracks, multi-spectral images, and videos (which represents a generic sequence of images).

A kwcoco file is a “manifest” that serves as a single reference that points to all images, categories, and annotations in a computer vision dataset. Thus, when applying an algorithm to a dataset, it is sufficient to have the algorithm take one dataset parameter: the path to the kwcoco file. Generally a kwcoco file will live in a “bundle” directory along with the data that it references, and paths in the kwcoco file will be relative to the location of the kwcoco file itself.

The main data structure in this model is largely based on the implementation in <https://github.com/cocodataset/cocoapi>. It uses the same efficient core indexing data structures, but in our implementation the indexing can be optionally turned off, functions are silent by default (with the exception of long running processes, which optionally show progress by default). We support helper functions that add and remove images, categories, and annotations.

The `kwcoco.CocoDataset` class is capable of dynamic addition and removal of categories, images, and annotations. Has better support for keypoints and segmentation formats than the original COCO format. Despite being written in Python, this data structure is reasonably efficient.

```
>>> import kwcoco
>>> import json
>>> # Create demo data
>>> demo = kwcoco.CocoDataset.demo()
>>> # Reroot can switch between absolute / relative-paths
>>> demo.reroot(absolute=True)
>>> # could also use demo.dump / demo.dumps, but this is more explicit
>>> text = json.dumps(demo.dataset)
>>> with open('demo.json', 'w') as file:
>>>     file.write(text)

>>> # Read from disk
>>> self = kwcoco.CocoDataset('demo.json')

>>> # Add data
>>> cid = self.add_category('Cat')
>>> gid = self.add_image('new-img.jpg')
>>> aid = self.add_annotation(image_id=gid, category_id=cid, bbox=[0, 0, 100, 100])

>>> # Remove data
>>> self.remove_annotations([aid])
>>> self.remove_images([gid])
>>> self.remove_categories([cid])
```

(continues on next page)

(continued from previous page)

```

>>> # Look at data
>>> import ubelt as ub
>>> print(ub.repr2(self.basic_stats(), nl=1))
>>> print(ub.repr2(self.extended_stats(), nl=2))
>>> print(ub.repr2(self.boxsize_stats(), nl=3))
>>> print(ub.repr2(self.category_annotation_frequency()))

>>> # Inspect data
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> import kwplot
>>> kwplot.autompl()
>>> self.show_image(gid=1)

>>> # Access single-item data via imgs, cats, anns
>>> cid = 1
>>> self.cats[cid]
{'id': 1, 'name': 'astronaut', 'supercategory': 'human'}

>>> gid = 1
>>> self.imgs[gid]
{'id': 1, 'file_name': 'astro.png', 'url': 'https://i.imgur.com/KXhKM72.png'}

>>> aid = 3
>>> self.anns[aid]
{'id': 3, 'image_id': 1, 'category_id': 3, 'line': [326, 369, 500, 500]}

>>> # Access multi-item data via the annots and images helper objects
>>> aids = self.index.gid_to_aids[2]
>>> annots = self.annots(aids)

>>> print('annots = {}'.format(ub.repr2(annots, nl=1, sv=1)))
annots = <Annots(num=2)>

>>> annots.lookup('category_id')
[6, 4]

>>> annots.lookup('bbox')
[[37, 6, 230, 240], [124, 96, 45, 18]]

>>> # built in conversions to efficient kwimage array DataStructures
>>> print(ub.repr2(annots.detections.data, sv=1))
{
    'boxes': <Boxes(xywh,
                      array([[ 37.,   6., 230., 240.],
                             [124.,  96.,  45.,  18.]], dtype=float32))>,
    'class_idxs': [5, 3],
    'keypoints': <PointsList(n=2)>,
    'segmentations': <PolygonList(n=2)>,
}

```

(continues on next page)

(continued from previous page)

```
>>> gids = list(self.imgs.keys())
>>> images = self.images(gids)
>>> print('images = {}'.format(ub.repr2(images, nl=1, sv=1)))
images = <Images(num=3)>

>>> images.lookup('file_name')
['astro.png', 'carl.png', 'stars.png']

>>> print('images.annots = {}'.format(images.annots))
images.annots = <AnnotGroups(n=3, m=3.7, s=3.9)>

>>> print('images.annots.cids = {!r}'.format(images.annots.cids))
images.annots.cids = [[1, 2, 3, 4, 5, 5, 5, 5, 5], [6, 4], []]
```

2.1 CocoDataset API

The following is a logical grouping of the public kwcoco.CocoDataset API attributes and methods. See the in-code documentation for further details.

2.1.1 CocoDataset classmethods (via MixinCocoExtras)

- `kwcoco.CocoDataset.coerce` - Attempt to transform the input into the intended CocoDataset.
- `kwcoco.CocoDataset.demo` - Create a toy coco dataset for testing and demo purposes
- `kwcoco.CocoDataset.random` - Creates a random CocoDataset according to distribution parameters

2.1.2 CocoDataset classmethods (via CocoDataset)

- `kwcoco.CocoDataset.from_coco_paths` - Constructor from multiple coco file paths.
- `kwcoco.CocoDataset.from_data` - Constructor from a json dictionary
- `kwcoco.CocoDataset.from_image_paths` - Constructor from a list of images paths.

2.1.3 CocoDataset slots

- `kwcoco.CocoDataset.index` - an efficient lookup index into the coco data structure. The index defines its own attributes like anns, cats, imgs, gid_to_aids, file_name_to_img, etc. See CocoIndex for more details on which attributes are available.
- `kwcoco.CocoDataset.hashid` - If computed, this will be a hash uniquely identifying the dataset. To ensure this is computed see `kwcoco.coco_dataset.MixinCocoExtras._build_hashid()`.
- `kwcoco.CocoDataset.hashid_parts` -
- `kwcoco.CocoDataset.tag` - A tag indicating the name of the dataset.
- `kwcoco.CocoDataset.dataset` - raw json data structure. This is the base dictionary that contains {‘annotations’: List, ‘images’: List, ‘categories’: List}

- `kwcoco.CocoDataset.bundle_dpath` - If known, this is the root path that all image file names are relative to. This can also be manually overwritten by the user.
- `kwcoco.CocoDataset.assets_dpath` -
- `kwcoco.CocoDataset.cache_dpath` -

2.1.4 CocoDataset properties

- `kwcoco.CocoDataset.anns` -
- `kwcoco.CocoDataset.cats` -
- `kwcoco.CocoDataset.cid_to_aids` -
- `kwcoco.CocoDataset.data_fpath` -
- `kwcoco.CocoDataset.data_root` -
- `kwcoco.CocoDataset.fpath` - if known, this stores the filepath the dataset was loaded from
- `kwcoco.CocoDataset.gid_to_aids` -
- `kwcoco.CocoDataset.img_root` -
- `kwcoco.CocoDataset.imgs` -
- `kwcoco.CocoDataset.n_annot` -
- `kwcoco.CocoDataset.n_cats` -
- `kwcoco.CocoDataset.n_images` -
- `kwcoco.CocoDataset.n_videos` -
- `kwcoco.CocoDataset.name_to_cat` -

2.1.5 CocoDataset methods (via MixinCocoAddRemove)

- `kwcoco.CocoDataset.add_annotation` - Add an annotation to the dataset (dynamically updates the index)
- `kwcoco.CocoDataset.add_annotations` - Faster less-safe multi-item alternative to add_annotation.
- `kwcoco.CocoDataset.add_category` - Adds a category
- `kwcoco.CocoDataset.add_image` - Add an image to the dataset (dynamically updates the index)
- `kwcoco.CocoDataset.add_images` - Faster less-safe multi-item alternative
- `kwcoco.CocoDataset.add_video` - Add a video to the dataset (dynamically updates the index)
- `kwcoco.CocoDataset.clear_annotations` - Removes all annotations (but not images and categories)
- `kwcoco.CocoDataset.clear_images` - Removes all images and annotations (but not categories)
- `kwcoco.CocoDataset.ensure_category` - Like add_category(), but returns the existing category id if it already exists instead of failing. In this case all metadata is ignored.
- `kwcoco.CocoDataset.ensure_image` - Like add_image(), but returns the existing image id if it already exists instead of failing. In this case all metadata is ignored.
- `kwcoco.CocoDataset.remove_annotation` - Remove a single annotation from the dataset
- `kwcoco.CocoDataset.remove_annotation_keypoints` - Removes all keypoints with a particular category
- `kwcoco.CocoDataset.remove_annotations` - Remove multiple annotations from the dataset.

- `kwcoco.CocoDataset.remove_categories` - Remove categories and all annotations in those categories. Currently does not change any hierarchy information
- `kwcoco.CocoDataset.remove_images` - Remove images and any annotations contained by them
- `kwcoco.CocoDataset.remove_keypoint_categories` - Removes all keypoints of a particular category as well as all annotation keypoints with those ids.
- `kwcoco.CocoDataset.remove_videos` - Remove videos and any images / annotations contained by them
- `kwcoco.CocoDataset.set_annotation_category` - Sets the category of a single annotation

2.1.6 CocoDataset methods (via MixinCocoObjects)

- `kwcoco.CocoDataset.annots` - Return vectorized annotation objects
- `kwcoco.CocoDataset.categories` - Return vectorized category objects
- `kwcoco.CocoDataset.images` - Return vectorized image objects
- `kwcoco.CocoDataset.videos` - Return vectorized video objects

2.1.7 CocoDataset methods (via MixinCocoStats)

- `kwcoco.CocoDataset.basic_stats` - Reports number of images, annotations, and categories.
- `kwcoco.CocoDataset.boxsize_stats` - Compute statistics about bounding box sizes.
- `kwcoco.CocoDataset.category_annotation_frequency` - Reports the number of annotations of each category
- `kwcoco.CocoDataset.category_annotation_type_frequency` - Reports the number of annotations of each type for each category
- `kwcoco.CocoDataset.conform` - Make the COCO file conform a stricter spec, infers attributes where possible.
- `kwcoco.CocoDataset.extended_stats` - Reports number of images, annotations, and categories.
- `kwcoco.CocoDataset.find_representative_images` - Find images that have a wide array of categories. Attempt to find the fewest images that cover all categories using images that contain both a large and small number of annotations.
- `kwcoco.CocoDataset.keypoint_annotation_frequency` -
- `kwcoco.CocoDataset.stats` - This function corresponds to `kwcoco.cli.coco_stats`.
- `kwcoco.CocoDataset.validate` - Performs checks on this coco dataset.

2.1.8 CocoDataset methods (via MixinCocoAccessors)

- `kwcoco.CocoDataset.category_graph` - Construct a networkx category hierarchy
- `kwcoco.CocoDataset.delayed_load` - Experimental method
- `kwcoco.CocoDataset.get_auxiliary_fpath` - Returns the full path to auxiliary data for an image
- `kwcoco.CocoDataset.get_image_fpath` - Returns the full path to the image
- `kwcoco.CocoDataset.keypoint_categories` - Construct a consistent CategoryTree representation of key-point classes

- `kwcoco.CocoDataset.load_annot_sample` - Reads the chip of an annotation. Note this is much less efficient than using a sampler, but it doesn't require disk cache.
- `kwcoco.CocoDataset.load_image` - Reads an image from disk and
- `kwcoco.CocoDataset.object_categories` - Construct a consistent CategoryTree representation of object classes

2.1.9 CocoDataset methods (via CocoDataset)

- `kwcoco.CocoDataset.copy` - Deep copies this object
- `kwcoco.CocoDataset.dump` - Writes the dataset out to the json format
- `kwcoco.CocoDataset.dumps` - Writes the dataset out to the json format
- `kwcoco.CocoDataset.subset` - Return a subset of the larger coco dataset by specifying which images to port. All annotations in those images will be taken.
- `kwcoco.CocoDataset.union` - Merges multiple `CocoDataset` items into one. Names and associations are retained, but ids may be different.
- `kwcoco.CocoDataset.view_sql` - Create a cached SQL interface to this dataset suitable for large scale multiprocesing use cases.

2.1.10 CocoDataset methods (via MixinCocoExtras)

- `kwcoco.CocoDataset.corrupted_images` - Check for images that don't exist or can't be opened
- `kwcoco.CocoDataset.missing_images` - Check for images that don't exist
- `kwcoco.CocoDataset.rename_categories` - Rename categories with a potentially coarser categorization.
- `kwcoco.CocoDataset.reroot` - Rebase image/data paths onto a new image/data root.

2.1.11 CocoDataset methods (via MixinCocoDraw)

- `kwcoco.CocoDataset.draw_image` - Use kwimage to draw all annotations on an image and return the pixels as a numpy array.
- `kwcoco.CocoDataset.imread` - Loads a particular image
- `kwcoco.CocoDataset.show_image` - Use matplotlib to show an image with annotations overlaid

2.2 Subpackages

2.2.1 kwcoco.cli

Submodules

`kwcoco.cli.__main__`

Module Contents

Functions

<code>main(cmdline=True, **kw)</code>	kw = dict(command='stats')
---	----------------------------

```
kwcoco.cli.__main__.main(cmdline=True, **kw)
    kw = dict(command='stats') cmdline = False
```

`kwcoco.cli.coco_conform`

Module Contents

Classes

<code>CocoConformCLI</code>	
---	--

Attributes

<code>_CLI</code>	
-----------------------------------	--

```
class kwcoco.cli.coco_conform.CocoConformCLI
    class CLIConfig(data=None, default=None, cmdline=False)
        Bases: scriptconfig.Config

        Make the COCO file conform to the spec.

        Populates inferable information such as image size, annotation area, etc.

        epilog = Multiline-String
            1     Example Usage:
            2         kwcoco conform --help
            3         kwcoco conform --src=special:shapes8 --dst conformed.json

        default

        name = conform

    classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> # xdoctest: +SKIP
>>> kw = {'src': 'special:shapes8'}
>>> cmdline = False
>>> cls = CocoConformCLI
>>> cls.main(cmdline, **kw)
```

`kwcoco.cli.coco_conform._CLI`

`kwcoco.cli.coco_eval`

Wraps the logic in `kwcoco/coco_evaluator.py` with a command line script

Module Contents

Classes

<code>CocoEvalCLIConfig</code>	Base class for custom configuration objects
<code>CocoEvalCLI</code>	

Functions

`main(cmdline=True, **kw)`

Todo:

- [X] should live in `kwcoco.cli.coco_eval`
-

Attributes

`_CLI`

`class kwcoco.cli.coco_eval.CocoEvalCLIConfig(data=None, default=None, cmdline=False)`
Bases: `scriptconfig.Config`

Base class for custom configuration objects

A configuration that can be specified by commandline args, a yaml config file, and / or a in-code dictionary. To use, define a class variable named “default” and assing it to a dict of default values. You can also use special *Value* classes to denote types. You can also define a method *normalize*, to postprocess the arguments after this class receives them.

Usage: Create a class that herits from this class.

Assign the “default” class-level variable as a dictionary of options

The keys of this dictionary must be command line friendly strings.

The values of the “defaults dictionary” can be literal values or instances of the `scriptconfig.Value` class, which allows for specification of default values, type information, help strings, and aliases.

You may also implement `normalize` (function with that takes no args and has no return) to postprocess your results after initialization.

When creating an instance of the class the `defaults` variable is used to make a dictionary-like object. You can override defaults by specifying the `data` keyword argument to either a file path or another dictionary. You can also specify `cmdline=True` to allow the contents of `sys.argv` to influence the values of the new object.

An instance of the config class behaves like a dictionary, except that you cannot set keys that do not already exist (as specified in the `defaults` dict).

Key Methods:

- `dump` - dump a json representation to a file
- `dumps` - dump a json representation to a string
- `argparse` - create the argparse object associated with this config
- **`argparse` - create an `argparse.ArgumentParser` object that** is defined by the defaults of this config.
- **`load` - rewrite the values based on a filepath, dictionary, or** command line contents.

Variables

- **`_data`** – this protected variable holds the raw state of the config object and is accessed by the dict-like
- **`_default`** – this protected variable maintains the default values for this config.

Example

```
>>> # Inherit from `Config` and assign `default`
>>> import scriptconfig as scfg
>>> class MyConfig(scfg.Config):
>>>     default = {
>>>         'option1': scfg.Value((1, 2, 3), tuple),
>>>         'option2': 'bar',
>>>         'option3': None,
>>>     }
>>> # You can now make instances of this class
>>> config1 = MyConfig()
>>> config2 = MyConfig(default=dict(option1='baz'))
```

`__doc__`

`default`

```
class kwcoco.cli.coco_eval.CocoEvalCLI
    name = eval
    CLICConfig
    classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> import ubelt as ub
>>> from kwcoco.cli.coco_eval import * # NOQA
>>> from os.path import join
>>> import kwcoco
>>> dpath = ub.ensure_app_cache_dir('kwcoco/tests/eval')
>>> true_dset = kwcoco.CocoDataset.demo('shapes8')
>>> from kwcoco.demo.perterb import perterb_coco
>>> kwargs = {
>>>     'box_noise': 0.5,
>>>     'n_fp': (0, 10),
>>>     'n_fn': (0, 10),
>>> }
>>> pred_dset = perterb_coco(true_dset, **kwargs)
>>> true_dset.fpath = join(dpath, 'true.mscoco.json')
>>> pred_dset.fpath = join(dpath, 'pred.mscoco.json')
>>> true_dset.dump(true_dset.fpath)
>>> pred_dset.dump(pred_dset.fpath)
>>> draw = False # set to false for faster tests
>>> CocoEvalCLI.main(
>>>     true_dataset=true_dset.fpath,
>>>     pred_dataset=pred_dset.fpath,
>>>     draw=draw)
```

kwcoco.cli.coco_eval.main(cmdline=True, **kw)

Todo:

- [X] should live in kwcoco.cli.coco_eval
-

CommandLine

```
# Generate test data
xdoctest -m kwcoco.cli.coco_eval CocoEvalCLI.main

kwcoco eval \
--true_dataset=$HOME/.cache/kwcoco/tests/eval/true.mscoco.json \
--pred_dataset=$HOME/.cache/kwcoco/tests/eval/pred.mscoco.json \
--out_dpath=$HOME/.cache/kwcoco/tests/eval/out \
--force_pycocoutils=False \
--area_range=all,0-4096,4096-inf

nautilus $HOME/.cache/kwcoco/tests/eval/out
```

kwcoco.cli.coco_eval._CLI

`kwcoco.cli.coco_grab`

Module Contents

Classes

`CocoGrabCLI`

Attributes

`_CLI`

```
class kwcoco.cli.coco_grab.CocoGrabCLI
    class CLIConfig(data=None, default=None, cmdline=False)
        Bases: scriptconfig.Config
        Grab standard datasets.
```

Example

```
kwcoco grab cifar10 camvid
default
name = grab
classmethod main(cls, cmdline=True, **kw)
kwcoco.cli.coco_grab._CLI
```

`kwcoco.cli.coco_modify_categories`

Module Contents

Classes

`CocoModifyCatsCLI`

Remove, rename, or coarsen categories.

Attributes

_CLI

```
class kwcoco.cli.coco_modify_categories.CocoModifyCatsCLI
```

Remove, rename, or coarsen categories.

```
class CLIConfig(data=None, default=None, cmdline=False)
```

Bases: `scriptconfig.Config`

Rename or remove categories

```
epilog = Multiline-String
```

```
1     Example Usage:  
2         kwcoco modify_categories --help  
3         kwcoco modify_categories --src=shapes8 --dst=  
4         ↵modcats.json  
5             kwcoco modify_categories --src=shapes8 --dst=  
6             ↵modcats.json --rename eff:F,star:sun  
7                 kwcoco modify_categories --src=shapes8 --dst=  
8                 ↵modcats.json --remove eff,star  
9                     kwcoco modify_categories --src=shapes8 --dst=  
10                    ↵modcats.json --keep eff,  
11  
12                        kwcoco modify_categories --src=shapes8 --dst=  
13                        ↵modcats.json --keep=[] --keep_annots=True
```

```
default
```

```
name = modify_categories
```

```
classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> # xdoctest: +SKIP  
>>> kw = {'src': 'shapes8'}  
>>> cmdline = False  
>>> cls = CocoModifyCatsCLI  
>>> cls.main(cmdline, **kw)
```

`kwcoco.cli.coco_modify_categories._CLI`

`kwcococo.cli.coco_reroot`

Module Contents

Classes

`CocoRerootCLI`

Attributes

`_CLI`

`class kwcococo.cli.coco_reroot.CocoRerootCLI`
 `class CLIConfig(data=None, default=None, cmdline=False)`
 `Bases: scriptconfig.Config`
 `Reroot image paths onto a new image root.`
 `Modify the root of a coco dataset such to either make paths relative to a new root or make paths absolute.`

Todo:

- [] Evaluate that all tests cases work
-

`epilog = Multiline-String`

```

1     Example Usage:
2         kwcococo reroot --help
3         kwcococo reroot --src=special:shapes8 --dst rerooted.json
4         kwcococo reroot --src=special:shapes8 --new_prefix=foo --
5             ↵check=True --dst rerooted.json

```

`default`

`name = reroot`

`classmethod main(cls, cmdline=True, **kw)`

Example

```

>>> # xdoctest: +SKIP
>>> kw = {'src': 'special:shapes8'}
>>> cmdline = False
>>> cls = CocoRerootCLI
>>> cls.main(cmdline, **kw)

```

`kwcococo.cli.coco_reroot._CLI`

`kwcoco.cli.coco_show`

Module Contents

Classes

`CocoShowCLI`

Attributes

`_CLI`

```
class kwcoco.cli.coco_show.CocoShowCLI
    class CLIConfig(data=None, default=None, cmdline=False)
        Bases: scriptconfig.Config
        Visualize a COCO image using matplotlib or opencv, optionally writing it to disk
        epilog = Multiline-String
            1     Example Usage:
            2         kwcoco show --help
            3         kwcoco show --src=special:shapes8 --gid=1
            4         kwcoco show --src=special:shapes8 --gid=1 --dst out.png
        default
        name = show
    classmethod main(cls, cmdline=True, **kw)
```

`Todo:`

- [] Visualize auxiliary data
-

Example

```
>>> # xdoctest: +SKIP
>>> kw = {'src': 'special:shapes8'}
>>> cmdline = False
>>> cls = CocoShowCLI
>>> cls.main(cmdline, **kw)
```

`kwcoco.cli.coco_show._CLI`

kwcococo.cli.coco_split**Module Contents****Classes**

[CocoSplitCLI](#)

Attributes

[_CLI](#)

```
class kwcococo.cli.coco_split.CocoSplitCLI
    Bases: object

    class CLICConfig(data=None, default=None, cmdline=False)
        Bases: scriptconfig.Config

        Split a single COCO dataset into two sub-datasets.

        default

        epilog = Multiline-String
            Example Usage:
            1             kwcoco split --src special:shapes8 --dst1=learn.mscoco.
            2             ↪json --dst2=test.mscoco.json --factor=3 --rng=42

    name = split

    classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> kw = {'src': 'special:shapes8',
>>>         'dst1': 'train.json', 'dst2': 'test.json'}
>>> cmdline = False
>>> cls = CocoSplitCLI
>>> cls.main(cmdline, **kw)
```

kwcococo.cli.coco_split._CLI

`kwcoco.cli.coco_stats`

Module Contents

Classes

`CocoStatsCLI`

Attributes

`_CLI`

```
class kwcoco.cli.coco_stats.CocoStatsCLI
    class CLIConfig(data=None, default=None, cmdline=False)
        Bases: scriptconfig.Config

        Compute summary statistics about a COCO dataset

        default

        epilog = Multiline-String
            1     Example Usage:
            2         kwcoco stats --src=special:shapes8
            3         kwcoco stats --src=special:shapes8 --boxes=True

        name = stats

    classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> kw = {'src': 'special:shapes8'}
>>> cmdline = False
>>> cls = CocoStatsCLI
>>> cls.main(cmdline, **kw)
```

`kwcoco.cli.coco_stats._CLI`

kwcoco.cli.coco_subset**Module Contents****Classes**

CocoSubsetCLI

Functions

*query_subset(dset, config)***Example**

Attributes

_CLI

```
class kwcoco.cli.coco_subset.CocoSubsetCLI
    Bases: object

class CLICConfig(data=None, default=None, cmdline=False)
    Bases: scriptconfig.Config

    Take a subset of this dataset and write it to a new file

    default

    epilog = Multiline-String
```

1	Example Usage: kwcoco subset --src special:shapes8 --dst=foo.kwcoco.json
2	# Take only the even image-ids kwcoco subset --src special:shapes8 --dst=foo-even.kwcoco.
3	↳ json --select_images '.id % 2 == 0'
4	# Take only the videos where the name ends with 2
5	kwcoco subset --src special:vidshapes8 --dst=vidsub.
6	↳ kwcoco.json --select_videos '.name endswith("2")'

```
name = subset

@classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> kw = {'src': 'special:shapes8',
>>>         'dst': 'subset.json', 'include_categories': 'superstar'}
>>> cmdline = False
>>> cls = CocoSubsetCLI
>>> cls.main(cmdline, **kw)
```

kwcoco.cli.coco_subset.query_subset(dset, config)

Example

```
>>> # xdoctest: +REQUIRES(module:jq)
>>> from kwcoco.cli.coco_subset import * # NOQA
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo()
>>> assert dset.n_images == 3
>>> #
>>> config = CocoSubsetCLI.CLICConfig({'select_images': '.id < 3'})
>>> new_dset = query_subset(dset, config)
>>> assert new_dset.n_images == 2
>>> #
>>> config = CocoSubsetCLI.CLICConfig({'select_images': '.file_name | test(".*.png")'
-> ''})
>>> new_dset = query_subset(dset, config)
>>> assert all(n.endswith('.png') for n in new_dset.images().lookup('file_name'))
>>> assert new_dset.n_images == 2
>>> #
>>> config = CocoSubsetCLI.CLICConfig({'select_images': '.file_name | test(".*.png")'
-> '| not'})
>>> new_dset = query_subset(dset, config)
>>> assert not any(n.endswith('.png') for n in new_dset.images().lookup('file_name'
->'))
>>> assert new_dset.n_images == 1
>>> #
>>> config = CocoSubsetCLI.CLICConfig({'select_images': '.id < 3 and (.file_name |'
-> test(".*.png"))'})
>>> new_dset = query_subset(dset, config)
>>> assert new_dset.n_images == 1
>>> #
>>> config = CocoSubsetCLI.CLICConfig({'select_images': '.id < 3 or (.file_name |'
-> test(".*.png"))'})
>>> new_dset = query_subset(dset, config)
>>> assert new_dset.n_images == 3
```

Example

```
>>> # xdoctest: +REQUIRES(module:jq)
>>> from kwcoco.cli.coco_subset import * # NOQA
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes8')
>>> assert dset.n_videos == 8
>>> assert dset.n_images == 16
>>> config = CocoSubsetCLI.CLICConfig({'select_videos': '.name == "toy_video_3"'})
>>> new_dset = query_subset(dset, config)
>>> assert new_dset.n_images == 2
>>> assert new_dset.n_videos == 1
```

`kwcoco.cli.coco_subset._CLI`

`kwcoco.cli.coco_toydata`

Module Contents

Classes

`CocoToyDataCLI`

Attributes

`_CLI`

```
class kwcoco.cli.coco_toydata.CocoToyDataCLI
    Bases: object

    class CLICConfig(data=None, default=None, cmdline=False)
        Bases: scriptconfig.Config

        Create COCO toydata for demo and testing purposes.

        default

        epilog = Multiline-String

            Example Usage:
                kwcoco toydata --key=shapes8 --dst=toydata.kwcoco.json

            kwcoco toydata --key=shapes8 --bundle_dpath=my_test_
            ↪bundle_v1
            kwcoco toydata --key=shapes8 --bundle_dpath=my_test_
            ↪bundle_v1

            kwcoco toydata --key=shapes8
            ↪--dst=../shapes8.kwcoco/dataset.kwcoco.json
```

(continues on next page) ▾

(continued from previous page)

```
8
9     TODO:
10    - [ ] allow specification of images directory
```

```
name = toydata
classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> kw = {'key': 'shapes8', 'dst': 'test.json'}
>>> cmdline = False
>>> cls = CocoToyDataCLI
>>> cls.main(cmdline, **kw)
```

kwcoco.cli.coco_toydata._CLI

kwcoco.cli.coco_union

Module Contents

Classes

CocoUnionCLI

Attributes

_CLI

```
class kwcoco.cli.coco_union.CocoUnionCLI
    Bases: object

    class CLICConfig(data=None, default=None, cmdline=False)
        Bases: scriptconfig.Config

        Combine multiple COCO datasets into a single merged dataset.

        default

        epilog = Multiline-String
```

```
1     Example Usage:
2         kwcoco union --src special:shapes8 special:shapes1 --
3             dst=combo.ms coco.json
```

```
name = union
classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> kw = {'src': ['special:shapes8', 'special:shapes1']}
>>> cmdline = False
>>> cls = CocoUnionCLI
>>> cls.main(cmdline, **kw)
```

`kwcoco.cli.coco_union._CLI`

`kwcoco.cli.coco_validate`

Module Contents

Classes

`CocoValidateCLI`

Attributes

`_CLI`

```
class kwcoco.cli.coco_validate.CocoValidateCLI
    class CLIConfig(data=None, default=None, cmdline=False)
        Bases: scriptconfig.Config

        Validate that a coco file conforms to the json schema, that assets exist, and potentially fix corrupted assets
        by removing them.

        default
        epilog = Multiline-String
            1   Example Usage:
            2       kwcoco toydata --dst foo.json --key=special:shapes8
            3       kwcoco validate --src=foo.json --corrupted=True

        name = validate
        classmethod main(cls, cmdline=True, **kw)
```

Example

```
>>> from kwcoco.cli.coco_validate import * # NOQA
>>> kw = {'src': 'special:shapes8'}
>>> cmdline = False
>>> cls = CocoValidateCLI
>>> cls.main(cmdline, **kw)
```

kwcoco.cli.coco_validate._CLI

2.2.2 kwcoco.data

Submodules

kwcoco.data.grab_camvid

Downloads the CamVid data if necessary, and converts it to COCO.

Module Contents

Functions

`_devcheck_sample_full_image()`

`_devcheck_load_sub_image()`

`grab_camvid_train_test_val_splits(coco_dset,`
mode='segnet')

`grab_camvid_sampler()` Grab a kwcoco.CocoSampler object for the CamVid dataset.

`grab_coco_camvid()`

Example

`grab_raw_camvid()` Grab the raw camvid data.

`rgb_to_cid(r, g, b)`

`cid_to_rgb(cid)`

`convert_camvid_raw_to_coco(camvid_raw_info)` Converts the raw camvid format to an MSCOCO based format, (which lets use

`_define_camvid_class_hierarchy(dset)`

`main()` Dump the paths to the coco file to stdout

kwcoco.data.grab_camvid._devcheck_sample_full_image()

kwcoco.data.grab_camvid._devcheck_load_sub_image()

kwcoco.data.grab_camvid.grab_camvid_train_test_val_splits(coco_dset, mode='segnet')

`kwcoco.data.grab_camvid.grab_camvid_sampler()`
 Grab a kwcoco.CocoSampler object for the CamVid dataset.

Returns sampler

Return type kwcoco.CocoSampler

Example

```
>>> # xdoctest: +REQUIRES(--download)
>>> sampler = grab_camvid_sampler()
>>> print('sampler = {!r}'.format(sampler))
>>> # sampler.load_sample()
>>> for gid in ub.ProgIter(sampler.image_ids, desc='load image'):
>>>     img = sampler.load_image(gid)
```

`kwcoco.data.grab_camvid.grab_coco_camvid()`

Example

```
>>> # xdoctest: +REQUIRES(--download)
>>> dset = grab_coco_camvid()
>>> print('dset = {!r}'.format(dset))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> plt = kwplot.autoplt()
>>> plt.clf()
>>> dset.show_image(gid=1)
```

`kwcoco.data.grab_camvid.grab_raw_camvid()`

Grab the raw camvid data.

`kwcoco.data.grab_camvid.rgb_to_cid(r, g, b)`

`kwcoco.data.grab_camvid.cid_to_rgb(cid)`

`kwcoco.data.grab_camvid.convert_camvid_raw_to_coco(camvid_raw_info)`

Converts the raw camvid format to an MSCOCO based format, (which lets use use kwcoco's COCO backend).

Example

```
>>> # xdoctest: +REQUIRES(--download)
>>> camvid_raw_info = grab_raw_camvid()
>>> # test with a reduced set of data
>>> del camvid_raw_info['img_paths'][2:]
>>> del camvid_raw_info['mask_paths'][2:]
>>> dset = convert_camvid_raw_to_coco(camvid_raw_info)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> plt = kwplot.autoplt()
>>> kwplot.figure(fnum=1, pnum=(1, 2, 1))
>>> dset.show_image(gid=1)
```

(continues on next page)

(continued from previous page)

```
>>> kwplot.figure(fnum=1, pnum=(1, 2, 2))
>>> dset.show_image(gid=2)
```

kwcoco.data.grab_camvid._define_camvid_class_hierarchy(dset)**kwcoco.data.grab_camvid.main()**

Dump the paths to the coco file to stdout

By default these will go to in the path: `~/.cache/kwcoco/camvid/camvid-master`The four files will be: `~/.cache/kwcoco/camvid/camvid-master/camvid-full.mscoco.json``~/.cache/kwcoco/camvid/camvid-master/camvid-train.mscoco.json` `~/.cache/kwcoco/camvid/camvid-master/camvid-vali.mscoco.json` `~/.cache/kwcoco/camvid/camvid-master/camvid-test.mscoco.json`

kwcoco.data.grab_cifar

Downloads and converts CIFAR 10 and CIFAR 100 to kwcoco format

Module Contents

Functions

`_convert_cifar_x(dpath, cifar_dset, cifar_name, classes)`

`convert_cifar10(dpath=None)`

`convert_cifar100(dpath=None)`

`main()`

`kwcoco.data.grab_cifar._convert_cifar_x(dpath, cifar_dset, cifar_name, classes)``kwcoco.data.grab_cifar.convert_cifar10(dpath=None)``kwcoco.data.grab_cifar.convert_cifar100(dpath=None)``kwcoco.data.grab_cifar.main()`

kwcoco.data.grab_datasets

[] HMDB: a large human motion database - <https://serre-lab.clps.brown.edu/resource/hmdb-a-large-human-motion-database/>

[] <https://paperswithcode.com/dataset/imagenet>

[] <https://paperswithcode.com/dataset/coco>

[] <https://paperswithcode.com/dataset/fashion-mnist>

[] <https://paperswithcode.com/dataset/visual-question-answering>

[] <https://paperswithcode.com/dataset/lfw>
[] <https://paperswithcode.com/dataset/lsun>
[] <https://paperswithcode.com/dataset/ava>
[] <https://paperswithcode.com/dataset/activitynet>
[] <https://paperswithcode.com/dataset/clevr>:

kwcoco.data.grab_domainnet

References

<http://ai.bu.edu/M3SDA/#dataset>

Module Contents

Functions

grab_domain_net()

kwcoco.data.grab_domainnet.grab_domain_net()

Todo:

- [] Allow the user to specify the download directory, generalize this pattern across the data grab scripts.
-

kwcoco.data.grab_spacenet

References

<https://medium.com/the-downlinq/the-spacenet-7-multi-temporal-urban-development-challenge-algorithmic-baseline-4515ec9bd9fe>
<https://arxiv.org/pdf/2102.11958.pdf> <https://spacenet.ai/sn7-challenge/>

Module Contents

Functions

grab_spacenet7(data_dpath)

References

continues on next page

Table 31 – continued from previous page

<code>convert_spacenet_to_kwcoco(extract_dpath,</code>	Converts the raw SpaceNet7 dataset to kwcoco
<code>coco_fpath)</code>	
<code>main()</code>	

`kwcoco.data.grab_spacenet.grab_spacenet7(data_dpath)`

References

<https://spacenet.ai/sn7-challenge/>

Requires: awscli

`kwcoco.data.grab_spacenet.convert_spacenet_to_kwcoco(extract_dpath, coco_fpath)`

Converts the raw SpaceNet7 dataset to kwcoco

Note:

- The “train” directory contains 60 “videos” representing a region over time.
- **Each “video” directory contains :**
 - images - unmasked images
 - images_masked - images with masks applied
 - labels - geojson polys in wgs84?
 - labels_match - geojson polys in wgs84 with track ids?
 - labels_match_pix - geojson polys in pixels with track ids?
 - UDM_masks - unusable data masks (binary data corresponding with an image, may not exist)

File names appear like: “global_monthly_2018_01_mosaic_L15-1538E-1163N_6154_3539_13”

`kwcoco.data.grab_spacenet.main()`

`kwcoco.data.grab_voc`

Module Contents

Functions

<code>__torrent_voc()</code>	Requires:
<code>convert_voc_to_coco(dpath=None)</code>	
<code>_convert_voc_split(devkit_dpath, classes, split, split, year = 'train', 2012</code>	
<code>year, root)</code>	
<code>_read_split_paths(devkit_dpath, split, year)</code>	<code>split = 'train'</code>
<code>ensure_voc_data(dpath=None, force=False, years=[2007, 2012])</code>	Download the Pascal VOC data if it does not already exist.

continues on next page

Table 32 – continued from previous page

<code>ensure_voc_coco(dpath=None)</code>	Download the Pascal VOC data and convert it to coco, if it does exit.
<code>main()</code>	

`kwcoco.data.grab_voc.__torrent_voc()`

Requires: pip install deluge pip install python-libtorrent-bin

References

<https://academictorrents.com/details/f6ddac36ac7ae2ef79dc72a26a065b803c9c7230>

Todo:

- [] Is there a pythonic way to download a torrent programatically?
-

`kwcoco.data.grab_voc.convert_voc_to_coco(dpath=None)`

`kwcoco.data.grab_voc._convert_voc_split(devkit_dpath, classes, split, year, root)`
split, year = ‘train’, 2012 split, year = ‘train’, 2007

`kwcoco.data.grab_voc._read_split_paths(devkit_dpath, split, year)`
split = ‘train’ self = VOCdataset(‘test’) year = 2007 year = 2012

`kwcoco.data.grab_voc.ensure_voc_data(dpath=None, force=False, years=[2007, 2012])`
Download the Pascal VOC data if it does not already exist.

Note:

- [] These URLs seem to be dead
-

Example

```
>>> # xdoctest: +REQUIRES(--download)
>>> devkit_dpath = ensure_voc_data()
```

`kwcoco.data.grab_voc.ensure_voc_coco(dpath=None)`

Download the Pascal VOC data and convert it to coco, if it does exit.

Parameters `dpath` (`str`) – download directory. Defaults to “~/data/VOC”.

Returns

mapping from dataset tags to coco file paths. The original datasets have keys prefixed with underscores. The standard splits keys are train, vali, and test.

Return type `Dict[str, str]`

`kwcoco.data.grab_voc.main()`

2.2.3 kwcoco.demo

Submodules

kwcoco.demo.boids

Module Contents

Classes

<code>Boids</code>	Efficient numpy based backend for generating boid positions.
--------------------	--

Functions

<code>clamp_mag(vec, mag, axis=None)</code>	<code>vec = np.random.rand(10, 2)</code>
<code>triu_condense_multi_index(multi_index, dims, symmetric=False)</code>	Like <code>np.ravel_multi_index</code> but returns positions in an upper triangular
<code>_spatial_index_scratch()</code>	
<code>closest_point_on_line_segment(pts, e1, e2)</code>	Finds the closet point from p on line segment (e1, e2)
<code>_pygame_render_boids()</code>	Fast and responsive BOID rendering. This is an easter egg.
<code>_yeah_boid()</code>	

```
class kwcoco.demo.boids.Boids(num, dims=2, rng=None, **kwargs)
```

Bases: `ubelt.NiceRepr`

Efficient numpy based backend for generating boid positions.

BOID = bird-oid object

References

<https://www.youtube.com/watch?v=mhjuuHl6qHM> <https://medium.com/better-programming/boids-simulating-birds-flock-behavior-in-python-9fff99375118> <https://en.wikipedia.org/wiki/Boids>

Example

```
>>> from kwcoco.demo.boids import * # NOQA
>>> num_frames = 10
>>> num_objects = 3
>>> rng = None
>>> self = Boids(num=num_objects, rng=rng).initialize()
>>> paths = self.paths(num_frames)
>>> #
>>> # xdoctest: +REQUIRES(--show)
```

(continues on next page)

(continued from previous page)

```
>>> import kwplot
>>> plt = kwplot.autopl()t()
>>> from mpl_toolkits.mplot3d import Axes3D # NOQA
>>> ax = plt.gca(projection='3d')
>>> ax.cla()
>>> #
>>> for path in paths:
>>>     time = np.arange(len(path))
>>>     ax.plot(time, path.T[0] * 1, path.T[1] * 1, ',-')
>>> ax.set_xlim(0, num_frames)
>>> ax.set_ylim(-.01, 1.01)
>>> ax.set_zlim(-.01, 1.01)
>>> ax.set_xlabel('time')
>>> ax.set_ylabel('u-pos')
>>> ax.set_zlabel('v-pos')
>>> kwplot.show_if_requested()
```

```
import xdev _ = xdev.profile_now(self.compute_forces)() _ = xdev.profile_now(self.update_neighbors)()
```

Example

```
>>> # Test determinism
>>> from kwcoco.demo.boids import * # NOQA
>>> num_frames = 2
>>> num_objects = 1
>>> rng = 4532
>>> self = Boids(num=num_objects, rng=rng).initialize()
>>> #print(ub.hash_data(self.pos))
>>> #print(ub.hash_data(self.vel))
>>> #print(ub.hash_data(self.acc))
>>> tocheck = []
>>> for i in range(100):
>>>     self = Boids(num=num_objects, rng=rng).initialize()
>>>     self.step()
>>>     self.step()
>>>     self.step()
>>>     tocheck.append(self.pos.copy())
>>> assert ub.allsame(list(map(ub.hash_data, tocheck)))
```

```
__nice__(self)
initialize(self)
update_neighbors(self)
compute_forces(self)
boundary_conditions(self)
step(self)
Update positions, velocities, and accelerations
paths(self, num_steps)
```

```
kwcococo.demo.boids.clamp_mag(vec, mag, axis=None)
vec = np.random.rand(10, 2) mag = 1.0 axis = 1 new_vec = clamp_mag(vec, mag, axis) np.linalg.norm(new_vec,
axis=axis)
```

```
kwcococo.demo.boids.triu_condense_multi_index(multi_index, dims, symmetric=False)
```

Like np.ravel_multi_index but returns positions in an upper triangular condensed square matrix

Examples

multi_index (Tuple[ArrayLike]): indexes for each dimension into the square matrix

dims (Tuple[int]): shape of each dimension in the square matrix (should all be the same)

symmetric (bool): if True, converts lower triangular indices to their upper triangular location. This may cause a copy to occur.

References

<https://stackoverflow.com/a/36867493/887074> https://numpy.org/doc/stable/reference/generated/numpy.ravel_multi_index.html#numpy.ravel_multi_index

Examples

```
>>> dims = (3, 3)
>>> symmetric = True
>>> multi_index = (np.array([0, 0, 1]), np.array([1, 2, 2]))
>>> condensed_idxs = triu_condense_multi_index(multi_index, dims, symmetric=symmetric)
>>> assert condensed_idxs.tolist() == [0, 1, 2]
```

```
>>> n = 7
>>> symmetric = True
>>> multi_index = np.triu_indices(n=n, k=1)
>>> condensed_idxs = triu_condense_multi_index(multi_index, [n] * 2, ↴
    ↪symmetric=symmetric)
>>> assert condensed_idxs.tolist() == list(range(n * (n - 1) // 2))
>>> from scipy.spatial.distance import pdist, squareform
>>> square_mat = np.zeros((n, n))
>>> condens_mat = squareform(square_mat)
>>> condens_mat[condensed_idxs] = np.arange(len(condensed_idxs)) + 1
>>> square_mat = squareform(condens_mat)
>>> print('square_mat =\n{}'.format(ub.repr2(square_mat, nl=1)))
```

```
>>> n = 7
>>> symmetric = True
>>> multi_index = np.tril_indices(n=n, k=-1)
>>> condensed_idxs = triu_condense_multi_index(multi_index, [n] * 2, ↴
    ↪symmetric=symmetric)
>>> assert sorted(condensed_idxs.tolist()) == list(range(n * (n - 1) // 2))
>>> from scipy.spatial.distance import pdist, squareform
>>> square_mat = np.zeros((n, n))
>>> condens_mat = squareform(square_mat, checks=False)
>>> condens_mat[condensed_idxs] = np.arange(len(condensed_idxs)) + 1
```

(continues on next page)

(continued from previous page)

```
>>> square_mat = squareform(conden_mat)
>>> print('square_mat =\n{}'.format(ub.repr2(square_mat, nl=1)))
```

`kwcococo.demo.boids._spatial_index_scratch()`
`kwcococo.demo.boids.closest_point_on_line_segment(pts, e1, e2)`

Finds the closet point from p on line segment (e1, e2)

Parameters

- `pts (ndarray)` – xy points [Nx2]
- `e1 (ndarray)` – the first xy endpoint of the segment
- `e2 (ndarray)` – the second xy endpoint of the segment

Returns `pt_on_seg` - the closest xy point on (e1, e2) from ptp

Return type ndarray

References

http://en.wikipedia.org/wiki/Distance_from_a_point_to_a_line <http://stackoverflow.com/questions/849211/shortest-distance-between-a-point-and-a-line-segment>

Example

```
>>> # ENABLE_DOCTEST
>>> from kwcococo.demo.boids import * # NOQA
>>> verts = np.array([[ 21.83012702,  13.16987298],
>>>                   [ 16.83012702,  21.83012702],
>>>                   [  8.16987298,  16.83012702],
>>>                   [ 13.16987298,   8.16987298],
>>>                   [ 21.83012702,  13.16987298]])
```

`kwcococo.demo.boids._pygame_render_boids()`

Fast and responsive BOID rendering. This is an easter egg.

Requirements: pip install pygame

CommandLine

```
python -m kwcococo.demo.boids
pip install pygame kwcococo -U && python -m kwcococo.demo.boids
```

`kwcococo.demo.boids._yeah_boid()`

kwcoco.demo.perterb**Module Contents****Functions**

<code>perterb_coco(coco_dset, **kwargs)</code>	Perterbs a coco dataset
<code>_demo_construct_probs(pred_cxs, pred_scores, classes, rng, hacked=1)</code>	Constructs random probabilities for demo data

kwcoco.demo.perterb.perterb_coco(*coco_dset*, *kwargs*)**

Perterbs a coco dataset

Parameters

- **`rng`** (*int, default=0*)
- **`box_noise`** (*int, default=0*)
- **`cls_noise`** (*int, default=0*)
- **`null_pred`** (*bool, default=False*)
- **`with_probs`** (*bool, default=False*)
- **`score_noise`** (*float, default=0.2*)
- **`hacked`** (*int, default=1*)

Example

```
>>> from kwcoco.demo.perterb import * # NOQA
>>> from kwcoco.demo.perterb import _demo_construct_probs
>>> import kwcoco
>>> coco_dset = true_dset = kwcoco.CocoDataset.demo('shapes8')
>>> kwargs = {
>>>     'box_noise': 0.5,
>>>     'n_fp': 3,
>>>     'with_probs': 1,
>>>     'with_heatmaps': 1,
>>> }
>>> pred_dset = perterb_coco(true_dset, **kwargs)
>>> pred_dset._check_json_serializable()
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> gid = 1
>>> canvas = true_dset.delayed_load(gid).finalize()
>>> canvas = true_dset.annots(gid=gid).detections.draw_on(canvas, color='green')
>>> canvas = pred_dset.annots(gid=gid).detections.draw_on(canvas, color='blue')
>>> kwplot.imshow(canvas)
```

kwcoco.demo.perterb._demo_construct_probs(*pred_cxs*, *pred_scores*, *classes*, *rng*, *hacked=1*)

Constructs random probabilities for demo data

Example

```
>>> import kwcoco
>>> import kwarray
>>> rng = kwarray.ensure_rng(0)
>>> classes = kwcoco.CategoryTree.coerce(10)
>>> hacked = 1
>>> pred_cxs = rng.randint(0, 10, 10)
>>> pred_scores = rng.rand(10)
>>> probs = _demo_construct_probs(pred_cxs, pred_scores, classes, rng, hacked)
>>> probs.sum(axis=1)
```

kwcoco.demo.toydata

Generates “toydata” for demo and testing purposes.

Note: The implementation of *demodata_toy_img* and *demodata_toy_dset* should be redone using the tools built for *random_video_dset*, which have more extensible implementations.

Module Contents

Functions

<i>random_single_video_dset</i> (image_size=(600, 600), num_frames=5, num_tracks=3, tid_start=1, gid_start=1, video_id=1, anchors=None, rng=None, render=False, dpath=None, autobuild=True, verbose=3, aux=None, multispectral=False, max_speed=0.01, channels=None, multisensor=False, **kwargs)	Create the video scene layout of object positions.
<i>random_video_dset</i> (num_videos=1, num_frames=2, num_tracks=2, anchors=None, image_size=(600, 600), verbose=3, render=False, aux=None, multispectral=False, multisensor=False, rng=None, dpath=None, max_speed=0.01, channels=None, **kwargs)	Create a toy Coco Video Dataset
<i>demodata_toy_dset</i> (image_size=(600, 600), n_imgs=5, verbose=3, rng=0, newstyle=True, dpath=None, bundle_dpath=None, aux=None, use_cache=True, **kwargs)	Create a toy detection problem
<i>demodata_toy_img</i> (anchors=None, image_size=(104, 104), categories=None, n_annots=(0, 50), fg_scale=0.5, bg_scale=0.8, bg_intensity=0.1, fg_intensity=0.9, gray=True, centerobj=None, exact=False, newstyle=True, rng=None, aux=None, **kwargs)	Generate a single image with non-overlapping toy objects of available

```
kwcoco.demo.toydata.random_single_video_dset(image_size=(600, 600), num_frames=5, num_tracks=3,  
tid_start=1, gid_start=1, video_id=1, anchors=None,  
rng=None, render=False, dpath=None, autobuild=True,  
verbose=3, aux=None, multispectral=False,  
max_speed=0.01, channels=None, multisensor=False,  
**kwargs)
```

Create the video scene layout of object positions.

Note: Does not render the data unless specified.

Parameters

- **image_size** (*Tuple[int, int]*) – size of the images
- **num_frames** (*int*) – number of frames in this video
- **num_tracks** (*int*) – number of tracks in this video
- **tid_start** (*int, default=1*) – track-id start index
- **gid_start** (*int, default=1*) – image-id start index
- **video_id** (*int, default=1*) – video-id of this video
- **anchors** (*ndarray | None*) – base anchor sizes of the object boxes we will generate.
- **rng** (*RandomState*) – random state / seed
- **render** (*bool | dict*) – if truthy, does the rendering according to provided params in the case of dict input.
- **autobuild** (*bool, default=True*) – prebuild coco lookup indexes
- **verbose** (*int*) – verbosity level
- **aux** (*bool | List[str]*) – if specified generates auxiliary channels
- **multispectral** (*bool*) – if specified simulates multispectral imagery This is similar to aux, but has no “main” file.
- **max_speed** (*float*) – max speed of movers
- **channels** (*str | None | ChannelSpec*) – if specified generates multispectral images with dummy channels
- **multisensor** (*bool*) –
if True, generates demodata from “multiple sensors”, in other words, observations may have different “bands”.
- ****kwargs** – used for old backwards compatible argument names gsize - alias for image_size

Todo:

- [] Need maximum allowed object overlap measure
 - [] Need better parameterized path generation
-

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> anchors = np.array([ [0.3, 0.3], [0.1, 0.1]] )
>>> dset = random_single_video_dset(render=True, num_frames=10, num_tracks=10, anchors=anchors, max_speed=0.2)
>>> # xdoctest: +REQUIRES(--show)
>>> # Show the tracks in a single image
>>> import kwplot
>>> kwplot.autopl()
>>> annots = dset.annots()
>>> tids = annots.lookup('track_id')
>>> tid_to_aids = ub.group_items(annots.aids, tids)
>>> paths = []
>>> track_boxes = []
>>> for tid, aids in tid_to_aids.items():
>>>     boxes = dset.annots(aids).boxes.to_cxywh()
>>>     path = boxes.data[:, 0:2]
>>>     paths.append(path)
>>>     track_boxes.append(boxes)
>>> import kwplot
>>> plt = kwplot.autopl()
>>> ax = plt.gca()
>>> ax.cla()
>>> #
>>> import kwimage
>>> colors = kwimage.Color.distinct(len(track_boxes))
>>> for i, boxes in enumerate(track_boxes):
>>>     color = colors[i]
>>>     path = boxes.data[:, 0:2]
>>>     boxes.draw(color=color, centers={'radius': 0.01}, alpha=0.5)
>>>     ax.plot(path.T[0], path.T[1], 'x-', color=color)
```

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> anchors = np.array([ [0.2, 0.2], [0.1, 0.1]] )
>>> gsize = np.array([(600, 600)])
>>> print(anchors * gsize)
>>> dset = random_single_video_dset(render=True, num_frames=10,
>>>                                   anchors=anchors, num_tracks=10,
>>>                                   image_size='random')
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> plt = kwplot.autopl()
>>> plt.clf()
>>> gids = list(dset.imgs.keys())
>>> pnums = kwplot.PlotNums(nSubplots=len(gids))
>>> for gid in gids:
>>>     dset.show_image(gid, pnum=pnums(), fnum=1, title=False)
>>>     pnums = kwplot.PlotNums(nSubplots=len(gids))
```

Example

```
>>> from kwCOCO.demo.toydata_video import * # NOQA
>>> dset = random_single_video_dset(num_frames=10, num_tracks=10, aux=True)
>>> assert 'auxiliary' in dset.imgs[1]
>>> assert dset.imgs[1]['auxiliary'][0]['channels']
>>> assert dset.imgs[1]['auxiliary'][1]['channels']
```

Example

```
>>> from kwCOCO.demo.toydata_video import * # NOQA
>>> multispectral = True
>>> dset = random_single_video_dset(num_frames=1, num_tracks=1, multispectral=True)
>>> dset._check_json_serializable()
>>> dset.dataset['images']
>>> assert dset.imgs[1]['auxiliary'][1]['channels']
>>> # test that we can render
>>> render_toy_dataset(dset, rng=0, dpath=None, renderkw={})
```

Example

```
>>> from kwCOCO.demo.toydata_video import * # NOQA
>>> dset = random_single_video_dset(num_frames=4, num_tracks=1, multispectral=True, ↴
    ↵multisensor=True, image_size='random', rng=2338)
>>> dset._check_json_serializable()
>>> assert dset.imgs[1]['auxiliary'][1]['channels']
>>> # Print before and after render
>>> #print('multisensor-images = {}'.format(ub.repr2(dset.dataset['images'], nl=-2)))
>>> #print('multisensor-images = {}'.format(ub.repr2(dset.dataset, nl=-2)))
>>> print(ub.hash_data(dset.dataset))
>>> # test that we can render
>>> render_toy_dataset(dset, rng=0, dpath=None, renderkw={})
>>> #print('multisensor-images = {}'.format(ub.repr2(dset.dataset['images'], nl=-2)))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> from kwCOCO.demo.toydata_video import _draw_video_sequence # NOQA
>>> gids = [1, 2, 3, 4]
>>> final = _draw_video_sequence(dset, gids)
>>> print('dset.fpath = {!r}'.format(dset.fpath))
>>> kwplot.imshow(final)
```

```
kwCOCO.demo.toydata.random_video_dset(num_videos=1, num_frames=2, num_tracks=2, anchors=None,
                                         image_size=(600, 600), verbose=3, render=False, aux=None,
                                         multispectral=False, multisensor=False, rng=None, dpath=None,
                                         max_speed=0.01, channels=None, **kwargs)
```

Create a toy Coco Video Dataset

Parameters

- **num_videos** (*int*) – number of videos

- **num_frames** (*int*) – number of images per video
- **num_tracks** (*int*) – number of tracks per video
- **image_size** (*Tuple[int, int]*) – The width and height of the generated images
- **render** (*bool | dict*) – if truthy the toy annotations are synthetically rendered. See `render_toy_image()` for details.
- **rng** (*int | None | RandomState*) – random seed / state
- **dpath** (*str*) – only used if render is truthy, place to write rendered images.
- **verbose** (*int, default=3*) – verbosity mode
- **aux** (*bool*) – if True generates dummy auxiliary channels
- **multispectral** (*bool*) – similar to aux, but does not have the concept of a “main” image.
- **max_speed** (*float*) – max speed of movers
- **channels** (*str*) – experimental new way to get MSI with specific band distributions.
- ****kwargs** – used for old backwards compatible argument names gsize - alias for image_size

SeeAlso: `random_single_video_dset`

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> dset = random_video_dset(render=True, num_videos=3, num_frames=2,
>>>                      num_tracks=5, image_size=(128, 128))
>>> # xdoctest: +REQUIRES(--show)
>>> dset.show_image(1, doclf=True)
>>> dset.show_image(2, doclf=True)
```

```
>>> from kwcoco.demo.toydata_video import * # NOQA
dset = random_video_dset(render=False, num_videos=3, num_frames=2,
    num_tracks=10)
dset._tree()
dset.imgs[1]
```

```
dset = random_single_video_dset() dset._tree() dset.imgs[1]
from kwcoco.demo.toydata_video import * # NOQA dset = random_video_dset(render=True, num_videos=3,
num_frames=2,
    num_tracks=10)
print(dset.imgs[1]) print('dset.bundle_dpath = {!r}'.format(dset.bundle_dpath)) dset._tree()
import xdev globals().update(xdev.get_func_kwargs(random_video_dset)) num_videos = 2
kwcoco.demo.toydata.demodata_toy_dset(image_size=(600, 600), n_imgs=5, verbose=3, rng=0,
    newstyle=True, dpath=None, bundle_dpath=None, aux=None,
    use_cache=True, **kwargs)
```

Create a toy detection problem

Parameters

- **image_size** (*Tuple[int, int]*) – The width and height of the generated images

- **n_imgs** (*int*) – number of images to generate
- **rng** (*int | RandomState, default=0*) – random number generator or seed
- **newstyle** (*bool, default=True*) – create newstyle kwcoco data
- **dpath** (*str*) – path to the directory that will contain the bundle, (defaults to a kwcoco cache dir). Ignored if *bundle_dpath* is given.
- **bundle_dpath** (*str*) – path to the directory that will store images. If specified, *dpath* is ignored. If unspecified, a bundle will be written inside *dpath*.
- **aux** (*bool*) – if True generates dummy auxiliary channels
- **verbose** (*int, default=3*) – verbosity mode
- **use_cache** (*bool, default=True*) – if True caches the generated json in the *dpath*.
- ****kwargs** – used for old backwards compatible argument names gsize - alias for image_size

Return type *kwcoco.CocoDataset*

SeeAlso: random_video_dset

CommandLine

```
xdoctest -m kwcoco.demo.toydata_image demodata_toy_dset --show
```

Todo:

- [] Non-homogeneous images sizes
-

Example

```
>>> from kwcoco.demo.toydata_image import *
>>> import kwcoco
>>> dset = demodata_toy_dset(image_size=(300, 300), aux=True, use_cache=False)
>>> # xdoctest: +REQUIRES(--show)
>>> print(ub.repr2(dset.dataset, nl=2))
>>> import kwplot
>>> kwplot.autopl()l()
>>> dset.show_image(gid=1)
>>> ub.startfile(dset.bundle_dpath)
```

dset._tree()

```
>>> from kwcoco.demo.toydata_image import *
>>> import kwcoco
```

```
dset = demodata_toy_dset(image_size=(300, 300), aux=True, use_cache=False) print(dset.imgs[1]) dset._tree()
dset = demodata_toy_dset(image_size=(300, 300), aux=True, use_cache=False, bundle_dpath='test_bundle')
print(dset.imgs[1]) dset._tree()
dset = demodata_toy_dset( image_size=(300, 300), aux=True, use_cache=False, dpath='test_cache_dpath')
```

```
kwcoco.demo.toydata.demodata_toy_img(anchors=None, image_size=(104, 104), categories=None,
                                         n_annot=(0, 50), fg_scale=0.5, bg_scale=0.8, bg_intensity=0.1,
                                         fg_intensity=0.9, gray=True, centerobj=None, exact=False,
                                         newstyle=True, rng=None, aux=None, **kwargs)
```

Generate a single image with non-overlapping toy objects of available categories.

Todo:

DEPRECATE IN FAVOR OF random_single_video_dset + render_toy_image

Parameters

- **anchors** (*ndarray*) – Nx2 base width / height of boxes
- **gsize** (*Tuple[int, int]*) – width / height of the image
- **categories** (*List[str]*) – list of category names
- **n_annot** (*Tuple | int*) – controls how many annotations are in the image. if it is a tuple, then it is interpreted as uniform random bounds
- **fg_scale** (*float*) – standard deviation of foreground intensity
- **bg_scale** (*float*) – standard deviation of background intensity
- **bg_intensity** (*float*) – mean of background intensity
- **fg_intensity** (*float*) – mean of foreground intensity
- **centerobj** (*bool*) – if ‘pos’, then the first annotation will be in the center of the image, if ‘neg’, then no annotations will be in the center.
- **exact** (*bool*) – if True, ensures that exactly the number of specified annots are generated.
- **newstyle** (*bool*) – use new-syle kwcoco format
- **rng** (*RandomState*) – the random state used to seed the process
- **aux** – if specified builds auxiliary channels
- ****kwargs** – used for old backwards compatible argument names. gsize - alias for image_size

CommandLine

```
xdoctest -m kwcoco.demo.toydata_image demodata_toy_img:0 --profile
xdoctest -m kwcoco.demo.toydata_image demodata_toy_img:1 --show
```

Example

```
>>> from kwcoco.demo.toydata_image import * # NOQA
>>> img, anns = demodata_toy_img(image_size=(32, 32), anchors=[[.3, .3]], rng=0)
>>> img['imdata'] = '<ndarray shape={}>'.format(img['imdata'].shape)
>>> print('img = {}'.format(ub.repr2(img)))
>>> print('anns = {}'.format(ub.repr2(anns, nl=2, cbr=True)))
>>> # xdoctest: +IGNORE_WANT
img = {
    'height': 32,
```

(continues on next page)

(continued from previous page)

```
'imdata': '<ndarray shape=(32, 32, 3)>',
'width': 32,
}
anns = [{`bbox': [15, 10, 9, 8],
'category_name': 'star',
'keypoints': [],
'segmentation': {'counts': '[`06j0000020N1000e8', 'size': [32, 32]},},
{'bbox': [11, 20, 7, 7],
'category_name': 'star',
'keypoints': [],
'segmentation': {'counts': 'g;1m04N0020N102L[=', 'size': [32, 32]},},
{'bbox': [4, 4, 8, 6],
'category_name': 'superstar',
'keypoints': [{"keypoint_category': 'left_eye', 'xy': [7.25, 6.8125]}, {"keypoint_category': 'right_eye', 'xy': [8.75, 6.8125]}],
'segmentation': {'counts': 'U4210j0300001010000MV00ed0', 'size': [32, 32]},},
{'bbox': [3, 20, 6, 7],
'category_name': 'star',
'keypoints': [],
'segmentation': {'counts': 'g31m04N000002L[f0', 'size': [32, 32]},},]
```

Example

```
>>> # xdoctest: +REQUIRES(--show)
>>> img, anns = demodata_toy_img(image_size=(172, 172), rng=None, aux=True)
>>> print('anns = {}'.format(ub.repr2(anns, nl=1)))
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(img['imdata'], pnum=(1, 2, 1), fnum=1)
>>> auxdata = img['auxiliary'][0]['imdata']
>>> kwplot.imshow(auxdata, pnum=(1, 2, 2), fnum=1)
>>> kwplot.show_if_requested()
```

Example

```
>>> # xdoctest: +REQUIRES(--show)
>>> img, anns = demodata_toy_img(image_size=(172, 172), rng=None, aux=True)
>>> print('anns = {}'.format(ub.repr2(anns, nl=1)))
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(img['imdata'], pnum=(1, 2, 1), fnum=1)
>>> auxdata = img['auxiliary'][0]['imdata']
>>> kwplot.imshow(auxdata, pnum=(1, 2, 2), fnum=1)
>>> kwplot.show_if_requested()
```

kwcoco.demo.toydata_image

Generates “toydata” for demo and testing purposes.

Loose image version of the toydata generators.

Note: The implementation of `demodata_toy_img` and `demodata_toy_dset` should be redone using the tools built for `random_video_dset`, which have more extensible implementations.

Module Contents

Functions

<code>demodata_toy_dset(image_size=(600, 600), n_imgs=5, verbose=3, rng=0, newstyle=True, dpath=None, bundle_dpath=None, aux=None, use_cache=True, **kwargs)</code>	Create a toy detection problem
<code>demodata_toy_img(anchors=None, image_size=(104, 104), categories=None, n_annots=(0, 50), fg_scale=0.5, bg_scale=0.8, bg_intensity=0.1, fg_intensity=0.9, gray=True, centerobj=None, exact=False, newstyle=True, rng=None, aux=None, **kwargs)</code>	Generate a single image with non-overlapping toy objects of available

Attributes

`profile`

`TOYDATA_IMAGE_VERSION`

kwcoco.demo.toydata_image.profile

`kwcoco.demo.toydata_image.TODYDATA_IMAGE_VERSION = 20`

`kwcoco.demo.toydata_image.demodata_toy_dset(image_size=(600, 600), n_imgs=5, verbose=3, rng=0, newstyle=True, dpath=None, bundle_dpath=None, aux=None, use_cache=True, **kwargs)`

Create a toy detection problem

Parameters

- `image_size` (`Tuple[int, int]`) – The width and height of the generated images
- `n_imgs` (`int`) – number of images to generate
- `rng` (`int | RandomState, default=0`) – random number generator or seed
- `newstyle` (`bool, default=True`) – create newstyle kwococo data
- `dpath` (`str`) – path to the directory that will contain the bundle, (defaults to a kwococo cache dir). Ignored if `bundle_dpath` is given.

- **bundle_dpath** (*str*) – path to the directory that will store images. If specified, dpath is ignored. If unspecified, a bundle will be written inside *dpath*.
- **aux** (*bool*) – if True generates dummy auxiliary channels
- **verbose** (*int, default=3*) – verbosity mode
- **use_cache** (*bool, default=True*) – if True caches the generated json in the *dpath*.
- ****kwargs** – used for old backwards compatible argument names gsize - alias for image_size

Return type *kwcoco.CocoDataset*

SeeAlso: random_video_dset

CommandLine

```
xdoctest -m kwcoco.demo.toydata_image demodata_toy_dset --show
```

Todo:

- [] Non-homogeneous images sizes
-

Example

```
>>> from kwcoco.demo.toydata_image import *
>>> import kwcoco
>>> dset = demodata_toy_dset(image_size=(300, 300), aux=True, use_cache=False)
>>> # xdoctest: +REQUIRES(--show)
>>> print(ub.repr2(dset.dataset, nl=2))
>>> import kwplot
>>> kwplot.autopl()
>>> dset.show_image(gid=1)
>>> ub.startfile(dset.bundle_dpath)
```

dset._tree()

```
>>> from kwcoco.demo.toydata_image import *
>>> import kwcoco
```

```
dset = demodata_toy_dset(image_size=(300, 300), aux=True, use_cache=False) print(dset.imgs[1]) dset._tree()

dset = demodata_toy_dset(image_size=(300, 300), aux=True, use_cache=False, bundle_dpath='test_bundle')
print(dset.imgs[1]) dset._tree()

dset = demodata_toy_dset(image_size=(300, 300), aux=True, use_cache=False, dpath='test_cache_dpath')

kwcoco.demo.toydata_image.demodata_toy_img(anchors=None, image_size=(104, 104), categories=None,
                                             n_annot=(0, 50), fg_scale=0.5, bg_scale=0.8,
                                             bg_intensity=0.1, fg_intensity=0.9, gray=True,
                                             centerobj=None, exact=False, newstyle=True, rng=None,
                                             aux=None, **kwargs)
```

Generate a single image with non-overlapping toy objects of available categories.

Todo:**DEPRECATE IN FAVOR OF** random_single_video_dset + render_toy_image

Parameters

- **anchors** (*ndarray*) – Nx2 base width / height of boxes
- **gsize** (*Tuple[int, int]*) – width / height of the image
- **categories** (*List[str]*) – list of category names
- **n_annot** (*Tuple | int*) – controls how many annotations are in the image. if it is a tuple, then it is interpreted as uniform random bounds
- **fg_scale** (*float*) – standard deviation of foreground intensity
- **bg_scale** (*float*) – standard deviation of background intensity
- **bg_intensity** (*float*) – mean of background intensity
- **fg_intensity** (*float*) – mean of foreground intensity
- **centerobj** (*bool*) – if ‘pos’, then the first annotation will be in the center of the image, if ‘neg’, then no annotations will be in the center.
- **exact** (*bool*) – if True, ensures that exactly the number of specified annots are generated.
- **newstyle** (*bool*) – use new-style kwcoco format
- **rng** (*RandomState*) – the random state used to seed the process
- **aux** – if specified builds auxiliary channels
- ****kwargs** – used for old backwards compatible argument names. gsize - alias for image_size

CommandLine

```
xdoctest -m kwcoco.demo.toydata_image demodata_toy_img:0 --profile
xdoctest -m kwcoco.demo.toydata_image demodata_toy_img:1 --show
```

Example

```
>>> from kwcoco.demo.toydata_image import * # NOQA
>>> img, anns = demodata_toy_img(image_size=(32, 32), anchors=[[.3, .3]], rng=0)
>>> img['imdata'] = '<ndarray shape={}>'.format(img['imdata'].shape)
>>> print('img = {}'.format(ub.repr2(img)))
>>> print('anns = {}'.format(ub.repr2(anns, nl=2, cbr=True)))
>>> # xdoctest: +IGNORE_WANT
img = {
    'height': 32,
    'imdata': '<ndarray shape=(32, 32, 3)>',
    'width': 32,
}
anns = [{`bbox`: [15, 10, 9, 8],
    'category_name': 'star',
```

(continues on next page)

(continued from previous page)

```
'keypoints': [],
'segmentation': {'counts': '[`06j0000020N1000e8', 'size': [32, 32]}, {},
{'bbox': [11, 20, 7, 7],
'category_name': 'star',
'keypoints': [],
'segmentation': {'counts': 'g;1m04N0020N102L[=', 'size': [32, 32]}, {},
{'bbox': [4, 4, 8, 6],
'category_name': 'superstar',
'keypoints': [{"keypoint_category': 'left_eye', 'xy': [7.25, 6.8125]}, {"keypoint_
category': 'right_eye', 'xy': [8.75, 6.8125]}],
'segmentation': {'counts': 'U4210j0300001010000MV00ed0', 'size': [32, 32]}, {},
{'bbox': [3, 20, 6, 7],
'category_name': 'star',
'keypoints': [],
'segmentation': {'counts': 'g31m04N000002L[f0', 'size': [32, 32]}, {}]
```

Example

```
>>> # xdoctest: +REQUIRES(--show)
>>> img, anns = demodata_toy_img(image_size=(172, 172), rng=None, aux=True)
>>> print('anns = {}'.format(ub.repr2(anns, nl=1)))
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(img['imdata'], pnum=(1, 2, 1), fnum=1)
>>> auxdata = img['auxiliary'][0]['imdata']
>>> kwplot.imshow(auxdata, pnum=(1, 2, 2), fnum=1)
>>> kwplot.show_if_requested()
```

Example

```
>>> # xdoctest: +REQUIRES(--show)
>>> img, anns = demodata_toy_img(image_size=(172, 172), rng=None, aux=True)
>>> print('anns = {}'.format(ub.repr2(anns, nl=1)))
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(img['imdata'], pnum=(1, 2, 1), fnum=1)
>>> auxdata = img['auxiliary'][0]['imdata']
>>> kwplot.imshow(auxdata, pnum=(1, 2, 2), fnum=1)
>>> kwplot.show_if_requested()
```

kwcoco.demo.toydata_video

Generates “toydata” for demo and testing purposes.

This is the video version of the toydata generator and should be preferred to the loose image version in toydata_image.

Module Contents

Functions

<code>random_video_dset(num_videos=1, num_frames=2, num_tracks=2, anchors=None, image_size=(600, 600), verbose=3, render=False, aux=None, multispectral=False, multisensor=False, rng=None, dpath=None, max_speed=0.01, channels=None, **kwargs)</code>	Create a toy Coco Video Dataset
<code>random_single_video_dset(image_size=(600, 600), num_frames=5, num_tracks=3, tid_start=1, gid_start=1, video_id=1, anchors=None, rng=None, render=False, dpath=None, autobuild=True, verbose=3, aux=None, multispectral=False, max_speed=0.01, channels=None, multisensor=False, **kwargs)</code>	Create the video scene layout of object positions.
<code>_draw_video_sequence(dset, gids)</code>	Helper to draw a multi-sensor sequence
<code>render_toy_dataset(dset, rng, dpath=None, renderkw=None, verbose=0)</code>	Create toydata_video renderings for a preconstructed coco dataset.
<code>render_toy_image(dset, gid, rng=None, renderkw=None)</code>	Modifies dataset inplace, rendering synthetic annotations.
<code>render_foreground(imdata, chan_to_auxinfo, dset, annots, catpats, with_sseg, with_kpts, dims, newstyle, gray, rng)</code>	Renders demo annotations on top of a demo background
<code>render_background(img, rng, gray, bg_intensity, bg_scale)</code>	
<code>false_color(twochan)</code>	TODO: the function ensure_false_color will eventually be ported to kwimage
<code>random_multi_object_path(num_objects, num_frames, rng=None, max_speed=0.01)</code>	
<code>random_path(num, degree=1, dimension=2, rng=None, mode='boid')</code>	Create a random path using a somem ethod curve.

Attributes

`profile`

`TOYDATA_VIDEO_VERSION`

`kwcoco.demo.toydata_video.profile`

`kwcoco.demo.toydata_video.TOYDATA_VIDEO_VERSION = 21`

```
kwcoco.demo.toydata_video.random_video_dset(num_videos=1, num_frames=2, num_tracks=2,
                                             anchors=None, image_size=(600, 600), verbose=3,
                                             render=False, aux=None, multispectral=False,
                                             multisensor=False, rng=None, dpath=None,
                                             max_speed=0.01, channels=None, **kwargs)
```

Create a toy Coco Video Dataset

Parameters

- **num_videos** (*int*) – number of videos
- **num_frames** (*int*) – number of images per video
- **num_tracks** (*int*) – number of tracks per video
- **image_size** (*Tuple[int, int]*) – The width and height of the generated images
- **render** (*bool | dict*) – if truthy the toy annotations are synthetically rendered. See [render_toy_image\(\)](#) for details.
- **rng** (*int | None | RandomState*) – random seed / state
- **dpath** (*str*) – only used if render is truthy, place to write rendered images.
- **verbose** (*int, default=3*) – verbosity mode
- **aux** (*bool*) – if True generates dummy auxiliary channels
- **multispectral** (*bool*) – similar to aux, but does not have the concept of a “main” image.
- **max_speed** (*float*) – max speed of movers
- **channels** (*str*) – experimental new way to get MSI with specific band distributions.
- ****kwargs** – used for old backwards compatible argument names gsize - alias for image_size

SeeAlso: [random_single_video_dset](#)

Example

```
>>> from kwCOCO.demo.toydata_video import * # NOQA
>>> dset = random_video_dset(render=True, num_videos=3, num_frames=2,
                               num_tracks=5, image_size=(128, 128))
>>> # xdoctest: +REQUIRES(--show)
>>> dset.show_image(1, doclf=True)
>>> dset.show_image(2, doclf=True)
```

```
>>> from kwCOCO.demo.toydata_video import * # NOQA
dset = random_video_dset(render=False, num_videos=3, num_frames=2,
                         num_tracks=10)
dset._tree()
dset.imgs[1]
```

```
dset = random_single_video_dset() dset._tree() dset.imgs[1]
```

```
from kwCOCO.demo.toydata_video import * # NOQA dset = random_video_dset(render=True, num_videos=3,
                           num_frames=2,
                           num_tracks=10)
```

```

print(dset.imgs[1]) print('dset.bundle_dpath = {!r}'.format(dset.bundle_dpath)) dset._tree()
import xdev globals().update(xdev.get_func_kwargs(random_video_dset)) num_videos = 2
kwcoco.demo.toydata_video.random_single_video_dset(image_size=(600, 600), num_frames=5,
                                                    num_tracks=3, tid_start=1, gid_start=1,
                                                    video_id=1, anchors=None, rng=None,
                                                    render=False, dpath=None, autobuild=True,
                                                    verbose=3, aux=None, multispectral=False,
                                                    max_speed=0.01, channels=None,
                                                    multisensor=False, **kwargs)

```

Create the video scene layout of object positions.

Note: Does not render the data unless specified.

Parameters

- **image_size** (*Tuple[int, int]*) – size of the images
- **num_frames** (*int*) – number of frames in this video
- **num_tracks** (*int*) – number of tracks in this video
- **tid_start** (*int, default=1*) – track-id start index
- **gid_start** (*int, default=1*) – image-id start index
- **video_id** (*int, default=1*) – video-id of this video
- **anchors** (*ndarray | None*) – base anchor sizes of the object boxes we will generate.
- **rng** (*RandomState*) – random state / seed
- **render** (*bool | dict*) – if truthy, does the rendering according to provided params in the case of dict input.
- **autobuild** (*bool, default=True*) – prebuild coco lookup indexes
- **verbose** (*int*) – verbosity level
- **aux** (*bool | List[str]*) – if specified generates auxiliary channels
- **multispectral** (*bool*) – if specified simulates multispectral imagery This is similar to aux, but has no “main” file.
- **max_speed** (*float*) – max speed of movers
- **channels** (*str | None | ChannelSpec*) – if specified generates multispectral images with dummy channels
- **multisensor** (*bool*) –

if True, generates demodata from “multiple sensors”, in other words, observations may have different “bands”.
- ****kwargs** – used for old backwards compatible argument names gsize - alias for image_size

Todo:

- [] Need maximum allowed object overlap measure
- [] Need better parameterized path generation

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> anchors = np.array([ [0.3, 0.3], [0.1, 0.1]] )
>>> dset = random_single_video_dset(render=True, num_frames=10, num_tracks=10, ↴
    ↪anchors=anchors, max_speed=0.2)
>>> # xdoctest: +REQUIRES(--show)
>>> # Show the tracks in a single image
>>> import kwplot
>>> kwplot.autompl()
>>> annots = dset.annots()
>>> tids = annots.lookup('track_id')
>>> tid_to_aids = ub.group_items(annots.aids, tids)
>>> paths = []
>>> track_boxes = []
>>> for tid, aids in tid_to_aids.items():
>>>     boxes = dset.annots(aids).boxes.to_cxywh()
>>>     path = boxes.data[:, 0:2]
>>>     paths.append(path)
>>>     track_boxes.append(boxes)
>>> import kwplot
>>> plt = kwplot.autopl()
>>> ax = plt.gca()
>>> ax.cla()
>>> #
>>> import kwimage
>>> colors = kwimage.Color.distinct(len(track_boxes))
>>> for i, boxes in enumerate(track_boxes):
>>>     color = colors[i]
>>>     path = boxes.data[:, 0:2]
>>>     boxes.draw(color=color, centers={'radius': 0.01}, alpha=0.5)
>>>     ax.plot(path.T[0], path.T[1], 'x-', color=color)
```

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> anchors = np.array([ [0.2, 0.2], [0.1, 0.1]] )
>>> gsize = np.array([(600, 600)])
>>> print(anchors * gsize)
>>> dset = random_single_video_dset(render=True, num_frames=10,
>>>                                 anchors=anchors, num_tracks=10,
>>>                                 image_size='random')
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> plt = kwplot.autopl()
>>> plt.clf()
>>> gids = list(dset.imgs.keys())
>>> pnums = kwplot.PlotNums(nSubplots=len(gids))
>>> for gid in gids:
```

(continues on next page)

(continued from previous page)

```
>>>     dset.show_image(gid, pnum=pnums(), fnum=1, title=False)
>>> pnums = kwplot.PlotNums(nSubplots=len(gids))
```

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> dset = random_single_video_dset(num_frames=10, num_tracks=10, aux=True)
>>> assert 'auxiliary' in dset.imgs[1]
>>> assert dset.imgs[1]['auxiliary'][0]['channels']
>>> assert dset.imgs[1]['auxiliary'][1]['channels']
```

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> multispectral = True
>>> dset = random_single_video_dset(num_frames=1, num_tracks=1, multispectral=True)
>>> dset._check_json_serializable()
>>> dset.dataset['images']
>>> assert dset.imgs[1]['auxiliary'][1]['channels']
>>> # test that we can render
>>> render_toy_dataset(dset, rng=0, dpath=None, renderkw={})
```

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> dset = random_single_video_dset(num_frames=4, num_tracks=1, multispectral=True, ↴
    ↪multisensor=True, image_size='random', rng=2338)
>>> dset._check_json_serializable()
>>> assert dset.imgs[1]['auxiliary'][1]['channels']
>>> # Print before and after render
>>> #print('multisensor-images = {}'.format(ub.repr2(dset.dataset['images'], nl=-2)))
>>> #print('multisensor-images = {}'.format(ub.repr2(dset.dataset, nl=-2)))
>>> print(ub.hash_data(dset.dataset))
>>> # test that we can render
>>> render_toy_dataset(dset, rng=0, dpath=None, renderkw={})
>>> #print('multisensor-images = {}'.format(ub.repr2(dset.dataset['images'], nl=-2)))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> from kwcoco.demo.toydata_video import _draw_video_sequence # NOQA
>>> gids = [1, 2, 3, 4]
>>> final = _draw_video_sequence(dset, gids)
>>> print('dset.fpath = {!r}'.format(dset.fpath))
>>> kwplot.imshow(final)
```

`kwcoco.demo.toydata_video._draw_video_sequence(dset, gids)`

Helper to draw a multi-sensor sequence

`kwcoco.demo.toydata_video.render_toy_dataset(dset, rng, dpath=None, renderkw=None, verbose=0)`

Create toydata_video renderings for a preconstructed coco dataset.

Parameters

- **dset** (*CocoDataset*) – A dataset that contains special “renderable” annotations. (e.g. the demo shapes). Each image can contain special fields that influence how an image will be rendered.
Currently this process is simple, it just creates a noisy image with the shapes superimposed over where they should exist as indicated by the annotations. In the future this may become more sophisticated.
Each item in *dset.dataset[‘images’]* will be modified to add the “file_name” field indicating where the rendered data is written.
- **rng** (*int | None | RandomState*) – random state
- **dpath** (*str*) – The location to write the images to. If unspecified, it is written to the rendered folder inside the kwcoco cache directory.
- **renderkw** (*dict*) – See [render_toy_image\(\)](#) for details. Also takes imwrite keywords args only handled in this function. TODO better docs.

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> import kwarray
>>> rng = None
>>> rng = kwarray.ensure_rng(rng)
>>> num_tracks = 3
>>> dset = random_video_dset(rng=rng, num_videos=3, num_frames=5,
>>>                         num_tracks=num_tracks, image_size=(128, 128))
>>> dset = render_toy_dataset(dset, rng)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> plt = kwplot.autoplt()
>>> plt.clf()
>>> gids = list(dset.imgs.keys())
>>> pnums = kwplot.PlotNums(nSubplots=len(gids), nRows=num_tracks)
>>> for gid in gids:
>>>     dset.show_image(gid, pnum=pnums(), fnum=1, title=False)
>>> pnums = kwplot.PlotNums(nSubplots=len(gids))
```

`kwcoco.demo.toydata_video.render_toy_image(dset, gid, rng=None, renderkw=None)`

Modifies dataset inplace, rendering synthetic annotations.

This does not write to disk. Instead this writes to placeholder values in the image dictionary.

Parameters

- **dset** (*CocoDataset*) – coco dataset with renderable annotations / images
- **gid** (*int*) – image to render
- **rng** (*int | None | RandomState*) – random state
- **renderkw** (*dict*) – rendering config gray (bool): gray or color images fg_scale (float): foreground noisiness (gauss std) bg_scale (float): background noisiness (gauss std) fg_intensity

(float): foreground brightness (gauss mean) bg_intensity (float): background brightness (gauss mean) newstyle (bool): use new kwcoco datastructure formats with_kpts (bool): include keypoint info with_sseg (bool): include segmentation info

Returns the inplace-modified image dictionary

Return type Dict

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> image_size=(600, 600)
>>> num_frames=5
>>> verbose=3
>>> rng = None
>>> import karray
>>> rng = karray.ensure_rng(rng)
>>> aux = 'mx'
>>> dset = random_single_video_dset(
>>>     image_size=image_size, num_frames=num_frames, verbose=verbose, aux=aux, ↴
>>>     rng=rng)
>>> print('dset.dataset = {}'.format(ub.repr2(dset.dataset, nl=2)))
>>> gid = 1
>>> renderkw = {}
>>> render_toy_image(dset, gid, rng, renderkw=renderkw)
>>> img = dset.imgs[gid]
>>> canvas = img['imdata']
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(canvas, doclf=True, pnum=(1, 2, 1))
>>> dets = dset.annots(gid=gid).detections
>>> dets.draw()
```

```
>>> auxdata = img['auxiliary'][0]['imdata']
>>> aux_canvas = false_color(auxdata)
>>> kwplot.imshow(aux_canvas, pnum=(1, 2, 2))
>>> _ = dets.draw()
```

```
>>> # xdoctest: +REQUIRES(--show)
>>> img, anns = demodata_toy_img(image_size=(172, 172), rng=None, aux=True)
>>> print('anns = {}'.format(ub.repr2(anns, nl=1)))
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(img['imdata'], pnum=(1, 2, 1), fnum=1)
>>> auxdata = img['auxiliary'][0]['imdata']
>>> kwplot.imshow(auxdata, pnum=(1, 2, 2), fnum=1)
>>> kwplot.show_if_requested()
```

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> multispectral = True
>>> dset = random_single_video_dset(num_frames=1, num_tracks=1, multispectral=True)
>>> gid = 1
>>> dset.imgs[gid]
>>> rng = kwarray.ensure_rng(0)
>>> renderkw = {'with_sseg': True}
>>> img = render_toy_image(dset, gid, rng=rng, renderkw=renderkw)
```

`kwcoco.demo.toydata_video.render_foreground(imdata, chan_to_auxinfo, dset, annots, catpats, with_sseg, with_kpts, dims, newstyle, gray, rng)`

Renders demo annotations on top of a demo background

`kwcoco.demo.toydata_video.render_background(img, rng, gray, bg_intensity, bg_scale)`

`kwcoco.demo.toydata_video.false_color(twochan)`

TODO: the function ensure_false_color will eventually be ported to kwimage use that instead.

`kwcoco.demo.toydata_video.random_multi_object_path(num_objects, num_frames, rng=None, max_speed=0.01)`

`kwcoco.demo.toydata_video.random_path(num, degree=1, dimension=2, rng=None, mode='boid')`

Create a random path using a somem ethod curve.

Parameters

- `num` (`int`) – number of points in the path
- `degree` (`int, default=1`) – degree of curvieness of the path
- `dimension` (`int, default=2`) – number of spatial dimensions
- `mode` (`str`) – can be boid, walk, or bezier
- `rng` (`RandomState, default=None`) – seed

References

<https://github.com/dhermes/bezier>

Example

```
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> num = 10
>>> dimension = 2
>>> degree = 3
>>> rng = None
>>> path = random_path(num, degree, dimension, rng, mode='boid')
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> plt = kwplot.autoplt()
>>> kwplot.multi_plot(xdata=path[:, 0], ydata=path[:, 1], fnum=1, doclf=1, xlim=(0, 1), ylim=(0, 1))
>>> kwplot.show_if_requested()
```

Example

```
>>> # xdoctest: +REQUIRES(--3d)
>>> # xdoctest: +REQUIRES(module:bezier)
>>> import kwarray
>>> import kwplot
>>> plt = kwplot.autoplt()
>>> #
>>> num= num_frames = 100
>>> rng = kwarray.ensure_rng(0)
>>> #
>>> from kwcoco.demo.toydata_video import * # NOQA
>>> paths = []
>>> paths.append(random_path(num, degree=3, dimension=3, mode='bezier'))
>>> paths.append(random_path(num, degree=2, dimension=3, mode='bezier'))
>>> paths.append(random_path(num, degree=4, dimension=3, mode='bezier'))
>>> #
>>> from mpl_toolkits.mplot3d import Axes3D # NOQA
>>> ax = plt.gca(projection='3d')
>>> ax.cla()
>>> #
>>> for path in paths:
>>>     time = np.arange(len(path))
>>>     ax.plot(time, path.T[0] * 1, path.T[1] * 1, 'o-')
>>> ax.set_xlim(0, num_frames)
>>> ax.set_ylim(-.01, 1.01)
>>> ax.set_zlim(-.01, 1.01)
>>> ax.set_xlabel('x')
>>> ax.set_ylabel('y')
>>> ax.set_zlabel('z')
```

kwcoco.demo.toypatterns

Module Contents

Classes

CategoryPatterns

Example

Rasters

Functions

<code>star(a, dtype=np.uint8)</code>	Generates a star shaped structuring element.
--------------------------------------	--

Attributes

<code>profile</code>

```
kwcoco.demo.toypatterns.profile  
class kwcoco.demo.toypatterns.CategoryPatterns(categories=None, fg_scale=0.5, fg_intensity=0.9,  
                                                rng=None)  
Bases: object
```

Example

```
>>> from kwcoco.demo.toypatterns import * # NOQA  
>>> self = CategoryPatterns.coerce()  
>>> chip = np.zeros((100, 100, 3))  
>>> offset = (20, 10)  
>>> dims = (160, 140)  
>>> info = self.random_category(chip, offset, dims)  
>>> print('info = {}'.format(ub.repr2(info, nl=1)))  
>>> # xdoctest: +REQUIRES(--show)  
>>> import kwplot  
>>> kwplot.autopl()  
>>> kwplot.imshow(info['data'], pnum=(1, 2, 1), fnum=1, title='chip-space')  
>>> kpts = kwimage.Points._from_coco(info['keypoints'])  
>>> kpts.translate(-np.array(offset)).draw(radius=3)  
>>> #####  
>>> mask = kwimage.Mask.coerce(info['segmentation'])  
>>> kwplot.imshow(mask.to_c_mask().data, pnum=(1, 2, 2), fnum=1, title='img-space')  
>>> kpts.draw(radius=3)  
>>> kwplot.show_if_requested()
```

```
_default_categories  
_default_keypoint_categories  
_default_catnames = ['star', 'eff', 'superstar']  
classmethod coerce(CategoryPatterns, data=None, **kwargs)
```

Construct category patterns from either defaults or only with specific categories. Can accept either an existig category pattern object, a list of known catnames, or mscoco category dictionaries.

Example

```
>>> data = ['superstar']
>>> self = CategoryPatterns.coerce(data)

__len__(self)
__getitem__(self, index)
__iter__(self)
index(self, name)
get(self, index, default=ub.NoParam)
random_category(self, chip, xy_offset=None, dims=None, newstyle=True, size=None)
```

Example

```
>>> from kwcoco.demo.toypatterns import * # NOQA
>>> self = CategoryPatterns.coerce(['superstar'])
>>> chip = np.random.rand(64, 64)
>>> info = self.random_category(chip)

render_category(self, cname, chip, xy_offset=None, dims=None, newstyle=True, size=None)
```

Example

```
>>> from kwcoco.demo.toypatterns import * # NOQA
>>> self = CategoryPatterns.coerce(['superstar'])
>>> chip = np.random.rand(64, 64)
>>> info = self.render_category('superstar', chip, newstyle=True)
>>> print('info = {}'.format(ub.repr2(info, nl=-1)))
>>> info = self.render_category('superstar', chip, newstyle=False)
>>> print('info = {}'.format(ub.repr2(info, nl=-1)))
```

Example

```
>>> from kwcoco.demo.toypatterns import * # NOQA
>>> self = CategoryPatterns.coerce(['superstar'])
>>> chip = None
>>> dims = (64, 64)
>>> info = self.render_category('superstar', chip, newstyle=True, dims=dims, size=dims)
>>> print('info = {}'.format(ub.repr2(info, nl=-1)))
```

`_todo_refactor_geometric_info(self, cname, xy_offset, dims)`

This function is used to populate kpts and sseg information in the autogenerated coco dataset before rendering. It is redundant with other functionality.

TODO: rectify with `_from_elem`

Example

```
>>> self = CategoryPatterns.coerce(['superstar'])
>>> dims = (64, 64)
>>> cname = 'superstar'
>>> xy_offset = None
>>> self._todo_refactor_geometric_info(cname, xy_offset, dims)
```

```
_package_info(self, cname, data, mask, kpts, xy_offset, dims, newstyle)
```

packages data from _from_elem into coco-like annotation

```
_from_elem(self, cname, chip, size=None)
```

Example

```
>>> # hack to allow chip to be None
>>> chip = None
>>> size = (32, 32)
>>> cname = 'superstar'
>>> self = CategoryPatterns.coerce()
>>> self._from_elem(cname, chip, size)
```

```
kwcoco.demo.toypatterns.star(a, dtype=np.uint8)
```

Generates a star shaped structuring element.

Much faster than skimage.morphology version

```
class kwcoco.demo.toypatterns.Rasters
    static superstar()
        test data patch

    static eff()
        test data patch
```

2.2.4 kwcoco.examples

Submodules

```
kwcoco.examples.bench_large_hyperspectral
```

Module Contents

Functions

```
benchmark_large_hyperspectral()
```

```
kwcoco.examples.bench_large_hyperspectral.benchmark_large_hyperspectral()
```

`kwcoco.examples.draw_gt_and_predicted_boxes`**Module Contents****Functions**

`draw_true_and_pred_boxes(true_fpath, pred_fpath, gid, viz_fpath)` How do you generally visualize gt and predicted bounding boxes together?

`kwcoco.examples.draw_gt_and_predicted_boxes.draw_true_and_pred_boxes(true_fpath, pred_fpath, gid, viz_fpath)`

How do you generally visualize gt and predicted bounding boxes together?

Example

```
>>> import kwcoco
>>> import ubelt as ub
>>> from os.path import join
>>> from kwcoco.demo.perterb import perterb_coco
>>> # Create a working directory
>>> dpath = ub.ensure_app_cache_dir('kwcoco/examples/draw_true_and_pred_boxes')
>>> # Lets setup some dummy true data
>>> true_dset = kwcoco.CocoDataset.demo('shapes2')
>>> true_dset.fpath = join(dpath, 'true_dset.kwcoco.json')
>>> true_dset.dump(true_dset.fpath, newlines=True)
>>> # Lets setup some dummy predicted data
>>> pred_dset = perterb_coco(true_dset, box_noise=100, rng=421)
>>> pred_dset.fpath = join(dpath, 'pred_dset.kwcoco.json')
>>> pred_dset.dump(pred_dset.fpath, newlines=True)
>>> #
>>> # We now have our true and predicted data, lets visualize
>>> true_fpath = true_dset.fpath
>>> pred_fpath = pred_dset.fpath
>>> print('dpath = {!r}'.format(dpath))
>>> print('true_fpath = {!r}'.format(true_fpath))
>>> print('pred_fpath = {!r}'.format(pred_fpath))
>>> # Lets choose an image id to visualize and a path to write to
>>> gid = 1
>>> viz_fpath = join(dpath, 'viz_{}.jpg'.format(gid))
>>> # The answer to the question is in the logic of this function
>>> draw_true_and_pred_boxes(true_fpath, pred_fpath, gid, viz_fpath)
```

kwcoco.examples.faq

These are answers to the questions: How do I?

Module Contents

Functions

`get_images_with_videoid()`

Q: How would you recommend querying a kwcoco file to get all of the images

`kwcoco.examples.faq.get_images_with_videoid()`

Q: How would you recommend querying a kwcoco file to get all of the images associated with a video id?

kwcoco.examples.getting_started_existing_dataset

Module Contents

Functions

`getting_started_existing_dataset()`

If you want to start using the Python API. Just open IPython and try:

`the_core_dataset_backend()`

`demo_vectorize_interface()`

>>> import kwcoco

`kwcoco.examples.getting_started_existing_dataset.getting_started_existing_dataset()`

If you want to start using the Python API. Just open IPython and try:

`kwcoco.examples.getting_started_existing_dataset.the_core_dataset_backend()`

`kwcoco.examples.getting_started_existing_dataset.demo_vectorize_interface()`

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes2')
>>> #
>>> aids = [1, 2, 3, 4]
>>> annots = dset.annots(aids)
...
>>> print('annots = {!r}'.format(annots))
annots = <Annots(num=4) at ...>
```

```
>>> annots.lookup('bbox')
[[346.5, 335.2, 33.2, 99.4],
 [344.5, 327.7, 48.8, 111.1],
 [548.0, 154.4, 57.2, 62.1],
 [548.7, 151.0, 59.4, 80.5]]
```

```
>>> gids = annots.lookup('image_id')
>>> print('gids = {!r}'.format(gids))
gids = [1, 2, 1, 2]
```

```
>>> images = dset.images(gids)
>>> list(zip(images.lookup('width'), images.lookup('height')))
[(600, 600), (600, 600), (600, 600), (600, 600)]
```

kwcoco.examples.loading_multispectral_data

Module Contents

Functions

`demo_load_msi_data()`

kwcoco.examples.loading_multispectral_data.`demo_load_msi_data()`

kwcoco.examples.modification_example

Module Contents

Functions

<code>dataset_modification_example_via_copy()</code>	Say you are given a dataset as input and you need to add your own
<code>dataset_modification_example_via_construction()</code>	Alternatively you can make a new dataset and copy over categories / images

kwcoco.examples.modification_example.`dataset_modification_example_via_copy()`

Say you are given a dataset as input and you need to add your own annotation “predictions” to it. You could copy the existing dataset, remove all the annotations, and then add your new annotations.

kwcoco.examples.modification_example.`dataset_modification_example_via_construction()`

Alternatively you can make a new dataset and copy over categories / images as needed

kwcoco.examples.simple_kwCOCO_torch_dataset

This example demonstrates how to use kwCOCO to write a very simple torch dataset. This assumes the dataset will be single-image RGB inputs. This file is intended to talk the reader through what we are doing and why.

This example aims for clarity over being concise. There are APIs exposed by kwCOCO (and its sister module ndsampler) that can perform the same tasks more efficiently and with fewer lines of code.

If you run the doctest, it will produce a visualization that shows the images with boxes drawn on it, running it multiple times will let you see the augmentations. This can be done with the following command:

```
xdoctest -m kwcoco.examples.simple_kwcoco_torch_dataset KW CocoSimpleTorchDataset --show  
Or just copy the doctest into IPython and run it.
```

Module Contents

Classes

<code>KWCocoSimpleTorchDataset</code>	A simple torch dataloader where each image is considered a single item.
---------------------------------------	---

Attributes

<code>DatasetBase</code>

```
kwcoco.examples.simple_kwcoco_torch_dataset.DatasetBase  
class kwcoco.examples.simple_kwcoco_torch_dataset.KWCocoSimpleTorchDataset(coco_dset,  
                           input_dims=None,  
                           antialias=False,  
                           rng=None)
```

Bases: `DatasetBase`

A simple torch dataloader where each image is considered a single item.

Parameters

- **coco_dset** (`kwcoco.CocoDataset` | `str`) – something coercable to a kwcoco dataset, this could either be a `kwcoco.CocoDataset` object, a path to a kwcoco manifest on disk, or a special toydata code. See `kwcoco.CocoDataset.coerce()` for more details.
- **input_dims** (`Tuple[int, int]`) – These are the (height, width) dimensions that the image will be resized to.
- **antialias** (`bool, default=False`) – If true, we will antialias before downsampling.
- **rng** (`RandomState` | `int` | `None`) – an existing random number generator or a random seed to produce deterministic augmentations.

Example

```
>>> # xdoctest: +REQUIRES(module:torch)
>>> from kwcoco.examples.simple_kwcoco_torch_dataset import * # NOQA
>>> import kwcoco
>>> coco_dset = kwcoco.CocoDataset.demo('shapes8')
>>> input_dims = (384, 384)
>>> self = torch_dset = KWCocoSimpleTorchDataset(coco_dset, input_dims=input_dims)
>>> index = len(self) // 2
>>> item = self[index]
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
```

(continues on next page)

(continued from previous page)

```
>>> kwplot.figure(doclf=True, fnum=1)
>>> kwplot.autompl()
>>> canvas = item['inputs']['rgb'].numpy().transpose(1, 2, 0)
>>> # Construct kwimage objects for batch item visualization
>>> dets = kwimage.Detections(
>>>     boxes=kwimage.Boxes(item['labels']['cxywh'], 'cxywh'),
>>>     class_idxs=item['labels']['class_idxs'],
>>>     classes=self.classes,
>>> ).numpy()
>>> # Overlay annotations on the image
>>> canvas = dets.draw_on(canvas)
>>> kwplot.imshow(canvas)
>>> kwplot.show_if_requested()
```

__len__(self)

Return the number of items in the Dataset

__getitem__(self, index)

Construct a batch item to be used in training

`kwcoco.examples.vectorized_interface`**Module Contents****Functions****`demo_vectorized_interface()`**

This demonstrates how to use the kwcoco vectorized interface for images /

`kwcoco.examples.vectorized_interface.demo_vectorized_interface()`

This demonstrates how to use the kwcoco vectorized interface for images / categories / annotations.

2.2.5 `kwcoco.metrics`

mkinit kwcoco.metrics -w --relative

Submodules**`kwcoco.metrics.assignment`**

when deciding whether to go up or down in the tree.

[] medschool applications true-pred matching (applicant proposing) fast algorithm.

[] Maybe looping over truth rather than pred is faster? but it makes you have to combine pred score / ious, which is weird.

2.2. Subpackages

[x] preallocate ndarray and use hstack to build confusion vectors?

doesn't help

[] relevant classes / classes / classes-of-interest we care about needs

to be a first class member of detection metrics.

[] Add parameter that allows one prediction to “match” to more than one

truth object. (example: we have a duck detector problem and all the ducks in a row are annotated as separate object, and we only care about getting the group):

Module Contents

Functions

<code>_assign_confusion_vectors(true_dets, pred_dets, bg_weight=1.0, iou_thresh=0.5, bg_cidx=-1, bias=0.0, classes=None, compat='all', prioritize='iou', ignore_classes='ignore', max_dets=None)</code>	Create confusion vectors for detections by assigning to ground true boxes
<code>_critical_loop(true_dets, pred_dets, iou_lookup, is_valid_lookup, cx_to_matchable_txs, bg_weight, prioritize, iou_thresh_, pdist_priority, cx_to_ancestors, bg_cidx, ignore_classes, max_dets)</code>	
<code>_fast_pdist_priority(classes, prioritize, _cache={})</code>	Custom priority computation. Needs some vetting.
<code>_filter_ignore_regions(true_dets, pred_dets, ioaa_thresh=0.5, ignore_classes='ignore')</code>	Determine which true and predicted detections should be ignored.

Attributes

`USE_NEG_INF`

`kwcoco.metrics.assignment.USE_NEG_INF = True`

`kwcoco.metrics.assignment._assign_confusion_vectors(true_dets, pred_dets, bg_weight=1.0, iou_thresh=0.5, bg_cidx=-1, bias=0.0, classes=None, compat='all', prioritize='iou', ignore_classes='ignore', max_dets=None)`

Create confusion vectors for detections by assigning to ground true boxes

Given predictions and truth for an image return (`y_pred`, `y_true`, `y_score`), which is suitable for sklearn classification metrics

Parameters

- **true_dets** (*Detections*) – groundtruth with boxes, classes, and weights
- **pred_dets** (*Detections*) – predictions with boxes, classes, and scores
- **iou_thresh** (*float, default=0.5*) – bounding box overlap iou threshold required for assignment

- **bias** (*float, default=0.0*) – for computing bounding box overlap, either 1 or 0
- **gids** (*List[int], default=None*) – which subset of images ids to compute confusion metrics on. If not specified all images are used.
- **compat** (*str, default='all'*) – can be ('ancestors' | 'mutex' | 'all'). determines which pred boxes are allowed to match which true boxes. If 'mutex', then pred boxes can only match true boxes of the same class. If 'ancestors', then pred boxes can match true boxes that match or have a coarser label. If 'all', then any pred can match any true, regardless of its category label.
- **prioritize** (*str, default='iou'*) – can be ('iou' | 'class' | 'correct') determines which box to assign to if mutiple true boxes overlap a predicted box. if prioritize is iou, then the true box with maximum iou (above iou_thresh) will be chosen. If prioritize is class, then it will prefer matching a compatible class above a higher iou. If prioritize is correct, then ancestors of the true class are preferred over descendants of the true class, over unrelated classes.
- **bg_cidx** (*int, default=-1*) – The index of the background class. The index used in the truth column when a predicted bounding box does not match any true bounding box.
- **classes** (*List[str] | kwcoco.CategoryTree*) – mapping from class indices to class names. Can also contain class hierarchy information.
- **ignore_classes** (*str | List[str]*) – class name(s) indicating ignore regions
- **max_dets** (*int*) – maximum number of detections to consider

Todo:

- [] This is a bottleneck function. An implementation in C / C++ / Cython would likely improve the overall system.
- [] **Implement crowd truth. Allow multiple predictions to match any** truth objet marked as "iscrowd".

Returns

with relevant confusion vectors. This keys of this dict can be interpreted as columns of a data frame. The *txs* / *pxs* columns represent the indexes of the true / predicted annotations that were assigned as matching. Additionally each row also contains the true and predicted class index, the predicted score, the true weight and the iou of the true and predicted boxes. A *txs* value of -1 means that the predicted box was not assigned to a true annotation and a *pxs* value of -1 means that the true annotation was not assigne to any predicted annotation.

Return type dict

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> import pandas as pd
>>> import kwimage
>>> # Given a raw numpy representation construct Detection wrappers
>>> true_dets = kwimage.Detections(
>>>     boxes=kwimage.Boxes(np.array([
>>>         [ 0,  0, 10, 10], [10,  0, 20, 10],
>>>         [10,  0, 20, 10], [20,  0, 30, 10]]), 'tlbr'),
>>>     weights=np.array([1, 0, .9, 1]),
```

(continues on next page)

(continued from previous page)

```
>>> class_idxs=np.array([0, 0, 1, 2]))
>>> pred_dets = kwimage.Detections(
>>>     boxes=kwimage.Boxes(np.array([
>>>         [6, 2, 20, 10], [3, 2, 9, 7],
>>>         [3, 9, 9, 7], [3, 2, 9, 7],
>>>         [2, 6, 7, 7], [20, 0, 30, 10]]), 'tlbr'),
>>>     scores=np.array([.5, .5, .5, .5, .5]),
>>>     class_idxs=np.array([0, 0, 1, 2, 0, 1]))
>>> bg_weight = 1.0
>>> compat = 'all'
>>> iou_thresh = 0.5
>>> bias = 0.0
>>> import kwcoco
>>> classes = kwcoco.CategoryTree.from_mutex(list(range(3)))
>>> bg_cidx = -1
>>> y = _assign_confusion_vectors(true_dets, pred_dets, bias=bias,
>>>                                bg_weight=bg_weight, iou_thresh=iou_thresh,
>>>                                compat=compat)
>>> y = pd.DataFrame(y)
>>> print(y) # xdoc: +IGNORE_WANT
   pred  true  score  weight      iou    txs    pxs
0     1     2  0.5000  1.0000  1.0000     3     5
1     0    -1  0.5000  1.0000 -1.0000    -1     4
2     2    -1  0.5000  1.0000 -1.0000    -1     3
3     1    -1  0.5000  1.0000 -1.0000    -1     2
4     0    -1  0.5000  1.0000 -1.0000    -1     1
5     0     0  0.5000  0.0000  0.6061     1     0
6    -1     0  0.0000  1.0000 -1.0000     0    -1
7    -1     1  0.0000  0.9000 -1.0000     2    -1
```

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> import pandas as pd
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(nimgs=1, nclasses=8,
>>>                           nboxes=(0, 20), n_fp=20,
>>>                           box_noise=.2, cls_noise=.3)
>>> classes = dmet.classes
>>> gid = 0
>>> true_dets = dmet.true_detections(gid)
>>> pred_dets = dmet.pred_detections(gid)
>>> y = _assign_confusion_vectors(true_dets, pred_dets,
>>>                               classes=dmet.classes,
>>>                               compat='all', prioritize='class')
>>> y = pd.DataFrame(y)
>>> print(y) # xdoc: +IGNORE_WANT
>>> y = _assign_confusion_vectors(true_dets, pred_dets,
>>>                               classes=dmet.classes,
>>>                               compat='ancestors', iou_thresh=.5)
```

(continues on next page)

(continued from previous page)

```
>>> y = pd.DataFrame(y)
>>> print(y) # xdoc: +IGNORE_WANT
```

`kwcoco.metrics.assignment._critical_loop(true_dets, pred_dets, iou_lookup, isvalid_lookup,
 cx_to_matchable_txs, bg_weight, prioritize, iou_thresh_,
 pdist_priority, cx_to_ancestors, bg_cidx, ignore_classes,
 max_dets)`

`kwcoco.metrics.assignment._fast_pdist_priority(classes, prioritize, _cache={})`
Custom priority computation. Needs some vetting.

This is the priority used when deciding which prediction to assign to which truth.

Todo:

- [] Look at absolute difference in sibling entropy when deciding whether to go up or down in the tree.

`kwcoco.metrics.assignment._filter_ignore_regions(true_dets, pred_dets, ioaa_thresh=0.5,
 ignore_classes='ignore')`

Determine which true and predicted detections should be ignored.

Parameters

- `true_dets` (*Detections*)
- `pred_dets` (*Detections*)
- `ioaa_thresh` (*float*) – intersection over other area thresh for ignoring a region.

Returns

flags indicating which **true** and **predicted** detections should be ignored.

Return type Tuple[ndarray, ndarray]

Example

```
>>> from kwcoco.metrics.assignment import * # NOQA
>>> from kwcoco.metrics.assignment import _filter_ignore_regions
>>> import kwimage
>>> pred_dets = kwimage.Detections.random(classes=['a', 'b', 'c'])
>>> true_dets = kwimage.Detections.random(
>>>     segmentations=True, classes=['a', 'b', 'c', 'ignore'])
>>> ignore_classes = {'ignore', 'b'}
>>> ioaa_thresh = 0.5
>>> print('true_dets = {!r}'.format(true_dets))
>>> print('pred_dets = {!r}'.format(pred_dets))
>>> flags1, flags2 = _filter_ignore_regions(
>>>     true_dets, pred_dets, ioaa_thresh=ioaa_thresh, ignore_classes=ignore_
>>>     classes)
>>> print('flags1 = {!r}'.format(flags1))
>>> print('flags2 = {!r}'.format(flags2))
```

```
>>> flags3, flags4 = _filter_ignore_regions(
>>>     true_dets, pred_dets, ioaa_thresh=ioaa_thresh,
>>>     ignore_classes={c.upper() for c in ignore_classes})
>>> assert np.all(flags1 == flags3)
>>> assert np.all(flags2 == flags4)
```

kwcoco.metrics.clf_report

Module Contents

Functions

<code>classification_report(y_true, y_pred, target_names=None, sample_weight=None, verbose=False, remove_unsupported=False, log=None, ascii_only=False)</code>	Computes a classification report which is a collection of various metrics
<code>ovr_classification_report(mc_y_true, mc_probs, target_names=None, sample_weight=None, metrics=None, verbose=0, remove_unsupported=False, log=None)</code>	One-vs-rest classification report

Attributes

`ASCII_ONLY`

`kwcoco.metrics.clf_report.ASCII_ONLY`

```
kwcoco.metrics.clf_report.classification_report(y_true, y_pred, target_names=None,
                                                sample_weight=None, verbose=False,
                                                remove_unsupported=False, log=None,
                                                ascii_only=False)
```

Computes a classification report which is a collection of various metrics commonly used to evaluate classification quality. This can handle binary and multiclass settings.

Note that this function does not accept probabilities or scores and must instead act on final decisions. See `ovr_classification_report` for a probability based report function using a one-vs-rest strategy.

This emulates the `bm(cm)` Matlab script written by David Powers that is used for computing bookmaker, markedness, and various other scores.

References: <https://csem.flinders.edu.au/research/techreps/SIE07001.pdf> <https://www.mathworks.com/matlabcentral/fileexchange/5648-bm-cm-?requestedDomain=www.mathworks.com> Jurman, Riccadonna, Furlanello, (2012). A Comparison of MCC and CEN

Error Measures in MultiClass Prediction

Args: `y_true` (array): true labels for each item `y_pred` (array): predicted labels for each item `target_names` (List): mapping from label to category name `sample_weight` (ndarray): weight

for each item verbose (False): print if True log (callable): print or logging function remove_unsupported (bool, default=False): removes categories that have no support.

ascii_only (bool, default=False): if True dont use unicode characters. if the environ ASCII_ONLY is present this is forced to True and cannot be undone.

Example:

```
>>> # xdoctest: +IGNORE_WANT
>>> # xdoctest: +REQUIRES(module:sklearn)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> y_true = [1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 3, 3, 3, 3, 3, 3, 3, 3]
>>> y_pred = [1, 2, 1, 3, 1, 2, 2, 3, 2, 2, 3, 3, 2, 3, 3, 3, 1, 3]
>>> target_names = None
>>> sample_weight = None
>>> report = classification_report(y_true, y_pred, verbose=0, ascii_
->only=1)
>>> print(report['confusion'])
pred  1   2   3   r
real
1      3   1   1   5
2      0   4   1   5
3      1   1   6   8
p     4   6   8   18
>>> print(report['metrics'])
metric  precision  recall    fpr  markedness  bookmaker  mcc
->support
class
1          0.7500  0.6000  0.0769      0.6071      0.5231  0.5635
->5
2          0.6667  0.8000  0.1538      0.5833      0.6462  0.6139
->5
3          0.7500  0.7500  0.2000      0.5500      0.5500  0.5500
->8
combined    0.7269  0.7222  0.1530      0.5751      0.5761  0.5758
->18
```

Example:

```
>>> # xdoctest: +IGNORE_WANT
>>> # xdoctest: +REQUIRES(module:sklearn)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics.clf_report import *  # NOQA
>>> y_true = [1, 1, 1, 1, 1, 2, 2, 2, 2, 2, 3, 3, 3, 3, 3, 3, 3, 3]
>>> y_pred = [1, 2, 1, 3, 1, 2, 2, 3, 2, 2, 3, 3, 2, 3, 3, 3, 1, 3]
>>> target_names = None
>>> sample_weight = None
>>> logs = []
>>> report = classification_report(y_true, y_pred, verbose=1, ascii_
->only=True, log=logs.append)
>>> print('
```

```
'join(logs))
```

Ignore:

```
>>> size = 100
>>> rng = np.random.RandomState(0)
>>> p_classes = np.array([.90, .05, .05][0:2])
>>> p_classes = p_classes / p_classes.sum()
>>> p_wrong = np.array([.03, .01, .02][0:2])
>>> y_true = testdata_ytrue(p_classes, p_wrong, size, rng)
>>> rs = []
>>> for x in range(17):
>>>     p_wrong += .05
>>>     y_pred = testdata_ypred(y_true, p_wrong, rng)
>>>     report = classification_report(y_true, y_pred, verbose='hack')
>>>     rs.append(report)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> import pandas as pd
>>> df = pd.DataFrame(rs).drop(['raw'], axis=1)
>>> delta = df.subtract(df['target'], axis=0)
>>> sqrd_error = np.sqrt((delta ** 2).sum(axis=0))
>>> print('Error')
>>> print(sqrd_error.sort_values())
>>> ys = df.to_dict(orient='list')
>>> kwplot.multi_plot(ydata_list=ys)
```

`kwcococo.metrics.clf_report.ovr_classification_report(mc_y_true, mc_probs, target_names=None, sample_weight=None, metrics=None, verbose=0, remove_unsupported=False, log=None)`

One-vs-rest classification report

Parameters

- **mc_y_true** (*ndarray[int]*) – multiclass truth labels (integer label format). Shape [N].
- **mc_probs** (*ndarray*) – multiclass probabilities for each class. Shape [N x C].
- **target_names** (*Dict[int, str]*) – mapping from int label to string name
- **sample_weight** (*ndarray*) – weight for each item. Shape [N].
- **metrics** (*List[str]*) – names of metrics to compute

Example

```
>>> # xdoctest: +IGNORE_WANT
>>> # xdoctest: +REQUIRES(module:sklearn)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcococo.metrics.clf_report import * # NOQA
>>> y_true = [1, 1, 1, 1, 1, 2, 2, 2, 2, 0, 0, 0, 0, 0, 0, 0, 0]
>>> y_probs = np.random.rand(len(y_true), max(y_true) + 1)
>>> target_names = None
>>> sample_weight = None
```

(continues on next page)

(continued from previous page)

```
>>> verbose = True
>>> report = ovr_classification_report(y_true, y_probs)
>>> print(report['ave'])
auc      0.6541
ap       0.6824
kappa    0.0963
mcc      0.1002
brier    0.2214
dtype: float64
>>> print(report['ovr'])
     auc   ap  kappa   mcc  brier  support  weight
0 0.6062 0.6161 0.0526 0.0598 0.2608      8  0.4444
1 0.5846 0.6014 0.0000 0.0000 0.2195      5  0.2778
2 0.8000 0.8693 0.2623 0.2652 0.1602      5  0.2778
```

kwcococo.metrics.confusion_measures

Classes that store accumulated confusion measures (usually derived from confusion vectors).

For each chosen threshold value:

- thresholds[i] - the i-th threshold value

The primary data we manipulate are arrays of “confusion” counts, i.e.

- tp_count[i] - true positives at the i-th threshold
- fp_count[i] - false positives at the i-th threshold
- fn_count[i] - false negatives at the i-th threshold
- tn_count[i] - true negatives at the i-th threshold

Module Contents

Classes

<i>Measures</i>	Holds accumulated confusion counts, and derived measures
<i>PerClass_Measures</i>	
<i>MeasureCombiner</i>	Helper to iteratively combine binary measures generated by some process
<i>OneVersusRestMeasureCombiner</i>	Helper to iteratively combine ovr measures generated by some process

Functions

<code>_combine_threshold</code> (to combine thresh, thresh_bins, growth, precision)	Logic to take care of combining thresholds in the case bins are not given
<code>reversible_diff</code> (arr, assume_sorted=1, re- verse=False)	Does a reversible array difference operation.
<code>populate_info</code> (info)	Given raw accumulated confusion counts, populated secondary measures like

Attributes

`profile`

`kwcoco.metrics.confusion_measures.profile`
`class kwcoco.metrics.confusion_measures.Measures(info)`
Bases: `ubelt.NiceRepr, kwcoco.metrics.util.DictProxy`
Holds accumulated confusion counts, and derived measures

Example

```
>>> from kwcoco.metrics.confusion_vectors import BinaryConfusionVectors # NOQA
>>> binvecs = BinaryConfusionVectors.demo(n=100, p_error=0.5)
>>> self = binvecs.measures()
>>> print('self = {!r}'.format(self))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> self.draw(doclf=True)
>>> self.draw(key='pr', pnum=(1, 2, 1))
>>> self.draw(key='roc', pnum=(1, 2, 2))
>>> kwplot.show_if_requested()
```

```
property catname(self)
__nice__(self)
reconstruct(self)
classmethod from_json(cls, state)
__json__(self)
```

Example

```
>>> from kwcoco.metrics.confusion_vectors import BinaryConfusionVectors # NOQA
>>> from kwcoco.metrics.confusion_measures import * # NOQA
>>> binvecs = BinaryConfusionVectors.demo(n=10, p_error=0.5)
>>> self = binvecs.measures()
>>> info = self.__json__()
>>> print('info = {}'.format(ub.repr2(info, nl=1)))
>>> populate_info(info)
>>> print('info = {}'.format(ub.repr2(info, nl=1)))
>>> recon = Measures.from_json(info)
```

summary(self)

maximized_thresholds(self)

Returns thresholds that maximize metrics.

counts(self)

draw(self, key=None, prefix='', **kw)

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics.confusion_vectors import ConfusionVectors # NOQA
>>> cfsn_vecs = ConfusionVectors.demo()
>>> ovr_cfsn = cfsn_vecs.binarize_ovr(keyby='name')
>>> self = ovr_cfsn.measures()['perclass']
>>> self.draw('mcc', doclf=True, fnum=1)
>>> self.draw('pr', doclf=1, fnum=2)
>>> self.draw('roc', doclf=1, fnum=3)
```

summary_plot(self, fnum=1, title='', subplots='auto')

Example

```
>>> from kwcoco.metrics.confusion_measures import * # NOQA
>>> from kwcoco.metrics.confusion_vectors import ConfusionVectors # NOQA
>>> cfsn_vecs = ConfusionVectors.demo(n=3, p_error=0.5)
>>> binvecs = cfsn_vecs.binarize_classless()
>>> self = binvecs.measures()
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> self.summary_plot()
>>> kwplot.show_if_requested()
```

classmethod demo(cls, **kwargs)

Create a demo Measures object for testing / demos

Parameters ****kwargs** – passed to `BinaryConfusionVectors.demo()`. some valid keys are:
n, rng, p_rue, p_error, p_miss.

```
classmethod combine(cls, tocombine, precision=None, growth=None, thresh_bins=None)
```

Combine binary confusion metrics

Parameters

- **tocombine** (*List[Measures]*) – a list of measures to combine into one
- **precision** (*int | None*) – If specified rounds thresholds to this precision which can prevent a RAM explosion when combining a large number of measures. However, this is a lossy operation and will impact the underlying scores. NOTE: use **growth** instead.
- **growth** (*int | None*) – if specified this limits how much the resulting measures are allowed to grow by. If *None*, growth is unlimited. Otherwise, if growth is ‘max’, the growth is limited to the maximum length of an input. We might make this more numerical in the future.
- **thresh_bins** (*int*) – Force this many threshold bins.

Returns Measures

Example

```
>>> from kwcococo.metrics.confusion_measures import * # NOQA
>>> measures1 = Measures.demo(n=15)
>>> measures2 = measures1
>>> tocombine = [measures1, measures2]
>>> new_measures = Measures.combine(tocombine)
>>> new_measures.reconstruct()
>>> print('new_measures = {!r}'.format(new_measures))
>>> print('measures1 = {!r}'.format(measures1))
>>> print('measures2 = {!r}'.format(measures2))
>>> print(ub.repr2(measures1.__json__(), nl=1, sort=0))
>>> print(ub.repr2(measures2.__json__(), nl=1, sort=0))
>>> print(ub.repr2(new_measures.__json__(), nl=1, sort=0))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> kwplot.figure(fnum=1)
>>> new_measures.summary_plot()
>>> measures1.summary_plot()
>>> measures1.draw('roc')
>>> measures2.draw('roc')
>>> new_measures.draw('roc')
```

Example

```
>>> # Demonstrate issues that can arrise from choosing a precision
>>> # that is too low when combining metrics. Breakpoints
>>> # between different metrics can get muddled, but choosing a
>>> # precision that is too high can overwhelm memory.
>>> from kwcococo.metrics.confusion_measures import * # NOQA
>>> base = ub.map_vals(np.asarray, {
>>>     'tp_count': [ 1, 1, 2, 2, 2, 2, 3],
>>>     'fp_count': [ 0, 1, 1, 2, 3, 4, 5],
```

(continues on next page)

(continued from previous page)

```

>>>     'fn_count': [ 1, 1, 0, 0, 0, 0, 0],
>>>     'tn_count': [ 5, 4, 4, 3, 2, 1, 0],
>>>     'thresholds': [.0, .0, .0, .0, .0, .0, .0],
>>>   })
>>> # Make tiny offsets to thresholds
>>> rng = kwaray.ensure_rng(0)
>>> n = len(base['thresholds'])
>>> offsets = [
>>>     sorted(rng.rand(n) * 10 ** -rng.randint(4, 7))[::-1]
>>>     for _ in range(20)
>>> ]
>>> tocombine = []
>>> for offset in offsets:
>>>     base_n = base.copy()
>>>     base_n['thresholds'] += offset
>>>     measures_n = Measures(base_n).reconstruct()
>>>     tocombine.append(measures_n)
>>> for precision in [6, 5, 2]:
>>>     combo = Measures.combine(tocombine, precision=precision).reconstruct()
>>>     print('precision = {!r}'.format(precision))
>>>     print('combo = {}'.format(ub.repr2(combo, nl=1)))
>>>     print('num_thresholds = {}'.format(len(combo['thresholds'])))
>>> for growth in [None, 'max', 'log', 'root', 'half']:
>>>     combo = Measures.combine(tocombine, growth=growth).reconstruct()
>>>     print('growth = {!r}'.format(growth))
>>>     print('combo = {}'.format(ub.repr2(combo, nl=1)))
>>>     print('num_thresholds = {}'.format(len(combo['thresholds'])))
>>> #print(combo.counts().pandas())

```

Example

```

>>> # Test case: combining a single measures should leave it unchanged
>>> from kwcoco.metrics.confusion_measures import * # NOQA
>>> measures = Measures.demo(n=40, p_true=0.2, p_error=0.4, p_miss=0.6)
>>> df1 = measures.counts().pandas().fillna(0)
>>> print(df1)
>>> tocombine = [measures]
>>> combo = Measures.combine(tocombine)
>>> df2 = combo.counts().pandas().fillna(0)
>>> print(df2)
>>> assert np.allclose(df1, df2)

```

```

>>> combo = Measures.combine(tocombine, thresh_bins=2)
>>> df3 = combo.counts().pandas().fillna(0)
>>> print(df3)

```

```

>>> # I am NOT sure if this is correct or not
>>> thresh_bins = 20
>>> combo = Measures.combine(tocombine, thresh_bins=thresh_bins)
>>> df4 = combo.counts().pandas().fillna(0)

```

(continues on next page)

(continued from previous page)

```
>>> print(df4)

>>> combo = Measures.combine(tocombine, thresh_bins=np.linspace(0, 1, 20))
>>> df4 = combo.counts().pandas().fillna(0)
>>> print(df4)
```

```
assert np.allclose(combo['thresholds'], measures['thresholds']) assert np.allclose(combo['fp_count'], measures['fp_count']) assert np.allclose(combo['tp_count'], measures['tp_count']) assert np.allclose(combo['tp_count'], measures['tp_count'])

globals().update(xdev.get_func_kwargs(Measures.combine))
```

`kwcoco.metrics.confusion_measures._combine_threshold(tocombine_thresh, thresh_bins, growth, precision)`

Logic to take care of combining thresholds in the case bins are not given

This can be fairly slow and lead to unnecessary memory usage

`kwcoco.metrics.confusion_measures.reversible_diff(arr, assume_sorted=1, reverse=False)`

Does a reversible array difference operation.

This will be used to find positions where accumulation happened in confusion count array.

`class kwcoco.metrics.confusion_measures.PerClass_Measures(cx_to_info)`

Bases: `ubelt.NiceRepr, kwcoco.metrics.util.DictProxy`

`__nice__(self)`

`summary(self)`

`classmethod from_json(cls, state)`

`__json__(self)`

`draw(self, key='mcc', prefix='', **kw)`

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> from kwcoco.metrics.confusion_vectors import ConfusionVectors # NOQA
>>> cfsn_vecs = ConfusionVectors.demo()
>>> ovr_cfsn = cfsn_vecs.binarize_ovr(keyby='name')
>>> self = ovr_cfsn.measures()['perclass']
>>> self.draw('mcc', doclf=True, fnum=1)
>>> self.draw('pr', doclf=1, fnum=2)
>>> self.draw('roc', doclf=1, fnum=3)
```

`draw_roc(self, prefix='', **kw)`

`draw_pr(self, prefix='', **kw)`

`summary_plot(self, fnum=1, title='', subplots='auto')`

CommandLine

```
python ~/code/kwcoco/kwcoco/metrics/confusion_measures.py PerClass_Measures.
    --summary_plot --show
```

Example

```
>>> from kwcoco.metrics.confusion_measures import * # NOQA
>>> from kwcoco.metrics.detect_metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     n_fp=(0, 1), n_fn=(0, 3), nimgs=32, nboxes=(0, 32),
>>>     classes=3, rng=0, newstyle=1, box_noise=0.7, cls_noise=0.2, score_
>>>     noise=0.3, with_probs=False)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> ovr_cfsn = cfsn_vecs.binarize_ovr(keyby='name', ignore_classes=['vector',
>>>     'raster'])
>>> self = ovr_cfsn.measures()['perclass']
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> import seaborn as sns
>>> sns.set()
>>> self.summary_plot(title='demo summary_plot ovr', subplots=['pr', 'roc'])
>>> kwplot.show_if_requested()
>>> self.summary_plot(title='demo summary_plot ovr', subplots=['mcc', 'acc'],
>>>     fnum=2)
```

`class kwcoco.metrics.confusion_measures.MeasureCombiner(precision=None, growth=None, thresh_bins=None)`

Helper to iteratively combine binary measures generated by some process

Example

```
>>> from kwcoco.metrics.confusion_measures import * # NOQA
>>> from kwcoco.metrics.confusion_vectors import BinaryConfusionVectors
>>> rng = kwarray.ensure_rng(0)
>>> bin_combiner = MeasureCombiner(growth='max')
>>> for _ in range(80):
>>>     bin_cfsn_vecs = BinaryConfusionVectors.demo(n=rng.randint(40, 50), rng=rng,
>>>         p_true=0.2, p_error=0.4, p_miss=0.6)
>>>     bin_measures = bin_cfsn_vecs.measures()
>>>     bin_combiner.submit(bin_measures)
>>> combined = bin_combiner.finalize()
>>> print('combined = {!r}'.format(combined))
```

`property queue_size(self)`

`submit(self, other)`

`combine(self)`

`finalize(self)`

```
class kwcococo.metrics.confusion_measures.OneVersusRestMeasureCombiner(precision=None,  
                           growth=None,  
                           thresh_bins=None)
```

Helper to iteratively combine ovr measures generated by some process

Example

```
>>> from kwcococo.metrics.confusion_measures import * # NOQA  
>>> from kwcococo.metrics.confusion_vectors import OneVsRestConfusionVectors  
>>> rng = kwarray.ensure_rng(0)  
>>> ovr_combiner = OneVersusRestMeasureCombiner(growth='max')  
>>> for _ in range(80):  
>>>     ovr_cfsn_vecs = OneVsRestConfusionVectors.demo()  
>>>     ovr_measures = ovr_cfsn_vecs.measures()  
>>>     ovr_combiner.submit(ovr_measures)  
>>> combined = ovr_combiner.finalize()  
>>> print('combined = {!r}'.format(combined))
```

```
submit(self, other)  
_summary(self)  
combine(self)  
finalize(self)
```

`kwcococo.metrics.confusion_measures.populate_info(info)`

Given raw accumulated confusion counts, populated secondary measures like AP, AUC, F1, MCC, etc..

kwcococo.metrics.confusion_vectors

Classes that store raw confusion vectors, which can be accumulated into confusion measures.

Module Contents

Classes

<code>ConfusionVectors</code>	Stores information used to construct a confusion matrix. This includes
<code>OneVsRestConfusionVectors</code>	Container for multiple one-vs-rest binary confusion vectors
<code>BinaryConfusionVectors</code>	Stores information about a binary classification problem.

Functions

<code>_stabalize_data(y_true, y_score, sample_weight, npad=7)</code>	Adds ideally calibrated dummy values to curves with few positive examples.
--	--

Attributes

`profile`

`kwcoco.metrics.confusion_vectors.profile`

`class kwcoco.metrics.confusion_vectors.ConfusionVectors(cfsn_vecs, data, classes, probs=None)`
Bases: `ubelt.NiceRepr`

Stores information used to construct a confusion matrix. This includes corresponding vectors of predicted labels, true labels, sample weights, etc...

Variables

- `data` (`kwarray.DataFrameArray`) – should at least have keys true, pred, weight
- `classes` (`Sequence` / `CategoryTree`) – list of category names or category graph
- `probs` (`ndarray`, *optional*) – probabilities for each class

Example

```
>>> # xdoctest: IGNORE_WANT
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo()
>>> nimgs=10, nboxes=(0, 10), n_fp=(0, 1), classes=3
>>> cfsn_vecs = dmet.confusion_vectors()
>>> print(cfsn_vecs.data._pandas())
   pred  true    score   weight     iou    txs    pxs    gid
0      2      2  10.0000  1.0000  1.0000      0      4      0
1      2      2  7.5025  1.0000  1.0000      1      3      0
2      1      1  5.0050  1.0000  1.0000      2      2      0
3      3     -1  2.5075  1.0000 -1.0000     -1      1      0
4      2     -1  0.0100  1.0000 -1.0000     -1      0      0
5     -1      2  0.0000  1.0000 -1.0000      3     -1      0
6     -1      2  0.0000  1.0000 -1.0000      4     -1      0
7      2      2  10.0000  1.0000  1.0000      0      5      1
8      2      2  8.0020  1.0000  1.0000      1      4      1
9      1      1  6.0040  1.0000  1.0000      2      3      1
...
62     -1      2  0.0000  1.0000 -1.0000      7     -1      7
63     -1      3  0.0000  1.0000 -1.0000      8     -1      7
64     -1      1  0.0000  1.0000 -1.0000      9     -1      7
65      1     -1  10.0000  1.0000 -1.0000     -1      0      8
66      1      1  0.0100  1.0000  1.0000      0      1      8
```

(continues on next page)

(continued from previous page)

67	3	-1	10.0000	1.0000	-1.0000	-1	3	9
68	2	2	6.6700	1.0000	1.0000	0	2	9
69	2	2	3.3400	1.0000	1.0000	1	1	9
70	3	-1	0.0100	1.0000	-1.0000	-1	0	9
71	-1	2	0.0000	1.0000	-1.0000	2	-1	9

```
>>> # xdoctest: +REQUIRES(--show)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> import kwplot
>>> kwplot.autopl()
>>> from kwcoco.metrics.confusion_vectors import ConfusionVectors
>>> cfsn_vecs = ConfusionVectors.demo(
...     nimgs=128, nboxes=(0, 10), n_fp=(0, 3), n_fn=(0, 3), classes=3)
>>> cx_to_binvecs = cfsn_vecs.binarize_ovr()
>>> measures = cx_to_binvecs.measures()['perclass']
>>> print('measures = {!r}'.format(measures))
measures = <PerClass_Measures({
    'cat_1': <Measures({'ap': 0.227, 'auc': 0.507, 'catname': cat_1, 'max_f1': f1=0.
    ↪45@0.47, 'nsupport': 788.000})>,
    'cat_2': <Measures({'ap': 0.288, 'auc': 0.572, 'catname': cat_2, 'max_f1': f1=0.
    ↪51@0.43, 'nsupport': 788.000})>,
    'cat_3': <Measures({'ap': 0.225, 'auc': 0.484, 'catname': cat_3, 'max_f1': f1=0.
    ↪46@0.40, 'nsupport': 788.000})>,
}) at 0x7facf77bdfd0>
>>> kwplot.figure(fnum=1, doclf=True)
>>> measures.draw(key='pr', fnum=1, pnum=(1, 3, 1))
>>> measures.draw(key='roc', fnum=1, pnum=(1, 3, 2))
>>> measures.draw(key='mcc', fnum=1, pnum=(1, 3, 3))
...

```

_nice__(cfsn_vecs)_json__(self)

Serialize to json

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics import ConfusionVectors
>>> self = ConfusionVectors.demo(n_imgs=1, classes=2, n_fp=0, nboxes=1)
>>> state = self._json_()
>>> print('state = {}'.format(ub.repr2(state, nl=2, precision=2, align=1)))
>>> recon = ConfusionVectors.from_json(state)
```

classmethod from_json(cls, state)**classmethod** demo(cfsn_vecs, **kw)**Parameters** ****kwargs** – See *kwcoco.metrics.DetectionMetrics.demo()***Returns** ConfusionVectors

Example

```
>>> cfsn_vecs = ConfusionVectors.demo()
>>> print('cfsn_vecs = {!r}'.format(cfsn_vecs))
>>> cx_to_binvecs = cfsn_vecs.binarize_ovr()
>>> print('cx_to_binvecs = {!r}'.format(cx_to_binvecs))
```

classmethod from_arrays(*ConfusionVectors*, *true*, *pred=None*, *score=None*, *weight=None*, *probs=None*, *classes=None*)

Construct confusion vector data structure from component arrays

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> import kwarray
>>> classes = ['person', 'vehicle', 'object']
>>> rng = kwarray.ensure_rng(0)
>>> true = (rng.rand(10) * len(classes)).astype(int)
>>> probs = rng.rand(len(true), len(classes))
>>> cfsn_vecs = ConfusionVectors.from_arrays(true=true, probs=probs, ↴
    ↴classes=classes)
>>> cfsn_vecs.confusion_matrix()
pred      person  vehicle  object
real
person        0        0        0
vehicle       2        4        1
object        2        1        0
```

confusion_matrix(*cfsn_vecs*, *compress=False*)

Builds a confusion matrix from the confusion vectors.

Parameters **compress** (*bool*, *default=False*) – if True removes rows / columns with no entries

Returns

cm [the labeled confusion matrix]

(Note: we should write a efficient replacement for this use case. #remove_pandas)

Return type pd.DataFrame

CommandLine

```
xdoctest -m kwcococo.metrics.confusion_vectors ConfusionVectors.confusion_matrix
```

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwCOCO.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     nImgs=10, nBoxes=(0, 10), n_fp=(0, 1), n_fn=(0, 1), classes=3, cls_
>>> _noise=.2)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> cm = cfsn_vecs.confusion_matrix()
>>> ...
>>> print(cm.to_string(float_format=lambda x: '%.2f' % x))
pred      background  cat_1  cat_2  cat_3
real
background      0.00   1.00   2.00   3.00
cat_1          3.00  12.00   0.00   0.00
cat_2          3.00   0.00  14.00   0.00
cat_3          2.00   0.00   0.00  17.00
```

coarsen(*cfsn_vecs, cx*s)

Creates a coarsened set of vectors

Returns ConfusionVectors

binarize_classless(*cfsn_vecs, negative_classes=None*)

Creates a binary representation useful for measuring the performance of detectors. It is assumed that scores of “positive” classes should be high and “negative” classes should be low.

Parameters *negative_classes* (*List[str | int]*) – list of negative class names or idxs, by default chooses any class with a true class index of -1. These classes should ideally have low scores.

Returns BinaryConfusionVectors

Note: The “classlessness” of this depends on the compat=”all” argument being used when constructing confusion vectors, otherwise it becomes something like a macro-average because the class information was used in deciding which true and predicted boxes were allowed to match.

Example

```
>>> from kwCOCO.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     nImgs=10, nBoxes=(0, 10), n_fp=(0, 1), n_fn=(0, 1), classes=3)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> class_idxs = list(dmet.classes.node_to_idx.values())
>>> binvecs = cfsn_vecs.binarize_classless()
```

binarize_ovr(*cfsn_vecs, mode=1, keyby='name', ignore_classes={'ignore'}, approx=0*)

Transforms *cfsn_vecs* into one-vs-rest BinaryConfusionVectors for each category.

Parameters

- **mode** (*int, default=1*) – 0 for heirarchy aware or 1 for voc like. MODE 0 IS PROBABLY BROKEN
- **keyby** (*int | str*) – can be cx or name

- **ignore_classes** (*Set[str]*) – category names to ignore
- **approx** (*bool, default=0*) – if True try and approximate missing scores otherwise assume they are irrecoverable and use -inf

Returns

which behaves like Dict[int, BinaryConfusionVectors]: cx_to_binvecs

Return type *OneVsRestConfusionVectors*

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> cfsn_vecs = ConfusionVectors.demo()
>>> print('cfsn_vecs = {!r}'.format(cfsn_vecs))
>>> catname_to_binvecs = cfsn_vecs.binarize_ovr(keyby='name')
>>> print('catname_to_binvecs = {!r}'.format(catname_to_binvecs))
```

cfsn_vecs.data.pandas() catname_to_binvecs.cx_to_binvecs['class_1'].data.pandas()

Note:**classification_report**(*cfsn_vecs, verbose=0*)

Build a classification report with various metrics.

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> cfsn_vecs = ConfusionVectors.demo()
>>> report = cfsn_vecs.classification_report(verbose=1)
```

class kwcoco.metrics.confusion_vectors.**OneVsRestConfusionVectors**(*cx_to_binvecs, classes*)

Bases: ubelt.NiceRepr

Container for multiple one-vs-rest binary confusion vectors

Variables

- **cx_to_binvecs** –
- **classes** –

Example

```
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     nimgs=10, nboxes=(0, 10), n_fp=(0, 1), classes=3)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> self = cfsn_vecs.binarize_ovr(keyby='name')
>>> print('self = {!r}'.format(self))
```

nice(*self*)

```
classmethod demo(cls)

    Parameters **kwargs – See kwcoco.metrics.DetectionMetrics.demo\(\)
    Returns ConfusionVectors

    keys(self)

    __getitem__(self, cx)

measures(self, stabilize_thresh=7, fp_cutoff=None, monotonic_ppv=True, ap_method='pycocotools')
    Creates binary confusion measures for every one-versus-rest category.
```

Parameters

- **stabilize_thresh** (int, default=7) – if fewer than this many data points inserts dummy stabilization data so curves can still be drawn.
- **fp_cutoff** (int, default=None) – maximum number of false positives in the truncated roc curves. None is equivalent to float('inf')
- **monotonic_ppv** (bool, default=True) – if True ensures that precision is always increasing as recall decreases. This is done in pycocotools scoring, but I'm not sure its a good idea.

SeeAlso: [BinaryConfusionVectors.measures\(\)](#)

Example

```
>>> self = OneVsRestConfusionVectors.demo()
>>> thresh_result = self.measures()['perclass']
```

```
abstract ovr_classification_report(self)

class kwcoco.metrics.confusion_vectors.BinaryConfusionVectors(data, cx=None, classes=None)
    Bases: ubelt.NiceRepr

    Stores information about a binary classification problem. This is always with respect to a specific class, which is given by cx and classes.

    The data DataFrameArray must contain is_true - if the row is an instance of class classes[cx] pred_score - the predicted probability of class classes[cx], and weight - sample weight of the example
```

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> self = BinaryConfusionVectors.demo(n=10)
>>> print('self = {!r}'.format(self))
>>> print('measures = {}'.format(ub.repr2(self.measures())))
```

```
>>> self = BinaryConfusionVectors.demo(n=0)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
```

```
>>> self = BinaryConfusionVectors.demo(n=1)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
```

```
>>> self = BinaryConfusionVectors.demo(n=2)
>>> print('measures = {}'.format(ub.repr2(self.measures())))

```

classmethod demo(cls, n=10, p_true=0.5, p_error=0.2, p_miss=0.0, rng=None)
Create random data for tests

Parameters

- **n** (*int*) – number of rows
- **p_true** (*int*) – fraction of real positive cases
- **p_error** (*int*) – probability of making a recoverable mistake
- **p_miss** (*int*) – probability of making a unrecoverable mistake
- **rng** (*int | RandomState*) – random seed / state

Returns BinaryConfusionVectors

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> cfsn = BinaryConfusionVectors.demo(n=1000, p_error=0.1, p_miss=0.1)
>>> measures = cfsn.measures()
>>> print('measures = {}'.format(ub.repr2(measures, nl=1)))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> kwplot.figure(fnum=1, pnum=(1, 2, 1))
>>> measures.draw('pr')
>>> kwplot.figure(fnum=1, pnum=(1, 2, 2))
>>> measures.draw('roc')
```

property catname(self)
__nice__(self)
__len__(self)
measures(self, stabilize_thresh=7, fp_cutoff=None, monotonic_ppv=True, ap_method='pycocotools')
Get statistics (F1, G1, MCC) versus thresholds

Parameters

- **stabilize_thresh** (*int, default=7*) – if fewer than this many data points inserts dummy stabilization data so curves can still be drawn.
- **fp_cutoff** (*int, default=None*) – maximum number of false positives in the truncated roc curves. None is equivalent to `float('inf')`
- **monotonic_ppv** (*bool, default=True*) – if True ensures that precision is always increasing as recall decreases. This is done in pycocotools scoring, but I'm not sure its a good idea.

Example

```
>>> from kwcocoo.metrics.confusion_vectors import * # NOQA
>>> self = BinaryConfusionVectors.demo(n=0)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
>>> self = BinaryConfusionVectors.demo(n=1, p_true=0.5, p_error=0.5)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
>>> self = BinaryConfusionVectors.demo(n=3, p_true=0.5, p_error=0.5)
>>> print('measures = {}'.format(ub.repr2(self.measures())))

>>> self = BinaryConfusionVectors.demo(n=100, p_true=0.5, p_error=0.5, p_miss=0.
    ↪3)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
>>> print('measures = {}'.format(ub.odict(self.measures()))))
```

References

https://en.wikipedia.org/wiki/Confusion_matrix https://en.wikipedia.org/wiki/Precision_and_recall https://en.wikipedia.org/wiki/Matthews_correlation_coefficient

`_binary_clf_curves(self, stabilize_thresh=7, fp_cutoff=None)`

Compute TP, FP, TN, and FN counts for this binary confusion vector.

Code common to ROC, PR, and threshold measures, computes the elements of the binary confusion matrix at all relevant operating point thresholds.

Parameters

- `stabilize_thresh (int)` – if fewer than this many data points insert stabilization data.
- `fp_cutoff (int)` – maximum number of false positives

Example

```
>>> from kwcocoo.metrics.confusion_vectors import * # NOQA
>>> self = BinaryConfusionVectors.demo(n=1, p_true=0.5, p_error=0.5)
>>> self._binary_clf_curves()

>>> self = BinaryConfusionVectors.demo(n=0, p_true=0.5, p_error=0.5)
>>> self._binary_clf_curves()

>>> self = BinaryConfusionVectors.demo(n=100, p_true=0.5, p_error=0.5)
>>> self._binary_clf_curves()
```

`draw_distribution(self)`

`_3dplot(self)`

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> from kwcoco.metrics.detect_metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     n_fp=(0, 1), n_fn=(0, 2), nimgs=256, nboxes=(0, 10),
>>>     bbox_noise=10,
>>>     classes=1)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> self = bin_cfsn = cfsn_vecs.binarize_classless()
>>> #dmet.summarize(plot=True)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.figure(fnum=3)
>>> self._3dplot()
```

`kwcoco.metrics.confusion_vectors._stabalize_data(y_true, y_score, sample_weight, npad=7)`

Adds ideally calibrated dummy values to curves with few positive examples. This acts somewhat like a Bayesian prior and smooths out the curve.

Example

```
y_score = np.array([0.5, 0.6]) y_true = np.array([1, 1]) sample_weight = np.array([1, 1]) npad = 7 _stabalize_data(y_true, y_score, sample_weight, npad=npad)
```

`kwcoco.metrics.detect_metrics`

Module Contents**Classes**

<code>DetectionMetrics</code>	Object that computes associations between detections and can convert them
-------------------------------	---

Functions

<code>_demo_construct_probs(pred_cxs, pred_scores, classes, rng, hacked=1)</code>	Constructs random probabilities for demo data
---	---

<code>pycocotools_confusion_vectors(dmet, evaler, iou_thresh=0.5, verbose=0)</code>	
---	--

Example

<code>eval_detections_cli(**kw)</code>	DEPRECATED USE <code>kwcoco eval</code> instead
<code>_summarize(self, ap=1, areaRngLbl='all', maxDets=100)</code>	

continues on next page

Table 64 – continued from previous page

`pct_summarize2(self)`

class kwCOCO.metrics.detect_metrics.DetectionMetrics(*dmet*, *classes*=*None*)
Bases: `ubelt.NiceRepr`

Object that computes associations between detections and can convert them into sklearn-compatible representations for scoring.

Variables

- `gid_to_true_dets` (`Dict`) – maps image ids to truth
- `gid_to_pred_dets` (`Dict`) – maps image ids to predictions
- `classes` (`CategoryTree`) – category coder

Example

```
>>> dmet = DetectionMetrics.demo()
>>>     nimgs=100, nboxes=(0, 3), n_fp=(0, 1), classes=8, score_noise=0.9, ↴
    ↪hacked=False)
>>> print(dmet.score_kwcoco(bias=0, compat='mutex', prioritize='iou')['mAP'])
...
>>> # NOTE: IN GENERAL NETHARN AND VOC ARE NOT THE SAME
>>> print(dmet.score_voc(bias=0)['mAP'])
0.8582...
>>> #print(dmet.score_coco()['mAP'])
```

`score_coco`

`clear(dmet)`

`__nice__(dmet)`

classmethod `from_coco`(*DetectionMetrics*, *true_coco*, *pred_coco*, *gids*=*None*, *verbose*=0)
Create detection metrics from two coco files representing the truth and predictions.

Parameters

- `true_coco` (`kwCOCO.CocoDataset`)
- `pred_coco` (`kwCOCO.CocoDataset`)

Example

```
>>> import kwCOCO
>>> from kwCOCO.demo.perterb import perterb_coco
>>> true_coco = kwCOCO.CocoDataset.demo('shapes')
>>> perterbkw = dict(box_noise=0.5, cls_noise=0.5, score_noise=0.5)
>>> pred_coco = perterb_coco(true_coco, **perterbkw)
>>> self = DetectionMetrics.from_coco(true_coco, pred_coco)
>>> self.score_voc()
```

`_register_imagename(dmet, imgname, gid=None)`

add_predictions(*dmet, pred_dets, imgname=None, gid=None*)

Register/Add predicted detections for an image

Parameters

- **pred_dets** (*Detections*) – predicted detections
- **imgname** (*str*) – a unique string to identify the image
- **gid** (*int, optional*) – the integer image id if known

add_truth(*dmet, true_dets, imgname=None, gid=None*)

Register/Add groundtruth detections for an image

Parameters

- **true_dets** (*Detections*) – groundtruth
- **imgname** (*str*) – a unique string to identify the image
- **gid** (*int, optional*) – the integer image id if known

true_detections(*dmet, gid*)

gets Detections representation for groundtruth in an image

pred_detections(*dmet, gid*)

gets Detections representation for predictions in an image

confusion_vectors(*dmet, iou_thresh=0.5, bias=0, gids=None, compat='mutex', prioritize='iou', ignore_classes='ignore', background_class=ub.NoParam, verbose='auto', workers=0, track_probs='try', max_dets=None*)

Assigns predicted boxes to the true boxes so we can transform the detection problem into a classification problem for scoring.

Parameters

- **iou_thresh** (*float | List[float], default=0.5*) – bounding box overlap iou threshold required for assignment if a list, then return type is a dict
- **bias** (*float, default=0.0*) – for computing bounding box overlap, either 1 or 0
- **gids** (*List[int], default=None*) – which subset of images ids to compute confusion metrics on. If not specified all images are used.
- **compat** (*str, default='all'*) – can be ('ancestors' | 'mutex' | 'all'). determines which pred boxes are allowed to match which true boxes. If 'mutex', then pred boxes can only match true boxes of the same class. If 'ancestors', then pred boxes can match true boxes that match or have a coarser label. If 'all', then any pred can match any true, regardless of its category label.
- **prioritize** (*str, default='iou'*) – can be ('iou' | 'class' | 'correct') determines which box to assign to if mutiple true boxes overlap a predicted box. if prioritize is iou, then the true box with maximum iou (above iou_thresh) will be chosen. If prioritize is class, then it will prefer matching a compatible class above a higher iou. If prioritize is correct, then ancestors of the true class are preferred over descendants of the true class, over unrelated classes.
- **ignore_classes** (*set, default={'ignore'}*) – class names indicating ignore regions
- **background_class** (*str, default=ub.NoParam*) – Name of the background class. If unspecified we try to determine it with heuristics. A value of None means there is no background class.
- **verbose** (*int, default='auto'*) – verbosity flag. In auto mode, verbose=1 if len(gids) > 1000.

- **workers** (*int, default=0*) – number of parallel assignment processes
- **track_probs** (*str, default='try'*) – can be ‘try’, ‘force’, or False. if truthy, we assume probabilities for multiple classes are available.

Returns ConfusionVectors | Dict[float, ConfusionVectors]

Example

```
>>> dmet = DetectionMetrics.demo(nimgs=30, classes=3,
>>>                               nboxes=10, n_fp=3, box_noise=10,
>>>                               with_probs=False)
>>> iou_to_cfsn = dmet.confusion_vectors(iou_thresh=[0.3, 0.5, 0.9])
>>> for t, cfsn in iou_to_cfsn.items():
>>>     print('t = {!r}'.format(t))
...     print(cfsn.binarize_ovr().measures())
...     print(cfsn.binarize_classless().measures())
```

score_kwant(*dmet, iou_thresh=0.5*)

Scores the detections using kwant

score_kwococo(*dmet, iou_thresh=0.5, bias=0, gids=None, compat='all', prioritize='iou'*)

our scoring method

score_voc(*dmet, iou_thresh=0.5, bias=1, method='voc2012', gids=None, ignore_classes='ignore'*)

score using voc method

Example

```
>>> dmet = DetectionMetrics.demo(
>>>     nimgs=100, nboxes=(0, 3), n_fp=(0, 1), classes=8,
>>>     score_noise=.5)
>>> print(dmet.score_voc()['mAP'])
0.9399...
```

_to_coco(*dmet*)

Convert to a coco representation of truth and predictions

with inverse aid mappings

score_pycocotools(*dmet, with_evaler=False, with_confusion=False, verbose=0, iou_thresholds=None*)

score using ms-coco method

Returns dictionary with pct info

Return type Dict

Example

```
>>> # xdoctest: +REQUIRES(module:pycocotools)
>>> from kwcoco.metrics.detect_metrics import *
>>> dmet = DetectionMetrics.demo(
>>>     nimgs=10, nboxes=(0, 3), n_fn=(0, 1), n_fp=(0, 1), classes=8, with_
>>>     _probs=False)
>>> pct_info = dmet.score_pycocotools(verbose=1,
>>>                                     with_evaler=True,
>>>                                     with_confusion=True,
>>>                                     iou_thresholds=[0.5, 0.9])
>>> evaler = pct_info['evaler']
>>> iou_to_cfsn_vecs = pct_info['iou_to_cfsn_vecs']
>>> for iou_thresh in iou_to_cfsn_vecs.keys():
>>>     print('iou_thresh = {!r}'.format(iou_thresh))
>>>     cfsn_vecs = iou_to_cfsn_vecs[iou_thresh]
>>>     ovr_measures = cfsn_vecs.binarize_ovr().measures()
>>>     print('ovr_measures = {}'.format(ub.repr2(ovr_measures, nl=1,_
>>>     precision=4)))
```

Note: by default pycocotools computes average precision as the literal average of computed precisions at 101 uniformly spaced recall thresholds.

pycocoutils seems to only allow predictions with the same category as the truth to match those truth objects. This should be the same as calling dmet.confusion_vectors with compat = mutex

pycocoutils does not take into account the fact that each box often has a score for each category.

pycocoutils will be incorrect if any annotation has an id of 0

a major difference in the way kwcoco scores versus pycocoutils is the calculation of AP. The assignment between truth and predicted detections produces similar enough results. Given our confusion vectors we use the scikit-learn definition of AP, whereas pycocoutils seems to compute precision and recall — more or less correctly — but then it resamples the precision at various specified recall thresholds (in the *accumulate* function, specifically how *pr* is resampled into the *q* array). This can lead to a large difference in reported scores.

pycocoutils also smooths out the precision such that it is monotonic decreasing, which might not be the best idea.

pycocotools area ranges are inclusive on both ends, that means the “small” and “medium” truth selections do overlap somewhat.

classmethod demo(*cls*, ***kwargs*)

Creates random true boxes and predicted boxes that have some noisy offset from the truth.

Kwargs:

classes (int, default=1): class list or the number of foreground classes.

nimgs (int, default=1): number of images in the coco datasets. *nboxes* (int, default=1): boxes per image.

n_fp (int, default=0): number of false positives. *n_fn* (int, default=0): number of false negatives.

box_noise (float, default=0): std of a normal distribution used to

perterb both box location and box size.

cls_noise (float, default=0): probability that a class label will change. Must be within 0 and 1.

anchors (ndarray, default=None): used to create random boxes null_pred (bool, default=0):
if True, predicted classes are returned as null, which means only localization scoring is suitable.

with_probs (bool, default=1): if True, includes per-class probabilities with predictions

CommandLine

```
xdoctest -m kwcococo.metrics.detect_metrics DetectionMetrics.demo:2 --show
```

Example

```
>>> kwargs = {}
>>> # Seed the RNG
>>> kwargs['rng'] = 0
>>> # Size parameters determine how big the data is
>>> kwargs['nimgs'] = 5
>>> kwargs['nboxes'] = 7
>>> kwargs['classes'] = 11
>>> # Noise parameters perterb predictions further from the truth
>>> kwargs['n_fp'] = 3
>>> kwargs['box_noise'] = 0.1
>>> kwargs['cls_noise'] = 0.5
>>> dmet = DetectionMetrics.demo(**kwargs)
>>> print('dmet.classes = {}'.format(dmet.classes))
dmet.classes = <CategoryTree(nNodes=12, maxDepth=3, maxBreadth=4...)>
>>> # Can grab kwimage.Detection object for any image
>>> print(dmet.true_detections(gid=0))
<Detections(4)>
>>> print(dmet.pred_detections(gid=0))
<Detections(7)>
```

Example

```
>>> # Test case with null predicted categories
>>> dmet = DetectionMetrics.demo(nimgs=30, null_pred=1, classes=3,
>>>                               nboxes=10, n_fp=3, box_noise=0.1,
>>>                               with_probs=False)
>>> dmet.gid_to_pred_dets[0].data
>>> dmet.gid_to_true_dets[0].data
>>> cfsn_vecs = dmet.confusion_vectors()
>>> binvecs_ovr = cfsn_vecs.binarize_ovr()
>>> binvecs_per = cfsn_vecs.binarize_classless()
>>> measures_per = binvecs_per.measures()
>>> measures_ovr = binvecs_ovr.measures()
>>> print('measures_per = {!r}'.format(measures_per))
>>> print('measures_ovr = {!r}'.format(measures_ovr))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
```

(continues on next page)

(continued from previous page)

```
>>> kwplot.autopl()
>>> measures_ovr['perclass'].draw(key='pr', fnum=2)
```

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> from kwcoco.metrics.detect_metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     n_fp=(0, 1), n_fn=(0, 1), nimgs=32, nboxes=(0, 16),
>>>     classes=3, rng=0, newstyle=1, box_noise=0.5, cls_noise=0.0, score_
>>> _noise=0.3, with_probs=False)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> summary = dmet.summarize(plot=True, title='DetectionMetrics summary demo',_
>>> with_ovr=True, with_bin=False)
>>> summary['bin_measures']
>>> kwplot.show_if_requested()
```

`summarize(dmet, out_dpath=None, plot=False, title='', with_bin='auto', with_ovr='auto')`

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> from kwcoco.metrics.detect_metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     n_fp=(0, 128), n_fn=(0, 4), nimgs=512, nboxes=(0, 32),
>>>     classes=3, rng=0)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> dmet.summarize(plot=True, title='DetectionMetrics summary demo')
>>> kwplot.show_if_requested()
```

`kwcoco.metrics.detect_metrics._demo_construct_probs(pred_cxs, pred_scores, classes, rng, hacked=1)`

Constructs random probabilities for demo data

`kwcoco.metrics.detect_metrics.pycocotools_confusion_vectors(dmet, evaler, iou_thresh=0.5, verbose=0)`

Example

```
>>> # xdoctest: +REQUIRES(module:pycocotools)
>>> from kwcoco.metrics.detect_metrics import *
>>> dmet = DetectionMetrics.demo(
>>>     nimgs=10, nboxes=(0, 3), n_fn=(0, 1), n_fp=(0, 1), classes=8, with_
>>> _probs=False)
>>> coco_scores = dmet.score_pycocotools(with_evaler=True)
```

(continues on next page)

(continued from previous page)

```
>>> evaler = coco_scores['evaler']
>>> cfsn_vecs = pycocotools_confusion_vectors(dmet, evaler, verbose=1)
```

`kwCOCO.metrics.detect_metrics.eval_detections_cli(**kw)`
DEPRECATED USE `kwCOCO eval` instead

CommandLine

```
xdoctest -m ~/code/kwCOCO/kwCOCO/metrics/detect_metrics.py eval_detections_cli
```

`kwCOCO.metrics.detect_metrics._summarize(self, ap=1, iouThr=None, areaRngLbl='all', maxDets=100)`
`kwCOCO.metrics.detect_metrics.pct_summarize2(self)`

`kwCOCO.metrics.drawing`

Module Contents

Functions

`draw_perclass_roc(cx_to_info, classes=None, prefix="", fnum=1, fp_axis='count', **kw)`

Parameters

- `cx_to_info` (*PerClass_Measures | Dict*)

`demo_format_options()`

`concise_si_display(val, eps=1e-08, precision=2, si_thresh=4)` Display numbers in scientific notation if above a threshold

`_realpos_label_suffix(info)` Creates a label suffix that indicates the number of real positive cases

`draw_perclass_prcurve(cx_to_info, classes=None, prefix="", fnum=1, **kw)`

Parameters `cx_to_info` (*PerClass_Measures | Dict*)

`draw_perclass_thresholds(cx_to_info, key='mcc', classes=None, prefix="", fnum=1, **kw)`

Parameters `cx_to_info` (*PerClass_Measures | Dict*)

`draw_roc(info, prefix="", fnum=1, **kw)`

Parameters `info` (*Measures | Dict*)

`draw_prcurve(info, prefix="", fnum=1, **kw)`

Draws a single pr curve.

`draw_threshold_curves(info, keys=None, prefix="", fnum=1, **kw)`

Parameters `info` (*Measures | Dict*)

`kwCOCO.metrics.drawing.draw_perclass_roc(cx_to_info, classes=None, prefix="", fnum=1, fp_axis='count', **kw)`

Parameters

- **cx_to_info** (*PerClass_Measures | Dict*)
- **fp_axis** (*str*) – can be count or rate

`kwcoco.metrics.drawing.demo_format_options()`

`kwcoco.metrics.drawing.concice_si_display(val, eps=1e-08, precision=2, si_thresh=4)`

Display numbers in scientific notation if above a threshold

Parameters

- **eps** (*float*) – threshold to be formated as an integer if other integer conditions hold.
- **precision** (*int*) – maximum significant digits (might print less)
- **si_thresh** (*int*) – If the number is less than $10^{\{si_thresh\}}$, then it will be printed as an integer if it is within eps of an integer.

References

<https://docs.python.org/2/library/stdtypes.html#string-formatting-operations>

Example

```
>>> grid = {
>>>     'sign': [1, -1],
>>>     'exp': [1, -1],
>>>     'big_part': [0, 32132e3, 4000000032],
>>>     'med_part': [0, 0.5, 0.9432, 0.000043, 0.01, 1, 2],
>>>     'small_part': [0, 1321e-3, 43242e-11],
>>> }
>>> for kw in ub.named_product(grid):
>>>     sign = kw.pop('sign')
>>>     exp = kw.pop('exp')
>>>     raw = (sum(map(float, kw.values())))
>>>     val = sign * raw ** exp
>>>     if raw != 0 else sign * raw
>>>     print('{:>20} - {}'.format(concice_si_display(val), val))
>>> from kwcoco.metrics.drawing import * # NOQA
>>> print(concice_si_display(40000000432432))
>>> print(concice_si_display(473243280432890))
>>> print(concice_si_display(473243284289))
>>> print(concice_si_display(473243289))
>>> print(concice_si_display(4739))
>>> print(concice_si_display(473))
>>> print(concice_si_display(0.432432))
>>> print(concice_si_display(0.132432))
>>> print(concice_si_display(1.0000043))
>>> print(concice_si_display(01.0000000000000000000000000000043))
```

`kwcoco.metrics.drawing._realpos_label_suffix(info)`

Creates a label suffix that indicates the number of real positive cases versus the total amount of cases considered for an evaluation curve.

Parameters **info** (*Dict*) – with keys, nsupport, realpos_total

Example

```
>>> from kwCOCO.metrics.drawing import * # NOQA
>>> info = {'nsupport': 10, 'realpos_total': 10}
>>> _realpos_label_suffix(info)
10/10
>>> info = {'nsupport': 10.0, 'realpos_total': 10.0}
>>> _realpos_label_suffix(info)
10/10
>>> info = {'nsupport': 10.3333, 'realpos_total': 10.22222}
>>> _realpos_label_suffix(info)
10.22/10.33
>>> info = {'nsupport': 10.00000001, 'realpos_total': None}
>>> _realpos_label_suffix(info)
10
>>> info = {'nsupport': 10.009}
>>> _realpos_label_suffix(info)
10.01
>>> info = {'nsupport': 3331033334342.432, 'realpos_total': 1033334342.432}
>>> _realpos_label_suffix(info)
1e9/3.3e12
>>> info = {'nsupport': 0.007, 'realpos_total': 0.0000893}
>>> _realpos_label_suffix(info)
8.9e-5/0.007
```

`kwCOCO.metrics.drawing.draw_perclass_prcurve(cx_to_info, classes=None, prefix='', fnum=1, **kw)`

Parameters `cx_to_info` (*PerClass_Measures | Dict*)

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> from kwCOCO.metrics.drawing import * # NOQA
>>> from kwCOCO.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo()
>>> nimgs=3, nboxes=(0, 10), n_fp=(0, 3), n_fn=(0, 2), classes=3, score_noise=0.
-> 1, box_noise=0.1, with_probs=False)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> print(cfsn_vecs.data.pandas())
>>> classes = cfsn_vecs.classes
>>> cx_to_info = cfsn_vecs.binarize_ovr().measures()['perclass']
>>> print('cx_to_info = {}'.format(ub.repr2(cx_to_info, nl=1)))
>>> import kwplot
>>> kwplot.autopl()
>>> draw_perclass_prcurve(cx_to_info, classes)
>>> # xdoctest: +REQUIRES(--show)
>>> kwplot.show_if_requested()
```

`kwCOCO.metrics.drawing.draw_perclass_thresholds(cx_to_info, key='mcc', classes=None, prefix='', fnum=1, **kw)`

Parameters `cx_to_info` (*PerClass_Measures | Dict*)

Note: Each category is inspected independently of one another, there is no notion of confusion.

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> from kwcoco.metrics.drawing import * # NOQA
>>> from kwcoco.metrics import ConfusionVectors
>>> cfsn_vecs = ConfusionVectors.demo()
>>> classes = cfsn_vecs.classes
>>> ovr_cfsn = cfsn_vecs.binarize_ovr(keyby='name')
>>> cx_to_info = ovr_cfsn.measures()['perclass']
>>> import kwplot
>>> kwplot.autopl()
>>> key = 'mcc'
>>> draw_perclass_thresholds(cx_to_info, key, classes)
>>> # xdoctest: +REQUIRES(--show)
>>> kwplot.show_if_requested()
```

`kwcoco.metrics.drawing.draw_roc(info, prefix='', fnum=1, **kw)`

Parameters `info` (*Measures | Dict*)

Note: There needs to be enough negative examples for using ROC to make any sense!

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot, module:seaborn)
>>> from kwcoco.metrics.drawing import * # NOQA
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(nimgs=30, null_pred=1, classes=3,
>>>                           nboxes=10, n_fp=10, box_noise=0.3,
>>>                           with_probs=False)
>>> dmet.true_detections().data
>>> cfsn_vecs = dmet.confusion_vectors(compat='mutex', prioritize='iou', bias=0)
>>> print(cfsn_vecs.data._pandas().sort_values('score'))
>>> classes = cfsn_vecs.classes
>>> info = ub.peek(cfsn_vecs.binarize_ovr().measures()['perclass'].values())
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> draw_roc(info)
>>> kwplot.show_if_requested()
```

`kwcoco.metrics.drawing.draw_prcurve(info, prefix='', fnum=1, **kw)`

Draws a single pr curve.

Parameters `info` (*Measures | Dict*)

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     nimgs=10, nboxes=(0, 10), n_fp=(0, 1), classes=3)
>>> cfsn_vecs = dmet.confusion_vectors()
```

```
>>> classes = cfsn_vecs.classes
>>> info = cfsn_vecs.binarize_classless().measures()
>>> import kwplot
>>> kwplot.autopl()
>>> draw_prcurve(info)
>>> # xdoctest: +REQUIRES(--show)
>>> kwplot.show_if_requested()
```

`kwcoco.metrics.drawing.draw_threshold_curves(info, keys=None, prefix='', fnum=1, **kw)`

Parameters `info` (*Measures | Dict*)

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> import sys, ubelt
>>> sys.path.append(ubelt.expandpath '~/code/kwcoco')
>>> from kwcoco.metrics.drawing import * # NOQA
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     nimgs=10, nboxes=(0, 10), n_fp=(0, 1), classes=3)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> info = cfsn_vecs.binarize_classless().measures()
>>> keys = None
>>> import kwplot
>>> kwplot.autopl()
>>> draw_threshold_curves(info, keys)
>>> # xdoctest: +REQUIRES(--show)
>>> kwplot.show_if_requested()
```

`kwcoco.metrics.functional`

Module Contents

Functions

<code>fast_confusion_matrix(y_true, y_pred, n_labels, sample_weight=None)</code>	faster version of sklearn confusion matrix that avoids the sample_weight=None
<code>_truncated_roc(y_df, bg_idx=-1, fp_cutoff=None)</code>	Computes truncated ROC info
<code>-pr_curves(y)</code>	Compute a PR curve from a method

continues on next page

Table 66 – continued from previous page

<code>_average_precision(tpr, ppv)</code>	Compute average precision of a binary PR curve. This is simply the area
---	---

`kwcoco.metrics.functional.fast_confusion_matrix(y_true, y_pred, n_labels, sample_weight=None)`
faster version of sklearn confusion matrix that avoids the expensive checks and label rectification

Parameters

- **y_true** (`ndarray[int]`) – ground truth class label for each sample
- **y_pred** (`ndarray[int]`) – predicted class label for each sample
- **n_labels** (`int`) – number of labels
- **sample_weight** (`ndarray[int|float]`) – weight of each sample

Returns matrix where rows represent real and cols represent pred and the value at each cell is the total amount of weight

Return type `ndarray[int64|float64, dim=2]`

Example

```
>>> y_true = np.array([0, 0, 0, 0, 1, 1, 1, 0, 1])
>>> y_pred = np.array([0, 0, 0, 0, 0, 0, 0, 1, 1])
>>> fast_confusion_matrix(y_true, y_pred, 2)
array([[4, 2],
       [3, 1]])
>>> fast_confusion_matrix(y_true, y_pred, 2).ravel()
array([4, 2, 3, 1])
```

`kwcoco.metrics.functional._truncated_roc(y_df, bg_idx=-1, fp_cutoff=None)`
Computes truncated ROC info

`kwcoco.metrics.functional._pr_curves(y)`
Compute a PR curve from a method

Parameters `y (pd.DataFrame | DataFrameArray)` – output of detection_confusions
Returns `Tuple[float, ndarray, ndarray]`

Example

```
>>> # xdoctest: +REQUIRES(module:sklearn)
>>> import pandas as pd
>>> y1 = pd.DataFrame.from_records([
>>>     {'pred': 0, 'score': 10.00, 'true': -1, 'weight': 1.00},
>>>     {'pred': 0, 'score': 1.65, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 8.64, 'true': -1, 'weight': 1.00},
>>>     {'pred': 0, 'score': 3.97, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 1.68, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 5.06, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 0.25, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 1.75, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 8.52, 'true': 0, 'weight': 1.00},
```

(continues on next page)

(continued from previous page)

```
>>>     {'pred': 0, 'score': 5.20, 'true': 0, 'weight': 1.00},  
>>> ])  
>>> import kwcoco as nh  
>>> import kwarray  
>>> y2 = kwarray.DataFrameArray(y1)  
>>> _pr_curves(y2)  
>>> _pr_curves(y1)
```

kwcoco.metrics.functional._average_precision(*tpr, ppv*)

Compute average precision of a binary PR curve. This is simply the area under the curve.

Parameters

- ***tpr*** (*ndarray*) – true positive rate - aka recall
- ***ppv*** (*ndarray*) – positive predictive value - aka precision

kwcoco.metrics.sklearn_alts

Faster pure-python versions of sklearn functions that avoid expensive checks and label rectifications. It is assumed that all labels are consecutive non-negative integers.

Module Contents

Functions

`confusion_matrix(y_true, y_pred, n_labels=None, labels=None, sample_weight=None)`

`global_accuracy_from_confusion(cfsn)`

`class_accuracy_from_confusion(cfsn)`

`_binary_clf_curve2(y_true, y_score, pos_label=None, sample_weight=None)`

MODIFIED VERSION OF SCIKIT-LEARN API

Attributes

`profile`

kwcoco.metrics.sklearn_alts.profile

`kwcoco.metrics.sklearn_alts.confusion_matrix(y_true, y_pred, n_labels=None, labels=None, sample_weight=None)`

faster version of sklearn confusion matrix that avoids the expensive checks and label rectification

Runs in about 0.7ms

Returns matrix where rows represent real and cols represent pred

Return type ndarray

Example

```
>>> y_true = np.array([0, 0, 0, 0, 1, 1, 1, 0, 1])
>>> y_pred = np.array([0, 0, 0, 0, 0, 0, 1, 1, 1])
>>> confusion_matrix(y_true, y_pred, 2)
array([[4, 2],
       [3, 1]])
>>> confusion_matrix(y_true, y_pred, 2).ravel()
array([4, 2, 3, 1])
```

Benchmarks: import ubelt as ub
`y_true = np.random.randint(0, 2, 10000)`
`y_pred = np.random.randint(0, 2, 10000)`

`n = 1000` for timer in ub.Timerit(n, bestof=10, label='py-time'):

```
    sample_weight = [1] * len(y_true)  confusion_matrix(y_true, y_pred, 2, sample_weight=sample_weight)
```

```
for timer in ub.Timerit(n, bestof=10, label='np-time'):
    sample_weight = np.ones(len(y_true), dtype=int)  confusion_matrix(y_true, y_pred, 2, sample_weight=sample_weight)
```

`kwcococo.metrics.sklearn_alts.global_accuracy_from_confusion(cfsn)`

`kwcococo.metrics.sklearn_alts.class_accuracy_from_confusion(cfsn)`

`kwcococo.metrics.sklearn_alts._binary_clf_curve2(y_true, y_score, pos_label=None, sample_weight=None)`

MODIFIED VERSION OF SCIKIT-LEARN API

Calculate true and false positives per binary classification threshold.

Parameters

- **y_true** (*array, shape = [n_samples]*) – True targets of binary classification
- **y_score** (*array, shape = [n_samples]*) – Estimated probabilities or decision function
- **pos_label** (*int or str, default=None*) – The label of the positive class
- **sample_weight** (*array-like of shape (n_samples,), default=None*) – Sample weights.

Returns

- **fps** (*array, shape = [n_thresholds]*) – A count of false positives, at index i being the number of negative samples assigned a score $\geq \text{thresholds}[i]$. The total number of negative samples is equal to `fps[-1]` (thus true negatives are given by `fps[-1] - fps`).
- **tps** (*array, shape = [n_thresholds <= len(np.unique(y_score))]*) – An increasing count of true positives, at index i being the number of positive samples assigned a score $\geq \text{thresholds}[i]$. The total number of positive samples is equal to `tps[-1]` (thus false negatives are given by `tps[-1] - tps`).
- **thresholds** (*array, shape = [n_thresholds]*) – Decreasing score values.

Example

```
>>> y_true = [    1,    1,    1,    1,    1,    0]
>>> y_score = [ np.nan, 0.2, 0.3, 0.4, 0.5, 0.6, 0.3]
>>> sample_weight = None
>>> pos_label = None
>>> fps, tps, thresholds = _binary_clf_curve2(y_true, y_score)
```

kwcoco.metrics.util

Module Contents

Classes

<i>DictProxy</i>	Allows an object to proxy the behavior of a dict attribute
----------------------------------	--

```
class kwcoco.metrics.util.DictProxy
Bases: scriptconfig.dict_like.DictLike

Allows an object to proxy the behavior of a dict attribute

__getitem__(self, key)
__setitem__(self, key, value)
keys(self)
__json__(self)
```

kwcoco.metrics.voc_metrics

Module Contents

Classes

<i>VOC_Metrics</i>	API to compute object detection scores using Pascal VOC evaluation method.
------------------------------------	--

Functions

<i>_pr_curves</i>(y, method='voc2012')	Compute a PR curve from a method
<i>_voc_eval</i>(lines, recs, classname, iou_thresh=0.5, method='voc2012', bias=1.0)	VOC AP evaluation for a single category.
<i>_voc_ave_precision</i>(rec, prec, method='voc2012')	Compute AP from precision and recall

```
class kwcoco.metrics.voc_metrics.VOC_Metrics(classes=None)
Bases: ubelt.NiceRepr
```

API to compute object detection scores using Pascal VOC evaluation method.

To use, add true and predicted detections for each image and then run the `VOC_Metrics.score()` function.

Variables

- `recs` (`Dict[int, List[dict]]`) – true boxes for each image. maps image ids to a list of records within that image. Each record is a tlbr bbox, a difficult flag, and a class name.
- `cx_to_lines` (`Dict[int, List]`) – VOC formatted prediction predictions. mapping from class index to all predictions for that category. Each “line” is a list of [

[<imgid>, <score>, <tl_x>, <tl_y>, <br_x>, <br_y>]].

```
__nice__(self)
add_truth(self, true_dets, gid)
add_predictions(self, pred_dets, gid)
score(self, iou_thresh=0.5, bias=1, method='voc2012')
    Compute VOC scores for every category
```

Example

```
>>> from kwcoco.metrics.detect_metrics import DetectionMetrics
>>> from kwcoco.metrics.voc_metrics import * # NOQA
>>> dmet = DetectionMetrics.demo(
>>>     nimgs=1, nboxes=(0, 100), n_fp=(0, 30), n_fn=(0, 30), classes=2, score_
>>>     _noise=0.9)
>>> self = VOC_Metrics(classes=dmet.classes)
>>> self.add_truth(dmet.true_detections(0), 0)
>>> self.add_predictions(dmet.pred_detections(0), 0)
>>> voc_scores = self.score()
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()l()
>>> kwplot.figure(fnum=1, doclf=True)
>>> voc_scores['perclass'].draw()
```

```
kwplot.figure(fnum=2)      dmet.true_detections(0).draw(color='green',           labels=None)
dmet.pred_detections(0).draw(color='blue',   labels=None)  kwplot.autopl().gca().set_xlim(0, 100)
kwplot.autopl().gca().set_ylim(0, 100)
```

`kwcoco.metrics.voc_metrics._pr_curves(y, method='voc2012')`

Compute a PR curve from a method

Parameters `y` (`pd.DataFrame | DataFrameArray`) – output of `detection_confusions`

Returns `Tuple[float, ndarray, ndarray]`

Example

```
>>> import pandas as pd
>>> y1 = pd.DataFrame.from_records([
>>>     {'pred': 0, 'score': 10.00, 'true': -1, 'weight': 1.00},
>>>     {'pred': 0, 'score': 1.65, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 8.64, 'true': -1, 'weight': 1.00},
>>>     {'pred': 0, 'score': 3.97, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 1.68, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 5.06, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 0.25, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 1.75, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 8.52, 'true': 0, 'weight': 1.00},
>>>     {'pred': 0, 'score': 5.20, 'true': 0, 'weight': 1.00},
>>> ])
>>> import kwarray
>>> y2 = kwarray.DataFrameArray(y1)
>>> _pr_curves(y2)
>>> _pr_curves(y1)
```

```
kwcoco.metrics.voc_metrics._voc_eval(lines, recs, classname, iou_thresh=0.5, method='voc2012',
                                         bias=1.0)
```

VOC AP evaluation for a single category.

Parameters

- **lines** (*List[list]*) – VOC formatted predictions. Each “line” is a list of [[<imgid>, <score>, <tl_x>, <tl_y>, <br_x>, <br_y>]].
- **recs** (*Dict[int, List[dict]]*) – true boxes for each image. maps image ids to a list of records within that image. Each record is a tlbr bbox, a difficult flag, and a class name.
- **classname** (*str*) – the category to evaluate.
- **method** (*str*) – code for how the AP is computed.
- **bias** (*float*) – either 1.0 or 0.0.

Returns info about the evaluation containing AP. Contains fp, tp, prec, rec,

Return type Dict

Note: Raw replication of matlab implementation of creating assignments and the resulting PR-curves and AP. Based on MATLAB code [1].

References

[1] http://host.robots.ox.ac.uk/pascal/VOC/voc2012/VOCdevkit_18-May-2011.tar

```
kwcoco.metrics.voc_metrics._voc_ave_precision(rec, prec, method='voc2012')
```

Compute AP from precision and recall Based on MATLAB code in¹, ², and³.

Parameters

¹ http://host.robots.ox.ac.uk/pascal/VOC/voc2012/VOCdevkit_18-May-2011.tar

² https://github.com/rbgirshick/voc-dpm/blob/master/test/pascal_eval.m

³ https://github.com/rbgirshick/voc-dpm/blob/c0b88564bd668bcc6216bbffe96cb061613be768/utils/bootstrap/VOCevaldet_bootstrap.m

- **rec** (*ndarray*) – recall
- **prec** (*ndarray*) – precision
- **method** (*str*) – either voc2012 or voc2007

Returns ap: average precision

Return type float

References

Package Contents

Classes

<i>DetectionMetrics</i>	Object that computes associations between detections and can convert them
<i>BinaryConfusionVectors</i>	Stores information about a binary classification problem.
<i>ConfusionVectors</i>	Stores information used to construct a confusion matrix. This includes
<i>Measures</i>	Holds accumulated confusion counts, and derived measures
<i>OneVsRestConfusionVectors</i>	Container for multiple one-vs-rest binary confusion vectors
<i>PerClass_Measures</i>	

Functions

<code>eval_detections_cli(**kw)</code>	DEPRECATED USE <code>kwcoco eval</code> instead
--	---

`class kwcoco.metrics.DetectionMetrics(dmet, classes=None)`

Bases: `ubelt.NiceRepr`

Object that computes associations between detections and can convert them into sklearn-compatible representations for scoring.

Variables

- **gid_to_true_dets** (*Dict*) – maps image ids to truth
- **gid_to_pred_dets** (*Dict*) – maps image ids to predictions
- **classes** (*CategoryTree*) – category coder

Example

```
>>> dmet = DetectionMetrics.demo(  
>>>     nimgs=100, nboxes=(0, 3), n_fp=(0, 1), classes=8, score_noise=0.9,  
>>>     hacked=False)  
>>> print(dmet.score_kwCOCO(bias=0, compat='mutex', prioritize='iou')['mAP'])  
...  
>>> # NOTE: IN GENERAL NETHARN AND VOC ARE NOT THE SAME  
>>> print(dmet.score_voc(bias=0)['mAP'])  
0.8582...  
>>> #print(dmet.score_coco()['mAP'])
```

`score_coco`

`clear(dmet)`

`__nice__(dmet)`

`classmethod from_coco(DetectionMetrics, true_coco, pred_coco, gids=None, verbose=0)`

Create detection metrics from two coco files representing the truth and predictions.

Parameters

- `true_coco` (`kwCOCO.CocoDataset`)
- `pred_coco` (`kwCOCO.CocoDataset`)

Example

```
>>> import kwCOCO  
>>> from kwCOCO.demo.perterb import perterb_coco  
>>> true_coco = kwCOCO.CocoDataset.demo('shapes')  
>>> perterbkw = dict(box_noise=0.5, cls_noise=0.5, score_noise=0.5)  
>>> pred_coco = perterb_coco(true_coco, **perterbkw)  
>>> self = DetectionMetrics.from_coco(true_coco, pred_coco)  
>>> self.score_voc()
```

`_register_imagename(dmet, imgname, gid=None)`

`add_predictions(dmet, pred_dets, imgname=None, gid=None)`

Register/Add predicted detections for an image

Parameters

- `pred_dets` (`Detections`) – predicted detections
- `imgname` (`str`) – a unique string to identify the image
- `gid` (`int, optional`) – the integer image id if known

`add_truth(dmet, true_dets, imgname=None, gid=None)`

Register/Add groundtruth detections for an image

Parameters

- `true_dets` (`Detections`) – groundtruth
- `imgname` (`str`) – a unique string to identify the image
- `gid` (`int, optional`) – the integer image id if known

true_detections(*dmet, gid*)

gets Detections representation for groundtruth in an image

pred_detections(*dmet, gid*)

gets Detections representation for predictions in an image

confusion_vectors(*dmet, iou_thresh=0.5, bias=0, gids=None, compat='mutex', prioritize='iou', ignore_classes='ignore', background_class=ub.NoParam, verbose='auto', workers=0, track_probs='try', max_dets=None*)

Assigns predicted boxes to the true boxes so we can transform the detection problem into a classification problem for scoring.

Parameters

- **iou_thresh** (*float | List[float], default=0.5*) – bounding box overlap iou threshold required for assignment if a list, then return type is a dict
- **bias** (*float, default=0.0*) – for computing bounding box overlap, either 1 or 0
- **gids** (*List[int], default=None*) – which subset of images ids to compute confusion metrics on. If not specified all images are used.
- **compat** (*str, default='all'*) – can be ('ancestors' | 'mutex' | 'all'). determines which pred boxes are allowed to match which true boxes. If 'mutex', then pred boxes can only match true boxes of the same class. If 'ancestors', then pred boxes can match true boxes that match or have a coarser label. If 'all', then any pred can match any true, regardless of its category label.
- **prioritize** (*str, default='iou'*) – can be ('iou' | 'class' | 'correct') determines which box to assign to if multiple true boxes overlap a predicted box. if prioritize is iou, then the true box with maximum iou (above iou_thresh) will be chosen. If prioritize is class, then it will prefer matching a compatible class above a higher iou. If prioritize is correct, then ancestors of the true class are preferred over descendants of the true class, over unrelated classes.
- **ignore_classes** (*set, default={'ignore'}*) – class names indicating ignore regions
- **background_class** (*str, default=ub.NoParam*) – Name of the background class. If unspecified we try to determine it with heuristics. A value of None means there is no background class.
- **verbose** (*int, default='auto'*) – verbosity flag. In auto mode, verbose=1 if len(gids) > 1000.
- **workers** (*int, default=0*) – number of parallel assignment processes
- **track_probs** (*str, default='try'*) – can be 'try', 'force', or False. if truthy, we assume probabilities for multiple classes are available.

Returns ConfusionVectors | Dict[float, ConfusionVectors]

Example

```
>>> dmet = DetectionMetrics.demo(nimgs=30, classes=3,
>>>                               nboxes=10, n_fp=3, box_noise=10,
>>>                               with_probs=False)
>>> iou_to_cfsn = dmet.confusion_vectors(iou_thresh=[0.3, 0.5, 0.9])
>>> for t, cfsn in iou_to_cfsn.items():
>>>     print('t = {!r}'.format(t))
```

(continues on next page)

(continued from previous page)

```
...     print(cfsn.binarize_ovr().measures())
...     print(cfsn.binarize_classless().measures())
```

score_kwant(*dmet*, *iou_thresh*=0.5)

Scores the detections using kwant

score_kwccoco(*dmet*, *iou_thresh*=0.5, *bias*=0, *gids*=None, *compat*='all', *prioritize*='iou')

our scoring method

score_voc(*dmet*, *iou_thresh*=0.5, *bias*=1, *method*='voc2012', *gids*=None, *ignore_classes*='ignore')

score using voc method

Example

```
>>> dmet = DetectionMetrics.demo()
>>> nimgs=100, nboxes=(0, 3), n_fp=(0, 1), classes=8,
>>> score_noise=.5
>>> print(dmet.score_voc()['mAP'])
0.9399...
```

_to_coco(*dmet*)

Convert to a coco representation of truth and predictions

with inverse aid mappings

score_pycocotools(*dmet*, *with_evaler*=False, *with_confusion*=False, *verbose*=0, *iou_thresholds*=None)

score using ms-coco method

Returns dictionary with pct info**Return type** Dict**Example**

```
>>> # xdoctest: +REQUIRES(module:pycocotools)
>>> from kwccoco.metrics.detect_metrics import *
>>> dmet = DetectionMetrics.demo()
>>> nimgs=10, nboxes=(0, 3), n_fn=(0, 1), n_fp=(0, 1), classes=8, with_
>>> _probs=False
>>> pct_info = dmet.score_pycocotools(verbose=1,
>>>                               with_evaler=True,
>>>                               with_confusion=True,
>>>                               iou_thresholds=[0.5, 0.9])
>>> evaler = pct_info['evaler']
>>> iou_to_cfsn_vecs = pct_info['iou_to_cfsn_vecs']
>>> for iou_thresh in iou_to_cfsn_vecs.keys():
>>>     print('iou_thresh = {!r}'.format(iou_thresh))
>>>     cfsn_vecs = iou_to_cfsn_vecs[iou_thresh]
>>>     ovr_measures = cfsn_vecs.binarize_ovr().measures()
>>>     print('ovr_measures = {}'.format(ub.repr2(ovr_measures, nl=1,
>>>                                         precision=4)))
```

Note: by default pycocotools computes average precision as the literal average of computed precisions at 101 uniformly spaced recall thresholds.

pycocoutils seems to only allow predictions with the same category as the truth to match those truth objects. This should be the same as calling dmet.confusion_vectors with compat = mutex

pycocoutils does not take into account the fact that each box often has a score for each category.

pycocoutils will be incorrect if any annotation has an id of 0

a major difference in the way kwcoco scores versus pycocoutils is the calculation of AP. The assignment between truth and predicted detections produces similar enough results. Given our confusion vectors we use the scikit-learn definition of AP, whereas pycocoutils seems to compute precision and recall — more or less correctly — but then it resamples the precision at various specified recall thresholds (in the *accumulate* function, specifically how *pr* is resampled into the *q* array). This can lead to a large difference in reported scores.

pycocoutils also smooths out the precision such that it is monotonic decreasing, which might not be the best idea.

pycocotools area ranges are inclusive on both ends, that means the “small” and “medium” truth selections do overlap somewhat.

classmethod demo(*cls*, ***kwargs*)

Creates random true boxes and predicted boxes that have some noisy offset from the truth.

Kwargs:

classes (int, default=1): class list or the number of foreground classes.

nimgs (int, default=1): number of images in the coco datasets. **nboxes (int, default=1):** boxes per image. **n_fp (int, default=0):** number of false positives. **n_fn (int, default=0):** number of false negatives. **box_noise (float, default=0):** std of a normal distribution used to

perterb both box location and box size.

cls_noise (float, default=0): probability that a class label will change. Must be within 0 and 1.

anchors (ndarray, default=None): used to create random boxes **null_pred (bool, default=0):**

if True, predicted classes are returned as null, which means only localization scoring is suitable.

with_probs (bool, default=1): if True, includes per-class probabilities with predictions

CommandLine

```
xdoctest -m kwcoco.metrics.detect_metrics DetectionMetrics.demo:2 --show
```

Example

```
>>> kwargs = {}
>>> # Seed the RNG
>>> kwargs['rng'] = 0
>>> # Size parameters determine how big the data is
>>> kwargs['nimgs'] = 5
>>> kwargs['nboxes'] = 7
>>> kwargs['classes'] = 11
>>> # Noise parameters perterb predictions further from the truth
>>> kwargs['n_fp'] = 3
>>> kwargs['box_noise'] = 0.1
>>> kwargs['cls_noise'] = 0.5
>>> dmet = DetectionMetrics.demo(**kwargs)
>>> print('dmet.classes = {}'.format(dmet.classes))
dmet.classes = <CategoryTree(nNodes=12, maxDepth=3, maxBreadth=4...)>
>>> # Can grab kwimage.Detection object for any image
>>> print(dmet.true_detections(gid=0))
<Detections(4)>
>>> print(dmet.pred_detections(gid=0))
<Detections(7)>
```

Example

```
>>> # Test case with null predicted categories
>>> dmet = DetectionMetrics.demo(nimgs=30, null_pred=1, classes=3,
>>>                               nboxes=10, n_fp=3, box_noise=0.1,
>>>                               with_probs=False)
>>> dmet.gid_to_pred_dets[0].data
>>> dmet.gid_to_true_dets[0].data
>>> cfsn_vecs = dmet.confusion_vectors()
>>> binvecs_ovr = cfsn_vecs.binarize_ovr()
>>> binvecs_per = cfsn_vecs.binarize_classless()
>>> measures_per = binvecs_per.measures()
>>> measures_ovr = binvecs_ovr.measures()
>>> print('measures_per = {!r}'.format(measures_per))
>>> print('measures_ovr = {!r}'.format(measures_ovr))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> measures_ovr['perclass'].draw(key='pr', fnum=2)
```

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> from kwcoco.metrics.detect_metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     n_fp=(0, 1), n_fn=(0, 1), nimgs=32, nboxes=(0, 16),
>>>     classes=3, rng=0, newstyle=1, box_noise=0.5, cls_noise=0.0, score_
>>> _noise=0.3, with_probs=False)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> summary = dmet.summarize(plot=True, title='DetectionMetrics summary demo', u
>>> _with_ovr=True, with_bin=False)
>>> summary['bin_measures']
>>> kwplot.show_if_requested()
```

`summarize(dmet, out_dpath=None, plot=False, title='', with_bin='auto', with_ovr='auto')`

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> from kwcoco.metrics.detect_metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     n_fp=(0, 128), n_fn=(0, 4), nimgs=512, nboxes=(0, 32),
>>>     classes=3, rng=0)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> dmet.summarize(plot=True, title='DetectionMetrics summary demo')
>>> kwplot.show_if_requested()
```

`kwcoco.metrics.eval_detections_cli(**kw)`

DEPRECATED USE `kwcoco eval` instead

CommandLine

```
xdoctest -m ~/code/kwcoco/kwcoco/metrics/detect_metrics.py eval_detections_cli
```

`class kwcoco.metrics.BinaryConfusionVectors(data, cx=None, classes=None)`

Bases: `ubelt.NiceRepr`

Stores information about a binary classification problem. This is always with respect to a specific class, which is given by `cx` and `classes`.

The `data DataFrameArray` must contain `is_true` - if the row is an instance of class `classes[cx]` `pred_score` - the predicted probability of class `classes[cx]`, and `weight` - sample weight of the example

Example

```
>>> from kwcococo.metrics.confusion_vectors import * # NOQA
>>> self = BinaryConfusionVectors.demo(n=10)
>>> print('self = {!r}'.format(self))
>>> print('measures = {}'.format(ub.repr2(self.measures())))
```

```
>>> self = BinaryConfusionVectors.demo(n=0)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
```

```
>>> self = BinaryConfusionVectors.demo(n=1)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
```

```
>>> self = BinaryConfusionVectors.demo(n=2)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
```

classmethod demo(cls, n=10, p_true=0.5, p_error=0.2, p_miss=0.0, rng=None)

Create random data for tests

Parameters

- **n** (*int*) – number of rows
- **p_true** (*int*) – fraction of real positive cases
- **p_error** (*int*) – probability of making a recoverable mistake
- **p_miss** (*int*) – probability of making a unrecoverable mistake
- **rng** (*int | RandomState*) – random seed / state

Returns BinaryConfusionVectors

Example

```
>>> from kwcococo.metrics.confusion_vectors import * # NOQA
>>> cfsn = BinaryConfusionVectors.demo(n=1000, p_error=0.1, p_miss=0.1)
>>> measures = cfsn.measures()
>>> print('measures = {}'.format(ub.repr2(measures, nl=1)))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.figure(fnum=1, pnum=(1, 2, 1))
>>> measures.draw('pr')
>>> kwplot.figure(fnum=1, pnum=(1, 2, 2))
>>> measures.draw('roc')
```

property catname(self)

__nice__(self)

__len__(self)

measures(self, stabalize_thresh=7, fp_cutoff=None, monotonic_ppv=True, ap_method='pycocotools')

Get statistics (F1, G1, MCC) versus thresholds

Parameters

- **stabalize_thresh** (*int, default=7*) – if fewer than this many data points inserts dummy stabilization data so curves can still be drawn.
- **fp_cutoff** (*int, default=None*) – maximum number of false positives in the truncated roc curves. None is equivalent to `float('inf')`
- **monotonic_ppv** (*bool, default=True*) – if True ensures that precision is always increasing as recall decreases. This is done in pycocotools scoring, but I'm not sure its a good idea.

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> self = BinaryConfusionVectors.demo(n=0)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
>>> self = BinaryConfusionVectors.demo(n=1, p_true=0.5, p_error=0.5)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
>>> self = BinaryConfusionVectors.demo(n=3, p_true=0.5, p_error=0.5)
>>> print('measures = {}'.format(ub.repr2(self.measures())))

>>> self = BinaryConfusionVectors.demo(n=100, p_true=0.5, p_error=0.5, p_miss=0.
   ↪3)
>>> print('measures = {}'.format(ub.repr2(self.measures())))
>>> print('measures = {}'.format(ub.repr2(ub.odict(self.measures()))))
```

References

https://en.wikipedia.org/wiki/Confusion_matrix https://en.wikipedia.org/wiki/Precision_and_recall https://en.wikipedia.org/wiki/Matthews_correlation_coefficient

`_binary_clf_curves(self, stabalize_thresh=7, fp_cutoff=None)`

Compute TP, FP, TN, and FN counts for this binary confusion vector.

Code common to ROC, PR, and threshold measures, computes the elements of the binary confusion matrix at all relevant operating point thresholds.

Parameters

- **stabalize_thresh** (*int*) – if fewer than this many data points insert stabilization data.
- **fp_cutoff** (*int*) – maximum number of false positives

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> self = BinaryConfusionVectors.demo(n=1, p_true=0.5, p_error=0.5)
>>> self._binary_clf_curves()

>>> self = BinaryConfusionVectors.demo(n=0, p_true=0.5, p_error=0.5)
>>> self._binary_clf_curves()

>>> self = BinaryConfusionVectors.demo(n=100, p_true=0.5, p_error=0.5)
>>> self._binary_clf_curves()
```

```
draw_distribution(self)
_3dplot(self)
```

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> from kwcoco.metrics.detect_metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     n_fp=(0, 1), n_fn=(0, 2), nimgs=256, nboxes=(0, 10),
>>>     bbox_noise=10,
>>>     classes=1)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> self = bin_cfsn = cfsn_vecs.binarize_classless()
>>> #dmet.summarize(plot=True)
>>> import kwplot
>>> kwplot.autopl()l()
>>> kwplot.figure(fnum=3)
>>> self._3dplot()
```

class kwcoco.metrics.ConfusionVectors(*cfsn_vecs*, *data*, *classes*, *probs=None*)
Bases: `ubelt.NiceRepr`

Stores information used to construct a confusion matrix. This includes corresponding vectors of predicted labels, true labels, sample weights, etc...

Variables

- ***data*** (`kwarray.DataFrameArray`) – should at least have keys true, pred, weight
- ***classes*** (`Sequence` / `CategoryTree`) – list of category names or category graph
- ***probs*** (`ndarray`, *optional*) – probabilities for each class

Example

```
>>> # xdoctest: IGNORE_WANT
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     nimgs=10, nboxes=(0, 10), n_fp=(0, 1), classes=3)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> print(cfsn_vecs.data._pandas())
   pred  true    score  weight      iou    txs    pxs    gid
0      2      2  10.0000  1.0000  1.0000      0      4      0
1      2      2   7.5025  1.0000  1.0000      1      3      0
2      1      1   5.0050  1.0000  1.0000      2      2      0
3      3     -1   2.5075  1.0000 -1.0000     -1      1      0
4      2     -1   0.0100  1.0000 -1.0000     -1      0      0
5     -1      2   0.0000  1.0000 -1.0000      3     -1      0
6     -1      2   0.0000  1.0000 -1.0000      4     -1      0
7      2      2  10.0000  1.0000  1.0000      0      5      1
```

(continues on next page)

(continued from previous page)

8	2	2	8.0020	1.0000	1.0000	1	4	1
9	1	1	6.0040	1.0000	1.0000	2	3	1
..
62	-1	2	0.0000	1.0000	-1.0000	7	-1	7
63	-1	3	0.0000	1.0000	-1.0000	8	-1	7
64	-1	1	0.0000	1.0000	-1.0000	9	-1	7
65	1	-1	10.0000	1.0000	-1.0000	-1	0	8
66	1	1	0.0100	1.0000	1.0000	0	1	8
67	3	-1	10.0000	1.0000	-1.0000	-1	3	9
68	2	2	6.6700	1.0000	1.0000	0	2	9
69	2	2	3.3400	1.0000	1.0000	1	1	9
70	3	-1	0.0100	1.0000	-1.0000	-1	0	9
71	-1	2	0.0000	1.0000	-1.0000	2	-1	9

```
>>> # xdoctest: +REQUIRES(--show)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> import kwplot
>>> kwplot.autopl()
>>> from kwcoco.metrics.confusion_vectors import ConfusionVectors
>>> cfsn_vecs = ConfusionVectors.demo(
    nimgs=128, nboxes=(0, 10), n_fp=(0, 3), n_fn=(0, 3), classes=3)
>>> cx_to_binvecs = cfsn_vecs.binarize_ovr()
>>> measures = cx_to_binvecs.measures()['perclass']
>>> print('measures = {!r}'.format(measures))
measures = <PerClass_Measures({
    'cat_1': <Measures({'ap': 0.227, 'auc': 0.507, 'catname': cat_1, 'max_f1': f1=0.
    ↵45@0.47, 'nsupport': 788.000})>,
    'cat_2': <Measures({'ap': 0.288, 'auc': 0.572, 'catname': cat_2, 'max_f1': f1=0.
    ↵51@0.43, 'nsupport': 788.000})>,
    'cat_3': <Measures({'ap': 0.225, 'auc': 0.484, 'catname': cat_3, 'max_f1': f1=0.
    ↵46@0.40, 'nsupport': 788.000})>,
}) at 0x7facf77bdf0>
>>> kwplot.figure(fnum=1, doclf=True)
>>> measures.draw(key='pr', fnum=1, pnum=(1, 3, 1))
>>> measures.draw(key='roc', fnum=1, pnum=(1, 3, 2))
>>> measures.draw(key='mcc', fnum=1, pnum=(1, 3, 3))
...

```

nice(cfsn_vecs)_json_(self)

Serialize to json

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics import ConfusionVectors
>>> self = ConfusionVectors.demo(n_imgs=1, classes=2, n_fp=0, nboxes=1)
>>> state = self.__json__()
>>> print('state = {}'.format(ub.repr2(state, nl=2, precision=2, align=1)))
>>> recon = ConfusionVectors.from_json(state)
```

```
classmethod from_json(cls, state)
classmethod demo(cfsn_vecs, **kw)
```

Parameters `**kwargs` – See `kwcoco.metrics.DetectionMetrics.demo()`

Returns ConfusionVectors

Example

```
>>> cfsn_vecs = ConfusionVectors.demo()
>>> print('cfsn_vecs = {!r}'.format(cfsn_vecs))
>>> cx_to_binvecs = cfsn_vecs.binarize_ovr()
>>> print('cx_to_binvecs = {!r}'.format(cx_to_binvecs))
```

```
classmethod from_arrays(ConfusionVectors, true, pred=None, score=None, weight=None, probs=None, classes=None)
```

Construct confusion vector data structure from component arrays

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> import kwarray
>>> classes = ['person', 'vehicle', 'object']
>>> rng = kwarray.ensure_rng(0)
>>> true = (rng.rand(10) * len(classes)).astype(int)
>>> probs = rng.rand(len(true), len(classes))
>>> cfsn_vecs = ConfusionVectors.from_arrays(true=true, probs=probs,
...     ↪classes=classes)
>>> cfsn_vecs.confusion_matrix()
pred      person  vehicle  object
real
person        0        0        0
vehicle       2        4        1
object        2        1        0
```

confusion_matrix(*cfsn_vecs*, *compress=False*)

Builds a confusion matrix from the confusion vectors.

Parameters `compress` (`bool, default=False`) – if True removes rows / columns with no entries

Returns

cm [the labeled confusion matrix]

(Note: we should write a efficient replacement for this use case. #remove_pandas)

Return type pd.DataFrame

CommandLine

```
xdoctest -m kwcoco.metrics.confusion_vectors ConfusionVectors.confusion_matrix
```

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo()
>>> nimgs=10, nboxes=(0, 10), n_fp=(0, 1), n_fn=(0, 1), classes=3, cls_noise=.2
>>> cfsn_vecs = dmet.confusion_vectors()
>>> cm = cfsn_vecs.confusion_matrix()
...
>>> print(cm.to_string(float_format=lambda x: '%.2f' % x))
pred      background  cat_1  cat_2  cat_3
real
background      0.00   1.00   2.00   3.00
cat_1           3.00  12.00   0.00   0.00
cat_2           3.00   0.00  14.00   0.00
cat_3           2.00   0.00   0.00  17.00
```

coarsen(*cfsn_vecs*, *cxs*)

Creates a coarsened set of vectors

Returns ConfusionVectors

binarize_classless(*cfsn_vecs*, *negative_classes=None*)

Creates a binary representation useful for measuring the performance of detectors. It is assumed that scores of “positive” classes should be high and “negative” classes should be low.

Parameters *negative_classes* (*List[str | int]*) – list of negative class names or idxs, by default chooses any class with a true class index of -1. These classes should ideally have low scores.

Returns BinaryConfusionVectors

Note: The “classlessness” of this depends on the *compat=”all”* argument being used when constructing confusion vectors, otherwise it becomes something like a macro-average because the class information was used in deciding which true and predicted boxes were allowed to match.

Example

```
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo()
>>> nimgs=10, nboxes=(0, 10), n_fp=(0, 1), n_fn=(0, 1), classes=3
>>> cfsn_vecs = dmet.confusion_vectors()
>>> class_idxs = list(dmet.classes.node_to_idx.values())
>>> binvecs = cfsn_vecs.binarize_classless()
```

binarize_ovr(*cfsn_vecs*, *mode*=1, *keyby*='name', *ignore_classes*={'ignore'}, *approx*=0)
Transforms *cfsn_vecs* into one-vs-rest BinaryConfusionVectors for each category.

Parameters

- **mode** (*int, default=1*) – 0 for heirarchy aware or 1 for voc like. MODE 0 IS PROBABLY BROKEN
- **keyby** (*int | str*) – can be cx or name
- **ignore_classes** (*Set[str]*) – category names to ignore
- **approx** (*bool, default=0*) – if True try and approximate missing scores otherwise assume they are irrecoverable and use -inf

Returns

which behaves like Dict[int, BinaryConfusionVectors]: cx_to_binvecs

Return type *OneVsRestConfusionVectors*

Example

```
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> cfsn_vecs = ConfusionVectors.demo()
>>> print('cfsn_vecs = {!r}'.format(cfsn_vecs))
>>> catname_to_binvecs = cfsn_vecs.binarize_ovr(keyby='name')
>>> print('catname_to_binvecs = {!r}'.format(catname_to_binvecs))
```

cfsn_vecs.data.pandas() *catname_to_binvecs*.cx_to_binvecs['class_1'].data.pandas()

Note:

classification_report(*cfsn_vecs*, *verbose*=0)
Build a classification report with various metrics.

Example

```
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcoco.metrics.confusion_vectors import * # NOQA
>>> cfsn_vecs = ConfusionVectors.demo()
>>> report = cfsn_vecs.classification_report(verbose=1)
```

class kwcoco.metrics.Measures(*info*)
Bases: *ubelt.NiceRepr*, *kwcoco.metrics.util.DictProxy*

Holds accumulated confusion counts, and derived measures

Example

```
>>> from kwcoco.metrics.confusion_vectors import BinaryConfusionVectors # NOQA
>>> binvecs = BinaryConfusionVectors.demo(n=100, p_error=0.5)
>>> self = binvecs.measures()
>>> print('self = {!r}'.format(self))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> self.draw(doclf=True)
>>> self.draw(key='pr', pnum=(1, 2, 1))
>>> self.draw(key='roc', pnum=(1, 2, 2))
>>> kwplot.show_if_requested()
```

```
property catname(self)
__nice__(self)
reconstruct(self)
classmethod from_json(cls, state)
__json__(self)
```

Example

```
>>> from kwcoco.metrics.confusion_vectors import BinaryConfusionVectors # NOQA
>>> from kwcoco.metrics.confusion_measures import * # NOQA
>>> binvecs = BinaryConfusionVectors.demo(n=10, p_error=0.5)
>>> self = binvecs.measures()
>>> info = self.__json__()
>>> print('info = {}'.format(ub.repr2(info, nl=1)))
>>> populate_info(info)
>>> print('info = {}'.format(ub.repr2(info, nl=1)))
>>> recon = Measures.from_json(info)
```

```
summary(self)
maximized_thresholds(self)
    Returns thresholds that maximize metrics.
counts(self)
draw(self, key=None, prefix='', **kw)
```

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> # xdoctest: +REQUIRES(module:pandas)
>>> from kwcococo.metrics.confusion_vectors import ConfusionVectors # NOQA
>>> cfsn_vecs = ConfusionVectors.demo()
>>> ovr_cfsn = cfsn_vecs.binarize_ovr(keyby='name')
>>> self = ovr_cfsn.measures()['perclass']
>>> self.draw('mcc', doclf=True, fnum=1)
>>> self.draw('pr', doclf=1, fnum=2)
>>> self.draw('roc', doclf=1, fnum=3)
```

```
summary_plot(self,fnum=1, title='', subplots='auto')
```

Example

```
>>> from kwcococo.metrics.confusion_measures import * # NOQA
>>> from kwcococo.metrics.confusion_vectors import ConfusionVectors # NOQA
>>> cfsn_vecs = ConfusionVectors.demo(n=3, p_error=0.5)
>>> binvecs = cfsn_vecs.binarize_classless()
>>> self = binvecs.measures()
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> self.summary_plot()
>>> kwplot.show_if_requested()
```

classmethod demo(cls, **kwargs)

Create a demo Measures object for testing / demos

Parameters ****kwargs** – passed to `BinaryConfusionVectors.demo()`. some valid keys are:
n, rng, p_rue, p_error, p_miss.

classmethod combine(cls, tocombine, precision=None, growth=None, thresh_bins=None)

Combine binary confusion metrics

Parameters

- **tocombine** (`List[Measures]`) – a list of measures to combine into one
- **precision** (`int | None`) – If specified rounds thresholds to this precision which can prevent a RAM explosion when combining a large number of measures. However, this is a lossy operation and will impact the underlying scores. NOTE: use `growth` instead.
- **growth** (`int | None`) – if specified this limits how much the resulting measures are allowed to grow by. If `None`, `growth` is unlimited. Otherwise, if `growth` is ‘`max`’, the `growth` is limited to the maximum length of an input. We might make this more numerical in the future.
- **thresh_bins** (`int`) – Force this many threshold bins.

Returns Measures

Example

```
>>> from kwCOCO.metrics.confusion_measures import * # NOQA
>>> measures1 = Measures.demo(n=15)
>>> measures2 = measures1
>>> tocombine = [measures1, measures2]
>>> new_measures = Measures.combine(tocombine)
>>> new_measures.reconstruct()
>>> print('new_measures = {!r}'.format(new_measures))
>>> print('measures1 = {!r}'.format(measures1))
>>> print('measures2 = {!r}'.format(measures2))
>>> print(ub.repr2(measures1.__json__(), nl=1, sort=0))
>>> print(ub.repr2(measures2.__json__(), nl=1, sort=0))
>>> print(ub.repr2(new_measures.__json__(), nl=1, sort=0))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> kwplot.figure(fnum=1)
>>> new_measures.summary_plot()
>>> measures1.summary_plot()
>>> measures1.draw('roc')
>>> measures2.draw('roc')
>>> new_measures.draw('roc')
```

Example

```
>>> # Demonstrate issues that can arise from choosing a precision
>>> # that is too low when combining metrics. Breakpoints
>>> # between different metrics can get muddled, but choosing a
>>> # precision that is too high can overwhelm memory.
>>> from kwCOCO.metrics.confusion_measures import * # NOQA
>>> base = ub.map_vals(np.asarray, {
>>>     'tp_count': [1, 1, 2, 2, 2, 2, 3],
>>>     'fp_count': [0, 1, 1, 2, 3, 4, 5],
>>>     'fn_count': [1, 1, 0, 0, 0, 0, 0],
>>>     'tn_count': [5, 4, 4, 3, 2, 1, 0],
>>>     'thresholds': [.0, .0, .0, .0, .0, .0, .0],
>>> })
>>> # Make tiny offsets to thresholds
>>> rng = kwarray.ensure_rng(0)
>>> n = len(base['thresholds'])
>>> offsets = [
>>>     sorted(rng.rand(n) * 10 ** -rng.randint(4, 7))[::-1]
>>>     for _ in range(20)
>>> ]
>>> tocombine = []
>>> for offset in offsets:
>>>     base_n = base.copy()
>>>     base_n['thresholds'] += offset
>>>     measures_n = Measures(base_n).reconstruct()
>>>     tocombine.append(measures_n)
```

(continues on next page)

(continued from previous page)

```
>>> for precision in [6, 5, 2]:
>>>     combo = Measures.combine(tocombine, precision=precision).reconstruct()
>>>     print('precision = {!r}'.format(precision))
>>>     print('combo = {}'.format(ub.repr2(combo, nl=1)))
>>>     print('num_thresholds = {}'.format(len(combo['thresholds'])))
>>> for growth in [None, 'max', 'log', 'root', 'half']:
>>>     combo = Measures.combine(tocombine, growth=growth).reconstruct()
>>>     print('growth = {!r}'.format(growth))
>>>     print('combo = {}'.format(ub.repr2(combo, nl=1)))
>>>     print('num_thresholds = {}'.format(len(combo['thresholds'])))
>>> #print(combo.counts().pandas())
```

Example

```
>>> # Test case: combining a single measures should leave it unchanged
>>> from kwcococo.metrics.confusion_measures import * # NOQA
>>> measures = Measures.demo(n=40, p_true=0.2, p_error=0.4, p_miss=0.6)
>>> df1 = measures.counts().pandas().fillna(0)
>>> print(df1)
>>> tocombine = [measures]
>>> combo = Measures.combine(tocombine)
>>> df2 = combo.counts().pandas().fillna(0)
>>> print(df2)
>>> assert np.allclose(df1, df2)
```

```
>>> combo = Measures.combine(tocombine, thresh_bins=2)
>>> df3 = combo.counts().pandas().fillna(0)
>>> print(df3)
```

```
>>> # I am NOT sure if this is correct or not
>>> thresh_bins = 20
>>> combo = Measures.combine(tocombine, thresh_bins=thresh_bins)
>>> df4 = combo.counts().pandas().fillna(0)
>>> print(df4)
```

```
>>> combo = Measures.combine(tocombine, thresh_bins=np.linspace(0, 1, 20))
>>> df4 = combo.counts().pandas().fillna(0)
>>> print(df4)
```

assert np.allclose(combo['thresholds'], measures['thresholds']) assert np.allclose(combo['fp_count'], measures['fp_count']) assert np.allclose(combo['tp_count'], measures['tp_count']) assert np.allclose(combo['tp_count'], measures['tp_count'])

globals().update(xdev.get_func_kwargs(Measures.combine))

class kwcococo.metrics.OneVsRestConfusionVectors(cx_to_binvecs, classes)

Bases: `ubelt.NiceRepr`

Container for multiple one-vs-rest binary confusion vectors

Variables

- `cx_to_binvecs` –

- **classes** –

Example

```
>>> from kwcoco.metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo(
>>>     nimgs=10, nboxes=(0, 10), n_fp=(0, 1), classes=3)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> self = cfsn_vecs.binarize_ovr(keyby='name')
>>> print('self = {!r}'.format(self))
```

`__nice__(self)`

`classmethod demo(cls)`

Parameters `**kwargs` – See `kwcoco.metrics.DetectionMetrics.demo()`

Returns `ConfusionVectors`

`keys(self)`

`__getitem__(self, cx)`

`measures(self, stabilize_thresh=7, fp_cutoff=None, monotonic_ppv=True, ap_method='pycocotools')`

Creates binary confusion measures for every one-versus-rest category.

Parameters

- `stabilize_thresh` (`int, default=7`) – if fewer than this many data points inserts dummy stabilization data so curves can still be drawn.
- `fp_cutoff` (`int, default=None`) – maximum number of false positives in the truncated roc curves. `None` is equivalent to `float('inf')`
- `monotonic_ppv` (`bool, default=True`) – if True ensures that precision is always increasing as recall decreases. This is done in pycocotools scoring, but I'm not sure its a good idea.

SeeAlso: `BinaryConfusionVectors.measures()`

Example

```
>>> self = OneVsRestConfusionVectors.demo()
>>> thresh_result = self.measures()['perclass']
```

`abstract ovr_classification_report(self)`

`class kwcoco.metrics.PerClass_Measures(cx_to_info)`
Bases: `ubelt.NiceRepr, kwcoco.metrics.util.DictProxy`

`__nice__(self)`

`summary(self)`

`classmethod from_json(cls, state)`

`__json__(self)`

`draw(self, key='mcc', prefix='', **kw)`

Example

```
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> from kwCOCO.metrics.confusion_vectors import ConfusionVectors # NOQA
>>> cfsn_vecs = ConfusionVectors.demo()
>>> ovr_cfsn = cfsn_vecs.binarize_ovr(keyby='name')
>>> self = ovr_cfsn.measures()['perclass']
>>> self.draw('mcc', doclf=True, fnum=1)
>>> self.draw('pr', doclf=1, fnum=2)
>>> self.draw('roc', doclf=1, fnum=3)
```

```
draw_roc(self, prefix='', **kw)
draw_pr(self, prefix='', **kw)
summary_plot(self, fnum=1, title='', subplots='auto')
```

CommandLine

```
python ~/code/kwCOCO/kwCOCO/metrics/confusion_measures.py PerClass_Measures.
->summary_plot --show
```

Example

```
>>> from kwCOCO.metrics.confusion_measures import * # NOQA
>>> from kwCOCO.metrics.detect_metrics import DetectionMetrics
>>> dmet = DetectionMetrics.demo()
>>>     n_fp=(0, 1), n_fn=(0, 3), nimgs=32, nboxes=(0, 32),
>>>     classes=3, rng=0, newstyle=1, box_noise=0.7, cls_noise=0.2, score_
>>> noise=0.3, with_probs=False)
>>> cfsn_vecs = dmet.confusion_vectors()
>>> ovr_cfsn = cfsn_vecs.binarize_ovr(keyby='name', ignore_classes=['vector',
>>> 'raster'])
>>> self = ovr_cfsn.measures()['perclass']
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> import seaborn as sns
>>> sns.set()
>>> self.summary_plot(title='demo summary_plot ovr', subplots=['pr', 'roc'])
>>> kwplot.show_if_requested()
>>> self.summary_plot(title='demo summary_plot ovr', subplots=['mcc', 'acc'],
>>> fnum=2)
```

2.2.6 kwcococo.util

`mkinit ~/code/kwcoco/kwcoco/util/_init__.py -w`

Submodules

`kwcococo.util.dict_like`

Module Contents

Classes

<code>DictLike</code>	An inherited class must specify the <code>getitem</code> , <code>setitem</code> , and
-----------------------	---

`class kwcococo.util.dict_like.DictLike`

Bases: `ubelt.NiceRepr`

An inherited class must specify the `getitem`, `setitem`, and keys methods.

A class is dictionary like if it has:

`__iter__`, `__len__`, `__contains__`, `__getitem__`, `items`, `keys`, `values`, `get`, and if it should be writable it should have: `__delitem__`, `__setitem__`, `update`,

And perhaps: `copy`,

`__iter__`, `__len__`, `__contains__`, `__getitem__`, `items`, `keys`, `values`, `get`, and if it should be writable it should have: `__delitem__`, `__setitem__`, `update`,

And perhaps: `copy`,

`asdict`

`abstract getitem(self, key)`

`abstract setitem(self, key, value)`

`abstract delitem(self, key)`

`abstract keys(self)`

`__len__(self)`

`__iter__(self)`

`__contains__(self, key)`

`__delitem__(self, key)`

`__getitem__(self, key)`

`__setitem__(self, key, value)`

`items(self)`

`values(self)`

`copy(self)`

`to_dict(self)`

```
update(self, other)
get(self, key, default=None)
```

kwcococo.util.jsonschema_elements

Functional interface into defining jsonschema structures.

See mixin classes for details.

Example

```
>>> from kwcococo.util.jsonschema_elements import * # NOQA
>>> elem = SchemaElements()
>>> for base in SchemaElements.__bases__:
>>>     print('\n\n====\nbase = {!r}'.format(base))
>>>     attrs = [key for key in dir(base) if not key.startswith('_')]
>>>     for key in attrs:
>>>         value = getattr(elem, key)
>>>         print('  {} = {}'.format(key, value))
```

Module Contents

Classes

<i>Element</i>	A dictionary used to define an element of a JSON Schema.
<i>ScalarElements</i>	Single-valued elements
<i>QuantifierElements</i>	Quantifier types
<i>ContainerElements</i>	Types that contain other types
<i>SchemaElements</i>	Functional interface into defining jsonschema structures.

Attributes

elem

ALLOF

ANY

ANYOF

ARRAY

BOOLEAN

continues on next page

Table 76 – continued from previous page

<i>INTEGER</i>
<i>NOT</i>
<i>NULL</i>
<i>NUMBER</i>
<i>OBJECT</i>
<i>ONEOF</i>
<i>STRING</i>

```
class kwcococo.util.jsonschema_elements.Element(base, options={}, _magic=None)
Bases: dict
```

A dictionary used to define an element of a JSON Schema.

The exact keys/values for the element will depend on the type of element being described. The *SchemaElements* defines exactly what these are for the core elements. (e.g. OBJECT, INTEGER, NULL, ARRAY, ANYOF)

Example

```
>>> from kwcococo.coco_schema import * # NOQA
>>> self = Element(base={'type': 'demo'}, options={'opt1', 'opt2'})
>>> new = self(opt1=3)
>>> print('self = {}'.format(ub.repr2(self, nl=1, sort=1)))
>>> print('new = {}'.format(ub.repr2(new, nl=1, sort=1)))
>>> print('new2 = {}'.format(ub.repr2(new(), nl=1, sort=1)))
>>> print('new3 = {}'.format(ub.repr2(new(title='myvar'), nl=1, sort=1)))
>>> print('new4 = {}'.format(ub.repr2(new(title='myvar')(examples=['']), nl=1, sort=1)))
>>> print('new5 = {}'.format(ub.repr2(new(badattr=True), nl=1, sort=1)))
self = {
    'type': 'demo',
}
new = {
    'opt1': 3,
    'type': 'demo',
}
new2 = {
    'opt1': 3,
    'type': 'demo',
}
new3 = {
    'opt1': 3,
    'title': 'myvar',
    'type': 'demo',
}
new4 = {
```

(continues on next page)

(continued from previous page)

```
'examples': [''],
'opt1': 3,
'title': 'myvar',
'type': 'demo',
}
new5 = {
    'opt1': 3,
    'type': 'demo',
}
```

__generics__**__call__**(*self*, **args*, ***kw*)**validate**(*self*, *instance*=*ub.NoParam*)

If *instance* is given, validates that that dictionary conforms to this schema. Otherwise validates that this is a valid schema element.

Parameters ***instance*** (*dict*) – a dictionary to validate

__or__(*self*, *other*)

Syntax for making an anyOf relationship

Example

```
>>> from kwcococo.util.jsonschema_elements import * # NOQA
>>> obj1 = OBJECT(dict(opt1=NUMBER()))
>>> obj2 = OBJECT(dict(opt2=STRING()))
>>> obj3 = OBJECT(dict(opt3=ANY()))
>>> any_v1 = obj1 | obj2
>>> any_v2 = ANYOF(obj1, obj2)
>>> assert any_v1 == any_v2
>>> any_v3 = any_v1 | obj3
>>> any_v4 = ANYOF(obj1, obj2, obj3)
>>> assert any_v3 == any_v4
```

class kwcococo.util.jsonschema_elements.**ScalarElements**

Bases: *object*

Single-valued elements

property **NULL**(*self*)

<https://json-schema.org/understanding-json-schema/reference/null.html>

property **BOOLEAN**(*self*)

<https://json-schema.org/understanding-json-schema/reference/null.html>

property **STRING**(*self*)

<https://json-schema.org/understanding-json-schema/reference/string.html>

property **NUMBER**(*self*)

<https://json-schema.org/understanding-json-schema/reference/numeric.html#number>

property **INTEGER**(*self*)

<https://json-schema.org/understanding-json-schema/reference/numeric.html#integer>

class kwcococo.util.jsonschema_elements.QquantifierElements

Bases: object

Quantifier types

<https://json-schema.org/understanding-json-schema/reference/combing.html#allof>

Example

```
>>> from kwcococo.util.jsonschema_elements import * # NOQA
>>> elem.ANYOF(elem.STRING, elem.NUMBER).validate()
>>> elem.ONEOF(elem.STRING, elem.NUMBER).validate()
>>> elem.NOT(elem.NULL).validate()
>>> elem.NOT(elem.ANY).validate()
>>> elem.ANY.validate()
```

property ANY(self)

ALLOF(self, *TYPES)

ANYOF(self, *TYPES)

ONEOF(self, *TYPES)

NOT(self, TYPE)

class kwcococo.util.jsonschema_elements.ContainerElements

Types that contain other types

Example

```
>>> from kwcococo.util.jsonschema_elements import * # NOQA
>>> print(elem.ARRAY().validate())
>>> print(elem.OBJECT().validate())
>>> print(elem.OBJECT().validate())
{'type': 'array', 'items': []}
{'type': 'object', 'properties': {}}
{'type': 'object', 'properties': {}}
```

ARRAY(self, TYPE={}, **kw)

<https://json-schema.org/understanding-json-schema/reference/array.html>

Example

```
>>> from kwcococo.util.jsonschema_elements import * # NOQA
>>> ARRAY(numItems=3)
>>> schema = ARRAY(minItems=3)
>>> schema.validate()
{'type': 'array', 'items': [], 'minItems': 3}
```

OBJECT(self, PROPERTIES={}, **kw)

<https://json-schema.org/understanding-json-schema/reference/object.html>

Example

```
>>> import jsonschema
>>> schema = elem.OBJECT()
>>> jsonschema.validate({}, schema)
>>> #
>>> import jsonschema
>>> schema = elem.OBJECT({
>>>     'key1': elem.ANY(),
>>>     'key2': elem.ANY(),
>>> }, required=['key1'])
>>> jsonschema.validate({'key1': None}, schema)
>>> #
>>> import jsonschema
>>> schema = elem.OBJECT({
>>>     'key1': elem.OBJECT({'arr': elem.ARRAY()}),
>>>     'key2': elem.ANY(),
>>> }, required=['key1'], title='a title')
>>> schema.validate()
>>> print('schema = {}'.format(ub.repr2(schema, sort=1, nl=-1)))
>>> jsonschema.validate({'key1': {'arr': []}}, schema)
schema = {
    'properties': {
        'key1': {
            'properties': {
                'arr': {'items': {}, 'type': 'array'}
            },
            'type': 'object'
        },
        'key2': {}
    },
    'required': ['key1'],
    'title': 'a title',
    'type': 'object'
}
```

class kwcococo.util.jsonschema_elements.SchemaElements
Bases: *ScalarElements, QuantifierElements, ContainerElements*

Functional interface into defining jsonschema structures.

See mixin classes for details.

References

<https://json-schema.org/understanding-json-schema/>

Todo:

- [] Generics: title, description, default, examples
-

CommandLine

```
xdoctest -m /home/joncrall/code/kwcoco/kwcoco/util/jsonschema_elements.py
↳ SchemaElements
```

Example

```
>>> from kwcoco.util.jsonschema_elements import * # NOQA
>>> elem = SchemaElements()
>>> elem.ARRAY(elem.ANY())
>>> schema = OBJECT({
>>>     'prop1': ARRAY(INTEGER, minItems=3),
>>>     'prop2': ARRAY(STRING, numItems=2),
>>>     'prop3': ARRAY(OBJECT({
>>>         'subprob1': NUMBER,
>>>         'subprob2': NUMBER,
>>>     })))
>>> })
>>> print('schema = {}'.format(ub.repr2(schema, nl=2, sort=1)))
schema = {
    'properties': {
        'prop1': {'items': {'type': 'integer'}, 'minItems': 3, 'type': 'array'},
        'prop2': {'items': {'type': 'string'}, 'maxItems': 2, 'minItems': 2, 'type':
↳ ': 'array'},
        'prop3': {'items': {'properties': {'subprob1': {'type': 'number'}, 'subprob2':
↳ ': {'type': 'number'}}}, 'type': 'object'}, 'type': 'array'},
    },
    'type': 'object',
}
```

```
>>> TYPE = elem.OBJECT({
>>>     'p1': ANY,
>>>     'p2': ANY,
>>> }, required=['p1'])
>>> import jsonschema
>>> inst = {'p1': None}
>>> jsonschema.validate(inst, schema=TYPE)
>>> #jsonschema.validate({'p2': None}, schema=TYPE)
```

kwcococo.util.jsonschema_elements.elem
kwcococo.util.jsonschema_elements.ALLOF
kwcococo.util.jsonschema_elements.ANY
kwcococo.util.jsonschema_elements.ANYOF
kwcococo.util.jsonschema_elements.ARRAY
kwcococo.util.jsonschema_elements.BOOLEAN
kwcococo.util.jsonschema_elements.INTEGER
kwcococo.util.jsonschema_elements.NOT
kwcococo.util.jsonschema_elements.NULL

```
kwcoco.util.jsonschema_elements.NUMBER  
kwcoco.util.jsonschema_elements.OBJECT  
kwcoco.util.jsonschema_elements.ONEOF  
kwcoco.util.jsonschema_elements.STRING
```

kwcoco.util.lazy_frame_backends

Ducktyped interfaces for loading subregions of images with standard slice syntax

Module Contents

Classes

<i>LazySpectralFrameFile</i>	Potentially faster than GDAL for HDR formats.
<i>LazyRasterIOFrameFile</i>	fpath = '/home/joncrall/.cache/kwcoco/demo/large_hyperspectral/big_img.tif'
<i>LazyGDalFrameFile</i>	

Functions

```
_have_gdal()  
  
_have_rasterio()  
  
_have_spectral()  
  
_demo_geotiff_with_nodata()
```

Example

```
_rectify_slice_dim(part, D)  
  
_validate_nonzero_data(file) Test to see if the image is all black.  
_read_envi_header(file) USAGE: hdr = _read_envi_header(file)
```

Attributes

```
profile  
  
_GDAL_DTYPE_LUT
```

```
kwcoco.util.lazy_frame_backends.profile  
kwcoco.util.lazy_frame_backends._have_gdal()
```

```

kwcoco.util.lazy_frame_backends._have_rasterio()
kwcoco.util.lazy_frame_backends._have_spectral()
kwcoco.util.lazy_frame_backends._GDAL_DTYPE_LUT
class kwcoco.util.lazy_frame_backends.LazySpectralFrameFile(fp)
Bases: ubelt.NiceRepr

Potentially faster than GDAL for HDR formats.

.ds(self)

classmethod available(self)
    Returns True if this backend is available

property ndim(self)
property shape(self)
property dtype(self)
__nice__(self)
__getitem__(self, index)

class kwcoco.util.lazy_frame_backends.LazyRasterIOFrameFile(fp)
Bases: ubelt.NiceRepr

fp = '/home/joncrall/.cache/kwcoco/demo/large_hyperspectral/big_img_128.bsq' lazy_rio = LazyRasterI-
OFrameFile(fp) ds = lazy_rio._ds

classmethod available(self)
    Returns True if this backend is available

.ds(self)

property ndim(self)
property shape(self)
property dtype(self)
__nice__(self)
__getitem__(self, index)

kwcoco.util.lazy_frame_backends._demo_geoinfo_with_nodata()

```

Example

```

from kwcoco.util.lazy_frame_backends import * # NOQA fp = _demo_geoinfo_with_nodata() self = LazyG-
DalFrameFile.demo()

class kwcoco.util.lazy_frame_backends.LazyGDalFrameFile(fp, nodata=None)
Bases: ubelt.NiceRepr

```

Todo:

- [] Move to its own backend module
 - [] When used with COCO, allow the image metadata to populate the height, width, and channels if possible.
-

Example

```
>>> # xdoctest: +REQUIRES(module:osgeo)
>>> self = LazyGDalFrameFile.demo()
>>> print('self = {!r}'.format(self))
>>> self[0:3, 0:3]
>>> self[:, :, 0]
>>> self[0]
>>> self[0, 3]
```

```
>>> # import kwplot
>>> # kwplot.imshow(self[:])
```

Parameters

- **nodata**
- **masking_method**

Example

```
>>> # See if we can reproduce the INTERLEAVE bug
```

```
data = np.random.rand(128, 128, 64) import kwimage import ubelt as ub from os.path import join dpath = ub.ensure_app_cache_dir('kwcoco/tests/reader') fpath = join(dpath, 'foo.tiff') kwimage.imwrite(fpath, data, backend='skimage') recon1 = kwimage.imread(fpath) recon1.shape

self = LazyGDalFrameFile(fpath) self.shape self[]

classmethod available(self)
    Returns True if this backend is available

_ds(self)

classmethod demo(cls, key='astro', dsize=None)

property ndim(self)
property shape(self)
property dtype(self)
__nice__(self)
__getitem__(self, index)
```

References

<https://gis.stackexchange.com/questions/162095/gdal-driver-create-typeerror>

Example

```
>>> # Test nodata works correctly
>>> # xdoctest: +REQUIRES(module:osgeo)
>>> from kwcoco.util.lazy_frame_backends import * # NOQA
>>> from kwcoco.util.lazy_frame_backends import _demo_geoinfo_with_nodata
>>> fpath = _demo_geoinfo_with_nodata()
>>> self = LazyGDalFrameFile(fpath, nodata='auto')
>>> imdata = self[:, :]
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> import kwarray
>>> kwplot.autompl()
>>> imdata = kwimage.normalize_intensity(imdata)
>>> imdata = np.nan_to_num(imdata)
>>> kwplot.imshow(imdata)
```

`__array__(self)`

Allow this object to be passed to np.asarray

References

<https://numpy.org/doc/stable/user/basics.dispatch.html>

`kwcoco.util.lazy_frame_backends._rectify_slice_dim(part, D)`

`kwcoco.util.lazy_frame_backends._validate_nonzero_data(file)`

Test to see if the image is all black.

May fail on all-black images

Example

```
>>> # xdoctest: +REQUIRES(module:osgeo)
>>> import kwimage
>>> gpath = kwimage.grab_test_image_fpath()
>>> file = LazyGDalFrameFile(gpath)
>>> _validate_nonzero_data(file)
```

`kwcoco.util.lazy_frame_backends._read_envi_header(file)`

USAGE: `hdr = _read_envi_header(file)`

Reads an ENVI “.hdr” file header and returns the parameters in a dictionary as strings. Header field names are treated as case insensitive and all keys in the dictionary are lowercase.

Modified from spectral/io/envi.py

References

<https://github.com/spectralpython/spectral>

kwcoco.util.util_archive

Module Contents

Classes

`Archive`

Abstraction over zipfile and tarfile

Functions

`unarchive_file(archive_fpath, output_dpath='.', verbose=1, overwrite=True)`

`class kwcoco.util.util_archive.Archive(fpath=None, mode='r', backend=None, file=None)`
Bases: `object`

Abstraction over zipfile and tarfile

Todo: see if we can use one of these other tools instead

SeeAlso: <https://github.com/RKrahl/archive-tools> <https://pypi.org/project/arlib/>

Example

```
>>> from os.path import join
>>> dpath = ub.ensure_app_cache_dir('ubelt', 'tests', 'archive')
>>> ub.delete(dpath)
>>> dpath = ub.ensure_app_cache_dir(dpath)
>>> import pathlib
>>> dpath = pathlib.Path(dpath)
>>> #
>>> #
>>> mode = 'w'
>>> self1 = Archive(str(dpath / 'demo.zip'), mode=mode)
>>> self2 = Archive(str(dpath / 'demo.tar.gz'), mode=mode)
>>> #
>>> open(dpath / 'data_1only.txt', 'w').write('bazbzzz')
>>> open(dpath / 'data_2only.txt', 'w').write('buzzz')
>>> open(dpath / 'data_both.txt', 'w').write('foobar')
>>> #
>>> self1.add(dpath / 'data_both.txt')
>>> self1.add(dpath / 'data_1only.txt')
```

(continues on next page)

(continued from previous page)

```
>>> #
>>> self2.add(dpath / 'data_both.txt')
>>> self2.add(dpath / 'data_2only.txt')
>>> #
>>> self1.close()
>>> self2.close()
>>> #
>>> self1 = Archive(str(dpath / 'demo.zip'), mode='r')
>>> self2 = Archive(str(dpath / 'demo.tar.gz'), mode='r')
>>> #
>>> extract_dpath = ub.ensuredir(str(dpath / 'extracted'))
>>> extracted1 = self1.extractall(extract_dpath)
>>> extracted2 = self2.extractall(extract_dpath)
>>> for fpath in extracted2:
>>>     print(open(fpath, 'r').read())
>>> for fpath in extracted1:
>>>     print(open(fpath, 'r').read())
```

classmethod _open(cls, fpath, mode)**__iter__**(self)**classmethod coerce**(cls, data)

Either open an archive file path or coerce an existing ZipFile or tarfile structure into this wrapper class

add(self, fpath, arcname=None)**close**(self)**__enter__**(self)**__exit__**(self, *args)**extractall**(self, output_dpath='.', verbose=1, overwrite=True)kwcoco.util.util_archive.**unarchive_file**(archive_fpath, output_dpath='.', verbose=1, overwrite=True)

kwcoco.util.util_delayed_poc

This module is ported from ndsampler, and will likely eventually move to kwimage and be refactored using symbolic
The classes in this file represent a tree of delayed operations.

Proof of concept for delayed chainable transforms in Python.

There are several optimizations that could be applied.

This is similar to GDAL's virtual raster table, but it works in memory and I think it is easier to chain operations.

SeeAlso: ../../dev/symbolic_delayed.py

Warning: As the name implies this is a proof of concept, and the actual implementation was hacked together too quickly. Serious refactoring will be necessary.

Concepts:

Each class should be a layer that adds a new transformation on top of underlying nested layers. Adding new layers should be quick, and there should always be the option to “finalize” a stack of layers, chaining the transforms / operations and then applying one final efficient transform at the end.

Todo:

- [] Need to handle masks / nodata values when warping. Might need to rely more on gdal / rasterio for this.
-

Conventions:

- dsize = (always in width / height), no channels are present
- shape for images is always (height, width, channels)
- channels are always the last dimension of each image, if no channel dim is specified, finalize will add it.
- **Videos must be the last process in the stack, and add a leading time dimension to the shape.** dsize is still width, height, but shape is now: (time, height, width, chan)

Example

```
>>> # Example demonstrating the motivating use case
>>> # We have multiple aligned frames for a video, but each of
>>> # those frames is in a different resolution. Furthermore,
>>> # each of the frames consists of channels in different resolutions.
>>> # Create raw channels in some "native" resolution for frame 1
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> f1_chan1 = DelayedIdentity.demo('astro', chan=0, dsize=(300, 300))
>>> f1_chan2 = DelayedIdentity.demo('astro', chan=1, dsize=(200, 200))
>>> f1_chan3 = DelayedIdentity.demo('astro', chan=2, dsize=(10, 10))
>>> # Create raw channels in some "native" resolution for frame 2
>>> f2_chan1 = DelayedIdentity.demo('carl', dsize=(64, 64), chan=0)
>>> f2_chan2 = DelayedIdentity.demo('carl', dsize=(260, 260), chan=1)
>>> f2_chan3 = DelayedIdentity.demo('carl', dsize=(10, 10), chan=2)
>>> #
>>> # Delayed warp each channel into its "image" space
>>> # Note: the images never actually enter this space we transform through it
>>> f1_dsize = np.array((3, 3))
>>> f2_dsize = np.array((2, 2))
>>> f1_img = DelayedChannelConcat([
>>>     f1_chan1.delayed_warp(kwimage.Affine.scale(f1_dsize / f1_chan1.dsize), dsize=f1_
>>>     dsize),
>>>     f1_chan2.delayed_warp(kwimage.Affine.scale(f1_dsize / f1_chan2.dsize), dsize=f1_
>>>     dsize),
>>>     f1_chan3.delayed_warp(kwimage.Affine.scale(f1_dsize / f1_chan3.dsize), dsize=f1_
>>>     dsize),
>>> ])
>>> f2_img = DelayedChannelConcat([
>>>     f2_chan1.delayed_warp(kwimage.Affine.scale(f2_dsize / f2_chan1.dsize), dsize=f2_
>>>     dsize),
>>>     f2_chan2.delayed_warp(kwimage.Affine.scale(f2_dsize / f2_chan2.dsize), dsize=f2_
>>>     dsize),
>>>     f2_chan3.delayed_warp(kwimage.Affine.scale(f2_dsize / f2_chan3.dsize), dsize=f2_
>>>     dsize),
```

(continues on next page)

(continued from previous page)

```
>>> ])
>>> # Combine frames into a video
>>> vid_dsize = np.array((280, 280))
>>> vid = DelayedFrameConcat([
>>>     f1_img.delayed_warp(kwimage.Affine.scale(vid_dsize / f1_img.dsize), dsize=vid_
>>> _dsize),
>>>     f2_img.delayed_warp(kwimage.Affine.scale(vid_dsize / f2_img.dsize), dsize=vid_
>>> _dsize),
>>> ])
>>> vid.nesting
>>> print('vid.nesting = {}'.format(ub.repr2(vid.__json__(), nl=-2)))
>>> final = vid.finalize(interpolation='nearest')
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(final[0], pnum=(1, 2, 1), fnum=1)
>>> kwplot.imshow(final[1], pnum=(1, 2, 2), fnum=1)
```

Example

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral')
>>> delayed = dset.delayed_load(1)
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> astro = DelayedLoad.demo('astro')
>>> print('MSI = ' + ub.repr2(delayed.__json__(), nl=-3, sort=0))
>>> print('ASTRO = ' + ub.repr2(astro.__json__(), nl=2, sort=0))
```

```
>>> subchan = delayed.take_channels('B1|B8')
>>> subcrop = subchan.delayed_crop((slice(10, 80), slice(30, 50)))
>>> #
>>> subcrop.nesting()
>>> subchan.nesting()
>>> subchan.finalize()
>>> subcrop.finalize()
>>> #
>>> msi_crop = delayed.delayed_crop((slice(10, 80), slice(30, 50)))
>>> msi_warp = msi_crop.delayed_warp(kwimage.Affine.scale(3), dsize='auto')
>>> subdata = msi_warp.take_channels('B11|B1')
>>> final = subdata.finalize()
>>> assert final.shape == (210, 60, 2)
```

Example

```

>>> # test case where an auxiliary image does not map entirely on the image.
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> import kwimage
>>> from os.path import join
>>> dpath = ub.ensure_app_cache_dir('kwcoco/tests/delayed_poc')
>>> chan1_fpath = join(dpath, 'chan1.tiff')
>>> chan2_fpath = join(dpath, 'chan2.tiff')
>>> chan3_fpath = join(dpath, 'chan2.tiff')
>>> chan1_raw = np.random.rand(128, 128, 1)
>>> chan2_raw = np.random.rand(64, 64, 1)
>>> chan3_raw = np.random.rand(256, 256, 1)
>>> kwimage.imwrite(chan1_fpath, chan1_raw)
>>> kwimage.imwrite(chan2_fpath, chan2_raw)
>>> kwimage.imwrite(chan3_fpath, chan3_raw)
>>> #
>>> c1 = channel_spec.FusedChannelSpec.coerce('c1')
>>> c2 = channel_spec.FusedChannelSpec.coerce('c2')
>>> c3 = channel_spec.FusedChannelSpec.coerce('c2')
>>> aux1 = DelayedLoad(chan1_fpath, dsize=chan1_raw.shape[0:2][::-1], channels=c1, num_
bands=1)
>>> aux2 = DelayedLoad(chan2_fpath, dsize=chan2_raw.shape[0:2][::-1], channels=c2, num_
bands=1)
>>> aux3 = DelayedLoad(chan3_fpath, dsize=chan3_raw.shape[0:2][::-1], channels=c3, num_
bands=1)
>>> #
>>> img_dsize = (128, 128)
>>> transform1 = kwimage.Affine.coerce(scale=0.5)
>>> transform2 = kwimage.Affine.coerce(theta=0.5, shearx=0.01, offset=(-20, -40))
>>> transform3 = kwimage.Affine.coerce(offset=(64, 0)) @ kwimage.Affine.random(rng=10)
>>> part1 = aux1.delayed_warp(np.eye(3), dsize=img_dsize)
>>> part2 = aux2.delayed_warp(transform2, dsize=img_dsize)
>>> part3 = aux3.delayed_warp(transform3, dsize=img_dsize)
>>> delayed = DelayedChannelConcat([part1, part2, part3])
>>> #
>>> delayed_crop = delayed.crop((slice(0, 10), slice(0, 10)))
>>> delayed_final = delayed_crop.finalize()
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> final = delayed.finalize()
>>> kwplot.imshow(final, fnum=1, pnum=(1, 2, 1))
>>> kwplot.imshow(delayed_final, fnum=1, pnum=(1, 2, 2))

```

```

comp = delayed_crop.components[2]
comp.sub_data.finalize()

data = np.array([[0]]).astype(np.float32) kwimage.warp_affine(data, np.eye(3), dsize=(32, 32)) kwim-
age.warp_affine(data, np.eye(3))

kwimage.warp_affine(data[0:0], np.eye(3))

transform = kwimage.Affine.coerce(scale=0.1) data = np.array([[0]]).astype(np.float32)

```

```

data = np.array([[]]).astype(np.float32) kwimage.warp_affine(data, transform, dsize=(0, 2), antialias=True)
data = np.array([[]]).astype(np.float32) kwimage.warp_affine(data, transform, dsize=(10, 10))
data = np.array([[0]]).astype(np.float32) kwimage.warp_affine(data, transform, dsize=(0, 2), antialias=True)
data = np.array([[0]]).astype(np.float32) kwimage.warp_affine(data, transform, dsize=(10, 10))
cv2.warpAffine( kwimage.grab_test_image(dsize=(1, 1)), kwimage.Affine.coerce(scale=0.1).matrix[0:2], dsize=(0,
    1),
)

```

Module Contents

Classes

<i>DelayedVisionOperation</i>	Base class for nodes in a tree of delayed computer-vision operations
<i>DelayedVideoOperation</i>	Base class for nodes in a tree of delayed computer-vision operations
<i>DelayedImageOperation</i>	Operations that pertain only to images
<i>DelayedIdentity</i>	Noop leaf that does nothing. Can be used to hold raw data.
<i>DelayedNans</i>	Constructs nan channels as needed
<i>DelayedLoad</i>	A load operation for a specific sub-region and sub-bands in a specified
<i>DelayedFrameConcat</i>	Represents multiple frames in a video
<i>DelayedChannelConcat</i>	Represents multiple channels in an image that could be concatenated
<i>DelayedWarp</i>	POC for chainable transforms
<i>DelayedCrop</i>	Represent a delayed crop operation

Functions

<i>dequantize(quant_data, quantization)</i>	Helper for dequantization
<i>_compute_leaf_subcrop(root_region_bounds,</i> <i>tf_leaf_to_root)</i>	Given a region in a "root" image and a transform between that "root" and
<i>_largest_shape(shapes)</i>	Finds maximum over all shapes
<i>_devcheck_corner()</i>	
<i>_auto_dsize(transform, sub_dsize)</i>	

Attributes

`xr`

`profile`

`kwcoco.util.util_delayed_poc.xr`

`kwcoco.util.util_delayed_poc.profile`

`class kwcoco.util.util_delayed_poc.DelayedVisionOperation`

Bases: `ubelt.NiceRepr`

Base class for nodes in a tree of delayed computer-vision operations

`__nice__(self)`

`abstract finalize(self, **kwargs)`

`abstract children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`_optimize_paths(self, **kwargs)`

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of heuristically optimized leaf repr wrt warps.

`__json__(self)`

`nesting(self)`

`warp(self, *args, **kwargs)`

alias for `delayed_warp`, might change to this API in the future

`crop(self, *args, **kwargs)`

alias for `delayed_crop`, might change to this API in the future

`class kwcoco.util.util_delayed_poc.DelayedVideoOperation`

Bases: `DelayedVisionOperation`

Base class for nodes in a tree of delayed computer-vision operations

`class kwcoco.util.util_delayed_poc.DelayedImageOperation`

Bases: `DelayedVisionOperation`

Operations that pertain only to images

`delayed_crop(self, region_slices)`

Create a new delayed image that performs a crop in the transformed “self” space.

Parameters `region_slices` (`Tuple[slice, slice]`) – y-slice and x-slice.

Note: Returns a heuristically “simplified” tree. In the current implementation there are only 3 operations, cat, warp, and crop. All cats go at the top, all crops go at the bottom, all warps are in the middle.

Returns lazy executed delayed transform

Return type `DelayedWarp`

Example

```
>>> dsize = (100, 100)
>>> tf2 = kwimage.Affine.affine(scale=3).matrix
>>> self = DelayedWarp(np.random.rand(33, 33), tf2, dsize)
>>> region_slices = (slice(5, 10), slice(1, 12))
>>> delayed_crop = self.delayed_crop(region_slices)
>>> print(ub.repr2(delayed_crop.nesting(), nl=-1, sort=0))
>>> delayed_crop.finalize()
```

Example

```
>>> chan1 = DelayedLoad.demo('astro')
>>> chan2 = DelayedLoad.demo('carl')
>>> warped1a = chan1.delayed_warp(kwimage.Affine.scale(1.2).matrix)
>>> warped2a = chan2.delayed_warp(kwimage.Affine.scale(1.5))
>>> warped1b = warped1a.delayed_warp(kwimage.Affine.scale(1.2).matrix)
>>> warped2b = warped2a.delayed_warp(kwimage.Affine.scale(1.5))
>>> #
>>> region_slices = (slice(97, 677), slice(5, 691))
>>> self = warped2b
>>> #
>>> crop1 = warped1b.delayed_crop(region_slices)
>>> crop2 = warped2b.delayed_crop(region_slices)
>>> print(ub.repr2(warped1b.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(warped2b.nesting(), nl=-1, sort=0))
>>> # Notice how the crop merges the two nesting layers
>>> # (via the heuristic optimize step)
>>> print(ub.repr2(crop1.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(crop2.nesting(), nl=-1, sort=0))
>>> frame1 = crop1.finalize(dsize=(500, 500))
>>> frame2 = crop2.finalize(dsize=(500, 500))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(frame1, pnum=(1, 2, 1), fnum=1)
>>> kwplot.imshow(frame2, pnum=(1, 2, 2), fnum=1)
```

delayed_warp(self, transform, dsize=None)

Delayed transform the underlying data.

Note: this deviates from kwimage warp functions because instead of “output_dims” (specified in c-style shape) we specify dsize (w, h).

Returns new delayed transform a chained transform

Return type *DelayedWarp*

abstract **take_channels(self, channels)**

```
class kwcoco.util.util_delayed_poc.DelayedIdentity(sub_data, dsize=None, channels=None,
                                                    quantization=None)
```

Bases: *DelayedImageOperation*

Noop leaf that does nothing. Can be used to hold raw data.

Typically used to just hold raw data.

```
DelayedIdentity.demo('astro', chan=0, dsize=(32, 32))
```

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> sub_data = np.random.rand(31, 37, 3)
>>> self = DelayedIdentity(sub_data)
>>> self = DelayedIdentity(sub_data, channels='L|a|b')
```

```
>>> # test with quantization
>>> rng = kwarrray.ensure_rng(32)
>>> sub_data_quant = (rng.rand(31, 37, 3) * 1000).astype(np.int16)
>>> sub_data_quant[0, 0] = -9999
>>> self = DelayedIdentity(sub_data_quant, channels='L|a|b', quantization={
>>>     'orig_min': 0.,
>>>     'orig_max': 1.,
>>>     'quant_min': 0,
>>>     'quant_max': 1000,
>>>     'nodata': -9999,
>>> })
>>> final1 = self.finalize(dequantize=True)
>>> final2 = self.finalize(dequantize=False)
>>> assert np.all(np.isnan(final1[0, 0]))
>>> scale = final2 / final1
>>> scales = scale[scale > 0]
>>> assert np.all(np.isclose(scales, 1000))
>>> # check that take channels works
>>> new_subdata = self.take_channels('a')
>>> sub_final1 = new_subdata.finalize(dequantize=True)
>>> sub_final2 = new_subdata.finalize(dequantize=False)
>>> assert sub_final1.dtype.kind == 'f'
>>> assert sub_final2.dtype.kind == 'i'
```

```
__hack_dont_optimize__ = True
```

```
classmethod demo(cls, key='astro', chan=None, dsize=None)
```

```
children(self)
```

Abstract method, which should generate all of the direct children of a node in the operation tree.

```
_optimize_paths(self, **kwargs)
```

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of hueristically optimized leaf repr wrt warps.

```
finalize(self, **kwargs)
```

```
take_channels(self, channels)
```

`kwcoco.util.util_delayed_poc.dequantize(quant_data, quantization)`
 Helper for dequantization

`class kwcoco.util.util_delayed_poc.DelayedNans(dsize=None, channels=None)`
 Bases: *DelayedImageOperation*
 Constructs nan channels as needed

Example

```
self = DelayedNans((10, 10), channel_spec.FusedChannelSpec.coerce('rgb')) region_slices = (slice(5, 10), slice(1, 12)) delayed = self.delayed_crop(region_slices)
```

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> dsize = (307, 311)
>>> c1 = DelayedNans(dsize=dsize, channels=channel_spec.FusedChannelSpec.coerce('foo
  ↵'))
>>> c2 = DelayedLoad.demo('astro', dsize=dsize).load_shape(True)
>>> cat = DelayedChannelConcat([c1, c2])
>>> warped_cat = cat.delayed_warp(kwimage.Affine.scale(1.07), dsize=(328, 332))
>>> warped_cat.finalize()
```

#>>> cropped = warped_cat.delayed_crop((slice(0, 300), slice(0, 100))) #>>> cropped.finalize().shape

property shape(*self*)

property num_bands(*self*)

property dsize(*self*)

property channels(*self*)

children(*self*)

Abstract method, which should generate all of the direct children of a node in the operation tree.

_optimize_paths(*self, **kwargs*)

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of heuristically optimized leaf repr wrt warps.

finalize(*self, **kwargs*)

delayed_crop(*self, region_slices*)

Create a new delayed image that performs a crop in the transformed “self” space.

Parameters *region_slices* (*Tuple[slice, slice]*) – y-slice and x-slice.

Note: Returns a heuristically “simplified” tree. In the current implementation there are only 3 operations, cat, warp, and crop. All cats go at the top, all crops go at the bottom, all warps are in the middle.

Returns lazy executed delayed transform

Return type *DelayedWarp*

Example

```
>>> dsize = (100, 100)
>>> tf2 = kwimage.Affine.affine(scale=3).matrix
>>> self = DelayedWarp(np.random.rand(33, 33), tf2, dsize)
>>> region_slices = (slice(5, 10), slice(1, 12))
>>> delayed_crop = self.delayed_crop(region_slices)
>>> print(ub.repr2(delayed_crop.nesting(), nl=-1, sort=0))
>>> delayed_crop.finalize()
```

Example

```
>>> chan1 = DelayedLoad.demo('astro')
>>> chan2 = DelayedLoad.demo('carl')
>>> warped1a = chan1.delayed_warp(kwimage.Affine.scale(1.2).matrix)
>>> warped2a = chan2.delayed_warp(kwimage.Affine.scale(1.5))
>>> warped1b = warped1a.delayed_warp(kwimage.Affine.scale(1.2).matrix)
>>> warped2b = warped2a.delayed_warp(kwimage.Affine.scale(1.5))
>>> #
>>> region_slices = (slice(97, 677), slice(5, 691))
>>> self = warped2b
>>> #
>>> crop1 = warped1b.delayed_crop(region_slices)
>>> crop2 = warped2b.delayed_crop(region_slices)
>>> print(ub.repr2(warped1b.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(warped2b.nesting(), nl=-1, sort=0))
>>> # Notice how the crop merges the two nesting layers
>>> # (via the heuristic optimize step)
>>> print(ub.repr2(crop1.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(crop2.nesting(), nl=-1, sort=0))
>>> frame1 = crop1.finalize(dsize=(500, 500))
>>> frame2 = crop2.finalize(dsize=(500, 500))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(frame1, pnum=(1, 2, 1), fnum=1)
>>> kwplot.imshow(frame2, pnum=(1, 2, 2), fnum=1)
```

delayed_warp(self, transform, dsize=None)

Delayed transform the underlying data.

Note: this deviates from kwimage warp functions because instead of “output_dims” (specified in c-style shape) we specify dsize (w, h).

Returns new delayed transform a chained transform

Return type *DelayedWarp*

```
class kwcoco.util.util_delayed_poc.DelayedLoad(fp, channels=None, dsize=None, num_bands=None,
                                                immediate_crop=None, immediate_chan_idxs=None,
                                                immediate_dsize=None, quantization=None)
```

Bases: *DelayedImageOperation*

A load operation for a specific sub-region and sub-bands in a specified image.

Note: This class contains support for fusing certain lazy operations into this layer, namely cropping, scaling, and channel selection.

For now these are named **immediates**

Example

```
>>> fpath = kwimage.grab_test_image_fpath()
>>> self = DelayedLoad(fpath)
>>> print('self = {!r}'.format(self))
>>> self.load_shape()
>>> print('self = {!r}'.format(self))
>>> self.finalize()
```

```
>>> f1_img = DelayedLoad.demo('astro', dsize=(300, 300))
>>> f2_img = DelayedLoad.demo('carl', dsize=(256, 320))
>>> print('f1_img = {!r}'.format(f1_img))
>>> print('f2_img = {!r}'.format(f2_img))
>>> print(f2_img.finalize().shape)
>>> print(f1_img.finalize().shape)
```

```
>>> fpath = kwimage.grab_test_image_fpath()
>>> channels = channel_spec.FusedChannelSpec.coerce('rgb')
>>> self = DelayedLoad(fpath, channels=channels)
```

Example

```
>>> # Test with quantization
>>> fpath = kwimage.grab_test_image_fpath()
>>> channels = channel_spec.FusedChannelSpec.coerce('rgb')
>>> self = DelayedLoad(fpath, channels=channels, quantization={
    >>>     'orig_min': 0.,
    >>>     'orig_max': 1.,
    >>>     'quant_min': 0,
    >>>     'quant_max': 256,
    >>>     'nodata': None,
    >>> })
>>> final1 = self.finalize(dequantize=False)
>>> final2 = self.finalize(dequantize=True)
>>> assert final1.dtype.kind == 'u'
>>> assert final2.dtype.kind == 'f'
>>> assert final2.max() <= 1
```

```
__hack_dont_optimize__ = True
classmethod demo(DelayedLoad, key='astro', dsize=None)
abstract classmethod coerce(cls, data)

children(self)
Abstract method, which should generate all of the direct children of a node in the operation tree.

nesting(self)

_optimize_paths(self, **kwargs)
Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of heuristically optimized leaf repr wrt warps.

load_shape(self, use_channel_heuristic=False)
_ensure_dsize(self)

property shape(self)
property num_bands(self)
property dsize(self)
property channels(self)
property fpath(self)
finalize(self, **kwargs)
```

Todo:

- [] Load from overviews if a scale will be necessary
-

Parameters `**kwargs` –

`nodata` [if specified this data item is treated as nodata, the] data is then converted to floats and the nodata value is replaced with nan.

`delayed_crop(self, region_slices)`

Parameters `region_slices` (`Tuple[slice, slice]`) – y-slice and x-slice.

Returns a new delayed load object with a fused crop operation

Return type `DelayedLoad`

Example

```
>>> # Test chained crop operations
>>> from kwcococo.util.util_delayed_poc import * # NOQA
>>> self = orig = DelayedLoad.demo('astro').load_shape()
>>> region_slices = slices1 = (slice(0, 90), slice(30, 60))
>>> self = crop1 = orig.delayed_crop(slices1)
>>> region_slices = slices2 = (slice(10, 21), slice(10, 22))
>>> self = crop2 = crop1.delayed_crop(slices2)
>>> region_slices = slices3 = (slice(3, 20), slice(5, 20))
>>> crop3 = crop2.delayed_crop(slices3)
```

(continues on next page)

(continued from previous page)

```
>>> # Spot check internals
>>> print('orig = {}'.format(ub.repr2(orig.__json__(), nl=2)))
>>> print('crop1 = {}'.format(ub.repr2(crop1.__json__(), nl=2)))
>>> print('crop2 = {}'.format(ub.repr2(crop2.__json__(), nl=2)))
>>> print('crop3 = {}'.format(ub.repr2(crop3.__json__(), nl=2)))
>>> # Test internals
>>> assert crop3._immediates['crop'][0].start == 13
>>> assert crop3._immediates['crop'][0].stop == 21
>>> # Test shapes work out correctly
>>> assert crop3.finalize().shape == (8, 7, 3)
>>> assert crop2.finalize().shape == (11, 12, 3)
>>> assert crop1.take_channels([1, 2]).finalize().shape == (90, 30, 2)
>>> assert orig.finalize().shape == (512, 512, 3)
```

Note:

This chart gives an intuition on how new absolute `slice` coords are computed **from existing** absolute coords and relative coords.

5	7	<- new
3	5	<- rel
<hr/>		
01234567		<- relative coordinates
<hr/>		
2	9	<- curr
<hr/>		
0123456789		<- absolute coordinates
<hr/>		

take_channels(self, channels)

This method returns a subset of the vision data with only the specified bands / channels.

Parameters `channels` (`List[int] | slice | channel_spec.FusedChannelSpec`) – List of integers indexes, a slice, or a channel spec, which is typically a pipe (|) delimited list of channel codes. See `kwcoco.ChannelSpec` for more details.

Returns a new delayed load with a fused take channel operation

Return type `DelayedLoad`

Note: The channel subset must exist here or it will raise an error. A better implementation (via symbolic) might be able to do better

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> import kwcoco
>>> self = DelayedLoad.demo('astro').load_shape()
>>> channels = [2, 0]
>>> new = self.take_channels(channels)
>>> new3 = new.take_channels([1, 0])
```

```
>>> final1 = self.finalize()
>>> final2 = new.finalize()
>>> final3 = new3.finalize()
>>> assert np.all(final1[..., 2] == final2[..., 0])
>>> assert np.all(final1[..., 0] == final2[..., 1])
>>> assert final2.shape[2] == 2
```

```
>>> assert np.all(final1[..., 2] == final3[..., 1])
>>> assert np.all(final1[..., 0] == final3[..., 0])
>>> assert final3.shape[2] == 2
```

class kwcoco.util.util_delayed_poc.DelayedFrameConcat(frames, dsize=None)
Bases: *DelayedVideoOperation*

Represents multiple frames in a video

Note:

```
Video[0]:
  Frame[0]:
    Chan[0]: (32) +-----+
    Chan[1]: (16) +-----+
    Chan[2]: ( 8) +----+
  Frame[1]:
    Chan[0]: (30) +-----+
    Chan[1]: (14) +-----+
    Chan[2]: ( 6) +----+
```

Todo:

- [] Support computing the transforms when none of the data is loaded
-

Example

```
>>> # Simpler case with fewer nesting levels
>>> rng = kwarray.ensure_rng(None)
>>> # Delayed warp each channel into its "image" space
>>> # Note: the images never enter the space we transform through
>>> f1_img = DelayedLoad.demo('astro', (300, 300))
>>> f2_img = DelayedLoad.demo('carl', (256, 256))
>>> # Combine frames into a video
>>> vid_dsize = np.array((100, 100))
>>> self = vid = DelayedFrameConcat([
>>>     f1_img.delayed_warp(kwimage.Affine.scale(vid_dsize / f1_img.dsize)),
>>>     f2_img.delayed_warp(kwimage.Affine.scale(vid_dsize / f2_img.dsize)),
>>> ], dsize=vid_dsize)
>>> print(ub.repr2(vid.nesting(), nl=-1, sort=0))
>>> final = vid.finalize(interpolation='nearest', dsize=(32, 32))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(final[0], pnum=(1, 2, 1), fnum=1)
>>> kwplot.imshow(final[1], pnum=(1, 2, 2), fnum=1)
>>> region_slices = (slice(0, 90), slice(30, 60))
```

`children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`property channels(self)`

`property shape(self)`

`finalize(self, **kwargs)`

Execute the final transform

`delayed_crop(self, region_slices)`

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> # Create raw channels in some "native" resolution for frame 1
>>> f1_chan1 = DelayedIdentity.demo('astro', chan=1, 0, dsize=(300, 300))
>>> f1_chan2 = DelayedIdentity.demo('astro', chan=2, dsize=(10, 10))
>>> # Create raw channels in some "native" resolution for frame 2
>>> f2_chan1 = DelayedIdentity.demo('carl', dsize=(64, 64), chan=(1, 0))
>>> f2_chan2 = DelayedIdentity.demo('carl', dsize=(10, 10), chan=2)
>>> #
>>> f1_dsize = np.array(f1_chan1.dsize)
>>> f2_dsize = np.array(f2_chan1.dsize)
>>> f1_img = DelayedChannelConcat([
>>>     f1_chan1.delayed_warp(kwimage.Affine.scale(f1_dsize / f1_chan1.dsize), -dsize=f1_dsize),
>>>     f1_chan2.delayed_warp(kwimage.Affine.scale(f1_dsize / f1_chan2.dsize), -dsize=f1_dsize),
>>> ])
>>> f2_img = DelayedChannelConcat([
```

(continues on next page)

(continued from previous page)

```

>>>     f2_chan1.delayed_warp(kwimage.Affine.scale(f2_dsize / f2_chan1.dsize),  

>>>     ~dszie=f2_dsize),  

>>>     f2_chan2.delayed_warp(kwimage.Affine.scale(f2_dsize / f2_chan2.dsize),  

>>>     ~dszie=f2_dsize),  

>>>   ])  

>>> vid_dsize = np.array((280, 280))  

>>> full_vid = DelayedFrameConcat([  

>>>     f1_img.delayed_warp(kwimage.Affine.scale(vid_dsize / f1_img.dsize),  

>>>     ~dszie=vid_dsize),  

>>>     f2_img.delayed_warp(kwimage.Affine.scale(vid_dsize / f2_img.dsize),  

>>>     ~dszie=vid_dsize),  

>>>   ])  

>>> region_slices = (slice(80, 200), slice(80, 200))  

>>> print(ub.repr2(full_vid.nesting(), nl=-1, sort=0))  

>>> crop_vid = full_vid.delayed_crop(region_slices)  

>>> final_full = full_vid.finalize(interpolation='nearest')  

>>> final_crop = crop_vid.finalize(interpolation='nearest')  

>>> import pytest  

>>> with pytest.raises(ValueError):  

>>>     # should not be able to crop a crop yet  

>>>     crop_vid.delayed_crop(region_slices)  

>>> # xdoctest: +REQUIRES(--show)  

>>> import kwplot  

>>> kwplot.autompl()  

>>> kwplot.imshow(final_full[0], pnum=(2, 2, 1), fnum=1)  

>>> kwplot.imshow(final_full[1], pnum=(2, 2, 2), fnum=1)  

>>> kwplot.imshow(final_crop[0], pnum=(2, 2, 3), fnum=1)  

>>> kwplot.imshow(final_crop[1], pnum=(2, 2, 4), fnum=1)

```

delayed_warp(self, transform, dsize=None)

Delayed transform the underlyng data.

Note: this deviates from kwimage warp functions because instead of “output_dims” (specified in c-style shape) we specify dsize (w, h).

Returns new delayed transform a chained transform

Return type *DelayedWarp*

```
class kwcoco.util.util_delayed_poc.DelayedChannelConcat(components, dsize=None)
Bases: DelayedImageOperation
```

Represents multiple channels in an image that could be concatenated

Variables **components** (*List[DelayedWarp]*) – a list of stackable channels. Each component may be comprised of multiple channels.

Todo:

- [] can this be generalized into a delayed concat?
- [] can all concats be delayed until the very end?

Example

```
>>> comp1 = DelayedWarp(np.random.rand(11, 7))
>>> comp2 = DelayedWarp(np.random.rand(11, 7, 3))
>>> comp3 = DelayedWarp(
>>>     np.random.rand(3, 5, 2),
>>>     transform=kwimage.Affine.affine(scale=(7/5, 11/3)).matrix,
>>>     dszie=(7, 11)
>>> )
>>> components = [comp1, comp2, comp3]
>>> chans = DelayedChannelConcat(components)
>>> final = chans.finalize()
>>> assert final.shape == chans.shape
>>> assert final.shape == (11, 7, 6)
```

```
>>> # We should be able to nest DelayedChannelConcat inside virutal images
>>> frame1 = DelayedWarp(
>>>     chans, transform=kwimage.Affine.affine(scale=2.2).matrix,
>>>     dszie=(20, 26))
>>> frame2 = DelayedWarp(
>>>     np.random.rand(3, 3, 6), dszie=(20, 26))
>>> frame3 = DelayedWarp(
>>>     np.random.rand(3, 3, 6), dszie=(20, 26))
```

```
>>> print(ub.repr2(frame1.nesting(), nl=-1, sort=False))
>>> frame1.finalize()
>>> vid = DelayedFrameConcat([frame1, frame2, frame3])
>>> print(ub.repr2(vid.nesting(), nl=-1, sort=False))
```

`children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`classmethod random(cls, num_parts=3, rng=None)`

Example

```
>>> self = DelayedChannelConcat.random()
>>> print('self = {!r}'.format(self))
>>> print(ub.repr2(self.nesting(), nl=-1, sort=0))
```

`property channels(self)`

`property shape(self)`

`finalize(self, **kwargs)`

Execute the final transform

`delayed_warp(self, transform, dszie=None)`

Delayed transform the underlying data.

Note: this deviates from kwimage warp functions because instead of “output_dims” (specified in c-style shape) we specify dszie (w, h).

Returns new delayed transform a chained transform

Return type *DelayedWarp*

take_channels(self, channels)

This method returns a subset of the vision data with only the specified bands / channels.

Parameters **channels** (*List[int]* | *slice* | *channel_spec.FusedChannelSpec*) – List of integers indexes, a slice, or a channel spec, which is typically a pipe (|) delimited list of channel codes. See `kwcoco.ChannelSpec` for more details.

Returns a delayed vision operation that only operates on the following channels.

Return type *DelayedVisionOperation*

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral')
>>> self = delayed = dset.delayed_load(1)
>>> channels = 'B11|B8|B1|B10'
>>> new = self.take_channels(channels)
```

Example

```
>>> # Complex case
>>> import kwcoco
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral')
>>> delayed = dset.delayed_load(1)
>>> astro = DelayedLoad.demo('astro').load_shape(use_channel_heuristic=True)
>>> aligned = astro.warp(kwimage.Affine.scale(600 / 512), dszie='auto')
>>> self = combo = DelayedChannelConcat(delayed.components + [aligned])
>>> channels = 'B1|r|B8|g'
>>> new = self.take_channels(channels)
>>> new_cropped = new.crop((slice(10, 200), slice(12, 350)))
>>> datas = new_cropped.finalize()
>>> vizable = kwimage.normalize_intensity(datas, axis=2)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> stacked = kwimage.stack_images(vizable.transpose(2, 0, 1))
>>> kwplot.imshow(stacked)
```

CommandLine

```
xdoc test -m /home/joncrall/code/kwcoco/kwcoco/util/util_delayed_poc.py
  ↳DelayedChannelConcat.take_channels:2 --profile
```

Example

```
>>> # Test case where requested channel does not exist
>>> import kwcoco
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral', use_cache=1,
  ↳verbose=100)
>>> self = dset.delayed_load(1)
>>> channels = 'B1|foobar|bazbiz|B8'
>>> new = self.take_channels(channels)
>>> new_cropped = new.crop((slice(10, 200), slice(12, 350)))
>>> fused = new_cropped.finalize()
>>> assert fused.shape == (190, 338, 4)
>>> assert np.all(np.isnan(fused[..., 1:3]))
>>> assert not np.any(np.isnan(fused[..., 0]))
>>> assert not np.any(np.isnan(fused[..., 3]))
```

class kwcoco.util.util_delayed_poc.DelayedWarp(*sub_data*, *transform*=None, *dsize*=None)

Bases: *DelayedImageOperation*

POC for chainable transforms

Note: “sub” is used to refer to the underlying data in its native coordinates and resolution.

“self” is used to refer to the data in the transformed coordinates that are exposed by this class.

Variables

- **sub_data** (*DelayedWarp* / *ArrayLike*) – array-like image data at a native resolution
- **transform** (*Transform*) – transforms data from native “sub”-image-space to “self”-image-space.

Example

```
>>> dsize = (12, 12)
>>> tf1 = np.array([[2, 0, 0], [0, 2, 0], [0, 0, 1]])
>>> tf2 = np.array([[3, 0, 0], [0, 3, 0], [0, 0, 1]])
>>> tf3 = np.array([[4, 0, 0], [0, 4, 0], [0, 0, 1]])
>>> band1 = DelayedWarp(np.random.rand(6, 6), tf1, dsize)
>>> band2 = DelayedWarp(np.random.rand(4, 4), tf2, dsize)
>>> band3 = DelayedWarp(np.random.rand(3, 3), tf3, dsize)
>>> #
>>> # Execute a crop in a one-level transformed space
>>> region_slices = (slice(5, 10), slice(0, 12))
>>> delayed_crop = band2.delayed_crop(region_slices)
```

(continues on next page)

(continued from previous page)

```
>>> final_crop = delayed_crop.finalize()
>>> #
>>> # Execute a crop in a nested transformed space
>>> tf4 = np.array([[1.5, 0, 0], [0, 1.5, 0], [0, 0, 1]])
>>> chained = DelayedWarp(band2, tf4, (18, 18))
>>> delayed_crop = chained.delayed_crop(region_slices)
>>> final_crop = delayed_crop.finalize()
>>> #
>>> tf4 = np.array([[.5, 0, 0], [0, .5, 0], [0, 0, 1]])
>>> chained = DelayedWarp(band2, tf4, (6, 6))
>>> delayed_crop = chained.delayed_crop(region_slices)
>>> final_crop = delayed_crop.finalize()
>>> #
>>> region_slices = (slice(1, 5), slice(2, 4))
>>> delayed_crop = chained.delayed_crop(region_slices)
>>> final_crop = delayed_crop.finalize()
```

Example

```
>>> dsizes = (17, 12)
>>> tf = np.array([[5.2, 0, 1.1], [0, 3.1, 2.2], [0, 0, 1]])
>>> self = DelayedWarp(np.random.rand(3, 5, 13), tf, dsizes=dsizes)
>>> self.finalize().shape
```

`classmethod random(cls, nesting=(2, 5), rng=None)`

Example

```
>>> self = DelayedWarp.random(nesting=(4, 7))
>>> print('self = {!r}'.format(self))
>>> print(ub.repr2(self.nesting(), nl=-1, sort=0))
```

`property channels(self)`

`children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`property dsizes(self)`

`property num_bands(self)`

`property shape(self)`

`_optimize_paths(self, **kwargs)`

Example

```
>>> self = DelayedWarp.random()
>>> leafs = list(self._optimize_paths())
>>> print('leafs = {!r}'.format(leafs))
```

finalize(*self*, *transform*=*None*, *dsize*=*None*, *interpolation*='linear', ***kwargs*)

Execute the final transform

Can pass a parent transform to augment this underlying transform.

Parameters

- **transform** (*Transform*) – an additional transform to perform
- **dsize** (*Tuple[int, int]*) – overrides destination canvas size

Example

```
>>> tf = np.array([[0.9, 0, 3.9], [0, 1.1, -.5], [0, 0, 1]])
>>> raw = kwimage.grab_test_image(dsize=(54, 65))
>>> raw = kwimage.ensure_float01(raw)
>>> # Test nested finalize
>>> layer1 = raw
>>> num = 10
>>> for _ in range(num):
...     layer1 = DelayedWarp(layer1, tf, dsize='auto')
>>> final1 = layer1.finalize()
>>> # Test non-nested finalize
>>> layer2 = list(layer1._optimize_paths())[0]
>>> final2 = layer2.finalize()
>>> #
>>> print(ub.repr2(layer1.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(layer2.nesting(), nl=-1, sort=0))
>>> print('final1 = {!r}'.format(final1))
>>> print('final2 = {!r}'.format(final2))
>>> print('final1.shape = {!r}'.format(final1.shape))
>>> print('final2.shape = {!r}'.format(final2.shape))
>>> assert np.allclose(final1, final2)
>>> #
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> kwplot.imshow(raw, pnum=(1, 3, 1), fnum=1)
>>> kwplot.imshow(final1, pnum=(1, 3, 2), fnum=1)
>>> kwplot.imshow(final2, pnum=(1, 3, 3), fnum=1)
>>> kwplot.show_if_requested()
```

Example

```
>>> # Test aliasing
>>> s = DelayedIdentity.demo()
>>> s = DelayedIdentity.demo('checkerboard')
>>> a = s.delayed_warp(kwimage.Affine.scale(0.05), dsize='auto')
>>> b = s.delayed_warp(kwimage.Affine.scale(3), dsize='auto')
```

```
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> # It looks like downsampling linear and area is the same
>>> # Does warpAffine have no alias handling?
>>> pnum_ = kwplot.PlotNums(nRows=2, nCols=4)
>>> kwplot.imshow(a.finalize(interpolation='area'), pnum=pnum_, title=
...>>> 'warpAffine area')
>>> kwplot.imshow(a.finalize(interpolation='linear'), pnum=pnum_, title=
...>>> 'warpAffine linear')
>>> kwplot.imshow(a.finalize(interpolation='nearest'), pnum=pnum_, title=
...>>> 'warpAffine nearest')
>>> kwplot.imshow(a.finalize(interpolation='nearest', antialias=False),
...>>> pnum=pnum_, title='warpAffine nearest AA=0')
>>> kwplot.imshow(kwimage.imresize(s.finalize(), dsize=a.dsize, interpolation=
...>>> 'area'), pnum=pnum_, title='resize area')
>>> kwplot.imshow(kwimage.imresize(s.finalize(), dsize=a.dsize, interpolation=
...>>> 'linear'), pnum=pnum_, title='resize linear')
>>> kwplot.imshow(kwimage.imresize(s.finalize(), dsize=a.dsize, interpolation=
...>>> 'nearest'), pnum=pnum_, title='resize nearest')
>>> kwplot.imshow(kwimage.imresize(s.finalize(), dsize=a.dsize, interpolation=
...>>> 'cubic'), pnum=pnum_, title='resize cubic')
```

`take_channels(self, channels)`

`class kwcoco.util.util_delayed_poc.DelayedCrop(sub_data, sub_slices)`
Bases: `DelayedImageOperation`

Represent a delayed crop operation

Example

```
>>> sub_data = DelayedLoad.demo()
>>> sub_slices = (slice(5, 10), slice(1, 12))
>>> self = DelayedCrop(sub_data, sub_slices)
>>> print(ub.repr2(self.nesting(), nl=-1, sort=0))
>>> final = self.finalize()
>>> print('final.shape = {!r}'.format(final.shape))
```

Example

```
>>> sub_data = DelayedLoad.demo()
>>> sub_slices = (slice(5, 10), slice(1, 12))
>>> crop1 = DelayedCrop(sub_data, sub_slices)
>>> import pytest
>>> # Should only error while heuristics are in use.
>>> with pytest.raises(ValueError):
>>>     crop2 = DelayedCrop(crop1, sub_slices)
```

`__hack_dont_optimize__ = True`

`property channels(self)`

`children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`finalize(self, **kwargs)`

`abstract _optimize_paths(self, **kwargs)`

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of heuristically optimized leaf repr wrt warps.

`kwcoco.util.util_delayed_poc._compute_leaf_subcrop(root_region_bounds, tf_leaf_to_root)`

Given a region in a “root” image and a transform between that “root” and some “leaf” image, compute the appropriate quantized region in the “leaf” image and the adjusted transformation between that root and leaf.

Example

```
>>> region_slices = (slice(33, 100), slice(22, 62))
>>> region_shape = (100, 100, 1)
>>> root_region_box = kwimage.Boxes.from_slice(region_slices, shape=region_shape)
>>> root_region_bounds = root_region_box.to_polygons()[0]
>>> tf_leaf_to_root = kwimage.Affine.affine(scale=7).matrix
>>> slices, tf_new = _compute_leaf_subcrop(root_region_bounds, tf_leaf_to_root)
>>> print('tf_new =\n{}'.format(tf_new))
>>> print('slices = {}'.format(slices))
```

`kwcoco.util.util_delayed_poc._largest_shape(shapes)`

Finds maximum over all shapes

Example

```
>>> shapes = [
>>>     (10, 20), None, (None, 30), (40, 50, 60, None), (100, )
>>> ]
>>> largest = _largest_shape(shapes)
>>> print('largest = {}'.format(largest))
>>> assert largest == (100, 50, 60, None)
```

`kwcoco.util.util_delayed_poc._devcheck_corner()`

`kwcoco.util.util_delayed_poc._auto_dsize(transform, sub_dsize)`

kwcoco.util.util_futures

Deprecated and functionality moved to ubelt

kwcoco.util.util_json

Module Contents

Functions

<code>ensure_json_serializable(dict_, normalize_containers=False, verbose=0)</code>	normal-	Attempt to convert common types (e.g. numpy) into something json compliant
<code>find_json_unserializable(data, quickcheck=False)</code>		Recurse through json datastructure and find any component that
<code>indexable_allclose(dct1, dct2, return_info=False)</code>		Walks through two nested data structures and ensures that everything is

Attributes

IndexableWalker

kwcoco.util.util_json.IndexableWalker

`kwcoco.util.util_json.ensure_json_serializable(dict_, normalize_containers=False, verbose=0)`

Attempt to convert common types (e.g. numpy) into something json compliant

Convert numpy and tuples into lists

Parameters `normalize_containers (bool, default=False)` – if True, normalizes dict containers to be standard python structures.

Example

```
>>> data = ub.ddict(lambda: int)
>>> data['foo'] = ub.ddict(lambda: int)
>>> data['bar'] = np.array([1, 2, 3])
>>> data['foo']['a'] = 1
>>> data['foo']['b'] = (1, np.array([1, 2, 3]), {3: np.int32(3), 4: np.float16(1.0)})
>>>
>>> dict_ = data
>>> print(ub.repr2(data, nl=-1))
>>> assert list(find_json_unserializable(data))
>>> result = ensure_json_serializable(data, normalize_containers=True)
>>> print(ub.repr2(result, nl=-1))
>>> assert not list(find_json_unserializable(result))
>>> assert type(result) is dict
```

kwcoco.util.util_json.find_json_unserializable(data, quickcheck=False)

Recurse through json datastructure and find any component that causes a serialization error. Record the location of these errors in the datastructure as we recurse through the call tree.

Parameters

- **data** (*object*) – data that should be json serializable
- **quickcheck** (*bool*) – if True, check the entire datastructure assuming its ok before doing the python-based recursive logic.

Returns

list of “bad part” dictionaries containing items ‘value’ - the value that caused the serialization error ‘loc’ - which contains a list of key/indexes that can be used

to lookup the location of the unserializable value. If the “loc” is a list, then it indicates a rare case where a key in a dictionary is causing the serialization error.

Return type List[Dict]

Example

```
>>> from kwcoco.util.util_json import * # NOQA
>>> part = ub.ddict(lambda: int)
>>> part['foo'] = ub.ddict(lambda: int)
>>> part['bar'] = np.array([1, 2, 3])
>>> part['foo']['a'] = 1
>>> # Create a dictionary with two unserializable parts
>>> data = [1, 2, {'nest1': [2, part]}, {frozenset({'badkey'}): 3, 2: 4}]
>>> parts = list(find_json_unserializable(data))
>>> print('parts = {}'.format(ub.repr2(parts, nl=1)))
>>> # Check expected structure of bad parts
>>> assert len(parts) == 2
>>> part = parts[1]
>>> assert list(part['loc']) == [2, 'nest1', 1, 'bar']
>>> # We can use the "loc" to find the bad value
>>> for part in parts:
>>>     # "loc" is a list of directions containing which keys/indexes
>>>     # to traverse at each descent into the data structure.
>>>     directions = part['loc']
>>>     curr = data
>>>     special_flag = False
>>>     for key in directions:
>>>         if isinstance(key, list):
>>>             # special case for bad keys
>>>             special_flag = True
>>>             break
>>>         else:
>>>             # normal case for bad values
>>>             curr = curr[key]
>>>     if special_flag:
>>>         assert part['data'] in curr.keys()
>>>         assert part['data'] is key[1]
>>>     else:
>>>         assert part['data'] is curr
```

kwcoco.util.util_json.indexable_allclose(*dct1, dct2, return_info=False*)

Walks through two nested data structures and ensures that everything is roughly the same.

Parameters

- **dct1** – a nested indexable item
- **dct2** – a nested indexable item

Example

```
>>> from kwcoco.util.util_json import indexable_allclose
>>> dct1 = {
>>>     'foo': [1.222222, 1.333],
>>>     'bar': 1,
>>>     'baz': [],
>>> }
>>> dct2 = {
>>>     'foo': [1.22222, 1.333],
>>>     'bar': 1,
>>>     'baz': [],
>>> }
>>> assert indexable_allclose(dct1, dct2)
```

kwcoco.util.util_monkey**Module Contents****Classes*****SupressPrint***

Temporarily replace the print function in a module with a noop

class kwcoco.util.util_monkey.*SupressPrint*(mods*, ***kw*)**

Bases: *object*

Temporarily replace the print function in a module with a noop

Parameters

- ***mods** – the modules to disable print in
- ****kw** – only accepts “enabled” enabled (bool, default=True): enables or disables this context

__enter__(*self*)**__exit__(*self, a, b, c*)**

kwcoco.util.util_sklearn

Extensions to sklearn constructs

Module Contents

Classes

<code>StratifiedGroupKFold</code>	Stratified K-Folds cross-validator with Grouping
<p>class kwcoco.util.util_sklearn.StratifiedGroupKFold(<i>n_splits</i>=3, <i>shuffle</i>=False, <i>random_state</i>=None)</p> <p>Bases: sklearn.model_selection._split._BaseKFold</p> <p>Stratified K-Folds cross-validator with Grouping</p> <p>Provides train/test indices to split data in train/test sets.</p> <p>This cross-validation object is a variation of GroupKFold that returns stratified folds. The folds are made by preserving the percentage of samples for each class.</p> <p>Read more in the User Guide.</p> <p>Parameters <code>n_splits</code> (int, default=3) – Number of folds. Must be at least 2.</p> <p><code>_make_test_folds</code>(self, X, y=None, groups=None)</p> <p>Parameters</p> <ul style="list-style-type: none"> • <code>X</code> (ndarray) – data • <code>y</code> (ndarray) – labels • <code>groups</code> (ndarray) – groupids for items. Items with the same groupid must be placed in the same group. <p>Returns test_folds</p> <p>Return type list</p>	

Example

```
>>> import kwarray
>>> rng = kwarray.ensure_rng(0)
>>> groups = [1, 1, 3, 4, 2, 2, 7, 8, 8]
>>> y      = [1, 1, 1, 1, 2, 2, 2, 3, 3]
>>> X = np.empty((len(y), 0))
>>> self = StratifiedGroupKFold(random_state=rng, shuffle=True)
>>> skf_list = list(self.split(X=X, y=y, groups=groups))
...
>>> import ubelt as ub
>>> print(ub.repr2(skf_list, nl=1, with_dtype=False))
[
```

(continues on next page)

(continued from previous page)

```
(np.array([0, 1, 3, 4, 5, 6, 7, 8]), np.array([2])),  
]
```

_iter_test_masks(self, X, y=None, groups=None)

Generates boolean masks corresponding to test sets.

By default, delegates to `_iter_test_indices(X, y, groups)`

split(self, X, y, groups=None)

Generate indices to split data into training and test set.

kwCOCO.util.util_truncate

Truncate utility based on python-slugify.

<https://pypi.org/project/python-slugify/1.2.2/>

Module Contents**Functions**

`_trunc_op(string, max_length, trunc_loc)`

Example

```
smart_truncate(string, max_length=0, separator=' ', Truncate a string.  
trunc_loc=0.5)
```

`kwCOCO.util.util_truncate._trunc_op(string, max_length, trunc_loc)`

Example

```
>>> from kwCOCO.util.util_truncate import _trunc_op  
>>> string =  
< 'DarnOvercastSculptureTipperBlazerConcaveUnsuitedDerangedHexagonRockband'  
>>> max_length = 16  
>>> trunc_loc = 0.5  
>>> _trunc_op(string, max_length, trunc_loc)
```

```
>>> from kwCOCO.util.util_truncate import _trunc_op  
>>> max_length = 16  
>>> string = 'a' * 16  
>>> _trunc_op(string, max_length, trunc_loc)
```

```
>>> string = 'a' * 17  
>>> _trunc_op(string, max_length, trunc_loc)
```

`kwCOCO.util.util_truncate.smart_truncate(string, max_length=0, separator=' ', trunc_loc=0.5)`
Truncate a string. :param string (str): string for modification :param max_length (int): output string length

:param word_boundary (bool): :param save_order (bool): if True then word order of output string is like input string :param separator (str): separator between words :param trunc_loc (float): fraction of location where to remove the text :return:

Package Contents

Classes

<i>DictLike</i>	An inherited class must specify the <code>getitem</code> , <code>setitem</code> , and
<i>ContainerElements</i>	Types that contain other types
<i>Element</i>	A dictionary used to define an element of a JSON Schema.
<i>QuantifierElements</i>	Quantifier types
<i>ScalarElements</i>	Single-valued elements
<i>SchemaElements</i>	Functional interface into defining jsonschema structures.
<i>LazyGDalFrameFile</i>	
<i>LazyRasterIOFrameFile</i>	fpath = '/home/joncrall/.cache/kwcoco/demo/large_hyperspectral/big_img_1.tif'
<i>LazySpectralFrameFile</i>	Potentially faster than GDAL for HDR formats.
<i>Archive</i>	Abstraction over zipfile and tarfile
<i>DelayedChannelConcat</i>	Represents multiple channels in an image that could be concatenated
<i>DelayedCrop</i>	Represent a delayed crop operation
<i>DelayedFrameConcat</i>	Represents multiple frames in a video
<i>DelayedIdentity</i>	Noop leaf that does nothing. Can be used to hold raw data.
<i>DelayedImageOperation</i>	Operations that pertain only to images
<i>DelayedLoad</i>	A load operation for a specific sub-region and sub-bands in a specified
<i>DelayedNans</i>	Constructs nan channels as needed
<i>DelayedVideoOperation</i>	Base class for nodes in a tree of delayed computer-vision operations
<i>DelayedVisionOperation</i>	Base class for nodes in a tree of delayed computer-vision operations
<i>DelayedWarp</i>	POC for chainable transforms
<i>SupressPrint</i>	Temporarily replace the print function in a module with a noop
<i>StratifiedGroupKFold</i>	Stratified K-Folds cross-validator with Grouping

Functions

<code>unarchive_file(archive_fpath, output_dpath='.', verbose=1, overwrite=True)</code>		
<code>ensure_json_serializable(dict_, normalize_containers=False, verbose=0)</code>	normal-	Attempt to convert common types (e.g. numpy) into something json compliant
<code>find_json_unserializable(data, quickcheck=False)</code>		Recurse through json datastructure and find any component that

continues on next page

Table 91 – continued from previous page

<code>indexable_allclose(dct1, dct2, return_info=False)</code>	Walks through two nested data structures and ensures that everything is
<code>smart_truncate(string, max_length=0, separator=' ', trunc_loc=0.5)</code>	Truncate a string.

Attributes

`ALLOF`

`ANY`

`ANYOF`

`ARRAY`

`BOOLEAN`

`INTEGER`

`NOT`

`NULL`

`NUMBER`

`OBJECT`

`ONEOF`

`STRING`

`elem`

`IndexableWalker`

`class kwcoc.util.DictLike`

Bases: `ubelt.NiceRepr`

An inherited class must specify the `getitem`, `setitem`, and `keys` methods.

A class is dictionary like if it has:

`__iter__`, `__len__`, `__contains__`, `__getitem__`, `items`, `keys`, `values`, `get`,

and if it should be writable it should have: `__delitem__`, `__setitem__`, `update`,

And perhaps: `copy`,

`__iter__`, `__len__`, `__contains__`, `__getitem__`, `items`, `keys`, `values`, `get`,

and if it should be writable it should have: `__delitem__`, `__setitem__`, `update`,

And perhaps: `copy`,

```

asdict
abstract getitem(self, key)
abstract setitem(self, key, value)
abstract delitem(self, key)
abstract keys(self)
__len__(self)
__iter__(self)
__contains__(self, key)
__delitem__(self, key)
__getitem__(self, key)
__setitem__(self, key, value)
items(self)
values(self)
copy(self)
to_dict(self)
update(self, other)
get(self, key, default=None)

kwcoco.util.ALLOF
kwcoco.util.ANY
kwcoco.util.ANYOF
kwcoco.util.ARRAY
kwcoco.util.BOOLEAN

class kwcoco.util.ContainerElements
    Types that contain other types

```

Example

```

>>> from kwcoco.util.jsonschema_elements import * # NOQA
>>> print(elem.ARRAY().validate())
>>> print(elem.OBJECT().validate())
>>> print(elem.OBJECT().validate())
{'type': 'array', 'items': []}
{'type': 'object', 'properties': {}}
{'type': 'object', 'properties': {}}

```

ARRAY(*self*, *TYPE={}*, ***kw*)
<https://json-schema.org/understanding-json-schema/reference/array.html>

Example

```
>>> from kwcoc.util.jsonschema_elements import * # NOQA
>>> ARRAY(numItems=3)
>>> schema = ARRAY(minItems=3)
>>> schema.validate()
{'type': 'array', 'items': {}, 'minItems': 3}
```

OBJECT(*self*, PROPERTIES={}, ***kw*)
<https://json-schema.org/understanding-json-schema/reference/object.html>

Example

```
>>> import jsonschema
>>> schema = elem.OBJECT()
>>> jsonschema.validate({}, schema)
>>> #
>>> import jsonschema
>>> schema = elem.OBJECT({
>>>     'key1': elem.ANY(),
>>>     'key2': elem.ANY(),
>>> }, required=['key1'])
>>> jsonschema.validate({'key1': None}, schema)
>>> #
>>> import jsonschema
>>> schema = elem.OBJECT({
>>>     'key1': elem.OBJECT({'arr': elem.ARRAY()}),
>>>     'key2': elem.ANY(),
>>> }, required=['key1'], title='a title')
>>> schema.validate()
>>> print('schema = {}'.format(ub.repr2(schema, sort=1, nl=-1)))
>>> jsonschema.validate({'key1': {'arr': []}}, schema)
schema = {
    'properties': {
        'key1': {
            'properties': {
                'arr': {'items': {}, 'type': 'array'}
            },
            'type': 'object'
        },
        'key2': {}
    },
    'required': ['key1'],
    'title': 'a title',
    'type': 'object'
}
```

class kwcoc.util.Element(*base*, options={}, _magic=None)
Bases: dict

A dictionary used to define an element of a JSON Schema.

The exact keys/values for the element will depend on the type of element being described. The *SchemaElements* defines exactly what these are for the core elements. (e.g. OBJECT, INTEGER, NULL, ARRAY, ANYOF)

Example

```
>>> from kwcoco.coco_schema import * # NOQA
>>> self = Element(base={'type': 'demo'}, options={'opt1', 'opt2'})
>>> new = self(opt1=3)
>>> print('self = {}'.format(ub.repr2(self, nl=1, sort=1)))
>>> print('new = {}'.format(ub.repr2(new, nl=1, sort=1)))
>>> print('new2 = {}'.format(ub.repr2(new(), nl=1, sort=1)))
>>> print('new3 = {}'.format(ub.repr2(new(title='myvar'), nl=1, sort=1)))
>>> print('new4 = {}'.format(ub.repr2(new(title='myvar')(examples=['']), nl=1, sort=1)))
>>> print('new5 = {}'.format(ub.repr2(new(badattr=True), nl=1, sort=1)))
self = {
    'type': 'demo',
}
new = {
    'opt1': 3,
    'type': 'demo',
}
new2 = {
    'opt1': 3,
    'type': 'demo',
}
new3 = {
    'opt1': 3,
    'title': 'myvar',
    'type': 'demo',
}
new4 = {
    'examples': [],
    'opt1': 3,
    'title': 'myvar',
    'type': 'demo',
}
new5 = {
    'opt1': 3,
    'type': 'demo',
}
```

__generics__

__call__(*self*, **args*, ***kw*)

validate(*self*, *instance*=*ub.NoParam*)

If *instance* is given, validates that that dictionary conforms to this schema. Otherwise validates that this is a valid schema element.

Parameters **instance** (*dict*) – a dictionary to validate

__or__(*self*, *other*)

Syntax for making an anyOf relationship

Example

```
>>> from kwCoco.util.jsonschema_elements import * # NOQA
>>> obj1 = OBJECT(dict(opt1=NUMBER()))
>>> obj2 = OBJECT(dict(opt2=STRING()))
>>> obj3 = OBJECT(dict(opt3=ANY()))
>>> any_v1 = obj1 | obj2
>>> any_v2 = ANYOF(obj1, obj2)
>>> assert any_v1 == any_v2
>>> any_v3 = any_v1 | obj3
>>> any_v4 = ANYOF(obj1, obj2, obj3)
>>> assert any_v3 == any_v4
```

kwCoco.util.INTEGER

kwCoco.util.NOT

kwCoco.util.NULL

kwCoco.util.NUMBER

kwCoco.util.OBJECT

kwCoco.util.ONEOF

class kwCoco.util.QuantifierElements

Bases: object

Quantifier types

<https://json-schema.org/understanding-json-schema/reference/combining.html#allof>

Example

```
>>> from kwCoco.util.jsonschema_elements import * # NOQA
>>> elem.ANYOF(elem.STRING, elem.NUMBER).validate()
>>> elem.ONEOF(elem.STRING, elem.NUMBER).validate()
>>> elem.NOT(elem.NULL).validate()
>>> elem.NOT(elem.ANY).validate()
>>> elem.ANY.validate()
```

property ANY(self)

ALLOF(self, *TYPES)

ANYOF(self, *TYPES)

ONEOF(self, *TYPES)

NOT(self, TYPE)

kwCoco.util.STRING

class kwCoco.util.ScalarElements

Bases: object

Single-valued elements

property NULL(self)

<https://json-schema.org/understanding-json-schema/reference/null.html>

```

property BOOLEAN(self)
    https://json-schema.org/understanding-json-schema/reference/null.html

property STRING(self)
    https://json-schema.org/understanding-json-schema/reference/string.html

property NUMBER(self)
    https://json-schema.org/understanding-json-schema/reference/numeric.html#number

property INTEGER(self)
    https://json-schema.org/understanding-json-schema/reference/numeric.html#integer

```

class kwCoco.util.SchemaElements

Bases: *ScalarElements, QuantifierElements, ContainerElements*

Functional interface into defining jsonschema structures.

See mixin classes for details.

References

<https://json-schema.org/understanding-json-schema/>

Todo:

- [] Generics: title, description, default, examples
-

CommandLine

```
xdoctest -m /home/joncrall/code/kwCoco/kwCoco/util/jsonschema_elements.py
↳ SchemaElements
```

Example

```

>>> from kwCoco.util.jsonschema_elements import * # NOQA
>>> elem = SchemaElements()
>>> elem.ARRAY(elem.ANY())
>>> schema = OBJECT({
>>>     'prop1': ARRAY(INTEGER, minItems=3),
>>>     'prop2': ARRAY(STRING, numItems=2),
>>>     'prop3': ARRAY(OBJECT({
>>>         'subprob1': NUMBER,
>>>         'subprob2': NUMBER,
>>>     })),
>>> })
>>> print('schema = {}'.format(ub.repr2(schema, nl=2, sort=1)))
schema = {
    'properties': {
        'prop1': {'items': {'type': 'integer'}, 'minItems': 3, 'type': 'array'},
        'prop2': {'items': {'type': 'string'}, 'maxItems': 2, 'minItems': 2, 'type':
↳ 'array'},
        'prop3': {'items': {'properties': {'subprob1': {'type': 'number'}, 'subprob2':
↳ {'type': 'number'}}}, 'type': 'object'}, 'type': 'array'}
}

```

(continues on next page)

(continued from previous page)

```
},
  'type': 'object',
}
```

```
>>> TYPE = elem.OBJECT({
>>>     'p1': ANY,
>>>     'p2': ANY,
>>> }, required=['p1'])
>>> import jsonschema
>>> inst = {'p1': None}
>>> jsonschema.validate(inst, schema=TYPE)
>>> #jsonschema.validate({'p2': None}, schema=TYPE)
```

kwcoco.util.elem

```
class kwcoco.util.LazyGDalFrameFile(fpather, nodata=None)
Bases: ubelt.NiceRepr
```

Todo:

- [] Move to its own backend module
 - [] When used with COCO, allow the image metadata to populate the height, width, and channels if possible.
-

Example

```
>>> # xdoctest: +REQUIRES(module:osgeo)
>>> self = LazyGDalFrameFile.demo()
>>> print('self = {!r}'.format(self))
>>> self[0:3, 0:3]
>>> self[:, :, 0]
>>> self[0]
>>> self[0, 3]
```

```
>>> # import kwplot
>>> # kwplot.imshow(self[:])
```

Parameters

- nodata
- masking_method

Example

```
>>> # See if we can reproduce the INTERLEAVE bug
```

```
data = np.random.rand(128, 128, 64) import kwimage import ubelt as ub from os.path import join dpath = ub.ensure_app_cache_dir('kwcoco/tests/reader') fpath = join(dpath, 'foo.tiff') kwimage.imwrite(fpath, data, backend='skimage') recon1 = kwimage.imread(fpath) recon1.shape

self = LazyGDalFrameFile(fpath) self.shape self[:]

classmethod available(self)
    Returns True if this backend is available

_ds(self)

classmethod demo(cls, key='astro', dsize=None)

property ndim(self)

property shape(self)

property dtype(self)

__nice__(self)

__getitem__(self, index)
```

References

<https://gis.stackexchange.com/questions/162095/gdal-driver-create-typeerror>

Example

```
>>> # Test nodata works correctly
>>> # xdoctest: +REQUIRES(module:osgeo)
>>> from kwcoco.util.lazy_frame_backends import * # NOQA
>>> from kwcoco.util.lazy_frame_backends import _demo_geoinf_with_nodata
>>> fpath = _demo_geoinf_with_nodata()
>>> self = LazyGDalFrameFile(fpath, nodata='auto')
>>> imdata = self[:]
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> import kwarray
>>> kwplot.autompl()
>>> imdata = kwimage.normalize_intensity(imdata)
>>> imdata = np.nan_to_num(imdata)
>>> kwplot.imshow(imdata)
```

__array__(self)

Allow this object to be passed to np.asarray

References

<https://numpy.org/doc/stable/user/basics.dispatch.html>

```
class kwcoco.util.LazyRasterIOFrameFile(fp)
Bases: ubelt.NiceRepr

fp = '/home/joncrall/.cache/kwcoco/demo/large_hyperspectral/big_img_128.bsq' lazy_rio = LazyRasterI-
OFrameFile(fp) ds = lazy_rio.ds

@classmethod available(self)
    Returns True if this backend is available

    _ds(self)

@property ndim(self)
@property shape(self)
@property dtype(self)
__nice__(self)
__getitem__(self, index)

class kwcoco.util.LazySpectralFrameFile(fp)
Bases: ubelt.NiceRepr

Potentially faster than GDAL for HDR formats.

    _ds(self)

    @classmethod available(self)
        Returns True if this backend is available

    @property ndim(self)
    @property shape(self)
    @property dtype(self)
    __nice__(self)
    __getitem__(self, index)

class kwcoco.util.Archive(fp=None, mode='r', backend=None, file=None)
Bases: object

Abstraction over zipfile and tarfile
```

Todo: see if we can use one of these other tools instead

SeeAlso: <https://github.com/RKrahl/archive-tools> <https://pypi.org/project/arlib/>

Example

```
>>> from os.path import join
>>> dpath = ub.ensure_app_cache_dir('ubelt', 'tests', 'archive')
>>> ub.delete(dpath)
>>> dpath = ub.ensure_app_cache_dir(dpath)
>>> import pathlib
>>> dpath = pathlib.Path(dpath)
>>> #
>>> #
>>> mode = 'w'
>>> self1 = Archive(str(dpath / 'demo.zip'), mode=mode)
>>> self2 = Archive(str(dpath / 'demo.tar.gz'), mode=mode)
>>> #
>>> open(dpath / 'data_1only.txt', 'w').write('bazbzzz')
>>> open(dpath / 'data_2only.txt', 'w').write('buzzz')
>>> open(dpath / 'data_both.txt', 'w').write('foobar')
>>> #
>>> self1.add(dpath / 'data_both.txt')
>>> self1.add(dpath / 'data_1only.txt')
>>> #
>>> self2.add(dpath / 'data_both.txt')
>>> self2.add(dpath / 'data_2only.txt')
>>> #
>>> self1.close()
>>> self2.close()
>>> #
>>> self1 = Archive(str(dpath / 'demo.zip'), mode='r')
>>> self2 = Archive(str(dpath / 'demo.tar.gz'), mode='r')
>>> #
>>> extract_dpath = ub.ensuredir(str(dpath / 'extracted'))
>>> extracted1 = self1.extractall(extract_dpath)
>>> extracted2 = self2.extractall(extract_dpath)
>>> for fpath in extracted2:
>>>     print(open(fpath, 'r').read())
>>> for fpath in extracted1:
>>>     print(open(fpath, 'r').read())
```

classmethod _open(cls, fpath, mode)

__iter__(self)

classmethod coerce(cls, data)

Either open an archive file path or coerce an existing ZipFile or tarfile structure into this wrapper class

add(self, fpath, arcname=None)

close(self)

__enter__(self)

__exit__(self, *args)

extractall(self, output_dpath='.', verbose=1, overwrite=True)

kwcococo.util.unarchive_file(archive_fpath, output_dpath='.', verbose=1, overwrite=True)

```
class kwcoco.util.DelayedChannelConcat(components, dsize=None)
```

Bases: *DelayedImageOperation*

Represents multiple channels in an image that could be concatenated

Variables **components** (*List[DelayedWarp]*) – a list of stackable channels. Each component may be comprised of multiple channels.

Todo:

- [] can this be generalized into a delayed concat?
 - [] can all concats be delayed until the very end?
-

Example

```
>>> comp1 = DelayedWarp(np.random.rand(11, 7))
>>> comp2 = DelayedWarp(np.random.rand(11, 7, 3))
>>> comp3 = DelayedWarp(
>>>     np.random.rand(3, 5, 2),
>>>     transform=kwimage.Affine.affine(scale=(7/5, 11/3)).matrix,
>>>     dsize=(7, 11)
>>> )
>>> components = [comp1, comp2, comp3]
>>> chans = DelayedChannelConcat(components)
>>> final = chans.finalize()
>>> assert final.shape == chans.shape
>>> assert final.shape == (11, 7, 6)
```

```
>>> # We should be able to nest DelayedChannelConcat inside virtual images
>>> frame1 = DelayedWarp(
>>>     chans, transform=kwimage.Affine.affine(scale=2.2).matrix,
>>>     dsize=(20, 26))
>>> frame2 = DelayedWarp(
>>>     np.random.rand(3, 3, 6), dsize=(20, 26))
>>> frame3 = DelayedWarp(
>>>     np.random.rand(3, 3, 6), dsize=(20, 26))
```

```
>>> print(ub.repr2(frame1.nesting(), nl=-1, sort=False))
>>> frame1.finalize()
>>> vid = DelayedFrameConcat([frame1, frame2, frame3])
>>> print(ub.repr2(vid.nesting(), nl=-1, sort=False))
```

children(self)

Abstract method, which should generate all of the direct children of a node in the operation tree.

classmethod random(*cls, num_parts=3, rng=None*)

Example

```
>>> self = DelayedChannelConcat.random()
>>> print('self = {!r}'.format(self))
>>> print(ub.repr2(self.nesting(), nl=-1, sort=0))
```

property channels(*self*)
property shape(*self*)
finalize(*self*, *kwargs*)**
 Execute the final transform
delayed_warp(*self*, *transform*, *dsize=None*)
 Delayed transform the underlying data.

Note: this deviates from kwimage warp functions because instead of “output_dims” (specified in c-style shape) we specify dsize (w, h).

Returns new delayed transform a chained transform

Return type *DelayedWarp*

take_channels(*self*, *channels*)

This method returns a subset of the vision data with only the specified bands / channels.

Parameters *channels* (*List[int]* | *slice* | *channel_spec.FusedChannelSpec*) – List of integers indexes, a slice, or a channel spec, which is typically a pipe (|) delimited list of channel codes. See kwcoco.ChannelSpec for more details.

Returns a delayed vision operation that only operates on the following channels.

Return type *DelayedVisionOperation*

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral')
>>> self = delayed = dset.delayed_load(1)
>>> channels = 'B11|B8|B1|B10'
>>> new = self.take_channels(channels)
```

Example

```
>>> # Complex case
>>> import kwcoco
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral')
>>> delayed = dset.delayed_load(1)
>>> astro = DelayedLoad.demo('astro').load_shape(use_channel_heuristic=True)
>>> aligned = astro.warp(kwimage.Affine.scale(600 / 512), dsize='auto')
```

(continues on next page)

(continued from previous page)

```
>>> self = combo = DelayedChannelConcat(delayed.components + [aligned])
>>> channels = 'B1|r|B8|g'
>>> new = self.take_channels(channels)
>>> new_cropped = new.crop((slice(10, 200), slice(12, 350)))
>>> datas = new_cropped.finalize()
>>> vizable = kwimage.normalize_intensity(datas, axis=2)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> stacked = kwimage.stack_images(vizable.transpose(2, 0, 1))
>>> kwplot.imshow(stacked)
```

CommandLine

```
xdoctest -m /home/joncrall/code/kwcoco/kwcoco/util/util_delayed_poc.py
  ↵DelayedChannelConcat.take_channels:2 --profile
```

Example

```
>>> # Test case where requested channel does not exist
>>> import kwcoco
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral', use_cache=1, ↵
  ↵verbose=100)
>>> self = dset.delayed_load(1)
>>> channels = 'B1|foobar|bazbiz|B8'
>>> new = self.take_channels(channels)
>>> new_cropped = new.crop((slice(10, 200), slice(12, 350)))
>>> fused = new_cropped.finalize()
>>> assert fused.shape == (190, 338, 4)
>>> assert np.all(np.isnan(fused[..., 1:3]))
>>> assert not np.any(np.isnan(fused[..., 0]))
>>> assert not np.any(np.isnan(fused[..., 3]))
```

class kwcoco.util.DelayedCrop(*sub_data*, *sub_slices*)

Bases: *DelayedImageOperation*

Represent a delayed crop operation

Example

```
>>> sub_data = DelayedLoad.demo()
>>> sub_slices = (slice(5, 10), slice(1, 12))
>>> self = DelayedCrop(sub_data, sub_slices)
>>> print(ub.repr2(self.nesting(), nl=-1, sort=0))
>>> final = self.finalize()
>>> print('final.shape = {!r}'.format(final.shape))
```

Example

```
>>> sub_data = DelayedLoad.demo()
>>> sub_slices = (slice(5, 10), slice(1, 12))
>>> crop1 = DelayedCrop(sub_data, sub_slices)
>>> import pytest
>>> # Should only error while heuristics are in use.
>>> with pytest.raises(ValueError):
>>>     crop2 = DelayedCrop(crop1, sub_slices)
```

`__hack_dont_optimize__ = True`

`property channels(self)`

`children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`finalize(self, **kwargs)`

`abstract _optimize_paths(self, **kwargs)`

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of heuristically optimized leaf repr wrt warps.

`class kwcoco.util.DelayedFrameConcat(frames, dsize=None)`

Bases: `DelayedVideoOperation`

Represents multiple frames in a video

Note:

```
Video[0]:
Frame[0]:
    Chan[0]: (32) +-----+
    Chan[1]: (16) +-----+
    Chan[2]: ( 8) +----+
Frame[1]:
    Chan[0]: (30) +-----+
    Chan[1]: (14) +-----+
    Chan[2]: ( 6) +----+
```

Todo:

- [] Support computing the transforms when none of the data is loaded

Example

```
>>> # Simpler case with fewer nesting levels
>>> rng = kwarray.ensure_rng(None)
>>> # Delayed warp each channel into its "image" space
>>> # Note: the images never enter the space we transform through
>>> f1_img = DelayedLoad.demo('astro', (300, 300))
>>> f2_img = DelayedLoad.demo('carl', (256, 256))
>>> # Combine frames into a video
>>> vid_dsize = np.array((100, 100))
>>> self = vid = DelayedFrameConcat([
>>>     f1_img.delayed_warp(kwimage.Affine.scale(vid_dsize / f1_img.dsize)),
>>>     f2_img.delayed_warp(kwimage.Affine.scale(vid_dsize / f2_img.dsize)),
>>> ], dsize=vid_dsize)
>>> print(ub.repr2(vid.nesting(), nl=-1, sort=0))
>>> final = vid.finalize(interpolation='nearest', dsize=(32, 32))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(final[0], pnum=(1, 2, 1), fnum=1)
>>> kwplot.imshow(final[1], pnum=(1, 2, 2), fnum=1)
>>> region_slices = (slice(0, 90), slice(30, 60))
```

`children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`property channels(self)`

`property shape(self)`

`finalize(self, **kwargs)`

Execute the final transform

`delayed_crop(self, region_slices)`

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> # Create raw channels in some "native" resolution for frame 1
>>> f1_chan1 = DelayedIdentity.demo('astro', chan=1, 0, dsize=(300, 300))
>>> f1_chan2 = DelayedIdentity.demo('astro', chan=2, dsize=(10, 10))
>>> # Create raw channels in some "native" resolution for frame 2
>>> f2_chan1 = DelayedIdentity.demo('carl', dsize=(64, 64), chan=(1, 0))
>>> f2_chan2 = DelayedIdentity.demo('carl', dsize=(10, 10), chan=2)
>>> #
>>> f1_dsize = np.array(f1_chan1.dsize)
>>> f2_dsize = np.array(f2_chan1.dsize)
>>> f1_img = DelayedChannelConcat([
>>>     f1_chan1.delayed_warp(kwimage.Affine.scale(f1_dsize / f1_chan1.dsize), -dsize=f1_dsize),
>>>     f1_chan2.delayed_warp(kwimage.Affine.scale(f1_dsize / f1_chan2.dsize), -dsize=f1_dsize),
>>> ])
>>> f2_img = DelayedChannelConcat([
```

(continues on next page)

(continued from previous page)

```

>>>     f2_chan1.delayed_warp(kwimage.Affine.scale(f2_dsize / f2_chan1.dsize),  

>>>     ~dszie=f2_dsize),  

>>>     f2_chan2.delayed_warp(kwimage.Affine.scale(f2_dsize / f2_chan2.dsize),  

>>>     ~dszie=f2_dsize),  

>>>   ])  

>>> vid_dsize = np.array((280, 280))  

>>> full_vid = DelayedFrameConcat([  

>>>     f1_img.delayed_warp(kwimage.Affine.scale(vid_dsize / f1_img.dsize),  

>>>     ~dszie=vid_dsize),  

>>>     f2_img.delayed_warp(kwimage.Affine.scale(vid_dsize / f2_img.dsize),  

>>>     ~dszie=vid_dsize),  

>>>   ])  

>>> region_slices = (slice(80, 200), slice(80, 200))  

>>> print(ub.repr2(full_vid.nesting(), nl=-1, sort=0))  

>>> crop_vid = full_vid.delayed_crop(region_slices)  

>>> final_full = full_vid.finalize(interpolation='nearest')  

>>> final_crop = crop_vid.finalize(interpolation='nearest')  

>>> import pytest  

>>> with pytest.raises(ValueError):  

>>>     # should not be able to crop a crop yet  

>>>     crop_vid.delayed_crop(region_slices)  

>>> # xdoctest: +REQUIRES(--show)  

>>> import kwplot  

>>> kwplot.autompl()  

>>> kwplot.imshow(final_full[0], pnum=(2, 2, 1), fnum=1)  

>>> kwplot.imshow(final_full[1], pnum=(2, 2, 2), fnum=1)  

>>> kwplot.imshow(final_crop[0], pnum=(2, 2, 3), fnum=1)  

>>> kwplot.imshow(final_crop[1], pnum=(2, 2, 4), fnum=1)

```

delayed_warp(self, transform, dsize=None)

Delayed transform the underlyng data.

Note: this deviates from kwimage warp functions because instead of “output_dims” (specified in c-style shape) we specify dsize (w, h).

Returns new delayed transform a chained transform

Return type *DelayedWarp*

```
class kwcoco.util.DelayedImageIdentity(sub_data, dsize=None, channels=None, quantization=None)
Bases: DelayedImageOperation
```

Noop leaf that does nothing. Can be used to hold raw data.

Typically used to just hold raw data.

```
DelayedIdentity.demo('astro', chan=0, dsize=(32, 32))
```

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> sub_data = np.random.rand(31, 37, 3)
>>> self = DelayedIdentity(sub_data)
>>> self = DelayedIdentity(sub_data, channels='L|a|b')

>>> # test with quantization
>>> rng = kwarray.ensure_rng(32)
>>> sub_data_quant = (rng.rand(31, 37, 3) * 1000).astype(np.int16)
>>> sub_data_quant[0, 0] = -9999
>>> self = DelayedIdentity(sub_data_quant, channels='L|a|b', quantization={
>>>     'orig_min': 0.,
>>>     'orig_max': 1.,
>>>     'quant_min': 0,
>>>     'quant_max': 1000,
>>>     'nodata': -9999,
>>> })
>>> final1 = self.finalize(dequantize=True)
>>> final2 = self.finalize(dequantize=False)
>>> assert np.all(np.isnan(final1[0, 0]))
>>> scale = final2 / final1
>>> scales = scale[scale > 0]
>>> assert np.all(np.isclose(scales, 1000))
>>> # check that take_channels works
>>> new_subdata = self.take_channels('a')
>>> sub_final1 = new_subdata.finalize(dequantize=True)
>>> sub_final2 = new_subdata.finalize(dequantize=False)
>>> assert sub_final1.dtype.kind == 'f'
>>> assert sub_final2.dtype.kind == 'i'
```

`__hack_dont_optimize__ = True`

`classmethod demo(cls, key='astro', chan=None, dsizes=None)`

`children(self)`

Abstract method, which should generate all of the direct children of a node in the operation tree.

`_optimize_paths(self, **kwargs)`

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of heuristically optimized leaf repr wrt warps.

`finalize(self, **kwargs)`

`take_channels(self, channels)`

`class kwcoco.util.DelayedImageOperation`

Bases: `DelayedVisionOperation`

Operations that pertain only to images

`delayed_crop(self, region_slices)`

Create a new delayed image that performs a crop in the transformed “self” space.

`Parameters region_slices (Tuple[slice, slice]) – y-slice and x-slice.`

Note: Returns a heuristically “simplified” tree. In the current implementation there are only 3 operations, cat, warp, and crop. All cats go at the top, all crops go at the bottom, all warps are in the middle.

Returns lazy executed delayed transform

Return type *DelayedWarp*

Example

```
>>> dsize = (100, 100)
>>> tf2 = kwimage.Affine.affine(scale=3).matrix
>>> self = DelayedWarp(np.random.rand(33, 33), tf2, dsize)
>>> region_slices = (slice(5, 10), slice(1, 12))
>>> delayed_crop = self.delayed_crop(region_slices)
>>> print(ub.repr2(delayed_crop.nesting(), nl=-1, sort=0))
>>> delayed_crop.finalize()
```

Example

```
>>> chan1 = DelayedLoad.demo('astro')
>>> chan2 = DelayedLoad.demo('carl')
>>> warped1a = chan1.delayed_warp(kwimage.Affine.scale(1.2).matrix)
>>> warped2a = chan2.delayed_warp(kwimage.Affine.scale(1.5))
>>> warped1b = warped1a.delayed_warp(kwimage.Affine.scale(1.2).matrix)
>>> warped2b = warped2a.delayed_warp(kwimage.Affine.scale(1.5))
>>> #
>>> region_slices = (slice(97, 677), slice(5, 691))
>>> self = warped2b
>>> #
>>> crop1 = warped1b.delayed_crop(region_slices)
>>> crop2 = warped2b.delayed_crop(region_slices)
>>> print(ub.repr2(warped1b.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(warped2b.nesting(), nl=-1, sort=0))
>>> # Notice how the crop merges the two nesting layers
>>> # (via the heuristic optimize step)
>>> print(ub.repr2(crop1.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(crop2.nesting(), nl=-1, sort=0))
>>> frame1 = crop1.finalize(dsize=(500, 500))
>>> frame2 = crop2.finalize(dsize=(500, 500))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> kwplot.imshow(frame1, pnum=(1, 2, 1), fnum=1)
>>> kwplot.imshow(frame2, pnum=(1, 2, 2), fnum=1)
```

delayed_warp(*self, transform, dsize=None*)

Delayed transform the underlying data.

Note: this deviates from kwimage warp functions because instead of “output_dims” (specified in c-style

shape) we specify dsize (w, h).

Returns new delayed transform a chained transform

Return type *DelayedWarp*

abstract `take_channels(self, channels)`

class `kwcoco.util.DelayedLoad(fpPath, channels=None, dsize=None, num_bands=None, immediate_crop=None, immediate_chan_idxs=None, immediate_dsize=None, quantization=None)`

Bases: *DelayedImageOperation*

A load operation for a specific sub-region and sub-bands in a specified image.

Note: This class contains support for fusing certain lazy operations into this layer, namely cropping, scaling, and channel selection.

For now these are named **immediates**

Example

```
>>> fpath = kwimage.grab_test_image_fpath()
>>> self = DelayedLoad(fpath)
>>> print('self = {!r}'.format(self))
>>> self.load_shape()
>>> print('self = {!r}'.format(self))
>>> self.finalize()
```

```
>>> f1_img = DelayedLoad.demo('astro', dsize=(300, 300))
>>> f2_img = DelayedLoad.demo('carl', dsize=(256, 320))
>>> print('f1_img = {!r}'.format(f1_img))
>>> print('f2_img = {!r}'.format(f2_img))
>>> print(f2_img.finalize().shape)
>>> print(f1_img.finalize().shape)
```

```
>>> fpath = kwimage.grab_test_image_fpath()
>>> channels = channel_spec.FusedChannelSpec.coerce('rgb')
>>> self = DelayedLoad(fpath, channels=channels)
```

Example

```
>>> # Test with quantization
>>> fpath = kwimage.grab_test_image_fpath()
>>> channels = channel_spec.FusedChannelSpec.coerce('rgb')
>>> self = DelayedLoad(fpath, channels=channels, quantization={
>>>     'orig_min': 0.,
>>>     'orig_max': 1.,
>>>     'quant_min': 0,
>>>     'quant_max': 256,
```

(continues on next page)

(continued from previous page)

```
>>>     'nodata': None,
>>> })
>>> final1 = self.finalize(dequantize=False)
>>> final2 = self.finalize(dequantize=True)
>>> assert final1.dtype.kind == 'u'
>>> assert final2.dtype.kind == 'f'
>>> assert final2.max() <= 1
```

__hack_dont_optimize__ = True**classmethod demo**(DelayedLoad, key='astro', dsizes=None)**abstract classmethod coerce**(cls, data)**children**(self)

Abstract method, which should generate all of the direct children of a node in the operation tree.

nesting(self)**_optimize_paths**(self, **kwargs)

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of heuristically optimized leaf repr wrt warps.

load_shape(self, use_channel_heuristic=False)**_ensure_dsizes**(self)**property shape**(self)**property num_bands**(self)**property dsizes**(self)**property channels**(self)**property fpath**(self)**finalize**(self, **kwargs)**Todo:**

- [] Load from overviews if a scale will be necessary

Parameters **kwargs –

nodata [if specified this data item is treated as nodata, the] data is then converted to floats and the nodata value is replaced with nan.

delayed_crop(self, region_slices)

Parameters region_slices (*Tuple[slice, slice]*) – y-slice and x-slice.

Returns a new delayed load object with a fused crop operation

Return type *DelayedLoad*

Example

```
>>> # Test chained crop operations
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> self = orig = DelayedLoad.demo('astro').load_shape()
>>> region_slices = slices1 = (slice(0, 90), slice(30, 60))
>>> self = crop1 = orig.delayed_crop(slices1)
>>> region_slices = slices2 = (slice(10, 21), slice(10, 22))
>>> self = crop2 = crop1.delayed_crop(slices2)
>>> region_slices = slices3 = (slice(3, 20), slice(5, 20))
>>> crop3 = crop2.delayed_crop(slices3)
>>> # Spot check internals
>>> print('orig = {}'.format(ub.repr2(orig.__json__(), nl=2)))
>>> print('crop1 = {}'.format(ub.repr2(crop1.__json__(), nl=2)))
>>> print('crop2 = {}'.format(ub.repr2(crop2.__json__(), nl=2)))
>>> print('crop3 = {}'.format(ub.repr2(crop3.__json__(), nl=2)))
>>> # Test internals
>>> assert crop3._immediates['crop'][0].start == 13
>>> assert crop3._immediates['crop'][0].stop == 21
>>> # Test shapes work out correctly
>>> assert crop3.finalize().shape == (8, 7, 3)
>>> assert crop2.finalize().shape == (11, 12, 3)
>>> assert crop1.take_channels([1, 2]).finalize().shape == (90, 30, 2)
>>> assert orig.finalize().shape == (512, 512, 3)
```

Note:

This chart gives an intuition on how new absolute `slice` coords are computed **from existing** absolute coords and relative coords.

5 7	<- new
3 5	<- rel

01234567	<- relative coordinates

2 9	<- curr

0123456789	<- absolute coordinates

`take_channels(self, channels)`

This method returns a subset of the vision data with only the specified bands / channels.

Parameters `channels` (`List[int] | slice | channel_spec.FusedChannelSpec`) – List of integers indexes, a slice, or a channel spec, which is typically a pipe (|) delimited list of channel codes. See `kwcoco.ChannelSpec` for more details.

Returns a new delayed load with a fused take channel operation

Return type `DelayedLoad`

Note: The channel subset must exist here or it will raise an error. A better implementation (via symbolic)

might be able to do better

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> import kwcoco
>>> self = DelayedLoad.demo('astro').load_shape()
>>> channels = [2, 0]
>>> new = self.take_channels(channels)
>>> new3 = new.take_channels([1, 0])
```

```
>>> final1 = self.finalize()
>>> final2 = new.finalize()
>>> final3 = new3.finalize()
>>> assert np.all(final1[..., 2] == final2[..., 0])
>>> assert np.all(final1[..., 0] == final2[..., 1])
>>> assert final2.shape[2] == 2
```

```
>>> assert np.all(final1[..., 2] == final3[..., 1])
>>> assert np.all(final1[..., 0] == final3[..., 0])
>>> assert final3.shape[2] == 2
```

class kwcoco.util.DelayedNans(dsize=None, channels=None)

Bases: *DelayedImageOperation*

Constructs nan channels as needed

Example

```
self = DelayedNans((10, 10), channel_spec.FusedChannelSpec.coerce('rgb')) region_slices = (slice(5, 10),
slice(1, 12)) delayed = self.delayed_crop(region_slices)
```

Example

```
>>> from kwcoco.util.util_delayed_poc import * # NOQA
>>> dsize = (307, 311)
>>> c1 = DelayedNans(dsize=dsize, channels=channel_spec.FusedChannelSpec.coerce('foo
˓→'))
>>> c2 = DelayedLoad.demo('astro', dsize=dsize).load_shape(True)
>>> cat = DelayedChannelConcat([c1, c2])
>>> warped_cat = cat.delayed_warp(kwimage.Affine.scale(1.07), dsize=(328, 332))
>>> warped_cat.finalize()
```

#>>> cropped = warped_cat.delayed_crop((slice(0, 300), slice(0, 100))) #>>> cropped.finalize().shape

property shape(self)

property num_bands(self)

property dsize(self)

property channels(self)

children(self)

Abstract method, which should generate all of the direct children of a node in the operation tree.

_optimize_paths(self, **kwargs)

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of hueristically optimized leaf repr wrt warps.

finalize(self, **kwargs)**delayed_crop(self, region_slices)**

Create a new delayed image that performs a crop in the transformed “self” space.

Parameters `region_slices` (`Tuple[slice, slice]`) – y-slice and x-slice.

Note: Returns a heuristically “simplified” tree. In the current implementation there are only 3 operations, cat, warp, and crop. All cats go at the top, all crops go at the bottom, all warps are in the middle.

Returns lazy executed delayed transform

Return type `DelayedWarp`

Example

```
>>> dsizes = (100, 100)
>>> tf2 = kwimage.Affine.affine(scale=3).matrix
>>> self = DelayedWarp(np.random.rand(33, 33), tf2, dsizes)
>>> region_slices = (slice(5, 10), slice(1, 12))
>>> delayed_crop = self.delayed_crop(region_slices)
>>> print(ub.repr2(delayed_crop.nesting(), nl=-1, sort=0))
>>> delayed_crop.finalize()
```

Example

```
>>> chan1 = DelayedLoad.demo('astro')
>>> chan2 = DelayedLoad.demo('carl')
>>> warped1a = chan1.delayed_warp(kwimage.Affine.scale(1.2).matrix)
>>> warped2a = chan2.delayed_warp(kwimage.Affine.scale(1.5))
>>> warped1b = warped1a.delayed_warp(kwimage.Affine.scale(1.2).matrix)
>>> warped2b = warped2a.delayed_warp(kwimage.Affine.scale(1.5))
>>> #
>>> region_slices = (slice(97, 677), slice(5, 691))
>>> self = warped2b
>>> #
>>> crop1 = warped1b.delayed_crop(region_slices)
>>> crop2 = warped2b.delayed_crop(region_slices)
>>> print(ub.repr2(warped1b.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(warped2b.nesting(), nl=-1, sort=0))
>>> # Notice how the crop merges the two nesting layers
>>> # (via the hueristic optimize step)
>>> print(ub.repr2(crop1.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(crop2.nesting(), nl=-1, sort=0))
```

(continues on next page)

(continued from previous page)

```
>>> frame1 = crop1.finalize(dsize=(500, 500))
>>> frame2 = crop2.finalize(dsize=(500, 500))
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(frame1, pnum=(1, 2, 1), fnum=1)
>>> kwplot.imshow(frame2, pnum=(1, 2, 2), fnum=1)
```

delayed_warp(*self*, *transform*, *dsize=None*)

Delayed transform the underlying data.

Note: this deviates from kwimage warp functions because instead of “output_dims” (specified in c-style shape) we specify dsize (w, h).

Returns new delayed transform a chained transform

Return type *DelayedWarp*

class `kwcoco.util.DelayedVideoOperation`Bases: *DelayedVisionOperation*

Base class for nodes in a tree of delayed computer-vision operations

class `kwcoco.util.DelayedVisionOperation`Bases: *ubelt.NiceRepr*

Base class for nodes in a tree of delayed computer-vision operations

__nice__(*self*)**abstract finalize**(*self*, ***kwargs*)**abstract children**(*self*)

Abstract method, which should generate all of the direct children of a node in the operation tree.

_optimize_paths(*self*, ***kwargs*)

Iterate through the leaf nodes, which are virtually transformed into the root space.

This returns some sort of heuristically optimized leaf repr wrt warps.

__json__(*self*)**nesting**(*self*)**warp**(*self*, **args*, ***kwargs*)

alias for delayed_warp, might change to this API in the future

crop(*self*, **args*, ***kwargs*)

alias for delayed_crop, might change to this API in the future

class `kwcoco.util.DelayedWarp`(*sub_data*, *transform=None*, *dsize=None*)Bases: *DelayedImageOperation*

POC for chainable transforms

Note: “sub” is used to refer to the underlying data in its native coordinates and resolution.

“self” is used to refer to the data in the transformed coordinates that are exposed by this class.

Variables

- **sub_data** (`DelayedWarp` / `ArrayLike`) – array-like image data at a native resolution
- **transform** (`Transform`) – transforms data from native “sub”-image-space to “self”-image-space.

Example

```
>>> dsizes = (12, 12)
>>> tf1 = np.array([[2, 0, 0], [0, 2, 0], [0, 0, 1]])
>>> tf2 = np.array([[3, 0, 0], [0, 3, 0], [0, 0, 1]])
>>> tf3 = np.array([[4, 0, 0], [0, 4, 0], [0, 0, 1]])
>>> band1 = DelayedWarp(np.random.rand(6, 6), tf1, dsizes)
>>> band2 = DelayedWarp(np.random.rand(4, 4), tf2, dsizes)
>>> band3 = DelayedWarp(np.random.rand(3, 3), tf3, dsizes)
>>> #
>>> # Execute a crop in a one-level transformed space
>>> region_slices = (slice(5, 10), slice(0, 12))
>>> delayed_crop = band2.delayed_crop(region_slices)
>>> final_crop = delayed_crop.finalize()
>>> #
>>> # Execute a crop in a nested transformed space
>>> tf4 = np.array([[1.5, 0, 0], [0, 1.5, 0], [0, 0, 1]])
>>> chained = DelayedWarp(band2, tf4, (18, 18))
>>> delayed_crop = chained.delayed_crop(region_slices)
>>> final_crop = delayed_crop.finalize()
>>> #
>>> tf4 = np.array([[.5, 0, 0], [0, .5, 0], [0, 0, 1]])
>>> chained = DelayedWarp(band2, tf4, (6, 6))
>>> delayed_crop = chained.delayed_crop(region_slices)
>>> final_crop = delayed_crop.finalize()
>>> #
>>> region_slices = (slice(1, 5), slice(2, 4))
>>> delayed_crop = chained.delayed_crop(region_slices)
>>> final_crop = delayed_crop.finalize()
```

Example

```
>>> dsizes = (17, 12)
>>> tf = np.array([[5.2, 0, 1.1], [0, 3.1, 2.2], [0, 0, 1]])
>>> self = DelayedWarp(np.random.rand(3, 5, 13), tf, dsizes=dsizes)
>>> self.finalize().shape
```

```
classmethod random(cls, nesting=(2, 5), rng=None)
```

Example

```
>>> self = DelayedWarp.random(nesting=(4, 7))
>>> print('self = {!r}'.format(self))
>>> print(ub.repr2(self.nesting(), nl=-1, sort=0))
```

property channels(self)

children(self)

Abstract method, which should generate all of the direct children of a node in the operation tree.

property dsize(self)

property num_bands(self)

property shape(self)

_optimize_paths(self, **kwargs)

Example

```
>>> self = DelayedWarp.random()
>>> leafs = list(self._optimize_paths())
>>> print('leafs = {!r}'.format(leafs))
```

finalize(self, transform=None, dsize=None, interpolation='linear', **kwargs)

Execute the final transform

Can pass a parent transform to augment this underlying transform.

Parameters

- **transform (Transform)** – an additional transform to perform
- **dsize (Tuple[int, int])** – overrides destination canvas size

Example

```
>>> tf = np.array([[0.9, 0, 3.9], [0, 1.1, -.5], [0, 0, 1]])
>>> raw = kwimage.grab_test_image(dsize=(54, 65))
>>> raw = kwimage.ensure_float01(raw)
>>> # Test nested finalize
>>> layer1 = raw
>>> num = 10
>>> for _ in range(num):
...     layer1 = DelayedWarp(layer1, tf, dsize='auto')
>>> final1 = layer1.finalize()
>>> # Test non-nested finalize
>>> layer2 = list(layer1._optimize_paths())[0]
>>> final2 = layer2.finalize()
>>> #
>>> print(ub.repr2(layer1.nesting(), nl=-1, sort=0))
>>> print(ub.repr2(layer2.nesting(), nl=-1, sort=0))
>>> print('final1 = {!r}'.format(final1))
>>> print('final2 = {!r}'.format(final2))
```

(continues on next page)

(continued from previous page)

```
>>> print('final1.shape = {!r}'.format(final1.shape))
>>> print('final2.shape = {!r}'.format(final2.shape))
>>> assert np.allclose(final1, final2)
>>> #
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> kwplot.imshow(raw, pnum=(1, 3, 1), fnum=1)
>>> kwplot.imshow(final1, pnum=(1, 3, 2), fnum=1)
>>> kwplot.imshow(final2, pnum=(1, 3, 3), fnum=1)
>>> kwplot.show_if_requested()
```

Example

```
>>> # Test aliasing
>>> s = DelayedIdentity.demo()
>>> s = DelayedIdentity.demo('checkerboard')
>>> a = s.delayed_warp(kwimage.Affine.scale(0.05), dszie='auto')
>>> b = s.delayed_warp(kwimage.Affine.scale(3), dszie='auto')
```

```
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autompl()
>>> # It looks like downsampling linear and area is the same
>>> # Does warpAffine have no alias handling?
>>> pnum_ = kwplot.PlotNums(nRows=2, nCols=4)
>>> kwplot.imshow(a.finalize(interpolation='area'), pnum=pnum_(), title=
-> 'warpAffine area')
>>> kwplot.imshow(a.finalize(interpolation='linear'), pnum=pnum_(), title=
-> 'warpAffine linear')
>>> kwplot.imshow(a.finalize(interpolation='nearest'), pnum=pnum_(), title=
-> 'warpAffine nearest')
>>> kwplot.imshow(a.finalize(interpolation='nearest', antialias=False),_
-> pnum=pnum_(), title='warpAffine nearest AA=0')
>>> kwplot.imshow(kwimage.imresize(s.finalize(), dszie=a.dszie, interpolation=
-> 'area'), pnum=pnum_(), title='resize area')
>>> kwplot.imshow(kwimage.imresize(s.finalize(), dszie=a.dszie, interpolation=
-> 'linear'), pnum=pnum_(), title='resize linear')
>>> kwplot.imshow(kwimage.imresize(s.finalize(), dszie=a.dszie, interpolation=
-> 'nearest'), pnum=pnum_(), title='resize nearest')
>>> kwplot.imshow(kwimage.imresize(s.finalize(), dszie=a.dszie, interpolation=
-> 'cubic'), pnum=pnum_(), title='resize cubic')
```

`take_channels(self, channels)`

`kwcoco.util.IndexableWalker`

`kwcoco.util.ensure_json_serializable(dict_, normalize_containers=False, verbose=0)`

Attempt to convert common types (e.g. numpy) into something json compliant

Convert numpy and tuples into lists

Parameters `normalize_containers` (*bool, default=False*) – if True, normalizes dict containers to be standard python structures.

Example

```
>>> data = ub.ddict(lambda: int)
>>> data['foo'] = ub.ddict(lambda: int)
>>> data['bar'] = np.array([1, 2, 3])
>>> data['foo']['a'] = 1
>>> data['foo']['b'] = (1, np.array([1, 2, 3]), {3: np.int32(3), 4: np.float16(1.0)})
>>>
>>> dict_ = data
>>> print(ub.repr2(data, nl=-1))
>>> assert list(find_json_unserializable(data))
>>> result = ensure_json_serializable(data, normalize_containers=True)
>>> print(ub.repr2(result, nl=-1))
>>> assert not list(find_json_unserializable(result))
>>> assert type(result) is dict
```

kwcococo.util.find_json_unserializable(*data, quickcheck=False*)

Recurse through json datastructure and find any component that causes a serialization error. Record the location of these errors in the datastructure as we recurse through the call tree.

Parameters

- `data` (*object*) – data that should be json serializable
- `quickcheck` (*bool*) – if True, check the entire datastructure assuming its ok before doing the python-based recursive logic.

Returns

list of “bad part” dictionaries containing items ‘value’ - the value that caused the serialization error ‘loc’ - which contains a list of key/indexes that can be used

to lookup the location of the unserializable value. If the “loc” is a list, then it indicates a rare case where a key in a dictionary is causing the serialization error.

Return type List[Dict]

Example

```
>>> from kwcococo.util.util_json import * # NOQA
>>> part = ub.ddict(lambda: int)
>>> part['foo'] = ub.ddict(lambda: int)
>>> part['bar'] = np.array([1, 2, 3])
>>> part['foo']['a'] = 1
>>> # Create a dictionary with two unserializable parts
>>> data = [1, 2, {'nest1': [2, part]}, {frozenset({'badkey'}): 3, 2: 4}]
>>> parts = list(find_json_unserializable(data))
>>> print('parts = {}'.format(ub.repr2(parts, nl=1)))
>>> # Check expected structure of bad parts
>>> assert len(parts) == 2
>>> part = parts[1]
>>> assert list(part['loc']) == [2, 'nest1', 1, 'bar']
```

(continues on next page)

(continued from previous page)

```
>>> # We can use the "loc" to find the bad value
>>> for part in parts:
>>>     # "loc" is a list of directions containing which keys/indexes
>>>     # to traverse at each descent into the data structure.
>>>     directions = part['loc']
>>>     curr = data
>>>     special_flag = False
>>>     for key in directions:
>>>         if isinstance(key, list):
>>>             # special case for bad keys
>>>             special_flag = True
>>>             break
>>>         else:
>>>             # normal case for bad values
>>>             curr = curr[key]
>>>     if special_flag:
>>>         assert part['data'] in curr.keys()
>>>         assert part['data'] is key[1]
>>>     else:
>>>         assert part['data'] is curr
```

kwcococo.util.indexable_allclose(dct1, dct2, return_info=False)

Walks through two nested data structures and ensures that everything is roughly the same.

Parameters

- **dct1** – a nested indexable item
- **dct2** – a nested indexable item

Example

```
>>> from kwcococo.util.util_json import indexable_allclose
>>> dct1 = {
>>>     'foo': [1.222222, 1.333],
>>>     'bar': 1,
>>>     'baz': [],
>>> }
>>> dct2 = {
>>>     'foo': [1.22222, 1.333],
>>>     'bar': 1,
>>>     'baz': [],
>>> }
>>> assert indexable_allclose(dct1, dct2)
```

class kwcococo.util.SuppressPrint(*mods, **kw)Bases: `object`

Temporarily replace the print function in a module with a noop

Parameters

- ***mods** – the modules to disable print in
- ****kw** – only accepts “enabled” enabled (bool, default=True): enables or disables this context

```
__enter__(self)
__exit__(self, a, b, c)

class kwcoco.util.StratifiedGroupKFold(n_splits=3, shuffle=False, random_state=None)
    Bases: sklearn.model_selection._split._BaseKFold
    Stratified K-Folds cross-validator with Grouping
    Provides train/test indices to split data in train/test sets.
```

This cross-validation object is a variation of GroupKFold that returns stratified folds. The folds are made by preserving the percentage of samples for each class.

Read more in the User Guide.

Parameters `n_splits` (`int, default=3`) – Number of folds. Must be at least 2.

`_make_test_folds(self, X, y=None, groups=None)`

Parameters

- `X` (`ndarray`) – data
- `y` (`ndarray`) – labels
- `groups` (`ndarray`) – groupids for items. Items with the same groupid must be placed in the same group.

Returns `test_folds`

Return type `list`

Example

```
>>> import kwarray
>>> rng = kwarray.ensure_rng(0)
>>> groups = [1, 1, 3, 4, 2, 2, 7, 8, 8]
>>> y      = [1, 1, 1, 1, 2, 2, 2, 3, 3]
>>> X = np.empty((len(y), 0))
>>> self = StratifiedGroupKFold(random_state=rng, shuffle=True)
>>> skf_list = list(self.split(X=X, y=y, groups=groups))
...
>>> import ubelt as ub
>>> print(ub.repr2(skf_list, nl=1, with_dtype=False))
[
    (np.array([2, 3, 4, 5, 6]), np.array([0, 1, 7, 8])),
    (np.array([0, 1, 2, 7, 8]), np.array([3, 4, 5, 6])),
    (np.array([0, 1, 3, 4, 5, 6, 7, 8]), np.array([2]))
]
```

`_iter_test_masks(self, X, y=None, groups=None)`

Generates boolean masks corresponding to test sets.

By default, delegates to `_iter_test_indices(X, y, groups)`

`split(self, X, y, groups=None)`

Generate indices to split data into training and test set.

```
kwcoco.util.smart_truncate(string, max_length=0, separator=' ', trunc_loc=0.5)
```

Truncate a string. :param string (str): string for modification :param max_length (int): output string length :param word_boundary (bool): :param save_order (bool): if True then word order of output string is like input string :param separator (str): separator between words :param trunc_loc (float): fraction of location where to remove the text :return:

2.3 Submodules

2.3.1 kwcoco.__main__

2.3.2 kwcoco._helpers

These items were split out of coco_dataset.py which is becoming too big

These are helper data structures used to do things like auto-increment ids, recycle ids, do renaming, extend sortedcontainers etc...

Module Contents

Classes

<code>_NextId</code>	Helper class to tracks unused ids for new items
<code>_ID_Remapper</code>	Helper to recycle ids for unions.
<code>UniqueNameRemapper</code>	helper to ensure names will be unique by appending suffixes
<code>SortedSetQuiet</code>	Sorted set is a sorted mutable set.

Functions

```
_lut_frame_index(imgs, gid)
```

```
_delitems(items, remove_idxs, thresh=750)
```

Parameters

- **items** (*List*) -- list which will be modified
-

```
class kwcoco._helpers._NextId(parent)
```

Bases: `object`

Helper class to tracks unused ids for new items

```
_update_unused(self, key)
```

Scans for what the next safe id can be for key

```
get(self, key)
```

Get the next safe item id for key

```
class kwcoco._helpers._ID_Remapper(reuse=False)
```

Bases: `object`

Helper to recycle ids for unions.

For each dataset we create a mapping between each old id and a new id. If possible and reuse=True we allow the new id to match the old id. After each dataset is finished we mark all those ids as used and subsequent new-ids cannot be chosen from that pool.

Parameters `reuse (bool)` – if True we are allowed to reuse ids as long as they haven't been used before.

Example

```
>>> video_trackids = [[1, 1, 3, 3, 200, 4], [204, 1, 2, 3, 3, 4, 5, 9]]
>>> self = _ID_Remapper(reuse=True)
>>> for tids in video_trackids:
>>>     new_tids = [self.remap(old_tid) for old_tid in tids]
>>>     self.block_seen()
>>>     print('new_tids = {!r}'.format(new_tids))
new_tids = [1, 1, 3, 3, 200, 4]
new_tids = [204, 205, 2, 206, 206, 207, 5, 9]
>>> #
>>> self = _ID_Remapper(reuse=False)
>>> for tids in video_trackids:
>>>     new_tids = [self.remap(old_tid) for old_tid in tids]
>>>     self.block_seen()
>>>     print('new_tids = {!r}'.format(new_tids))
new_tids = [0, 0, 1, 1, 2, 3]
new_tids = [4, 5, 6, 7, 7, 8, 9, 10]
```

`remap(self, old_id)`

Convert a old-id into a new-id. If self.reuse is True then we will return the same id if it hasn't been blocked yet.

`block_seen(self)`

Mark all seen ids as unable to be used. Any ids sent to remap will now generate new ids.

`next_id(self)`

Generate a new id that hasnt been used yet

class kwcoco._helpers.UniqueNameRemapper

Bases: `object`

helper to ensure names will be unique by appending suffixes

Example

```
>>> from kwcoco.coco_dataset import * # NOQA
>>> self = UniqueNameRemapper()
>>> assert self.remap('foo') == 'foo'
>>> assert self.remap('foo') == 'foo_v001'
>>> assert self.remap('foo') == 'foo_v002'
>>> assert self.remap('foo_v001') == 'foo_v003'
```

`remap(self, name)`

`kwcoco._helpers._lut_frame_index(imgs, gid)`

```
class kwcoco._helpers.SortedSetQuiet(iterable=None, key=None)
```

Bases: sortedcontainers.SortedSet

Sorted set is a sorted mutable set.

Sorted set values are maintained in sorted order. The design of sorted set is simple: sorted set uses a set for set-operations and maintains a sorted list of values.

Sorted set values must be hashable and comparable. The hash and total ordering of values must not change while they are stored in the sorted set.

Mutable set methods:

- `SortedSet.__contains__()`
- `SortedSet.__iter__()`
- `SortedSet.__len__()`
- `SortedSet.add()`
- `SortedSet.discard()`

Sequence methods:

- `SortedSet.__getitem__()`
- `SortedSet.__delitem__()`
- `SortedSet.__reversed__()`

Methods for removing values:

- `SortedSet.clear()`
- `SortedSet.pop()`
- `SortedSet.remove()`

Set-operation methods:

- `SortedSet.difference()`
- `SortedSet.difference_update()`
- `SortedSet.intersection()`
- `SortedSet.intersection_update()`
- `SortedSet.symmetric_difference()`
- `SortedSet.symmetric_difference_update()`
- `SortedSet.union()`
- `SortedSet.update()`

Methods for miscellany:

- `SortedSet.copy()`
- `SortedSet.count()`
- `SortedSet.__repr__()`
- `SortedSet._check()`

Sorted list methods available:

- `SortedList.bisect_left()`

- `SortedList.bisect_right()`
- `SortedList.index()`
- `SortedList.irange()`
- `SortedList.islice()`
- `SortedList._reset()`

Additional sorted list methods available, if key-function used:

- `SortedKeyList.bisect_key_left()`
- `SortedKeyList.bisect_key_right()`
- `SortedKeyList.irange_key()`

Sorted set comparisons use subset and superset relations. Two sorted sets are equal if and only if every element of each sorted set is contained in the other (each is a subset of the other). A sorted set is less than another sorted set if and only if the first sorted set is a proper subset of the second sorted set (is a subset, but is not equal). A sorted set is greater than another sorted set if and only if the first sorted set is a proper superset of the second sorted set (is a superset, but is not equal).

`__repr__(self)`

Return string representation of sorted set.

`ss.__repr__() <==> repr(ss)`

Returns string representation

`kwcoco._helpers._delitems(items, remove_idxs, thresh=750)`

Parameters

- `items (List)` – list which will be modified
- `remove_idxs (List[int])` – integers to remove (MUST BE UNIQUE)

2.3.3 kwcoco.abstract_coco_dataset

Module Contents

Classes

<code>AbstractCocoDataset</code>	This is a common base for all variants of the Coco Dataset
----------------------------------	--

`class kwcoco.abstract_coco_dataset.AbstractCocoDataset`

Bases: `abc.ABC`

This is a common base for all variants of the Coco Dataset

At the time of writing there is `kwcoco.CocoDataset` (which is the dictionary-based backend), and the `kwcoco.coco_sql_dataset.CocoSqlDataset`, which is experimental.

2.3.4 kwcoco.category_tree

The `category_tree` module defines the `CategoryTree` class, which is used for maintaining flat or hierarchical category information. The kwcoco version of this class only contains the datastructure and does not contain any torch operations. See the ndsampler version for the extension with torch operations.

Module Contents

Classes

<code>CategoryTree</code>	Wrapper that maintains flat or hierarchical category information.
---------------------------	---

`class kwcoco.category_tree.CategoryTree(graph=None, checks=True)`

Bases: `ubelt.NiceRepr`

Wrapper that maintains flat or hierarchical category information.

Helps compute softmaxes and probabilities for tree-based categories where a directed edge (A, B) represents that A is a superclass of B.

Note: There are three basic properties that this object maintains:

`node`:

Alphanumeric string names that should be generally descriptive. Using spaces `and` special characters `in` these names `is` discouraged, but can be done. This `is` the COCO category "name" attribute. For categories this may be denoted `as` (name, node, cname, catname).

`id`:

The integer `id` of a category should ideally remain consistent. These are often given by a dataset (e.g. a COCO dataset). This `is` the COCO category "id" attribute. For categories this `is` often denoted `as` (id, cid).

`index`:

Contiguous zero-based indices that indexes the `list` of categories. These should be used `for` the fastest access `in` backend computation tasks. Typically corresponds to the ordering of the channels `in` the final linear layer `in` an associated model. For categories this `is` often denoted `as` (index, cidx, idx, `or` cx).

Variables

- `idx_to_node` (`List[str]`) – a list of class names. Implicitly maps from index to category name.
- `id_to_node` (`Dict[int, str]`) – maps integer ids to category names
- `node_to_id` (`Dict[str, int]`) – maps category names to ids

- **node_to_idx** (*Dict[str, int]*) – maps category names to indexes
- **graph** (*networkx.Graph*) – a Graph that stores any hierarchy information. For standard mutually exclusive classes, this graph is edgeless. Nodes in this graph can maintain category attributes / properties.
- **idx_groups** (*List[List[int]]*) – groups of category indices that share the same parent category.

Example

```
>>> from kwcoco.category_tree import *
>>> graph = nx.from_dict_of_lists({
>>>     'background': [],
>>>     'foreground': ['animal'],
>>>     'animal': ['mammal', 'fish', 'insect', 'reptile'],
>>>     'mammal': ['dog', 'cat', 'human', 'zebra'],
>>>     'zebra': ['grevys', 'plains'],
>>>     'grevys': ['fred'],
>>>     'dog': ['boxer', 'beagle', 'golden'],
>>>     'cat': ['maine coon', 'persian', 'sphynx'],
>>>     'reptile': ['bearded dragon', 't-rex'],
>>> }, nx.DiGraph)
>>> self = CategoryTree(graph)
>>> print(self)
<CategoryTree(nNodes=22, maxDepth=6, maxBreadth=4...)>
```

Example

```
>>> # The coerce classmethod is the easiest way to create an instance
>>> import kwcoco
>>> kwcoco.CategoryTree.coerce(['a', 'b', 'c'])
<CategoryTree...nNodes=3, nodes='a', 'b', 'c'...
>>> kwcoco.CategoryTree.coerce(4)
<CategoryTree...nNodes=4, nodes='class_1', 'class_2', 'class_3', ...
>>> kwcoco.CategoryTree.coerce(4)
```

```
copy(self)
classmethod from_mutex(cls, nodes, bg_hack=True)
```

Parameters **nodes** (*List[str]*) – or a list of class names (in which case they will all be assumed to be mutually exclusive)

Example

```
>>> print(CategoryTree.from_mutex(['a', 'b', 'c']))
<CategoryTree(nNodes=3, ...)>
```

classmethod from_json(*cls, state*)

Parameters state (*Dict*) – see `__getstate__` / `__json__` for details

classmethod from_coco(*cls, categories*)

Create a CategoryTree object from coco categories

Parameters List[*Dict*] – list of coco-style categories

classmethod coerce(*cls, data, **kw*)

Attempt to coerce data as a CategoryTree object.

This is primarily useful for when the software stack depends on categories being represented

This will work if the input data is a specially formatted json dict, a list of mutually exclusive classes, or if it is already a CategoryTree. Otherwise an error will be thrown.

Parameters

- **data (*object*)** – a known representation of a category tree.
- ****kwargs** – input type specific arguments

Returns self

Return type *CategoryTree*

Raises

- **TypeError** – if the input format is unknown –
- **ValueError** – if kwargs are not compatible with the input format –

Example

```
>>> import kwcoco
>>> classes1 = kwcoco.CategoryTree.coerce(3) # integer
>>> classes2 = kwcoco.CategoryTree.coerce(classes1.__json__()) # graph dict
>>> classes3 = kwcoco.CategoryTree.coerce(['class_1', 'class_2', 'class_3']) # _mutex list
>>> classes4 = kwcoco.CategoryTree.coerce(classes1.graph) # nx Graph
>>> classes5 = kwcoco.CategoryTree.coerce(classes1) # cls
>>> # xdoctest: +REQUIRES(module:nd sampler)
>>> import nd sampler
>>> classes6 = nd sampler.CategoryTree.coerce(3)
>>> classes7 = nd sampler.CategoryTree.coerce(classes1)
>>> classes8 = kwcoco.CategoryTree.coerce(classes6)
```

classmethod demo(*cls, key='coco', **kwargs*)

Parameters key (*str*) – specify which demo dataset to use. Can be ‘coco’ (which uses the default coco demo data). Can be ‘btree’ which creates a binary tree and accepts kwargs ‘r’ and ‘h’ for branching-factor and height. Can be ‘btree2’, which is the same as btree but returns strings

CommandLine

```
xdoc test -m ~/code/kwcoco/kwcoco/category_tree.py CategoryTree.demo
```

Example

```
>>> from kwcoco.category_tree import *
>>> self = CategoryTree.demo()
>>> print('self = {}'.format(self))
self = <CategoryTree(nNodes=10, maxDepth=2, maxBreadth=4...)>
```

`to_coco(self)`

Converts to a coco-style data structure

Yields *Dict* – coco category dictionaries

`id_to_idx(self)`

Example

```
>>> import kwcoco
>>> self = kwcoco.CategoryTree.demo()
>>> self.id_to_idx[1]
```

`idx_to_id(self)`

Example

```
>>> import kwcoco
>>> self = kwcoco.CategoryTree.demo()
>>> self.idx_to_id[0]
```

`idx_to_ancestor_idxs(self, include_self=True)`

Mapping from a class index to its ancestors

Parameters `include_self (bool, default=True)` – if True includes each node as its own ancestor.

`idx_to_descendants_idxs(self, include_self=False)`

Mapping from a class index to its descendants (including itself)

Parameters `include_self (bool, default=False)` – if True includes each node as its own descendant.

`idx_pairwise_distance(self)`

Get a matrix encoding the distance from one class to another.

Distances

- from parents to children are positive (descendants),
- from children to parents are negative (ancestors),
- between unreachable nodes (wrt to forward and reverse graph) are nan.

`__len__(self)`

```
__iter__(self)
__getitem__(self, index)
__contains__(self, node)
__json__(self)
```

Example

```
>>> import pickle
>>> self = CategoryTree.demo()
>>> print('self = {!r}'.format(self.__json__()))
```

```
__getstate__(self)
Serializes information in this class
```

Example

```
>>> from kwcoco.category_tree import *
>>> import pickle
>>> self = CategoryTree.demo()
>>> state = self.__getstate__()
>>> serialization = pickle.dumps(self)
>>> recon = pickle.loads(serialization)
>>> assert recon.__json__() == self.__json__()
```

```
__setstate__(self, state)
__nice__(self)
is_mutex(self)
Returns True if all categories are mutually exclusive (i.e. flat)

If true, then the classes may be represented as a simple list of class names without any loss of information,
otherwise the underlying category graph is necessary to preserve all knowledge.
```

Todo:

- [] what happens when we have a dummy root?
-

```
property num_classes(self)
property class_names(self)
property category_names(self)
property cats(self)
Returns a mapping from category names to category attributes.

If this category tree was constructed from a coco-dataset, then this will contain the coco category attributes.

>Returns Dict[str, Dict[str, object]]
```

Example

```
>>> from kwCOCO.category_tree import *
>>> self = CategoryTree.demo()
>>> print('self.cats = {!r}'.format(self.cats))
```

index(self, node)

Return the index that corresponds to the category name

_build_index(self)

construct lookup tables

show(self)

forest_str(self)

normalize(self)

Applies a normalization scheme to the categories.

Note: this may break other tasks that depend on exact category names.

Returns CategoryTree

Example

```
>>> from kwCOCO.category_tree import * # NOQA
>>> import kwCOCO
>>> orig = kwCOCO.CategoryTree.demo('animals_v1')
>>> self = kwCOCO.CategoryTree(nx.relabel_nodes(orig.graph, str.upper))
>>> norm = self.normalize()
```

2.3.5 kwCOCO.channel_spec

This module defines the KWCOCO Channel Specification and API.

The KWCOCO Channel specification is a way to semantically express how a combination of image channels are grouped. This can specify how these channels (sometimes called bands or features) are arranged on disk or input to an algorithm. The core idea reduces to a Set[List[str]] — or a unordered set of ordered sequences of strings corresponding to channel “names”. The way these are specified is with a “,” to separate lists in an unordered set and with a “|” to separate the channel names. Other syntax exists for convinience, but a strict normalized channel spec only contains these core symbols.

Another way to think of a kwCOCO channel spec is that splitting the spec by “,” gives groups of channels that should be processed together and “late-fused”. Within each group the “|” operator “early-fuses” the channels.

For instance, say we had a network and we wanted to process 3-channel rgb images in one stream and 1-channel infrared images in a second stream and then fuse them together. The kwCOCO channel specification for channels labeled as ‘red’, ‘green’, ‘blue’, and ‘infrared’ would be:

infrared,red|green|blue

Note, it is up to an algorithm to do any early-late fusion. KWCOCO simply provides the specification as a tool to quickly access a particular combination of channels from disk.

The ChannelSpec has these simple rules:

```
* each 1D channel is a alphanumeric string.  
  
* The pipe ('|') separates aligned early fused stremas (non-communative)  
  
* The comma (',') separates late-fused streams, (happens after pipe operations, and is  
→communative)  
  
* Certain common sets of early fused channels have codenames, for example:  
  
    rgb = r|g|b  
    rgba = r|g|b|a  
    dxdy = dy|dy  
  
* Multiple channels can be specified via a "slice" notation. For example:  
  
    mychan.0:4  
  
    represents 4 channels:  
        mychan.0, mychan.1, mychan.2, and mychan.3  
  
    slices after the "." work like python slices
```

For single arrays, the spec is always an early fused spec.

Todo:

- [X] : normalize representations? e.g: rgb = r|g|b? - OPTIONAL
 - [X] : rename to BandsSpec or SensorSpec? - REJECTED
 - [] : allow bands to be coerced, i.e. rgb -> gray, or gray->rgb
-

Todo:

- [x]: Use FusedChannelSpec as a member of ChannelSpec
 - [x]: Handle special slice suffix for length calculations
-

Note:

- do not specify the same channel in FusedChannelSpec twice
-

Example

```
>>> import kwcoco
>>> spec = kwcoco.ChannelSpec('b1|b2|b3,m.0:4|x1|x2,x.3|x.4|x.5')
>>> print(spec)
<ChannelSpec(b1|b2|b3,m.0:4|x1|x2,x.3|x.4|x.5)>
>>> for stream in spec.streams():
>>>     print(stream)
<FusedChannelSpec(b1|b2|b3)>
<FusedChannelSpec(m.0:4|x1|x2)>
<FusedChannelSpec(x.3|x.4|x.5)>
>>> # Normalization
>>> normalized = spec.normalize()
>>> print(normalized)
<ChannelSpec(b1|b2|b3,m.0|m.1|m.2|m.3|x1|x2,x.3|x.4|x.5)>
>>> print(normalized.fuse().spec)
b1|b2|b3|m.0|m.1|m.2|m.3|x1|x2|x.3|x.4|x.5
>>> print(normalized.fuse().concise().spec)
b1|b2|b3|m:4|x1|x2|x.3:6
```

Module Contents

Classes

<code>BaseChannelSpec</code>	Common code API between <code>FusedChannelSpec</code> and <code>ChannelSpec</code>
<code>FusedChannelSpec</code>	A specific type of channel spec with only one early fused stream.
<code>ChannelSpec</code>	Parse and extract information about network input channel specs for

Functions

<code>_cached_single_fused_mapping(item_keys,</code> <code>parsed_items, axis=0)</code>	
<code>_cached_single_stream_idxs(key, axis=0)</code>	
<code>subsequence_index(ose1, oset2)</code>	Returns a slice into the first items indicating the position of
<code>_parse_concise_slice_syntax(v)</code>	Helper for our slice syntax, which is may be a bit strange

<code>ose1_insert(self, index, obj)</code>	
	for ubelt oset, todo contribute back to luminosoinsight

`class kwcoco.channel_spec.BaseChannelSpec`
Bases: `ubelt.NiceRepr`
Common code API between `FusedChannelSpec` and `ChannelSpec`

Todo:

- [] Keep working on this base spec and ensure the inheriting classes conform to it.
-

property `spec(self)`

The string encodeing of this spec

Returns str

abstract classmethod `coerce(cls, data)`

Try and interpret the input data as some sort of spec

Parameters `data` (`str | int | list | dict | BaseChannelSpec`) – any input data that is known to represent a spec

Returns BaseChannelSpec

abstract `streams(self)`

Breakup this spec into individual early-fused components

Returns List[FusedChannelSpec]

abstract `normalize(self)`

Expand all channel codes into their normalized long-form

Returns BaseChannelSpec

abstract `intersection(self, other)`**abstract** `union(self, other)`**abstract** `difference(self)`**abstract** `issubset(self, other)`**abstract** `issuperset(self, other)`**__sub__(self, other)****__nice__(self)****__json__(self)****__and__(self, other)****__or__(self, other)****path_sanitize(self)**

Clean up the channel spec so it can be used in a pathname.

Returns path suitable for usage in a filename

Return type str

Note: This mapping is not invertible and should not be relied on to reconstruct the path spec. This is only a convenience.

Example

```
>>> import kwcoco
>>> print(kwcoco.FusedChannelSpec.coerce('a chan with space|bar|baz').path_
>>>     _sanitize())
a chan with space_bar_baz
>>> print(kwcoco.ChannelSpec.coerce('foo|bar|baz,biz').path_sanitize())
foo_bar_baz,biz
```

class kwcoco.channel_spec.FusedChannelSpec(*parsed*, *_is_normalized=False*)
Bases: *BaseChannelSpec*

A specific type of channel spec with only one early fused stream.

The channels in this stream are non-commutative

Behaves like a list of atomic-channel codes (which may represent more than 1 channel), normalized codes always represent exactly 1 channel.

Note: This class name and API is in flux and subject to change.

Todo: A special code indicating a name and some number of bands that that names contains, this would primarily be used for large numbers of channels produced by a network. Like:

resnet_d35d060_L5:512

or

resnet_d35d060_L5[:512]

might refer to a very specific (hashed) set of resnet parameters with 512 bands

maybe we can do something slicily like:

resnet_d35d060_L5[A:B] resnet_d35d060_L5:A:B

Do we want to “just store the code” and allow for parsing later?

Or do we want to ensure the serialization is parsed before we construct the data structure?

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> import pickle
>>> self = FusedChannelSpec.coerce(3)
>>> recon = pickle.loads(pickle.dumps(self))
>>> self = ChannelSpec.coerce('a|b,c|d')
>>> recon = pickle.loads(pickle.dumps(self))
```

_alias_lut

_memo

_size_lut

__len__(self)

```
__getitem__(self, index)
classmethod concat(cls, items)
spec(self)
    The string encodeing of this spec

    Returns str

unique(self)

classmethod parse(cls, spec)
classmethod coerce(cls, data)
```

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> FusedChannelSpec.coerce(['a', 'b', 'c'])
>>> FusedChannelSpec.coerce('a|b|c')
>>> FusedChannelSpec.coerce(3)
>>> FusedChannelSpec.coerce(FusedChannelSpec(['a']))
>>> assert FusedChannelSpec.coerce('') .numel() == 0
```

concise(self)
Shorted the channel spec by de-normaliz slice syntax

Returns concise spec
Return type *FusedChannelSpec*

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> self = FusedChannelSpec.coerce(
>>>     'b|a|a.0|a.1|a.2|a.5|c|a.8|a.9|b.0:3|c.0')
>>> short = self.concise()
>>> long = short.normalize()
>>> numels = [c.numel() for c in [self, short, long]]
>>> print('self.spec = {!r}'.format(self.spec))
>>> print('short.spec = {!r}'.format(short.spec))
>>> print('long.spec = {!r}'.format(long.spec))
>>> print('numels = {!r}'.format(numels))
self.spec = 'b|a|a.0|a.1|a.2|a.5|c|a.8|a.9|b.0:3|c.0'
short.spec = 'b|a|a:3|a.5|c|a.8:10|b:3|c.0'
long.spec = 'b|a|a.0|a.1|a.2|a.5|c|a.8|a.9|b.0|b.1|b.2|c.0'
numels = [13, 13, 13]
>>> assert long.concise().spec == short.spec
```

normalize(self)
Replace aliases with explicit single-band-per-code specs

 Returns normalize spec
Return type *FusedChannelSpec*

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> self = FusedChannelSpec.coerce('b1|b2|b3|rgb')
>>> normed = self.normalize()
>>> print('self = {}'.format(self))
>>> print('normed = {}'.format(normed))
self = <FusedChannelSpec(b1|b2|b3|rgb)>
normed = <FusedChannelSpec(b1|b2|b3|r|g|b)>
>>> self = FusedChannelSpec.coerce('B:1:11')
>>> normed = self.normalize()
>>> print('self = {}'.format(self))
>>> print('normed = {}'.format(normed))
self = <FusedChannelSpec(B:1:11)>
normed = <FusedChannelSpec(B.1|B.2|B.3|B.4|B.5|B.6|B.7|B.8|B.9|B.10)>
>>> self = FusedChannelSpec.coerce('B.1:11')
>>> normed = self.normalize()
>>> print('self = {}'.format(self))
>>> print('normed = {}'.format(normed))
self = <FusedChannelSpec(B.1:11)>
normed = <FusedChannelSpec(B.1|B.2|B.3|B.4|B.5|B.6|B.7|B.8|B.9|B.10>
```

numel(self)

Total number of channels in this spec

sizes(self)

Returns a list indicating the size of each atomic code

Returns List[int]**Example**

```
>>> from kwcoco.channel_spec import * # NOQA
>>> self = FusedChannelSpec.coerce('b1|Z:3|b2|b3|rgb')
>>> self.sizes()
[1, 3, 1, 1, 3]
>>> assert(FusedChannelSpec.parse('a.0').numel() == 1
>>> assert(FusedChannelSpec.parse('a:0').numel() == 0
>>> assert(FusedChannelSpec.parse('a:1').numel() == 1
```

__contains__(self, key)**Example**

```
>>> FCS = FusedChannelSpec.coerce
>>> 'disparity' in FCS('rgb|disparity|flowx|flowy')
True
>>> 'gray' in FCS('rgb|disparity|flowx|flowy')
False
```

code_list(self)

Return the expanded code list

as_list(self)**as_oset(self)****as_set(self)****as_path(self)**

Returns a string suitable for use in a path.

Note, this may no longer be a valid channel spec

__set__(self)**difference(self, other)**

Set difference

Example

```
>>> FCS = FusedChannelSpec.coerce
>>> self = FCS('rgb|disparity|flowx|flowy')
>>> other = FCS('r|b')
>>> self.difference(other)
>>> other = FCS('flowx')
>>> self.difference(other)
>>> FCS = FusedChannelSpec.coerce
>>> assert len((FCS('a') - {'a'}).parsed) == 0
>>> assert len((FCS('a.0:3') - {'a.0'}).parsed) == 2
```

intersection(self, other)

Example

```
>>> FCS = FusedChannelSpec.coerce
>>> self = FCS('rgb|disparity|flowx|flowy')
>>> other = FCS('r|b|XX')
>>> self.intersection(other)
```

union(self, other)

Example

```
>>> from kwcocoo.channel_spec import * # NOQA
>>> FCS = FusedChannelSpec.coerce
>>> self = FCS('rgb|disparity|flowx|flowy')
>>> other = FCS('r|b|XX')
>>> self.union(other)
```

issubset(self, other)**issuperset(self, other)****component_indices(self, axis=2)**

Look up component indices within this stream

Example

```
>>> FCS = FusedChannelSpec.coerce
>>> self = FCS('disparity|rgb|flowx|flowy')
>>> component_indices = self.component_indices()
>>> print('component_indices = {}'.format(ub.repr2(component_indices, nl=1)))
component_indices =
    'disparity': (slice(...), slice(...), slice(0, 1, None)),
    'flowx': (slice(...), slice(...), slice(4, 5, None)),
    'flowy': (slice(...), slice(...), slice(5, 6, None)),
    'rgb': (slice(...), slice(...), slice(1, 4, None)),
}
```

`streams(self)`

Idempotence with `ChannelSpec.streams()`

`fuse(self)`

Idempotence with `ChannelSpec.streams()`

class kwcoco.channel_spec.ChannelSpec(spec, parsed=None)

Bases: `BaseChannelSpec`

Parse and extract information about network input channel specs for early or late fusion networks.

Behaves like a dictionary of `FusedChannelSpec` objects

Todo:

- [] Rename to something that indicates this is a collection of `FusedChannelSpec`? `MultiChannelSpec`?

Note: This class name and API is in flux and subject to change.

Note: The pipe ('|') character represents an early-fused input stream, and order matters (it is non-commutative).

The comma (',') character separates different inputs streams/branches for a multi-stream/branch network which will be later fused. Order does not matter

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> # Integer spec
>>> ChannelSpec.coerce(3)
<ChannelSpec(u0|u1|u2) ...>
```

```
>>> # single mode spec
>>> ChannelSpec.coerce('rgb')
<ChannelSpec(rgb) ...>
```

```
>>> # early fused input spec
>>> ChannelSpec.coerce('rgb|disparity')
<ChannelSpec(rgb|disparity) ...>
```

```
>>> # late fused input spec
>>> ChannelSpec.coerce('rgb,disparity')
<ChannelSpec(rgb,disparity) ...>
```

```
>>> # early and late fused input spec
>>> ChannelSpec.coerce('rgb|ir,disparity')
<ChannelSpec(rgb|ir,disparity) ...>
```

Example

```
>>> self = ChannelSpec('gray')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>> self = ChannelSpec('rgb')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>> self = ChannelSpec('rgb|disparity')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>> self = ChannelSpec('rgb|disparity,disparity')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>> self = ChannelSpec('rgb,disparity,flowx|flowy')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
```

Example

```
>>> specs = [
>>>     'rgb',           # and rgb input
>>>     'rgb|disparity', # rgb early fused with disparity
>>>     'rgb,disparity', # rgb early late with disparity
>>>     'rgb|ir,disparity', # rgb early fused with ir and late fused with disparity
>>>     3,               # 3 unknown channels
>>> ]
>>> for spec in specs:
>>>     print('=====')
>>>     print('spec = {!r}'.format(spec))
>>>     #
>>>     self = ChannelSpec.coerce(spec)
>>>     print('self = {!r}'.format(self))
>>>     sizes = self.sizes()
>>>     print('sizes = {!r}'.format(sizes))
>>>     print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>>     #
>>>     item = self._demo_item((1, 1), rng=0)
>>>     inputs = self.encode(item)
>>>     components = self.decode(inputs)
>>>     input_shapes = ub.map_vals(lambda x: x.shape, inputs)
>>>     component_shapes = ub.map_vals(lambda x: x.shape, components)
```

(continues on next page)

(continued from previous page)

```
>>> print('item = {}'.format(ub.repr2(item, precision=1)))
>>> print('inputs = {}'.format(ub.repr2(inputs, precision=1)))
>>> print('input_shapes = {}'.format(ub.repr2(input_shapes)))
>>> print('components = {}'.format(ub.repr2(components, precision=1)))
>>> print('component_shapes = {}'.format(ub.repr2(component_shapes, nl=1)))
```

property spec(self)

The string encodeing of this spec

Returns str**__contains__(self, key)****Example**

```
>>> 'disparity' in ChannelSpec('rgb,disparity,flowx|flowy')
True
>>> 'gray' in ChannelSpec('rgb,disparity,flowx|flowy')
False
```

property info(self)**classmethod coerce(cls, data)**

Attempt to interpret the data as a channel specification

Returns ChannelSpec**Example**

```
>>> from kwcoco.channel_spec import * # NOQA
>>> data = FusedChannelSpec.coerce(3)
>>> assert ChannelSpec.coerce(data).spec == 'u0|u1|u2'
>>> data = ChannelSpec.coerce(3)
>>> assert data.spec == 'u0|u1|u2'
>>> assert ChannelSpec.coerce(data).spec == 'u0|u1|u2'
>>> data = ChannelSpec.coerce('u:3')
>>> assert data.normalize().spec == 'u.0|u.1|u.2'
```

parse(self)

Build internal representation

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> self = ChannelSpec('b1|b2|b3|rgb,B:3')
>>> print(self.parse())
>>> print(self.normalize().parse())
>>> ChannelSpec('').parse()
```

Example

```
>>> base = ChannelSpec('rgb|disparity,flowx|r|flowy')
>>> other = ChannelSpec('rgb')
>>> self = base.intersection(other)
>>> assert self.numel() == 4
```

concise(self)**Example**

```
>>> self = ChannelSpec('b1|b2,b3|rgb|B.0,B.1|B.2')
>>> print(self.concise().spec)
b1|b2,b3|r|g|b|B.0,B.1:3
```

normalize(self)

Replace aliases with explicit single-band-per-code specs

Returns normalized spec

Return type *ChannelSpec*

Example

```
>>> self = ChannelSpec('b1|b2,b3|rgb,B:3')
>>> normed = self.normalize()
>>> print('self = {}'.format(self))
>>> print('normed = {}'.format(normed))
self = <ChannelSpec(b1|b2,b3|rgb,B:3)>
normed = <ChannelSpec(b1|b2,b3|r|g|b,B.0|B.1|B.2)>
```

keys(self)**values(self)****items(self)****fuse(self)**

Fuse all parts into an early fused channel spec

Returns FusedChannelSpec

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> self = ChannelSpec.coerce('b1|b2,b3|rgb,B:3')
>>> fused = self.fuse()
>>> print('self = {}'.format(self))
>>> print('fused = {}'.format(fused))
self = <ChannelSpec(b1|b2,b3|rgb,B:3)>
fused = <FusedChannelSpec(b1|b2|b3|rgb|B:3)>
```

streams(self)

Breaks this spec up into one spec for each early-fused input stream

Example

```
self = ChannelSpec.coerce('r|g,B1|B2,fx|fy') list(map(len, self.streams()))
code_list(self)
as_path(self)
```

Returns a string suitable for use in a path.

Note, this may no longer be a valid channel spec

difference(self, other)

Set difference. Remove all instances of other channels from this set of channels.

Example

```
>>> from kwcoco.channel_spec import *
>>> self = ChannelSpec('rgb|disparity,flowx|r|flowy')
>>> other = ChannelSpec('rgb')
>>> print(self.difference(other))
>>> other = ChannelSpec('flowx')
>>> print(self.difference(other))
<ChannelSpec(disparity,flowx|flowy)>
<ChannelSpec(r|g|b|disparity,r|flowy)>
```

Example

```
>>> from kwcoco.channel_spec import *
>>> self = ChannelSpec('a|b,c|d')
>>> new = self - {'a', 'b'}
>>> len(new.sizes()) == 1
>>> empty = new - 'c|d'
>>> assert empty.numel() == 0
```

intersection(self, other)

Set difference. Remove all instances of other channels from this set of channels.

Example

```
>>> from kwcoco.channel_spec import *
>>> self = ChannelSpec('rgb|disparity,flowx|r|flowy')
>>> other = ChannelSpec('rgb')
>>> new = self.intersection(other)
>>> print(new)
>>> print(new.numel())
>>> other = ChannelSpec('flowx')
>>> new = self.intersection(other)
>>> print(new)
>>> print(new.numel())
<ChannelSpec(r|g|b,r)>
4
```

(continues on next page)

(continued from previous page)

```
<ChannelSpec(flowx)>
1
```

union(self, other)

Union simply tags on a second channel spec onto this one. Duplicates are maintained.

Example

```
>>> from kwcoco.channel_spec import *
>>> self = ChannelSpec('rgb|disparity,flowx|r|flowy')
>>> other = ChannelSpec('rgb')
>>> new = self.union(other)
>>> print(new)
>>> print(new.numel())
>>> other = ChannelSpec('flowx')
>>> new = self.union(other)
>>> print(new)
>>> print(new.numel())
<ChannelSpec(r|g|b|disparity,flowx|r|flowy,r|g|b)>
10
<ChannelSpec(r|g|b|disparity,flowx|r|flowy,flowx)>
8
```

abstract issubset(self, other)**abstract issuperset(self, other)****numel(self)**

Total number of channels in this spec

sizes(self)

Number of dimensions for each fused stream channel

IE: The EARLY-FUSED channel sizes

Example

```
>>> self = ChannelSpec('rgb|disparity,flowx|flowy,B:10')
>>> self.normalize().concise()
>>> self.sizes()
```

unique(self, normalize=False)

Returns the unique channels that will need to be given or loaded

_item_shapes(self, dims)

Expected shape for an input item

Parameters **dims** (*Tuple[int, int]*) – the spatial dimension

Returns *Dict[int, tuple]*

_demo_item(self, dims=(4, 4), rng=None)

Create an input that satisfies this spec

Returns

an item like it might appear when its returned from the `__getitem__` method of a `torch...Dataset`.

Return type `dict`

Example

```
>>> dims = (1, 1)
>>> ChannelSpec.coerce(3).demo_item(dims, rng=0)
>>> ChannelSpec.coerce('r|g|b|disparity').demo_item(dims, rng=0)
>>> ChannelSpec.coerce('rgb|disparity').demo_item(dims, rng=0)
>>> ChannelSpec.coerce('rgb,disparity').demo_item(dims, rng=0)
>>> ChannelSpec.coerce('rgb').demo_item(dims, rng=0)
>>> ChannelSpec.coerce('gray').demo_item(dims, rng=0)
```

encode(self, item, axis=0, mode=1)

Given a dictionary containing preloaded components of the network inputs, build a concatenated (fused) network representations of each input stream.

Parameters

- **item** (`Dict[str, Tensor]`) – a batch item containing unfused parts. each key should be a single-stream (optionally early fused) channel key.
- **axis** (`int, default=0`) – concatenation dimension

Returns mapping between input stream and its early fused tensor input.

Return type `Dict[str, Tensor]`

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> import numpy as np
>>> dims = (4, 4)
>>> item = {
>>>     'rgb': np.random.rand(3, *dims),
>>>     'disparity': np.random.rand(1, *dims),
>>>     'flowx': np.random.rand(1, *dims),
>>>     'flowy': np.random.rand(1, *dims),
>>> }
>>> # Complex Case
>>> self = ChannelSpec('rgb,disparity,rgb|disparity|flowx|flowy,flowx|flowy')
>>> fused = self.encode(item)
>>> input_shapes = ub.map_vals(lambda x: x.shape, fused)
>>> print('input_shapes = {}'.format(ub.repr2(input_shapes, nl=1)))
>>> # Simpler case
>>> self = ChannelSpec('rgb|disparity')
>>> fused = self.encode(item)
>>> input_shapes = ub.map_vals(lambda x: x.shape, fused)
>>> print('input_shapes = {}'.format(ub.repr2(input_shapes, nl=1)))
```

Example

```
>>> # Case where we have to break up early fused data
>>> import numpy as np
>>> dims = (40, 40)
>>> item = {
>>>     'rgb|disparity': np.random.rand(4, *dims),
>>>     'flowx': np.random.rand(1, *dims),
>>>     'flowy': np.random.rand(1, *dims),
>>> }
>>> # Complex Case
>>> self = ChannelSpec('rgb,disparity,rgb|disparity,rgb|disparity|flowx|flowy',
>>>                     ~flowx|flowy,flowx,disparity')
>>> inputs = self.encode(item)
>>> input_shapes = ub.map_vals(lambda x: x.shape, inputs)
>>> print('input_shapes = {}'.format(ub.repr2(input_shapes, nl=1)))
```

```
>>> # xdoctest: +REQUIRES(--bench)
>>> #self = ChannelSpec('rgb/disparity,flowx/flowy')
>>> import timerit
>>> ti = timerit.Timerit(100, bestof=10, verbose=2)
>>> for timer in ti.reset('mode=simple'):
>>>     with timer:
>>>         inputs = self.encode(item, mode=0)
>>> for timer in ti.reset('mode=minimize-concat'):
>>>     with timer:
>>>         inputs = self.encode(item, mode=1)
```

`decode(self, inputs, axis=1)`
break an early fused item into its components

Parameters

- `inputs` (`Dict[str, Tensor]`) – dictionary of components
- `axis` (`int, default=1`) – channel dimension

Example

```
>>> from kwcoco.channel_spec import *  # NOQA
>>> import numpy as np
>>> dims = (4, 4)
>>> item_components = {
>>>     'rgb': np.random.rand(3, *dims),
>>>     'ir': np.random.rand(1, *dims),
>>> }
>>> self = ChannelSpec('rgb|ir')
>>> item_encoded = self.encode(item_components)
>>> batch = {k: np.concatenate([v[None, :], v[None, :]], axis=0)
>>>           for k, v in item_encoded.items()}
>>> components = self.decode(batch)
```

Example

```
>>> # xdoctest: +REQUIRES(module:netharn, module:torch)
>>> import torch
>>> import numpy as np
>>> dims = (4, 4)
>>> components = {
>>>     'rgb': np.random.rand(3, *dims),
>>>     'ir': np.random.rand(1, *dims),
>>> }
>>> components = ub.map_vals(torch.from_numpy, components)
>>> self = ChannelSpec('rgb|ir')
>>> encoded = self.encode(components)
>>> from netharn.data import data_containers
>>> item = {k: data_containers.ItemContainer(v, stack=True)
>>>          for k, v in encoded.items()}
>>> batch = data_containers.container_collate([item, item])
>>> components = self.decode(batch)
```

`component_indices(self, axis=2)`

Look up component indices within fused streams

Example

```
>>> dims = (4, 4)
>>> inputs = ['flowx', 'flowy', 'disparity']
>>> self = ChannelSpec('disparity,flowx|flowy')
>>> component_indices = self.component_indices()
>>> print('component_indices = {}'.format(ub.repr2(component_indices, nl=1)))
component_indices = {
    'disparity': ('disparity', (slice(None, None, None), slice(None, None, None), slice(0, 1, None))),
    'flowx': ('flowx|flowy', (slice(None, None, None), slice(None, None, None), slice(0, 1, None))),
    'flowy': ('flowx|flowy', (slice(None, None, None), slice(None, None, None), slice(1, 2, None))),
}
```

`kwcoco.channel_spec._cached_single_fused_mapping(item_keys, parsed_items, axis=0)`

`kwcoco.channel_spec._cached_single_stream_idxs(key, axis=0)`

`kwcoco.channel_spec.subsequence_index(oset1, oset2)`

Returns a slice into the first items indicating the position of the second items if they exist.

This is a variant of the substring problem.

Returns None | slice

Example

```
>>> oset1 = ub.oset([1, 2, 3, 4, 5, 6])
>>> oset2 = ub.oset([2, 3, 4])
>>> index = subsequence_index(oset1, oset2)
>>> assert index
```

```
>>> oset1 = ub.oset([1, 2, 3, 4, 5, 6])
>>> oset2 = ub.oset([2, 4, 3])
>>> index = subsequence_index(oset1, oset2)
>>> assert not index
```

kwcococo.channel_spec._parse_concise_slice_syntax(v)
Helper for our slice syntax, which is may be a bit strange

Example

```
>>> print(_parse_concise_slice_syntax('B:10'))
>>> print(_parse_concise_slice_syntax('B.0:10:3'))
>>> print(_parse_concise_slice_syntax('B.:10:3'))
>>> print(_parse_concise_slice_syntax('B::10:3'))
>>> # Careful, this next one is quite different
>>> print(_parse_concise_slice_syntax('B:10:3'))
>>> print(_parse_concise_slice_syntax('B:3:10:3'))
>>> print(_parse_concise_slice_syntax('B.:10'))
>>> print(_parse_concise_slice_syntax('B.:3:'))
>>> print(_parse_concise_slice_syntax('B.:3:2'))
>>> print(_parse_concise_slice_syntax('B::2:3'))
>>> print(_parse_concise_slice_syntax('B.0:10:3'))
>>> print(_parse_concise_slice_syntax('B.:10:3'))
('B', 0, 10, 1)
('B', 0, 10, 3)
('B', 0, 10, 3)
('B', 0, 10, 3)
('B', 10, 3, 1)
('B', 3, 10, 3)
('B', 0, 10, 1)
('B', 0, 3, 1)
('B', 0, 3, 2)
('B', 0, 2, 3)
('B', 0, 10, 3)
('B', 0, 10, 3)
>>> import pytest
>>> with pytest.raises(ValueError):
>>>     _parse_concise_slice_syntax('B.0')
>>> with pytest.raises(ValueError):
>>>     _parse_concise_slice_syntax('B0')
>>> with pytest.raises(ValueError):
>>>     _parse_concise_slice_syntax('B:')
>>> with pytest.raises(ValueError):
>>>     _parse_concise_slice_syntax('B:0.10')
```

(continues on next page)

(continued from previous page)

```
>>> with pytest.raises(ValueError):
>>>     _parse_concise_slice_syntax('B:::')
```

`kwcoco.channel_spec.oset_insert(self, index, obj)`
`kwcoco.channel_spec.oset_delitem(self, index)`
 for ubelt oset, todo contribute back to luminosoinsight

```
>>> self = ub.oset([1, 2, 3, 4, 5, 6, 7, 8, 9])
>>> index = slice(3, 5)
>>> oset_delitem(self, index)
```

2.3.6 kwcoco.coco_dataset

An implementation and extension of the original MS-COCO API¹.

Extends the format to also include line annotations.

The following describes psuedo-code for the high level spec (some of which may not be have full support in the Python API). A formal json-schema is defined in [kwcoco.coco_schema](#).

An informal spec is as follows:

```
# All object categories are defined here.
category = {
    'id': int,
    'name': str, # unique name of the category
    'supercategory': str, # parent category name
}

# Videos are used to manage collections or sequences of images.
# Frames do not necesarilly have to be aligned or uniform time steps
video = {
    'id': int,
    'name': str, # a unique name for this video.

    'width': int # the base width of this video (all associated images must have this)
    'height': int # the base height of this video (all associated images must have this)

    # In the future this may be extended to allow pointing to video files
}

# Specifies how to find sensor data of a particular scene at a particular
# time. This is usually paths to rgb images, but auxiliary information
# can be used to specify multiple bands / etc...
image = {
    'id': int,

    'name': str, # an encouraged but optional unique name
```

(continues on next page)

¹ <http://cocodataset.org/#format-data>

(continued from previous page)

```
'file_name': str, # relative path to the "base" image data

'width': int, # pixel width of "base" image
'height': int, # pixel height of "base" image

'channels': <ChannelSpec>, # a string encoding of the channels in the main image

'auxiliary': [ # information about any auxiliary channels / bands
{
    'file_name': str, # relative path to associated file
    'channels': <ChannelSpec>, # a string encoding
    'width': <int> # pixel width of auxiliary image
    'height': <int> # pixel height of auxiliary image
    'warp_aux_to_img': <TransformSpec>, # transform from "base" image space to
    ↵ auxiliary image space. (identity if unspecified)
    'quantization': <QuantizationSpec>, # indicates that the underlying data
    ↵ was quantized
    },
    ...
]

'video_id': str # if this image is a frame in a video sequence, this id is shared
    ↵ by all frames in that sequence.
'timestamp': str | int # a iso-string timestamp or an integer in flicks.
'frame_index': int # ordinal frame index which can be used if timestamp is unknown.
    'warp_img_to_vid': <TransformSpec> # a transform image space to video space
    ↵ (identity if unspecified), can be used for sensor alignment or video stabilization
}
```

TransformSpec:

The spec can be anything coercable to a kwimage.Affine object.
 This can be an explicit affine transform matrix like:
 {'type': 'affine': 'matrix': <a-3x3 matrix>},

But it can also be a concise dict containing one or more of these keys

```
{
    'scale': <float|Tuple[float, float]>,
    'offset': <float|Tuple[float, float]>,
    'skew': <float>,
    'theta': <float>, # radians counter-clock-wise
}
```

ChannelSpec:

This is a string that describes the channel composition of an image.
 For the purposes of kwcoco, separate different channel names with a
 pipe ('|'). If the spec is not specified, methods may fall back on
 grayscale or rgb processing. There are special strings. For instance
 'rgb' will expand into 'r|g|b'. In other applications you can "late
 fuse" inputs by separating them with a "," and "early fuse" by
 separating with a "|". Early fusion returns a solid array/tensor, late
 fusion returns separated arrays/tensors.

QuantizationSpec:

(continues on next page)

(continued from previous page)

This is a dictionary of the form:

```

{
    'orig_min': <float>, # min original intensity
    'orig_max': <float>, # min original intensity
    'quant_min': <int>, # min quantized intensity
    'quant_max': <int>, # max quantized intensity
    'nodata': <int|None>, # integer value to interpret as nan
}

# Ground truth is specified as annotations, each belongs to a spatial
# region in an image. This must reference a subregion of the image in pixel
# coordinates. Additional non-schema properties can be specified to track
# location in other coordinate systems. Annotations can be linked over time
# by specifying track-ids.
annotation = {
    'id': int,
    'image_id': int,
    'category_id': int,

    'track_id': <int | str | uuid> # indicates association between annotations across
    ↵images

    'bbox': [tl_x, tl_y, w, h], # xywh format)
    'score' : float,
    'prob' : List[float],
    'weight' : float,

    'caption': str, # a text caption for this annotation
    'keypoints' : <Keypoints | List[int] > # an accepted keypoint format
    'segmentation': <RunLengthEncoding | Polygon | MaskPath | WKT >, # an accepted
    ↵segmentation format
}

# A dataset bundles a manifest of all aforementioned data into one structure.
dataset = {
    'categories': [category, ...],
    'videos': [video, ...]
    'images': [image, ...]
    'annotations': [annotation, ...]
    'licenses': [],
    'info': [],
}

```

Polygon:

A flattened list of xy coordinates.
 $[x_1, y_1, x_2, y_2, \dots, x_n, y_n]$

or a list of flattened list of xy coordinates if the CCs are disjoint
 $[[x_1, y_1, x_2, y_2, \dots, x_n, y_n], [x_1, y_1, \dots, x_m, y_m],]$

Note: the original coco spec does not allow for holes in polygons.

(continues on next page)

(continued from previous page)

We also allow a non-standard dictionary encoding of polygons

```
{'exterior': [(x1, y1)...],  
 'interiors': [[[x1, y1], ...], ...]}
```

TODO: Support WTK

RunLengthEncoding:

The RLE can be in a special bytes encoding or in a binary array encoding. We reuse the original C functions are in [2]_ in ``kwimage.structs.Mask`` to provide a convinient way to abstract this rather esoteric bytes encoding.

For pure python implementations see kwimage:

Converting from an image to RLE can be done via kwimage.run_length_encoding

Converting from RLE back to an image can be done via:

```
kwimage.decode_run_length
```

For compatibility with the COCO specs ensure the binary flags for these functions are set to true.

Keypoints:

Annotation keypoints may also be specified in this non-standard (but ultimately more general) way:

```
'annotations': [  
    {  
        'keypoints': [  
            {  
                'xy': <x1, y1>,  
                'visible': <0 or 1 or 2>,  
                'keypoint_category_id': <kp_cid>,  
                'keypoint_category': <kp_name, optional>, # this can be specified  
                ↵ instead of an id  
                }, ...  
            ]  
        }, ...  
    ],  
    'keypoint_categories': [{  
        'name': <str>,  
        'id': <int>, # an id for this keypoint category  
        'supercategory': <kp_name> # name of coarser parent keypoint class (for  
        ↵ hierarchical keypoints)  
        'reflection_id': <kp_cid> # specify only if the keypoint id would be swapped  
        ↵ with another keypoint type  
    }, ...  
]
```

In this scheme the "keypoints" property of each annotation (which used to be a list of floats) is now specified as a list of dictionaries that specify each keypoints location, id, and visibility explicitly. This allows for things like non-unique keypoints, partial keypoint annotations. This also removes the ordering requirement, which makes it

(continues on next page)

(continued from previous page)

simpler to keep track of each keypoints class type.

We also have a new top-level dictionary to specify all the possible keypoint categories.

TODO: Support WTK

Auxiliary Channels:

For multimodal or multispectral images it is possible to specify auxiliary channels in an image dictionary as follows:

```
{
    'id': int,
    'file_name': str,      # path to the "base" image (may be None)
    'name': str,           # a unique name for the image (must be given if file_name ↴
    ↴ is None)
    'channels': <spec>,   # a spec code that indicates the layout of the "base" image ↴
    ↴ channels.
    'auxiliary': [          # information about auxiliary channels
        {
            'file_name': str,
            'channels': <spec>
        }, ... # can have many auxiliary channels with unique specs
    ]
}
```

Video Sequences:

For video sequences, we add the following video level index:

```
'videos': [
    { 'id': <int>, 'name': <video_name:str> },
]
```

Note that the videos might be given as encoded mp4/avi/etc.. files (in which case the name should correspond to a path) or as a series of frames in which case the images should be used to index the extracted frames and information in them.

Then image dictionaries are augmented as follows:

```
{
    'video_id': str # optional, if this image is a frame in a video sequence, this ↴
    ↴ id is shared by all frames in that sequence.
    'timestamp': int # optional, timestamp (ideally in flicks), used to identify ↴
    ↴ the timestamp of the frame. Only applicable video inputs.
    'frame_index': int # optional, ordinal frame index which can be used if ↴
    ↴ timestamp is unknown.
}
```

And annotations are augmented as follows:

```
{
```

(continues on next page)

(continued from previous page)

```
'track_id': <int | str | uuid> # optional, indicates association between  
Annotations across frames  
}
```

Note: The main object in this file is [CocoDataset](#), which is composed of several mixin classes. See the class and method documentation for more details.

Todo:

- [] Use ijson to lazily load pieces of the dataset in the background or on demand. This will give us faster access to categories / images, whereas we will always have to wait for annotations etc...
 - [X] Should img_root be changed to bundle_dpath?
 - [] Read video data, return numpy arrays (requires API for images)
 - [] Spec for video URI, and convert to frames @ framerate function.
 - [] Document channel spec
 - [X] remove videos
-

References**Module Contents****Classes**

<i>MixinCocoDeprecate</i>	These functions are marked for deprecation and may be removed at any time
<i>MixinCocoAccessors</i>	TODO: better name
<i>MixinCocoExtras</i>	Misc functions for coco
<i>MixinCocoObjects</i>	Expose methods to construct object lists / groups.
<i>MixinCocoStats</i>	Methods for getting stats about the dataset
<i>MixinCocoDraw</i>	Matplotlib / display functionality
<i>MixinCocoAddRemove</i>	Mixin functions to dynamically add / remove annotations images and
<i>CocoIndex</i>	Fast lookup index for the COCO dataset with dynamic modification
<i>MixinCocoIndex</i>	Give the dataset top level access to index attributes
<i>CocoDataset</i>	The main coco dataset class with a json dataset backend.

Functions

<code>demo_coco_data()</code>	Simple data for testing.
-------------------------------	--------------------------

Attributes

<code>_dict</code>

<code>SPEC_KEYS</code>

`kwcoco.coco_dataset._dict`

`kwcoco.coco_dataset.SPEC_KEYS = ['info', 'licenses', 'categories', 'keypoint_categories', 'videos', 'images', 'annotations']`

`class kwcoco.coco_dataset.MixinCocoDeprecate`

Bases: `object`

These functions are marked for deprecation and may be removed at any time

`class kwcoco.coco_dataset.MixinCocoAccessors`

Bases: `object`

TODO: better name

`delayed_load(self, gid, channels=None, space='image')`

Experimental method

Parameters

- `gid (int)` – image id to load
- `channels (FusedChannelSpec)` – specific channels to load. if unspecified, all channels are loaded.
- `space (str)` – can either be “image” for loading in image space, or “video” for loading in video space.

Todo:

- [X] Currently can only take all or none of the channels from each base-image / auxiliary dict.
For instance if the main image is r|g|b you can't just select g|b at the moment.
 - [X] The order of the channels in the delayed load should match the requested channel order.
 - [X] TODO: add nans to bands that don't exist or throw an error
-

Example

```
>>> import kwCOCO
>>> gid = 1
>>> #
>>> self = kwCOCO.CocoDataset.demo('vidshapes8-multispectral')
>>> delayed = self.delayed_load(gid)
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize()))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
>>> #
>>> self = kwCOCO.CocoDataset.demo('shapes8')
>>> delayed = self.delayed_load(gid)
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize()))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
```

```
>>> crop = delayed.delayed_crop((slice(0, 3), slice(0, 3)))
>>> crop.finalize()
>>> crop.finalize(as_xarray=True)
```

```
>>> # TODO: should only select the "red" channel
>>> self = kwCOCO.CocoDataset.demo('shapes8')
>>> delayed = self.delayed_load(gid, channels='r')
```

```
>>> import kwCOCO
>>> gid = 1
>>> #
>>> self = kwCOCO.CocoDataset.demo('vidshapes8-multispectral')
>>> delayed = self.delayed_load(gid, channels='B1|B2', space='image')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
>>> delayed = self.delayed_load(gid, channels='B1|B2|B11', space='image')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
>>> delayed = self.delayed_load(gid, channels='B8|B1', space='video')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
```

```
>>> delayed = self.delayed_load(gid, channels='B8|foo|bar|B1', space='video')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
```

load_image(*self*, *gid_or_img*, *channels=None*)

Reads an image from disk and

Parameters

- **gid_or_img** (*int or dict*) – image id or image dict
- **channels** (*str | None*) – if specified, load data from auxiliary channels instead

Returns the image

Return type np.ndarray

Todo:

- [] allow specification of multiple channels - use `delayed image` for this.
-

get_image_fpath(*self*, *gid_or_img*, *channels=None*)

Returns the full path to the image

Parameters

- **gid_or_img** (*int or dict*) – image id or image dict
- **channels** (*str, default=None*) – if specified, return a path to data containing auxiliary channels instead

Returns full path to the image

Return type PathLike

_get_img_auxiliary(*self*, *gid_or_img*, *channels*)

returns the auxiliary dictionary for a specific channel

get_auxiliary_fpath(*self*, *gid_or_img*, *channels*)

Returns the full path to auxiliary data for an image

Parameters

- **gid_or_img** (*int | dict*) – an image or its id
- **channels** (*str*) – the auxiliary channel to load (e.g. disparity)

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo('shapes8', aux=True)
>>> self.get_auxiliary_fpath(1, 'disparity')
```

load_annot_sample(*self*, *aid_or_ann*, *image=None*, *pad=None*)

Reads the chip of an annotation. Note this is much less efficient than using a sampler, but it doesn't require disk cache.

Maybe deprecate?

Parameters

- **aid_or_int** (*int or dict*) – annot id or dict
- **image** (*ArrayLike, default=None*) – preloaded image (note: this process is inefficient unless image is specified)

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> sample = self.load_annot_sample(2, pad=100)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(sample['im'])
>>> kwplot.show_if_requested()
```

_resolve_to_id(self, id_or_dict)

Ensures output is an id

_resolve_to_cid(self, id_or_name_or_dict)

Ensures output is an category id

Note: this does not resolve aliases (yet), for that see _alias_to_cat

Todo: we could maintain an alias index to make this fast

_resolve_to_gid(self, id_or_name_or_dict)

Ensures output is an category id

_resolve_to_vidid(self, id_or_name_or_dict)

Ensures output is an video id

_resolve_to_ann(self, aid_or_ann)

Ensures output is an annotation dictionary

_resolve_to_img(self, gid_or_img)

Ensures output is an image dictionary

_resolve_to_kpcat(self, kp_identifier)

Lookup a keypoint-category dict via its name or id

Parameters **kp_identifier** (*int* | *str* | *dict*) – either the keypoint category name, alias, or its key-point_category_id.

Returns keypoint category dictionary

Return type Dict

Example

```
>>> self = CocoDataset.demo('shapes')
>>> kpcat1 = self._resolve_to_kpcat(1)
>>> kpcat2 = self._resolve_to_kpcat('left_eye')
>>> assert kpcat1 is kpcat2
>>> import pytest
>>> with pytest.raises(KeyError):
>>>     self._resolve_to_cat('human')
```

_resolve_to_cat(self, cat_identifier)

Lookup a coco-category dict via its name, alias, or id.

Parameters `cat_identifier` (`int | str | dict`) – either the category name, alias, or its category_id.

Raises `KeyError` – if the category doesn't exist.

Note: If the index is not built, the method will work but may be slow.

Example

```
>>> self = CocoDataset.demo()
>>> cat = self._resolve_to_cat('human')
>>> import pytest
>>> assert self._resolve_to_cat(cat['id']) is cat
>>> assert self._resolve_to_cat(cat) is cat
>>> with pytest.raises(KeyError):
>>>     self._resolve_to_cat(32)
>>> self.index.clear()
>>> assert self._resolve_to_cat(cat['id']) is cat
>>> with pytest.raises(KeyError):
>>>     self._resolve_to_cat(32)
```

_alias_to_cat(self, alias_catname)

Lookup a coco-category via its name or an “alias” name. In production code, use `_resolve_to_cat()` instead.

Parameters `alias_catname` (`str`) – category name or alias

Returns coco category dictionary

Return type `dict`

Example

```
>>> self = CocoDataset.demo()
>>> cat = self._alias_to_cat('human')
>>> import pytest
>>> with pytest.raises(KeyError):
>>>     self._alias_to_cat('person')
>>> cat['alias'] = ['person']
>>> self._alias_to_cat('person')
>>> cat['alias'] = 'person'
>>> self._alias_to_cat('person')
>>> assert self._alias_to_cat(None) is None
```

category_graph(self)

Construct a networkx category hierarchy

Returns graph: a directed graph where category names are the nodes, supercategories define edges, and items in each category dict (e.g. category id) are added as node properties.

Return type `networkx.DiGraph`

Example

```
>>> self = CocoDataset.demo()  
>>> graph = self.category_graph()  
>>> assert 'astronaut' in graph.nodes()  
>>> assert 'keypoints' in graph.nodes['human']
```

object_categories(self)

Construct a consistent CategoryTree representation of object classes

Returns category data structure

Return type *kwcoco.CategoryTree*

Example

```
>>> self = CocoDataset.demo()  
>>> classes = self.object_categories()  
>>> print('classes = {}'.format(classes))
```

keypoint_categories(self)

Construct a consistent CategoryTree representation of keypoint classes

Returns category data structure

Return type *kwcoco.CategoryTree*

Example

```
>>> self = CocoDataset.demo()  
>>> classes = self.keypoint_categories()  
>>> print('classes = {}'.format(classes))
```

_keypoint_category_names(self)

Construct keypoint categories names.

Uses new-style if possible, otherwise this falls back on old-style.

Returns names: list of keypoint category names

Return type List[str]

Example

```
>>> self = CocoDataset.demo()  
>>> names = self._keypoint_category_names()  
>>> print(names)
```

_lookup_kpnames(self, cid)

Get the keypoint categories for a certain class

_coco_image(self, gid)**coco_image(self, gid)**

Parameters `gid` (*int*) – image id
Returns `kwcoco.coco_image.CocoImage`

`class kwcoco.coco_dataset.MixinCocoExtras`
Bases: `object`

Misc functions for coco

`classmethod coerce(cls, key, **kw)`

Attempt to transform the input into the intended CocoDataset.

Parameters

- `key` – this can either be an instance of a CocoDataset, a string URI pointing to an on-disk dataset, or a special key for creating demodata.
- `**kw` – passed to whatever constructor is chosen (if any)

Example

```
>>> # test coerce for various input methods
>>> import kwcoco
>>> from kwcoco.coco_sql_dataset import assert_dsets_allclose
>>> dct_dset = kwcoco.CocoDataset.coerce('special:shapes8')
>>> copy1 = kwcoco.CocoDataset.coerce(dct_dset)
>>> copy2 = kwcoco.CocoDataset.coerce(dct_dset.fpath)
>>> assert assert_dsets_allclose(dct_dset, copy1)
>>> assert assert_dsets_allclose(dct_dset, copy2)
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> sql_dset = dct_dset.view_sql()
>>> copy3 = kwcoco.CocoDataset.coerce(sql_dset)
>>> copy4 = kwcoco.CocoDataset.coerce(sql_dset.fpath)
>>> assert assert_dsets_allclose(dct_dset, sql_dset)
>>> assert assert_dsets_allclose(dct_dset, copy3)
>>> assert assert_dsets_allclose(dct_dset, copy4)
```

`classmethod demo(cls, key='photos', **kwargs)`

Create a toy coco dataset for testing and demo purposes

Parameters

- `key` (*str, default=photos*) – Either ‘photos’, ‘shapes’, or ‘vidshapes’. There are also special suffixes that can control behavior.

Basic options that define which flavor of demodata to generate are: *photos*, *shapes*, and *vidshapes*. A numeric suffix e.g. *vidshapes8* can be specified to indicate the size of the generated demo dataset. There are other special suffixes that are available. See the code in this function for explicit details on what is allowed.

TODO: better documentation for these demo datasets.

As a quick summary: the *vidshapes* key is the most robust and mature demodata set, and here are several useful variants of the *vidshapes* key.

- (1) *vidshapes8* - the 8 suffix is the number of videos in this case.
- (2) *vidshapes8-multispectral* - generate 8 multispectral videos.
- (3) *vidshapes8-msi* - msi is an alias for multispectral.

(4) vidshapes8-frames5 - generate 8 videos with 5 frames each. (4) vidshapes2-speed0.1-frames7 - generate 2 videos with 7

frames where the objects move with with a speed of 0.1.

- ****kwargs** – if key is shapes, these arguments are passed to toydata generation. The Kwargs section of this docstring documents a subset of the available options. For full details, see `demodata_toy_dset()` and `random_video_dset()`.

Kwargs: `image_size (Tuple[int, int]):` width / height size of the images

dpath (str): path to the output image directory, defaults to using kwcoco cache dir.

`aux (bool):` if True generates dummy auxiliary channels

rng (int | RandomState, default=0): random number generator or seed

`verbose (int, default=3):` verbosity mode

Example

```
>>> # Basic demodata keys
>>> print(CocoDataset.demo('photos', verbose=1))
>>> print(CocoDataset.demo('shapes', verbose=1))
>>> print(CocoDataset.demo('vidshapes', verbose=1))
>>> # Variants of demodata keys
>>> print(CocoDataset.demo('shapes8', verbose=0))
>>> print(CocoDataset.demo('shapes8-msi', verbose=0))
>>> print(CocoDataset.demo('shapes8-frames1-speed0.2-msi', verbose=0))
```

Example

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes5', num_frames=5,
>>>                               verbose=0, rng=None)
>>> dset = kwcoco.CocoDataset.demo('vidshapes5', num_frames=5,
>>>                               num_tracks=4, verbose=0, rng=44)
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> pnums = kwplot.PlotNums(nSubplots=len(dset.index.imgs))
>>> fnum = 1
>>> for gx, gid in enumerate(dset.index.imgs.keys()):
>>>     canvas = dset.draw_image(gid=gid)
>>>     kwplot.imshow(canvas, pnum=pnums[gx], fnum=fnum)
>>>     #dset.show_image(gid=gid, pnum=pnums[gx])
>>> kwplot.show_if_requested()
```

Example

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes5-aux', num_frames=1,
>>>                                         verbose=0, rng=None)
```

Example

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes1-multispectral', num_frames=5,
>>>                                         verbose=0, rng=None)
>>> # This is the first use-case of image names
>>> assert len(dset.index.file_name_to_img) == 0, (
>>>     'the multispectral demo case has no "base" image')
>>> assert len(dset.index.name_to_img) == len(dset.index.imgs) == 5
>>> dset.remove_images([1])
>>> assert len(dset.index.name_to_img) == len(dset.index.imgs) == 4
>>> dset.remove_videos([1])
>>> assert len(dset.index.name_to_img) == len(dset.index.imgs) == 0
```

_tree(self)

developer helper

classmethod random(cls, rng=None)

Creates a random CocoDataset according to distribution parameters

Todo:

- [] parametrize

_build_hashid(self, hash_pixels=False, verbose=0)

Construct a hash that uniquely identifies the state of this dataset.

Parameters

- **hash_pixels (bool, default=False)** – If False the image data is not included in the hash, which can speed up computation, but is not 100% robust.
- **verbose (int)** – verbosity level

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> self._build_hashid(hash_pixels=True, verbose=3)
...
>>> # Shorten hashes for readability
>>> walker = ub.IndexableWalker(self.hashid_parts)
>>> for path, val in walker:
>>>     if isinstance(val, str):
>>>         walker[path] = val[0:8]
>>> # Note: this may change in different versions of kwcoco
```

(continues on next page)

(continued from previous page)

```
>>> print('self.hashid_parts = ' + ub.repr2(self.hashid_parts))
>>> print('self.hashid = {!r}'.format(self.hashid[0:8]))
self.hashid_parts = {
    'annotations': {
        'json': 'e573f49d',
        'num': 11,
    },
    'images': {
        'pixels': '67d741fe',
        'json': '2221c714',
        'num': 3,
    },
    'categories': {
        'json': '82d22e00',
        'num': 8,
    },
}
self.hashid = '77d445f0'
```

Doctest:

```
>>> self = CocoDataset.demo()
>>> self._build_hashid(hash_pixels=True, verbose=3)
>>> self.hashid_parts
>>> # Test that when we modify the dataset only the relevant
>>> # hashid parts are recomputed.
>>> orig = self.hashid_parts['categories']['json']
>>> self.add_category('foobar')
>>> assert 'categories' not in self.hashid_parts
>>> self.hashid_parts
>>> self.hashid_parts['images']['json'] = 'should not change'
>>> self._build_hashid(hash_pixels=True, verbose=3)
>>> assert self.hashid_parts['categories']['json']
>>> assert self.hashid_parts['categories']['json'] != orig
>>> assert self.hashid_parts['images']['json'] == 'should not change'
```

_invalidate_hashid(self, parts=None)

Called whenever the coco dataset is modified. It is possible to specify which parts were modified so unmodified parts can be reused next time the hash is constructed.

Todo:

- [] Rename to _notify_modification — or something like that
-

_cached_hashid(self)

Under Construction.

The idea is to cache the hashid when we are sure that the dataset was loaded from a file and has not been modified. We can record the modification time of the file (because we know it hasn't changed in memory), and use that as a key to the cache. If the modification time on the file is different than the one recorded in the cache, we know the cache could be invalid, so we recompute the hashid.

_dataset_id(self)

A human interpretable name that can be used to uniquely identify the dataset.

Note: This function is currently subject to change.

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> print(self._dataset_id())
>>> self = kwcoco.CocoDataset.demo('vidshapes8')
>>> print(self._dataset_id())
>>> self = kwcoco.CocoDataset()
>>> print(self._dataset_id())
```

_ensure_imgszie(self, workers=0, verbose=1, fail=False)

Populate the imgsize field if it does not exist.

Parameters

- **workers** (*int, default=0*) – number of workers for parallel processing.
- **verbose** (*int, default=1*) – verbosity level
- **fail** (*bool, default=False*) – if True, raises an exception if anything size fails to load.

Returns

a list of “bad” image dictionaries where the size could not be determined. Typically these are corrupted images and should be removed.

Return type List[dict]

Example

```
>>> # Normal case
>>> self = CocoDataset.demo()
>>> bad_imgs = self._ensure_imgszie()
>>> assert len(bad_imgs) == 0
>>> assert self.imgs[1]['width'] == 512
>>> assert self.imgs[2]['width'] == 300
>>> assert self.imgs[3]['width'] == 256
```

```
>>> # Fail cases
>>> self = CocoDataset()
>>> self.add_image('does-not-exist.jpg')
>>> bad_imgs = self._ensure_imgszie()
>>> assert len(bad_imgs) == 1
>>> import pytest
>>> with pytest.raises(Exception):
>>>     self._ensure_imgszie(fail=True)
```

_ensure_image_data(self, gids=None, verbose=1)

Download data from “url” fields if specified.

Parameters `gids` (*List*) – subset of images to download

missing_images(*self*, `check_aux=False`, `verbose=0`)

Check for images that don't exist

Parameters

- `check_aux` (*bool*, `default=False`) – if specified also checks auxiliary images
- `verbose` (*int*) – verbosity level

Returns bad indexes and paths and ids

Return type `List[Tuple[int, str, int]]`

corrupted_images(*self*, `check_aux=False`, `verbose=0`)

Check for images that don't exist or can't be opened

Parameters

- `check_aux` (*bool*, `default=False`) – if specified also checks auxiliary images
- `verbose` (*int*) – verbosity level

Returns bad indexes and paths and ids

Return type `List[Tuple[int, str, int]]`

rename_categories(*self*, `mapper`, `rebuild=True`, `merge_policy='ignore'`)

Rename categories with a potentially coarser categorization.

Parameters

- `mapper` (*dict or Function*) – maps old names to new names. If multiple names are mapped to the same category, those categories will be merged.
- `merge_policy` (*str*) – How to handle multiple categories that map to the same name. Can be update or ignore.

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> self.rename_categories({'astronomer': 'person',
>>>                         'astronaut': 'person',
>>>                         'mouth': 'person',
>>>                         'helmet': 'hat'})
>>> assert 'hat' in self.name_to_cat
>>> assert 'helmet' not in self.name_to_cat
>>> # Test merge case
>>> self = kwcoco.CocoDataset.demo()
>>> mapper = {
>>>     'helmet': 'rocket',
>>>     'astronomer': 'rocket',
>>>     'human': 'rocket',
>>>     'mouth': 'helmet',
>>>     'star': 'gas'
>>> }
>>> self.rename_categories(mapper)
```

`_ensure_json_serializable(self)`

_aspycoco(self)
Converts to the official pycocotools.coco.COCO object

Todo:

- [] Maybe expose as a public API?
-

reroot(self, new_root=None, old_prefix=None, new_prefix=None, absolute=False, check=True, safe=True)
Modify the prefix of the image/data paths onto a new image/data root.

Parameters

- **new_root** (str, default=None) – New image root. If unspecified the current `self.bundle_dpath` is used. If `old_prefix` and `new_prefix` are unspecified, they will attempt to be determined based on the current root (which assumes the file paths exist at that root) and this new root.
- **old_prefix** (str, default=None) – If specified, removes this prefix from file names. This also prevents any inferences that might be made via “`new_root`”.
- **new_prefix** (str, default=None) – If specified, adds this prefix to the file names. This also prevents any inferences that might be made via “`new_root`”.
- **absolute** (bool, default=False) – if True, file names are stored as absolute paths, otherwise they are relative to the new image root.
- **check** (bool, default=True) – if True, checks that the images all exist.
- **safe** (bool, default=True) – if True, does not overwrite values until all checks pass

CommandLine

```
xdoctest -m kwcoco.coco_dataset MixinCocoExtras.reroot
```

Todo:

- [] Incorporate maximum ordered subtree embedding?
-

Example

```
>>> import kwcoco
>>> def report(dset, name):
>>>     gid = 1
>>>     abs_fpath = dset.get_image_fpath(gid)
>>>     rel_fpath = dset.index.imgs[gid]['file_name']
>>>     color = 'green' if exists(abs_fpath) else 'red'
>>>     print('strategy_name = {!r}'.format(name))
>>>     print(ub.color_text('abs_fpath = {!r}'.format(abs_fpath), color))
>>>     print('rel_fpath = {!r}'.format(rel_fpath))
>>> dset = self = kwcoco.CocoDataset.demo()
>>> # Change base relative directory
>>> bundle_dpath = ub.expandpath('~')
>>> print('ORIG self.imgs = {!r}'.format(self.imgs))
```

(continues on next page)

(continued from previous page)

```
>>> print('ORIG dset.bundle_dpath = {!r}'.format(dset.bundle_dpath))
>>> print('NEW bundle_dpath      = {!r}'.format(bundle_dpath))
>>> self.reroot(bundle_dpath)
>>> report(self, 'self')
>>> print('NEW self.imgs = {!r}'.format(self.imgs))
>>> assert self.imgs[1]['file_name'].startswith('.cache')
```

```
>>> # Use absolute paths
>>> self.reroot(absolute=True)
>>> assert self.imgs[1]['file_name'].startswith(bundle_dpath)
```

```
>>> # Switch back to relative paths
>>> self.reroot()
>>> assert self.imgs[1]['file_name'].startswith('.cache')
```

Example

```
>>> # demo with auxiliary data
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo('shapes8', aux=True)
>>> bundle_dpath = ub.expandpath('~')
>>> print(self.imgs[1]['file_name'])
>>> print(self.imgs[1]['auxiliary'][0]['file_name'])
>>> self.reroot(new_root=bundle_dpath)
>>> print(self.imgs[1]['file_name'])
>>> print(self.imgs[1]['auxiliary'][0]['file_name'])
>>> assert self.imgs[1]['file_name'].startswith('.cache')
>>> assert self.imgs[1]['auxiliary'][0]['file_name'].startswith('.cache')
```

property data_root(self)

In the future we will deprecate data_root for bundle_dpath

property img_root(self)

In the future we will deprecate img_root for bundle_dpath

property data_fpath(self)

data_fpath is an alias of fpath

class kwcoco.coco_dataset.MixinCocoObjects

Bases: `object`

Expose methods to construct object lists / groups.

This is an alternative vectorized ORM-like interface to the coco dataset

annots(self, aids=None, gid=None, trackid=None)

Return vectorized annotation objects

Parameters

- **aids** (`List[int]`) – annotation ids to reference, if unspecified all annotations are returned.
- **gid** (`int`) – return all annotations that belong to this image id. mutually exclusive with other arguments.

- **trackid** (*int*) – return all annotations that belong to this track. mutually exclusive with other arguments.

Returns vectorized annotation object

Return type *Annots*

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> annots = self.annots()
>>> print(annots)
<Annots(num=11)>
>>> sub_annotss = annots.take([1, 2, 3])
>>> print(sub_annotss)
<Annots(num=3)>
>>> print(ub.repr2(sub_annotss.get('bbox', None)))
[
    [350, 5, 130, 290],
    None,
    None,
]
```

images(*self*, *gids=None*, *vidid=None*, *names=None*)

Return vectorized image objects

Parameters

- **gids** (*List[int]*) – image ids to reference, if unspecified all images are returned.
- **vidid** (*int*) – returns all images that belong to this video id. mutually exclusive with *gids* arg.
- **names** (*List[str]*) – lookup images by their names.

Returns vectorized image object

Return type *Images*

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> images = self.images()
>>> print(images)
<Images(num=3)>
```

```
>>> self = kwcoco.CocoDataset.demo('vidshapes2')
>>> vidid = 1
>>> images = self.images(vidid=vidid)
>>> assert all(v == vidid for v in images.lookup('video_id'))
>>> print(images)
<Images(num=2)>
```

categories(*self*, *cids=None*)

Return vectorized category objects

Parameters *cids* (*List[int]*) – category ids to reference, if unspecified all categories are returned.

Returns vectorized category object

Return type *Categories*

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> categories = self.categories()
>>> print(categories)
<Categories(num=8)>
```

videos(*self*, *vidids=None*, *names=None*)

Return vectorized video objects

Parameters

- *vidids* (*List[int]*) – video ids to reference, if unspecified all videos are returned.
- *names* (*List[str]*) – lookup videos by their name.

Returns vectorized video object

Return type *Videos*

Todo:

- [] This conflicts with what should be the property that should redirect to `index.videos`, we should resolve this somehow. E.g. all other main members of the index (anns, imgs, cats) have a toplevel dataset property, we don't have one for videos because the name we would pick conflicts with this.
-

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo('vidshapes2')
>>> videos = self.videos()
>>> print(videos)
>>> videos.lookup('name')
>>> videos.lookup('id')
>>> print('videos objs = {}'.format(ub.repr2(videos.objs[0:2], nl=1)))
```

class kwcoco.coco_dataset.MixinCocoStats

Bases: *object*

Methods for getting stats about the dataset

property n_annots(*self*)

The number of annotations in the dataset

property n_images(*self*)

The number of images in the dataset

property n_cats(self)
The number of categories in the dataset

property n_videos(self)
The number of videos in the dataset

keypoint_annotation_frequency(self)
DEPRECATED

Example

```
>>> from kwcoco.coco_dataset import *
>>> self = CocoDataset.demo('shapes', rng=0)
>>> hist = self.keypoint_annotation_frequency()
>>> hist = ub.odict(sorted(hist.items()))
>>> # FIXME: for whatever reason demodata generation is not deterministic when
>>> # seeded
>>> print(ub.repr2(hist))  # xdoc: +IGNORE_WANT
{
    'bot_tip': 6,
    'left_eye': 14,
    'mid_tip': 6,
    'right_eye': 14,
    'top_tip': 6,
}
```

category_annotation_frequency(self)
Reports the number of annotations of each category

Example

```
>>> from kwcoco.coco_dataset import *
>>> self = CocoDataset.demo()
>>> hist = self.category_annotation_frequency()
>>> print(ub.repr2(hist))
{
    'astroturf': 0,
    'human': 0,
    'astronaut': 1,
    'astronomer': 1,
    'helmet': 1,
    'rocket': 1,
    'mouth': 2,
    'star': 5,
}
```

category_annotation_type_frequency(self)
DEPRECATED

Reports the number of annotations of each type for each category

Example

```
>>> self = CocoDataset.demo()  
>>> hist = self.category_annotation_frequency()  
>>> print(ub.repr2(hist))
```

conform(*self*, ***config*)

Make the COCO file conform a stricter spec, infers attributes where possible.

Corresponds to the kwCOCO conform CLI tool.

KWArgs:

****config** : pycocotools_info (default=True): returns info required by pycocotools ensure_imgszie (default=True): ensure image size is populated legacy (default=False): if true tries to convert data structures to items compatible with the original pycocotools spec workers (int): number of parallel jobs for IO tasks

Example

```
>>> import kwCOCO  
>>> dset = kwCOCO.CocoDataset.demo('shapes8')  
>>> dset.index.imgs[1].pop('width')  
>>> dset.conform(legacy=True)  
>>> assert 'width' in dset.index.imgs[1]  
>>> assert 'area' in dset.index.anns[1]
```

validate(*self*, ***config*)

Performs checks on this coco dataset.

Corresponds to the kwCOCO validate CLI tool.

KWArgs:

****config** : schema (default=True): validates the json-schema unique (default=True): validates unique secondary keys missing (default=True): validates registered files exist corrupted (default=False): validates data in registered files verbose (default=1): verbosity flag fastfail (default=False): if True raise errors immediately

Returns

result containing keys: status (bool): False if any errors occurred errors (List[str]): list of all error messages missing (List): List of any missing images corrupted (List): List of any corrupted images

Return type dict

SeeAlso: _check_integrity() - performs internal checks

Example

```
>>> from kwcoco.coco_dataset import *
>>> self = CocoDataset.demo()
>>> import pytest
>>> with pytest.warns(UserWarning):
>>>     result = self.validate()
>>> assert not result['errors']
>>> assert result['warnings']
```

`stats(self, **kwargs)`

Compute summary statistics to describe the dataset at a high level

This function corresponds to [kwcoco.cli.coco_stats](#).

KWargs: basic(bool, default=True): return basic stats' extended(bool, default=True): return extended stats' catfreq(bool, default=True): return category frequency stats' boxes(bool, default=False): return bounding box stats'

annot_attrs(bool, default=True): return annotation attribute information' image_attrs(bool, default=True): return image attribute information'

Returns info

Return type dict

`basic_stats(self)`

Reports number of images, annotations, and categories.

SeeAlso: [kwcoco.coco_dataset.MixinCocoStats.basic_stats\(\)](#) [kwcoco.coco_dataset.MixinCocoStats.extended_stats\(\)](#)

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> print(ub.repr2(self.basic_stats()))
{
    'n_annts': 11,
    'n_imgs': 3,
    'n_videos': 0,
    'n_cats': 8,
}
```

```
>>> from kwcoco.demo.toydata_video import random_video_dset
>>> dset = random_video_dset(render=True, num_frames=2, num_tracks=10, rng=0)
>>> print(ub.repr2(dset.basic_stats()))
{
    'n_annts': 20,
    'n_imgs': 2,
    'n_videos': 1,
    'n_cats': 3,
}
```

extended_stats(self)

Reports number of images, annotations, and categories.

SeeAlso: [kwcoco.coco_dataset.MixinCocoStats.basic_stats\(\)](#) [kwcoco.coco_dataset.MixinCocoStats.extended_stats\(\)](#)

Example

```
>>> self = CocoDataset.demo()  
>>> print(ub.repr2(self.extended_stats()))
```

boxsize_stats(self, anchors=None, perclass=True, gids=None, aids=None, verbose=0, clusterkw={}, statskw={})

Compute statistics about bounding box sizes.

Also computes anchor boxes using kmeans if `anchors` is specified.

Parameters

- **anchors** (*int*) – if specified also computes box anchors via KMeans clustering
- **perclass** (*bool*) – if True also computes stats for each category
- **gids** (*List[int]*, *default=None*) – if specified only compute stats for these image ids.
- **aids** (*List[int]*, *default=None*) – if specified only compute stats for these annotation ids.
- **verbose** (*int*) – verbosity level
- **clusterkw** (*dict*) – kwargs for `sklearn.cluster.KMeans` used if computing anchors.
- **statskw** (*dict*) – kwargs for `kwarray.stats_dict()`

Returns Stats are returned in width-height format.

Return type Dict[str, Dict[str, Dict | ndarray]]

Example

```
>>> import kwcoco  
>>> self = kwcoco.CocoDataset.demo('shapes32')  
>>> infos = self.boxsize_stats(anchors=4, perclass=False)  
>>> print(ub.repr2(infos, nl=-1, precision=2))
```

```
>>> infos = self.boxsize_stats(gids=[1], statskw=dict(median=True))  
>>> print(ub.repr2(infos, nl=-1, precision=2))
```

findRepresentativeImages(self, gids=None)

Find images that have a wide array of categories.

Attempt to find the fewest images that cover all categories using images that contain both a large and small number of annotations.

Parameters **gids** (*None* | *List*) – Subset of image ids to consider when finding representative images. Uses all images if unspecified.

Returns list of image ids determined to be representative

Return type List

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> gids = self.find_representative_images()
>>> print('gids = {!r}'.format(gids))
>>> gids = self.find_representative_images([3])
>>> print('gids = {!r}'.format(gids))
```

```
>>> self = kwcoco.CocoDataset.demo('shapes8')
>>> gids = self.find_representative_images()
>>> print('gids = {!r}'.format(gids))
>>> valid = {7, 1}
>>> gids = self.find_representative_images(valid)
>>> assert valid.issuperset(gids)
>>> print('gids = {!r}'.format(gids))
```

class kwcoco.coco_dataset.MixinCocoDraw

Bases: `object`

Matplotlib / display functionality

imread(self, gid)

DEPRECATE: use `load_image` or `delayed_image`

Loads a particular image

draw_image(self, gid, channels=None)

Use `kwimage` to draw all annotations on an image and return the pixels as a numpy array.

Parameters

- **gid** (`int`) – image id to draw
- **channels** (`ChannelSpec`) – the channel to draw on

Returns canvas

Return type ndarray

SeeAlso `kwcoco.coco_dataset.MixinCocoDraw.draw_image()`

`kwcoco.coco_dataset.`

`MixinCocoDraw.show_image()`

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo('shapes8')
>>> self.draw_image(1)
>>> # Now you can dump the annotated image to disk / whatever
>>> # xdoctest: +REQUIRES(--show)
>>> import kwplot
>>> kwplot.autopl()
>>> kwplot.imshow(canvas)
```

show_image(self, gid=None, aids=None, aid=None, channels=None, **kwargs)

Use matplotlib to show an image with annotations overlaid

Parameters

- **gid** (*int*) – image to show
- **aids** (*list*) – aids to highlight within the image
- **aid** (*int*) – a specific aid to focus on. If gid is not give, look up gid based on this aid.
- ****kwargs** – show_annot, show_aid, show_catname, show_kpname, show_segmentation, title, show_gid, show_filename, show_boxes,

SeeAlso `kwcoco.coco_dataset.MixinCocoDraw.draw_image()` `kwcoco.coco_dataset.MixinCocoDraw.show_image()`

Example

```
>>> # xdoctest: +REQUIRES(--show)
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-msi')
>>> dset.show_image(gid=1, channels='B8')
```

class `kwcoco.coco_datasetMixinCocoAddRemove`
Bases: `object`

Mixin functions to dynamically add / remove annotations images and categories while maintaining lookup indexes.

add_video(*self, name, id=None, **kw*)

Register a new video with the dataset

Parameters

- **name** (*str*) – Unique name for this video.
- **id** (*None or int*) – ADVANCED. Force using this image id.
- ****kw** – stores arbitrary key/value pairs in this new video

Returns the video id assigned to the new video

Return type `int`

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset()
>>> print('self.index.videos = {}'.format(ub.repr2(self.index.videos, nl=1)))
>>> print('self.index.imgs = {}'.format(ub.repr2(self.index.imgs, nl=1)))
>>> print('self.index.vidid_to_gids = {!r}'.format(self.index.vidid_to_gids))
```

```
>>> vidid1 = self.add_video('foo', id=3)
>>> vidid2 = self.add_video('bar')
>>> vidid3 = self.add_video('baz')
>>> print('self.index.videos = {}'.format(ub.repr2(self.index.videos, nl=1)))
>>> print('self.index.imgs = {}'.format(ub.repr2(self.index.imgs, nl=1)))
>>> print('self.index.vidid_to_gids = {!r}'.format(self.index.vidid_to_gids))
```

```
>>> gid1 = self.add_image('foo1.jpg', video_id=vidid1, frame_index=0)
>>> gid2 = self.add_image('foo2.jpg', video_id=vidid1, frame_index=1)
>>> gid3 = self.add_image('foo3.jpg', video_id=vidid1, frame_index=2)
>>> gid4 = self.add_image('bar1.jpg', video_id=vidid2, frame_index=0)
>>> print('self.index.videos = {}'.format(ub.repr2(self.index.videos, nl=1)))
>>> print('self.index.imgs = {}'.format(ub.repr2(self.index.imgs, nl=1)))
>>> print('self.index.vidid_to_gids = {!r}'.format(self.index.vidid_to_gids))
```

```
>>> self.remove_images([gid2])
>>> print('self.index.vidid_to_gids = {!r}'.format(self.index.vidid_to_gids))
```

add_image(*self*, *file_name=None*, *id=None*, ***kw*)

Register a new image with the dataset

Parameters

- **file_name** (*str*) – relative or absolute path to image
- **id** (*None* or *int*) – ADVANCED. Force using this image id.
- **name** (*str*) – a unique key to identify this image
- **width** (*int*) – base width of the image
- **height** (*int*) – base height of the image
- **channels** (*ChannelSpec*) – specification of base channels
- **auxiliary** (*List[Dict]*) – specification of auxiliary information
- **video_id** (*int*) – parent video, if applicable
- **frame_index** (*int*) – frame index in parent video
- **timestamp** (*number* | *str*) – timestamp of frame index
- ****kw** – stores arbitrary key/value pairs in this new image

Returns the image id assigned to the new image

Return type *int*

SeeAlso: [add_image\(\)](#) [add_images\(\)](#) [ensure_image\(\)](#)

Example

```
>>> self = CocoDataset.demo()
>>> import kwimage
>>> gname = kwimage.grab_test_image_fpath('paraview')
>>> gid = self.add_image(gname)
>>> assert self.imgs[gid]['file_name'] == gname
```

add_annotation(*self*, *image_id*, *category_id=None*, *bbox=ub.NoParam*, *segmentation=ub.NoParam*, *keypoints=ub.NoParam*, *id=None*, ***kw*)

Register a new annotation with the dataset

Parameters

- **image_id** (*int*) – image_id the annotation is added to.
- **category_id** (*int* | *None*) – category_id for the new annotation

- **bbox** (*list | kwimage.Boxes*) – bounding box in xywh format
- **segmentation** (*MaskLike | MultiPolygonLike*) – keypoints in some accepted format, see `kwimage.Mask.to_coco()` and `kwimage.MultiPolygon.to_coco()`.
- **keypoints** (*KeypointsLike*) – keypoints in some accepted format, see `kwimage.Keypoints.to_coco()`.
- **id** (*None | int*) – Force using this annotation id. Typically you should NOT specify this. A new unused id will be chosen and returned.
- ****kw** – stores arbitrary key/value pairs in this new image, Common respected key/values include but are not limited to the following:

track_id (*int | str*): **some value used to associate annotations** that belong to the same “track”.

score : float

prob : List[float]

weight (float): a weight, usually used to indicate if a ground truth annotation is difficult / important. This generalizes standard “is_hard” or “ignore” attributes in other formats.

caption (str): a text caption for this annotation

Returns the annotation id assigned to the new annotation

Return type `int`

SeeAlso: `kwcoco.coco_dataset.MixinCocoAddRemove.add_annotation()` `kwcoco.coco_dataset.MixinCocoAddRemove.add_annotations()`

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> image_id = 1
>>> cid = 1
>>> bbox = [10, 10, 20, 20]
>>> aid = self.add_annotation(image_id, cid, bbox)
>>> assert self.anns[aid]['bbox'] == bbox
```

Example

```
>>> import kwimage
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> new_det = kwimage.Detections.random(1, segmentations=True, keypoints=True)
>>> # kwimage datastructures have methods to convert to coco recognized formats
>>> new_ann_data = list(new_det.to_coco(style='new'))[0]
>>> image_id = 1
>>> aid = self.add_annotation(image_id, **new_ann_data)
>>> # Lookup the annotation we just added
>>> ann = self.index.anns[aid]
>>> print('ann = {}'.format(ub.repr2(ann, nl=-2)))
```

Example

```
>>> # Attempt to add annot without a category or bbox
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> image_id = 1
>>> aid = self.add_annotation(image_id)
>>> assert None in self.index.cid_to_aids
```

Example

```
>>> # Attempt to add annot using various styles of kwimage structures
>>> import kwcoco
>>> import kwimage
>>> self = kwcoco.CocoDataset.demo()
>>> image_id = 1
>>> #--
>>> kw = {}
>>> kw['segmentation'] = kwimage.Polygon.random()
>>> kw['keypoints'] = kwimage.Points.random()
>>> aid = self.add_annotation(image_id, **kw)
>>> ann = self.index.anns[aid]
>>> print('ann = {}'.format(ub.repr2(ann, nl=2)))
>>> #--
>>> kw = {}
>>> kw['segmentation'] = kwimage.Mask.random()
>>> aid = self.add_annotation(image_id, **kw)
>>> ann = self.index.anns[aid]
>>> assert ann.get('segmentation', None) is not None
>>> print('ann = {}'.format(ub.repr2(ann, nl=2)))
>>> #--
>>> kw = {}
>>> kw['segmentation'] = kwimage.Mask.random().to_array_rle()
>>> aid = self.add_annotation(image_id, **kw)
>>> ann = self.index.anns[aid]
>>> assert ann.get('segmentation', None) is not None
>>> print('ann = {}'.format(ub.repr2(ann, nl=2)))
>>> #--
>>> kw = {}
>>> kw['segmentation'] = kwimage.Polygon.random().to_coco()
>>> kw['keypoints'] = kwimage.Points.random().to_coco()
>>> aid = self.add_annotation(image_id, **kw)
>>> ann = self.index.anns[aid]
>>> assert ann.get('segmentation', None) is not None
>>> assert ann.get('keypoints', None) is not None
>>> print('ann = {}'.format(ub.repr2(ann, nl=2)))
```

add_category(*self*, *name*, *supercategory=None*, *id=None*, ***kw*)

Register a new category with the dataset

Parameters

- **name** (*str*) – name of the new category

- **supercategory** (*str, optional*) – parent of this category
- **id** (*int, optional*) – use this category id, if it was not taken
- ****kw** – stores arbitrary key/value pairs in this new image

Returns the category id assigned to the new category

Return type `int`

SeeAlso: `kwcoco.coco_dataset.MixinCocoAddRemove.add_category()` `coco_dataset.MixinCocoAddRemove.ensure_category()`

`kwcoco.`

Example

```
>>> self = CocoDataset.demo()
>>> prev_n_cats = self.n_cats
>>> cid = self.add_category('dog', supercategory='object')
>>> assert self.cats[cid]['name'] == 'dog'
>>> assert self.n_cats == prev_n_cats + 1
>>> import pytest
>>> with pytest.raises(ValueError):
>>>     self.add_category('dog', supercategory='object')
```

ensure_image(*self, file_name, id=None, **kw*)

Register an image if it is new or returns an existing id.

Like `kwcoco.coco_dataset.MixinCocoAddRemove.add_image()`, but returns the existing image id if it already exists instead of failing. In this case all metadata is ignored.

Parameters

- **file_name** (*str*) – relative or absolute path to image
- **id** (*None or int*) – ADVANCED. Force using this image id.
- ****kw** – stores arbitrary key/value pairs in this new image

Returns the existing or new image id

Return type `int`

SeeAlso: `kwcoco.coco_dataset.MixinCocoAddRemove.add_image()` `kwcoco.coco_dataset.MixinCocoAddRemove.add_images()` `kwcoco.coco_dataset.MixinCocoAddRemove.ensure_image()`

ensure_category(*self, name, supercategory=None, id=None, **kw*)

Register a category if it is new or returns an existing id.

Like `kwcoco.coco_dataset.MixinCocoAddRemove.add_category()`, but returns the existing category id if it already exists instead of failing. In this case all metadata is ignored.

Returns the existing or new category id

Return type `int`

SeeAlso: `kwcoco.coco_dataset.MixinCocoAddRemove.add_category()` `coco_dataset.MixinCocoAddRemove.ensure_category()`

`kwcoco.`

add_annotations(*self, anns*)

Faster less-safe multi-item alternative to add_annotation.

We assume the annotations are well formatted in kwcoco compliant dictionaries, including the “id” field. No validation checks are made when calling this function.

Parameters *anns* (*List[Dict]*) – list of annotation dictionaries

SeeAlso: [add_annotation\(\)](#) [add_annotations\(\)](#)

Example

```
>>> self = CocoDataset.demo()
>>> anns = [self.anns[aid] for aid in [2, 3, 5, 7]]
>>> self.remove_annotations(anns)
>>> assert self.n_annot == 7 and self._check_index()
>>> self.add_annotations(anns)
>>> assert self.n_annot == 11 and self._check_index()
```

add_images(*self, imgs*)

Faster less-safe multi-item alternative

We assume the images are well formatted in kwcoco compliant dictionaries, including the “id” field. No validation checks are made when calling this function.

Note: THIS FUNCTION WAS DESIGNED FOR SPEED, AS SUCH IT DOES NOT CHECK IF THE IMAGE-IDS OR FILE NAMES ARE DUPLICATED AND WILL BLINDLY ADD DATA EVEN IF IT IS BAD. THE SINGLE IMAGE VERSION IS SLOWER BUT SAFER.

Parameters *imgs* (*List[Dict]*) – list of image dictionaries

SeeAlso: [kwcoco.coco_dataset.MixinCocoAddRemove.add_image\(\)](#) [kwcoco.coco_dataset.MixinCocoAddRemove.add_images\(\)](#) [kwcoco.coco_dataset.MixinCocoAddRemove.ensure_image\(\)](#)

Example

```
>>> imgs = CocoDataset.demo().dataset['images']
>>> self = CocoDataset()
>>> self.add_images(imgs)
>>> assert self.n_images == 3 and self._check_index()
```

clear_images(*self*)

Removes all images and annotations (but not categories)

Example

```
>>> self = CocoDataset.demo()
>>> self.clear_images()
>>> print(ub.repr2(self.basic_stats(), nobr=1, nl=0, si=1))
n_anns: 0, n_imgs: 0, n_videos: 0, n_cats: 8
```

`clear_annotations(self)`

Removes all annotations (but not images and categories)

Example

```
>>> self = CocoDataset.demo()
>>> self.clear_annotations()
>>> print(ub.repr2(self.basic_stats(), nobr=1, nl=0, si=1))
n_anns: 0, n_imgs: 3, n_videos: 0, n_cats: 8
```

`remove_annotation(self, aid_or_ann)`

Remove a single annotation from the dataset

If you have multiple annotations to remove its more efficient to remove them in batch with `kwCOCO.coco_dataset.MixinCocoAddRemove.remove_annotations()`

Example

```
>>> import kwCOCO
>>> self = kwCOCO.CocoDataset.demo()
>>> aids_or_anns = [self.anns[2], 3, 4, self.anns[1]]
>>> self.remove_annotations(aids_or_anns)
>>> assert len(self.dataset['annotations']) == 7
>>> self._check_index()
```

`remove_annotations(self, aids_or_anns, verbose=0, safe=True)`

Remove multiple annotations from the dataset.

Parameters

- `aids_or_anns (List)` – list of annotation dicts or ids
- `safe (bool, default=True)` – if True, we perform checks to remove duplicates and non-existing identifiers.

`Returns` `num_removed`: information on the number of items removed

`Return type` Dict

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> prev_n_annots = self.n_annots
>>> aids_or_annots = [self.anns[2], 3, 4, self.anns[1]]
>>> self.remove_annotations(aids_or_annots) # xdoc: +IGNORE_WANT
{'annotations': 4}
>>> assert len(self.dataset['annotations']) == prev_n_annots - 4
>>> self._check_index()
```

remove_categories(*self*, *cat_identifiers*, *keep_annots=False*, *verbose=0*, *safe=True*)

Remove categories and all annotations in those categories.

Currently does not change any hierarchy information

Parameters

- **cat_identifiers** (*List*) – list of category dicts, names, or ids
- **keep_annots** (*bool, default=False*) – if True, keeps annotations, but removes category labels.
- **safe** (*bool, default=True*) – if True, we perform checks to remove duplicates and non-existing identifiers.

Returns num_removed: information on the number of items removed

Return type Dict

Example

```
>>> self = CocoDataset.demo()
>>> cat_identifiers = [self.cats[1], 'rocket', 3]
>>> self.remove_categories(cat_identifiers)
>>> assert len(self.dataset['categories']) == 5
>>> self._check_index()
```

remove_images(*self*, *gids_or_imgs*, *verbose=0*, *safe=True*)

Remove images and any annotations contained by them

Parameters

- **gids_or_imgs** (*List*) – list of image dicts, names, or ids
- **safe** (*bool, default=True*) – if True, we perform checks to remove duplicates and non-existing identifiers.

Returns num_removed: information on the number of items removed

Return type Dict

Example

```
>>> from kwCOCO.coco_dataset import *
>>> self = CocoDataset.demo()
>>> assert len(self.dataset['images']) == 3
>>> gids_or_imgs = [self.imgs[2], 'astro.png']
>>> self.remove_images(gids_or_imgs) # xdoc: +IGNORE_WANT
{'annotations': 11, 'images': 2}
>>> assert len(self.dataset['images']) == 1
>>> self._check_index()
>>> gids_or_imgs = [3]
>>> self.remove_images(gids_or_imgs)
>>> assert len(self.dataset['images']) == 0
>>> self._check_index()
```

remove_videos(*self*, *vidids_or_videos*, *verbose*=0, *safe*=True)

Remove videos and any images / annotations contained by them

Parameters

- **vidids_or_videos** (*List*) – list of video dicts, names, or ids
- **safe** (*bool*, *default=True*) – if True, we perform checks to remove duplicates and non-existing identifiers.

Returns num_removed: information on the number of items removed

Return type Dict

Example

```
>>> from kwCOCO.coco_dataset import *
>>> self = CocoDataset.demo('vidshapes8')
>>> assert len(self.dataset['videos']) == 8
>>> vidids_or_videos = [self.dataset['videos'][0]['id']]
>>> self.remove_videos(vidids_or_videos) # xdoc: +IGNORE_WANT
{'annotations': 4, 'images': 2, 'videos': 1}
>>> assert len(self.dataset['videos']) == 7
>>> self._check_index()
```

remove_annotation_keypoints(*self*, *kp_identifiers*)

Removes all keypoints with a particular category

Parameters **kp_identifiers** (*List*) – list of keypoint category dicts, names, or ids

Returns num_removed: information on the number of items removed

Return type Dict

remove_keypoint_categories(*self*, *kp_identifiers*)

Removes all keypoints of a particular category as well as all annotation keypoints with those ids.

Parameters **kp_identifiers** (*List*) – list of keypoint category dicts, names, or ids

Returns num_removed: information on the number of items removed

Return type Dict

Example

```
>>> self = CocoDataset.demo('shapes', rng=0)
>>> kp_identifiers = ['left_eye', 'mid_tip']
>>> remove_info = self.remove_keypoint_categories(kp_identifiers)
>>> print('remove_info = {!r}'.format(remove_info))
>>> # FIXME: for whatever reason demodata generation is not deterministic when
>>> ~seeded
>>> # assert remove_info == {'keypoint_categories': 2, 'annotation_keypoints': 16,
>>> ~'reflection_ids': 1}
>>> assert self._resolve_to_kpcat('right_eye')['reflection_id'] is None
```

set_annotation_category(*self, aid_or_ann, cid_or_cat*)

Sets the category of a single annotation

Parameters

- **aid_or_ann** (*dict | int*) – annotation dict or id
- **cid_or_cat** (*dict | int*) – category dict or id

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> old_freq = self.category_annotation_frequency()
>>> aid_or_ann = aid = 2
>>> cid_or_cat = new_cid = self.ensure_category('kitten')
>>> self.set_annotation_category(aid, new_cid)
>>> new_freq = self.category_annotation_frequency()
>>> print('new_freq = {}'.format(ub.repr2(new_freq, nl=1)))
>>> print('old_freq = {}'.format(ub.repr2(old_freq, nl=1)))
>>> assert sum(new_freq.values()) == sum(old_freq.values())
>>> assert new_freq['kitten'] == 1
```

class kwcoco.coco_dataset.CocoIndex(*index*)

Bases: *object*

Fast lookup index for the COCO dataset with dynamic modification

Variables

- **imgs** (*Dict[int, dict]*) – mapping between image ids and the image dictionaries
- **anns** (*Dict[int, dict]*) – mapping between annotation ids and the annotation dictionaries
- **cats** (*Dict[int, dict]*) – mapping between category ids and the category dictionaries
- **kpcats** (*Dict[int, dict]*) – mapping between keypoint category ids and keypoint category dictionaries
- **gid_to_aids** (*Dict[int, List[int]]*) – mapping between an image-id and annotation-ids that belong to it
- **cid_to_aids** (*Dict[int, List[int]]*) – mapping between an category-id and annotation-ids that belong to it

- **cid_to_gids** (*Dict[int, List[int]]*) – mapping between an category-id and image-ids that contain at least one annotation with this category id.
- **trackid_to_aids** (*Dict[int, List[int]]*) – mapping between a track-id and annotation-ids that belong to it
- **vidid_to_gids** (*Dict[int, List[int]]*) – mapping between an video-id and images-ids that belong to it
- **name_to_video** (*Dict[str, dict]*) – mapping between a video name and the video dictionary.
- **name_to_cat** (*Dict[str, dict]*) – mapping between a category name and the category dictionary.
- **name_to_img** (*Dict[str, dict]*) – mapping between a image name and the image dictionary.
- **file_name_to_img** (*Dict[str, dict]*) – mapping between a image file_name and the image dictionary.

_set

__nonzero__

_set_sorted_by_frame_index(*index, gids=None*)

Helper for ensuring that vidid_to_gids returns image ids ordered by frame index.

__bool__(*index*)

property cid_to_gids(*index*)

Example

```
>>> import kwCOCO
>>> self = dset = kwCOCO.CocoDataset()
>>> self.index.cid_to_gids
```

_add_video(*index, vidid, video*)

_add_image(*index, gid, img*)

Example

```
>>> # Test adding image to video that doesn't exist
>>> import kwCOCO
>>> self = dset = kwCOCO.CocoDataset()
>>> dset.add_image(file_name='frame1', video_id=1, frame_index=0)
>>> dset.add_image(file_name='frame2', video_id=1, frame_index=0)
>>> dset._check_pointers()
>>> dset._check_index()
>>> print('dset.index.vidid_to_gids = {!r}'.format(dset.index.vidid_to_gids))
>>> assert len(dset.index.vidid_to_gids) == 1
>>> dset.add_video(name='foo-vid', id=1)
>>> assert len(dset.index.vidid_to_gids) == 1
>>> dset._check_pointers()
>>> dset._check_index()
```

_add_images(index, imgs)

See ./dev/bench/bench_add_image_check.py

Note: THIS FUNCTION WAS DESIGNED FOR SPEED, AS SUCH IT DOES NOT CHECK IF THE IMAGE-IDS or FILE_NAMES ARE DUPLICATED AND WILL BLINDLY ADD DATA EVEN IF IT IS BAD. THE SINGLE IMAGE VERSION IS SLOWER BUT SAFER.

```
_add_annotation(index, aid, gid, cid, tid, ann)
_add_annotations(index, anns)
_add_category(index, cid, name, cat)
_remove_all_annotations(index)
_remove_all_images(index)
_remove_annotations(index, remove_aids, verbose=0)
_remove_categories(index, remove_cids, verbose=0)
_remove_images(index, remove_gids, verbose=0)
_remove_videos(index, remove_vidids, verbose=0)
clear(index)
```

build(index, parent)

Build all id-to-obj reverse indexes from scratch.

Parameters *parent* (*CocoDataset*) – the dataset to index

Notation: aid - Annotation ID gid - imaGe ID cid - Category ID vidid - Video ID

Example

```
>>> import kwcoco
>>> parent = kwcoco.CocoDataset.demo('vidshapes1', num_frames=4, rng=1)
>>> index = parent.index
>>> index.build(parent)
```

class kwcoco.coco_dataset.MixinCocoIndex

Bases: *object*

Give the dataset top level access to index attributes

```
property anns(self)
property imgs(self)
property cats(self)
property gid_to_aids(self)
property cid_to_aids(self)
property name_to_cat(self)
```

```
class kwcoco.coco_dataset.CocoDataset(data=None, tag=None, bundle_dpath=None, img_root=None,
                                       fname=None, autobuild=True)
Bases:      kwcoco.abstract_coco_dataset.AbstractCocoDataset,      MixinCocoAddRemove,
            MixinCocoStats, MixinCocoObjects, MixinCocoDraw, MixinCocoAccessors, MixinCocoExtras,
            MixinCocoIndex, MixinCocoDepriate, ubelt.NiceRepr
```

The main coco dataset class with a json dataset backend.

Variables

- **dataset** (*Dict*) – raw json data structure. This is the base dictionary that contains {‘annotations’: List, ‘images’: List, ‘categories’: List}
- **index** (*CocoIndex*) – an efficient lookup index into the coco data structure. The index defines its own attributes like `anns`, `cats`, `imgs`, `gid_to_aids`, `file_name_to_img`, etc. See `CocoIndex` for more details on which attributes are available.
- **fpath** (*PathLike* / *None*) – if known, this stores the filepath the dataset was loaded from
- **tag** (*str*) – A tag indicating the name of the dataset.
- **bundle_dpath** (*PathLike* / *None*) – If known, this is the root path that all image file names are relative to. This can also be manually overwritten by the user.
- **hashid** (*str* / *None*) – If computed, this will be a hash uniquely identifying the dataset. To ensure this is computed see `kwcoco.coco_dataset.MixinCocoExtras._build_hashid()`.

References

<http://cocodataset.org/#format> <http://cocodataset.org/#download>

CommandLine

```
python -m kwcoco.coco_dataset CocoDataset --show
```

Example

```
>>> from kwcoco.coco_dataset import demo_coco_data
>>> import kwcoco
>>> import ubelt as ub
>>> # Returns a coco json structure
>>> dataset = demo_coco_data()
>>> # Pass the coco json structure to the API
>>> self = kwcoco.CocoDataset(dataset, tag='demo')
>>> # Now you can access the data using the index and helper methods
>>> #
>>> # Start by looking up an image by it's COCO id.
>>> image_id = 1
>>> img = self.index.imgs[image_id]
>>> print(ub.repr2(img, nl=1, sort=1))
{
```

```
    'file_name': 'astro.png',
    'id': 1,
```

(continues on next page)

(continued from previous page)

```

        'url': 'https://i.imgur.com/KXhKM72.png',
    }

>>> #
>>> # Use the (gid_to_aids) index to lookup annotations in the iamge
>>> annotation_id = sorted(self.index.gid_to_aids[image_id])[0]
>>> ann = self.index.anns[annotation_id]
>>> print(ub.repr2(ub.dict_diff(ann, {'segmentation'}), nl=1))
{
    'bbox': [10, 10, 360, 490],
    'category_id': 1,
    'id': 1,
    'image_id': 1,
    'keypoints': [247, 101, 2, 202, 100, 2],
}
>>> #
>>> # Use annotation category id to look up that information
>>> category_id = ann['category_id']
>>> cat = self.index.cats[category_id]
>>> print('cat = {}'.format(ub.repr2(cat, nl=1, sort=1)))
cat = {
    'id': 1,
    'name': 'astronaut',
    'supercategory': 'human',
}
>>> #
>>> # Now play with some helper functions, like extended statistics
>>> extended_stats = self.extended_stats()
>>> print('extended_stats = {}'.format(ub.repr2(extended_stats, nl=1, precision=2,
    sort=1)))
extended_stats = {
    'annots_per_img': {'mean': 3.67, 'std': 3.86, 'min': 0.00, 'max': 9.00, 'nMin': 1,
    'nMax': 1, 'shape': (3,)},
    'imgs_per_cat': {'mean': 0.88, 'std': 0.60, 'min': 0.00, 'max': 2.00, 'nMin': 2,
    'nMax': 1, 'shape': (8,)},
    'cats_per_img': {'mean': 2.33, 'std': 2.05, 'min': 0.00, 'max': 5.00, 'nMin': 1,
    'nMax': 1, 'shape': (3,)},
    'annots_per_cat': {'mean': 1.38, 'std': 1.49, 'min': 0.00, 'max': 5.00, 'nMin': 2,
    'nMax': 1, 'shape': (8,)},
    'imgs_per_video': {'empty_list': True},
}
>>> # You can "draw" a raster of the annotated image with cv2
>>> canvas = self.draw_image(2)
>>> # Or if you have matplotlib you can "show" the image with mpl objects
>>> # xdoctest: +REQUIRES(--show)
>>> from matplotlib import pyplot as plt
>>> fig = plt.figure()
>>> ax1 = fig.add_subplot(1, 2, 1)
>>> self.show_image(gid=2)
>>> ax2 = fig.add_subplot(1, 2, 2)
>>> ax2.imshow(canvas)
>>> ax1.set_title('show with matplotlib')
>>> ax2.set_title('draw with cv2')

```

(continues on next page)

(continued from previous page)

```
>>> plt.show()
```

property fpath(self)

In the future we will deprecate img_root for bundle_dpath

_infer_dirs(self)**classmethod from_data(CocoDataset, data, bundle_dpath=None, img_root=None)**

Constructor from a json dictionary

classmethod from_image_paths(CocoDataset, gpaths, bundle_dpath=None, img_root=None)

Constructor from a list of images paths.

This is a convinience method.

Parameters **gpaths** (*List[str]*) – list of image paths

Example

```
>>> coco_dset = CocoDataset.from_image_paths(['a.png', 'b.png'])
>>> assert coco_dset.n_images == 2
```

classmethod from_coco_paths(CocoDataset, fpaths, max_workers=0, verbose=1, mode='thread', union='try')

Constructor from multiple coco file paths.

Loads multiple coco datasets and unions the result

Note: if the union operation fails, the list of individually loaded files is returned instead.

Parameters

- **fpaths** (*List[str]*) – list of paths to multiple coco files to be loaded and unioned.
- **max_workers** (*int*, *default=0*) – number of worker threads / processes
- **verbose** (*int*) – verbosity level
- **mode** (*str*) – thread, process, or serial
- **union** (*str | bool*, *default='try'*) – If True, unions the result datasets after loading. If False, just returns the result list. If ‘try’, then try to preform the union, but return the result list if it fails.

copy(self)

Deep copies this object

Example

```
>>> from kwcoco.coco_dataset import *
>>> self = CocoDataset.demo()
>>> new = self.copy()
>>> assert new.imgs[1] is new.dataset['images'][0]
>>> assert new.imgs[1] == self.dataset['images'][0]
>>> assert new.imgs[1] is not self.dataset['images'][0]
```

`__nice__(self)`

`dumps(self, indent=None, newlines=False)`

Writes the dataset out to the json format

Parameters `newlines (bool)` – if True, each annotation, image, category gets its own line

Note:

Using `newlines=True` is similar to: `print(ub.repr2(dset.dataset, nl=2, trailsep=False))` However, the above may not output valid json if it contains ndarrays.

Example

```
>>> from kwcoco.coco_dataset import *
>>> import json
>>> self = CocoDataset.demo()
>>> text = self.dumps(newlines=True)
>>> print(text)
>>> self2 = CocoDataset(json.loads(text), tag='demo2')
>>> assert self2.dataset == self.dataset
>>> assert self2.dataset is not self.dataset
```

```
>>> text = self.dumps(newlines=True)
>>> print(text)
>>> self2 = CocoDataset(json.loads(text), tag='demo2')
>>> assert self2.dataset == self.dataset
>>> assert self2.dataset is not self.dataset
```

`dump(self, file, indent=None, newlines=False)`

Writes the dataset out to the json format

Parameters

- `file (PathLike | FileLike)` – Where to write the data. Can either be a path to a file or an open file pointer / stream.
- `newlines (bool)` – if True, each annotation, image, category gets its own line.

Example

```
>>> import tempfile
>>> from kwcoco.coco_dataset import *
>>> self = CocoDataset.demo()
>>> file = tempfile.NamedTemporaryFile('w')
>>> self.dump(file)
>>> file.seek(0)
>>> text = open(file.name, 'r').read()
>>> print(text)
>>> file.seek(0)
>>> dataset = json.load(open(file.name, 'r'))
>>> self2 = CocoDataset(dataset, tag='demo2')
>>> assert self2.dataset == self.dataset
>>> assert self2.dataset is not self.dataset
```

```
>>> file = tempfile.NamedTemporaryFile('w')
>>> self.dump(file, newlines=True)
>>> file.seek(0)
>>> text = open(file.name, 'r').read()
>>> print(text)
>>> file.seek(0)
>>> dataset = json.load(open(file.name, 'r'))
>>> self2 = CocoDataset(dataset, tag='demo2')
>>> assert self2.dataset == self.dataset
>>> assert self2.dataset is not self.dataset
```

_check_json_serializable(self, verbose=1)
Debug which part of a coco dataset might not be json serializable

_check_integrity(self)
perform all checks

_check_index(self)

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo()
>>> self._check_index()
>>> # Force a failure
>>> self.index.anns.pop(1)
>>> self.index.anns.pop(2)
>>> import pytest
>>> with pytest.raises(AssertionError):
>>>     self._check_index()
```

_check_pointers(self, verbose=1)
Check that all category and image ids referenced by annotations exist

_build_index(self)

```
union(*others, disjoint_tracks=True, **kwargs)
```

Merges multiple `CocoDataset` items into one. Names and associations are retained, but ids may be different.

Parameters

- ***others** – a series of CocoDatasets that we will merge. Note, if called as an instance method, the “self” instance will be the first item in the “others” list. But if called like a classmethod, “others” will be empty by default.
- **disjoint_tracks (bool, default=True)** – if True, we will assume track-ids are disjoint and if two datasets share the same track-id, we will disambiguate them. Otherwise they will be copied over as-is.
- ****kwargs** – constructor options for the new merged CocoDataset

Returns a new merged coco dataset

Return type `CocoDataset`

CommandLine

```
xdoctest -m kwcoco.coco_dataset CocoDataset.union
```

Example

```
>>> # Test union works with different keypoint categories
>>> dset1 = CocoDataset.demo('shapes1')
>>> dset2 = CocoDataset.demo('shapes2')
>>> dset1.remove_keypoint_categories(['bot_tip', 'mid_tip', 'right_eye'])
>>> dset2.remove_keypoint_categories(['top_tip', 'left_eye'])
>>> dset_12a = CocoDataset.union(dset1, dset2)
>>> dset_12b = dset1.union(dset2)
>>> dset_21 = dset2.union(dset1)
>>> def add_hist(h1, h2):
>>>     return {k: h1.get(k, 0) + h2.get(k, 0) for k in set(h1) | set(h2)}
>>> kpfreq1 = dset1.keypoint_annotation_frequency()
>>> kpfreq2 = dset2.keypoint_annotation_frequency()
>>> kpfreq_want = add_hist(kpfreq1, kpfreq2)
>>> kpfreq_got1 = dset_12a.keypoint_annotation_frequency()
>>> kpfreq_got2 = dset_12b.keypoint_annotation_frequency()
>>> assert kpfreq_want == kpfreq_got1
>>> assert kpfreq_want == kpfreq_got2
```

```
>>> # Test disjoint gid datasets
>>> import kwcoco
>>> dset1 = kwcoco.CocoDataset.demo('shapes3')
>>> for new_gid, img in enumerate(dset1.dataset['images'], start=10):
>>>     for aid in dset1.gid_to_aids[img['id']]:
>>>         dset1.anns[aid]['image_id'] = new_gid
>>>     img['id'] = new_gid
>>> dset1.index.clear()
>>> dset1._build_index()
```

(continues on next page)

(continued from previous page)

```
>>> # -----
>>> dset2 = kwCOCO.CocoDataset.demo('shapes2')
>>> for new_gid, img in enumerate(dset2.dataset['images'], start=100):
>>>     for aid in dset2.gid_to_aids[img['id']]:
>>>         dset2.anns[aid]['image_id'] = new_gid
>>>     img['id'] = new_gid
>>> dset1.index.clear()
>>> dset2._build_index()
>>> others = [dset1, dset2]
>>> merged = kwCOCO.CocoDataset.union(*others)
>>> print('merged = {!r}'.format(merged))
>>> print('merged imgs = {}'.format(ub.repr2(merged.imgs, nl=1)))
>>> assert set(merged.imgs) & set([10, 11, 12, 100, 101]) == set(merged.imgs)
```

```
>>> # Test data is not preserved
>>> dset2 = kwCOCO.CocoDataset.demo('shapes2')
>>> dset1 = kwCOCO.CocoDataset.demo('shapes3')
>>> others = (dset1, dset2)
>>> cls = self = kwCOCO.CocoDataset
>>> merged = cls.union(*others)
>>> print('merged = {!r}'.format(merged))
>>> print('merged imgs = {}'.format(ub.repr2(merged.imgs, nl=1)))
>>> assert set(merged.imgs) & set([1, 2, 3, 4, 5]) == set(merged.imgs)
```

```
>>> # Test track-ids are mapped correctly
>>> dset1 = kwCOCO.CocoDataset.demo('vidshapes1')
>>> dset2 = kwCOCO.CocoDataset.demo('vidshapes2')
>>> dset3 = kwCOCO.CocoDataset.demo('vidshapes3')
>>> others = (dset1, dset2, dset3)
>>> for dset in others:
>>>     [a.pop('segmentation', None) for a in dset.index.anns.values()]
>>>     [a.pop('keypoints', None) for a in dset.index.anns.values()]
>>> cls = self = kwCOCO.CocoDataset
>>> merged = cls.union(*others, disjoint_tracks=1)
>>> print('dset1.anns = {}'.format(ub.repr2(dset1.anns, nl=1)))
>>> print('dset2.anns = {}'.format(ub.repr2(dset2.anns, nl=1)))
>>> print('dset3.anns = {}'.format(ub.repr2(dset3.anns, nl=1)))
>>> print('merged.anns = {}'.format(ub.repr2(merged.anns, nl=1)))
```

Example

```
>>> import kwCOCO
>>> # Test empty union
>>> empty_union = kwCOCO.CocoDataset.union()
>>> assert len(empty_union.index.imgs) == 0
```

Todo:

- [] are supercategories broken?
- [] reuse image ids where possible

- [] reuse annotation / category ids where possible
- [X] handle case where no inputs are given
- [x] disambiguate track-ids
- [x] disambiguate video-ids

subset(self, gids, copy=False, autobuild=True)

Return a subset of the larger coco dataset by specifying which images to port. All annotations in those images will be taken.

Parameters

- **gids** (*List[int]*) – image-ids to copy into a new dataset
- **copy** (*bool, default=False*) – if True, makes a deep copy of all nested attributes, otherwise makes a shallow copy.
- **autobuild** (*bool, default=True*) – if True will automatically build the fast lookup index.

Example

```
>>> self = CocoDataset.demo()
>>> gids = [1, 3]
>>> sub_dset = self.subset(gids)
>>> assert len(self.index.gid_to_aids) == 3
>>> assert len(sub_dset.gid_to_aids) == 2
```

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo('vidshapes2')
>>> gids = [1, 2]
>>> sub_dset = self.subset(gids, copy=True)
>>> assert len(sub_dset.index.videos) == 1
>>> assert len(self.index.videos) == 2
```

Example

```
>>> self = CocoDataset.demo()
>>> sub1 = self.subset([1])
>>> sub2 = self.subset([2])
>>> sub3 = self.subset([3])
>>> others = [sub1, sub2, sub3]
>>> rejoined = CocoDataset.union(*others)
>>> assert len(sub1.anns) == 9
>>> assert len(sub2.anns) == 2
>>> assert len(sub3.anns) == 0
>>> assert rejoined.basic_stats() == self.basic_stats()
```

view_sql(self, force_rewrite=False, memory=False)

Create a cached SQL interface to this dataset suitable for large scale multiprocessing use cases.

Parameters

- **force_rewrite** (*bool, default=False*) – if True, forces an update to any existing cache file on disk
- **memory** (*bool, default=False*) – if True, the database is constructed in memory.

Note: This view cache is experimental and currently depends on the timestamp of the file pointed to by `self.fpath`. In other words dont use this on in-memory datasets.

`kwcoco.coco_dataset.demo_coco_data()`

Simple data for testing.

This contains several non-standard fields, which help ensure robustness of functions tested with this data. For more compliant demodata see the `kwcoco.demodata` submodule

Example

```
>>> # xdoctest: +REQUIRES(--show)
>>> from kwcoco.coco_dataset import demo_coco_data, CocoDataset
>>> dataset = demo_coco_data()
>>> self = CocoDataset(dataset, tag='demo')
>>> import kwplot
>>> kwplot.autopl()l()
>>> self.show_image(gid=1)
>>> kwplot.show_if_requested()
```

2.3.7 `kwcoco.coco_evaluator`

Evaluates a predicted coco dataset against a truth coco dataset.

The components in this module work programmaticaly or as a command line script.

Todo:

- [] **does evaluate return one result or multiple results** based on different configurations?
 - [] max_dets - TODO: in original pycocoutils but not here
 - [] Flag that allows for polygon instead of bounding box overlap
 - [] **How do we note what iou_thresh and area-range were in** the result plots?
-

CommandLine

```
xdoc test -m kwcoco.coco_evaluator __doc__:0 --vd --slow
```

Example

```
>>> from kwcoco.coco_evaluator import * # NOQA
>>> from kwcoco.coco_evaluator import CocoEvaluator
>>> import kwcoco
>>> # note: increase the number of images for better looking metrics
>>> true_dset = kwcoco.CocoDataset.demo('shapes8')
>>> from kwcoco.demo.perterb import perterb_coco
>>> kwargs = {
>>>     'box_noise': 0.5,
>>>     'n_fp': (0, 10),
>>>     'n_fn': (0, 10),
>>>     'with_probs': True,
>>> }
>>> pred_dset = perterb_coco(true_dset, **kwargs)
>>> print('true_dset = {!r}'.format(true_dset))
>>> print('pred_dset = {!r}'.format(pred_dset))
>>> config = {
>>>     'true_dataset': true_dset,
>>>     'pred_dataset': pred_dset,
>>>     'area_range': ['all', 'small'],
>>>     'iou_thresh': [0.3, 0.95],
>>> }
>>> coco_eval = CocoEvaluator(config)
>>> results = coco_eval.evaluate()
>>> # Now we can draw / serialize the results as we please
>>> dpath = ub.ensure_app_cache_dir('kwcoco/tests/test_out_dpath')
>>> results_fpath = join(dpath, 'metrics.json')
>>> print('results_fpath = {!r}'.format(results_fpath))
>>> results.dump(results_fpath, indent='    ')
>>> measures = results['area_range=all,iou_thresh=0.3'].ncls_measures
>>> import pandas as pd
>>> print(pd.DataFrame(ub.dict_isect(
>>>     measures, ['f1', 'g1', 'mcc', 'thresholds',
>>>                 'ppv', 'tpr', 'tnr', 'npv', 'fpr',
>>>                 'tp_count', 'fp_count',
>>>                 'tn_count', 'fn_count'])).iloc[:100])
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> # xdoctest: +REQUIRES(--slow)
>>> results.dump_figures(dpath)
>>> print('dpath = {!r}'.format(dpath))
>>> # xdoctest: +REQUIRES(--vd)
>>> if ub.argflag('--vd') or 1:
>>>     import xdev
>>>     xdev.view_directory(dpath)
```

Module Contents

Classes

<i>CocoEvalConfig</i>	Evaluate and score predicted versus truth detections / classifications in a COCO dataset
<i>CocoEvaluator</i>	Abstracts the evaluation process to execute on two coco datasets.
<i>CocoResults</i>	

CommandLine

<i>CocoSingleResult</i>	Container class to store, draw, summarize, and serialize results from
-------------------------	---

Functions

<i>_dmet_area_weights(dmet, orig_weights, cfsn_vecs, area_ranges, coco_eval, use_area_attr=False)</i>	Hacky function to compute confusion vector ignore weights for different
<i>_writefig(fig, metrics_dpath, fname, figsize, verbose, tight)</i>	
<i>_load_dets(pred_fpaths, workers=0)</i>	

Example

<i>_load_dets_worker(single_pred_fpath, with_coco=True)</i>

Attributes

<i>profile</i>
<i>COCO_SAMPLER_CLS</i>

```
kwcoco.coco_evaluator.profile
kwcoco.coco_evaluator.COCO_SAMPLER_CLS
class kwcoco.coco_evaluator.CocoEvalConfig(data=None, default=None, cmdline=False)
    Bases: scriptconfig.Config
    Evaluate and score predicted versus truth detections / classifications in a COCO dataset
    default
    normalize(self)
        overloadable function called after each load
class kwcoco.coco_evaluator.CocoEvaluator(coco_eval, config)
    Bases: object
```

Abstracts the evaluation process to execute on two coco datasets.

This can be run as a standalone script where the user specifies the paths to the true and predicted dataset explicitly, or this can be used by a higher level script that produces the predictions and then sends them to this evaluator.

Example

```
>>> from kwcoco.coco_evaluator import CocoEvaluator
>>> from kwcoco.demo.perterb import perterb_coco
>>> import kwcoco
>>> true_dset = kwcoco.CocoDataset.demo('shapes8')
>>> kwargs = {
>>>     'box_noise': 0.5,
>>>     'n_fp': (0, 10),
>>>     'n_fn': (0, 10),
>>>     'with_probs': True,
>>> }
>>> pred_dset = perterb_coco(true_dset, **kwargs)
>>> config = {
>>>     'true_dataset': true_dset,
>>>     'pred_dataset': pred_dset,
>>>     'classes_of_interest': [],
>>> }
>>> coco_eval = CocoEvaluator(config)
>>> results = coco_eval.evaluate()
```

Config

`log(coco_eval, msg, level='INFO')`

`_init(coco_eval)`

Performs initial coercion from given inputs into dictionaries of kwimage.Detection objects and attempts to ensure comparable category and image ids.

`_ensure_init(coco_eval)`

`classmethod _rectify_classes(coco_eval, true_classes, pred_classes)`

`classmethod _coerce_dets(CocoEvaluator, dataset, verbose=0, workers=0)`

Coerce the input to a mapping from image-id to kwimage.Detection

Also capture a CocoDataset if possible.

Returns `gid_to_det`: mapping from gid to dets extra: any extra information we gathered via coercion

Return type `Tuple[Dict[int, Detections], Dict]`

Example

```
>>> from kwCOCO.coco_evaluator import * # NOQA
>>> import kwCOCO
>>> coco_dset = kwCOCO.CocoDataset.demo('shapes8')
>>> gid_to_det, extras = CocoEvaluator._coerce_dets(coco_dset)
```

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwCOCO.coco_evaluator import * # NOQA
>>> import kwCOCO
>>> coco_dset = kwCOCO.CocoDataset.demo('shapes8').view_sql()
>>> gid_to_det, extras = CocoEvaluator._coerce_dets(coco_dset)
```

`_build_dmet(coco_eval)`

Builds the detection metrics object

Returns

DetectionMetrics - object that can perform assignment and build confusion vectors.

`evaluate(coco_eval)`

Executes the main evaluation logic. Performs assignments between detections to make DetectionMetrics object, then creates per-item and ovr confusion vectors, and performs various threshold-vs-confusion analyses.

Returns

container storing (and capable of drawing / serializing) results

Return type *CocoResults*

`kwCOCO.coco_evaluator.dmet_area_weights(dmet, orig_weights, cfsn_vecs, area_ranges, coco_eval, use_area_attr=False)`

Hacky function to compute confusion vector ignore weights for different area thresholds. Needs to be slightly refactored.

`class kwCOCO.coco_evaluator.CocoResults(results, resdata=None)`

Bases: `ubelt.NiceRepr, kwCOCO.metrics.util.DictProxy`

CommandLine

```
xdoctest -m /home/joncrall/code/kwCOCO/kwCOCO/coco_evaluator.py CocoResults --
    -profile
```

Example

```
>>> from kwcoco.coco_evaluator import * # NOQA
>>> from kwcoco.coco_evaluator import CocoEvaluator
>>> import kwcoco
>>> true_dset = kwcoco.CocoDataset.demo('shapes2')
>>> from kwcoco.demo.perterb import perterb_coco
>>> kwargs = {
>>>     'box_noise': 0.5,
>>>     'n_fp': (0, 10),
>>>     'n_fn': (0, 10),
>>> }
>>> pred_dset = perterb_coco(true_dset, **kwargs)
>>> print('true_dset = {!r}'.format(true_dset))
>>> print('pred_dset = {!r}'.format(pred_dset))
>>> config = {
>>>     'true_dataset': true_dset,
>>>     'pred_dataset': pred_dset,
>>>     'area_range': ['small'],
>>>     'iou_thresh': [0.3],
>>> }
>>> coco_eval = CocoEvaluator(config)
>>> results = coco_eval.evaluate()
>>> # Now we can draw / serialize the results as we please
>>> dpath = ub.ensure_app_cache_dir('kwcoco/tests/test_out_dpath')
>>> #
>>> # test deserialization works
>>> state = results.__json__()
>>> self2 = CocoResults.from_json(state)
>>> #
>>> # xdoctest: +REQUIRES(module:kwplot)
>>> results.dump_figures(dpath, figsize=(3, 2), tight=False) # make this go faster
>>> results.dump(join(dpath, 'metrics.json'), indent=' ')
```

`dump_figures(results, out_dpath, expt_title=None, figsize='auto', tight=True)`

`__json__(results)`

`classmethod from_json(cls, state)`

`dump(result, file, indent='')`

Serialize to json file

`class kwcoco.coco_evaluator.CocoSingleResult(result, nocls_measures, ovr_measures, cfsn_vecs, meta=None)`

Bases: `ubelt.NiceRepr`

Container class to store, draw, summarize, and serialize results from CocoEvaluator.

Example

```
>>> # xdoctest: +REQUIRES(--slow)
>>> from kwcoco.coco_evaluator import * # NOQA
>>> from kwcoco.coco_evaluator import CocoEvaluator
>>> import kwcoco
>>> true_dset = kwcoco.CocoDataset.demo('shapes8')
>>> from kwcoco.demo.perterb import perterb_coco
>>> kwargs = {
>>>     'box_noise': 0.2,
>>>     'n_fp': (0, 3),
>>>     'n_fn': (0, 3),
>>>     'with_probs': False,
>>> }
>>> pred_dset = perterb_coco(true_dset, **kwargs)
>>> print('true_dset = {!r}'.format(true_dset))
>>> print('pred_dset = {!r}'.format(pred_dset))
>>> config = {
>>>     'true_dataset': true_dset,
>>>     'pred_dataset': pred_dset,
>>>     'area_range': [(0, 32 ** 2), (32 ** 2, 96 ** 2)],
>>>     'iou_thresh': [0.3, 0.5, 0.95],
>>> }
>>> coco_eval = CocoEvaluator(config)
>>> results = coco_eval.evaluate()
>>> result = ub.peek(results.values())
>>> state = result.__json__()
>>> print('state = {}'.format(ub.repr2(state, nl=-1)))
>>> recon = CocoSingleResult.from_json(state)
>>> state = recon.__json__()
>>> print('state = {}'.format(ub.repr2(state, nl=-1)))
```

`__nice__(result)`

`classmethod from_json(cls, state)`

`__json__(result)`

`dump(result, file, indent=' ')`

Serialize to json file

`dump_figures(result, out_dpath, expt_title=None, figsize='auto', tight=True, verbose=1)`

`kwcoco.coco_evaluator._writefig(fig, metrics_dpath, fname, figsize, verbose, tight)`

`kwcoco.coco_evaluator._load_dets(pred_fpaths, workers=0)`

Example

```
>>> from kwcoco.coco_evaluator import _load_dets, _load_dets_worker
>>> import ubelt as ub
>>> import kwcoco
>>> from os.path import join
>>> dpath = ub.ensure_app_cache_dir('kwcoco/tests/load_dets')
>>> N = 4
>>> pred_fpaths = []
>>> for i in range(1, N + 1):
>>>     dset = kwcoco.CocoDataset.demo('shapes{}'.format(i))
>>>     dset.fpath = join(dpath, 'shapes_{}.mscoco.json'.format(i))
>>>     dset.dump(dset.fpath)
>>>     pred_fpaths.append(dset.fpath)
>>> dets, coco_dset = _load_dets(pred_fpaths)
>>> print('dets = {!r}'.format(dets))
>>> print('coco_dset = {!r}'.format(coco_dset))
```

`kwcoco.coco_evaluator._load_dets_worker(single_pred_fpath, with_coco=True)`

2.3.8 kwcoco.coco_image

Module Contents

Classes

<code>CocoImage</code>	An object-oriented representation of a coco image.
------------------------	--

Functions

<code>_delay_load_imglike(bundle_dpath, obj)</code>

Attributes

<code>profile</code>

`kwcoco.coco_image.profile`

`class kwcoco.coco_image.CocoImage(img, dset=None)`
Bases: `ubelt.NiceRepr`

An object-oriented representation of a coco image.

It provides helper methods that are specific to a single image.

This operates directly on a single coco image dictionary, but it can optionally be connected to a parent dataset, which allows it to use CocoDataset methods to query about relationships and resolve pointers.

This is different than the Images class in coco_object1d, which is just a vectorized interface to multiple objects.

Example

```
>>> import kwcoco
>>> dset1 = kwcoco.CocoDataset.demo('shapes8')
>>> dset2 = kwcoco.CocoDataset.demo('vidshapes8-multispectral')

>>> self = CocoImage(dset1 imgs[1], dset1)
>>> print('self = {!r}'.format(self))
>>> print('self.channels = {}'.format(ub.repr2(self.channels, nl=1)))

>>> self = CocoImage(dset2 imgs[1], dset2)
>>> print('self.channels = {}'.format(ub.repr2(self.channels, nl=1)))
>>> self.primary_asset()

classmethod from_gid(cls, dset, gid)
property bundle_dpath(self)
property video(self)
    Helper to grab the video for this image if it exists
detach(self)
    Removes references to the underlying coco dataset, but keeps special information such that it wont be
    needed.
__nice__(self)
```

Example

```
>>> from kwcoco.coco_image import * # NOQA
>>> import kwcoco
>>> with ub.CaptureStdout() as cap:
...     dset = kwcoco.CocoDataset.demo('shapes8')
>>> self = CocoImage(dset.dataset['images'][0], dset)
>>> print('self = {!r}'.format(self))

>>> dset = kwcoco.CocoDataset.demo()
>>> self = CocoImage(dset.dataset['images'][0], dset)
>>> print('self = {!r}'.format(self))

stats(self)
__getitem__(self, key)
keys(self)
get(self, key, default=ub.NoParam)
    Duck type some of the dict interface
property channels(self)
property num_channels(self)
property dsize(self)
```

primary_image_filepath(*self*, *requires=None*)
primary_asset(*self*, *requires=None*)
Compute a “main” image asset.

Notes

Uses a heuristic.

- First, try to find the auxiliary image that has with the smallest distortion to the base image (if known via warp_aux_to_img)
- Second, break ties by using the largest image if w / h is known
- Last, if previous information not available use the first auxiliary image.

Parameters *requires* (*List[str]*) – list of attribute that must be non-None to consider an object as the primary one.

Todo:

- [] Add in primary heuristics
-

Example

```
>>> import kwarray
>>> from kwcoco.coco_image import * # NOQA
>>> rng = kwarray.ensure_rng(0)
>>> def random_auxiliary(name, w=None, h=None):
>>>     return {'file_name': name, 'width': w, 'height': h}
>>> self = CocoImage({
>>>     'auxiliary': [
>>>         random_auxiliary('1'),
>>>         random_auxiliary('2'),
>>>         random_auxiliary('3'),
>>>     ]
>>> })
>>> assert self.primary_asset()['file_name'] == '1'
>>> self = CocoImage({
>>>     'auxiliary': [
>>>         random_auxiliary('1'),
>>>         random_auxiliary('2', 3, 3),
>>>         random_auxiliary('3'),
>>>     ]
>>> })
>>> assert self.primary_asset()['file_name'] == '2'
```

iter_image_filepaths(*self*)
iter_asset_objs(*self*)
Iterate through base + auxiliary dicts that have file paths
Yields *dict* – an image or auxiliary dictionary

find_asset_obj(*self, channels*)

Find the asset dictionary with the specified channels

add_auxiliary_item(*self, file_name=None, channels=None, imdata=None, warp_aux_to_img=None, width=None, height=None, imwrite=False*)

Adds an auxiliary item to the image dictionary.

This operation can be done purely in-memory (the default), or the image data can be written to a file on disk (via the imwrite=True flag).

Parameters

- **file_name** (*str | None*) – The name of the file relative to the bundle directory. If unspecified, imdata must be given.
- **channels** (*str | kwcoco.FusedChannelSpec*) – The channel code indicating what each of the bands represents. These channels should be disjoint wrt to the existing data in this image (this is not checked).
- **imdata** (*ndarray | None*) – The underlying image data this auxiliary item represents. If unspecified, it is assumed file_name points to a path on disk that will eventually exist. If imdata, file_name, and the special imwrite=True flag are specified, this function will write the data to disk.
- **warp_aux_to_img** (*kwimage.Affine*) – The transformation from this auxiliary space to image space. If unspecified, assumes this item is related to image space by only a scale factor.
- **width** (*int*) – Width of the data in auxiliary space (inferred if unspecified)
- **height** (*int*) – Height of the data in auxiliary space (inferred if unspecified)
- **imwrite** (*bool*) – If specified, both imdata and file_name must be specified, and this will write the data to disk. Note: it is recommended that you simply call imwrite yourself before or after calling this function. This lets you better control imwrite parameters.

Todo:

- [] Allow imwrite to specify an executor that is used to return a Future so the imwrite call does not block.
-

Example

```
>>> from kwcoco.coco_image import * # NOQA
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral')
>>> coco_img = dset.coco_image(1)
>>> imdata = np.random.rand(32, 32, 5)
>>> channels = kwcoco.FusedChannelSpec.coerce('Aux:5')
>>> coco_img.add_auxiliary_item(imdata=imdata, channels=channels)
```

delay(*self, channels=None, space='image', bundle_dpath=None*)

Perform a delayed load on the data in this image.

The delayed load can load a subset of channels, and perform lazy warping operations. If the underlying data is in a tiled format this can reduce the amount of disk IO needed to read the data if only a small crop or lower resolution view of the data is needed.

Note: This method is experimental and relies on the delayed load proof-of-concept.

Parameters

- **gid** (*int*) – image id to load
- **channels** (*FusedChannelSpec*) – specific channels to load. if unspecified, all channels are loaded.
- **space** (*str*) – can either be “image” for loading in image space, or “video” for loading in video space.

Todo:

- [X] **Currently can only take all or none of the channels from each base-image / auxiliary dict.**
For instance if the main image is r|g|b you can't just select g|b at the moment.
 - [X] **The order of the channels in the delayed load should** match the requested channel order.
 - [X] TODO: add nans to bands that don't exist or throw an error
 - [] **This function could stand to have a better name. Maybe imread with a delayed=True flag? Or maybe just delayed_load?**
-

Example

```
>>> from kwcoco.coco_image import * # NOQA
>>> import kwcoco
>>> gid = 1
>>> #
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral')
>>> self = CocoImage(dset.imgs[gid], dset)
>>> delayed = self.delay()
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize()))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
>>> #
>>> dset = kwcoco.CocoDataset.demo('shapes8')
>>> delayed = dset.delayed_load(gid)
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize()))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
```

```
>>> crop = delayed.delayed_crop((slice(0, 3), slice(0, 3)))
>>> crop.finalize()
>>> crop.finalize(as_xarray=True)
```

```
>>> # TODO: should only select the "red" channel
>>> dset = kwcoco.CocoDataset.demo('shapes8')
>>> delayed = CocoImage(dset.imgs[gid], dset).delay(channels='r')
```

```
>>> import kwCOCO
>>> gid = 1
>>> #
>>> dset = kwCOCO.CocoDataset.demo('vidshapes8-multispectral')
>>> delayed = dset.delayed_load(gid, channels='B1|B2', space='image')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
>>> delayed = dset.delayed_load(gid, channels='B1|B2|B11', space='image')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
>>> delayed = dset.delayed_load(gid, channels='B8|B1', space='video')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))

>>> delayed = dset.delayed_load(gid, channels='B8|foo|bar|B1', space='video')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
```

Example

```
>>> import kwCOCO
>>> dset = kwCOCO.CocoDataset.demo()
>>> coco_img = dset.coco_image(1)
>>> # Test case where nothing is registered in the dataset
>>> delayed = coco_img.delay()
>>> final = delayed.finalize()
>>> assert final.shape == (512, 512, 3)
```

Example

```
>>> # Test that delay works when imdata is stored in the image
>>> # dictionary itself.
>>> from kwCOCO.coco_image import * # NOQA
>>> import kwCOCO
>>> dset = kwCOCO.CocoDataset.demo('vidshapes8-multispectral')
>>> coco_img = dset.coco_image(1)
>>> imdata = np.random.rand(6, 6, 5)
>>> imdata[:] = np.arange(5)[None, None, :]
>>> channels = kwCOCO.FusedChannelSpec.coerce('Aux:5')
>>> coco_img.add_auxiliary_item(imdata=imdata, channels=channels)
>>> delayed = coco_img.delay(channels='B1|Aux:2:4')
>>> final = delayed.finalize()
```

Example

```
>>> # Test delay when loading in auxiliary space
>>> from kwcoco.coco_image import * # NOQA
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-msi-multisensor')
>>> coco_img = dset.coco_image[1]
>>> stream1 = coco_img.channels.streams()[0]
>>> stream2 = coco_img.channels.streams()[1]
>>> aux_delayed = coco_img.delay(stream1, space='auxiliary')
>>> img_delayed = coco_img.delay(stream1, space='image')
>>> vid_delayed = coco_img.delay(stream1, space='video')
>>> #
>>> aux_imdata = aux_delayed.finalize()
>>> img_imdata = img_delayed.finalize()
>>> assert aux_imdata.shape != img_imdata.shape
>>> # Cannot load multiple auxiliary items at the same time in
>>> # auxiliary space
>>> import pytest
>>> fused_channels = stream1 | stream2
>>> with pytest.raises(kwcoco.exceptions.CoordinateCompatibilityError):
>>>     aux_delayed2 = coco_img.delay(fused_channels, space='auxiliary')
```

`kwcoco.coco_image._delay_load_imglike(bundle_dpath, obj)`

2.3.9 kwcoco.coco_objects1d

Vectorized ORM-like objects used in conjunction with coco_dataset

Module Contents

Classes

<code>ObjectList1D</code>	Vectorized access to lists of dictionary objects
<code>ObjectGroups</code>	An object for holding a groups of <code>ObjectList1D</code> objects
<code>Categories</code>	Vectorized access to category attributes
<code>Videos</code>	Vectorized access to video attributes
<code>Images</code>	Vectorized access to image attributes
<code>Annots</code>	Vectorized access to annotation attributes
<code>AnnotGroups</code>	An object for holding a groups of <code>ObjectList1D</code> objects
<code>ImageGroups</code>	An object for holding a groups of <code>ObjectList1D</code> objects

`class kwcoco.coco_objects1d.ObjectList1D(ids, dset, key)`

Bases: `ubelt.NiceRepr`

Vectorized access to lists of dictionary objects

Lightweight reference to a set of object (e.g. annotations, images) that allows for convenient property access.

Parameters

- **ids** (*List[int]*) – list of ids
- **dset** (*CocoDataset*) – parent dataset
- **key** (*str*) – main object name (e.g. ‘images’, ‘annotations’)

Types: ObjT = Ann | Img | Cat # can be one of these types ObjectList1D gives us access to a List[ObjT]

Example

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo()
>>> # Both annots and images are object lists
>>> self = dset.annots()
>>> self = dset.images()
>>> # can call with a list of ids or not, for everything
>>> self = dset.annots([1, 2, 11])
>>> self = dset.images([1, 2, 3])
>>> self.lookup('id')
>>> self.lookup(['id'])
```

```
__nice__(self)
__iter__(self)
__len__(self)
property _id_to_obj(self)
__getitem__(self, index)
property objs(self)
```

Returns all object dictionaries

Return type List[ObjT]

take(*self, idxs*)
Take a subset by index

Returns ObjectList1D

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo().annots()
>>> assert len(self.take([0, 2, 3])) == 3
```

compress(*self, flags*)
Take a subset by flags

Returns ObjectList1D

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo().images()
>>> assert len(self.compress([True, False, True])) == 2
```

peek(self)

Return the first object dictionary

Returns object dictionary**Return type** ObjT**Example**

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo()
>>> self = dset.images()
>>> assert self.peek()['id'] == 1
>>> # Check that subsets return correct items
>>> sub0 = self.compress([i % 2 == 0 for i in range(len(self))])
>>> sub1 = self.compress([i % 2 == 1 for i in range(len(self))])
>>> assert sub0.peek()['id'] == 1
>>> assert sub1.peek()['id'] == 2
```

lookup(self, key, default=ub.NoParam, keepid=False)

Lookup a list of object attributes

Parameters

- **key** (*str | Iterable*) – name of the property you want to lookup can also be a list of names, in which case we return a dict
- **default** – if specified, uses this value if it doesn't exist in an ObjT.
- **keepid** – if True, return a mapping from ids to the property

Returns a list of whatever type the object is Dict[str, ObjT]**Return type** List[ObjT]**Example**

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo()
>>> self = dset.annots()
>>> self.lookup('id')
>>> key = ['id']
>>> default = None
>>> self.lookup(key=['id', 'image_id'])
>>> self.lookup(key=['id', 'image_id'])
>>> self.lookup(key='foo', default=None, keepid=True)
>>> self.lookup(key=['foo'], default=None, keepid=True)
>>> self.lookup(key=['id', 'image_id'], keepid=True)
```

get(*self, key, default=ub.NoParam, keepid=False*)

Lookup a list of object attributes

Parameters

- **key** (*str*) – name of the property you want to lookup
- **default** – if specified, uses this value if it doesn't exist in an ObjT.
- **keepid** – if True, return a mapping from ids to the property

Returns a list of whatever type the object is Dict[str, ObjT]**Return type** List[ObjT]**Example**

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo()
>>> self = dset.annots()
>>> self.get('id')
>>> self.get(key='foo', default=None, keepid=True)
```

set(*self, key, values*)

Assign a value to each annotation

Parameters

- **key** (*str*) – the annotation property to modify
- **values** (*Iterable | scalar*) – an iterable of values to set for each annot in the dataset. If the item is not iterable, it is assigned to all objects.

Example

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo()
>>> self = dset.annots()
>>> self.set('my-key1', 'my-scalar-value')
>>> self.set('my-key2', np.random.rand(len(self)))
>>> print('dset.imgs = {}'.format(ub.repr2(dset.imgs, nl=1)))
>>> self.get('my-key2')
```

_set(*self, key, values*)

faster less safe version of set

_lookup(*self, key, default=ub.NoParam*)

Example

```
>>> # xdoctest: +REQUIRES(--benchmark)
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('shapes256')
>>> self = annots = dset.annots()
>>> #
>>> import timerit
>>> ti = timerit.Timerit(100, bestof=10, verbose=2)
>>> #
>>> for timer in ti.reset('lookup'):
>>>     with timer:
>>>         self.lookup('image_id')
>>> #
>>> for timer in ti.reset('_lookup'):
>>>     with timer:
>>>         self._lookup('image_id')
>>> #
>>> for timer in ti.reset('image_id'):
>>>     with timer:
>>>         self.image_id
>>> #
>>> for timer in ti.reset('raw1'):
>>>     with timer:
>>>         key = 'image_id'
>>>         [self._dset.anns[_id][key] for _id in self._ids]
>>> #
>>> for timer in ti.reset('raw2'):
>>>     with timer:
>>>         anns = self._dset.anns
>>>         key = 'image_id'
>>>         [anns[_id][key] for _id in self._ids]
>>> #
>>> for timer in ti.reset('lut-gen'):
>>>     with timer:
>>>         _lut = self._obj_lut
>>>         objs = (_lut[_id] for _id in self._ids)
>>>         [obj[key] for obj in objs]
>>> #
>>> for timer in ti.reset('lut-gen-single'):
>>>     with timer:
>>>         _lut = self._obj_lut
>>>         [_lut[_id][key] for _id in self._ids]
```

`attribute_frequency(self)`

Compute the number of times each key is used in a dictionary

Returns Dict[str, int]

Example

```
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo()
>>> self = dset.annots()
>>> attrs = self.attribute_frequency()
>>> print('attrs = {}'.format(ub.repr2(attrs, nl=1)))
```

class kwcoco.coco_objects1d.ObjectGroups(*groups, dset*)

Bases: ubelt.NiceRepr

An object for holding a groups of *ObjectList1D* objects

lookup(*self, key*)

__getitem__(*self, index*)

lookup(*self, key, default=ub.NoParam*)

__nice__(*self*)

class kwcoco.coco_objects1d.Categories(*ids, dset*)

Bases: *ObjectList1D*

Vectorized access to category attributes

SeeAlso: [kwcoco.coco_dataset.MixinCocoObjects.categories\(\)](#)

Example

```
>>> from kwcoco.coco_objects1d import Categories # NOQA
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo()
>>> ids = list(dset.cats.keys())
>>> self = Categories(ids, dset)
>>> print('self.name = {!r}'.format(self.name))
>>> print('self.supercategory = {!r}'.format(self.supercategory))
```

property cids(*self*)

property name(*self*)

property supercategory(*self*)

class kwcoco.coco_objects1d.Videos(*ids, dset*)

Bases: *ObjectList1D*

Vectorized access to video attributes

SeeAlso: [kwcoco.coco_dataset.MixinCocoObjects.videos\(\)](#)

Example

```
>>> from kwcoco.coco_objects1d import Videos # NOQA
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes5')
>>> ids = list(dset.index.videos.keys())
>>> self = Videos(ids, dset)
>>> print('self = {!r}'.format(self))
```

property images(self)**Example**

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo('vidshapes8').videos()
>>> print(self.images)
<ImageGroups(n=8, m=2.0, s=0.0)>
```

class kwcoco.coco_objects1d.Images(ids, dset)
Bases: *ObjectList1D*

Vectorized access to image attributes

SeeAlso: [kwcoco.coco_dataset.MixinCocoObjects.images\(\)](#)

property coco_images(self)
property gids(self)
property gname(self)
property gpath(self)
property width(self)
property height(self)
property size(self)

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo().images()
>>> self._dset._ensure_imgsize()
>>> print(self.size)
[(512, 512), (300, 250), (256, 256)]
```

property area(self)

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo().images()
>>> self._dset._ensure_imgszie()
>>> print(self.area)
[262144, 75000, 65536]
```

property n_annotss(self)

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo().images()
>>> print(ub.repr2(self.n_annotss, nl=0))
[9, 2, 0]
```

property aids(self)

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo().images()
>>> print(ub.repr2(list(map(list, self.aids)), nl=0))
[[1, 2, 3, 4, 5, 6, 7, 8, 9], [10, 11], []]
```

property annotss(self)

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo().images()
>>> print(self.annotss)
<AnnotGroups(n=3, m=3.7, s=3.9)>
```

class kwcoco.coco_objects1d.Annots(ids, dset)

Bases: *ObjectList1D*

Vectorized access to annotation attributes

SeeAlso: *kwcoco.coco_dataset.MixinCocoObjects.annotss()*

property aids(self)

The annotation ids of this column of annotations

property images(self)

Get the column of images

Returns Images

property image_id(self)

property category_id(self)

property gids(self)
Get the column of image-ids

Returns list of image ids

Return type List[int]

property cids(self)
Get the column of category-ids

Returns List[int]

property cnames(self)
Get the column of category names

Returns List[int]

property detections(self)
Get the kwimage-style detection objects

Returns kwimage.Detections

Example

```
>>> # xdoctest: +REQUIRES(module:kwimage)
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo('shapes32').annots([1, 2, 11])
>>> dets = self.detections
>>> print('dets.data = {!r}'.format(dets.data))
>>> print('dets.meta = {!r}'.format(dets.meta))
```

property boxes(self)
Get the column of kwimage-style bounding boxes

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo().annots([1, 2, 11])
>>> print(self.boxes)
<Boxes(xywh,
      array([[ 10,  10, 360, 490],
             [350,   5, 130, 290],
             [124,  96,  45,  18]]))>
```

property xywh(self)
Returns raw boxes

Example

```
>>> import kwCOCO
>>> self = kwCOCO.CocoDataset.demo().annots([1, 2, 11])
>>> print(self.xywh)
```

class kwCOCO.coco_objects1d.AnnotGroups(groups, dset)

Bases: *ObjectGroups*

An object for holding a groups of *ObjectList1D* objects

property cids(self)

property cnames(self)

class kwCOCO.coco_objects1d.ImageGroups(groups, dset)

Bases: *ObjectGroups*

An object for holding a groups of *ObjectList1D* objects

2.3.10 kwCOCO.coco_schema

CommandLine

```
python -m kwCOCO.coco_schema
xdoctest -m kwCOCO.coco_schema __doc__
```

Example

```
>>> import kwCOCO
>>> from kwCOCO.coco_schema import COCO_SCHEMA
>>> import jsonschema
>>> dset = kwCOCO.CocoDataset.demo('shapes1')
>>> # print('dset.dataset = {}'.format(ub.repr2(dset.dataset, nl=2)))
>>> COCO_SCHEMA.validate(dset.dataset)

>>> try:
>>>     jsonschema.validate(dset.dataset, schema=COCO_SCHEMA)
>>> except jsonschema.exceptions.ValidationError as ex:
>>>     vali_ex = ex
>>>     print('ex = {!r}'.format(ex))
>>>     raise
>>> except jsonschema.exceptions.SchemaError as ex:
>>>     print('ex = {!r}'.format(ex))
>>>     schema_ex = ex
>>>     print('schema_ex.instance = {}'.format(ub.repr2(schema_ex.instance, nl=-1)))
>>>     raise

>>> # Test the multispectral image defintino
>>> import copy
>>> dataset = dset.copy().dataset
>>> img = dataset['images'][0]
```

(continues on next page)

(continued from previous page)

```
>>> img.pop('file_name')
>>> import pytest
>>> with pytest.raises(jsonschema.ValidationError):
...     COCO_SCHEMA.validate(dataset)
>>> import pytest
>>> img['auxiliary'] = [{'file_name': 'foobar'}]
>>> with pytest.raises(jsonschema.ValidationError):
...     COCO_SCHEMA.validate(dataset)
>>> img['name'] = 'aux-only images must have a name'
>>> COCO_SCHEMA.validate(dataset)
```

Module Contents

Functions

deprecated(*args)

TUPLE(*args, **kw)

Attributes

elem

ALLOF

ANY

ANYOF

ARRAY

BOOLEAN

INTEGER

NOT

NULL

NUMBER

OBJECT

ONEOF

continues on next page

Table 110 – continued from previous page

<i>STRING</i>
<i>UUID</i>
<i>PATH</i>
<i>KWCOCO_KEYPOINT</i>
<i>KWCOCO_POLYGON</i>
<i>ORIG_COCO_KEYPOINTS</i>
<i>KWCOCO_KEYPOINTS</i>
<i>KEYPOINTS</i>
<i>ORIG_COCO_POLYGON</i>
<i>POLYGON</i>
<i>RUN_LENGTH_ENCODING</i>
<i>BBOX</i>
<i>SEGMENTATION</i>
<i>CATEGORY</i>
<i>KEYPOINT_CATEGORY</i>
<i>VIDEO</i>
<i>CHANNELS</i>
<i>IMAGE</i>
<i>ANNOTATION</i>
<i>COCO_SCHEMA</i>

```
kwcoco.coco_schema.deprecated(*args)
kwcoco.coco_schema.TUPLE(*args, **kw)
kwcoco.coco_schema.elem
kwcoco.coco_schema.ALLOF
kwcoco.coco_schema.ANY
kwcoco.coco_schema.ANYOF
kwcoco.coco_schema.ARRAY
kwcoco.coco_schema.BOOLEAN
```

```
kwcoco.coco_schema.INTEGER
kwcoco.coco_schema.NOT
kwcoco.coco_schema.NULL
kwcoco.coco_schema.NUMBER
kwcoco.coco_schema.OBJECT
kwcoco.coco_schema.ONEOF
kwcoco.coco_schema.STRING
kwcoco.coco_schema.UUID
kwcoco.coco_schema.PATH
kwcoco.coco_schema.KWCOCO_KEYPOINT
kwcoco.coco_schema.KWCOCO_POLYGON
kwcoco.coco_schema.ORIG_COCO_KEYPOINTS
kwcoco.coco_schema.KWCOCO_KEYPOINTS
kwcoco.coco_schema.KEYPOINTS
kwcoco.coco_schema.ORIG_COCO_POLYGON
kwcoco.coco_schema.POLYGON
kwcoco.coco_schema.RUN_LENGTH_ENCODING
kwcoco.coco_schema.BBOX
kwcoco.coco_schema.SEGMENTATION
kwcoco.coco_schema.CATEGORY
kwcoco.coco_schema.KEYPOINT_CATEGORY
kwcoco.coco_schema.VIDEO
kwcoco.coco_schema.CHANNELS
kwcoco.coco_schema.IMAGE
kwcoco.coco_schema.ANNOTATION
kwcoco.coco_schema.COCO_SCHEMA
```

2.3.11 kwcoco.coco_sql_dataset

speed difference so we can take advantage of alchemy's expressiveness?:

Finally got a baseline implementation of an SQLite backend for COCO datasets. This mostly plugs into my existing tools (as long as only read operations are used; haven't implemented writing yet) by duck-typing the dict API.

This solves the issue of forking and then accessing nested dictionaries in the JSON-style COCO objects. (When you access the dictionary Python will increment a reference count which triggers copy-on-write for whatever memory page that data happened to live in. Non-contiguous access had the effect of excessive memory copies).

For “medium sized” datasets its quite a bit slower. Running through a torch DataLoader with 4 workers for 10,000 images executes at a rate of 100Hz but takes 850MB of RAM. Using the duck-typed SQL backend only uses 500MB (which includes the cost of caching), but runs at 45Hz (which includes the benefit of caching).

However, once I scale up to 100,000 images I start seeing benefits. The in-memory dictionary interface chugs at 1.05HZ, and is taking more than 4GB of memory at the time I killed the process (eta was over an hour). The SQL backend ran at 45Hz and took about 3 minutes and used about 2.45GB of memory.

Without a cache, SQL runs at 30HZ and takes 400MB for 10,000 images, and for 100,000 images it gets 30Hz with 1.1GB. There is also a much larger startup time. I’m not exactly sure what it is yet, but its probably some preprocessing I’m doing.

Using a LRU cache we get 45Hz and 1.05GB of memory, so that’s a clear win. We do need to be sure to disable the cache if we ever implement write mode.

I’d like to be a bit faster on the medium sized datasets (I’d really like to avoid caching rows, which is why the speed is currently semi-reasonable), but I don’t think I can do any better than this because single-row lookup time is $O(\log(N))$ for sqlite, whereas its $O(1)$ for dictionaries. (I wish sqlite had an option to create a hash-table index for a table, but I don’t think it does). I optimized as many of the dictionary operations as possible (for instance, iterating through keys, values, and items should be $O(N)$ instead of $O(N \log(N))$), but the majority of the runtime cost is in the single-row lookup time.

There are a few questions I still have if anyone has insight:

- Say I want to select a subset of K rows from a table with N entries, and I have a list of all of the rowids that I want. Is there any way to do this better than $O(K \log(N))$? I tried using a `SELECT col FROM table WHERE id IN (?, ?, ?, ?, ...)` filling in enough ? as there are rows in my subset. I’m not sure what the complexity of using a query like this is. I’m not sure what the `IN` implementation looks like. Can this be done more efficiently by with a temporary table and a `JOIN`?
- There really is no way to do $O(1)$ row lookup in sqlite right? Is there a way in PostgreSQL or some other backend sqlalchemy supports?

I found that PostgreSQL does support hash indexes: <https://www.postgresql.org/docs/13/indexes-types.html> I’m really not interested in setting up a global service though . I also found a 10-year old thread with a hash-index feature request for SQLite, which I unabashedly resurrected <http://sqlite.1065341.n5.nabble.com/Feature-request-hash-index-td23367.html>

Module Contents

Classes

Category

KeypointCategory

Video

Image

Annotation

SqlListProxy

A view of an SQL table that behaves like a Python list

SqlDictProxy

Duck-types an SQL table as a dictionary of dictionaries.

continues on next page

Table 111 – continued from previous page

<code>SqlIdGroupDictProxy</code>	Similar to <code>SqlDictProxy</code> , but maps ids to groups of other ids.
<code>CocoSqlIndex</code>	Simulates the dictionary provided by <code>kwcoco.coco_dataset.CocoIndex</code>
<code>CocoSqlDatabase</code>	Provides an API nearly identical to <code>kwcoco.CocoDatabase</code> , but uses

Functions

<code>orm_to_dict(obj)</code>	
<code>_orm_yielder(query, size=300)</code>	TODO: figure out the best way to yield, in batches or otherwise
<code>_raw_yielder(result, size=300)</code>	TODO: figure out the best way to yield, in batches or otherwise
<code>_new_proxy_cache()</code>	By returning None, we wont use item caching
<code>_handle_sql_uri(uri)</code>	Temporary function to deal with URI. Modern tools seem to use RFC 3968
<code>cached_sql_coco_view(dct_db_fpath=None, sql_db_fpath=None, dset=None, force_rewrite=False)</code>	Attempts to load a cached SQL-View dataset, only loading and converting the
<code>ensure_sql_coco_view(dset, db_fpath=None, force_rewrite=False)</code>	Create a cached on-disk SQL view of an on-disk COCO dataset.
<code>demo(num=10)</code>	
<code>assert_dsets_allclose(dset1, dset2, tag1='dset1', tag2='dset2')</code>	
<code>_benchmark_dset_readtime(dset, tag='?')</code>	Helper for understanding the time differences between backends
<code>_benchmark_dict_proxy_ops(proxy)</code>	Get insight on the efficiency of operations
<code>devcheck()</code>	Scratch work for things that should eventually become unit or doc tests

Attributes

<code>CocoBase</code>	
<code>ALCHEMY_MODE_DEFAULT</code>	
<code>TBLNAME_TO_CLASS</code>	
<code>tblname</code>	

```
kwcoco.coco_sql_dataset.CocoBase
class kwcoco.coco_sql_dataset.Category
    Bases: CocoBase
    __tablename__ = categories
```

```
    id
    name
    alias
    supercategory
    extra

class kwcoco.coco_sql_dataset.KeypointCategory
    Bases: CocoBase

    __tablename__ = keypoint_categories

    id
    name
    alias
    supercategory
    reflection_id
    extra

class kwcoco.coco_sql_dataset.Video
    Bases: CocoBase

    __tablename__ = videos

    id
    name
    caption
    width
    height
    extra

class kwcoco.coco_sql_dataset.Image
    Bases: CocoBase

    __tablename__ = images

    id
    name
    file_name
    width
    height
    video_id
    timestamp
    frame_index
    channels
    auxiliary
    extra
```

```

class kwcoco.coco_sql_dataset.Annotation
    Bases: CocoBase

        __tablename__ = annotations

        id
        image_id
        category_id
        track_id
        segmentation
        keypoints
        bbox
            _bbox_x
            _bbox_y
            _bbox_w
            _bbox_h
        score
        weight
        prob
        iscrowd
        caption
        extra

        kwcoco.coco_sql_dataset.ALCHEMY_MODE_DEFAULT = 0
        kwcoco.coco_sql_dataset.TBLNAME_TO_CLASS
        kwcoco.coco_sql_dataset.tblname
        kwcoco.coco_sql_dataset.orm_to_dict(obj)
        kwcoco.coco_sql_dataset._orm_yielder(query, size=300)
            TODO: figure out the best way to yield, in batches or otherwise
        kwcoco.coco_sql_dataset._raw_yielder(result, size=300)
            TODO: figure out the best way to yield, in batches or otherwise
        kwcoco.coco_sql_dataset._new_proxy_cache()
            By returning None, we wont use item caching

class kwcoco.coco_sql_dataset.SqlListProxy(proxy, session, cls)
    Bases: ubelt.NiceRepr

        A view of an SQL table that behaves like a Python list

        __len__(proxy)
        __nice__(proxy)
        __iter__(proxy)
        __getitem__(proxy, index)
        __contains__(proxy, item)

```

```
__setitem__(proxy, index, value)
__delitem__(proxy, index)

class kwcococo.coco_sql_dataset.SqlDictProxy(proxy, session, cls, keyattr=None, ignore_null=False)
Bases: kwcococo.util.dict_like.DictLike
```

Duck-types an SQL table as a dictionary of dictionaries.

The key is specified by an indexed column (by default it is the *id* column). The values are dictionaries containing all data for that row.

Note: With SQLite indexes are B-Trees so lookup is O(log(N)) and not O(1) as will regular dictionaries. Iteration should still be O(N), but databases have much more overhead than Python dictionaries.

Parameters

- **session** (*Session*) – the sqlalchemy session
- **cls** (*Type*) – the declarative sqlalchemy table class
- **keyattr** – the indexed column to use as the keys
- **ignore_null** (*bool*) – if True, ignores any keys set to NULL, otherwise NULL keys are allowed.

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcococo.coco_sql_dataset import * # NOQA
>>> import pytest
>>> sql_dset, dct_dset = demo(num=10)
>>> proxy = sql_dset.index.anns
```

```
>>> keys = list(proxy.keys())
>>> values = list(proxy.values())
>>> items = list(proxy.items())
>>> item_keys = [t[0] for t in items]
>>> item_vals = [t[1] for t in items]
>>> lut_vals = [proxy[key] for key in keys]
>>> assert item_vals == lut_vals == values
>>> assert item_keys == keys
>>> assert len(proxy) == len(keys)
```

```
>>> goodkey1 = keys[1]
>>> badkey1 = -1000000000000
>>> badkey2 = 'foobarbazbiz'
>>> badkey3 = object()
>>> assert goodkey1 in proxy
>>> assert badkey1 not in proxy
>>> assert badkey2 not in proxy
>>> assert badkey3 not in proxy
>>> with pytest.raises(KeyError):
>>>     proxy[badkey1]
```

(continues on next page)

(continued from previous page)

```
>>> with pytest.raises(KeyError):
>>>     proxy[badkey2]
>>> with pytest.raises(KeyError):
>>>     proxy[badkey3]

>>> # xdoctest: +SKIP
>>> from kwcoco.coco_sql_dataset import _benchmark_dict_proxy_ops
>>> ti = _benchmark_dict_proxy_ops(proxy)
>>> print('ti.measures = {}'.format(ub.repr2(ti.measures, nl=2, align=':', precision=6)))

```

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcoco.coco_sql_dataset import * # NOQA
>>> import kwcoco
>>> # Test the variant of the SqlDictProxy where we ignore None keys
>>> # This is the case for name_to_img and file_name_to_img
>>> dct_dset = kwcoco.CocoDataset.demo('shapes1')
>>> dct_dset.add_image(name='no_file_image1')
>>> dct_dset.add_image(name='no_file_image2')
>>> dct_dset.add_image(name='no_file_image3')
>>> sql_dset = dct_dset.view_sql(memory=True)
>>> assert len(dct_dset.index.imgs) == 4
>>> assert len(dct_dset.index.file_name_to_img) == 1
>>> assert len(dct_dset.index.name_to_img) == 3
>>> assert len(sql_dset.index.imgs) == 4
>>> assert len(sql_dset.index.file_name_to_img) == 1
>>> assert len(sql_dset.index.name_to_img) == 3
```

```
>>> proxy = sql_dset.index.file_name_to_img
>>> assert len(list(proxy.keys())) == 1
>>> assert len(list(proxy.values())) == 1
```

```
>>> proxy = sql_dset.index.name_to_img
>>> assert len(list(proxy.keys())) == 3
>>> assert len(list(proxy.values())) == 3
```

```
>>> proxy = sql_dset.index.imgs
>>> assert len(list(proxy.keys())) == 4
>>> assert len(list(proxy.values())) == 4
```

```
__len__(proxy)
__nice__(proxy)
__contains__(proxy, key)
__getitem__(proxy, key)
keys(proxy)
values(proxy)
```

```
items(proxy)
class kwcoco.coco_sql_dataset.SqlIdGroupDictProxy(proxy, session, valattr, keyattr, parent_keyattr,
group_order_attr=None)
```

Bases: `kwcoco.util.dict_like.DictLike`

Similar to `SqlDictProxy`, but maps ids to groups of other ids.

Simulates a dictionary that maps ids of a parent table to all ids of another table corresponding to rows where a specific column has that parent id.

The items in the group can be sorted by the `group_order_attr` if specified.

For example, imagine two tables: images with one column (id) and annotations with two columns (id, image_id). This class can help provide a mapping from each `image.id` to a `Set[annotation.id]` where those annotation rows have `annotation.image_id = image.id`.

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcoco.coco_sql_dataset import * # NOQA
>>> sql_dset, dct_dset = demo(num=10)
>>> proxy = sql_dset.index.gid_to_aids
```

```
>>> keys = list(proxy.keys())
>>> values = list(proxy.values())
>>> items = list(proxy.items())
>>> item_keys = [t[0] for t in items]
>>> item_vals = [t[1] for t in items]
>>> lut_vals = [proxy[key] for key in keys]
>>> assert item_vals == lut_vals == values
>>> assert item_keys == keys
>>> assert len(proxy) == len(keys)
```

```
>>> # xdoctest: +SKIP
>>> from kwcoco.coco_sql_dataset import _benchmark_dict_proxy_ops
>>> ti = _benchmark_dict_proxy_ops(proxy)
>>> print('ti.measures = {}'.format(ub.repr2(ti.measures, nl=2, align=':', precision=6)))
```

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcoco.coco_sql_dataset import * # NOQA
>>> import kwcoco
>>> # Test the group sorted variant of this by using vidid_to_gids
>>> # where the "gids" must be sorted by the image frame indexes
>>> dct_dset = kwcoco.CocoDataset.demo('vidshapes1')
>>> dct_dset.add_image(name='frame-index-order-demo1', frame_index=-30, video_id=1)
>>> dct_dset.add_image(name='frame-index-order-demo2', frame_index=10, video_id=1)
>>> dct_dset.add_image(name='frame-index-order-demo3', frame_index=3, video_id=1)
>>> dct_dset.add_video(name='empty-video1')
>>> dct_dset.add_video(name='empty-video2')
```

(continues on next page)

(continued from previous page)

```
>>> dct_dset.add_video(name='empty-video3')
>>> sql_dset = dct_dset.view_sql(memory=True)
>>> orig = dct_dset.index.vidid_to_gids
>>> proxy = sql_dset.index.vidid_to_gids
>>> from kwcoco.util.util_json import indexable_allclose
>>> assert indexable_allclose(orig, dict(proxy))
>>> items = list(proxy.items())
>>> vals = list(proxy.values())
>>> keys = list(proxy.keys())
>>> assert len(keys) == len(vals)
>>> assert dict(zip(keys, vals)) == dict(items)
```

```
__nice__(self)
__len__(proxy)
__getitem__(proxy, key)
__contains__(proxy, key)
keys(proxy)
items(proxy)
values(proxy)
```

class kwcoco.coco_sql_dataset.CocoSqlIndex(*index*)

Bases: `object`

Simulates the dictionary provided by `kwcoco.coco_dataset.CocoIndex`

build(*index, parent*)

kwcoco.coco_sql_dataset._handle_sql_uri(*uri*)

Temporary function to deal with URI. Modern tools seem to use RFC 3968 URIs, but sqlalchemy uses RFC 1738. Attempt to gracefully handle special cases. With a better understanding of the above specs, this function may be able to be written more eloquently.

class kwcoco.coco_sql_dataset.CocoSqlDatabase(*uri=None, tag=None, img_root=None*)

Bases: `kwcoco.abstract_coco_dataset.AbstractCocoDataset`, `kwcoco.coco_dataset.MixinCocoAccessors`, `kwcoco.coco_dataset.MixinCocoObjects`, `kwcoco.coco_dataset.MixinCocoStats`, `kwcoco.coco_dataset.MixinCocoDraw`, `ubelt.NiceRepr`

Provides an API nearly identical to `kwcoco.CocoDatabase`, but uses an SQL backend data store. This makes it robust to copy-on-write memory issues that arise when forking, as discussed in¹.

Note: By default constructing an instance of the CocoSqlDatabase does not create a connection to the database. Use the `connect()` method to open a connection.

¹ <https://github.com/pytorch/pytorch/issues/13246>

References

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcococo.coco_sql_dataset import * # NOQA
>>> sql_dset, dct_dset = demo()
>>> dset1, dset2 = sql_dset, dct_dset
>>> tag1, tag2 = 'dset1', 'dset2'
>>> assert_dsets_allclose(sql_dset, dct_dset)
```

`MEMORY_URI = sqlite:///memory:`

`__nice__(self)`

`__getstate__(self)`

Return only the minimal info when pickling this object.

Note: This object IS pickled when the multiprocessing context is “spawn”.

This object is NOT pickled when the multiprocessing context is “fork”. In this case the user needs to be careful to create new connections in the forked subprocesses.

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcococo.coco_sql_dataset import * # NOQA
>>> sql_dset, dct_dset = demo()
>>> # Test pickling works correctly
>>> import pickle
>>> serialized = pickle.dumps(sql_dset)
>>> assert len(serialized) < 3e4, 'should be very small'
>>> copy = pickle.loads(serialized)
>>> dset1, dset2, tag1, tag2 = sql_dset, copy, 'orig', 'copy'
>>> assert_dsets_allclose(dset1, dset2, tag1, tag2)
>>> # --- other methods of copying ---
>>> rw_copy = CocoSqlDatabase(
>>>     sql_dset.uri, img_root=sql_dset.img_root, tag=sql_dset.tag)
>>> rw_copy.connect()
>>> ro_copy = CocoSqlDatabase(
>>>     sql_dset.uri, img_root=sql_dset.img_root, tag=sql_dset.tag)
>>> ro_copy.connect(readonly=True)
>>> assert_dsets_allclose(dset1, ro_copy, tag1, 'ro-copy')
>>> assert_dsets_allclose(dset1, rw_copy, tag1, 'rw-copy')
```

`__setstate__(self, state)`

Reopen new readonly connections when unpickling the object.

`disconnect(self)`

Drop references to any SQL or cache objects

`connect(self, readonly=False)`

Connects this instance to the underlying database.

References

details on read only mode, some of these didnt seem to work <https://github.com/sqlalchemy/sqlalchemy/blob/master/lib/sqlalchemy/dialects/sqlite/pysqlite.py#L71> https://github.com/pudo/dataset/issues/136 <https://writeonly.wordpress.com/2009/07/16/simple-read-only-sqlalchemy-sessions/>

```
property fpath(self)
delete(self)
populate_from(self, dset, verbose=1)
    Copy the information in a CocoDataset into this SQL database.
```

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcoco.coco_sql_dataset import _benchmark_dset_readtime # NOQA
>>> import kwcoco
>>> from kwcoco.coco_sql_dataset import *
>>> dset2 = dset = kwcoco.CocoDataset.demo()
>>> dset1 = self = CocoSqlDatabase('sqlite:///memory:')
>>> self.connect()
>>> self.populate_from(dset)
>>> assert_dsets_allclose(dset1, dset2, tag1='sql', tag2='dct')
>>> ti_sql = _benchmark_dset_readtime(dset1, 'sql')
>>> ti_dct = _benchmark_dset_readtime(dset2, 'dct')
>>> print('ti_sql.rankings = {}'.format(ub.repr2(ti_sql.rankings, nl=2,
... precision=6, align=':')))
>>> print('ti_dct.rankings = {}'.format(ub.repr2(ti_dct.rankings, nl=2,
... precision=6, align=':')))
```

```
property dataset(self)
property anns(self)
property cats(self)
property imgs(self)
property name_to_cat(self)
raw_table(self, table_name)
    Loads an entire SQL table as a pandas DataFrame
```

Parameters `table_name` (`str`) – name of the table

Returns DataFrame

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcoco.coco_sql_dataset import * # NOQA
>>> self, dset = demo()
>>> table_df = self.raw_table('annotations')
>>> print(table_df)
```

`_column_lookup(self, tablename, key, rowids, default=ub.NoParam, keepid=False)`

Convinience method to lookup only a single column of information

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcoco.coco_sql_dataset import * # NOQA
>>> self, dset = demo(10)
>>> tablename = 'annotations'
>>> key = 'category_id'
>>> rowids = list(self.anns.keys())[::-3]
>>> cids1 = self._column_lookup(tablename, key, rowids)
>>> cids2 = self.annots(rowids).get(key)
>>> cids3 = dset.annots(rowids).get(key)
>>> assert cids3 == cids2 == cids1
```

`_all_rows_column_lookup(self, tablename, keys)`

Convinience method to look up all rows from a table and only a few columns.

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcoco.coco_sql_dataset import * # NOQA
>>> self, dset = demo(10)
>>> tablename = 'annotations'
>>> keys = ['id', 'category_id']
>>> rows = self._all_rows_column_lookup(tablename, keys)
```

`tabular_targets(self)`

Convinience method to create an in-memory summary of basic annotation properties with minimal SQL overhead.

Example

```
>>> # xdoctest: +REQUIRES(module:sqlalchemy)
>>> from kwcoco.coco_sql_dataset import * # NOQA
>>> self, dset = demo()
>>> targets = self.tabular_targets()
>>> print(targets.pandas())
```

`property bundle_dpath(self)`

```
property data_fpath(self)
    data_fpath is an alias of fpath

classmethod coerce(self, data)
    Create an SQL CocoDataset from the input pointer.
```

Example

```
import kwcoco dset = kwcoco.CocoDataset.demo('shapes8') data = dset.fpath self = CocoSqlDatabase.coerce(data)

from kwcoco.coco_sql_dataset import CocoSqlDatabase import kwcoco dset = kwcoco.CocoDataset.coerce('spacenet7.kwcoco.json')

self = CocoSqlDatabase.coerce(dset)

from kwcoco.coco_sql_dataset import CocoSqlDatabase sql_dset = CocoSqlDatabase.coerce('spacenet7.kwcoco.json')

# from kwcoco.coco_sql_dataset import CocoSqlDatabase import kwcoco sql_dset = kwcoco.CocoDataset.coerce('_spacenet7.kwcoco.view.v006.sqlite')

kwcoco.coco_sql_dataset.cached_sql_coco_view(dct_db_fpath=None, sql_db_fpath=None, dset=None, force_rewrite=False)

Attempts to load a cached SQL-View dataset, only loading and converting the json dataset if necessary.

kwcoco.coco_sql_dataset.ensure_sql_coco_view(dset, db_fpath=None, force_rewrite=False)

Create a cached on-disk SQL view of an on-disk COCO dataset.
```

Note: This function is fragile. It depends on looking at file modified timestamps to determine if it needs to write the dataset.

```
kwcoco.coco_sql_dataset.demo(num=10)

kwcoco.coco_sql_dataset.assert_dsets_allclose(dset1, dset2, tag1='dset1', tag2='dset2')

kwcoco.coco_sql_dataset._benchmark_dset_readtime(dset, tag='?')
    Helper for understanding the time differences between backends

kwcoco.coco_sql_dataset._benchmark_dict_proxy_ops(proxy)
    Get insight on the efficiency of operations

kwcoco.coco_sql_dataset.devcheck()
    Scratch work for things that should eventually become unit or doc tests

from kwcoco.coco_sql_dataset import * # NOQA self, dset = demo()
```

2.3.12 kwcoco.compat_dataset

A wrapper around the basic kwcoco dataset with a pycocotools API.

We do not recommend using this API because it has some idiosyncrasies, where names can be misleading and APIs are not always clear / efficient: e.g.

- (1) catToImgs returns integer image ids but imgToAnns returns annotation dictionaries.
- (2) showAnns takes a dictionary list as an argument instead of an integer list

The cool thing is that this extends the kwcoco API so you can drop this for compatibility with the old API, but you still get access to all of the kwcoco API including dynamic addition / removal of categories / annotations / images.

Module Contents

Classes

COCO	A wrapper around the basic kwcoco dataset with a pycocotools API.
----------------------	---

class `kwcoco.compat_dataset.COCO(annotation_file=None, **kw)`
Bases: `kwcoco.coco_dataset.CocoDataset`

A wrapper around the basic kwcoco dataset with a pycocotools API.

Example

```
>>> from kwcoco.compat_dataset import * # NOQA
>>> import kwcoco
>>> basic = kwcoco.CocoDataset.demo('shapes8')
>>> self = COCO(basic.dataset)
>>> self.info()
>>> print('self.imgToAnns = {!r}'.format(self.imgToAnns[1]))
>>> print('self.catToImgs = {!r}'.format(self.catToImgs))
```

createIndex(self)

info(self)

Print information about the annotation file. :return:

property imgToAnns(self)

property catToImgs(self)

unlike the name implies, this actually goes from category to image ids Name retained for backward compatibility

getAnnIds(self, imgIds=[], catIds=[], areaRng=[], iscrowd=None)

Get ann ids that satisfy given filter conditions. default skips that filter :param imgIds (int array) : get anns for given imgs

catIds (int array) : get anns for given cats areaRng (float array) : get anns for given area range
(e.g. [0 inf]) iscrowd (boolean) : get anns for given crowd label (False or True)

Returns ids (int array) : integer array of ann ids

Example

```
>>> from kwcoco.compat_dataset import * # NOQA
>>> import kwcoco
>>> self = COCO(kwcoco.CocoDataset.demo('shapes8').dataset)
>>> self.getAnnIds()
>>> self.getAnnIds(imgIds=1)
>>> self.getAnnIds(imgIds=[1])
>>> self.getAnnIds(catIds=[3])
```

getCatIds(*self*, *catNms*=[], *supNms*=[], *catIds*=[])

filtering parameters. default skips that filter. :param catNms (str array) : get cats for given cat names :param supNms (str array) : get cats for given supercategory names :param catIds (int array) : get cats for given cat ids :return: ids (int array) : integer array of cat ids

Example

```
>>> from kwcoco.compat_dataset import * # NOQA
>>> import kwcoco
>>> self = COCO(kwcoco.CocoDataset.demo('shapes8').dataset)
>>> self.getCatIds()
>>> self.getCatIds(catNms=['superstar'])
>>> self.getCatIds(supNms=['raster'])
>>> self.getCatIds(catIds=[3])
```

getImgIds(*self*, *imgIds*=[], *catIds*=[])

Get img ids that satisfy given filter conditions. :param imgIds (int array) : get imgs for given ids :param catIds (int array) : get imgs with all given cats :return: ids (int array) : integer array of img ids

Example

```
>>> from kwcoco.compat_dataset import * # NOQA
>>> import kwcoco
>>> self = COCO(kwcoco.CocoDataset.demo('shapes8').dataset)
>>> self.getImgIds(imgIds=[1, 2])
>>> self.getImgIds(catIds=[3, 6, 7])
>>> self.getImgIds(catIds=[3, 6, 7], imgIds=[1, 2])
```

loadAnns(*self*, *ids*=[])

Load anns with the specified ids. :param ids (int array) : integer ids specifying anns :return: anns (object array) : loaded ann objects

loadCats(*self*, *ids*=[])

Load cats with the specified ids. :param ids (int array) : integer ids specifying cats :return: cats (object array) : loaded cat objects

loadImgs(*self*, *ids*=[])

Load anns with the specified ids. :param ids (int array) : integer ids specifying img :return: imgs (object array) : loaded img objects

showAnns(*self*, *anns*, *draw_bbox=False*)

Display the specified annotations. :param anns (array of object): annotations to display :return: None

loadRes(*self, resFile*)

Load result file and return a result api object. :param resFile (str) : file name of result file :return: res (obj) : result api object

download(*self, tarDir=None, imgIds=[]*)

Download COCO images from mscoco.org server. :param tarDir (str): COCO results directory name
imgIds (list): images to be downloaded

Returns**loadNumpyAnnotations**(*self, data*)

Convert result data from a numpy array [Nx7] where each row contains {imageID,x1,y1,w,h,score,class} :param data (numpy.ndarray) :return: annotations (python nested list)

annToRLE(*self, ann*)

Convert annotation which can be polygons, uncompressed RLE to RLE. :return: binary mask (numpy 2D array)

Note:

- This requires the C-extensions for kwimage to be installed due to the need to interface with the bytes RLE format.
-

Example

```
>>> from kwcoco.compat_dataset import * # NOQA
>>> import kwcoco
>>> self = COCO(kwcoco.CocoDataset.demo('shapes8').dataset)
>>> try:
>>>     rle = self.annToRLE(self.anns[1])
>>> except NotImplementedError:
>>>     import pytest
>>>     pytest.skip('missing kwimage c-extensions')
>>> else:
>>>     assert len(rle['counts']) > 2
>>> # xdoctest: +REQUIRES(module:pycocotools)
>>> self.conform(legacy=True)
>>> orig = self._aspycoco().annToRLE(self.anns[1])
```

annToMask(*self, ann*)

Convert annotation which can be polygons, uncompressed RLE, or RLE to binary mask.

Returns binary mask (numpy 2D array)

Note: The mask is returned as a fortran (F-style) array with the same dimensions as the parent image.

2.3.13 kwcoco.exceptions

Module Contents

exception `kwcoco.exceptions.AddError`

Bases: `ValueError`

Generic error when trying to add a category/annotation/image

exception `kwcoco.exceptions.DuplicateAddError`

Bases: `ValueError`

Error when trying to add a duplicate item

exception `kwcoco.exceptions.InvalidAddError`

Bases: `ValueError`

Error when trying to invalid data

exception `kwcoco.exceptions.CoordinateCompatibilityError`

Bases: `ValueError`

Error when trying to perform operations on data in different coordinate systems.

2.3.14 kwcoco.kpf

WIP:

Conversions to and from KPF format.

Module Contents

Functions

<code>coco_to_kpf(coco_dset)</code>	import kwcoco
<code>demo()</code>	

`kwcoco.kpf.coco_to_kpf(coco_dset)`

import kwcoco coco_dset = kwcoco.CocoDataset.demo('shapes8')

`kwcoco.kpf.demo()`

2.3.15 kwcoco.kw18

A helper for converting COCO to / from KW18 format.

KW18 File Format <https://docs.google.com/spreadsheets/d/1DFCwoTKnDv8qfy3raM7QXtir2Fjfj9j8-z8px5Bu0q8/edit#gid=10>

The kw18.trk files are text files, space delimited; each row is one frame of one track and all rows have the same number of columns. The fields are:

<code>01) track_ID</code>	: identifies the track
<code>02) num_frames:</code>	number of frames in the track

(continues on next page)

(continued from previous page)

```

03) frame_id      : frame number for this track sample
04) loc_x         : X-coordinate of the track (image/ground coords)
05) loc_y         : Y-coordinate of the track (image/ground coords)
06) vel_x          : X-velocity of the object (image/ground coords)
07) vel_y          : Y-velocity of the object (image/ground coords)
08) obj_loc_x     : X-coordinate of the object (image coords)
09) obj_loc_y     : Y-coordinate of the object (image coords)
10) bbox_min_x    : minimum X-coordinate of bounding box (image coords)
11) bbox_min_y    : minimum Y-coordinate of bounding box (image coords)
12) bbox_max_x    : maximum X-coordinate of bounding box (image coords)
13) bbox_max_y    : maximum Y-coordinate of bounding box (image coords)
14) area           : area of object (pixels)
15) world_loc_x   : X-coordinate of object in world
16) world_loc_y   : Y-coordinate of object in world
17) world_loc_z   : Z-coordiante of object in world
18) timestamp      : timestamp of frame (frames)
For the location and velocity of object centroids, use fields 4-7.
Bounding box is specified using coordinates of the top-left and bottom
right corners. Fields 15-17 may be ignored.

```

The kw19.trk **and** kw20.trk files, when present, add the following field(s):

19) **object** class: estimated **class of** the **object**, either 1 (person), 2 (vehicle), **or** 3 (other).
 20) Activity ID -- refer to activities.txt **for** index **and** list of activities.

Module Contents

Classes

[KW18](#)

A DataFrame like object that stores KW18 column data

Functions

[_ensure_kw18_column_order\(df\)](#)

Ensure expected kw18 columns exist and are in the correct order.

[class kwcoco.kw18.KW18\(data\)](#)

Bases: [kwarray.DataFrameArray](#)

A DataFrame like object that stores KW18 column data

Example

```
>>> import kwcoco
>>> from kwcoco.kw18 import KW18
>>> coco_dset = kwcoco.CocoDataset.demo('shapes')
>>> kw18_dset = KW18.from_coco(coco_dset)
>>> print(kw18_dset.pandas())

DEFAULT_COLUMNS = ['track_id', 'track_length', 'frame_number',
'tracking_plane_loc_x', 'tracking_plane_loc_y', ...]

classmethod demo(KW18)

classmethod from_coco(KW18, coco_dset)

to_coco(self, image_paths=None, video_name=None)
    Translates a kw18 files to a CocoDataset.
```

Note: kw18 does not contain complete information, and as such the returned coco dataset may need to be augmented.

Parameters

- **image_paths** (*Dict[int, str]*, *default=None*) – if specified, maps frame numbers to image file paths.
- **video_name** (*str*, *default=None*) – if specified records the name of the video this kw18 belongs to

Todo:

- [X] allow kwargs to specify path to frames / videos
-

Example

```
>>> from kwcoco.kw18 import KW18
>>> from os.path import join
>>> import ubelt as ub
>>> import kwimage
>>> # Prep test data - autogen a demo kw18 and write it to disk
>>> dpath = ub.ensure_app_cache_dir('kwcoco/kw18')
>>> kw18_fpath = join(dpath, 'test.kw18')
>>> KW18.demo().dump(kw18_fpath)
>>> #
>>> # Load the kw18 file
>>> self = KW18.load(kw18_fpath)
>>> # Pretend that these image correspond to kw18 frame numbers
>>> frame_names = [kwimage.grab_test_image_fpath(k) for k in kwimage.grab_test_
>>> image.keys()]
>>> frame_ids = sorted(set(self['frame_number']))
>>> image_paths = dict(zip(frame_ids, frame_names))
```

(continues on next page)

(continued from previous page)

```
>>> #
>>> # Convert the kw18 to kwcoco and specify paths to images
>>> coco_dset = self.to_coco(image_paths=image_paths, video_name='dummy.mp4')
>>> #
>>> # Now we can draw images
>>> canvas = coco_dset.draw_image(1)
>>> # xdoctest: +REQUIRES(--draw)
>>> kwimage.imwrite('foo.jpg', canvas)
>>> # Draw all images
>>> for gid in coco_dset.imgs.keys():
>>>     canvas = coco_dset.draw_image(gid)
>>>     fpath = join(dpath, 'gid_{}.jpg'.format(gid))
>>>     print('write fpath = {!r}'.format(fpath))
>>>     kwimage.imwrite(fpath, canvas)
```

classmethod `load(KW18, file)`**Example**

```
>>> import kwcoco
>>> from kwcoco.kw18 import KW18
>>> coco_dset = kwcoco.CocoDataset.demo('shapes')
>>> kw18_dset = KW18.from_coco(coco_dset)
>>> print(kw18_dset.pandas())
```

classmethod `loads(KW18, text)`**Example**

```
>>> self = KW18.demo()
>>> text = self.dumps()
>>> self2 = KW18.loads(text)
>>> empty = KW18.loads('')
```

dump(self, file)**dumps(self)****Example**

```
>>> self = KW18.demo()
>>> text = self.dumps()
>>> print(text)
```

`kwcoco.kw18._ensure_kw18_column_order(df)`

Ensure expected kw18 columns exist and are in the correct order.

Example

```
>>> import pandas as pd
>>> df = pd.DataFrame(columns=KW18.DEFAULT_COLUMNS[0:18])
>>> _ensure_kw18_column_order(df)
>>> df = pd.DataFrame(columns=KW18.DEFAULT_COLUMNS[0:19])
>>> _ensure_kw18_column_order(df)
>>> df = pd.DataFrame(columns=KW18.DEFAULT_COLUMNS[0:18] + KW18.DEFAULT_
>>> COLUMNS[20:21])
>>> assert np.all(_ensure_kw18_column_order(df).columns == df.columns)
```

2.4 Package Contents

2.4.1 Classes

<code>AbstractCocoDataset</code>	This is a common base for all variants of the Coco Dataset
<code>CocoDataset</code>	The main coco dataset class with a json dataset backend.
<code>CocoImage</code>	An object-oriented representation of a coco image.
<code>CategoryTree</code>	Wrapper that maintains flat or hierarchical category information.
<code>ChannelSpec</code>	Parse and extract information about network input channel specs for
<code>FusedChannelSpec</code>	A specific type of channel spec with only one early fused stream.

`class kwcoco.AbstractCocoDataset`

Bases: `abc.ABC`

This is a common base for all variants of the Coco Dataset

At the time of writing there is `kwcoco.CocoDataset` (which is the dictionary-based backend), and the `kwcoco.coco_sql_dataset.CocoSqlDataset`, which is experimental.

`class kwcoco.CocoDataset(data=None, tag=None, bundle_dpath=None, img_root=None, fname=None, autobuild=True)`

Bases: `kwcoco.abstract_coco_dataset.AbstractCocoDataset, MixinCocoAddRemove, MixinCocoStats, MixinCocoObjects, MixinCocoDraw, MixinCocoAccessors, MixinCocoExtras, MixinCocoIndex, MixinCocoDepriate, ubelt.NiceRepr`

The main coco dataset class with a json dataset backend.

Variables

- `dataset` (`Dict`) – raw json data structure. This is the base dictionary that contains {‘annotations’: List, ‘images’: List, ‘categories’: List}
- `index` (`CocoIndex`) – an efficient lookup index into the coco data structure. The index defines its own attributes like `anns`, `cats`, `imgs`, `gid_to_aids`, `file_name_to_img`, etc. See `CocoIndex` for more details on which attributes are available.
- `fpath` (`PathLike` / `None`) – if known, this stores the filepath the dataset was loaded from
- `tag` (`str`) – A tag indicating the name of the dataset.

- **bundle_dpath** (*PathLike / None*) – If known, this is the root path that all image file names are relative to. This can also be manually overwritten by the user.
- **hashid** (*str / None*) – If computed, this will be a hash uniquely identifying the dataset. To ensure this is computed see `kwcoco.coco_dataset.MixinCocoExtras._build_hashid()`.

References

<http://cocodataset.org/#format> <http://cocodataset.org/#download>

CommandLine

```
python -m kwcoco.coco_dataset CocoDataset --show
```

Example

```
>>> from kwcoco.coco_dataset import demo_coco_data
>>> import kwcoco
>>> import ubelt as ub
>>> # Returns a coco json structure
>>> dataset = demo_coco_data()
>>> # Pass the coco json structure to the API
>>> self = kwcoco.CocoDataset(dataset, tag='demo')
>>> # Now you can access the data using the index and helper methods
>>> #
>>> # Start by looking up an image by it's COCO id.
>>> image_id = 1
>>> img = self.index.imgs[image_id]
>>> print(ub.repr2(img, nl=1, sort=1))
{
    'file_name': 'astro.png',
    'id': 1,
    'url': 'https://i.imgur.com/KXhKM72.png',
}
>>> #
>>> # Use the (gid_to_aids) index to lookup annotations in the image
>>> annotation_id = sorted(self.index.gid_to_aids[image_id])[0]
>>> ann = self.index.anns[annotation_id]
>>> print(ub.repr2(ub.dict_diff(ann, {'segmentation'}), nl=1))
{
    'bbox': [10, 10, 360, 490],
    'category_id': 1,
    'id': 1,
    'image_id': 1,
    'keypoints': [247, 101, 2, 202, 100, 2],
}
>>> #
>>> # Use annotation category id to look up that information
>>> category_id = ann['category_id']
```

(continues on next page)

(continued from previous page)

```

>>> cat = self.index.cats[category_id]
>>> print('cat = {}'.format(ub.repr2(cat, nl=1, sort=1)))
cat = {
    'id': 1,
    'name': 'astronaut',
    'supercategory': 'human',
}
>>> #
>>> # Now play with some helper functions, like extended statistics
>>> extended_stats = self.extended_stats()
>>> print('extended_stats = {}'.format(ub.repr2(extended_stats, nl=1, precision=2, sort=1)))
extended_stats = {
    'annots_per_img': {'mean': 3.67, 'std': 3.86, 'min': 0.00, 'max': 9.00, 'nMin': 1, 'nMax': 1, 'shape': (3,)},
    'imgs_per_cat': {'mean': 0.88, 'std': 0.60, 'min': 0.00, 'max': 2.00, 'nMin': 2, 'nMax': 1, 'shape': (8,)},
    'cats_per_img': {'mean': 2.33, 'std': 2.05, 'min': 0.00, 'max': 5.00, 'nMin': 1, 'nMax': 1, 'shape': (3,)},
    'annots_per_cat': {'mean': 1.38, 'std': 1.49, 'min': 0.00, 'max': 5.00, 'nMin': 2, 'nMax': 1, 'shape': (8,)},
    'imgs_per_video': {'empty_list': True},
}
>>> # You can "draw" a raster of the annotated image with cv2
>>> canvas = self.draw_image(2)
>>> # Or if you have matplotlib you can "show" the image with mpl objects
>>> # xdoctest: +REQUIRES(--show)
>>> from matplotlib import pyplot as plt
>>> fig = plt.figure()
>>> ax1 = fig.add_subplot(1, 2, 1)
>>> self.show_image(gid=2)
>>> ax2 = fig.add_subplot(1, 2, 2)
>>> ax2.imshow(canvas)
>>> ax1.set_title('show with matplotlib')
>>> ax2.set_title('draw with cv2')
>>> plt.show()

```

property fpath(self)

In the future we will deprecate img_root for bundle_dpath

_infer_dirs(self)**classmethod from_data(CocoDataset, data, bundle_dpath=None, img_root=None)**

Constructor from a json dictionary

classmethod from_image_paths(CocoDataset, gpaths, bundle_dpath=None, img_root=None)

Constructor from a list of images paths.

This is a convinience method.

Parameters **gpaths** (*List[str]*) – list of image paths

Example

```
>>> coco_dset = CocoDataset.from_image_paths(['a.png', 'b.png'])
>>> assert coco_dset.n_images == 2
```

classmethod from_coco_paths(CocoDataset, fpaths, max_workers=0, verbose=1, mode='thread', union='try')

Constructor from multiple coco file paths.

Loads multiple coco datasets and unions the result

Note: if the union operation fails, the list of individually loaded files is returned instead.

Parameters

- **fpaths** (*List[str]*) – list of paths to multiple coco files to be loaded and unioned.
- **max_workers** (*int, default=0*) – number of worker threads / processes
- **verbose** (*int*) – verbosity level
- **mode** (*str*) – thread, process, or serial
- **union** (*str | bool, default='try'*) – If True, unions the result datasets after loading. If False, just returns the result list. If 'try', then try to preform the union, but return the result list if it fails.

copy(self)

Deep copies this object

Example

```
>>> from kwcoco.coco_dataset import *
>>> self = CocoDataset.demo()
>>> new = self.copy()
>>> assert new.imgs[1] is new.dataset['images'][0]
>>> assert new.imgs[1] == self.dataset['images'][0]
>>> assert new.imgs[1] is not self.dataset['images'][0]
```

__nice__(self)

dumps(self, indent=None, newlines=False)

Writes the dataset out to the json format

Parameters newlines (bool) – if True, each annotation, image, category gets its own line

Note:

Using newlines=True is similar to: print(ub.repr2(dset.dataset, nl=2, trailsep=False)) However, the above may not output valid json if it contains ndarrays.

Example

```
>>> from kwcoco.coco_dataset import *
>>> import json
>>> self = CocoDataset.demo()
>>> text = self.dumps(newlines=True)
>>> print(text)
>>> self2 = CocoDataset(json.loads(text), tag='demo2')
>>> assert self2.dataset == self.dataset
>>> assert self2.dataset is not self.dataset
```

```
>>> text = self.dumps(newlines=True)
>>> print(text)
>>> self2 = CocoDataset(json.loads(text), tag='demo2')
>>> assert self2.dataset == self.dataset
>>> assert self2.dataset is not self.dataset
```

dump(self, file, indent=None, newlines=False)

Writes the dataset out to the json format

Parameters

- **file (PathLike | FileLike)** – Where to write the data. Can either be a path to a file or an open file pointer / stream.
- **newlines (bool)** – if True, each annotation, image, category gets its own line.

Example

```
>>> import tempfile
>>> from kwcoco.coco_dataset import *
>>> self = CocoDataset.demo()
>>> file = tempfile.NamedTemporaryFile('w')
>>> self.dump(file)
>>> file.seek(0)
>>> text = open(file.name, 'r').read()
>>> print(text)
>>> file.seek(0)
>>> dataset = json.load(open(file.name, 'r'))
>>> self2 = CocoDataset(dataset, tag='demo2')
>>> assert self2.dataset == self.dataset
>>> assert self2.dataset is not self.dataset
```

```
>>> file = tempfile.NamedTemporaryFile('w')
>>> self.dump(file, newlines=True)
>>> file.seek(0)
>>> text = open(file.name, 'r').read()
>>> print(text)
>>> file.seek(0)
>>> dataset = json.load(open(file.name, 'r'))
>>> self2 = CocoDataset(dataset, tag='demo2')
>>> assert self2.dataset == self.dataset
>>> assert self2.dataset is not self.dataset
```

```
_check_json_serializable(self, verbose=1)
    Debug which part of a coco dataset might not be json serializable

_check_integrity(self)
    perform all checks

_check_index(self)
```

Example

```
>>> import kwCOCO
>>> self = kwCOCO.CocoDataset.demo()
>>> self._check_index()
>>> # Force a failure
>>> self.index.anns.pop(1)
>>> self.index.anns.pop(2)
>>> import pytest
>>> with pytest.raises(AssertionError):
>>>     self._check_index()
```

```
_check_pointers(self, verbose=1)
    Check that all category and image ids referenced by annotations exist

_build_index(self)

union(*others, disjoint_tracks=True, **kwargs)
    Merges multiple CocoDataset items into one. Names and associations are retained, but ids may be different.
```

Parameters

- ***others** – a series of CocoDatasets that we will merge. Note, if called as an instance method, the “self” instance will be the first item in the “others” list. But if called like a classmethod, “others” will be empty by default.
- **disjoint_tracks** (*bool, default=True*) – if True, we will assume track-ids are disjoint and if two datasets share the same track-id, we will disambiguate them. Otherwise they will be copied over as-is.
- ****kwargs** – constructor options for the new merged CocoDataset

Returns a new merged coco dataset

Return type *CocoDataset*

CommandLine

```
xdoctest -m kwCOCO.coco_dataset CocoDataset.union
```

Example

```
>>> # Test union works with different keypoint categories
>>> dset1 = CocoDataset.demo('shapes1')
>>> dset2 = CocoDataset.demo('shapes2')
>>> dset1.remove_keypoint_categories(['bot_tip', 'mid_tip', 'right_eye'])
>>> dset2.remove_keypoint_categories(['top_tip', 'left_eye'])
>>> dset_12a = CocoDataset.union(dset1, dset2)
>>> dset_12b = dset1.union(dset2)
>>> dset_21 = dset2.union(dset1)
>>> def add_hist(h1, h2):
>>>     return {k: h1.get(k, 0) + h2.get(k, 0) for k in set(h1) | set(h2)}
>>> kpfreq1 = dset1.keypoint_annotation_frequency()
>>> kpfreq2 = dset2.keypoint_annotation_frequency()
>>> kpfreq_want = add_hist(kpfreq1, kpfreq2)
>>> kpfreq_got1 = dset_12a.keypoint_annotation_frequency()
>>> kpfreq_got2 = dset_12b.keypoint_annotation_frequency()
>>> assert kpfreq_want == kpfreq_got1
>>> assert kpfreq_want == kpfreq_got2
```

```
>>> # Test disjoint gid datasets
>>> import kwcoco
>>> dset1 = kwcoco.CocoDataset.demo('shapes3')
>>> for new_gid, img in enumerate(dset1.dataset['images'], start=10):
>>>     for aid in dset1.gid_to_aids[img['id']]:
>>>         dset1.anns[aid]['image_id'] = new_gid
>>>     img['id'] = new_gid
>>> dset1.index.clear()
>>> dset1._build_index()
>>> #
>>> dset2 = kwcoco.CocoDataset.demo('shapes2')
>>> for new_gid, img in enumerate(dset2.dataset['images'], start=100):
>>>     for aid in dset2.gid_to_aids[img['id']]:
>>>         dset2.anns[aid]['image_id'] = new_gid
>>>     img['id'] = new_gid
>>> dset1.index.clear()
>>> dset2._build_index()
>>> others = [dset1, dset2]
>>> merged = kwcoco.CocoDataset.union(*others)
>>> print('merged = {!r}'.format(merged))
>>> print('merged imgs = {}'.format(ub.repr2(merged.imgs, nl=1)))
>>> assert set(merged.imgs) & set([10, 11, 12, 100, 101]) == set(merged.imgs)
```

```
>>> # Test data is not preserved
>>> dset2 = kwcoco.CocoDataset.demo('shapes2')
>>> dset1 = kwcoco.CocoDataset.demo('shapes3')
>>> others = (dset1, dset2)
>>> cls = self = kwcoco.CocoDataset
>>> merged = cls.union(*others)
>>> print('merged = {!r}'.format(merged))
>>> print('merged imgs = {}'.format(ub.repr2(merged.imgs, nl=1)))
>>> assert set(merged.imgs) & set([1, 2, 3, 4, 5]) == set(merged.imgs)
```

```
>>> # Test track-ids are mapped correctly
>>> dset1 = kwcoco.CocoDataset.demo('vidshapes1')
>>> dset2 = kwcoco.CocoDataset.demo('vidshapes2')
>>> dset3 = kwcoco.CocoDataset.demo('vidshapes3')
>>> others = (dset1, dset2, dset3)
>>> for dset in others:
>>>     [a.pop('segmentation', None) for a in dset.index.anns.values()]
>>>     [a.pop('keypoints', None) for a in dset.index.anns.values()]
>>>     cls = self = kwcoco.CocoDataset
>>>     merged = cls.union(*others, disjoint_tracks=1)
>>>     print('dset1.anns = {}'.format(ub.repr2(dset1.anns, nl=1)))
>>>     print('dset2.anns = {}'.format(ub.repr2(dset2.anns, nl=1)))
>>>     print('dset3.anns = {}'.format(ub.repr2(dset3.anns, nl=1)))
>>>     print('merged.anns = {}'.format(ub.repr2(merged.anns, nl=1)))
```

Example

```
>>> import kwcoco
>>> # Test empty union
>>> empty_union = kwcoco.CocoDataset.union()
>>> assert len(empty_union.index.imgs) == 0
```

Todo:

- [] are supercategories broken?
 - [] reuse image ids where possible
 - [] reuse annotation / category ids where possible
 - [X] handle case where no inputs are given
 - [x] disambiguate track-ids
 - [x] disambiguate video-ids
-

`subset(self, gids, copy=False, autobuild=True)`

Return a subset of the larger coco dataset by specifying which images to port. All annotations in those images will be taken.

Parameters

- **gids** (*List[int]*) – image-ids to copy into a new dataset
- **copy** (*bool, default=False*) – if True, makes a deep copy of all nested attributes, otherwise makes a shallow copy.
- **autobuild** (*bool, default=True*) – if True will automatically build the fast lookup index.

Example

```
>>> self = CocoDataset.demo()
>>> gids = [1, 3]
>>> sub_dset = self.subset(gids)
>>> assert len(self.index.gid_to_aids) == 3
>>> assert len(sub_dset.gid_to_aids) == 2
```

Example

```
>>> import kwcoco
>>> self = kwcoco.CocoDataset.demo('vidshapes2')
>>> gids = [1, 2]
>>> sub_dset = self.subset(gids, copy=True)
>>> assert len(sub_dset.index.videos) == 1
>>> assert len(self.index.videos) == 2
```

Example

```
>>> self = CocoDataset.demo()
>>> sub1 = self.subset([1])
>>> sub2 = self.subset([2])
>>> sub3 = self.subset([3])
>>> others = [sub1, sub2, sub3]
>>> rejoined = CocoDataset.union(*others)
>>> assert len(sub1.anns) == 9
>>> assert len(sub2.anns) == 2
>>> assert len(sub3.anns) == 0
>>> assert rejoined.basic_stats() == self.basic_stats()
```

`view_sql(self, force_rewrite=False, memory=False)`

Create a cached SQL interface to this dataset suitable for large scale multiprocessing use cases.

Parameters

- **force_rewrite** (*bool, default=False*) – if True, forces an update to any existing cache file on disk
- **memory** (*bool, default=False*) – if True, the database is constructed in memory.

Note: This view cache is experimental and currently depends on the timestamp of the file pointed to by `self.fpath`. In other words dont use this on in-memory datasets.

`class kwcoco.CocoImage(img, dset=None)`
Bases: `ubelt.NiceRepr`

An object-oriented representation of a coco image.

It provides helper methods that are specific to a single image.

This operates directly on a single coco image dictionary, but it can optionally be connected to a parent dataset, which allows it to use CocoDataset methods to query about relationships and resolve pointers.

This is different than the Images class in coco_object1d, which is just a vectorized interface to multiple objects.

Example

```
>>> import kwcoco
>>> dset1 = kwcoco.CocoDataset.demo('shapes8')
>>> dset2 = kwcoco.CocoDataset.demo('vidshapes8-multispectral')

>>> self = CocoImage(dset1 imgs[1], dset1)
>>> print('self = {!r}'.format(self))
>>> print('self.channels = {}'.format(ub.repr2(self.channels, nl=1)))

>>> self = CocoImage(dset2 imgs[1], dset2)
>>> print('self.channels = {}'.format(ub.repr2(self.channels, nl=1)))
>>> self.primary_asset()

classmethod from_gid(cls, dset, gid)
property bundle_dpath(self)
property video(self)
    Helper to grab the video for this image if it exists
detach(self)
    Removes references to the underlying coco dataset, but keeps special information such that it wont be
    needed.
__nice__(self)
```

Example

```
>>> from kwcoco.coco_image import * # NOQA
>>> import kwcoco
>>> with ub.CaptureStdout() as cap:
...     dset = kwcoco.CocoDataset.demo('shapes8')
>>> self = CocoImage(dset.dataset['images'][0], dset)
>>> print('self = {!r}'.format(self))

>>> dset = kwcoco.CocoDataset.demo()
>>> self = CocoImage(dset.dataset['images'][0], dset)
>>> print('self = {!r}'.format(self))

stats(self)
__getitem__(self, key)
keys(self)
get(self, key, default=ub.NoParam)
    Duck type some of the dict interface
property channels(self)
property num_channels(self)
property dsize(self)
```

primary_image_filepath(*self*, *requires=None*)
primary_asset(*self*, *requires=None*)
Compute a “main” image asset.

Notes

Uses a heuristic.

- First, try to find the auxiliary image that has with the smallest distortion to the base image (if known via warp_aux_to_img)
- Second, break ties by using the largest image if w / h is known
- Last, if previous information not available use the first auxiliary image.

Parameters *requires* (*List[str]*) – list of attribute that must be non-None to consider an object as the primary one.

Todo:

- [] Add in primary heuristics
-

Example

```
>>> import kwarray
>>> from kwcoco.coco_image import * # NOQA
>>> rng = kwarray.ensure_rng(0)
>>> def random_auxiliary(name, w=None, h=None):
>>>     return {'file_name': name, 'width': w, 'height': h}
>>> self = CocoImage({
>>>     'auxiliary': [
>>>         random_auxiliary('1'),
>>>         random_auxiliary('2'),
>>>         random_auxiliary('3'),
>>>     ]
>>> })
>>> assert self.primary_asset()['file_name'] == '1'
>>> self = CocoImage({
>>>     'auxiliary': [
>>>         random_auxiliary('1'),
>>>         random_auxiliary('2', 3, 3),
>>>         random_auxiliary('3'),
>>>     ]
>>> })
>>> assert self.primary_asset()['file_name'] == '2'
```

iter_image_filepaths(*self*)
iter_asset_objs(*self*)
Iterate through base + auxiliary dicts that have file paths
Yields *dict* – an image or auxiliary dictionary

find_asset_obj(*self, channels*)

Find the asset dictionary with the specified channels

add_auxiliary_item(*self, file_name=None, channels=None, imdata=None, warp_aux_to_img=None, width=None, height=None, imwrite=False*)

Adds an auxiliary item to the image dictionary.

This operation can be done purely in-memory (the default), or the image data can be written to a file on disk (via the imwrite=True flag).

Parameters

- **file_name** (*str | None*) – The name of the file relative to the bundle directory. If unspecified, imdata must be given.
- **channels** (*str | kwcoco.FusedChannelSpec*) – The channel code indicating what each of the bands represents. These channels should be disjoint wrt to the existing data in this image (this is not checked).
- **imdata** (*ndarray | None*) – The underlying image data this auxiliary item represents. If unspecified, it is assumed file_name points to a path on disk that will eventually exist. If imdata, file_name, and the special imwrite=True flag are specified, this function will write the data to disk.
- **warp_aux_to_img** (*kwimage.Affine*) – The transformation from this auxiliary space to image space. If unspecified, assumes this item is related to image space by only a scale factor.
- **width** (*int*) – Width of the data in auxiliary space (inferred if unspecified)
- **height** (*int*) – Height of the data in auxiliary space (inferred if unspecified)
- **imwrite** (*bool*) – If specified, both imdata and file_name must be specified, and this will write the data to disk. Note: it is recommended that you simply call imwrite yourself before or after calling this function. This lets you better control imwrite parameters.

Todo:

- [] Allow imwrite to specify an executor that is used to return a Future so the imwrite call does not block.
-

Example

```
>>> from kwcoco.coco_image import * # NOQA
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral')
>>> coco_img = dset.coco_image(1)
>>> imdata = np.random.rand(32, 32, 5)
>>> channels = kwcoco.FusedChannelSpec.coerce('Aux:5')
>>> coco_img.add_auxiliary_item(imdata=imdata, channels=channels)
```

delay(*self, channels=None, space='image', bundle_dpath=None*)

Perform a delayed load on the data in this image.

The delayed load can load a subset of channels, and perform lazy warping operations. If the underlying data is in a tiled format this can reduce the amount of disk IO needed to read the data if only a small crop or lower resolution view of the data is needed.

Note: This method is experimental and relies on the delayed load proof-of-concept.

Parameters

- **gid** (*int*) – image id to load
- **channels** (*FusedChannelSpec*) – specific channels to load. if unspecified, all channels are loaded.
- **space** (*str*) – can either be “image” for loading in image space, or “video” for loading in video space.

Todo:

- [X] **Currently can only take all or none of the channels from each base-image / auxiliary dict.**
For instance if the main image is r|g|b you can't just select g|b at the moment.
 - [X] **The order of the channels in the delayed load should** match the requested channel order.
 - [X] TODO: add nans to bands that don't exist or throw an error
 - [] **This function could stand to have a better name. Maybe imread with a delayed=True flag? Or maybe just delayed_load?**
-

Example

```
>>> from kwcoco.coco_image import * # NOQA
>>> import kwcoco
>>> gid = 1
>>> #
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-multispectral')
>>> self = CocoImage(dset.imgs[gid], dset)
>>> delayed = self.delay()
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize()))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
>>> #
>>> dset = kwcoco.CocoDataset.demo('shapes8')
>>> delayed = dset.delayed_load(gid)
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize()))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
```

```
>>> crop = delayed.delayed_crop((slice(0, 3), slice(0, 3)))
>>> crop.finalize()
>>> crop.finalize(as_xarray=True)
```

```
>>> # TODO: should only select the "red" channel
>>> dset = kwcoco.CocoDataset.demo('shapes8')
>>> delayed = CocoImage(dset.imgs[gid], dset).delay(channels='r')
```

```
>>> import kwCOCO
>>> gid = 1
>>> #
>>> dset = kwCOCO.CocoDataset.demo('vidshapes8-multispectral')
>>> delayed = dset.delayed_load(gid, channels='B1|B2', space='image')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
>>> delayed = dset.delayed_load(gid, channels='B1|B2|B11', space='image')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
>>> delayed = dset.delayed_load(gid, channels='B8|B1', space='video')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))

>>> delayed = dset.delayed_load(gid, channels='B8|foo|bar|B1', space='video')
>>> print('delayed = {!r}'.format(delayed))
>>> print('delayed.finalize() = {!r}'.format(delayed.finalize(as_xarray=True)))
```

Example

```
>>> import kwCOCO
>>> dset = kwCOCO.CocoDataset.demo()
>>> coco_img = dset.coco_image(1)
>>> # Test case where nothing is registered in the dataset
>>> delayed = coco_img.delay()
>>> final = delayed.finalize()
>>> assert final.shape == (512, 512, 3)
```

Example

```
>>> # Test that delay works when imdata is stored in the image
>>> # dictionary itself.
>>> from kwCOCO.coco_image import * # NOQA
>>> import kwCOCO
>>> dset = kwCOCO.CocoDataset.demo('vidshapes8-multispectral')
>>> coco_img = dset.coco_image(1)
>>> imdata = np.random.rand(6, 6, 5)
>>> imdata[:] = np.arange(5)[None, None, :]
>>> channels = kwCOCO.FusedChannelSpec.coerce('Aux:5')
>>> coco_img.add_auxiliary_item(imdata=imdata, channels=channels)
>>> delayed = coco_img.delay(channels='B1|Aux:2:4')
>>> final = delayed.finalize()
```

Example

```
>>> # Test delay when loading in auxiliary space
>>> from kwcoco.coco_image import * # NOQA
>>> import kwcoco
>>> dset = kwcoco.CocoDataset.demo('vidshapes8-msi-multisensor')
>>> coco_img = dset.coco_image[1]
>>> stream1 = coco_img.channels.streams()[0]
>>> stream2 = coco_img.channels.streams()[1]
>>> aux_delayed = coco_img.delay(stream1, space='auxiliary')
>>> img_delayed = coco_img.delay(stream1, space='image')
>>> vid_delayed = coco_img.delay(stream1, space='video')
>>> #
>>> aux_imdata = aux_delayed.finalize()
>>> img_imdata = img_delayed.finalize()
>>> assert aux_imdata.shape != img_imdata.shape
>>> # Cannot load multiple auxiliary items at the same time in
>>> # auxiliary space
>>> import pytest
>>> fused_channels = stream1 | stream2
>>> with pytest.raises(kwcoco.exceptions.CoordinateCompatibilityError):
>>>     aux_delayed2 = coco_img.delay(fused_channels, space='auxiliary')
```

class kwcoco.CategoryTree(graph=None, checks=True)

Bases: `ubelt.NiceRepr`

Wrapper that maintains flat or hierarchical category information.

Helps compute softmaxes and probabilities for tree-based categories where a directed edge (A, B) represents that A is a superclass of B.

Note: There are three basic properties that this object maintains:

node: Alphanumeric string names that should be generally descriptive. Using spaces and special characters in these names is discouraged, but can be done. This is the COCO category "name" attribute. For categories this may be denoted as (name, node, cname, catname).	id: The integer id of a category should ideally remain consistent. These are often given by a dataset (e.g. a COCO dataset). This is the COCO category "id" attribute. For categories this is often denoted as (id, cid).	index: Contiguous zero-based indices that indexes the list of categories. These should be used for the fastest access in backend computation tasks. Typically corresponds to the ordering of the channels in the final linear layer in an associated model. For categories this is often denoted as (index, cidx, idx, or cx).
--	--	---

Variables

- **idx_to_node** (*List[str]*) – a list of class names. Implicitly maps from index to category name.
- **id_to_node** (*Dict[int, str]*) – maps integer ids to category names
- **node_to_id** (*Dict[str, int]*) – maps category names to ids
- **node_to_idx** (*Dict[str, int]*) – maps category names to indexes
- **graph** (*networkx.Graph*) – a Graph that stores any hierarchy information. For standard mutually exclusive classes, this graph is edgeless. Nodes in this graph can maintain category attributes / properties.
- **idx_groups** (*List[List[int]]*) – groups of category indices that share the same parent category.

Example

```
>>> from kwcoco.category_tree import *
>>> graph = nx.from_dict_of_lists({
>>>     'background': [],
>>>     'foreground': ['animal'],
>>>     'animal': ['mammal', 'fish', 'insect', 'reptile'],
>>>     'mammal': ['dog', 'cat', 'human', 'zebra'],
>>>     'zebra': ['grevys', 'plains'],
>>>     'grevys': ['fred'],
>>>     'dog': ['boxer', 'beagle', 'golden'],
>>>     'cat': ['maine coon', 'persian', 'sphynx'],
>>>     'reptile': ['bearded dragon', 't-rex'],
>>> }, nx.DiGraph)
>>> self = CategoryTree(graph)
>>> print(self)
<CategoryTree(nNodes=22, maxDepth=6, maxBreadth=4...)>
```

Example

```
>>> # The coerce classmethod is the easiest way to create an instance
>>> import kwcoco
>>> kwcoco.CategoryTree.coerce(['a', 'b', 'c'])
<CategoryTree...nNodes=3, nodes='a', 'b', 'c'...
>>> kwcoco.CategoryTree.coerce(4)
<CategoryTree...nNodes=4, nodes='class_1', 'class_2', 'class_3', ...
>>> kwcoco.CategoryTree.coerce(4)
```

```
copy(self)
classmethod from_mutex(cls, nodes, bg_hack=True)
```

Parameters **nodes** (*List[str]*) – or a list of class names (in which case they will all be assumed to be mutually exclusive)

Example

```
>>> print(CategoryTree.from_mutex(['a', 'b', 'c']))
<CategoryTree(nNodes=3, ...)>
```

classmethod from_json(*cls*, *state*)

Parameters state (Dict) – see `__getstate__` / `__json__` for details

classmethod from_coco(*cls*, *categories*)

Create a CategoryTree object from coco categories

Parameters List[Dict] – list of coco-style categories

classmethod coerce(*cls*, *data*, *kw*)**

Attempt to coerce data as a CategoryTree object.

This is primarily useful for when the software stack depends on categories being represented

This will work if the input data is a specially formatted json dict, a list of mutually exclusive classes, or if it is already a CategoryTree. Otherwise an error will be thrown.

Parameters

- **data (object)** – a known representation of a category tree.
- ****kwargs** – input type specific arguments

Returns self

Return type `CategoryTree`

Raises

- **TypeError** – if the input format is unknown –
- **ValueError** – if kwargs are not compatible with the input format –

Example

```
>>> import kwcoco
>>> classes1 = kwcoco.CategoryTree.coerce(3) # integer
>>> classes2 = kwcoco.CategoryTree.coerce(classes1.__json__()) # graph dict
>>> classes3 = kwcoco.CategoryTree.coerce(['class_1', 'class_2', 'class_3']) # _mutex list
>>> classes4 = kwcoco.CategoryTree.coerce(classes1.graph) # nx Graph
>>> classes5 = kwcoco.CategoryTree.coerce(classes1) # cls
>>> # xdoctest: +REQUIRES(module:nd sampler)
>>> import nd sampler
>>> classes6 = nd sampler.CategoryTree.coerce(3)
>>> classes7 = nd sampler.CategoryTree.coerce(classes1)
>>> classes8 = kwcoco.CategoryTree.coerce(classes6)
```

classmethod demo(*cls*, key='coco', *kwargs*)**

Parameters key (str) – specify which demo dataset to use. Can be ‘coco’ (which uses the default coco demo data). Can be ‘btree’ which creates a binary tree and accepts kwargs ‘r’ and ‘h’ for branching-factor and height. Can be ‘btree2’, which is the same as btree but returns strings

CommandLine

```
xdoctest -m ~/code/kwCOCO/kwCOCO/category_tree.py CategoryTree.demo
```

Example

```
>>> from kwCOCO.category_tree import *
>>> self = CategoryTree.demo()
>>> print('self = {}'.format(self))
self = <CategoryTree(nNodes=10, maxDepth=2, maxBreadth=4...)>
```

to_coco(self)

Converts to a coco-style data structure

Yields *Dict* – coco category dictionaries

id_to_idx(self)

Example

```
>>> import kwCOCO
>>> self = kwCOCO.CategoryTree.demo()
>>> self.id_to_idx[1]
```

idx_to_id(self)

Example

```
>>> import kwCOCO
>>> self = kwCOCO.CategoryTree.demo()
>>> self.idx_to_id[0]
```

idx_to_ancestor_idxs(self, include_self=True)

Mapping from a class index to its ancestors

Parameters **include_self** (*bool*, *default=True*) – if True includes each node as its own ancestor.

idx_to_descendants_idxs(self, include_self=False)

Mapping from a class index to its descendants (including itself)

Parameters **include_self** (*bool*, *default=False*) – if True includes each node as its own descendant.

idx_pairwise_distance(self)

Get a matrix encoding the distance from one class to another.

Distances

- from parents to children are positive (descendants),
- from children to parents are negative (ancestors),
- between unreachable nodes (wrt to forward and reverse graph) are nan.

__len__(self)

```
__iter__(self)
__getitem__(self, index)
__contains__(self, node)
__json__(self)
```

Example

```
>>> import pickle
>>> self = CategoryTree.demo()
>>> print('self = {!r}'.format(self.__json__()))
```

`__getstate__(self)`
Serializes information in this class

Example

```
>>> from kwcoco.category_tree import *
>>> import pickle
>>> self = CategoryTree.demo()
>>> state = self.__getstate__()
>>> serialization = pickle.dumps(self)
>>> recon = pickle.loads(serialization)
>>> assert recon.__json__() == self.__json__()
```

`__setstate__(self, state)`
`__nice__(self)`
`is_mutex(self)`
Returns True if all categories are mutually exclusive (i.e. flat)
If true, then the classes may be represented as a simple list of class names without any loss of information, otherwise the underlying category graph is necessary to preserve all knowledge.

Todo:

- [] what happens when we have a dummy root?
-

`property num_classes(self)`
`property class_names(self)`
`property category_names(self)`
`property cats(self)`
Returns a mapping from category names to category attributes.
If this category tree was constructed from a coco-dataset, then this will contain the coco category attributes.
Returns Dict[str, Dict[str, object]]

Example

```
>>> from kwcoco.category_tree import *
>>> self = CategoryTree.demo()
>>> print('self.cats = {!r}'.format(self.cats))
```

index(self, node)

Return the index that corresponds to the category name

_build_index(self)

construct lookup tables

show(self)

forest_str(self)

normalize(self)

Applies a normalization scheme to the categories.

Note: this may break other tasks that depend on exact category names.

Returns CategoryTree

Example

```
>>> from kwcoco.category_tree import * # NOQA
>>> import kwcoco
>>> orig = kwcoco.CategoryTree.demo('animals_v1')
>>> self = kwcoco.CategoryTree(nx.relabel_nodes(orig.graph, str.upper))
>>> norm = self.normalize()
```

class kwcoco.ChannelSpec(spec, parsed=None)

Bases: BaseChannelSpec

Parse and extract information about network input channel specs for early or late fusion networks.

Behaves like a dictionary of FusedChannelSpec objects

Todo:

- [] Rename to something that indicates this is a collection of FusedChannelSpec? MultiChannelSpec?
-

Note: This class name and API is in flux and subject to change.

Note: The pipe ('|') character represents an early-fused input stream, and order matters (it is non-commutative).

The comma (',') character separates different inputs streams/branches for a multi-stream/branch network which will be later fused. Order does not matter

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> # Integer spec
>>> ChannelSpec.coerce(3)
<ChannelSpec(u0|u1|u2) ...>
```

```
>>> # single mode spec
>>> ChannelSpec.coerce('rgb')
<ChannelSpec(rgb) ...>
```

```
>>> # early fused input spec
>>> ChannelSpec.coerce('rgb|disparity')
<ChannelSpec(rgb|disparity) ...>
```

```
>>> # late fused input spec
>>> ChannelSpec.coerce('rgb,disparity')
<ChannelSpec(rgb,disparity) ...>
```

```
>>> # early and late fused input spec
>>> ChannelSpec.coerce('rgb|ir,disparity')
<ChannelSpec(rgb|ir,disparity) ...>
```

Example

```
>>> self = ChannelSpec('gray')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>> self = ChannelSpec('rgb')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>> self = ChannelSpec('rgb|disparity')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>> self = ChannelSpec('rgb|disparity,disparity')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>> self = ChannelSpec('rgb,disparity,flowx|flowy')
>>> print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
```

Example

```
>>> specs = [
>>>     'rgb',                  # and rgb input
>>>     'rgb|disparity',        # rgb early fused with disparity
>>>     'rgb,disparity',        # rgb early late with disparity
>>>     'rgb|ir,disparity',    # rgb early fused with ir and late fused with disparity
>>>     3,                      # 3 unknown channels
>>> ]
>>> for spec in specs:
>>>     print('=====')
>>>     print('spec = {!r}'.format(spec))
>>>     #
```

(continues on next page)

(continued from previous page)

```
>>>     self = ChannelSpec.coerce(spec)
>>>     print('self = {!r}'.format(self))
>>>     sizes = self.sizes()
>>>     print('sizes = {!r}'.format(sizes))
>>>     print('self.info = {}'.format(ub.repr2(self.info, nl=1)))
>>>     #
>>>     item = self._demo_item((1, 1), rng=0)
>>>     inputs = self.encode(item)
>>>     components = self.decode(inputs)
>>>     input_shapes = ub.map_vals(lambda x: x.shape, inputs)
>>>     component_shapes = ub.map_vals(lambda x: x.shape, components)
>>>     print('item = {}'.format(ub.repr2(item, precision=1)))
>>>     print('inputs = {}'.format(ub.repr2(inputs, precision=1)))
>>>     print('input_shapes = {}'.format(ub.repr2(input_shapes)))
>>>     print('components = {}'.format(ub.repr2(components, precision=1)))
>>>     print('component_shapes = {}'.format(ub.repr2(component_shapes, nl=1)))
```

property spec(self)

The string encodeing of this spec

Returns str**__contains__(self, key)****Example**

```
>>> 'disparity' in ChannelSpec('rgb,disparity,flowx|flowy')
True
>>> 'gray' in ChannelSpec('rgb,disparity,flowx|flowy')
False
```

property info(self)**classmethod coerce(cls, data)**

Attempt to interpret the data as a channel specification

Returns ChannelSpec**Example**

```
>>> from kwcoco.channel_spec import * # NOQA
>>> data = FusedChannelSpec.coerce(3)
>>> assert ChannelSpec.coerce(data).spec == 'u0|u1|u2'
>>> data = ChannelSpec.coerce(3)
>>> assert data.spec == 'u0|u1|u2'
>>> assert ChannelSpec.coerce(data).spec == 'u0|u1|u2'
>>> data = ChannelSpec.coerce('u:3')
>>> assert data.normalize().spec == 'u.0|u.1|u.2'
```

parse(self)

Build internal representation

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> self = ChannelSpec('b1|b2|b3|rgb,B:3')
>>> print(self.parse())
>>> print(self.normalize().parse())
>>> ChannelSpec('').parse()
```

Example

```
>>> base = ChannelSpec('rgb|disparity,flowx|r|flowy')
>>> other = ChannelSpec('rgb')
>>> self = base.intersection(other)
>>> assert self.numel() == 4
```

concise(self)**Example**

```
>>> self = ChannelSpec('b1|b2,b3|rgb|B.0,B.1|B.2')
>>> print(self.concise().spec)
b1|b2,b3|r|g|b|B.0,B.1:3
```

normalize(self)

Replace aliases with explicit single-band-per-code specs

Returns normalized spec**Return type** *ChannelSpec***Example**

```
>>> self = ChannelSpec('b1|b2,b3|rgb,B:3')
>>> normed = self.normalize()
>>> print('self = {}'.format(self))
>>> print('normed = {}'.format(normed))
self  = <ChannelSpec(b1|b2,b3|rgb,B:3)>
normed = <ChannelSpec(b1|b2,b3|r|g|b,B.0|B.1|B.2)>
```

keys(self)**values(self)****items(self)****fuse(self)**

Fuse all parts into an early fused channel spec

Returns FusedChannelSpec

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> self = ChannelSpec.coerce('b1|b2,b3|rgb,B:3')
>>> fused = self.fuse()
>>> print('self = {}'.format(self))
>>> print('fused = {}'.format(fused))
self = <ChannelSpec(b1|b2,b3|rgb,B:3)>
fused = <FusedChannelSpec(b1|b2|b3|rgb|B:3)>
```

streams(self)

Breaks this spec up into one spec for each early-fused input stream

Example

```
self = ChannelSpec.coerce('r|g,B1|B2,fx|fy') list(map(len, self.streams()))
```

code_list(self)**as_path(self)**

Returns a string suitable for use in a path.

Note, this may no longer be a valid channel spec

difference(self, other)

Set difference. Remove all instances of other channels from this set of channels.

Example

```
>>> from kwcoco.channel_spec import *
>>> self = ChannelSpec('rgb|disparity,flowx|r|flowy')
>>> other = ChannelSpec('rgb')
>>> print(self.difference(other))
>>> other = ChannelSpec('flowx')
>>> print(self.difference(other))
<ChannelSpec(disparity,flowx|flowy)>
<ChannelSpec(r|g|b|disparity,r|flowy)>
```

Example

```
>>> from kwcoco.channel_spec import *
>>> self = ChannelSpec('a|b,c|d')
>>> new = self - {'a', 'b'}
>>> len(new.sizes()) == 1
>>> empty = new - 'c|d'
>>> assert empty.numel() == 0
```

intersection(self, other)

Set difference. Remove all instances of other channels from this set of channels.

Example

```
>>> from kwcoco.channel_spec import *
>>> self = ChannelSpec('rgb|disparity,flowx|r|flowy')
>>> other = ChannelSpec('rgb')
>>> new = self.intersection(other)
>>> print(new)
>>> print(new.numel())
>>> other = ChannelSpec('flowx')
>>> new = self.intersection(other)
>>> print(new)
>>> print(new.numel())
<ChannelSpec(r|g|b,r)>
4
<ChannelSpec(flowx)>
1
```

union(self, other)

Union simply tags on a second channel spec onto this one. Duplicates are maintained.

Example

```
>>> from kwcoco.channel_spec import *
>>> self = ChannelSpec('rgb|disparity,flowx|r|flowy')
>>> other = ChannelSpec('rgb')
>>> new = self.union(other)
>>> print(new)
>>> print(new.numel())
>>> other = ChannelSpec('flowx')
>>> new = self.union(other)
>>> print(new)
>>> print(new.numel())
<ChannelSpec(r|g|b|disparity,flowx|r|flowy,r|g|b)>
10
<ChannelSpec(r|g|b|disparity,flowx|r|flowy,flowx)>
8
```

abstract issubset(self, other)**abstract issuperset(self, other)****numel(self)**

Total number of channels in this spec

sizes(self)

Number of dimensions for each fused stream channel

IE: The EARLY-FUSED channel sizes

Example

```
>>> self = ChannelSpec('rgb|disparity,flowx|flowy,B:10')
>>> self.normalize().concise()
>>> self.sizes()
```

`unique(self, normalize=False)`

Returns the unique channels that will need to be given or loaded

`_item_shapes(self, dims)`

Expected shape for an input item

Parameters `dims` (`Tuple[int, int]`) – the spatial dimension

Returns `Dict[int, tuple]`

`_demo_item(self, dims=(4, 4), rng=None)`

Create an input that satisfies this spec

Returns

an item like it might appear when its returned from the `__getitem__` method of a `torch...Dataset`.

Return type `dict`

Example

```
>>> dims = (1, 1)
>>> ChannelSpec.coerce(3)._demo_item(dims, rng=0)
>>> ChannelSpec.coerce('r|g|b|disparity')._demo_item(dims, rng=0)
>>> ChannelSpec.coerce('rgb|disparity')._demo_item(dims, rng=0)
>>> ChannelSpec.coerce('rgb,disparity')._demo_item(dims, rng=0)
>>> ChannelSpec.coerce('rgb')._demo_item(dims, rng=0)
>>> ChannelSpec.coerce('gray')._demo_item(dims, rng=0)
```

`encode(self, item, axis=0, mode=1)`

Given a dictionary containing preloaded components of the network inputs, build a concatenated (fused) network representations of each input stream.

Parameters

- `item` (`Dict[str, Tensor]`) – a batch item containing unfused parts. each key should be a single-stream (optionally early fused) channel key.
- `axis` (`int, default=0`) – concatenation dimension

Returns mapping between input stream and its early fused tensor input.

Return type `Dict[str, Tensor]`

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> import numpy as np
>>> dims = (4, 4)
>>> item = {
    '>>>     'rgb': np.random.rand(3, *dims),
    '>>>     'disparity': np.random.rand(1, *dims),
    '>>>     'flowx': np.random.rand(1, *dims),
    '>>>     'flowy': np.random.rand(1, *dims),
}
>>> # Complex Case
>>> self = ChannelSpec('rgb|disparity', 'flowx|flowy')
>>> fused = self.encode(item)
>>> input_shapes = ub.map_vals(lambda x: x.shape, fused)
>>> print('input_shapes = {}'.format(ub.repr2(input_shapes, nl=1)))
>>> # Simpler case
>>> self = ChannelSpec('rgb|disparity')
>>> fused = self.encode(item)
>>> input_shapes = ub.map_vals(lambda x: x.shape, fused)
>>> print('input_shapes = {}'.format(ub.repr2(input_shapes, nl=1)))
```

Example

```
>>> # Case where we have to break up early fused data
>>> import numpy as np
>>> dims = (40, 40)
>>> item = {
    '>>>     'rgb|disparity': np.random.rand(4, *dims),
    '>>>     'flowx': np.random.rand(1, *dims),
    '>>>     'flowy': np.random.rand(1, *dims),
}
>>> # Complex Case
>>> self = ChannelSpec('rgb|disparity', 'flowx|flowy|disparity')
>>> inputs = self.encode(item)
>>> input_shapes = ub.map_vals(lambda x: x.shape, inputs)
>>> print('input_shapes = {}'.format(ub.repr2(input_shapes, nl=1)))
```

```
>>> # xdoctest: +REQUIRES(--bench)
>>> #self = ChannelSpec('rgb|disparity', 'flowx|flowy')
>>> import timerit
>>> ti = timerit.Timerit(100, bestof=10, verbose=2)
>>> for timer in ti.reset('mode=simple'):
    with timer:
        inputs = self.encode(item, mode=0)
>>> for timer in ti.reset('mode=minimize-concat'):
    with timer:
        inputs = self.encode(item, mode=1)
```

`decode(self, inputs, axis=1)`
break an early fused item into its components

Parameters

- **inputs** (*Dict[str, Tensor]*) – dictionary of components
- **axis** (*int, default=1*) – channel dimension

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> import numpy as np
>>> dims = (4, 4)
>>> item_components = {
>>>     'rgb': np.random.rand(3, *dims),
>>>     'ir': np.random.rand(1, *dims),
>>> }
>>> self = ChannelSpec('rgb|ir')
>>> item_encoded = self.encode(item_components)
>>> batch = {k: np.concatenate([v[None, :], v[None, :]]), axis=0}
>>>         for k, v in item_encoded.items()}
>>> components = self.decode(batch)
```

Example

```
>>> # xdoctest: +REQUIRES(module:netharn, module:torch)
>>> import torch
>>> import numpy as np
>>> dims = (4, 4)
>>> components = {
>>>     'rgb': np.random.rand(3, *dims),
>>>     'ir': np.random.rand(1, *dims),
>>> }
>>> components = ub.map_vals(torch.from_numpy, components)
>>> self = ChannelSpec('rgb|ir')
>>> encoded = self.encode(components)
>>> from netharn.data import data_containers
>>> item = {k: data_containers.ItemContainer(v, stack=True)
>>>         for k, v in encoded.items()}
>>> batch = data_containers.container_collate([item, item])
>>> components = self.decode(batch)
```

component_indices(*self, axis=2*)

Look up component indices within fused streams

Example

```
>>> dims = (4, 4)
>>> inputs = ['flowx', 'flowy', 'disparity']
>>> self = ChannelSpec('disparity,flowx|flowy')
>>> component_indices = self.component_indices()
>>> print('component_indices = {}'.format(ub.repr2(component_indices, nl=1)))
component_indices =
    'disparity': ('disparity', (slice(None, None, None), slice(None, None, None),
        slice(0, 1, None))),
    'flowx': ('flowx|flowy', (slice(None, None, None), slice(None, None, None),
        slice(0, 1, None))),
    'flowy': ('flowx|flowy', (slice(None, None, None), slice(None, None, None),
        slice(1, 2, None))),
}
```

class kwcococo.FusedChannelSpec(*parsed, _is_normalized=False*)

Bases: BaseChannelSpec

A specific type of channel spec with only one early fused stream.

The channels in this stream are non-commutative

Behaves like a list of atomic-channel codes (which may represent more than 1 channel), normalized codes always represent exactly 1 channel.

Note: This class name and API is in flux and subject to change.

Todo: A special code indicating a name and some number of bands that that names contains, this would primarily be used for large numbers of channels produced by a network. Like:

resnet_d35d060_L5:512

or

resnet_d35d060_L5[:512]

might refer to a very specific (hashed) set of resnet parameters with 512 bands

maybe we can do something slicily like:

resnet_d35d060_L5[A:B] resnet_d35d060_L5:A:B

Do we want to “just store the code” and allow for parsing later?

Or do we want to ensure the serialization is parsed before we construct the data structure?

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> import pickle
>>> self = FusedChannelSpec.coerce(3)
>>> recon = pickle.loads(pickle.dumps(self))
>>> self = ChannelSpec.coerce('a|b,c|d')
>>> recon = pickle.loads(pickle.dumps(self))
```

`_alias_lut`

`_memo`

`_size_lut`

`__len__(self)`

`__getitem__(self, index)`

`classmethod concat(cls, items)`

`spec(self)`

The string encodeing of this spec

Returns str

`unique(self)`

`classmethod parse(cls, spec)`

`classmethod coerce(cls, data)`

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> FusedChannelSpec.coerce(['a', 'b', 'c'])
>>> FusedChannelSpec.coerce('a|b|c')
>>> FusedChannelSpec.coerce(3)
>>> FusedChannelSpec.coerce(FusedChannelSpec(['a']))
>>> assert FusedChannelSpec.coerce('') .numel() == 0
```

`concise(self)`

Shorted the channel spec by de-normaliz slice syntax

Returns concise spec

Return type *FusedChannelSpec*

Example

```
>>> from kwcoco.channel_spec import * # NOQA
>>> self = FusedChannelSpec.coerce(
>>>     'b|a|a.0|a.1|a.2|a.5|c|a.8|a.9|b.0:3|c.0')
>>> short = self.concise()
>>> long = short.normalize()
>>> numels = [c.numel() for c in [self, short, long]]
>>> print('self.spec = {!r}'.format(self.spec))
```

(continues on next page)

(continued from previous page)

```
>>> print('short.spec = {!r}'.format(short.spec))
>>> print('long.spec = {!r}'.format(long.spec))
>>> print('numels = {!r}'.format(numels))
self.spec = 'b|a|a.0|a.1|a.2|a.5|c|a.8|a.9|b.0:3|c.0'
short.spec = 'b|a|a:3|a.5|c|a.8:10|b:3|c.0'
long.spec = 'b|a|a.0|a.1|a.2|a.5|c|a.8|a.9|b.0|b.1|b.2|c.0'
numels = [13, 13, 13]
>>> assert long.concise().spec == short.spec
```

normalize(self)

Replace aliases with explicit single-band-per-code specs

Returns normalize spec**Return type** *FusedChannelSpec***Example**

```
>>> from kwcoco.channel_spec import * # NOQA
>>> self = FusedChannelSpec.coerce('b1|b2|b3|rgb')
>>> normed = self.normalize()
>>> print('self = {}'.format(self))
>>> print('normed = {}'.format(normed))
self = <FusedChannelSpec(b1|b2|b3|rgb)>
normed = <FusedChannelSpec(b1|b2|b3|r|g|b)>
>>> self = FusedChannelSpec.coerce('B:1:11')
>>> normed = self.normalize()
>>> print('self = {}'.format(self))
>>> print('normed = {}'.format(normed))
self = <FusedChannelSpec(B:1:11)>
normed = <FusedChannelSpec(B.1|B.2|B.3|B.4|B.5|B.6|B.7|B.8|B.9|B.10)>
>>> self = FusedChannelSpec.coerce('B.1:11')
>>> normed = self.normalize()
>>> print('self = {}'.format(self))
>>> print('normed = {}'.format(normed))
self = <FusedChannelSpec(B.1:11)>
normed = <FusedChannelSpec(B.1|B.2|B.3|B.4|B.5|B.6|B.7|B.8|B.9|B.10)>
```

numel(self)

Total number of channels in this spec

sizes(self)

Returns a list indicating the size of each atomic code

Returns List[int]

Example

```
>>> from kwcoc.channel_spec import * # NOQA
>>> self = FusedChannelSpec.coerce('b1|Z:3|b2|b3|rgb')
>>> self.sizes()
[1, 3, 1, 1, 3]
>>> assert(FusedChannelSpec.parse('a.0')).numel() == 1
>>> assert(FusedChannelSpec.parse('a:0')).numel() == 0
>>> assert(FusedChannelSpec.parse('a:1')).numel() == 1
```

`__contains__(self, key)`

Example

```
>>> FCS = FusedChannelSpec.coerce
>>> 'disparity' in FCS('rgb|disparity|flowx|flowy')
True
>>> 'gray' in FCS('rgb|disparity|flowx|flowy')
False
```

`code_list(self)`

Return the expanded code list

`as_list(self)`

`as_oset(self)`

`as_set(self)`

`as_path(self)`

Returns a string suitable for use in a path.

Note, this may no longer be a valid channel spec

`__set__(self)`

`difference(self, other)`

Set difference

Example

```
>>> FCS = FusedChannelSpec.coerce
>>> self = FCS('rgb|disparity|flowx|flowy')
>>> other = FCS('r|b')
>>> self.difference(other)
>>> other = FCS('flowx')
>>> self.difference(other)
>>> FCS = FusedChannelSpec.coerce
>>> assert len((FCS('a') - {'a'}).parsed) == 0
>>> assert len((FCS('a.0:3') - {'a.0'}).parsed) == 2
```

`intersection(self, other)`

Example

```
>>> FCS = FusedChannelSpec.coerce
>>> self = FCS('rgb|disparity|flowx|flowy')
>>> other = FCS('r|b|XX')
>>> self.intersection(other)
```

union(self, other)**Example**

```
>>> from kwcoco.channel_spec import * # NOQA
>>> FCS = FusedChannelSpec.coerce
>>> self = FCS('rgb|disparity|flowx|flowy')
>>> other = FCS('r|b|XX')
>>> self.union(other)
```

issubset(self, other)**issuperset(self, other)****component_indices(self, axis=2)**

Look up component indices within this stream

Example

```
>>> FCS = FusedChannelSpec.coerce
>>> self = FCS('disparity|rgb|flowx|flowy')
>>> component_indices = self.component_indices()
>>> print('component_indices = {}'.format(ub.repr2(component_indices, nl=1)))
component_indices = {
    'disparity': (slice(...), slice(...), slice(0, 1, None)),
    'flowx': (slice(...), slice(...), slice(4, 5, None)),
    'flowy': (slice(...), slice(...), slice(5, 6, None)),
    'rgb': (slice(...), slice(...), slice(1, 4, None)),
}
```

streams(self)Idempotence with `ChannelSpec.streams()`**fuse(self)**Idempotence with `ChannelSpec.streams()`

PYTHON MODULE INDEX

k

kwcoco, 9
kwcoco.__init__, 1
kwcoco.__main__, 202
kwcoco._helpers, 202
kwcoco.abstract_coco_dataset, 205
kwcoco.category_tree, 206
kwcoco.channel_spec, 211
kwcoco.cli, 14
kwcoco.cli.__main__, 14
kwcoco.cli.coco_conform, 15
kwcoco.cli.coco_eval, 16
kwcoco.cli.coco_grab, 19
kwcoco.cli.coco_modify_categories, 19
kwcoco.cli.coco_reroot, 21
kwcoco.cli.coco_show, 22
kwcoco.cli.coco_split, 23
kwcoco.cli.coco_stats, 24
kwcoco.cli.coco_subset, 25
kwcoco.cli.coco_toydata, 27
kwcoco.cli.coco_union, 28
kwcoco.cli.coco_validate, 29
kwcoco.coco_dataset, 229
kwcoco.coco_evaluator, 276
kwcoco.coco_image, 283
kwcoco.coco_objects1d, 289
kwcoco.coco_schema, 298
kwcoco.coco_sql_dataset, 301
kwcoco.compat_dataset, 313
kwcoco.data, 30
kwcoco.data.grab_camvid, 30
kwcoco.data.grab_cifar, 32
kwcoco.data.grab_datasets, 32
kwcoco.data.grab_domainnet, 33
kwcoco.data.grab_spacenet, 33
kwcoco.data.grab_voc, 34
kwcoco.demo, 36
kwcoco.demo.boids, 36
kwcoco.demo.perterb, 40
kwcoco.demo.toydata, 41
kwcoco.demo.toydata_image, 49
kwcoco.demo.toydata_video, 53

kwcoco.demo.toypatterns, 61
kwcoco.examples, 64
kwcoco.examples.bench_large_hyperspectral, 64
kwcoco.examples.draw_gt_and_predicted_boxes,
65
kwcoco.examples.faq, 66
kwcoco.examples.getting_started_existing_dataset,
66
kwcoco.examples.loading_multispectral_data,
67
kwcoco.examples.modification_example, 67
kwcoco.examples.simple_kwcoco_torch_dataset,
67
kwcoco.examples.vectorized_interface, 69
kwcoco.exceptions, 317
kwcoco.kpf, 317
kwcoco.kw18, 317
kwcoco.metrics, 69
kwcoco.metrics.assignment, 69
kwcoco.metrics.clf_report, 74
kwcoco.metrics.confusion_measures, 77
kwcoco.metrics.confusion_vectors, 84
kwcoco.metrics.detect_metrics, 93
kwcoco.metrics.drawing, 100
kwcoco.metrics.functional, 104
kwcoco.metrics.sklearn_alts, 106
kwcoco.metrics.util, 108
kwcoco.metrics.voc_metrics, 108
kwcoco.util, 131
kwcoco.util.dict_like, 131
kwcoco.util.jsonschema_elements, 132
kwcoco.util.lazy_frame_backends, 138
kwcoco.util.util_archive, 142
kwcoco.util.util_delayed_poc, 143
kwcoco.util.util_futures, 166
kwcoco.util.util_json, 166
kwcoco.util.util_monkey, 168
kwcoco.util.util_sklearn, 169
kwcoco.util.util_truncate, 170

INDEX

Symbols

_3dplot() (kwcoco.metrics.BinaryConfusionVectors method), 120
_3dplot() (kwcoco.metrics.confusion_vectors.BinaryConfusionVectors method), 92
_CLI (in module kwcoco.cli.coco_conform), 16
_CLI (in module kwcoco.cli.coco_eval), 18
_CLI (in module kwcoco.cli.coco_grab), 19
_CLI (in module kwcoco.cli.coco_modify_categories), 20
_CLI (in module kwcoco.cli.coco_reroot), 21
_CLI (in module kwcoco.cli.coco_show), 22
_CLI (in module kwcoco.cli.coco_split), 23
_CLI (in module kwcoco.cli.coco_stats), 24
_CLI (in module kwcoco.cli.coco_subset), 27
_CLI (in module kwcoco.cli.coco_toydata), 28
_CLI (in module kwcoco.cli.coco_union), 29
_CLI (in module kwcoco.cli.coco_validate), 30
_GDAL_DTYPE_LUT (in module coco.util.lazy_frame_backends), 139
_ID_Remapper (class in kwcoco._helpers), 202
_NextId (class in kwcoco._helpers), 202
__and__() (kwcoco.channel_spec.BaseChannelSpec method), 214
__array__() (kwcoco.util.LazyGDalFrameFile method), 179
__array__() (kwcoco.util.lazy_frame_backends.LazyGDalFrameFile method), 141
__bool__() (kwcoco.coco_dataset.CocoIndex method), 266
__call__() (kwcoco.util.Element method), 175
__call__() (kwcoco.util.jsonschema_elements.Element method), 134
__contains__() (kwcoco.CategoryTree method), 339
__contains__() (kwcoco.ChannelSpec method), 342
__contains__() (kwcoco.FusedChannelSpec method), 352
__contains__() (kwcoco.category_tree.CategoryTree method), 210
__contains__() (kwcoco.channel_spec.ChannelSpec method), 221
__contains__() (kwcoco.channel_spec.FusedChannelSpec method), 217
__contains__() (kwcoco.coco_sql_dataset.SqlDictProxy method), 307
__contains__() (kwcoco.coco_sql_dataset.SqlIdGroupDictProxy method), 309
__contains__() (kwcoco.coco_sql_dataset.SqlListProxy method), 305
__contains__() (kwcoco.util.DictLike method), 173
__contains__() (kwcoco.util.dict_like.DictLike method), 131
__delitem__() (kwcoco.coco_sql_dataset.SqlListProxy method), 306
__delitem__() (kwcoco.util.DictLike method), 173
__delitem__() (kwcoco.util.dict_like.DictLike method), 131
__doc__ (kwcoco.cli.coco_eval.CocoEvalCLICConfig attribute), 17
__enter__() (kwcoco.util.Archive method), 181
__enter__() (kwcoco.util.SuppressPrint method), 200
__enter__() (kwcoco.util.util_archive.Archive method), 143
__enter__() (kwcoco.util.util_monkey.SuppressPrint method), 168
__exit__() (kwcoco.util.Archive method), 181
__exit__() (kwcoco.util.SuppressPrint method), 201
__exit__() (kwcoco.util.util_archive.Archive method), 143
__exit__() (kwcoco.util.util_monkey.SuppressPrint method), 168
__generics__ (kwcoco.util.Element attribute), 175
__generics__ (kwcoco.util.jsonschema_elements.Element attribute), 134
__getitem__() (kwcoco.CategoryTree method), 339
__getitem__() (kwcoco.CocoImage method), 330
__getitem__() (kwcoco.FusedChannelSpec method), 350
__getitem__() (kwcoco.category_tree.CategoryTree method), 210
__getitem__() (kwcoco.channel_spec.FusedChannelSpec method), 215
__getitem__() (kwcoco.coco_image.CocoImage method), 284
__getitem__() (kwcoco.coco_objects1d.ObjectGroups

method), 294
__getitem__(kwcoco.coco_objects1d.ObjectList1D
 method), 290
__getitem__(kwcoco.coco_sql_dataset.SqlDictProxy
 method), 307
__getitem__(kwcoco.coco_sql_dataset.SqlIdGroupDictProxy
 method), 309
__getitem__(kwcoco.coco_sql_dataset.SqlListProxy
 method), 305
__getitem__(kwcoco.coco_sql_dataset.SqlListProxy
 method), 305
__getitem__(kwcoco.demo.toypatterns.CategoryPatterns
 method), 63
__getitem__(kwcoco.demo.toypatterns.CategoryPatterns
 method), 63
__getitem__(kwcoco.examples.simple_kwcoco_torch_dataset.KWcocoSimpleDataset.DictLike
 method), 69
__getitem__(kwcoco.metrics.OneVsRestConfusionVectors
 method), 129
__getitem__(kwcoco.metrics.confusion_vectors.OneVsRestConfusionVectors
 method), 90
__getitem__(kwcoco.metrics.util.DictProxy
 method), 108
__getitem__(kwcoco.util.DictLike method), 173
__getitem__(kwcoco.util.LazyGDalFrameFile
 method), 179
__getitem__(kwcoco.util.LazyRasterIOFrameFile
 method), 180
__getitem__(kwcoco.util.LazySpectralFrameFile
 method), 180
__getitem__(kwcoco.util.dict_like.DictLike
 method), 131
__getitem__(kwcoco.util.lazy_frame_backends.LazyGDalFrameFile
 method), 140
__getitem__(kwcoco.util.lazy_frame_backends.LazyRasterIOFrameFile
 method), 139
__getitem__(kwcoco.util.lazy_frame_backends.LazySpectralFrameFile
 method), 139
__getstate__(kwcoco.CategoryTree method), 339
__getstate__(kwcoco.category_tree.CategoryTree
 method), 210
__iter__(kwcoco.CategoryTree method), 338
__iter__(kwcoco.category_tree.CategoryTree
 method), 209
__iter__(kwcoco.coco_objects1d.ObjectList1D
 method), 290
__iter__(kwcoco.coco_sql_dataset.SqlListProxy
 method), 305
__iter__(kwcoco.demo.toypatterns.CategoryPatterns
 method), 63
__iter__(kwcoco.util.Archive method), 181
__iter__(kwcoco.util.DictLike method), 173
__iter__(kwcoco.util.util_archive.Archive method),
 143
__json__(kwcoco.CategoryTree method), 339
__json__(kwcoco.category_tree.CategoryTree
 method), 210
__json__(kwcoco.channel_spec.BaseChannelSpec
 method), 214
__json__(kwcoco.coco_evaluator.CocoResults
 method), 281
__json__(kwcoco.coco_evaluator.CocoSingleResult
 method), 282
__json__(kwcoco.metrics.ConfusionVectors method),
 121
__json__(kwcoco.metrics.Measures method), 125
__json__(kwcoco.metrics.PerClass_Measures
 method), 125
__json__(kwcoco.metrics.confusion_measures.Measures
 method), 86
__json__(kwcoco.metrics.confusion_measures.PerClass_Measures
 method), 108
__json__(kwcoco.util.DelayedVisionOperation
 method), 195
__json__(kwcoco.util.util_delayed_poc.DelayedVisionOperation
 method), 148
__len__(kwcoco.CategoryTree method), 338
__len__(kwcoco.FusedChannelSpec method), 350
__len__(kwcoco.category_tree.CategoryTree
 method), 209
__len__(kwcoco.channel_spec.FusedChannelSpec
 method), 215
__len__(kwcoco.coco_objects1d.ObjectList1D
 method), 290
__len__(kwcoco.coco_sql_dataset.SqlDictProxy
 method), 307
__len__(kwcoco.coco_sql_dataset.SqlIdGroupDictProxy
 method), 309
__len__(kwcoco.coco_sql_dataset.SqlListProxy
 method), 305

`method), 305`
`__len__(kwcoco.demo.toypatterns.CategoryPatterns
method), 63`
`__len__(kwcoco.examples.simple_kwccoco_torch_dataset.KWCocoSimpleTorchDataset
method), 69`
`__len__(kwcoco.metrics.BinaryConfusionVectors
method), 118`
`__len__(kwcoco.metrics.confusion_vectors.BinaryConfusionVector
method), 91`
`__len__(kwcoco.util.DictLike method), 173`
`__len__(kwcoco.util.dict_like.DictLike method), 131`
`__nice__(kwcoco.CategoryTree method), 339`
`__nice__(kwcoco.CocoDataset method), 324`
`__nice__(kwcoco.CocoImage method), 330`
`__nice__(kwcoco.category_tree.CategoryTree
method), 210`
`__nice__(kwcoco.channel_spec.BaseChannelSpec
method), 214`
`__nice__(kwcoco.coco_dataset.CocoDataset
method), 271`
`__nice__(kwcoco.coco_evaluator.CocoSingleResult
method), 282`
`__nice__(kwcoco.coco_image.CocoImage method),
284`
`__nice__(kwcoco.coco_objects1d.ObjectGroups
method), 294`
`__nice__(kwcoco.coco_objects1d.ObjectList1D
method), 290`
`__nice__(kwcoco.coco_sql_dataset.CocoSqlDatabase
method), 310`
`__nice__(kwcoco.coco_sql_dataset.SqlDictProxy
method), 307`
`__nice__(kwcoco.coco_sql_dataset.SqlIdGroupDictProxy
method), 309`
`__nice__(kwcoco.coco_sql_dataset.SqlListProxy
method), 305`
`__nice__(kwcoco.demo.boids.Boids method), 37`
`__nice__(kwcoco.metrics.BinaryConfusionVectors
method), 118`
`__nice__(kwcoco.metrics.ConfusionVectors method),
121`
`__nice__(kwcoco.metrics.DetectionMetrics method),
112`
`__nice__(kwcoco.metrics.Measures method), 125`
`__nice__(kwcoco.metrics.OneVsRestConfusionVectors
method), 129`
`__nice__(kwcoco.metrics.PerClass_Measures
method), 129`
`__nice__(kwcoco.metrics.confusion_measures.Measures_sub
method), 78`
`__nice__(kwcoco.metrics.confusion_measures.PerClass_Matches
method), 82`
`__nice__(kwcoco.metrics.confusion_vectors.BinaryConfusionVector
method), 91`
`__nice__(kwcoco.metrics.confusion_vectors.ConfusionVectors
method), 86`
~~`__nice__(kwcoco.metrics.confusion_vectors.OneVsRestConfusionVector
method), 129`~~
`__nice__(kwcoco.metrics.detect_metrics.DetectionMetrics
method), 94`
`__nice__(kwcoco.metrics.voc_metrics.VOC_Metrics
method), 109`
`__nice__(kwcoco.util.DelayedVisionOperation
method), 195`
`__nice__(kwcoco.util.LazyGDalFrameFile method),
179`
`__nice__(kwcoco.util.LazyRasterIOFrameFile
method), 180`
`__nice__(kwcoco.util.LazySpectralFrameFile
method), 180`
`__nice__(kwcoco.util.lazy_frame_backends.LazyGDalFrameFile
method), 140`
`__nice__(kwcoco.util.lazy_frame_backends.LazyRasterIOFrameFile
method), 139`
`__nice__(kwcoco.util.lazy_frame_backends.LazySpectralFrameFile
method), 139`
`__nice__(kwcoco.util.util_delayed_poc.DelayedVisionOperation
method), 148`
`__nonzero__(kwcoco.coco_dataset.CocoIndex
attribute), 266`
`__or__(kwcoco.channel_spec.BaseChannelSpec
method), 214`
`__or__(kwcoco.util.Element method), 175`
`__or__(kwcoco.util.jsonschema_elements.Element
method), 134`
`__repr__(kwcoco._helpers.SortedSetQuiet method),
205`
`__set__(kwcoco.FusedChannelSpec method), 352`
`__set__(kwcoco.channel_spec.FusedChannelSpec
method), 218`
`__setitem__(kwcoco.coco_sql_dataset.SqlListProxy
method), 305`
`__setitem__(kwcoco.metrics.util.DictProxy
method), 108`
`__setitem__(kwcoco.util.DictLike method), 173`
`__setitem__(kwcoco.util.dict_like.DictLike
method), 131`
`__setstate__(kwcoco.CategoryTree method), 339`
`__setstate__(kwcoco.category_tree.CategoryTree
method), 210`
`__setstate__(kwcoco.coco_sql_dataset.CocoSqlDatabase
method), 310`
~~`__setstate__(kwcoco.channel_spec.BaseChannelSpec
method), 214`~~
`__tablelename__(kwcoco.coco_sql_dataset.Annotation
attribute), 305`
~~`__tablename__(kwcoco.coco_sql_dataset.Category
attribute), 303`~~

`_tablename_` (`kwcoco.coco_sql_dataset.Image` attribute), 304
`_tablename_` (`kwcoco.coco_sql_dataset.KeypointCategory` attribute), 304
`_tablename_` (`kwcoco.coco_sql_dataset.Video` attribute), 304
`_torrent_voc()` (in module `kwcoco.data.grab_voc`), 35
`_add_annotation()` (`kwcoco.coco_dataset.CocoIndex` method), 267
`_add_annotations()` (kw-coco.coco_dataset.CocoIndex method), 267
`_add_image()` (kw-coco.coco_dataset.CocoIndex method), 266
`_add_images()` (kw-coco.coco_dataset.CocoIndex method), 266
`_add_video()` (kw-coco.coco_dataset.CocoIndex method), 266
`_alias_lut` (`kwcoco.FusedChannelSpec` attribute), 350
`_alias_lut` (`kwcoco.channel_spec.FusedChannelSpec` attribute), 215
`_alias_to_cat()` (kw-coco.coco_dataset.MixinCocoAccessors method), 239
`_all_rows_column_lookup()` (kw-coco.coco_sql_dataset.CocoSqlDatabase method), 312
`_aspycoco()` (kw-coco.coco_dataset.MixinCocoExtras method), 246
`_assign_confusion_vectors()` (in module `kw-coco.metrics.assignment`), 70
`_auto_dsize()` (in module `coco.util.util_delayed_poc`), 165
`_average_precision()` (in module `coco.metrics.functional`), 106
`_bbox_h` (`kwcoco.coco_sql_dataset.Annotation` tribute), 305
`_bbox_w` (`kwcoco.coco_sql_dataset.Annotation` tribute), 305
`_bbox_x` (`kwcoco.coco_sql_dataset.Annotation` tribute), 305
`_bbox_y` (`kwcoco.coco_sql_dataset.Annotation` tribute), 305
`_benchmark_dict_proxy_ops()` (in module `coco.coco_sql_dataset`), 313
`_benchmark_dset_readtime()` (in module `coco.coco_sql_dataset`), 313
`_binary_clf_curve2()` (in module `coco.metrics.sklearn_alts`), 107
`_binary_clf_curves()` (kw-coco.metrics.BinaryConfusionVectors method), 119
`_binary_clf_curves()` (kw-coco.metrics.confusion_vectors.BinaryConfusionVectors method), 92
`_build_dmet()` (`kwcoco.coco_evaluator.CocoEvaluator` method), 280
`_build_hashid()` (kw-coco.coco_dataset.MixinCocoExtras method), 243
`_build_index()` (`kwcoco.CategoryTree` method), 340
`_build_index()` (`kwcoco.CocoDataset` method), 326
`_build_index()` (`kwcoco.category_tree.CategoryTree` method), 211
`_build_index()` (`kwcoco.coco_dataset.CocoDataset` method), 272
`_cached_hashid()` (kw-coco.coco_dataset.MixinCocoExtras method), 244
`_cached_single_fused_mapping()` (in module `kw-coco.channel_spec`), 227
`_cached_single_stream_idxs()` (in module `kw-coco.channel_spec`), 227
`_check_index()` (`kwcoco.CocoDataset` method), 326
`_check_index()` (`kwcoco.coco_dataset.CocoDataset` method), 272
`_check_integrity()` (`kwcoco.CocoDataset` method), 326
`_check_integrity()` (kw-coco.coco_dataset.CocoDataset method), 272
`_check_json_serializable()` (`kwcoco.CocoDataset` method), 325
`_check_json_serializable()` (kw-coco.coco_dataset.CocoDataset method), 272
`_check_pointers()` (`kwcoco.CocoDataset` method), 326
`_check_pointers()` (kw-coco.coco_dataset.CocoDataset method), 272
`_coco_image()` (kw-coco.coco_dataset.MixinCocoAccessors method), 240
`_coerce_dets()` (`kwcoco.coco_evaluator.CocoEvaluator` class method), 279
`_column_lookup()` (kw-coco.coco_sql_dataset.CocoSqlDatabase method), 312
`_combine_threshold()` (in module `coco.metrics.confusion_measures`), 82
`_compute_leaf_subcrop()` (in module `coco.util.util_delayed_poc`), 165
`_convert_cifar_x()` (in module `coco.data.grab_cifar`), 32
`_convert_voc_split()` (in module `coco.data.grab_voc`), 35

_critical_loop()	(in module <code>coco.metrics.assignment</code>), 73	kw-	_ensure_imgsizes()	(kw- coco.coco_dataset.MixinCocoExtras method), 245
_dataset_id()	(kwcoco.coco_dataset.MixinCocoExtras method), 244		_ensure_init()	(kwcoco.coco_evaluator.CocoEvaluator method), 279
_default_categories	(kw- coco.demo.toypatterns.CategoryPatterns attribute), 62	kw-	_ensure_json_serializable()	(kw- coco.coco_dataset.MixinCocoExtras method), 246
_default_catnames	(kw- coco.demo.toypatterns.CategoryPatterns attribute), 62	kw-	_ensure_kw18_column_order()	(in module <code>coco_kw18</code>), 320
_default_keypoint_categories	(kw- coco.demo.toypatterns.CategoryPatterns attribute), 62	kw-	_fast_pdist_priority()	(in module <code>coco.metrics.assignment</code>), 73
_define_camvid_class_hierarchy()	(in module <code>coco.data.grab_camvid</code>), 32	kw-	_filter_ignore_regions()	(in module <code>coco.metrics.assignment</code>), 73
_delay_load_imglike()	(in module <code>coco.coco_image</code>), 289	kw-	_from_elem()	(kwcoco.demo.toypatterns.CategoryPatterns method), 64
_delitems()	(in module <code>kwcoco._helpers</code>), 205		_get_img_auxiliary()	(kw- coco.coco_dataset.MixinCocoAccessors method), 237
_demo_construct_probs()	(in module <code>coco.demo.perterb</code>), 40	kw-	_handle_sql_uri()	(in module <code>coco.coco_sql_dataset</code>), 309
_demo_construct_probs()	(in module <code>coco.metrics.detect_metrics</code>), 99	kw-	_have_gdal()	(in module <code>coco.util.lazy_frame_backends</code>), 138
_demo_geoinfo_with_nodata()	(in module <code>coco.util.lazy_frame_backends</code>), 139	kw-	_have_rasterio()	(in module <code>coco.util.lazy_frame_backends</code>), 138
_demo_item()	(kwcoco.ChannelSpec method), 346		_have_spectral()	(in module <code>coco.util.lazy_frame_backends</code>), 139
_demo_item()	(kwcoco.channel_spec.ChannelSpec method), 224		_id_to_obj	(kwcoco.coco_objects1d.ObjectList1D property), 290
_devcheck_corner()	(in module <code>coco.util.util_delayed_poc</code>), 165	kw-	_infer_dirs()	(kwcoco.CocoDataset method), 323
_devcheck_load_sub_image()	(in module <code>coco.data.grab_camvid</code>), 30	kw-	_infer_dirs()	(kwcoco.coco_dataset.CocoDataset method), 270
_devcheck_sample_full_image()	(in module <code>coco.data.grab_camvid</code>), 30	kw-	_init()	(kwcoco.coco_evaluator.CocoEvaluator method), 279
_dict	(in module <code>kwcoco.coco_dataset</code>), 235		_invalidate_hashid()	(kw- coco.coco_dataset.MixinCocoExtras method), 244
_draw_video_sequence()	(in module <code>coco.demo.toydata_video</code>), 57	kw-	_item_shapes()	(kwcoco.ChannelSpec method), 346
_ds()	(kwcoco.util.LazyGdalFrameFile method), 179		_item_shapes()	(kwcoco.channel_spec.ChannelSpec method), 224
_ds()	(kwcoco.util.LazyRasterIOFrameFile method), 180		_filter_test_masks()	(kw- coco.util.StratifiedGroupKFold method), 201
_ds()	(kwcoco.util.LazySpectralFrameFile method), 180		_iter_test_masks()	(kw- coco.util.util_sklearn.StratifiedGroupKFold method), 170
_ds()	(kwcoco.util.lazy_frame_backends.LazyGdalFrameFile method), 140		_keypoint_category_names()	(kw- coco.coco_dataset.MixinCocoAccessors method), 240
_ds()	(kwcoco.util.lazy_frame_backends.LazyRasterIOFrameFile method), 139		_largest_shape()	(in module <code>coco.util.util_delayed_poc</code>), 165
_ds()	(kwcoco.util.lazy_frame_backends.LazySpectralFrameFile method), 139		_load_dets()	(in module <code>kwcoco.coco_evaluator</code>), 282
_ensure_dsize()	(kwcoco.util.DelayedLoad method), 191		_load_dets_worker()	(in module <code>kwcoco.coco_evaluator</code>), 283
_ensure_dsize()	(kw- coco.util.util_delayed_poc.DelayedLoad method), 154			
_ensure_image_data()	(kw- coco.coco_dataset.MixinCocoExtras method), 245			

_lookup() (kwcoco.coco_objects1d.ObjectGroups method), 294
_lookup() (kwcoco.coco_objects1d.ObjectList1D method), 292
_lookup_kpnames() (kw-coco.coco_dataset.MixinCocoAccessors method), 240
_lut_frame_index() (in module kwcoco._helpers), 203
_make_test_folds() (kw-coco.util.StratifiedGroupKFold method), 201
_make_test_folds() (kw-coco.util.util_sklearn.StratifiedGroupKFold method), 169
_memo (kwcoco.FusedChannelSpec attribute), 350
_memo (kwcoco.channel_spec.FusedChannelSpec attribute), 215
_new_proxy_cache() (in module kw-coco.coco_sql_dataset), 305
_open() (kwcoco.util.Archive class method), 181
_open() (kwcoco.util.util_archive.Archive class method), 143
_optimize_paths() (kwcoco.util.DelayedCrop method), 185
_optimize_paths() (kwcoco.util.DelayedIdentity method), 188
_optimize_paths() (kwcoco.util.DelayedLoad method), 191
_optimize_paths() (kwcoco.util.DelayedNans method), 194
_optimize_paths() (kw-coco.util.DelayedVisionOperation method), 195
_optimize_paths() (kwcoco.util.DelayedWarp method), 197
_optimize_paths() (kw-coco.util.util_delayed_poc.DelayedCrop method), 165
_optimize_paths() (kw-coco.util.util_delayed_poc.DelayedIdentity method), 150
_optimize_paths() (kw-coco.util.util_delayed_poc.DelayedLoad method), 154
_optimize_paths() (kw-coco.util.util_delayed_poc.DelayedNans method), 151
_optimize_paths() (kw-coco.util.util_delayed_poc.DelayedVisionOperation method), 148
_optimize_paths() (kw-coco.util.util_delayed_poc.DelayedWarp method), 162
_orm_yielder() (in module kwcoco.coco_sql_dataset), 305
_package_info() (kw-coco.demo.toypatterns.CategoryPatterns method), 64
_parse_concise_slice_syntax() (in module kw-coco.channel_spec), 228
_pr_curves() (in module kwcoco.metrics.functional), 105
_pr_curves() (in module kwcoco.metrics.voc_metrics), 109
_pygame_render_boids() (in module kw-coco.demo.boids), 39
_raw_yielder() (in module kwcoco.coco_sql_dataset), 305
_read_envi_header() (in module kw-coco.util.lazy_frame_backends), 141
_read_split_paths() (in module kw-coco.data.grab_voc), 35
_realpos_label_suffix() (in module kw-coco.metrics.drawing), 101
_rectify_classes() (kw-coco.coco_evaluator.CocoEvaluator method), 279
_rectify_slice_dim() (in module kw-coco.util.lazy_frame_backends), 141
_register_imagename() (kw-coco.metrics.DetectionMetrics method), 112
_register_imagename() (kw-coco.metrics.detect_metrics.DetectionMetrics method), 94
_remove_all_annotations() (kw-coco.coco_dataset.CocoIndex method), 267
_remove_all_images() (kw-coco.coco_dataset.CocoIndex method), 267
_remove_annotations() (kw-coco.coco_dataset.CocoIndex method), 267
_remove_categories() (kw-coco.coco_dataset.CocoIndex method), 267
_remove_images() (kw-coco.coco_dataset.CocoIndex method), 267
_remove_videos() (kw-coco.coco_dataset.CocoIndex method), 267
_resolve_to_ann() (kw-coco.coco_dataset.MixinCocoAccessors method), 238
_resolve_to_cat() (kw-coco.coco_dataset.MixinCocoAccessors method), 238
_resolve_to_cid() (kw-coco.coco_dataset.MixinCocoAccessors method), 238
_resolve_to_gid() (kw-coco.coco_dataset.MixinCocoAccessors method)

<code>_method), 238</code>		
<code>_resolve_to_id()</code>	(kw-	<code>AbstractCocoDataset (class in coco.abstract_coco_dataset), 205</code>
<code>coco.coco_dataset.MixinCocoAccessors</code>		<code>add() (kwcoco.util.Archive method), 181</code>
<code>method), 238</code>		<code>add() (kwcoco.util.util_archive.Archive method), 143</code>
<code>_resolve_to_img()</code>	(kw-	<code>add_annotation()</code>
<code>coco.coco_dataset.MixinCocoAccessors</code>		<code>coco.coco_dataset.MixinCocoAddRemove</code>
<code>method), 238</code>		<code>method), 257</code>
<code>_resolve_to_kpcat()</code>	(kw-	<code>add_annotations()</code>
<code>coco.coco_dataset.MixinCocoAccessors</code>		<code>coco.coco_dataset.MixinCocoAddRemove</code>
<code>method), 238</code>		<code>method), 260</code>
<code>_resolve_to_vidid()</code>	(kw-	<code>add_auxiliary_item()</code>
<code>coco.coco_dataset.MixinCocoAccessors</code>		<code>coco.coco_image.CocoImage method), 286</code>
<code>method), 238</code>		<code>add_auxiliary_item() (kwcoco.CocoImage method), 332</code>
<code>_set (kwcoco.coco_dataset.CocoIndex attribute), 266</code>		<code>add_category() (kwcoco.coco_dataset.MixinCocoAddRemove</code>
<code>_set() (kwcoco.coco_objectsId.ObjectListID method), 292</code>		<code>method), 259</code>
<code>_set_sorted_by_frame_index()</code>	(kw-	<code>add_image() (kwcoco.coco_dataset.MixinCocoAddRemove</code>
<code>coco.coco_dataset.CocoIndex method), 266</code>		<code>method), 257</code>
<code>_size_lut (kwcoco.FusedChannelSpec attribute), 350</code>		<code>add_images() (kwcoco.coco_dataset.MixinCocoAddRemove</code>
<code>_size_lut (kwcoco.channel_spec.FusedChannelSpec attribute), 215</code>		<code>method), 261</code>
<code>_spatial_index_scratch() (in module coco.demo.boids), 39</code>	(in module kw-	<code>add_predictions()</code>
		<code>coco.metrics.detect_metrics.DetectionMetrics</code>
<code>_stabalize_data() (in module coco.metrics.confusion_vectors), 93</code>		<code>method), 94</code>
<code>_summarize() (in module coco.metrics.detect_metrics), 100</code>		<code>add_predictions() (kwcoco.metrics.DetectionMetrics</code>
<code>_summary() (kwcoco.metrics.confusion_measures.OneVersusRestMeanIoU method), 84</code>		<code>method), 112</code>
<code>_to_coco() (kwcoco.metrics.DetectionMetrics method), 114</code>		<code>add_predictions() (kw-</code>
<code>_to_coco() (kwcoco.metrics.detect_metrics.DetectionMetrics method), 96</code>		<code>coco.metrics.voc_metrics.VOC_Metrics</code>
<code>_todo_refactor_geometric_info() (kw-</code>		<code>add_truth() (kwcoco.metrics.detect_metrics.DetectionMetrics</code>
<code>coco.demo.toypatterns.CategoryPatterns</code>		<code>method), 95</code>
<code>method), 63</code>		<code>add_truth() (kwcoco.metrics.detect_metrics.DetectionMetrics</code>
<code>_tree() (kwcoco.coco_dataset.MixinCocoExtras method), 243</code>		<code>method), 112</code>
<code>_trunc_op() (in module kwcoco.util.util_truncate), 170</code>		<code>add_truth() (kwcoco.metrics.voc_metrics.VOC_Metrics</code>
<code>_truncated_roc() (in module coco.metrics.functional), 105</code>		<code>method), 109</code>
<code>_update_unused() (kwcoco._helpers._NextId method), 202</code>		<code>add_video() (kwcoco.coco_dataset.MixinCocoAddRemove</code>
<code>_validate_nonzero_data() (in module coco.util.lazy_frame_backends), 141</code>		<code>method), 256</code>
<code>_voc_ave_precision() (in module coco.metrics.voc_metrics), 110</code>		<code>AddError, 317</code>
<code>_voc_eval() (in module kwcoco.metrics.voc_metrics), 110</code>		<code>aids (kwcoco.coco_objectsId.Annots property), 296</code>
<code>_writefig() (in module kwcoco.coco_evaluator), 282</code>		<code>aids (kwcoco.coco_objectsId.Images property), 296</code>
<code>_yeah_boid() (in module kwcoco.demo.boids), 39</code>		<code>ALCHEMY_MODE_DEFAULT (in module coco.coco_sql_dataset), 305</code>
A		<code>alias (kwcoco.coco_sql_dataset.Category attribute), 304</code>
<code>AbstractCocoDataset (class in kwcoco), 321</code>		<code>alias (kwcoco.coco_sql_dataset.KeypointCategory attribute), 304</code>
		<code>ALLOF (in module kwcoco.coco_schema), 300</code>
		<code>ALLOF (in module kwcoco.util), 173</code>
		<code>ALLOF (in module kwcoco.util.jsonschema_elements), 137</code>
		<code>ALLOF () (kwcoco.util.jsonschema_elements.QuantifierElements method), 135</code>
		<code>ALLOF () (kwcoco.util.QuantifierElements method), 176</code>
		<code>Annotation (class in kwcoco.coco_sql_dataset), 304</code>
		<code>ANNOTATION (in module kwcoco.coco_schema), 301</code>
		<code>AnnotGroups (class in kwcoco.coco_objectsId), 298</code>

Annotations (class in `kwcoco.coco_objects1d`), 296
annots (`kwcoco.coco_objects1d.Images` property), 296
annots() (`kwcoco.coco_dataset.MixinCocoObjects` method), 248
anns (`kwcoco.coco_dataset.MixinCocoIndex` property), 267
anns (`kwcoco.coco_sql_dataset.CocoSqlDatabase` property), 311
annToMask() (`kwcoco.compat_dataset.COCO` method), 316
annToRLE() (`kwcoco.compat_dataset.COCO` method), 316
ANY (in module `kwcoco.coco_schema`), 300
ANY (in module `kwcoco.util`), 173
ANY (in module `kwcoco.util.jsonschema_elements`), 137
ANY (`kwcoco.util.jsonschema_elements.QuantifierElements` property), 135
ANY (`kwcoco.util.QuantifierElements` property), 176
ANYOF (in module `kwcoco.coco_schema`), 300
ANYOF (in module `kwcoco.util`), 173
ANYOF (in module `kwcoco.util.jsonschema_elements`), 137
ANYOF() (`kwcoco.util.jsonschema_elements.QuantifierElements` method), 135
ANYOF() (`kwcoco.util.QuantifierElements` method), 176
Archive (class in `kwcoco.util`), 180
Archive (class in `kwcoco.util.util_archive`), 142
area (`kwcoco.coco_objects1d.Images` property), 295
ARRAY (in module `kwcoco.coco_schema`), 300
ARRAY (in module `kwcoco.util`), 173
ARRAY (in module `kwcoco.util.jsonschema_elements`), 137
ARRAY() (`kwcoco.util.ContainerElements` method), 173
ARRAY() (`kwcoco.util.jsonschema_elements.ContainerElements` method), 135
as_list() (`kwcoco.channel_spec.FusedChannelSpec` method), 217
as_list() (`kwcoco.FusedChannelSpec` method), 352
as_oerset() (`kwcoco.channel_spec.FusedChannelSpec` method), 218
as_oerset() (`kwcoco.FusedChannelSpec` method), 352
as_path() (`kwcoco.channel_spec.ChannelSpec` method), 223
as_path() (`kwcoco.channel_spec.FusedChannelSpec` method), 218
as_path() (`kwcoco.ChannelSpec` method), 344
as_path() (`kwcoco.FusedChannelSpec` method), 352
as_set() (`kwcoco.channel_spec.FusedChannelSpec` method), 218
as_set() (`kwcoco.FusedChannelSpec` method), 352
ASCII_ONLY (in module `kwcoco.metrics.clf_report`), 74
asdict (`kwcoco.util.dict_like.DictLike` attribute), 131
asdict (`kwcoco.util.DictLike` attribute), 172
assert_dsets_allclose() (in module `kwcoco.coco_sql_dataset`), 313
attribute_frequency() (kw-

coco.coco_objects1d.ObjectList1D method), 293
auxiliary (`kwcoco.coco_sql_dataset.Image` attribute), 304
available() (`kwcoco.util.lazy_frame_backends.LazyGDalFrameFile` class method), 140
available() (`kwcoco.util.lazy_frame_backends.LazyRasterIOFrameFile` class method), 139
available() (`kwcoco.util.lazy_frame_backends.LazySpectralFrameFile` class method), 139
available() (`kwcoco.util.LazyGDalFrameFile` class method), 179
available() (`kwcoco.util.LazyRasterIOFrameFile` class method), 180
available() (`kwcoco.util.LazySpectralFrameFile` class method), 180

B

BaseChannelSpec (class in `kwcoco.channel_spec`), 213
basic_stats() (`kwcoco.coco_dataset.MixinCocoStats` method), 253
BBOX (in module `kwcoco.coco_schema`), 301
bbox (`kwcoco.coco_sql_dataset.Annotation` attribute), 305
benchmark_large_hyperspectral() (in module `kwcoco.examples.bench_large_hyperspectral`), 64
binarize_classless() (kw-coco.metrics.confusion_vectors.ConfusionVectors method), 88
binarize_classless() (kw-coco.metrics.ConfusionVectors method), 123
binarize_ovr() (`kwcoco.metrics.confusion_vectors.ConfusionVectors` method), 88
binarize_ovr() (kw-coco.metrics.ConfusionVectors method), 124
BinaryConfusionVectors (class in `kwcoco.metrics`), 117
BinaryConfusionVectors (class in kw-coco.metrics.confusion_vectors), 90
block_seen() (`kwcoco._helpers._ID_Remapper` method), 203
Boids (class in `kwcoco.demo.boids`), 36
BOOLEAN (in module `kwcoco.coco_schema`), 300
BOOLEAN (in module `kwcoco.util`), 173
BOOLEAN (in module `kwcoco.util.jsonschema_elements`), 137
BOOLEAN (`kwcoco.util.jsonschema_elements.ScalarElements` property), 134
BOOLEAN (`kwcoco.util.ScalarElements` property), 176
boundary_conditions() (`kwcoco.demo.boids.Boids` method), 37
boxes (`kwcoco.coco_objects1d.Annots` property), 297

`boxsize_stats()` (kw-
`coco.coco_dataset.MixinCocoStats` method), 254

`build()` (kwcoco.coco_dataset.CocoIndex method), 267

`build()` (kwcoco.coco_sql_dataset.CocoSqlIndex method), 309

`bundle_dpath` (kwcoco.coco_image.CocoImage property), 284

`bundle_dpath` (kwcoco.coco_sql_dataset.CocoSqlDatabase property), 312

`bundle_dpath` (kwcoco.CocoImage property), 330

C

`cached_sql_coco_view()` (in module `kw-
 coco.coco_sql_dataset`), 313

`caption` (kwcoco.coco_sql_dataset.Annotation attribute), 305

`caption` (kwcoco.coco_sql_dataset.Video attribute), 304

`Categories` (class in kwcoco.coco_objectsId), 294

`categories()` (kwcoco.coco_dataset.MixinCocoObjects method), 249

`Category` (class in kwcoco.coco_sql_dataset), 303

`CATEGORY` (in module `kwcoco.coco_schema`), 301

`category_annotation_frequency()` (kw-
`coco.coco_dataset.MixinCocoStats` method), 251

`category_annotation_type_frequency()` (kw-
`coco.coco_dataset.MixinCocoStats` method), 251

`category_graph()` (kw-
`coco.coco_dataset.MixinCocoAccessors` method), 239

`category_id` (kwcoco.coco_objectsId.Annots property), 296

`category_id` (kwcoco.coco_sql_dataset.Annotation attribute), 305

`category_names` (kwcoco.category_tree.CategoryTree property), 210

`category_names` (kwcoco.CategoryTree property), 339

`CategoryPatterns` (class in kwcoco.demo.toypatterns), 62

`CategoryTree` (class in kwcoco), 335

`CategoryTree` (class in kwcoco.category_tree), 206

`catname` (kwcoco.metrics.BinaryConfusionVectors property), 118

`catname` (kwcoco.metrics.confusion_measures.Measures property), 78

`catname` (kwcoco.metrics.confusion_vectors.BinaryConfusion property), 91

`catname` (kwcoco.metrics.Measures property), 125

`cats` (kwcoco.category_tree.CategoryTree property), 210

`cats` (kwcoco.CategoryTree property), 339

`cats` (kwcoco.coco_dataset.MixinCocoIndex property), 267

`cats` (kwcoco.coco_sql_dataset.CocoSqlDatabase property), 311

`catToImgs` (kwcoco.compat_dataset.COCO property), 314

`CHANNELS` (in module `kwcoco.coco_schema`), 301

`channels` (kwcoco.coco_image.CocoImage property), 284

`channels` (kwcoco.coco_sql_dataset.Image attribute), 304

`channels` (kwcoco.CocoImage property), 330

`channels` (kwcoco.util.DelayedChannelConcat property), 183

`channels` (kwcoco.util.DelayedCrop property), 185

`channels` (kwcoco.util.DelayedFrameConcat property), 186

`channels` (kwcoco.util.DelayedLoad property), 191

`channels` (kwcoco.util.DelayedNans property), 193

`channels` (kwcoco.util.DelayedWarp property), 197

`channels` (kwcoco.util.util_delayed_poc.DelayedChannelConcat property), 159

`channels` (kwcoco.util.util_delayed_poc.DelayedCrop property), 165

`channels` (kwcoco.util.util_delayed_poc.DelayedFrameConcat property), 157

`channels` (kwcoco.util.util_delayed_poc.DelayedLoad property), 154

`channels` (kwcoco.util.util_delayed_poc.DelayedNans property), 151

`channels` (kwcoco.util.util_delayed_poc.DelayedWarp property), 162

`ChannelSpec` (class in kwcoco), 340

`ChannelSpec` (class in kwcoco.channel_spec), 219

`children()` (kwcoco.util.DelayedChannelConcat method), 182

`children()` (kwcoco.util.DelayedCrop method), 185

`children()` (kwcoco.util.DelayedFrameConcat method), 186

`children()` (kwcoco.util.DelayedIdentity method), 188

`children()` (kwcoco.util.DelayedLoad method), 191

`children()` (kwcoco.util.DelayedNans method), 193

`children()` (kwcoco.util.DelayedVisionOperation method), 195

`children()` (kwcoco.util.DelayedWarp method), 197

`children()` (kwcoco.util.util_delayed_poc.DelayedChannelConcat method), 159

`children()` (kwcoco.util.util_delayed_poc.DelayedCrop method), 165

`children()` (kwcoco.util.util_delayed_poc.DelayedFrameConcat method), 157

`children()` (kwcoco.util.util_delayed_poc.DelayedIdentity method), 150

`children()` (kwcoco.util.util_delayed_poc.DelayedLoad method), 154

`children()` (kwcoco.util.util_delayed_poc.DelayedNans

method), 151
children() (kwCOCO.util.util_delayed_poc.DelayedVisionOperation method), 148
children() (kwCOCO.util.util_delayed_poc.DelayedWarp method), 162
cid_to_aids (kwCOCO.coco_dataset.MixinCocoIndex property), 267
cid_to_gids (kwCOCO.coco_dataset.CocoIndex property), 266
cid_to_rgb() (in module kwCOCO.data.grab_camvid), 31
cids (kwCOCO.coco_objectsId.AnnotGroups property), 298
cids (kwCOCO.coco_objectsId.Annots property), 297
cids (kwCOCO.coco_objectsId.Categories property), 294
clamp_mag() (in module kwCOCO.demo.boids), 37
class_accuracy_from_confusion() (in module kwCOCO.metrics.sklearn_alts), 107
class_names (kwCOCO.category_tree.CategoryTree property), 210
class_names (kwCOCO.CategoryTree property), 339
classification_report() (in module kwCOCO.metrics.clf_report), 74
classification_report() (kwCOCO.metrics.confusion_vectors.ConfusionVectors method), 89
classification_report() (kwCOCO.metrics.ConfusionVectors method), 124
clear() (kwCOCO.coco_dataset.CocoIndex method), 267
clear() (kwCOCO.metrics.detect_metrics.DetectionMetrics method), 94
clear() (kwCOCO.metrics.DetectionMetrics method), 112
clear_annotations() (kwCOCO.coco_dataset.MixinCocoAddRemove method), 262
clear_images() (kwCOCO.coco_dataset.MixinCocoAddRemove method), 261
CLIConfig (kwCOCO.cli.coco_eval.CocoEvalCLI attribute), 17
close() (kwCOCO.util.Archive method), 181
close() (kwCOCO.util.util_archive.Archive method), 143
closest_point_on_line_segment() (in module kwCOCO.demo.boids), 39
cnames (kwCOCO.coco_objectsId.AnnotGroups property), 298
cnames (kwCOCO.coco_objectsId.Annots property), 297
coarsen() (kwCOCO.metrics.confusion_vectors.ConfusionVectors method), 88
coarsen() (kwCOCO.metrics.ConfusionVectors method), 123
COCO (class in kwCOCO.compat_dataset), 314
coco_image() (kwCOCO.coco_dataset.MixinCocoAccessors method), 240
coco_images (kwCOCO.coco_objectsId.Images property), 295
COCO_SAMPLER_CLS (in module kwCOCO.coco_evaluator), 278
COCO_SCHEMA (in module kwCOCO.coco_schema), 301
coco_to_kpf() (in module kwCOCO.kpf), 317
CocoBase (in module kwCOCO.coco_sql_dataset), 303
CocoConformCLI (class in kwCOCO.cli.coco_conform), 15
CocoConformCLI.CLICConfig (class in kwCOCO.cli.coco_conform), 15
CocoDataset (class in kwCOCO), 321
CocoDataset (class in kwCOCO.coco_dataset), 267
CocoEvalCLI (class in kwCOCO.cli.coco_eval), 17
CocoEvalCLIConfig (class in kwCOCO.cli.coco_eval), 16
CocoEvalConfig (class in kwCOCO.coco_evaluator), 278
CocoEvaluator (class in kwCOCO.coco_evaluator), 278
CocoGrabCLI (class in kwCOCO.cli.coco_grab), 19
CocoGrabCLI.CLICConfig (class in kwCOCO.cli.coco_grab), 19
CocoImage (class in kwCOCO), 329
CocoImage (class in kwCOCO.coco_image), 283
CocoIndex (class in kwCOCO.coco_dataset), 265
CocoModifyCatsCLI (class in kwCOCO.cli.coco_modify_categories), 20
CocoModifyCatsCLI.CLICConfig (class in kwCOCO.cli.coco_modify_categories), 20
CocoRerootCLI (class in kwCOCO.cli.coco_reroot), 21
CocoRerootCLI.CLICConfig (class in kwCOCO.cli.coco_reroot), 21
CocoResults (class in kwCOCO.coco_evaluator), 280
CocoShowCLI (class in kwCOCO.cli.coco_show), 22
CocoShowCLI.CLICConfig (class in kwCOCO.cli.coco_show), 22
CocoSingleResult (class in kwCOCO.coco_evaluator), 281
CocoSplitCLI (class in kwCOCO.cli.coco_split), 23
CocoSplitCLI.CLICConfig (class in kwCOCO.cli.coco_split), 23
CocoSqlDatabase (class in kwCOCO.coco_sql_dataset), 309
CocoSqlIndex (class in kwCOCO.coco_sql_dataset), 309
CocoStatsCLI (class in kwCOCO.cli.coco_stats), 24
CocoStatsCLI.CLICConfig (class in kwCOCO.cli.coco_stats), 24
CocoSubsetCLI (class in kwCOCO.cli.coco_subset), 25
CocoSubsetCLI.CLICConfig (class in kwCOCO.cli.coco_subset), 25
CocoToyDataCLI (class in kwCOCO.cli.coco_toydata), 27
CocoToyDataCLI.CLICConfig (class in kwCOCO.cli.coco_toydata), 27
CocoUnionCLI (class in kwCOCO.cli.coco_union), 28
CocoUnionCLI.CLICConfig (class in kwCOCO.cli.coco_union), 28
CocoValidateCLI (class in kwCOCO.cli.coco_validate),

29	37
CocoValidateCLI.CLIConfig (class in kwcoco.cli.coco_validate), 29	concat() (kwcoco.channel_spec.FusedChannelSpec class method), 216
code_list() (kwcoco.channel_spec.ChannelSpec method), 223	concat() (kwcoco.FusedChannelSpec class method), 350
code_list() (kwcoco.channel_spec.FusedChannelSpec method), 217	concise_si_display() (in module kwcoco.metrics.drawing), 101
code_list() (kwcoco.ChannelSpec method), 344	concise() (kwcoco.channel_spec.ChannelSpec method), 222
code_list() (kwcoco.FusedChannelSpec method), 352	concise() (kwcoco.channel_spec.FusedChannelSpec method), 216
coerce() (kwcoco.category_tree.CategoryTree class method), 208	concise() (kwcoco.ChannelSpec method), 343
coerce() (kwcoco.CategoryTree class method), 337	concise() (kwcoco.FusedChannelSpec method), 350
coerce() (kwcoco.channel_spec.BaseChannelSpec class method), 214	Config (kwcoco.coco_evaluator.CocoEvaluator attribute), 279
coerce() (kwcoco.channel_spec.ChannelSpec class method), 221	conform() (kwcoco.coco_dataset.MixinCocoStats method), 252
coerce() (kwcoco.channel_spec.FusedChannelSpec class method), 216	confusion_matrix() (in module kwcoco.metrics.sklearn_alts), 106
coerce() (kwcoco.ChannelSpec class method), 342	confusion_matrix() (kwcoco.metrics.confusion_vectors.ConfusionVectors method), 87
coerce() (kwcoco.coco_dataset.MixinCocoExtras class method), 241	confusion_matrix() (kwcoco.metrics.ConfusionVectors method), 122
coerce() (kwcoco.coco_sql_dataset.CocoSqlDatabase class method), 313	confusion_vectors() (kwcoco.metrics.detect_metrics.DetectionMetrics method), 95
coerce() (kwcoco.demo.toypatterns.CategoryPatterns class method), 62	confusion_vectors() (kwcoco.metrics.DetectionMetrics method), 113
coerce() (kwcoco.FusedChannelSpec class method), 350	ConfusionVectors (class in kwcoco.metrics), 120
coerce() (kwcoco.util.Archive class method), 181	ConfusionVectors (class in kwcoco.metrics.combiner_coco.metrics.confusion_vectors), 85
coerce() (kwcoco.util.DelayedLoad class method), 191	connect() (kwcoco.coco_sql_dataset.CocoSqlDatabase method), 310
coerce() (kwcoco.util.util_archive.Archive class method), 143	ContainerElements (class in kwcoco.util), 173
coerce() (kwcoco.util.util_delayed_poc.DelayedLoad class method), 154	PartialContainerElement (class in kwcoco.util.jsonschema_elements), 135
combine() (kwcoco.metrics.confusion_measures.Measure class method), 83	convert_camvid_raw_to_coco() (in module kwcoco.data.grab_camvid), 31
combine() (kwcoco.metrics.confusion_measures.Measures class method), 79	convert_cifar10() (in module kwcoco.data.grab_cifar), 32
combine() (kwcoco.metrics.confusion_measures.OneVersusAll class method), 84	convert_cifar100() (in module kwcoco.data.grab_cifar), 32
combine() (kwcoco.metrics.Measures class method), 126	convert_spacenet_to_kwccoco() (in module kwcoco.data.grab_spacenet), 34
component_indices() (kwcoco.channel_spec.ChannelSpec method), 227	convert_voc_to_coco() (in module kwcoco.data.grab_voc), 35
component_indices() (kwcoco.channel_spec.FusedChannelSpec method), 218	CoordinateCompatibilityError, 317
component_indices() (kwcoco.ChannelSpec method), 348	copy() (kwcoco.category_tree.CategoryTree method), 207
component_indices() (kwcoco.FusedChannelSpec method), 353	copy() (kwcoco.CategoryTree method), 336
compress() (kwcoco.coco_objects1d.ObjectList1D method), 290	copy() (kwcoco.coco_dataset.CocoDataset method),
compute_forces() (kwcoco.demo.boids.Boids method),	

270
copy() (kwcoco.CocoDataset method), 324
copy() (kwcoco.util.dict_like.DictLike method), 131
copy() (kwcoco.util.DictLike method), 173
corrupted_images() (kw-
coco.coco_dataset.MixinCocoExtras method),
246
counts() (kwcoco.metrics.confusion_measures.Measures
method), 79
counts() (kwcoco.metrics.Measures method), 125
createIndex() (kwcoco.compat_dataset.COCO
method), 314
crop() (kwcoco.util.DelayedVisionOperation method),
195
crop() (kwcoco.util.util_delayed_poc.DelayedVisionOperation
method), 148

D

data_fpath (kwcoco.coco_dataset.MixinCocoExtras
property), 248
data_fpath (kwcoco.coco_sql_dataset.CocoSqlDatabase
property), 312
data_root (kwcoco.coco_dataset.MixinCocoExtras
property), 248
dataset (kwcoco.coco_sql_dataset.CocoSqlDatabase
property), 311
dataset_modification_example_via_construction()
(in module kw-
coco.examples.modification_example), 67
dataset_modification_example_via_copy()
(in module kw-
coco.examples.modification_example), 67
DatasetBase (in module kw-
coco.examples.simple_kwkcoco_torch_dataset),
68
decode() (kwcoco.channel_spec.ChannelSpec method),
226
decode() (kwcoco.ChannelSpec method), 347
default (kwcoco.cli.coco_conform.CocoConformCLI.CLICConfig
attribute), 15
default (kwcoco.cli.coco_eval.CocoEvalCLICConfig at-
tribute), 17
default (kwcoco.cli.coco_grab.CocoGrabCLI.CLICConfig
attribute), 19
default (kwcoco.cli.coco_modify_categories.CocoModifyCatsCLI.CLICConfig
attribute), 149
default (kwcoco.cli.coco_modify_attributes.CocoModifyAttributesCLI.
CLICConfig attribute), 20
default (kwcoco.cli.coco_reroot.CocoRerootCLI.CLICConfig
attribute), 21
default (kwcoco.cli.coco_show.CocoShowCLI.CLICConfig
attribute), 22
default (kwcoco.cli.coco_split.CocoSplitCLI.CLICConfig
attribute), 23
default (kwcoco.cli.coco_stats.CocoStatsCLI.CLICConfig
attribute), 24

default (kwcoco.cli.coco_subset.CocoSubsetCLI.CLICConfig
attribute), 25
default (kwcoco.cli.coco_toydata.CocoToyDataCLI.CLICConfig
attribute), 27
default (kwcoco.cli.coco_union.CocoUnionCLI.CLICConfig
attribute), 28
default (kwcoco.cli.coco_validate.CocoValidateCLI.CLICConfig
attribute), 29
default (kwcoco.coco_evaluator.CocoEvalConfig
attribute), 278
DEFAULT_COLUMNS (kwcoco.kw18.KW18 attribute), 319
delay() (kwcoco.coco_image.CocoImage method), 286
delay() (kwcoco.CocoImage method), 332
delayed_crop() (kwcoco.util.DelayedFrameConcat
method), 186
delayed_crop() (kwcoco.util.DelayedImageOperation
method), 188
delayed_crop() (kwcoco.util.DelayedLoad method),
191
delayed_crop() (kwcoco.util.DelayedNans method),
194
delayed_crop() (kwcoco.util.util_delayed_poc.DelayedFrameConcat
method), 157
delayed_crop() (kwcoco.util.util_delayed_poc.DelayedImageOperation
method), 148
delayed_crop() (kwcoco.util.util_delayed_poc.DelayedLoad
method), 154
delayed_crop() (kwcoco.util.util_delayed_poc.DelayedNans
method), 151
delayed_load() (kwcoco.coco_dataset.MixinCocoAccessors
method), 235
delayed_warp() (kwcoco.util.DelayedChannelConcat
method), 183
delayed_warp() (kwcoco.util.DelayedFrameConcat
method), 187
delayed_warp() (kwcoco.util.DelayedImageOperation
method), 189
delayed_warp() (kwcoco.util.DelayedNans method),
195
delayed_warp() (kwcoco.util.util_delayed_poc.DelayedChannelConcat
method), 159
delayed_warp() (kwcoco.util.util_delayed_poc.DelayedFrameConcat
method), 158
delayed_warp() (kwcoco.util.util_delayed_poc.DelayedImageOperation
method), 149
delayed_warp() (kwcoco.util.util_delayed_poc.DelayedNans
method), 152
DelayedChannelConcat (class in kwcoco.util), 181
DelayedChannelConcat (class in kw-
coco.util.util_delayed_poc), 158
DelayedCrop (class in kwcoco.util), 184
DelayedCrop (class in kwcoco.util.util_delayed_poc),
164
DelayedFrameConcat (class in kwcoco.util), 185

DelayedFrameConcat (class in `coco.util.util_delayed_poc`), 156
DelayedIdentity (class in `kwcoco.util`), 187
DelayedIdentity (class in `coco.util.util_delayed_poc`), 149
DelayedImageOperation (class in `kwcoco.util`), 188
DelayedImageOperation (class in `coco.util.util_delayed_poc`), 148
DelayedLoad (class in `kwcoco.util`), 190
DelayedLoad (class in `kwcoco.util.util_delayed_poc`), 152
DelayedNans (class in `kwcoco.util`), 193
DelayedNans (class in `kwcoco.util.util_delayed_poc`), 151
DelayedVideoOperation (class in `kwcoco.util`), 195
DelayedVideoOperation (class in `coco.util.util_delayed_poc`), 148
DelayedVisionOperation (class in `kwcoco.util`), 195
DelayedVisionOperation (class in `coco.util.util_delayed_poc`), 148
DelayedWarp (class in `kwcoco.util`), 195
DelayedWarp (class in `kwcoco.util.util_delayed_poc`), 161
delete() (`kwcoco.coco_sql_dataset.CocoSqlDatabase` method), 311
delitem() (`kwcoco.util.dict_like.DictLike` method), 131
delitem() (`kwcoco.util.DictLike` method), 173
demo() (in module `kwcoco.coco_sql_dataset`), 313
demo() (in module `kwcoco.kpf`), 317
demo() (`kwcoco.category_tree.CategoryTree` class method), 208
demo() (`kwcoco.CategoryTree` class method), 337
demo() (`kwcoco.coco_dataset.MixinCocoExtras` class method), 241
demo() (`kwcoco.kw18.KW18` class method), 319
demo() (`kwcoco.metrics.BinaryConfusionVectors` class method), 118
demo() (`kwcoco.metrics.confusion_measures.Measures` class method), 79
demo() (`kwcoco.metrics.confusion_vectors.BinaryConfusionVectors` class method), 91
demo() (`kwcoco.metrics.confusion_vectors.ConfusionVector` class method), 86
demo() (`kwcoco.metrics.confusion_vectors.OneVsRestConfusionVector` class method), 89
demo() (`kwcoco.metrics.ConfusionVectors` class method), 122
demo() (`kwcoco.metrics.detect_metrics.DetectionMetrics` class method), 97
demo() (`kwcoco.metrics.DetectionMetrics` class method), 115
demo() (`kwcoco.metrics.Measures` class method), 126
demo() (`kwcoco.metrics.OneVsRestConfusionVectors` class method), 129
demo() (`kwcoco.util.DelayedIdentity` class method), 188
demo() (`kwcoco.util.DelayedLoad` class method), 191
demo() (`kwcoco.util.lazy_frame_backends.LazyGdalFrameFile` class method), 140
demo() (`kwcoco.util.LazyGdalFrameFile` class method), 179
demo() (`kwcoco.util.util_delayed_poc.DelayedIdentity` class method), 150
demo() (`kwcoco.util.util_delayed_poc.DelayedLoad` class method), 154
demo_coco_data() (in module `kwcoco.coco_dataset`), 276
demo_format_options() (in module `coco.metrics.drawing`), 101
demo_load_msi_data() (in module `kwcoco.examples.loading_multispectral_data`), 67
demo_vectorize_interface() (in module `kwcoco.examples.getting_started_existing_dataset`), 66
demo_vectorized_interface() (in module `kwcoco.examples.vectorized_interface`), 69
demodata_toy_dset() (in module `coco.demo.toydata`), 45
demodata_toy_dset() (in module `coco.demo.toydata_image`), 49
demodata_toy_img() (in module `coco.demo.toydata`), 47
demodata_toy_img() (in module `coco.demo.toydata_image`), 50
deprecated() (in module `kwcoco.coco_schema`), 300
dequantize() (in module `coco.util.util_delayed_poc`), 150
detach() (`kwcoco.coco_image.CocoImage` method), 284
detach() (`kwcoco.CocoImage` method), 330
DetectionMetrics (class in `kwcoco.metrics`), 111
DetectionMetrics (class in `kwcoco.metrics.detect_metrics`), 94
detections (`kwcoco.coco_objects1d.Annots` property), 297
devcheck() (in module `kwcoco.coco_sql_dataset`), 313
DictLike (class in `kwcoco.util`), 172
DictLike (class in `kwcoco.util.dict_like`), 131
DictProxy (class in `kwcoco.metrics.util`), 108
difference() (`kwcoco.channel_spec.BaseChannelSpec` method), 214
difference() (`kwcoco.channel_spec.ChannelSpec` method), 223
difference() (`kwcoco.channel_spec.FusedChannelSpec` method), 218
difference() (`kwcoco.ChannelSpec` method), 344
difference() (`kwcoco.FusedChannelSpec` method), 352
disconnect() (`kwcoco.coco_sql_dataset.CocoSqlDatabase`

method), 310
dmet_area_weights() (in module kwcoco.coco_evaluator), 280
download() (kwCOCO.compat_dataset.COCO method), 316
draw() (kwCOCO.metrics.confusion_measures.Measures method), 79
draw() (kwCOCO.metrics.confusion_measures.PerClass_Measures method), 82
draw() (kwCOCO.metrics.Measures method), 125
draw() (kwCOCO.metrics.PerClass_Measures method), 129
draw_distribution() (kwcoco.metrics.BinaryConfusionVectors method), 119
draw_distribution() (kwcoco.metrics.confusion_vectors.BinaryConfusion method), 92
draw_image() (kwCOCO.coco_dataset.MixinCocoDraw method), 255
draw_perclass_prcurve() (in module kwcoco.metrics.drawing), 102
draw_perclass_roc() (in module kwcoco.metrics.drawing), 100
draw_perclass_thresholds() (in module kwcoco.metrics.drawing), 102
draw_pr() (kwCOCO.metrics.confusion_measures.PerClass_Measures method), 82
draw_pr() (kwCOCO.metrics.PerClass_Measures method), 130
draw_prcurve() (in module kwCOCO.metrics.drawing), 103
draw_roc() (in module kwCOCO.metrics.drawing), 103
draw_roc() (kwCOCO.metrics.confusion_measures.PerClass_Measures method), 82
draw_roc() (kwCOCO.metrics.PerClass_Measures method), 130
draw_threshold_curves() (in module kwcoco.metrics.drawing), 104
draw_true_and_pred_boxes() (in module kwcoco.examples.draw_gt_and_predicted_boxes), 65
dszie (kwCOCO.coco_image.CocoImage property), 284
dszie (kwCOCO.CocoImage property), 330
dszie (kwCOCO.util.DelayedLoad property), 191
dszie (kwCOCO.util.DelayedNans property), 193
dszie (kwCOCO.util.DelayedWarp property), 197
dszie (kwCOCO.util.util_delayed_poc.DelayedLoad property), 154
dszie (kwCOCO.util.util_delayed_poc.DelayedNans property), 151
dszie (kwCOCO.util.util_delayed_poc.DelayedWarp property), 162
dtype (kwCOCO.util.lazy_frame_backends.LazyGDalFrameFile
property), 140
dtype (kwCOCO.util.lazy_frame_backends.LazyRasterIOFrameFile
property), 139
dtype (kwCOCO.util.lazy_frame_backends.LazySpectralFrameFile
property), 139
dtype (kwCOCO.util.LazyGDalFrameFile property), 179
dtype (kwCOCO.util.LazyRasterIOFrameFile property), 180
dtype (kwCOCO.util.LazySpectralFrameFile property), 180
dump() (kwCOCO.coco_dataset.CocoDataset method), 271
dump() (kwCOCO.coco_evaluator.CocoResults method), 281
dump() (kwCOCO.coco_evaluator.CocoSingleResult
method), 282
dump() (kwCOCO.CocoDataset method), 325
dump() (kwCOCO.kw18.KW18 method), 320
dump_figures() (kwCOCO.coco_evaluator.CocoResults
method), 281
dump_figures() (kwCOCO.coco_evaluator.CocoSingleResult
method), 282
dumps() (kwCOCO.coco_dataset.CocoDataset method), 271
dumps() (kwCOCO.CocoDataset method), 324
dumps() (kwCOCO.kw18.KW18 method), 320
DuplicateAddError, 317

E

eff() (kwCOCO.demo.toypatterns.Rasters static method), 64
elem (in module kwCOCO.coco_schema), 300
elem (in module kwCOCO.util), 178
elem (module kwCOCO.util.jsonschema_elements), 137
Element (class in kwCOCO.util), 174
Element (class in kwCOCO.util.jsonschema_elements), 133
encode() (kwCOCO.channel_spec.ChannelSpec method), 225
encode() (kwCOCO.ChannelSpec method), 346
ensure_category() (kwcoco.coco_dataset.MixinCocoAddRemove
method), 260
ensure_image() (kwCOCO.coco_dataset.MixinCocoAddRemove
method), 260
ensure_json_serializable() (in module kwcoco.util), 198
ensure_json_serializable() (in module kwcoco.util.util_json), 166
ensure_sql_coco_view() (in module kwcoco.coco_sql_dataset), 313
ensure_voc_coco() (in module kwcoco.data.grab_voc), 35

`ensure_voc_data()` (in module `coco.data.grab_voc`), 35

`epilog` (`kwcoco.cli.coco_conform.CocoConformCLI.CLICat` attribute), 15

`epilog` (`kwcoco.cli.coco_modify_categories.CocoModifyCatsCLI.CLICat` attribute), 20

`epilog` (`kwcoco.cli.coco_reroot.CocoRerootCLI.CLICat` attribute), 21

`epilog` (`kwcoco.cli.coco_show.CocoShowCLI.CLICat` attribute), 22

`epilog` (`kwcoco.cli.coco_split.CocoSplitCLI.CLICat` attribute), 23

`epilog` (`kwcoco.cli.coco_stats.CocoStatsCLI.CLICat` attribute), 24

`epilog` (`kwcoco.cli.coco_subset.CocoSubsetCLI.CLICat` attribute), 25

`epilog` (`kwcoco.cli.coco_toydata.CocoToyDataCLI.CLICat` attribute), 27

`epilog` (`kwcoco.cli.coco_union.CocoUnionCLI.CLICat` attribute), 28

`epilog` (`kwcoco.cli.coco_validate.CocoValidateCLI.CLICat` attribute), 29

`eval_detections_cli()` (in module `kwcoco.metrics`), 117

`eval_detections_cli()` (in module `kwcoco.metrics.detect_metrics`), 100

`evaluate()` (`kwcoco.coco_evaluator.CocoEvaluator` method), 280

`extended_stats()` (`kwcoco.coco_dataset.MixinCocoStats` method), 253

`extra` (`kwcoco.coco_sql_dataset.Annotation` attribute), 305

`extra` (`kwcoco.coco_sql_dataset.Category` attribute), 304

`extra` (`kwcoco.coco_sql_dataset.Image` attribute), 304

`extra` (`kwcoco.coco_sql_dataset.KeypointCategory` attribute), 304

`extra` (`kwcoco.coco_sql_dataset.Video` attribute), 304

`extractall()` (`kwcoco.util.Archive` method), 181

`extractall()` (`kwcoco.util.util_archive.Archive` method), 143

F

`false_color()` (in module `coco.demo.toydata_video`), 60

`fast_confusion_matrix()` (in module `kwcoco.metrics.functional`), 105

`file_name` (`kwcoco.coco_sql_dataset.Image` attribute), 304

`finalize()` (`kwcoco.metrics.confusion_measures.Measure` method), 83

`finalize()` (`kwcoco.metrics.confusion_measures.OneVersusRestMeasurer` method), 84

`finalize()` (in module `kwcoco.util.DelayedChannelConcat` method), 183

`finalize()` (`kwcoco.util.DelayedCrop` method), 185

`finalize()` (`kwcoco.util.DelayedFrameConcat` method), 186

`finalize()` (`kwcoco.util.DelayedIdentity` method), 188

`finalize()` (`kwcoco.util.DelayedLoad` method), 191

`finalize()` (`kwcoco.util.DelayedNans` method), 194

`finalize()` (`kwcoco.util.DelayedVisionOperation` method), 195

`finalize()` (`kwcoco.util.DelayedWarp` method), 197

`finalize()` (`kwcoco.util.util_delayed_poc.DelayedChannelConcat` method), 159

`finalize()` (`kwcoco.util.util_delayed_poc.DelayedCrop` method), 165

`finalize()` (`kwcoco.util.util_delayed_poc.DelayedFrameConcat` method), 157

`finalize()` (`kwcoco.util.util_delayed_poc.DelayedIdentity` method), 150

`finalize()` (`kwcoco.util.util_delayed_poc.DelayedLoad` method), 154

`finalize()` (`kwcoco.util.util_delayed_poc.DelayedNans` method), 151

`finalize()` (`kwcoco.util.util_delayed_poc.DelayedVisionOperation` method), 148

`finalize()` (`kwcoco.util.util_delayed_poc.DelayedWarp` method), 163

`find_asset_obj()` (`kwcoco.coco_image.CocoImage` method), 285

`find_asset_obj()` (`kwcoco.CocoImage` method), 331

`find_json_unserializable()` (in module `kwcoco.util`), 199

`find_json_unserializable()` (in module `kwcoco.util.util_json`), 166

`findRepresentativeImages()` (`kwcoco.coco_dataset.MixinCocoStats` method), 254

`forest_str()` (`kwcoco.category_tree.CategoryTree` method), 211

`forest_str()` (`kwcoco.CategoryTree` method), 340

`fpPath` (`kwcoco.coco_dataset.CocoDataset` property), 270

`fpPath` (`kwcoco.coco_sql_dataset.CocoSqlDatabase` property), 311

`fpPath` (`kwcoco.CocoDataset` property), 323

`fpPath` (`kwcoco.util.DelayedLoad` property), 191

`fpPath` (`kwcoco.util.util_delayed_poc.DelayedLoad` property), 154

`frame_index` (`kwcoco.coco_sql_dataset.Image` attribute), 304

`from_arrays()` (`kwcoco.metrics.confusion_vectors.ConfusionVectors` class method), 87

`from_arrays()` (`kwcoco.metrics.ConfusionVectors` class method), 122

`from_coco()` (`kwcoco.category_tree.CategoryTree` class

method), 208
`from_coco()` (*kwcoco.CategoryTree class method*), 337
`from_coco()` (*kwcoco.kw18.KW18 class method*), 319
`from_coco()` (*kwcoco.metrics.detect_metrics.DetectionMetrics class method*), 94
`from_coco()` (*kwcoco.metrics.DetectionMetrics class method*), 112
`from_coco_paths()` (*kw-coco.coco_dataset.CocoDataset class method*), 270
`from_coco_paths()` (*kwcoco.CocoDataset class method*), 324
`from_data()` (*kwcoco.coco_dataset.CocoDataset class method*), 270
`from_data()` (*kwcoco.CocoDataset class method*), 323
`from_gid()` (*kwcoco.coco_image.CocoImage class method*), 284
`from_gid()` (*kwcoco.CocoImage class method*), 330
`from_image_paths()` (*kw-coco.coco_dataset.CocoDataset class method*), 270
`from_image_paths()` (*kwcoco.CocoDataset class method*), 323
`from_json()` (*kwcoco.category_tree.CategoryTree class method*), 208
`from_json()` (*kwcoco.CategoryTree class method*), 337
`from_json()` (*kwcoco.coco_evaluator.CocoResults class method*), 281
`from_json()` (*kwcoco.coco_evaluator.CocoSingleResult class method*), 282
`from_json()` (*kwcoco.metrics.confusion_measures.Measures class method*), 78
`from_json()` (*kwcoco.metrics.confusion_measures.PerClass class method*), 82
`from_json()` (*kwcoco.metrics.confusion_vectors.ConfusionVector class method*), 86
`from_json()` (*kwcoco.metrics.ConfusionVectors class method*), 122
`from_json()` (*kwcoco.metrics.Measures class method*), 125
`from_json()` (*kwcoco.metrics.PerClass_Measures class method*), 129
`from_mutex()` (*kwcoco.category_tree.CategoryTree class method*), 207
`from_mutex()` (*kwcoco.CategoryTree class method*), 336
`fuse()` (*kwcoco.channel_spec.ChannelSpec method*), 222
`fuse()` (*kwcoco.channel_spec.FusedChannelSpec method*), 219
`fuse()` (*kwcoco.ChannelSpec method*), 343
`fuse()` (*kwcoco.FusedChannelSpec method*), 353
`FusedChannelSpec` (*class in kwcoco*), 349
`FusedChannelSpec` (*class in kwcoco.channel_spec*), 215

G

`get()` (*kwcoco._helpers._NextId method*), 202
`get()` (*kwcoco.coco_image.CocoImage method*), 284
`get()` (*kwcoco.coco_objects1d.ObjectList1D method*), 291
`get()` (*kwcoco.CocoImage method*), 330
`get()` (*kw-coco.demo.toypatterns.CategoryPatterns method*), 63
`get()` (*kw-coco.util.dict_like.DictLike method*), 132
`get()` (*kw-coco.util.DictLike method*), 173
`get_auxiliary_fpath()` (*kw-coco.coco_dataset.MixinCocoAccessors method*), 237
`get_image_fpath()` (*kw-coco.coco_dataset.MixinCocoAccessors method*), 237
`get_images_with_videoid()` (*in module kw-coco.examples.faq*), 66
`getAnnIds()` (*kwcoco.compat_dataset.COCO method*), 314
`getCatIds()` (*kwcoco.compat_dataset.COCO method*), 315
`getImgIds()` (*kwcoco.compat_dataset.COCO method*), 315
`getitem()` (*kw-coco.util.dict_like.DictLike method*), 131
`getitem()` (*kw-coco.util.DictLike method*), 173
`getting_started_existing_dataset()` (*in module kw-coco.examples.getting_started_existing_dataset*), 66
`gid_to_aids` (*kwcoco.coco_dataset.MixinCocoIndex property*), 267
`gids` (*kwcoco.coco_objects1d.Annots property*), 296
`gids` (*kwcoco.coco_objects1d.Images property*), 295
`global_accuracy_from_confusion()` (*in module kw-coco.metrics.sklearn_alts*), 107
`gname` (*kwcoco.coco_objects1d.Images property*), 295
`gpath` (*kwcoco.coco_objects1d.Images property*), 295
`grab_camvid_sampler()` (*in module kw-coco.data.grab_camvid*), 30
`grab_camvid_train_test_val_splits()` (*in module kw-coco.data.grab_camvid*), 30
`grab_coco_camvid()` (*in module kw-coco.data.grab_camvid*), 31
`grab_domain_net()` (*in module kw-coco.data.grab_domainnet*), 33
`grab_raw_camvid()` (*in module kw-coco.data.grab_camvid*), 31
`grab_spacenet7()` (*in module kw-coco.data.grab_spacenet*), 34

H

`height` (*kwcoco.coco_objects1d.Images property*), 295
`height` (*kwcoco.coco_sql_dataset.Image attribute*), 304

height (`kwcoco.coco_sql_dataset.Video` attribute), 304

|

`id` (`kwcoco.coco_sql_dataset.Annotation` attribute), 305

`id` (`kwcoco.coco_sql_dataset.Category` attribute), 303

`id` (`kwcoco.coco_sql_dataset.Image` attribute), 304

`id` (`kwcoco.coco_sql_dataset.KeypointCategory` attribute), 304

`id` (`kwcoco.coco_sql_dataset.Video` attribute), 304

`id_to_idx()` (`kwcoco.category_tree.CategoryTree` method), 209

`id_to_idx()` (`kwcoco.CategoryTree` method), 338

`idx_pairwise_distance()` (`kwcoco.category_tree.CategoryTree` method), 209

`idx_pairwise_distance()` (`kwcoco.CategoryTree` method), 338

`idx_to_ancestor_idxs()` (`kwcoco.category_tree.CategoryTree` method), 209

`idx_to_ancestor_idxs()` (`kwcoco.CategoryTree` method), 338

`idx_to_descendants_idxs()` (`kwcoco.category_tree.CategoryTree` method), 209

`idx_to_descendants_idxs()` (`kwcoco.CategoryTree` method), 338

`idx_to_id()` (`kwcoco.category_tree.CategoryTree` method), 209

`idx_to_id()` (`kwcoco.CategoryTree` method), 338

`Image` (class in `kwcoco.coco_sql_dataset`), 304

`IMAGE` (in module `kwcoco.coco_schema`), 301

`image_id` (`kwcoco.coco_objects1d.Annots` property), 296

`image_id` (`kwcoco.coco_sql_dataset.Annotation` attribute), 305

`ImageGroups` (class in `kwcoco.coco_objects1d`), 298

`Images` (class in `kwcoco.coco_objects1d`), 295

`images` (`kwcoco.coco_objects1d.Annots` property), 296

`images` (`kwcoco.coco_objects1d.Videos` property), 295

`images()` (`kwcoco.coco_dataset.MixinCocoObjects` method), 249

`img_root` (`kwcoco.coco_dataset.MixinCocoExtras` property), 248

`imgs` (`kwcoco.coco_dataset.MixinCocoIndex` property), 267

`imgs` (`kwcoco.coco_sql_dataset.CocoSqlDatabase` property), 311

`imgToAnns` (`kwcoco.compat_dataset.COCO` property), 314

`imread()` (`kwcoco.coco_dataset.MixinCocoDraw` method), 255

`index()` (`kwcoco.category_tree.CategoryTree` method), 211

`index()` (`kwcoco.CategoryTree` method), 340

`index()` (`kwcoco.demo.toypatterns.CategoryPatterns` method), 63

`indexable_allclose()` (in module `kwcoco.util`), 200

`indexable_allclose()` (in module `kwcoco.util_json`), 167

`IndexableWalker` (in module `kwcoco.util`), 198

`IndexableWalker` (in module `kwcoco.util.util_json`), 166

`info` (`kwcoco.channel_spec.ChannelSpec` property), 221

`info` (`kwcoco.ChannelSpec` property), 342

`info()` (`kwcoco.compat_dataset.COCO` method), 314

`initialize()` (`kwcoco.demo.boids.Boids` method), 37

`INTEGER` (in module `kwcoco.coco_schema`), 301

`INTEGER` (in module `kwcoco.util`), 176

`INTEGER` (in module `kwcoco.util.jsonschema_elements`), 137

`INTEGER` (`kwcoco.util.jsonschema_elements.ScalarElements` property), 134

`INTEGER` (`kwcoco.util.ScalarElements` property), 177

`intersection()` (`kwcoco.channel_spec.BaseChannelSpec` method), 214

`intersection()` (`kwcoco.channel_spec.ChannelSpec` method), 223

`intersection()` (`kwcoco.channel_spec.FusedChannelSpec` method), 218

`intersection()` (`kwcoco.ChannelSpec` method), 344

`intersection()` (`kwcoco.FusedChannelSpec` method), 352

`InvalidAddError`, 317

`is_mutex()` (`kwcoco.category_tree.CategoryTree` method), 210

`is_mutex()` (`kwcoco.CategoryTree` method), 339

`iscrowd` (`kwcoco.coco_sql_dataset.Annotation` attribute), 305

`issubset()` (`kwcoco.channel_spec.BaseChannelSpec` method), 214

`issubset()` (`kwcoco.channel_spec.ChannelSpec` method), 224

`issubset()` (`kwcoco.channel_spec.FusedChannelSpec` method), 218

`issubset()` (`kwcoco.ChannelSpec` method), 345

`issubset()` (`kwcoco.FusedChannelSpec` method), 353

`issuperset()` (`kwcoco.channel_spec.BaseChannelSpec` method), 214

`issuperset()` (`kwcoco.channel_spec.ChannelSpec` method), 224

`issuperset()` (`kwcoco.channel_spec.FusedChannelSpec` method), 218

`issuperset()` (`kwcoco.ChannelSpec` method), 345

`issuperset()` (`kwcoco.FusedChannelSpec` method), 353

`items()` (`kwcoco.channel_spec.ChannelSpec` method), 222

items() (*kwcoco.ChannelSpec method*), 343
items() (*kwcoco.coco_sql_dataset.SqlDictProxy method*), 308
items() (*kwcoco.coco_sql_dataset.SqlIdGroupDictProxy method*), 309
items() (*kwcoco.util.dict_like.DictLike method*), 131
items() (*kwcoco.util.DictLike method*), 173
iter_asset_objs() (*kwcoco.coco_image.CocoImage method*), 285
iter_asset_objs() (*kwcoco.CocoImage method*), 331
iter_image_filepaths() (*kwcoco.coco_image.CocoImage method*), 285
iter_image_filepaths() (*kwcoco.CocoImage method*), 331

K

keypoint_annotation_frequency() (*kwcoco.coco_dataset.MixinCocoStats method*), 251
keypoint_categories() (*kwcoco.coco_dataset.MixinCocoAccessors method*), 240
KEYPOINT_CATEGORY (*in module kwcoco.coco_schema*), 301
KeypointCategory (*class in kwcoco.coco_sql_dataset*), 304
KEYPOINTS (*in module kwcoco.coco_schema*), 301
keypoints (*kwcoco.coco_sql_dataset.Annotation attribute*), 305
keys() (*kwcoco.channel_spec.ChannelSpec method*), 222
keys() (*kwcoco.ChannelSpec method*), 343
keys() (*kwcoco.coco_image.CocoImage method*), 284
keys() (*kwcoco.coco_sql_dataset.SqlDictProxy method*), 307
keys() (*kwcoco.coco_sql_dataset.SqlIdGroupDictProxy method*), 309
keys() (*kwcoco.CocoImage method*), 330
keys() (*kwcoco.metrics.confusion_vectors.OneVsRestConfusionVectors method*), 90
keys() (*kwcoco.metrics.OneVsRestConfusionVectors method*), 129
keys() (*kwcoco.metrics.util.DictProxy method*), 108
keys() (*kwcoco.util.dict_like.DictLike method*), 131
keys() (*kwcoco.util.DictLike method*), 173
KW18 (*class in kwcoco.kw18*), 318
kwcoco
 module, 9
kwcoco.__init__
 module, 1
kwcoco.__main__
 module, 202
kwcoco._helpers
 module, 202

kwcoco.abstract_coco_dataset
 module, 205
kwcoco.category_tree
 module, 206
kwcoco.channel_spec
 module, 211
kwcoco.cli
 module, 14
kwcoco.cli.__main__
 module, 14
kwcoco.cli.coco_conform
 module, 15
kwcoco.cli.coco_eval
 module, 16
kwcoco.cli.coco_grab
 module, 19
kwcoco.cli.coco_modify_categories
 module, 19
kwcoco.cli.coco_reroot
 module, 21
kwcoco.cli.coco_show
 module, 22
kwcoco.cli.coco_split
 module, 23
kwcoco.cli.coco_stats
 module, 24
kwcoco.cli.coco_subset
 module, 25
kwcoco.cli.coco_toydata
 module, 27
kwcoco.cli.coco_union
 module, 28
kwcoco.cli.coco_validate
 module, 29
kwcoco.coco_dataset
 module, 229
kwcoco.coco_evaluator
 module, 276
kwcoco.coco_image
 module, 283
kwcoco.coco_objects1d
 module, 289
kwcoco.coco_schema
 module, 298
kwcoco.coco_sql_dataset
 module, 301
kwcoco.compat_dataset
 module, 313
kwcoco.data
 module, 30
kwcoco.data.grab_camvid
 module, 30
kwcoco.data.grab_cifar
 module, 32

kwcoco.data.grab_datasets
 module, 32
 kwcoco.data.grab_domainnet
 module, 33
 kwcoco.data.grab_spacenet
 module, 33
 kwcoco.data.grab_voc
 module, 34
 kwcoco.demo
 module, 36
 kwcoco.demo.boids
 module, 36
 kwcoco.demo.perterb
 module, 40
 kwcoco.demo.toydata
 module, 41
 kwcoco.demo.toydata_image
 module, 49
 kwcoco.demo.toydata_video
 module, 53
 kwcoco.demo.toypatterns
 module, 61
 kwcoco.examples
 module, 64
 kwcoco.examples.bench_large_hyperspectral
 module, 64
 kwcoco.examples.draw_gt_and_predicted_boxes
 module, 65
 kwcoco.examples.faq
 module, 66
 kwcoco.examples.getting_started_existing_dataset
 module, 66
 kwcoco.examples.loading_multispectral_data
 module, 67
 kwcoco.examples.modification_example
 module, 67
 kwcoco.examples.simple_kwkcoco_torch_dataset
 module, 67
 kwcoco.examples.vectorized_interface
 module, 69
 kwcoco.exceptions
 module, 317
 kwcoco.kpf
 module, 317
 kwcoco.kw18
 module, 317
 kwcoco.metrics
 module, 69
 kwcoco.metrics.assignment
 module, 69
 kwcoco.metrics.clf_report
 module, 74
 kwcoco.metrics.confusion_measures
 module, 77
 kwcoco.metrics.confusion_vectors
 module, 84
 kwcoco.metrics.detect_metrics
 module, 93
 kwcoco.metrics.drawing
 module, 100
 kwcoco.metrics.functional
 module, 104
 kwcoco.metrics.sklearn_alts
 module, 106
 kwcoco.metrics.util
 module, 108
 kwcoco.metrics.voc_metrics
 module, 108
 kwcoco.util
 module, 131
 kwcoco.util.dict_like
 module, 131
 kwcoco.util.jsonschema_elements
 module, 132
 kwcoco.util.lazy_frame_backends
 module, 138
 kwcoco.util.util_archive
 module, 142
 kwcoco.util.util_delayed_poc
 module, 143
 kwcoco.util.util_futures
 module, 166
 kwcoco.util.util_json
 module, 166
 kwcoco.util.util_monkey
 module, 168
 kwcoco.util.util_sklearn
 module, 169
 kwcoco.util.util_truncate
 module, 170
 KWCOCO_KEYPOINT (in module kwkcoco.coco_schema),
 301
 KWCOCO_KEYPOINTS (in module kwkcoco.coco_schema),
 301
 KWCOCO_POLYGON (in module kwkcoco.coco_schema), 301
 KW CocoSimpleTorchDataset (class in kwkcoco.examples.simple_kwkcoco_torch_dataset),
 68

L

LazyGDalFrameFile (class in kwkcoco.util), 178
 LazyGDalFrameFile (class in kwkcoco.util.lazy_frame_backends), 139
 LazyRasterIOFrameFile (class in kwkcoco.util), 180
 LazyRasterIOFrameFile (class in kwkcoco.util.lazy_frame_backends), 139
 LazySpectralFrameFile (class in kwkcoco.util), 180

LazySpectralFrameFile (class in `coco.util.lazy_frame_backends`), 139
load() (`kwcoco.kw18.KW18` class method), 320
load_annot_sample() (`kwcoco.coco_dataset.MixinCocoAccessors` method), 237
load_image() (`kwcoco.coco_dataset.MixinCocoAccessors` method), 236
load_shape() (`kwcoco.util.DelayedLoad` method), 191
load_shape() (`kwcoco.util.util_delayed_poc.DelayedLoad` method), 154
loadAnns() (`kwcoco.compat_dataset.COCO` method), 315
loadCats() (`kwcoco.compat_dataset.COCO` method), 315
loadImgs() (`kwcoco.compat_dataset.COCO` method), 315
loadNumpyAnnotations() (`kwcoco.compat_dataset.COCO` method), 316
loadRes() (`kwcoco.compat_dataset.COCO` method), 315
loads() (`kwcoco.kw18.KW18` class method), 320
log() (`kwcoco.coco_evaluator.CocoEvaluator` method), 279
lookup() (`kwcoco.coco_objects1d.ObjectGroups` method), 294
lookup() (`kwcoco.coco_objects1d.ObjectList1D` method), 291

M

main() (in module `kwcoco.cli.__main__`), 15
main() (in module `kwcoco.cli.coco_eval`), 18
main() (in module `kwcoco.data.grab_camvid`), 32
main() (in module `kwcoco.data.grab_cifar`), 32
main() (in module `kwcoco.data.grab_spacenet`), 34
main() (in module `kwcoco.data.grab_voc`), 35
main() (`kwcoco.cli.coco_conform.CocoConformCLI` class method), 15
main() (`kwcoco.cli.coco_eval.CocoEvalCLI` class method), 17
main() (`kwcoco.cli.coco_grab.CocoGrabCLI` class method), 19
main() (`kwcoco.cli.coco_modify_categories.CocoModifyCatsCLI` class method), 20
main() (`kwcoco.cli.coco_reroot.CocoRerootCLI` class method), 21
main() (`kwcoco.cli.coco_show.CocoShowCLI` class method), 22
main() (`kwcoco.cli.coco_split.CocoSplitCLI` class method), 23
main() (`kwcoco.cli.coco_stats.CocoStatsCLI` class method), 24
main() (`kwcoco.cli.coco_subset.CocoSubsetCLI` class method), 25

main() (`kwcoco.cli.coco_toydata.CocoToyDataCLI` class method), 28
main() (`kwcoco.cli.coco_union.CocoUnionCLI` class method), 28
main() (`kwcoco.cli.coco_validate.CocoValidateCLI` class method), 29
maximized_thresholds() (`kwcoco.metrics.confusion_measures.Measures` method), 79
maximized_thresholds() (`kwcoco.metrics.Measures` method), 125
MeasureCombiner (class in `kwcoco.metrics.confusion_measures`), 83
Measures (class in `kwcoco.metrics`), 124
Measures (class in `kwcoco.metrics.confusion_measures`), 78
measures() (`kwcoco.metrics.BinaryConfusionVectors` method), 118
measures() (`kwcoco.metrics.confusion_vectors.BinaryConfusionVectors` method), 91
measures() (`kwcoco.metrics.confusion_vectors.OneVsRestConfusionVector` method), 90
measures() (`kwcoco.metrics.OneVsRestConfusionVectors` method), 129
MEMORY_URI (`kwcoco.coco_sql_dataset.CocoSqlDatabase` attribute), 310
missing_images() (`kwcoco.coco_dataset.MixinCocoExtras` method), 246
MixinCocoAccessors (class in `kwcoco.coco_dataset`), 235
MixinCocoAddRemove (class in `kwcoco.coco_dataset`), 256
MixinCocoDeprecate (class in `kwcoco.coco_dataset`), 235
MixinCocoDraw (class in `kwcoco.coco_dataset`), 255
MixinCocoExtras (class in `kwcoco.coco_dataset`), 241
MixinCocoIndex (class in `kwcoco.coco_dataset`), 267
MixinCocoObjects (class in `kwcoco.coco_dataset`), 248
MixinCocoStats (class in `kwcoco.coco_dataset`), 250
module
 kwcoco, 9
kwcoco.__init__, 1
kwcoco.__main__, 202
kwcoco._helpers, 202
kwcoco.abstract_coco_dataset, 205
kwcoco.category_tree, 206
kwcoco.channel_spec, 211
kwcoco.cli, 14
kwcoco.cli.__main__, 14
kwcoco.cli.coco_conform, 15
kwcoco.cli.coco_eval, 16
kwcoco.cli.coco_grab, 19
kwcoco.cli.coco_modify_categories, 19

kwCOCO.cli.coco_reroot, 21
 kwCOCO.cli.coco_show, 22
 kwCOCO.cli.coco_split, 23
 kwCOCO.cli.coco_stats, 24
 kwCOCO.cli.coco_subset, 25
 kwCOCO.cli.coco_toydata, 27
 kwCOCO.cli.coco_union, 28
 kwCOCO.cli.coco_validate, 29
 kwCOCO.coco_dataset, 229
 kwCOCO.coco_evaluator, 276
 kwCOCO.coco_image, 283
 kwCOCO.coco_objects1d, 289
 kwCOCO.coco_schema, 298
 kwCOCO.coco_sql_dataset, 301
 kwCOCO.compat_dataset, 313
 kwCOCO.data, 30
 kwCOCO.data.grab_camvid, 30
 kwCOCO.data.grab_cifar, 32
 kwCOCO.data.grab_datasets, 32
 kwCOCO.data.grab_domainnet, 33
 kwCOCO.data.grab_spacenet, 33
 kwCOCO.data.grab_voc, 34
 kwCOCO.demo, 36
 kwCOCO.demo.boids, 36
 kwCOCO.demo.perterb, 40
 kwCOCO.demo.toydata, 41
 kwCOCO.demo.toydata_image, 49
 kwCOCO.demo.toydata_video, 53
 kwCOCO.demo.toypatterns, 61
 kwCOCO.examples, 64
 kwCOCO.examples.bench_large_hyperspectral, 64
 kwCOCO.examples.draw_gt_and_predicted_boxes, 65
 kwCOCO.examples.faq, 66
 kwCOCO.examples.getting_started_existing_dataset, 66
 kwCOCO.examples.loading_multispectral_data, 67
 kwCOCO.examples.modification_example, 67
 kwCOCO.examples.simple_kwCOCO_torch_dataset, 67
 kwCOCO.examples.vectorized_interface, 69
 kwCOCO.exceptions, 317
 kwCOCO.kpf, 317
 kwCOCO.kw18, 317
 kwCOCO.metrics, 69
 kwCOCO.metrics.assignment, 69
 kwCOCO.metrics.clf_report, 74
 kwCOCO.metrics.confusion_measures, 77
 kwCOCO.metrics.confusion_vectors, 84
 kwCOCO.metrics.detect_metrics, 93
 kwCOCO.metrics.drawing, 100
 kwCOCO.metrics.functional, 104
 kwCOCO.metrics.sklearn_alts, 106
 kwCOCO.metrics.util, 108
 kwCOCO.metrics.voc_metrics, 108
 kwCOCO.util, 131
 kwCOCO.util.dict_like, 131
 kwCOCO.util.jsonschema_elements, 132
 kwCOCO.util.lazy_frame_backends, 138
 kwCOCO.util.util_archive, 142
 kwCOCO.util.util_delayed_poc, 143
 kwCOCO.util.util_futures, 166
 kwCOCO.util.util_json, 166
 kwCOCO.util.util_monkey, 168
 kwCOCO.util.util_sklearn, 169
 kwCOCO.util.util_truncate, 170

N

n_annot (kwCOCO.coco_dataset.MixinCocoStats property), 250
 n_annot (kwCOCO.coco_objects1d.Images property), 296
 n_cats (kwCOCO.coco_dataset.MixinCocoStats property), 251
 n_images (kwCOCO.coco_dataset.MixinCocoStats property), 250
 n_videos (kwCOCO.coco_dataset.MixinCocoStats property), 251
 name (kwCOCO.cli.coco_conform.CocoConformCLI attribute), 15
 name (kwCOCO.cli.coco_eval.CocoEvalCLI attribute), 17
 name (kwCOCO.cli.coco_grab.CocoGrabCLI attribute), 19
 name (kwCOCO.cli.coco_modify_categories.CocoModifyCatsCLI attribute), 20
 name (kwCOCO.cli.coco_reroot.CocoRerootCLI attribute), 21
 name (kwCOCO.cli.coco_show.CocoShowCLI attribute), 22
 name (kwCOCO.cli.coco_split.CocoSplitCLI attribute), 23
 name (kwCOCO.cli.coco_stats.CocoStatsCLI attribute), 24
 name (kwCOCO.cli.coco_subset.CocoSubsetCLI attribute), 25
 name (kwCOCO.cli.coco_toydata.CocoToyDataCLI attribute), 28
 name (kwCOCO.cli.coco_union.CocoUnionCLI attribute), 28
 name (kwCOCO.cli.coco_validate.CocoValidateCLI attribute), 29
 name (kwCOCO.coco_objects1d.Categories property), 294
 name (kwCOCO.coco_sql_dataset.Category attribute), 304
 name (kwCOCO.coco_sql_dataset.Image attribute), 304
 name (kwCOCO.coco_sql_dataset.KeypointCategory attribute), 304
 name (kwCOCO.coco_sql_dataset.Video attribute), 304
 name_to_cat (kwCOCO.coco_dataset.MixinCocoIndex property), 267

name_to_cat (`kwcoco.coco_sql_dataset.CocoSqlDatabase`)
 num_channels (`kwcoco.coco_image.CocoImage` property), 311
ndim (`kwcoco.util.lazy_frame_backends.LazyGDalFrameFile`)
 num_channels (`kwcoco.CocoImage` property), 330
 property), 140
ndim (`kwcoco.util.lazy_frame_backends.LazyRasterIOFrameFile`)
 num_classes (`kwcoco.category_tree.CategoryTree` property), 210
 property), 139
ndim (`kwcoco.util.lazy_frame_backends.LazySpectralFrameFile`)
 num_classes (`kwcoco.CategoryTree` property), 339
NUMBER (*in module* `kwcoco.coco_schema`), 301
NUMBER (*in module* `kwcoco.util`), 176
NUMBER (*in module* `kwcoco.util.jsonschema_elements`), 138
NUMBER (`kwcoco.util.jsonschema_elements.ScalarElements` property), 134
NUMBER (`kwcoco.util.ScalarElements` property), 177
numel () (`kwcoco.channel_spec.ChannelSpec` method), 224
numel () (`kwcoco.channel_spec.FusedChannelSpec` method), 217
numel () (`kwcoco.ChannelSpec` method), 345
numel () (`kwcoco.FusedChannelSpec` method), 351

O

OBJECT (*in module* `kwcoco.coco_schema`), 301
OBJECT (*in module* `kwcoco.util`), 176
OBJECT (*in module* `kwcoco.util.jsonschema_elements`), 138
OBJECT () (`kwcoco.util.ContainerElements` method), 174
OBJECT () (`kwcoco.util.jsonschema_elements.ContainerElements` method), 135
object_categories () (`kwcoco.coco_dataset.MixinCocoAccessors` method), 240
ObjectGroups (*class in* `kwcoco.coco_objects1d`), 294
ObjectList1D (*class in* `kwcoco.coco_objects1d`), 289
objs (`kwcoco.coco_objects1d.ObjectList1D` property), 290
ONEOF (*in module* `kwcoco.coco_schema`), 301
ONEOF (*in module* `kwcoco.util`), 176
ONEOF (*in module* `kwcoco.util.jsonschema_elements`), 138
ONEOF () (`kwcoco.util.jsonschema_elements.QuantifierElements` method), 135
ONEOF () (`kwcoco.util.QuantifierElements` method), 176
NULL (*in module* `kwcoco.coco_schema`), 301
NULL (*in module* `kwcoco.util`), 176
NULL (*in module* `kwcoco.util.jsonschema_elements`), 137
NULL (`kwcoco.util.jsonschema_elements.ScalarElements` property), 134
NULL (`kwcoco.util.ScalarElements` property), 176
num_bands (`kwcoco.util.DelayedLoad` property), 191
num_bands (`kwcoco.util.DelayedNans` property), 193
num_bands (`kwcoco.util.DelayedWarp` property), 197
num_bands (`kwcoco.util.util_delayed_poc.DelayedLoad` property), 154
num_bands (`kwcoco.util.util_delayed_poc.DelayedNans` property), 151
num_bands (`kwcoco.util.util_delayed_poc.DelayedWarp` property), 162
oset_delitem () (*in module* `kwcoco.channel_spec`), 229

`oset_insert()` (*in module kwcoco.channel_spec*), 229
`ovr_classification_report()` (*in module kwcoco.metrics.clf_report*), 76
`ovr_classification_report()` (*kw-coco.metrics.confusion_vectors*.*OneVsRestConfusionVectors* method), 90
`ovr_classification_report()` (*kw-coco.metrics*.*OneVsRestConfusionVectors* method), 129

P

`parse()` (*kwcoco.channel_spec.ChannelSpec* method), 221
`parse()` (*kwcoco.channel_spec.FusedChannelSpec* class method), 216
`parse()` (*kwcoco.ChannelSpec* method), 342
`parse()` (*kwcoco.FusedChannelSpec* class method), 350
`PATH` (*in module kwcoco.coco_schema*), 301
`path_SANITIZE()` (*kw-coco.channel_spec.BaseChannelSpec* method), 214
`paths()` (*kwcoco.demo.boids.Boids* method), 37
`pct_summarize2()` (*in module kw-coco.metrics.detect_metrics*), 100
`peek()` (*kwcoco.coco_objects1d.ObjectListID* method), 291
`PerClass_Measures` (*class in kwcoco.metrics*), 129
`PerClass_Measures` (*class in kw-coco.metrics.confusion_measures*), 82
`perterb_coco()` (*in module kwcoco.demo.perterb*), 40
`POLYGON` (*in module kwcoco.coco_schema*), 301
`populate_from()` (*kw-coco.coco_sql_dataset.CocoSqlDatabase* method), 311
`populate_info()` (*in module kw-coco.metrics.confusion_measures*), 84
`pred_detections()` (*kw-coco.metrics.detect_metrics.DetectionMetrics* method), 95
`pred_detections()` (*kwcoco.metrics.DetectionMetrics* method), 113
`primary_asset()` (*kwcoco.coco_image.CocoImage* method), 285
`primary_asset()` (*kwcoco.CocoImage* method), 331
`primary_image_filepath()` (*kw-coco.coco_image.CocoImage* method), 284
`primary_image_filepath()` (*kwcoco.CocoImage* method), 330
`prob` (*kwcoco.coco_sql_dataset.Annotation* attribute), 305
`profile` (*in module kwcoco.coco_evaluator*), 278
`profile` (*in module kwcoco.coco_image*), 283
`profile` (*in module kwcoco.demo.toydata_image*), 49
`profile` (*in module kwcoco.demo.toydata_video*), 53

`profile` (*in module kwcoco.demo.toypatterns*), 62
`profile` (*in module kwcoco.metrics.confusion_measures*), 78
`profile` (*in module kwcoco.metrics.confusion_vectors*), 85
`profile` (*in module kwcoco.metrics.sklearn_alts*), 106
`profile` (*in module kwcoco.util.lazy_frame_backends*), 138
`profile` (*in module kwcoco.util.util_delayed_poc*), 148
`pycocotools_confusion_vectors()` (*in module kwcoco.metrics.detect_metrics*), 99

Q

`QuantifierElements` (*class in kwcoco.util*), 176
`QuantifierElements` (*class in kw-coco.util.jsonschema_elements*), 134
`query_subset()` (*in module kwcoco.cli.coco_subset*), 26
`queue_size` (*kwcoco.metrics.confusion_measures.MeasureCombiner* property), 83

R

`random()` (*kwcoco.coco_dataset.MixinCocoExtras* class method), 243
`random()` (*kwcoco.util.DelayedChannelConcat* class method), 182
`random()` (*kwcoco.util.DelayedWarp* class method), 196
`random()` (*kwcoco.util.util_delayed_poc.DelayedChannelConcat* class method), 159
`random()` (*kwcoco.util.util_delayed_poc.DelayedWarp* class method), 162
`random_category()` (*kw-coco.demo.toypatterns.CategoryPatterns* method), 63
`random_multi_object_path()` (*in module kw-coco.demo.toydata_video*), 60
`random_path()` (*in module kw-coco.demo.toydata_video*), 60
`random_single_video_dset()` (*in module kw-coco.demo.toydata*), 41
`random_single_video_dset()` (*in module kw-coco.demo.toydata_video*), 55
`random_video_dset()` (*in module kw-coco.demo.toydata*), 44
`random_video_dset()` (*in module kw-coco.demo.toydata_video*), 53
`Rasters` (*class in kwcoco.demo.toypatterns*), 64
`raw_table()` (*kwcoco.coco_sql_dataset.CocoSqlDatabase* method), 311
`reconstruct()` (*kwcoco.metrics.confusion_measures.Measures* method), 78
`reconstruct()` (*kwcoco.metrics.Measures* method), 125

reflection_id(kwcoco.coco_sql_dataset.KeypointCategorySchemaElements attribute), 304	(class in kwcoco.util.jsonschema_elements), 136
remap() (kwcoco._helpers._ID_Remapper method), 203	score (kwcoco.coco_sql_dataset.Annotation attribute), 305
remap() (kwcoco._helpers.UniqueNameRemapper method), 203	score() (kwcoco.metrics.voc_metrics.VOC_Metrics method), 109
remove_annotation() (kw-coco.coco_dataset.MixinCocoAddRemove method), 262	score_coco (kwcoco.metrics.detect_metrics.DetectionMetrics attribute), 94
remove_annotation_keypoints() (kw-coco.coco_dataset.MixinCocoAddRemove method), 264	score_coco (kwcoco.metrics.DetectionMetrics attribute), 112
remove_annotations() (kw-coco.coco_dataset.MixinCocoAddRemove method), 262	score_kwant() (kwcoco.metrics.detect_metrics.DetectionMetrics method), 96
remove_categories() (kw-coco.coco_dataset.MixinCocoAddRemove method), 263	score_kwant() (kwcoco.metrics.DetectionMetrics method), 114
remove_images() (kw-coco.coco_dataset.MixinCocoAddRemove method), 263	score_kwkcoco() (kwcoco.metrics.detect_metrics.DetectionMetrics method), 96
remove_keypoint_categories() (kw-coco.coco_dataset.MixinCocoAddRemove method), 264	score_kwkcoco() (kwcoco.metrics.DetectionMetrics method), 114
remove_videos() (kw-coco.coco_dataset.MixinCocoAddRemove method), 264	score_pycocotools() (kw-coco.metrics.detect_metrics.DetectionMetrics method), 96
rename_categories() (kw-coco.coco_dataset.MixinCocoExtras method), 246	score_pycocotools() (kw-coco.metrics.DetectionMetrics method), 114
render_background() (in module coco.demo.toydata_video), 60	score_voc() (kw-coco.metrics.detect_metrics.DetectionMetrics method), 96
render_category() (coco.demo.toypatterns.CategoryPatterns method), 63	score_voc() (kwcoco.metrics.DetectionMetrics method), 114
render_foreground() (in module coco.demo.toydata_video), 60	SEGMENTATION (in module kwcoco.coco_schema), 301
render_toy_dataset() (in module coco.demo.toydata_video), 57	segmentation (kwcoco.coco_sql_dataset.Annotation attribute), 305
render_toy_image() (in module coco.demo.toydata_video), 58	set() (kwcoco.coco_objects1d.ObjectList1D method), 292
reroot() (kwcoco.coco_dataset.MixinCocoExtras method), 247	set_annotation_category() (kw-coco.coco_dataset.MixinCocoAddRemove method), 265
reversible_diff() (in module coco.metrics.confusion_measures), 82	setitem() (kwcoco.util.dict_like.DictLike method), 131
rgb_to_cid() (in module kwcoco.data.grab_camvid), 31	setitem() (kwcoco.util.DictLike method), 173
RUN_LENGTH_ENCODING (in module coco.coco_schema), 301	shape (kwcoco.util.DelayedChannelConcat property), 183
S	shape (kwcoco.util.DelayedFrameConcat property), 186
ScalarElements (class in kwcoco.util), 176	shape (kwcoco.util.DelayedLoad property), 191
ScalarElements (class in kwcoco.util.jsonschema_elements), 134	shape (kwcoco.util.DelayedNans property), 193
SchemaElements (class in kwcoco.util), 177	shape (kwcoco.util.DelayedWarp property), 197
	shape (kwcoco.util.lazy_frame_backends.LazyGDalFrameFile property), 140
	shape (kwcoco.util.lazy_frame_backends.LazyRasterIOFrameFile property), 139
	shape (kwcoco.util.lazy_frame_backends.LazySpectralFrameFile property), 139
	shape (kwcoco.util.LazyGDalFrameFile property), 179
	shape (kwcoco.util.LazyRasterIOFrameFile property), 180
	shape (kwcoco.util.LazySpectralFrameFile property),

180
shape (*kwcoco.util.util_delayed_poc.DelayedChannelConcat property*), 159
shape (*kwcoco.util.util_delayed_poc.DelayedFrameConcat property*), 157
shape (*kwcoco.util.util_delayed_poc.DelayedLoad property*), 154
shape (*kwcoco.util.util_delayed_poc.DelayedNans property*), 151
shape (*kwcoco.util.util_delayed_poc.DelayedWarp property*), 162
show() (*kwcoco.category_tree.CategoryTree method*), 211
show() (*kwcoco.CategoryTree method*), 340
show_image() (*kwcoco.coco_dataset.MixinCocoDraw method*), 255
showAnns() (*kwcoco.compat_dataset.COCO method*), 315
size (*kwcoco.coco_objects1d.Images property*), 295
sizes() (*kwcoco.channel_spec.ChannelSpec method*), 224
sizes() (*kwcoco.channel_spec.FusedChannelSpec method*), 217
sizes() (*kwcoco.ChannelSpec method*), 345
sizes() (*kwcoco.FusedChannelSpec method*), 351
smart_truncate() (*in module kwcoco.util*), 201
smart_truncate() (*in module kwcoco.util.util_truncate*), 170
SortedSetQuiet (*class in kwcoco._helpers*), 203
spec (*kwcoco.channel_spec.BaseChannelSpec property*), 214
spec (*kwcoco.channel_spec.ChannelSpec property*), 221
spec (*kwcoco.ChannelSpec property*), 342
spec() (*kwcoco.channel_spec.FusedChannelSpec method*), 216
spec() (*kwcoco.FusedChannelSpec method*), 350
SPEC_KEYS (*in module kwcoco.coco_dataset*), 235
split() (*kwcoco.util.StratifiedGroupKFold method*), 201
split() (*kwcoco.util.util_sklearn.StratifiedGroupKFold method*), 170
SqlDictProxy (*class in kwcoco.coco_sql_dataset*), 306
SqlIdGroupDictProxy (*class in kwcoco.coco_sql_dataset*), 308
SqlListProxy (*class in kwcoco.coco_sql_dataset*), 305
star() (*in module kwcoco.demo.toypatterns*), 64
stats() (*kwcoco.coco_dataset.MixinCocoStats method*), 253
stats() (*kwcoco.coco_image.CocoImage method*), 284
stats() (*kwcoco.CocoImage method*), 330
step() (*kwcoco.demo.boids.Boids method*), 37
StratifiedGroupKFold (*class in kwcoco.util*), 201
StratifiedGroupKFold (*class in kwcoco.util.util_sklearn*), 169
streams() (*kwcoco.channel_spec.BaseChannelSpec method*), 214
streams() (*kwcoco.channel_spec.ChannelSpec method*), 222
streams() (*kwcoco.channel_spec.FusedChannelSpec method*), 219
streams() (*kwcooco.ChannelSpec method*), 344
streams() (*kwcooco.FusedChannelSpec method*), 353
STRING (*in module kwcoco.coco_schema*), 301
STRING (*in module kwcoco.util*), 176
STRING (*in module kwcoco.util.jsonschema_elements*), 138
STRING (*kwcoco.util.jsonschema_elements.ScalarElements property*), 134
STRING (*kwcoco.util.ScalarElements property*), 177
submit() (*kwcoco.metrics.confusion_measures.MeasureCombiner method*), 83
submit() (*kwcoco.metrics.confusion_measures.OneVersusRestMeasureCombiner method*), 84
subsequence_index() (*in module kwcoco.channel_spec*), 227
subset() (*kwcoco.coco_dataset.CocoDataset method*), 275
subset() (*kwcoco.CocoDataset method*), 328
summarize() (*kwcoco.metrics.detect_metrics.DetectionMetrics method*), 99
summarize() (*kwcooco.metrics.DetectionMetrics method*), 117
summary() (*kwcoco.metrics.confusion_measures.Measures method*), 79
summary() (*kwcoco.metrics.confusion_measures.PerClass_Measures method*), 82
summary() (*kwcooco.metrics.Measures method*), 125
summary() (*kwcooco.metrics.PerClass_Measures method*), 129
summary_plot() (*kwcoco.metrics.confusion_measures.Measures method*), 79
summary_plot() (*kwcoco.metrics.confusion_measures.PerClass_Measures method*), 82
summary_plot() (*kwcooco.metrics.Measures method*), 126
summary_plot() (*kwcooco.metrics.PerClass_Measures method*), 130
supercategory (*kwcoco.coco_objects1d.Categories property*), 294
supercategory (*kwcoco.coco_sql_dataset.Category attribute*), 304
supercategory (*kwcoco.coco_sql_dataset.KeypointCategory attribute*), 304
superstar() (*kwcoco.demo.toypatterns.Rasters static method*), 64
SuppressPrint (*class in kwcoco.util*), 200
SuppressPrint (*class in kwcoco.util.util_monkey*), 168

T

tabular_targets() (kw-
 coco.coco_sql_dataset.CocoSqlDatabase
 method), 312
take() (kwcoco.coco_objects1d.ObjectListID method),
 290
take_channels() (kwcoco.util.DelayedChannelConcat
 method), 183
take_channels() (kwcoco.util.DelayedIdentity
 method), 188
take_channels() (kw-
 coco.util.DelayedImageOperation
 method), 190
take_channels() (kwcoco.util.DelayedLoad method),
 192
take_channels() (kwcoco.util.DelayedWarp method),
 198
take_channels() (kw-
 coco.util.util_delayed_poc.DelayedChannelConcat
 method), 160
take_channels() (kw-
 coco.util.util_delayed_poc.DelayedIdentity
 method), 150
take_channels() (kw-
 coco.util.util_delayed_poc.DelayedImageOperation
 method), 149
take_channels() (kw-
 coco.util.util_delayed_poc.DelayedLoad
 method), 155
take_channels() (kw-
 coco.util.util_delayed_poc.DelayedWarp
 method), 164
tblname (in module kwcoco.coco_sql_dataset), 305
TBLNAME_TO_CLASS (in module kw-
 coco.coco_sql_dataset), 305
the_core_dataset_backend() (in module kw-
 coco.examples.getting_started_existing_dataset),
 66
timestamp (kwcoco.coco_sql_dataset.Image attribute),
 304
to_coco() (kwcoco.category_tree.CategoryTree
 method), 209
to_coco() (kwcoco.CategoryTree method), 338
to_coco() (kwcoco.kw18.KW18 method), 319
to_dict() (kwcoco.util.dict_like.DictLike method), 131
to_dict() (kwcoco.util.DictLike method), 173
TOYDATA_IMAGE_VERSION (in module kw-
 coco.demo.toydata_image), 49
TOYDATA_VIDEO_VERSION (in module kw-
 coco.demo.toydata_video), 53
track_id (kwcoco.coco_sql_dataset.Annotation attribute), 305
triu_condense_multi_index() (in module kw-
 coco.demo.boids), 38

true_detections() (kw-
 coco.metrics.detect_metrics.DetectionMetrics
 method), 95
true_detections() (kwcoco.metrics.DetectionMetrics
 method), 112
TUPLE() (in module kwcoco.coco_schema), 300

U

unarchive_file() (in module kwcoco.util), 181
unarchive_file() (in module kw-
 coco.util.util_archive), 143
union() (kwcoco.channel_spec.BaseChannelSpec
 method), 214
union() (kwcoco.channel_spec.ChannelSpec method),
 224
union() (kwcoco.channel_spec.FusedChannelSpec
 method), 218
union() (kwcoco.ChannelSpec method), 345
union() (kwcoco.coco_dataset.CocoDataset method),
 272
union() (kwcoco.CocoDataset method), 326
union() (kwcoco.FusedChannelSpec method), 353
unique() (kwcoco.channel_spec.ChannelSpec method),
 224
unique() (kwcoco.channel_spec.FusedChannelSpec
 method), 216

unique() (kwcoco.ChannelSpec method), 346
unique() (kwcoco.FusedChannelSpec method), 350
UniqueNameRemapper (class in kwcoco._helpers), 203
update() (kwcoco.util.dict_like.DictLike method), 132
update() (kwcoco.util.DictLike method), 173
update_neighbors() (kwcoco.demo.boids.Boids
 method), 37
USE_NEG_INF (in module kwcoco.metrics.assignment),
 70
UUID (in module kwcoco.coco_schema), 301

V

validate() (kwcoco.coco_dataset.MixinCocoStats
 method), 252
validate() (kwcoco.util.Element method), 175
validate() (kwcoco.util.jsonschema_elements.Element
 method), 134
values() (kwcoco.channel_spec.ChannelSpec method),
 222
values() (kwcoco.ChannelSpec method), 343
values() (kwcoco.coco_sql_dataset.SqlDictProxy
 method), 307
values() (kwcoco.coco_sql_dataset.SqlIdGroupDictProxy
 method), 309
values() (kwcoco.util.dict_like.DictLike method), 131
values() (kwcoco.util.DictLike method), 173
Video (class in kwcoco.coco_sql_dataset), 304
VIDEO (in module kwcoco.coco_schema), 301

`video` (*kwcoco.coco_image.CocoImage property*), 284
`video` (*kwcoco.CocoImage property*), 330
`video_id` (*kwcoco.coco_sql_dataset.Image attribute*),
 304
`Videos` (*class in kwcoco.coco_objects1d*), 294
`videos()` (*kwcoco.coco_dataset.MixinCocoObjects
method*), 250
`view_sql()` (*kwcoco.coco_dataset.CocoDataset
method*), 275
`view_sql()` (*kwcoco.CocoDataset method*), 329
`VOC_Metrics` (*class in kwcoco.metrics.voc_metrics*), 108

W

`warp()` (*kwcoco.util.DelayedVisionOperation method*),
 195
`warp()` (*kwcoco.util.util_delayed_poc.DelayedVisionOperation
method*), 148
`weight` (*kwcoco.coco_sql_dataset.Annotation attribute*),
 305
`width` (*kwcoco.coco_objects1d.Images property*), 295
`width` (*kwcoco.coco_sql_dataset.Image attribute*), 304
`width` (*kwcoco.coco_sql_dataset.Video attribute*), 304

X

`xr` (*in module kwcoco.util.util_delayed_poc*), 148
`xywh` (*kwcoco.coco_objects1d.Annots property*), 297